



kea

# Kea Messages Manual

*Release 2.7.2*

**Internet Systems Consortium**

**Aug 27, 2024**



# CONTENTS

<b>1</b>	<b>ALLOC</b>	<b>3</b>
1.1	ALLOC_ENGINE_IGNOREING_UNSUITABLE_GLOBAL_ADDRESS	3
1.2	ALLOC_ENGINE_IGNOREING_UNSUITABLE_GLOBAL_ADDRESS6	3
1.3	ALLOC_ENGINE_LEASE_RECLAIMED	3
1.4	ALLOC_ENGINE_V4_ALLOC_ERROR	3
1.5	ALLOC_ENGINE_V4_ALLOC_FAIL	4
1.6	ALLOC_ENGINE_V4_ALLOC_FAIL_CLASSES	4
1.7	ALLOC_ENGINE_V4_ALLOC_FAIL_NO_POOLS	4
1.8	ALLOC_ENGINE_V4_ALLOC_FAIL_SHARED_NETWORK	4
1.9	ALLOC_ENGINE_V4_ALLOC_FAIL_SUBNET	5
1.10	ALLOC_ENGINE_V4_DECLINED_RECOVERED	5
1.11	ALLOC_ENGINE_V4_DISCOVER_ADDRESS_CONFLICT	5
1.12	ALLOC_ENGINE_V4_DISCOVER_HR	5
1.13	ALLOC_ENGINE_V4_LEASES_RECLAMATION_COMPLETE	6
1.14	ALLOC_ENGINE_V4_LEASES_RECLAMATION_FAILED	6
1.15	ALLOC_ENGINE_V4_LEASES_RECLAMATION_SLOW	6
1.16	ALLOC_ENGINE_V4_LEASES_RECLAMATION_START	6
1.17	ALLOC_ENGINE_V4_LEASES_RECLAMATION_TIMEOUT	6
1.18	ALLOC_ENGINE_V4_LEASE_RECLAIM	7
1.19	ALLOC_ENGINE_V4_LEASE_RECLAMATION_FAILED	7
1.20	ALLOC_ENGINE_V4_NO_MORE_EXPIRED_LEASES	7
1.21	ALLOC_ENGINE_V4_OFFER_EXISTING_LEASE	7
1.22	ALLOC_ENGINE_V4_OFFER_NEW_LEASE	7
1.23	ALLOC_ENGINE_V4_OFFER_REQUESTED_LEASE	8
1.24	ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE	8
1.25	ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE_COMPLETE	8
1.26	ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE_FAILED	8
1.27	ALLOC_ENGINE_V4_REQUEST_ADDRESS_RESERVED	8
1.28	ALLOC_ENGINE_V4_REQUEST_ALLOC_REQUESTED	9
1.29	ALLOC_ENGINE_V4_REQUEST_EXTEND_LEASE	9
1.30	ALLOC_ENGINE_V4_REQUEST_INVALID	9
1.31	ALLOC_ENGINE_V4_REQUEST_IN_USE	9
1.32	ALLOC_ENGINE_V4_REQUEST_OUT_OF_POOL	9
1.33	ALLOC_ENGINE_V4_REQUEST_PICK_ADDRESS	10
1.34	ALLOC_ENGINE_V4_REQUEST_REMOVE_LEASE	10
1.35	ALLOC_ENGINE_V4_REQUEST_USE_HR	10
1.36	ALLOC_ENGINE_V4_REUSE_EXPIRED_LEASE_DATA	10
1.37	ALLOC_ENGINE_V6_ALLOC_ERROR	10
1.38	ALLOC_ENGINE_V6_ALLOC_FAIL	11
1.39	ALLOC_ENGINE_V6_ALLOC_FAIL_CLASSES	11

1.40	ALLOC_ENGINE_V6_ALLOC_FAIL_NO_POOLS	11
1.41	ALLOC_ENGINE_V6_ALLOC_FAIL_SHARED_NETWORK	11
1.42	ALLOC_ENGINE_V6_ALLOC_FAIL_SUBNET	12
1.43	ALLOC_ENGINE_V6_ALLOC_HR_LEASE_EXISTS	12
1.44	ALLOC_ENGINE_V6_ALLOC_LEASES_HR	12
1.45	ALLOC_ENGINE_V6_ALLOC_LEASES_NO_HR	12
1.46	ALLOC_ENGINE_V6_ALLOC_NO_LEASES_HR	13
1.47	ALLOC_ENGINE_V6_ALLOC_NO_V6_HR	13
1.48	ALLOC_ENGINE_V6_ALLOC_UNRESERVED	13
1.49	ALLOC_ENGINE_V6_CALCULATED_PREFERRED_LIFETIME	13
1.50	ALLOC_ENGINE_V6_DECLINED_RECOVERED	13
1.51	ALLOC_ENGINE_V6_EXPIRED_HINT_RESERVED	14
1.52	ALLOC_ENGINE_V6_EXTEND_ALLOC_UNRESERVED	14
1.53	ALLOC_ENGINE_V6_EXTEND_ERROR	14
1.54	ALLOC_ENGINE_V6_EXTEND_LEASE	14
1.55	ALLOC_ENGINE_V6_EXTEND_LEASE_DATA	14
1.56	ALLOC_ENGINE_V6_EXTEND_NEW_LEASE_DATA	15
1.57	ALLOC_ENGINE_V6_HINT_RESERVED	15
1.58	ALLOC_ENGINE_V6_HR_ADDR_GRANTED	15
1.59	ALLOC_ENGINE_V6_HR_PREFIX_GRANTED	15
1.60	ALLOC_ENGINE_V6_LEASES_RECLAMATION_COMPLETE	15
1.61	ALLOC_ENGINE_V6_LEASES_RECLAMATION_FAILED	16
1.62	ALLOC_ENGINE_V6_LEASES_RECLAMATION_SLOW	16
1.63	ALLOC_ENGINE_V6_LEASES_RECLAMATION_START	16
1.64	ALLOC_ENGINE_V6_LEASES_RECLAMATION_TIMEOUT	16
1.65	ALLOC_ENGINE_V6_LEASE_RECLAIM	16
1.66	ALLOC_ENGINE_V6_LEASE_RECLAMATION_FAILED	17
1.67	ALLOC_ENGINE_V6_NO_MORE_EXPIRED_LEASES	17
1.68	ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE	17
1.69	ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE_COMPLETE	17
1.70	ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE_FAILED	17
1.71	ALLOC_ENGINE_V6_RENEW_HR	18
1.72	ALLOC_ENGINE_V6_RENEW_REMOVE_RESERVED	18
1.73	ALLOC_ENGINE_V6_REUSE_EXPIRED_LEASE_DATA	18
1.74	ALLOC_ENGINE_V6_REVOKED_ADDR_LEASE	18
1.75	ALLOC_ENGINE_V6_REVOKED_PREFIX_LEASE	18
1.76	ALLOC_ENGINE_V6_REVOKED_SHARED_ADDR_LEASE	19
<b>2</b>	<b>ASIODNS</b>	<b>21</b>
2.1	ASIODNS_FETCH_COMPLETED	21
2.2	ASIODNS_FETCH_STOPPED	21
2.3	ASIODNS_OPEN_SOCKET	21
2.4	ASIODNS_READ_DATA	21
2.5	ASIODNS_READ_TIMEOUT	22
2.6	ASIODNS_SEND_DATA	22
2.7	ASIODNS_UNKNOWN_ORIGIN	22
<b>3</b>	<b>BOOTP</b>	<b>23</b>
3.1	BOOTP_BOOTP_QUERY	23
3.2	BOOTP_LOAD	23
3.3	BOOTP_PACKET_OPTIONS_SKIPPED	23
3.4	BOOTP_PACKET_PACK	23
3.5	BOOTP_PACKET_PACK_FAIL	24
3.6	BOOTP_PACKET_UNPACK_FAILED	24

<b>4</b>	<b>COMMAND</b>	<b>25</b>
4.1	COMMAND_ACCEPTOR_START . . . . .	25
4.2	COMMAND_DEREGISTERED . . . . .	25
4.3	COMMAND_EXTENDED_REGISTERED . . . . .	25
4.4	COMMAND_HTTP_LISTENER_COMMAND_REJECTED . . . . .	25
4.5	COMMAND_HTTP_LISTENER_STARTED . . . . .	26
4.6	COMMAND_HTTP_LISTENER_STOPPED . . . . .	26
4.7	COMMAND_HTTP_LISTENER_STOPPING . . . . .	26
4.8	COMMAND_PROCESS_ERROR1 . . . . .	26
4.9	COMMAND_PROCESS_ERROR2 . . . . .	26
4.10	COMMAND_RECEIVED . . . . .	27
4.11	COMMAND_REGISTERED . . . . .	27
4.12	COMMAND_RESPONSE_ERROR . . . . .	27
4.13	COMMAND_SOCKET_ACCEPT_FAIL . . . . .	27
4.14	COMMAND_SOCKET_CLOSED_BY_FOREIGN_HOST . . . . .	27
4.15	COMMAND_SOCKET_CONNECTION_CANCEL_FAIL . . . . .	27
4.16	COMMAND_SOCKET_CONNECTION_CLOSED . . . . .	28
4.17	COMMAND_SOCKET_CONNECTION_CLOSE_FAIL . . . . .	28
4.18	COMMAND_SOCKET_CONNECTION_OPENED . . . . .	28
4.19	COMMAND_SOCKET_CONNECTION_SHUTDOWN_FAIL . . . . .	28
4.20	COMMAND_SOCKET_CONNECTION_TIMEOUT . . . . .	28
4.21	COMMAND_SOCKET_READ . . . . .	28
4.22	COMMAND_SOCKET_READ_FAIL . . . . .	29
4.23	COMMAND_SOCKET_WRITE . . . . .	29
4.24	COMMAND_SOCKET_WRITE_FAIL . . . . .	29
4.25	COMMAND_WATCH_SOCKET_CLEAR_ERROR . . . . .	29
4.26	COMMAND_WATCH_SOCKET_CLOSE_ERROR . . . . .	29
4.27	COMMAND_WATCH_SOCKET_MARK_READY_ERROR . . . . .	29
<b>5</b>	<b>CTRL</b>	<b>31</b>
5.1	CTRL_AGENT_COMMAND_FORWARDED . . . . .	31
5.2	CTRL_AGENT_COMMAND_FORWARD_BEGIN . . . . .	31
5.3	CTRL_AGENT_COMMAND_FORWARD_FAILED . . . . .	31
5.4	CTRL_AGENT_COMMAND_RECEIVED . . . . .	31
5.5	CTRL_AGENT_CONFIG_CHECK_FAIL . . . . .	32
5.6	CTRL_AGENT_CONFIG_FAIL . . . . .	32
5.7	CTRL_AGENT_CONFIG_SYNTAX_WARNING . . . . .	32
5.8	CTRL_AGENT_FAILED . . . . .	32
5.9	CTRL_AGENT_HTTPS_SERVICE_STARTED . . . . .	32
5.10	CTRL_AGENT_HTTP_SERVICE_STARTED . . . . .	32
5.11	CTRL_AGENT_RUN_EXIT . . . . .	33
<b>6</b>	<b>DATABASE</b>	<b>35</b>
6.1	DATABASE_INVALID_ACCESS . . . . .	35
6.2	DATABASE_MYSQL_COMMIT . . . . .	35
6.3	DATABASE_MYSQL_FATAL_ERROR . . . . .	35
6.4	DATABASE_MYSQL_INITIALIZE_SCHEMA . . . . .	35
6.5	DATABASE_MYSQL_ROLLBACK . . . . .	36
6.6	DATABASE_MYSQL_START_TRANSACTION . . . . .	36
6.7	DATABASE_PGSQL_COMMIT . . . . .	36
6.8	DATABASE_PGSQL_CREATE_SAVEPOINT . . . . .	36
6.9	DATABASE_PGSQL_DEALLOC_ERROR . . . . .	36
6.10	DATABASE_PGSQL_FATAL_ERROR . . . . .	37
6.11	DATABASE_PGSQL_INITIALIZE_SCHEMA . . . . .	37

6.12	DATABASE_PGSQL_ROLLBACK . . . . .	37
6.13	DATABASE_PGSQL_ROLLBACK_SAVEPOINT . . . . .	37
6.14	DATABASE_PGSQL_START_TRANSACTION . . . . .	37
6.15	DATABASE_PGSQL_TCP_USER_TIMEOUT_UNSUPPORTED . . . . .	38
6.16	DATABASE_TO_JSON_BOOLEAN_ERROR . . . . .	38
6.17	DATABASE_TO_JSON_INTEGER_ERROR . . . . .	38
<b>7</b>	<b>DCTL</b> . . . . .	<b>39</b>
7.1	DCTL_ALREADY_RUNNING . . . . .	39
7.2	DCTL_CFG_FILE_RELOAD_ERROR . . . . .	39
7.3	DCTL_CFG_FILE_RELOAD_SIGNAL_RECVD . . . . .	39
7.4	DCTL_CONFIG_CHECK_COMPLETE . . . . .	39
7.5	DCTL_CONFIG_COMPLETE . . . . .	40
7.6	DCTL_CONFIG_DEPRECATED . . . . .	40
7.7	DCTL_CONFIG_FETCH . . . . .	40
7.8	DCTL_CONFIG_FILE_LOAD_FAIL . . . . .	40
7.9	DCTL_CONFIG_START . . . . .	40
7.10	DCTL_DB_OPEN_CONNECTION_WITH_RETRY_FAILED . . . . .	41
7.11	DCTL_DEVELOPMENT_VERSION . . . . .	41
7.12	DCTL_INIT_PROCESS . . . . .	41
7.13	DCTL_INIT_PROCESS_FAIL . . . . .	41
7.14	DCTL_NOT_RUNNING . . . . .	41
7.15	DCTL_OPEN_CONFIG_DB . . . . .	41
7.16	DCTL_PARSER_FAIL . . . . .	42
7.17	DCTL_PID_FILE_ERROR . . . . .	42
7.18	DCTL_PROCESS_FAILED . . . . .	42
7.19	DCTL_RUN_PROCESS . . . . .	42
7.20	DCTL_SHUTDOWN . . . . .	42
7.21	DCTL_SHUTDOWN_SIGNAL_RECVD . . . . .	43
7.22	DCTL_STANDALONE . . . . .	43
7.23	DCTL_STARTING . . . . .	43
7.24	DCTL_UNLOAD_LIBRARIES_ERROR . . . . .	43
<b>8</b>	<b>DHCP4</b> . . . . .	<b>45</b>
8.1	DHCP4_ALREADY_RUNNING . . . . .	45
8.2	DHCP4_BUFFER_RECEIVED . . . . .	45
8.3	DHCP4_BUFFER_RECEIVE_FAIL . . . . .	45
8.4	DHCP4_BUFFER_UNPACK . . . . .	46
8.5	DHCP4_BUFFER_WAIT_SIGNAL . . . . .	46
8.6	DHCP4_CB_ON_DEMAND_FETCH_UPDATES_FAIL . . . . .	46
8.7	DHCP4_CB_PERIODIC_FETCH_UPDATES_FAIL . . . . .	46
8.8	DHCP4_CB_PERIODIC_FETCH_UPDATES_RETRIES_EXHAUSTED . . . . .	46
8.9	DHCP4_CLASSES_ASSIGNED . . . . .	47
8.10	DHCP4_CLASSES_ASSIGNED_AFTER_SUBNET_SELECTION . . . . .	47
8.11	DHCP4_CLASS_ASSIGNED . . . . .	47
8.12	DHCP4_CLASS_UNCONFIGURED . . . . .	47
8.13	DHCP4_CLASS_UNDEFINED . . . . .	47
8.14	DHCP4_CLASS_UNTESTABLE . . . . .	48
8.15	DHCP4_CLIENTID_IGNORED_FOR_LEASES . . . . .	48
8.16	DHCP4_CLIENT_FQDN_DATA . . . . .	48
8.17	DHCP4_CLIENT_FQDN_PROCESS . . . . .	48
8.18	DHCP4_CLIENT_HOSTNAME_DATA . . . . .	48
8.19	DHCP4_CLIENT_HOSTNAME_MALFORMED . . . . .	49
8.20	DHCP4_CLIENT_HOSTNAME_PROCESS . . . . .	49

8.21	DHCP4_CLIENT_NAME_PROC_FAIL	49
8.22	DHCP4_CONFIG_COMPLETE	49
8.23	DHCP4_CONFIG_LOAD_FAIL	49
8.24	DHCP4_CONFIG_PACKET_QUEUE	50
8.25	DHCP4_CONFIG_RECEIVED	50
8.26	DHCP4_CONFIG_START	50
8.27	DHCP4_CONFIG_SYNTAX_WARNING	50
8.28	DHCP4_CONFIG_UNRECOVERABLE_ERROR	50
8.29	DHCP4_CONFIG_UNSUPPORTED_OBJECT	51
8.30	DHCP4_DB_RECONNECT_DISABLED	51
8.31	DHCP4_DB_RECONNECT_FAILED	51
8.32	DHCP4_DB_RECONNECT_LOST_CONNECTION	51
8.33	DHCP4_DB_RECONNECT_NO_DB_CTL	51
8.34	DHCP4_DB_RECONNECT_SUCCEEDED	51
8.35	DHCP4_DDNS_REQUEST_SEND_FAILED	52
8.36	DHCP4_DECLINE_FAIL	52
8.37	DHCP4_DECLINE_LEASE	52
8.38	DHCP4_DECLINE_LEASE_MISMATCH	52
8.39	DHCP4_DECLINE_LEASE_NOT_FOUND	52
8.40	DHCP4_DEFERRED_OPTION_MISSING	53
8.41	DHCP4_DEFERRED_OPTION_UNPACK_FAIL	53
8.42	DHCP4_DEVELOPMENT_VERSION	53
8.43	DHCP4_DHCP4O6_BAD_PACKET	53
8.44	DHCP4_DHCP4O6_HOOK_SUBNET4_SELECT_DROP	53
8.45	DHCP4_DHCP4O6_HOOK_SUBNET4_SELECT_SKIP	53
8.46	DHCP4_DHCP4O6_PACKET_RECEIVED	54
8.47	DHCP4_DHCP4O6_PACKET_SEND	54
8.48	DHCP4_DHCP4O6_PACKET_SEND_FAIL	54
8.49	DHCP4_DHCP4O6_RECEIVE_FAIL	54
8.50	DHCP4_DHCP4O6_RECEIVING	54
8.51	DHCP4_DHCP4O6_RESPONSE_DATA	55
8.52	DHCP4_DHCP4O6_SUBNET_DATA	55
8.53	DHCP4_DHCP4O6_SUBNET_SELECTED	55
8.54	DHCP4_DHCP4O6_SUBNET_SELECTION_FAILED	55
8.55	DHCP4_DISCOVER	55
8.56	DHCP4_DYNAMIC_RECONFIGURATION	56
8.57	DHCP4_DYNAMIC_RECONFIGURATION_FAIL	56
8.58	DHCP4_DYNAMIC_RECONFIGURATION_SUCCESS	56
8.59	DHCP4_EMPTY_HOSTNAME	56
8.60	DHCP4_FLEX_ID	56
8.61	DHCP4_GENERATE_FQDN	57
8.62	DHCP4_HOOK_BUFFER_RCVD_DROP	57
8.63	DHCP4_HOOK_BUFFER_RCVD_SKIP	57
8.64	DHCP4_HOOK_BUFFER_SEND_SKIP	57
8.65	DHCP4_HOOK_DDNS_UPDATE	57
8.66	DHCP4_HOOK_DECLINE_SKIP	58
8.67	DHCP4_HOOK_LEASE4_OFFER_ARGUMENT_MISSING	58
8.68	DHCP4_HOOK_LEASE4_OFFER_DROP	58
8.69	DHCP4_HOOK_LEASE4_OFFER_PARK	58
8.70	DHCP4_HOOK_LEASE4_OFFER_PARKING_LOT_FULL	58
8.71	DHCP4_HOOK_LEASE4_RELEASE_SKIP	59
8.72	DHCP4_HOOK_LEASES4_COMMITTED_DROP	59
8.73	DHCP4_HOOK_LEASES4_COMMITTED_PARK	59
8.74	DHCP4_HOOK_LEASES4_COMMITTED_PARKING_LOT_FULL	59

8.75	DHCP4_HOOK_PACKET_RCVD_SKIP	59
8.76	DHCP4_HOOK_PACKET_SEND_DROP	60
8.77	DHCP4_HOOK_PACKET_SEND_SKIP	60
8.78	DHCP4_HOOK_SUBNET4_SELECT_406_PARKING_LOT_FULL	60
8.79	DHCP4_HOOK_SUBNET4_SELECT_DROP	60
8.80	DHCP4_HOOK_SUBNET4_SELECT_PARK	60
8.81	DHCP4_HOOK_SUBNET4_SELECT_PARKING_LOT_FULL	61
8.82	DHCP4_HOOK_SUBNET4_SELECT_SKIP	61
8.83	DHCP4_HOOK_SUBNET6_SELECT_PARKING_LOT_FULL	61
8.84	DHCP4_INFORM_DIRECT_REPLY	61
8.85	DHCP4_INIT_FAIL	61
8.86	DHCP4_INIT_REBOOT	62
8.87	DHCP4_LEASE_ALLOC	62
8.88	DHCP4_LEASE_OFFER	62
8.89	DHCP4_LEASE_REUSE	62
8.90	DHCP4_MULTI_THREADING_INFO	62
8.91	DHCP4_NCR_CREATION_FAILED	63
8.92	DHCP4_NOT_RUNNING	63
8.93	DHCP4_NO_LEASE_INIT_REBOOT	63
8.94	DHCP4_OPEN_SOCKET	63
8.95	DHCP4_OPEN_SOCKETS_FAILED	63
8.96	DHCP4_OPEN_SOCKETS_NO_RECONNECT_CTL	64
8.97	DHCP4_PACKET_DROP_0001	64
8.98	DHCP4_PACKET_DROP_0002	64
8.99	DHCP4_PACKET_DROP_0003	64
8.100	DHCP4_PACKET_DROP_0004	64
8.101	DHCP4_PACKET_DROP_0005	65
8.102	DHCP4_PACKET_DROP_0006	65
8.103	DHCP4_PACKET_DROP_0007	65
8.104	DHCP4_PACKET_DROP_0008	65
8.105	DHCP4_PACKET_DROP_0009	65
8.106	DHCP4_PACKET_DROP_0010	66
8.107	DHCP4_PACKET_DROP_0011	66
8.108	DHCP4_PACKET_DROP_0012	66
8.109	DHCP4_PACKET_DROP_0013	66
8.110	DHCP4_PACKET_DROP_0014	66
8.111	DHCP4_PACKET_NAK_0001	67
8.112	DHCP4_PACKET_NAK_0002	67
8.113	DHCP4_PACKET_NAK_0003	67
8.114	DHCP4_PACKET_NAK_0004	67
8.115	DHCP4_PACKET_OPTIONS_SKIPPED	67
8.116	DHCP4_PACKET_PACK	68
8.117	DHCP4_PACKET_PACK_FAIL	68
8.118	DHCP4_PACKET_PROCESS_EXCEPTION	68
8.119	DHCP4_PACKET_PROCESS_EXCEPTION_MAIN	68
8.120	DHCP4_PACKET_PROCESS_STD_EXCEPTION	68
8.121	DHCP4_PACKET_PROCESS_STD_EXCEPTION_MAIN	69
8.122	DHCP4_PACKET_QUEUE_FULL	69
8.123	DHCP4_PACKET_RECEIVED	69
8.124	DHCP4_PACKET_SEND	69
8.125	DHCP4_PACKET_SEND_FAIL	70
8.126	DHCP4_PARSER_COMMIT_EXCEPTION	70
8.127	DHCP4_PARSER_COMMIT_FAIL	70
8.128	DHCP4_PARSER_EXCEPTION	70



8.129	DHCP4_PARSER_FAIL	70
8.130	DHCP4_POST_ALLOCATION_NAME_UPDATE_FAIL	71
8.131	DHCP4_QUERY_DATA	71
8.132	DHCP4_QUERY_LABEL	71
8.133	DHCP4_RECLAIM_EXPIRED_LEASES_FAIL	71
8.134	DHCP4_RECOVERED_STASHED_RELAY_AGENT_INFO	71
8.135	DHCP4_RELEASE	72
8.136	DHCP4_RELEASE_DELETED	72
8.137	DHCP4_RELEASE_EXCEPTION	72
8.138	DHCP4_RELEASE_EXPIRED	72
8.139	DHCP4_RELEASE_FAIL	72
8.140	DHCP4_RELEASE_FAIL_NO_LEASE	73
8.141	DHCP4_RELEASE_FAIL_WRONG_CLIENT	73
8.142	DHCP4_REQUEST	73
8.143	DHCP4_REQUIRED_CLASS_EVAL_ERROR	73
8.144	DHCP4_REQUIRED_CLASS_EVAL_RESULT	73
8.145	DHCP4_RESERVATIONS_LOOKUP_FIRST_ENABLED	74
8.146	DHCP4_RESERVED_HOSTNAME_ASSIGNED	74
8.147	DHCP4_RESPONSE_DATA	74
8.148	DHCP4_RESPONSE_FQDN_DATA	74
8.149	DHCP4_RESPONSE_HOSTNAME_DATA	74
8.150	DHCP4_RESPONSE_HOSTNAME_GENERATE	75
8.151	DHCP4_SERVER_FAILED	75
8.152	DHCP4_SERVER_INITIATED_DECLINE	75
8.153	DHCP4_SERVER_INITIATED_DECLINE_ADD_FAILED	75
8.154	DHCP4_SERVER_INITIATED_DECLINE_RESOURCE_BUSY	75
8.155	DHCP4_SERVER_INITIATED_DECLINE_UPDATE_FAILED	76
8.156	DHCP4_SHUTDOWN	76
8.157	DHCP4_SHUTDOWN_REQUEST	76
8.158	DHCP4_SRV_CONSTRUCT_ERROR	76
8.159	DHCP4_SRV_D2STOP_ERROR	76
8.160	DHCP4_SRV_DHCP4O6_ERROR	77
8.161	DHCP4_SRV_UNLOAD_LIBRARIES_ERROR	77
8.162	DHCP4_STARTED	77
8.163	DHCP4_STARTING	77
8.164	DHCP4_START_INFO	77
8.165	DHCP4_SUBNET_DATA	78
8.166	DHCP4_SUBNET_DYNAMICALLY_CHANGED	78
8.167	DHCP4_SUBNET_SELECTED	78
8.168	DHCP4_SUBNET_SELECTION_FAILED	78
8.169	DHCP4_TESTING_MODE_SEND_TO_SOURCE_ENABLED	78
8.170	DHCP4_UNKNOWN_ADDRESS_REQUESTED	79
8.171	DHCP4_V6_ONLY_PREFERRED_MISSING_IN_ACK	79
<b>9</b>	<b>DHCP6</b>	<b>81</b>
9.1	DHCP6_ADD_GLOBAL_STATUS_CODE	81
9.2	DHCP6_ADD_STATUS_CODE_FOR_IA	81
9.3	DHCP6_ALREADY_RUNNING	81
9.4	DHCP6_BUFFER_RECEIVED	82
9.5	DHCP6_BUFFER_UNPACK	82
9.6	DHCP6_BUFFER_WAIT_SIGNAL	82
9.7	DHCP6_CB_ON_DEMAND_FETCH_UPDATES_FAIL	82
9.8	DHCP6_CB_PERIODIC_FETCH_UPDATES_FAIL	82
9.9	DHCP6_CB_PERIODIC_FETCH_UPDATES_RETRIES_EXHAUSTED	83

9.10	DHCP6_CLASSES_ASSIGNED	83
9.11	DHCP6_CLASSES_ASSIGNED_AFTER_SUBNET_SELECTION	83
9.12	DHCP6_CLASS_ASSIGNED	83
9.13	DHCP6_CLASS_UNCONFIGURED	83
9.14	DHCP6_CLASS_UNDEFINED	84
9.15	DHCP6_CLASS_UNTESTABLE	84
9.16	DHCP6_CONFIG_COMPLETE	84
9.17	DHCP6_CONFIG_LOAD_FAIL	84
9.18	DHCP6_CONFIG_PACKET_QUEUE	84
9.19	DHCP6_CONFIG_RECEIVED	85
9.20	DHCP6_CONFIG_START	85
9.21	DHCP6_CONFIG_SYNTAX_WARNING	85
9.22	DHCP6_CONFIG_UNRECOVERABLE_ERROR	85
9.23	DHCP6_CONFIG_UNSUPPORTED_OBJECT	85
9.24	DHCP6_DB_RECONNECT_DISABLED	86
9.25	DHCP6_DB_RECONNECT_FAILED	86
9.26	DHCP6_DB_RECONNECT_LOST_CONNECTION	86
9.27	DHCP6_DB_RECONNECT_NO_DB_CTL	86
9.28	DHCP6_DB_RECONNECT_SUCCEEDED	86
9.29	DHCP6_DDNS_CREATE_ADD_NAME_CHANGE_REQUEST	86
9.30	DHCP6_DDNS_FQDN_GENERATED	87
9.31	DHCP6_DDNS_GENERATED_FQDN_UPDATE_FAIL	87
9.32	DHCP6_DDNS_GENERATE_FQDN	87
9.33	DHCP6_DDNS_RECEIVE_FQDN	87
9.34	DHCP6_DDNS_REMOVE_OLD_LEASE_FQDN	87
9.35	DHCP6_DDNS_REQUEST_SEND_FAILED	88
9.36	DHCP6_DDNS_RESPONSE_FQDN_DATA	88
9.37	DHCP6_DECLINE_FAIL	88
9.38	DHCP6_DECLINE_FAIL_DUID_MISMATCH	88
9.39	DHCP6_DECLINE_FAIL_IAID_MISMATCH	88
9.40	DHCP6_DECLINE_FAIL_LEASE_WITHOUT_DUID	89
9.41	DHCP6_DECLINE_FAIL_NO_LEASE	89
9.42	DHCP6_DECLINE_LEASE	89
9.43	DHCP6_DECLINE_PROCESS_IA	89
9.44	DHCP6_DEVELOPMENT_VERSION	89
9.45	DHCP6_DHCP4O6_PACKET_RECEIVED	90
9.46	DHCP6_DHCP4O6_RECEIVE_FAIL	90
9.47	DHCP6_DHCP4O6_RECEIVING	90
9.48	DHCP6_DHCP4O6_RESPONSE_DATA	90
9.49	DHCP6_DHCP4O6_SEND_FAIL	90
9.50	DHCP6_DYNAMIC_RECONFIGURATION	91
9.51	DHCP6_DYNAMIC_RECONFIGURATION_FAIL	91
9.52	DHCP6_DYNAMIC_RECONFIGURATION_SUCCESS	91
9.53	DHCP6_FLEX_ID	91
9.54	DHCP6_HOOK_BUFFER_RCVD_DROP	91
9.55	DHCP6_HOOK_BUFFER_RCVD_SKIP	92
9.56	DHCP6_HOOK_BUFFER_SEND_SKIP	92
9.57	DHCP6_HOOK_DDNS_UPDATE	92
9.58	DHCP6_HOOK_DECLINE_DROP	92
9.59	DHCP6_HOOK_DECLINE_SKIP	93
9.60	DHCP6_HOOK_LEASE6_RELEASE_NA_SKIP	93
9.61	DHCP6_HOOK_LEASE6_RELEASE_PD_SKIP	93
9.62	DHCP6_HOOK_LEASES6_COMMITTED_DROP	93
9.63	DHCP6_HOOK_LEASES6_COMMITTED_PARK	93

9.64	DHCP6_HOOK_LEASES6_PARKING_LOT_FULL	94
9.65	DHCP6_HOOK_PACKET_RCVD_SKIP	94
9.66	DHCP6_HOOK_PACKET_SEND_DROP	94
9.67	DHCP6_HOOK_PACKET_SEND_SKIP	94
9.68	DHCP6_HOOK_SUBNET6_SELECT_DROP	94
9.69	DHCP6_HOOK_SUBNET6_SELECT_PARK	95
9.70	DHCP6_HOOK_SUBNET6_SELECT_SKIP	95
9.71	DHCP6_INIT_FAIL	95
9.72	DHCP6_LEASE_ADVERT	95
9.73	DHCP6_LEASE_ADVERT_FAIL	95
9.74	DHCP6_LEASE_ALLOC	96
9.75	DHCP6_LEASE_ALLOC_FAIL	96
9.76	DHCP6_LEASE_DATA	96
9.77	DHCP6_LEASE_NA_WITHOUT_DUID	96
9.78	DHCP6_LEASE_PD_WITHOUT_DUID	96
9.79	DHCP6_LEASE_RENEW	97
9.80	DHCP6_LEASE_REUSE	97
9.81	DHCP6_MULTI_THREADING_INFO	97
9.82	DHCP6_NOT_RUNNING	97
9.83	DHCP6_NO_INTERFACES	97
9.84	DHCP6_OPEN_SOCKET	98
9.85	DHCP6_OPEN_SOCKETS_FAILED	98
9.86	DHCP6_OPEN_SOCKETS_NO_RECONNECT_CTL	98
9.87	DHCP6_PACKET_DROP_DHCP_DISABLED	98
9.88	DHCP6_PACKET_DROP_DROP_CLASS	98
9.89	DHCP6_PACKET_DROP_DROP_CLASS2	99
9.90	DHCP6_PACKET_DROP_DROP_CLASS_EARLY	99
9.91	DHCP6_PACKET_DROP_DUPLICATE	99
9.92	DHCP6_PACKET_DROP_PARSE_FAIL	99
9.93	DHCP6_PACKET_DROP_SERVERID_MISMATCH	99
9.94	DHCP6_PACKET_DROP_UNICAST	100
9.95	DHCP6_PACKET_OPTIONS_SKIPPED	100
9.96	DHCP6_PACKET_PROCESS_EXCEPTION	100
9.97	DHCP6_PACKET_PROCESS_EXCEPTION_MAIN	100
9.98	DHCP6_PACKET_PROCESS_FAIL	100
9.99	DHCP6_PACKET_PROCESS_STD_EXCEPTION	101
9.100	DHCP6_PACKET_PROCESS_STD_EXCEPTION_MAIN	101
9.101	DHCP6_PACKET_QUEUE_FULL	101
9.102	DHCP6_PACKET_RECEIVED	101
9.103	DHCP6_PACKET_RECEIVE_FAIL	101
9.104	DHCP6_PACKET_SEND	102
9.105	DHCP6_PACKET_SEND_FAIL	102
9.106	DHCP6_PACK_FAIL	102
9.107	DHCP6_PARSER_COMMIT_EXCEPTION	102
9.108	DHCP6_PARSER_COMMIT_FAIL	102
9.109	DHCP6_PARSER_EXCEPTION	103
9.110	DHCP6_PARSER_FAIL	103
9.111	DHCP6_PD_LEASE_ADVERT	103
9.112	DHCP6_PD_LEASE_ADVERT_FAIL	103
9.113	DHCP6_PD_LEASE_ALLOC	103
9.114	DHCP6_PD_LEASE_ALLOC_FAIL	104
9.115	DHCP6_PD_LEASE_RENEW	104
9.116	DHCP6_PD_LEASE_REUSE	104
9.117	DHCP6_PROCESS_IA_NA_EXTEND	104

9.118	DHCP6_PROCESS_IA_NA_RELEASE	104
9.119	DHCP6_PROCESS_IA_NA_REQUEST	105
9.120	DHCP6_PROCESS_IA_NA_SOLICIT	105
9.121	DHCP6_PROCESS_IA_PD_EXTEND	105
9.122	DHCP6_PROCESS_IA_PD_REQUEST	105
9.123	DHCP6_PROCESS_IA_PD_SOLICIT	105
9.124	DHCP6_QUERY_DATA	106
9.125	DHCP6_QUERY_LABEL	106
9.126	DHCP6_RAPID_COMMIT	106
9.127	DHCP6_RECLAIM_EXPIRED_LEASES_FAIL	106
9.128	DHCP6_RELEASE_NA	106
9.129	DHCP6_RELEASE_NA_DELETED	107
9.130	DHCP6_RELEASE_NA_EXPIRED	107
9.131	DHCP6_RELEASE_NA_FAIL	107
9.132	DHCP6_RELEASE_NA_FAIL_WRONG_DUID	107
9.133	DHCP6_RELEASE_NA_FAIL_WRONG_IAID	107
9.134	DHCP6_RELEASE_PD	108
9.135	DHCP6_RELEASE_PD_DELETED	108
9.136	DHCP6_RELEASE_PD_EXPIRED	108
9.137	DHCP6_RELEASE_PD_FAIL	108
9.138	DHCP6_RELEASE_PD_FAIL_WRONG_DUID	108
9.139	DHCP6_RELEASE_PD_FAIL_WRONG_IAID	109
9.140	DHCP6_REQUIRED_CLASS_EVAL_ERROR	109
9.141	DHCP6_REQUIRED_CLASS_EVAL_RESULT	109
9.142	DHCP6_REQUIRED_OPTIONS_CHECK_FAIL	109
9.143	DHCP6_RESERVATIONS_LOOKUP_FIRST_ENABLED	109
9.144	DHCP6_RESPONSE_DATA	110
9.145	DHCP6_SERVER_FAILED	110
9.146	DHCP6_SHUTDOWN	110
9.147	DHCP6_SHUTDOWN_REQUEST	110
9.148	DHCP6_SRV_CONSTRUCT_ERROR	110
9.149	DHCP6_SRV_D2STOP_ERROR	111
9.150	DHCP6_SRV_UNLOAD_LIBRARIES_ERROR	111
9.151	DHCP6_STARTED	111
9.152	DHCP6_STARTING	111
9.153	DHCP6_START_INFO	111
9.154	DHCP6_SUBNET_DATA	112
9.155	DHCP6_SUBNET_DYNAMICALLY_CHANGED	112
9.156	DHCP6_SUBNET_SELECTED	112
9.157	DHCP6_SUBNET_SELECTION_FAILED	112
9.158	DHCP6_UNKNOWN_MSG_RECEIVED	112

<b>10</b>	<b>DHCPSRV</b>	<b>113</b>
10.1	DHCPSRV_CFGMGR_ADD_IFACE	113
10.2	DHCPSRV_CFGMGR_ADD_SUBNET4	113
10.3	DHCPSRV_CFGMGR_ADD_SUBNET6	113
10.4	DHCPSRV_CFGMGR_ALL_IFACES_ACTIVE	113
10.5	DHCPSRV_CFGMGR_CFG_DHCP_DDNS	114
10.6	DHCPSRV_CFGMGR_CONFIG4_MERGED	114
10.7	DHCPSRV_CFGMGR_CONFIG6_MERGED	114
10.8	DHCPSRV_CFGMGR_CONFIGURE_SERVERID	114
10.9	DHCPSRV_CFGMGR_DEL_SUBNET4	114
10.10	DHCPSRV_CFGMGR_DEL_SUBNET6	115
10.11	DHCPSRV_CFGMGR_FLQ_POPULATE_FREE_ADDRESS_LEASES	115

10.12	DHCPSRV_CFGMGR_FLQ_POPULATE_FREE_ADDRESS_LEASES_DONE	115
10.13	DHCPSRV_CFGMGR_FLQ_POPULATE_FREE_PREFIX_LEASES	115
10.14	DHCPSRV_CFGMGR_FLQ_POPULATE_FREE_PREFIX_LEASES_DONE	115
10.15	DHCPSRV_CFGMGR_IPV4_RESERVATIONS_NON_UNIQUE_IGNORED	116
10.16	DHCPSRV_CFGMGR_IPV6_RESERVATIONS_NON_UNIQUE_IGNORED	116
10.17	DHCPSRV_CFGMGR_IP_RESERVATIONS_UNIQUE_DUPLICATES_DETECTED	116
10.18	DHCPSRV_CFGMGR_IP_RESERVATIONS_UNIQUE_DUPLICATES_POSSIBLE	116
10.19	DHCPSRV_CFGMGR_NEW_SUBNET4	117
10.20	DHCPSRV_CFGMGR_NEW_SUBNET6	117
10.21	DHCPSRV_CFGMGR_OPTION_DUPLICATE	117
10.22	DHCPSRV_CFGMGR_RENEW_GTR_REBIND	117
10.23	DHCPSRV_CFGMGR_SOCKET_RAW_UNSUPPORTED	117
10.24	DHCPSRV_CFGMGR_SOCKET_TYPE_DEFAULT	118
10.25	DHCPSRV_CFGMGR_SOCKET_TYPE_SELECT	118
10.26	DHCPSRV_CFGMGR_SUBNET4	118
10.27	DHCPSRV_CFGMGR_SUBNET4_ADDR	118
10.28	DHCPSRV_CFGMGR_SUBNET4_IFACE	118
10.29	DHCPSRV_CFGMGR_SUBNET4_RELAY	119
10.30	DHCPSRV_CFGMGR_SUBNET6	119
10.31	DHCPSRV_CFGMGR_SUBNET6_IFACE	119
10.32	DHCPSRV_CFGMGR_SUBNET6_IFACE_ID	119
10.33	DHCPSRV_CFGMGR_SUBNET6_RELAY	119
10.34	DHCPSRV_CFGMGR_UNICAST_LINK_LOCAL	120
10.35	DHCPSRV_CFGMGR_UPDATE_SUBNET4	120
10.36	DHCPSRV_CFGMGR_UPDATE_SUBNET6	120
10.37	DHCPSRV_CFGMGR_USE_ADDRESS	120
10.38	DHCPSRV_CFGMGR_USE_ALLOCATOR	120
10.39	DHCPSRV_CFGMGR_USE_UNICAST	120
10.40	DHCPSRV_CLOSE_DB	121
10.41	DHCPSRV_DDNS_TTL_PERCENT_TOO_SMALL	121
10.42	DHCPSRV_DHCP4O6_RECEIVED_BAD_PACKET	121
10.43	DHCPSRV_DHCP_DDNS_ERROR_EXCEPTION	121
10.44	DHCPSRV_DHCP_DDNS_HANDLER_NULL	121
10.45	DHCPSRV_DHCP_DDNS_NCR_REJECTED	122
10.46	DHCPSRV_DHCP_DDNS_NCR_SENT	122
10.47	DHCPSRV_DHCP_DDNS_SENDER_STARTED	122
10.48	DHCPSRV_DHCP_DDNS_SENDER_STOPPED	122
10.49	DHCPSRV_DHCP_DDNS_SUSPEND_UPDATES	122
10.50	DHCPSRV_EVAL_ERROR	123
10.51	DHCPSRV_EVAL_RESULT	123
10.52	DHCPSRV_HOOK_LEASE4_RECOVER_SKIP	123
10.53	DHCPSRV_HOOK_LEASE4_RENEW_SKIP	123
10.54	DHCPSRV_HOOK_LEASE4_SELECT_SKIP	123
10.55	DHCPSRV_HOOK_LEASE6_EXTEND_SKIP	124
10.56	DHCPSRV_HOOK_LEASE6_RECOVER_SKIP	124
10.57	DHCPSRV_HOOK_LEASE6_SELECT_SKIP	124
10.58	DHCPSRV_HOST_MGR_DB_OPEN_CONNECTION_WITH_RETRY_FAILED	124
10.59	DHCPSRV_LEASE4_EXTENDED_INFO_SANITY_FAIL	124
10.60	DHCPSRV_LEASE4_EXTENDED_INFO_UPGRADED	125
10.61	DHCPSRV_LEASE6_EXTENDED_INFO_SANITY_FAIL	125
10.62	DHCPSRV_LEASE6_EXTENDED_INFO_UPGRADED	125
10.63	DHCPSRV_LEASE_MGR_CALLBACK_EXCEPTION	125
10.64	DHCPSRV_LEASE_MGR_CALLBACK_UNKNOWN_EXCEPTION	125
10.65	DHCPSRV_LEASE_MGR_DB_OPEN_CONNECTION_WITH_RETRY_FAILED	126

10.66	DHCPSRV_LEASE_SANITY_FAIL	126
10.67	DHCPSRV_LEASE_SANITY_FAIL_DISCARD	126
10.68	DHCPSRV_LEASE_SANITY_FIXED	126
10.69	DHCPSRV_MEMFILE_ADD_ADDR4	126
10.70	DHCPSRV_MEMFILE_ADD_ADDR6	127
10.71	DHCPSRV_MEMFILE_BEGIN_BUILD_EXTENDED_INFO_TABLES6	127
10.72	DHCPSRV_MEMFILE_BEGIN_EXTRACT_EXTENDED_INFO4	127
10.73	DHCPSRV_MEMFILE_BUILD_EXTENDED_INFO_TABLES6	127
10.74	DHCPSRV_MEMFILE_BUILD_EXTENDED_INFO_TABLES6_ERROR	127
10.75	DHCPSRV_MEMFILE_COMMIT	127
10.76	DHCPSRV_MEMFILE_CONVERTING_LEASE_FILES	128
10.77	DHCPSRV_MEMFILE_DB	128
10.78	DHCPSRV_MEMFILE_DELETE_ADDR	128
10.79	DHCPSRV_MEMFILE_DELETE_EXPIRED_RECLAIMED4	128
10.80	DHCPSRV_MEMFILE_DELETE_EXPIRED_RECLAIMED6	128
10.81	DHCPSRV_MEMFILE_DELETE_EXPIRED_RECLAIMED_START	129
10.82	DHCPSRV_MEMFILE_EXTRACT_EXTENDED_INFO4	129
10.83	DHCPSRV_MEMFILE_EXTRACT_EXTENDED_INFO4_ERROR	129
10.84	DHCPSRV_MEMFILE_GET4	129
10.85	DHCPSRV_MEMFILE_GET6	129
10.86	DHCPSRV_MEMFILE_GET6_DUID	130
10.87	DHCPSRV_MEMFILE_GET_ADDR4	130
10.88	DHCPSRV_MEMFILE_GET_ADDR6	130
10.89	DHCPSRV_MEMFILE_GET_CLIENTID	130
10.90	DHCPSRV_MEMFILE_GET_EXPIRED4	130
10.91	DHCPSRV_MEMFILE_GET_EXPIRED6	130
10.92	DHCPSRV_MEMFILE_GET_HOSTNAME4	131
10.93	DHCPSRV_MEMFILE_GET_HOSTNAME6	131
10.94	DHCPSRV_MEMFILE_GET_HWADDR	131
10.95	DHCPSRV_MEMFILE_GET_IAID_DUID	131
10.96	DHCPSRV_MEMFILE_GET_IAID_SUBID_DUID	131
10.97	DHCPSRV_MEMFILE_GET_PAGE4	132
10.98	DHCPSRV_MEMFILE_GET_PAGE6	132
10.99	DHCPSRV_MEMFILE_GET_RELAYID4	132
10.100	DHCPSRV_MEMFILE_GET_RELAYID6	132
10.101	DHCPSRV_MEMFILE_GET_REMOTEID4	132
10.102	DHCPSRV_MEMFILE_GET_REMOTEID6	133
10.103	DHCPSRV_MEMFILE_GET_SUBID4	133
10.104	DHCPSRV_MEMFILE_GET_SUBID6	133
10.105	DHCPSRV_MEMFILE_GET_SUBID_CLIENTID	133
10.106	DHCPSRV_MEMFILE_GET_SUBID_HWADDR	133
10.107	DHCPSRV_MEMFILE_GET_SUBID_PAGE6	133
10.108	DHCPSRV_MEMFILE_LEASE_FILE_LOAD	134
10.109	DHCPSRV_MEMFILE_LEASE_LOAD	134
10.110	DHCPSRV_MEMFILE_LEASE_LOAD_ROW_ERROR	134
10.111	DHCPSRV_MEMFILE_LFC_EXECUTE	134
10.112	DHCPSRV_MEMFILE_LFC_LEASE_FILE_RENAME_FAIL	134
10.113	DHCPSRV_MEMFILE_LFC_LEASE_FILE_REOPEN_FAIL	134
10.114	DHCPSRV_MEMFILE_LFC_SETUP	135
10.115	DHCPSRV_MEMFILE_LFC_SPAWN_FAIL	135
10.116	DHCPSRV_MEMFILE_LFC_START	135
10.117	DHCPSRV_MEMFILE_LFC_UNREGISTER_TIMER_FAILED	135
10.118	DHCPSRV_MEMFILE_NEEDS_DOWNGRADING	135
10.119	DHCPSRV_MEMFILE_NEEDS_UPGRADING	136

10.120	DHCPSRV_MEMFILE_NO_STORAGE	136
10.121	DHCPSRV_MEMFILE_READ_HWADDR_FAIL	136
10.122	DHCPSRV_MEMFILE_ROLLBACK	136
10.123	DHCPSRV_MEMFILE_UPDATE_ADDR4	136
10.124	DHCPSRV_MEMFILE_UPDATE_ADDR6	137
10.125	DHCPSRV_MEMFILE_WIPE_LEASES4	137
10.126	DHCPSRV_MEMFILE_WIPE_LEASES4_FINISHED	137
10.127	DHCPSRV_MEMFILE_WIPE_LEASES6	137
10.128	DHCPSRV_MEMFILE_WIPE_LEASES6_FINISHED	137
10.129	DHCPSRV_MT_DISABLED_QUEUE_CONTROL	137
10.130	DHCPSRV_MULTIPLE_RAW_SOCKETS_PER_IFACE	138
10.131	DHCPSRV_MYSQL_ADD_ADDR4	138
10.132	DHCPSRV_MYSQL_ADD_ADDR6	138
10.133	DHCPSRV_MYSQL_COMMIT	138
10.134	DHCPSRV_MYSQL_DB	138
10.135	DHCPSRV_MYSQL_DELETED_EXPIRED_RECLAIMED	139
10.136	DHCPSRV_MYSQL_DELETE_ADDR	139
10.137	DHCPSRV_MYSQL_DELETE_EXPIRED_RECLAIMED4	139
10.138	DHCPSRV_MYSQL_DELETE_EXPIRED_RECLAIMED6	139
10.139	DHCPSRV_MYSQL_GET4	139
10.140	DHCPSRV_MYSQL_GET6	140
10.141	DHCPSRV_MYSQL_GET_ADDR4	140
10.142	DHCPSRV_MYSQL_GET_ADDR6	140
10.143	DHCPSRV_MYSQL_GET_CLIENTID	140
10.144	DHCPSRV_MYSQL_GET_DUID	140
10.145	DHCPSRV_MYSQL_GET_EXPIRED4	140
10.146	DHCPSRV_MYSQL_GET_EXPIRED6	141
10.147	DHCPSRV_MYSQL_GET_HOSTNAME4	141
10.148	DHCPSRV_MYSQL_GET_HOSTNAME6	141
10.149	DHCPSRV_MYSQL_GET_HWADDR	141
10.150	DHCPSRV_MYSQL_GET_IAID_DUID	141
10.151	DHCPSRV_MYSQL_GET_IAID_SUBID_DUID	142
10.152	DHCPSRV_MYSQL_GET_PAGE4	142
10.153	DHCPSRV_MYSQL_GET_PAGE6	142
10.154	DHCPSRV_MYSQL_GET_RELAYID4	142
10.155	DHCPSRV_MYSQL_GET_RELAYID6	142
10.156	DHCPSRV_MYSQL_GET_REMOTEID4	143
10.157	DHCPSRV_MYSQL_GET_REMOTEID6	143
10.158	DHCPSRV_MYSQL_GET_SUBID4	143
10.159	DHCPSRV_MYSQL_GET_SUBID6	143
10.160	DHCPSRV_MYSQL_GET_SUBID_CLIENTID	143
10.161	DHCPSRV_MYSQL_GET_SUBID_HWADDR	144
10.162	DHCPSRV_MYSQL_GET_SUBID_PAGE6	144
10.163	DHCPSRV_MYSQL_GET_VERSION	144
10.164	DHCPSRV_MYSQL_HOST_DB	144
10.165	DHCPSRV_MYSQL_HOST_DB_GET_VERSION	144
10.166	DHCPSRV_MYSQL_HOST_DB_READONLY	145
10.167	DHCPSRV_MYSQL_HOST_DB_RECONNECT_ATTEMPT_FAILED	145
10.168	DHCPSRV_MYSQL_HOST_DB_RECONNECT_ATTEMPT_SCHEDULE	145
10.169	DHCPSRV_MYSQL_HOST_DB_RECONNECT_FAILED	145
10.170	DHCPSRV_MYSQL_LEASE_DB_RECONNECT_ATTEMPT_FAILED	145
10.171	DHCPSRV_MYSQL_LEASE_DB_RECONNECT_ATTEMPT_SCHEDULE	145
10.172	DHCPSRV_MYSQL_LEASE_DB_RECONNECT_FAILED	146
10.173	DHCPSRV_MYSQL_NEGATIVE_LEASES_STAT	146

10.174	DHCPSRV_MYSQL_NO_TLS	146
10.175	DHCPSRV_MYSQL_ROLLBACK	146
10.176	DHCPSRV_MYSQL_TLS_CIPHER	146
10.177	DHCPSRV_MYSQL_UPDATE_ADDR4	146
10.178	DHCPSRV_MYSQL_UPDATE_ADDR6	147
10.179	DHCPSRV_MYSQL_UPGRADE_EXTENDED_INFO4	147
10.180	DHCPSRV_MYSQL_UPGRADE_EXTENDED_INFO4_ERROR	147
10.181	DHCPSRV_MYSQL_UPGRADE_EXTENDED_INFO4_PAGE	147
10.182	DHCPSRV_MYSQL_UPGRADE_EXTENDED_INFO6	147
10.183	DHCPSRV_MYSQL_UPGRADE_EXTENDED_INFO6_ERROR	147
10.184	DHCPSRV_MYSQL_UPGRADE_EXTENDED_INFO6_PAGE	148
10.185	DHCPSRV_NOTYPE_DB	148
10.186	DHCPSRV_NO_SOCKETS_OPEN	148
10.187	DHCPSRV_OPEN_SOCKET_FAIL	148
10.188	DHCPSRV_PGSQL_ADD_ADDR4	148
10.189	DHCPSRV_PGSQL_ADD_ADDR6	148
10.190	DHCPSRV_PGSQL_COMMIT	149
10.191	DHCPSRV_PGSQL_DB	149
10.192	DHCPSRV_PGSQL_DELETE_ADDR	149
10.193	DHCPSRV_PGSQL_DELETE_EXPIRED_RECLAIMED4	149
10.194	DHCPSRV_PGSQL_DELETE_EXPIRED_RECLAIMED6	149
10.195	DHCPSRV_PGSQL_GET4	150
10.196	DHCPSRV_PGSQL_GET6	150
10.197	DHCPSRV_PGSQL_GET_ADDR4	150
10.198	DHCPSRV_PGSQL_GET_ADDR6	150
10.199	DHCPSRV_PGSQL_GET_CLIENTID	150
10.200	DHCPSRV_PGSQL_GET_DUID	150
10.201	DHCPSRV_PGSQL_GET_EXPIRED4	151
10.202	DHCPSRV_PGSQL_GET_EXPIRED6	151
10.203	DHCPSRV_PGSQL_GET_HOSTNAME4	151
10.204	DHCPSRV_PGSQL_GET_HOSTNAME6	151
10.205	DHCPSRV_PGSQL_GET_HWADDR	151
10.206	DHCPSRV_PGSQL_GET_IAID_DUID	151
10.207	DHCPSRV_PGSQL_GET_IAID_SUBID_DUID	152
10.208	DHCPSRV_PGSQL_GET_PAGE4	152
10.209	DHCPSRV_PGSQL_GET_PAGE6	152
10.210	DHCPSRV_PGSQL_GET_RELAYID4	152
10.211	DHCPSRV_PGSQL_GET_RELAYID6	152
10.212	DHCPSRV_PGSQL_GET_REMOTEID4	153
10.213	DHCPSRV_PGSQL_GET_REMOTEID6	153
10.214	DHCPSRV_PGSQL_GET_SUBID4	153
10.215	DHCPSRV_PGSQL_GET_SUBID6	153
10.216	DHCPSRV_PGSQL_GET_SUBID_CLIENTID	153
10.217	DHCPSRV_PGSQL_GET_SUBID_HWADDR	154
10.218	DHCPSRV_PGSQL_GET_SUBID_PAGE6	154
10.219	DHCPSRV_PGSQL_GET_VERSION	154
10.220	DHCPSRV_PGSQL_HOST_DB	154
10.221	DHCPSRV_PGSQL_HOST_DB_GET_VERSION	154
10.222	DHCPSRV_PGSQL_HOST_DB_READONLY	155
10.223	DHCPSRV_PGSQL_HOST_DB_RECONNECT_ATTEMPT_FAILED	155
10.224	DHCPSRV_PGSQL_HOST_DB_RECONNECT_ATTEMPT_SCHEDULE	155
10.225	DHCPSRV_PGSQL_HOST_DB_RECONNECT_FAILED	155
10.226	DHCPSRV_PGSQL_LEASE_DB_RECONNECT_ATTEMPT_FAILED	155
10.227	DHCPSRV_PGSQL_LEASE_DB_RECONNECT_ATTEMPT_SCHEDULE	155



10.228	DHCP_SRV_PGSQL_LEASE_DB_RECONNECT_FAILED	156
10.229	DHCP_SRV_PGSQL_NEGATIVE_LEASES_STAT	156
10.230	DHCP_SRV_PGSQL_NO_TLS_SUPPORT	156
10.231	DHCP_SRV_PGSQL_ROLLBACK	156
10.232	DHCP_SRV_PGSQL_TLS_SUPPORT	156
10.233	DHCP_SRV_PGSQL_UPDATE_ADDR4	157
10.234	DHCP_SRV_PGSQL_UPDATE_ADDR6	157
10.235	DHCP_SRV_PGSQL_UPGRADE_EXTENDED_INFO4	157
10.236	DHCP_SRV_PGSQL_UPGRADE_EXTENDED_INFO4_ERROR	157
10.237	DHCP_SRV_PGSQL_UPGRADE_EXTENDED_INFO4_PAGE	157
10.238	DHCP_SRV_PGSQL_UPGRADE_EXTENDED_INFO6	157
10.239	DHCP_SRV_PGSQL_UPGRADE_EXTENDED_INFO6_ERROR	158
10.240	DHCP_SRV_PGSQL_UPGRADE_EXTENDED_INFO6_PAGE	158
10.241	DHCP_SRV_QUEUE_NCR	158
10.242	DHCP_SRV_QUEUE_NCR_FAILED	158
10.243	DHCP_SRV_QUEUE_NCR_SKIP	158
10.244	DHCP_SRV_SUBNET4O6_SELECT_FAILED	159
10.245	DHCP_SRV_SUBNET4_SELECT_BY_ADDRESS_NO_MATCH	159
10.246	DHCP_SRV_SUBNET4_SELECT_BY_INTERFACE_NO_MATCH	159
10.247	DHCP_SRV_SUBNET4_SELECT_BY_RELAY_ADDRESS_NO_MATCH	159
10.248	DHCP_SRV_SUBNET4_SELECT_NO_RAIOPTIONS	159
10.249	DHCP_SRV_SUBNET4_SELECT_NO_RELAY_ADDRESS	159
10.250	DHCP_SRV_SUBNET4_SELECT_NO_USABLE_ADDRESS	160
10.251	DHCP_SRV_SUBNET6_SELECT_BY_ADDRESS_NO_MATCH	160
10.252	DHCP_SRV_SUBNET6_SELECT_BY_INTERFACE_ID_NO_MATCH	160
10.253	DHCP_SRV_SUBNET6_SELECT_BY_INTERFACE_NO_MATCH	160
10.254	DHCP_SRV_TEMPLATE_EVAL_ERROR	160
10.255	DHCP_SRV_TEMPLATE_EVAL_RESULT	160
10.256	DHCP_SRV_TIMERMGR_CALLBACK_FAILED	161
10.257	DHCP_SRV_TIMERMGR_REGISTER_TIMER	161
10.258	DHCP_SRV_TIMERMGR_RUN_TIMER_OPERATION	161
10.259	DHCP_SRV_TIMERMGR_START_TIMER	161
10.260	DHCP_SRV_TIMERMGR_STOP_TIMER	161
10.261	DHCP_SRV_TIMERMGR_UNREGISTER_ALL_TIMERS	162
10.262	DHCP_SRV_TIMERMGR_UNREGISTER_TIMER	162

**11 DHCP 163**

11.1	DHCP_DDNS_ADD_FAILED	163
11.2	DHCP_DDNS_ADD_SUCCEEDED	163
11.3	DHCP_DDNS_AT_MAX_TRANSACTIONS	163
11.4	DHCP_DDNS_CLEARED_FOR_SHUTDOWN	163
11.5	DHCP_DDNS_CONFIGURE	164
11.6	DHCP_DDNS_CONFIGURED_CALLOUT_DROP	164
11.7	DHCP_DDNS_CONFIG_CHECK_FAIL	164
11.8	DHCP_DDNS_CONFIG_FAIL	164
11.9	DHCP_DDNS_CONFIG_SYNTAX_WARNING	164
11.10	DHCP_DDNS_FAILED	164
11.11	DHCP_DDNS_FORWARD_ADD_BAD_DNSCLIENT_STATUS	165
11.12	DHCP_DDNS_FORWARD_ADD_BUILD_FAILURE	165
11.13	DHCP_DDNS_FORWARD_ADD_IO_ERROR	165
11.14	DHCP_DDNS_FORWARD_ADD_REJECTED	165
11.15	DHCP_DDNS_FORWARD_ADD_RESP_CORRUPT	165
11.16	DHCP_DDNS_FORWARD_ADD_TIMEOUT	166
11.17	DHCP_DDNS_FORWARD_REMOVE_ADDRS_BAD_DNSCLIENT_STATUS	166

11.18	DHCP_DDNS_FORWARD_REMOVE_ADDRS_BUILD_FAILURE	166
11.19	DHCP_DDNS_FORWARD_REMOVE_ADDRS_IO_ERROR	166
11.20	DHCP_DDNS_FORWARD_REMOVE_ADDRS_REJECTED	166
11.21	DHCP_DDNS_FORWARD_REMOVE_ADDRS_RESP_CORRUPT	167
11.22	DHCP_DDNS_FORWARD_REMOVE_ADDRS_TIMEOUT	167
11.23	DHCP_DDNS_FORWARD_REMOVE_RRS_BAD_DNSCLIENT_STATUS	167
11.24	DHCP_DDNS_FORWARD_REMOVE_RRS_BUILD_FAILURE	167
11.25	DHCP_DDNS_FORWARD_REMOVE_RRS_IO_ERROR	167
11.26	DHCP_DDNS_FORWARD_REMOVE_RRS_REJECTED	168
11.27	DHCP_DDNS_FORWARD_REMOVE_RRS_RESP_CORRUPT	168
11.28	DHCP_DDNS_FORWARD_REMOVE_RRS_TIMEOUT	168
11.29	DHCP_DDNS_FORWARD_REPLACE_BAD_DNSCLIENT_STATUS	168
11.30	DHCP_DDNS_FORWARD_REPLACE_BUILD_FAILURE	168
11.31	DHCP_DDNS_FORWARD_REPLACE_IO_ERROR	169
11.32	DHCP_DDNS_FORWARD_REPLACE_REJECTED	169
11.33	DHCP_DDNS_FORWARD_REPLACE_RESP_CORRUPT	169
11.34	DHCP_DDNS_FORWARD_REPLACE_TIMEOUT	169
11.35	DHCP_DDNS_FWD_REQUEST_IGNORED	169
11.36	DHCP_DDNS_INVALID_NCR	170
11.37	DHCP_DDNS_INVALID_RESPONSE	170
11.38	DHCP_DDNS_LISTENING_ON_ALL_INTERFACES	170
11.39	DHCP_DDNS_NCR_FLUSH_IO_ERROR	170
11.40	DHCP_DDNS_NCR_LISTEN_CLOSE_ERROR	170
11.41	DHCP_DDNS_NCR_RECV_NEXT_ERROR	171
11.42	DHCP_DDNS_NCR_SEND_CLOSE_ERROR	171
11.43	DHCP_DDNS_NCR_SEND_NEXT_ERROR	171
11.44	DHCP_DDNS_NCR_UDP_CLEAR_READY_ERROR	171
11.45	DHCP_DDNS_NCR_UDP_RECV_CANCELED	171
11.46	DHCP_DDNS_NCR_UDP_RECV_ERROR	172
11.47	DHCP_DDNS_NCR_UDP_SEND_CANCELED	172
11.48	DHCP_DDNS_NCR_UDP_SEND_ERROR	172
11.49	DHCP_DDNS_NOT_ON_LOOPBACK	172
11.50	DHCP_DDNS_NO_ELIGIBLE_JOBS	172
11.51	DHCP_DDNS_NO_FWD_MATCH_ERROR	173
11.52	DHCP_DDNS_NO_MATCH	173
11.53	DHCP_DDNS_NO_REV_MATCH_ERROR	173
11.54	DHCP_DDNS_QUEUE_MGR_QUEUE_FULL	173
11.55	DHCP_DDNS_QUEUE_MGR_QUEUE_RECEIVE	173
11.56	DHCP_DDNS_QUEUE_MGR_RECONFIGURING	174
11.57	DHCP_DDNS_QUEUE_MGR_RECOVERING	174
11.58	DHCP_DDNS_QUEUE_MGR_RECV_ERROR	174
11.59	DHCP_DDNS_QUEUE_MGR_RESUME_ERROR	174
11.60	DHCP_DDNS_QUEUE_MGR_RESUMING	174
11.61	DHCP_DDNS_QUEUE_MGR_STARTED	175
11.62	DHCP_DDNS_QUEUE_MGR_START_ERROR	175
11.63	DHCP_DDNS_QUEUE_MGR_STOPPED	175
11.64	DHCP_DDNS_QUEUE_MGR_STOPPING	175
11.65	DHCP_DDNS_QUEUE_MGR_STOP_ERROR	175
11.66	DHCP_DDNS_QUEUE_MGR_UNEXPECTED_HANDLER_ERROR	176
11.67	DHCP_DDNS_QUEUE_MGR_UNEXPECTED_STOP	176
11.68	DHCP_DDNS_REMOVE_FAILED	176
11.69	DHCP_DDNS_REMOVE_SUCCEEDED	176
11.70	DHCP_DDNS_REQUEST_DROPPED	176
11.71	DHCP_DDNS_REVERSE_REMOVE_BAD_DNSCLIENT_STATUS	177

11.72	DHCP_DDNS_REVERSE_REMOVE_BUILD_FAILURE	177
11.73	DHCP_DDNS_REVERSE_REMOVE_IO_ERROR	177
11.74	DHCP_DDNS_REVERSE_REMOVE_REJECTED	177
11.75	DHCP_DDNS_REVERSE_REMOVE_RESP_CORRUPT	177
11.76	DHCP_DDNS_REVERSE_REMOVE_TIMEOUT	178
11.77	DHCP_DDNS_REVERSE_REPLACE_BAD_DNSCLIENT_STATUS	178
11.78	DHCP_DDNS_REVERSE_REPLACE_BUILD_FAILURE	178
11.79	DHCP_DDNS_REVERSE_REPLACE_IO_ERROR	178
11.80	DHCP_DDNS_REVERSE_REPLACE_REJECTED	178
11.81	DHCP_DDNS_REVERSE_REPLACE_RESP_CORRUPT	179
11.82	DHCP_DDNS_REVERSE_REPLACE_TIMEOUT	179
11.83	DHCP_DDNS_REV_REQUEST_IGNORED	179
11.84	DHCP_DDNS_RUN_EXIT	179
11.85	DHCP_DDNS_SHUTDOWN_COMMAND	179
11.86	DHCP_DDNS_STARTED	180
11.87	DHCP_DDNS_STARTING_TRANSACTION	180
11.88	DHCP_DDNS_STATE_MODEL_UNEXPECTED_ERROR	180
11.89	DHCP_DDNS_TRANS_SEND_ERROR	180
11.90	DHCP_DDNS_UDP_SENDER_WATCH_SOCKET_CLOSE_ERROR	180
11.91	DHCP_DDNS_UNCAUGHT_NCR_RECV_HANDLER_ERROR	181
11.92	DHCP_DDNS_UPDATE_REQUEST_SENT	181
<b>12 EVAL</b>		<b>183</b>
12.1	EVAL_DEBUG_AND	183
12.2	EVAL_DEBUG_BRANCH	183
12.3	EVAL_DEBUG_CONCAT	183
12.4	EVAL_DEBUG_EQUAL	183
12.5	EVAL_DEBUG_HEXSTRING	184
12.6	EVAL_DEBUG_IFELSE_FALSE	184
12.7	EVAL_DEBUG_IFELSE_TRUE	184
12.8	EVAL_DEBUG_INT16TOTEXT	184
12.9	EVAL_DEBUG_INT32TOTEXT	184
12.10	EVAL_DEBUG_INT8TOTEXT	184
12.11	EVAL_DEBUG_IPADDRESS	185
12.12	EVAL_DEBUG_IPADDRESSSTOTEXT	185
12.13	EVAL_DEBUG_LCASE	185
12.14	EVAL_DEBUG_MATCH	185
12.15	EVAL_DEBUG_MATCH_ERROR	185
12.16	EVAL_DEBUG_MEMBER	185
12.17	EVAL_DEBUG_NOT	186
12.18	EVAL_DEBUG_OPTION	186
12.19	EVAL_DEBUG_OR	186
12.20	EVAL_DEBUG_PKT	186
12.21	EVAL_DEBUG_PKT4	186
12.22	EVAL_DEBUG_PKT6	187
12.23	EVAL_DEBUG_POP_AND_BRANCH_FALSE	187
12.24	EVAL_DEBUG_POP_OR_BRANCH_FALSE	187
12.25	EVAL_DEBUG_POP_OR_BRANCH_TRUE	187
12.26	EVAL_DEBUG_RELAY6	187
12.27	EVAL_DEBUG_RELAY6_RANGE	187
12.28	EVAL_DEBUG_SPLIT	188
12.29	EVAL_DEBUG_SPLIT_DELIM_EMPTY	188
12.30	EVAL_DEBUG_SPLIT_EMPTY	188
12.31	EVAL_DEBUG_SPLIT_FIELD_OUT_OF_RANGE	188

12.32	EVAL_DEBUG_STRING	188
12.33	EVAL_DEBUG_SUBSTRING	189
12.34	EVAL_DEBUG_SUBSTRING_EMPTY	189
12.35	EVAL_DEBUG_SUBSTRING_RANGE	189
12.36	EVAL_DEBUG_SUB_OPTION	189
12.37	EVAL_DEBUG_SUB_OPTION_NO_OPTION	189
12.38	EVAL_DEBUG_TOHEXSTRING	190
12.39	EVAL_DEBUG_UCASE	190
12.40	EVAL_DEBUG_UINT16TOTEXT	190
12.41	EVAL_DEBUG_UINT32TOTEXT	190
12.42	EVAL_DEBUG_UINT8TOTEXT	190
12.43	EVAL_DEBUG_VENDOR_CLASS_DATA	191
12.44	EVAL_DEBUG_VENDOR_CLASS_DATA_NOT_FOUND	191
12.45	EVAL_DEBUG_VENDOR_CLASS_ENTERPRISE_ID	191
12.46	EVAL_DEBUG_VENDOR_CLASS_ENTERPRISE_ID_MISMATCH	191
12.47	EVAL_DEBUG_VENDOR_CLASS_EXISTS	191
12.48	EVAL_DEBUG_VENDOR_CLASS_NO_OPTION	192
12.49	EVAL_DEBUG_VENDOR_ENTERPRISE_ID	192
12.50	EVAL_DEBUG_VENDOR_ENTERPRISE_ID_MISMATCH	192
12.51	EVAL_DEBUG_VENDOR_EXISTS	192
<b>13</b>	<b>FLEX</b>	<b>193</b>
13.1	FLEX_OPTION_LOAD_ERROR	193
13.2	FLEX_OPTION_PROCESS_ADD	193
13.3	FLEX_OPTION_PROCESS_CLIENT_CLASS	193
13.4	FLEX_OPTION_PROCESS_ERROR	193
13.5	FLEX_OPTION_PROCESS_REMOVE	194
13.6	FLEX_OPTION_PROCESS_SUB_ADD	194
13.7	FLEX_OPTION_PROCESS_SUB_CLIENT_CLASS	194
13.8	FLEX_OPTION_PROCESS_SUB_REMOVE	194
13.9	FLEX_OPTION_PROCESS_SUB_SUPERSEDE	194
13.10	FLEX_OPTION_PROCESS_SUPERSEDE	195
13.11	FLEX_OPTION_PROCESS_VENDOR_ID_MISMATCH	195
<b>14</b>	<b>FUZZ</b>	<b>197</b>
14.1	FUZZ_DATA_READ	197
14.2	FUZZ_INIT_COMPLETE	197
14.3	FUZZ_INIT_FAIL	197
14.4	FUZZ_READ_FAIL	197
14.5	FUZZ_SEND	198
14.6	FUZZ_SEND_ERROR	198
14.7	FUZZ_SHORT_SEND	198
<b>15</b>	<b>HA</b>	<b>199</b>
15.1	HA_BUFFER4_RECEIVE_FAILED	199
15.2	HA_BUFFER4_RECEIVE_NOT_FOR_US	199
15.3	HA_BUFFER4_RECEIVE_PACKET_OPTIONS_SKIPPED	199
15.4	HA_BUFFER4_RECEIVE_UNPACK_FAILED	199
15.5	HA_BUFFER6_RECEIVE_FAILED	200
15.6	HA_BUFFER6_RECEIVE_NOT_FOR_US	200
15.7	HA_BUFFER6_RECEIVE_PACKET_OPTIONS_SKIPPED	200
15.8	HA_BUFFER6_RECEIVE_UNPACK_FAILED	200
15.9	HA_COMMAND_PROCESSED_FAILED	200
15.10	HA_COMMUNICATION_INTERRUPTED	201

15.11 HA_COMMUNICATION_INTERRUPTED_CLIENT4	201
15.12 HA_COMMUNICATION_INTERRUPTED_CLIENT4_UNACKED	201
15.13 HA_COMMUNICATION_INTERRUPTED_CLIENT6	201
15.14 HA_COMMUNICATION_INTERRUPTED_CLIENT6_UNACKED	202
15.15 HA_CONFIGURATION_FAILED	202
15.16 HA_CONFIGURATION_SUCCESSFUL	202
15.17 HA_CONFIG_AUTO_FAILOVER_DISABLED	202
15.18 HA_CONFIG_DHCP_MT_DISABLED	202
15.19 HA_CONFIG_DHCP_MT_DISABLED_AND_KEA_MT_ENABLED	203
15.20 HA_CONFIG_LEASE_SYNCING_DISABLED	203
15.21 HA_CONFIG_LEASE_SYNCING_DISABLED_REMINDER	203
15.22 HA_CONFIG_LEASE_UPDATES_AND_SYNCING_DIFFER	203
15.23 HA_CONFIG_LEASE_UPDATES_DISABLED	203
15.24 HA_CONFIG_LEASE_UPDATES_DISABLED_REMINDER	204
15.25 HA_CONFIG_SYSTEM_MT_UNSUPPORTED	204
15.26 HA_CONTINUE_HANDLER_FAILED	204
15.27 HA_DEINIT_OK	204
15.28 HA_DHCP4_START_SERVICE_FAILED	204
15.29 HA_DHCP6_START_SERVICE_FAILED	205
15.30 HA_DHCP_DISABLE_COMMUNICATIONS_FAILED	205
15.31 HA_DHCP_DISABLE_FAILED	205
15.32 HA_DHCP_ENABLE_COMMUNICATIONS_FAILED	205
15.33 HA_DHCP_ENABLE_FAILED	205
15.34 HA_HEARTBEAT_COMMUNICATIONS_FAILED	206
15.35 HA_HEARTBEAT_FAILED	206
15.36 HA_HEARTBEAT_HANDLER_FAILED	206
15.37 HA_HIGH_CLOCK_SKEW	206
15.38 HA_HIGH_CLOCK_SKEW_CAUSED_TERMINATION	206
15.39 HA_INIT_OK	207
15.40 HA_INVALID_PARTNER_STATE_COMMUNICATION_RECOVERY	207
15.41 HA_INVALID_PARTNER_STATE_HOT_STANDBY	207
15.42 HA_INVALID_PARTNER_STATE_LOAD_BALANCING	207
15.43 HA_LEASE4_SERVER_DECLINE_FAILED	207
15.44 HA_LEASES4_COMMITTED_FAILED	208
15.45 HA_LEASES4_COMMITTED_NOHING_TO_UPDATE	208
15.46 HA_LEASES4_COMMITTED_NO_RELATIONSHIP	208
15.47 HA_LEASES6_COMMITTED_FAILED	208
15.48 HA_LEASES6_COMMITTED_NOHING_TO_UPDATE	208
15.49 HA_LEASES6_COMMITTED_NO_RELATIONSHIP	209
15.50 HA_LEASES_BACKLOG_COMMUNICATIONS_FAILED	209
15.51 HA_LEASES_BACKLOG_FAILED	209
15.52 HA_LEASES_BACKLOG_NOHING_TO_SEND	209
15.53 HA_LEASES_BACKLOG_START	209
15.54 HA_LEASES_BACKLOG_SUCCESS	210
15.55 HA_LEASES_SYNC_APPLIED_LEASES	210
15.56 HA_LEASES_SYNC_COMMUNICATIONS_FAILED	210
15.57 HA_LEASES_SYNC_FAILED	210
15.58 HA_LEASES_SYNC_LEASE_PAGE_RECEIVED	210
15.59 HA_LEASE_SYNC_FAILED	211
15.60 HA_LEASE_SYNC_STALE_LEASE4_SKIP	211
15.61 HA_LEASE_SYNC_STALE_LEASE6_SKIP	211
15.62 HA_LEASE_UPDATES_DISABLED	211
15.63 HA_LEASE_UPDATES_ENABLED	211
15.64 HA_LEASE_UPDATE_COMMUNICATIONS_FAILED	212

15.65	HA_LEASE_UPDATE_CONFLICT	212
15.66	HA_LEASE_UPDATE_CREATE_UPDATE_FAILED_ON_PEER	212
15.67	HA_LEASE_UPDATE_DELETE_FAILED_ON_PEER	212
15.68	HA_LEASE_UPDATE_FAILED	212
15.69	HA_LEASE_UPDATE_REJECTS_CAUSED_TERMINATION	213
15.70	HA_LOAD_BALANCING_DUID_MISSING	213
15.71	HA_LOAD_BALANCING_IDENTIFIER_MISSING	213
15.72	HA_LOCAL_DHCP_DISABLE	213
15.73	HA_LOCAL_DHCP_ENABLE	213
15.74	HA_MAINTENANCE_CANCEL_HANDLER_FAILED	214
15.75	HA_MAINTENANCE_NOTIFY_CANCEL_COMMUNICATIONS_FAILED	214
15.76	HA_MAINTENANCE_NOTIFY_CANCEL_FAILED	214
15.77	HA_MAINTENANCE_NOTIFY_COMMUNICATIONS_FAILED	214
15.78	HA_MAINTENANCE_NOTIFY_FAILED	214
15.79	HA_MAINTENANCE_NOTIFY_HANDLER_FAILED	215
15.80	HA_MAINTENANCE_SHUTDOWN_SAFE	215
15.81	HA_MAINTENANCE_STARTED	215
15.82	HA_MAINTENANCE_STARTED_IN_PARTNER_DOWN	215
15.83	HA_MAINTENANCE_START_HANDLER_FAILED	216
15.84	HA_MISSING_CONFIGURATION	216
15.85	HA_PAUSE_CLIENT_LISTENER_FAILED	216
15.86	HA_PAUSE_CLIENT_LISTENER_ILLEGAL	216
15.87	HA_RESET_COMMUNICATIONS_FAILED	216
15.88	HA_RESET_FAILED	217
15.89	HA_RESET_HANDLER_FAILED	217
15.90	HA_RESUME_CLIENT_LISTENER_FAILED	217
15.91	HA_SCOPES_HANDLER_FAILED	217
15.92	HA_SERVICE_STARTED	217
15.93	HA_STATE_MACHINE_CONTINUED	218
15.94	HA_STATE_MACHINE_PAUSED	218
15.95	HA_STATE_TRANSITION	218
15.96	HA_STATE_TRANSITION_PASSIVE_BACKUP	218
15.97	HA_SUBNET4_SELECT_FAILED	218
15.98	HA_SUBNET4_SELECT_INVALID_HA_SERVER_NAME	219
15.99	HA_SUBNET4_SELECT_NOT_FOR_US	219
15.100	HA_SUBNET4_SELECT_NO_RELATIONSHIP_FOR_SUBNET	219
15.101	HA_SUBNET4_SELECT_NO_RELATIONSHIP_SELECTOR_FOR_SUBNET	219
15.102	HA_SUBNET4_SELECT_NO_SUBNET_SELECTED	219
15.103	HA_SUBNET6_SELECT_FAILED	220
15.104	HA_SUBNET6_SELECT_INVALID_HA_SERVER_NAME	220
15.105	HA_SUBNET6_SELECT_NOT_FOR_US	220
15.106	HA_SUBNET6_SELECT_NO_RELATIONSHIP_FOR_SUBNET	220
15.107	HA_SUBNET6_SELECT_NO_RELATIONSHIP_SELECTOR_FOR_SUBNET	220
15.108	HA_SUBNET6_SELECT_NO_SUBNET_SELECTED	221
15.109	HA_SYNC_COMPLETE_NOTIFY_COMMUNICATIONS_FAILED	221
15.110	HA_SYNC_COMPLETE_NOTIFY_FAILED	221
15.111	HA_SYNC_COMPLETE_NOTIFY_HANDLER_FAILED	221
15.112	HA_SYNC_FAILED	221
15.113	HA_SYNC_HANDLER_FAILED	222
15.114	HA_SYNC_START	222
15.115	HA_SYNC_SUCCESSFUL	222
15.116	HA_TERMINATED	222
15.117	HA_TERMINATED_PARTNER_DID_NOT_RESTART	222

<b>16 HOOKS</b>	<b>223</b>
16.1 HOOKS_ALL_CALLOUTS_DEREGISTERED	223
16.2 HOOKS_CALLOUTS_BEGIN	223
16.3 HOOKS_CALLOUTS_COMPLETE	223
16.4 HOOKS_CALLOUTS_REMOVED	223
16.5 HOOKS_CALLOUT_CALLED	224
16.6 HOOKS_CALLOUT_DEREGISTERED	224
16.7 HOOKS_CALLOUT_ERROR	224
16.8 HOOKS_CALLOUT_EXCEPTION	224
16.9 HOOKS_CALLOUT_REGISTRATION	224
16.10 HOOKS_CLOSE_ERROR	225
16.11 HOOKS_HOOK_LIST_RESET	225
16.12 HOOKS_INCORRECT_VERSION	225
16.13 HOOKS_LIBRARY_CLOSED	225
16.14 HOOKS_LIBRARY_LOADED	225
16.15 HOOKS_LIBRARY_LOADING	226
16.16 HOOKS_LIBRARY_MULTI_THREADING_COMPATIBLE	226
16.17 HOOKS_LIBRARY_MULTI_THREADING_NOT_COMPATIBLE	226
16.18 HOOKS_LIBRARY_UNLOADED	226
16.19 HOOKS_LIBRARY_UNLOADING	226
16.20 HOOKS_LIBRARY_VERSION	226
16.21 HOOKS_LOAD_ERROR	227
16.22 HOOKS_LOAD_EXCEPTION	227
16.23 HOOKS_LOAD_FRAMEWORK_EXCEPTION	227
16.24 HOOKS_LOAD_SUCCESS	227
16.25 HOOKS_MULTI_THREADING_COMPATIBLE_EXCEPTION	227
16.26 HOOKS_NO_LOAD	228
16.27 HOOKS_NO_UNLOAD	228
16.28 HOOKS_NO_VERSION	228
16.29 HOOKS_OPEN_ERROR	228
16.30 HOOKS_STD_CALLOUT_REGISTERED	228
16.31 HOOKS_UNLOAD_ERROR	229
16.32 HOOKS_UNLOAD_EXCEPTION	229
16.33 HOOKS_UNLOAD_FRAMEWORK_EXCEPTION	229
16.34 HOOKS_UNLOAD_SUCCESS	229
<b>17 HOSTS</b>	<b>231</b>
17.1 HOSTS_BACKENDS_REGISTERED	231
17.2 HOSTS_BACKEND_DEREGISTER	231
17.3 HOSTS_BACKEND_REGISTER	231
17.4 HOSTS_CFG_ADD_HOST	231
17.5 HOSTS_CFG_CACHE_HOST_DATA_SOURCE	232
17.6 HOSTS_CFG_CLOSE_HOST_DATA_SOURCE	232
17.7 HOSTS_CFG_DEL	232
17.8 HOSTS_CFG_DEL4	232
17.9 HOSTS_CFG_DEL6	232
17.10 HOSTS_CFG_DEL_ALL_SUBNET4	233
17.11 HOSTS_CFG_DEL_ALL_SUBNET6	233
17.12 HOSTS_CFG_GET_ALL	233
17.13 HOSTS_CFG_GET_ALL_ADDRESS4	233
17.14 HOSTS_CFG_GET_ALL_ADDRESS4_COUNT	233
17.15 HOSTS_CFG_GET_ALL_ADDRESS4_HOST	234
17.16 HOSTS_CFG_GET_ALL_ADDRESS6	234
17.17 HOSTS_CFG_GET_ALL_ADDRESS6_COUNT	234

17.18	HOSTS_CFG_GET_ALL_ADDRESS6_HOST	234
17.19	HOSTS_CFG_GET_ALL_COUNT	234
17.20	HOSTS_CFG_GET_ALL_HOST	234
17.21	HOSTS_CFG_GET_ALL_HOSTNAME	235
17.22	HOSTS_CFG_GET_ALL_HOSTNAME_COUNT	235
17.23	HOSTS_CFG_GET_ALL_HOSTNAME_HOST	235
17.24	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4	235
17.25	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4_COUNT	235
17.26	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4_HOST	235
17.27	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6	236
17.28	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6_COUNT	236
17.29	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6_HOST	236
17.30	HOSTS_CFG_GET_ALL_IDENTIFIER	236
17.31	HOSTS_CFG_GET_ALL_IDENTIFIER_COUNT	236
17.32	HOSTS_CFG_GET_ALL_IDENTIFIER_HOST	236
17.33	HOSTS_CFG_GET_ALL_SUBNET_ID4	237
17.34	HOSTS_CFG_GET_ALL_SUBNET_ID4_COUNT	237
17.35	HOSTS_CFG_GET_ALL_SUBNET_ID4_HOST	237
17.36	HOSTS_CFG_GET_ALL_SUBNET_ID6	237
17.37	HOSTS_CFG_GET_ALL_SUBNET_ID6_COUNT	237
17.38	HOSTS_CFG_GET_ALL_SUBNET_ID6_HOST	237
17.39	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4	238
17.40	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4_COUNT	238
17.41	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4_HOST	238
17.42	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6	238
17.43	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6_COUNT	238
17.44	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6_HOST	239
17.45	HOSTS_CFG_GET_ONE_PREFIX	239
17.46	HOSTS_CFG_GET_ONE_PREFIX_HOST	239
17.47	HOSTS_CFG_GET_ONE_PREFIX_NULL	239
17.48	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4	239
17.49	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4_HOST	239
17.50	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4_NULL	240
17.51	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6	240
17.52	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6_HOST	240
17.53	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6_NULL	240
17.54	HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER	240
17.55	HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER_HOST	241
17.56	HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER_NULL	241
17.57	HOSTS_CFG_UPDATE_ADD	241
17.58	HOSTS_CFG_UPDATE_DEL4	241
17.59	HOSTS_CFG_UPDATE_DEL6	241
17.60	HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_ADDRESS4	242
17.61	HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER	242
17.62	HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER_HOST	242
17.63	HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER_NULL	242
17.64	HOSTS_MGR_ALTERNATE_GET6_PREFIX	242
17.65	HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_ADDRESS6	243
17.66	HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER	243
17.67	HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER_HOST	243
17.68	HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER_NULL	243
17.69	HOSTS_MGR_ALTERNATE_GET_ALL_SUBNET_ID_ADDRESS4	243
17.70	HOSTS_MGR_ALTERNATE_GET_ALL_SUBNET_ID_ADDRESS6	244



<b>18 HTTPS</b>	<b>245</b>
18.1 HTTPS_REQUEST_RECEIVE_START . . . . .	245
<b>19 HTTP</b>	<b>247</b>
19.1 HTTP_BAD_CLIENT_REQUEST_RECEIVED . . . . .	247
19.2 HTTP_BAD_CLIENT_REQUEST_RECEIVED_DETAILS . . . . .	247
19.3 HTTP_BAD_SERVER_RESPONSE_RECEIVED . . . . .	247
19.4 HTTP_BAD_SERVER_RESPONSE_RECEIVED_DETAILS . . . . .	248
19.5 HTTP_CLIENT_MT_STARTED . . . . .	248
19.6 HTTP_CLIENT_QUEUE_SIZE_GROWING . . . . .	248
19.7 HTTP_CLIENT_REQUEST_AUTHORIZED . . . . .	248
19.8 HTTP_CLIENT_REQUEST_BAD_AUTH_HEADER . . . . .	248
19.9 HTTP_CLIENT_REQUEST_NOT_AUTHORIZED . . . . .	249
19.10 HTTP_CLIENT_REQUEST_RECEIVED . . . . .	249
19.11 HTTP_CLIENT_REQUEST_RECEIVED_DETAILS . . . . .	249
19.12 HTTP_CLIENT_REQUEST_SEND . . . . .	249
19.13 HTTP_CLIENT_REQUEST_SEND_DETAILS . . . . .	249
19.14 HTTP_CLIENT_REQUEST_TIMEOUT_OCCURRED . . . . .	250
19.15 HTTP_COMMAND_MGR_IGNORED_TLS_SETUP_CHANGES . . . . .	250
19.16 HTTP_COMMAND_MGR_SERVICE_STARTED . . . . .	250
19.17 HTTP_CONNECTION_CLOSE_CALLBACK_FAILED . . . . .	250
19.18 HTTP_CONNECTION_HANDSHAKE_FAILED . . . . .	250
19.19 HTTP_CONNECTION_HANDSHAKE_START . . . . .	251
19.20 HTTP_CONNECTION_SHUTDOWN . . . . .	251
19.21 HTTP_CONNECTION_SHUTDOWN_FAILED . . . . .	251
19.22 HTTP_CONNECTION_STOP . . . . .	251
19.23 HTTP_CONNECTION_STOP_FAILED . . . . .	251
19.24 HTTP_CONNECTION_WATCH_SOCKET_CLEAR_ERROR . . . . .	251
19.25 HTTP_CONNECTION_WATCH_SOCKET_CLOSE_ERROR . . . . .	252
19.26 HTTP_CONNECTION_WATCH_SOCKET_MARK_READY_ERROR . . . . .	252
19.27 HTTP_DATA_RECEIVED . . . . .	252
19.28 HTTP_IDLE_CONNECTION_TIMEOUT_OCCURRED . . . . .	252
19.29 HTTP_PREMATURE_CONNECTION_TIMEOUT_OCCURRED . . . . .	252
19.30 HTTP_REQUEST_RECEIVE_START . . . . .	253
19.31 HTTP_SERVER_RESPONSE_RECEIVED . . . . .	253
19.32 HTTP_SERVER_RESPONSE_RECEIVED_DETAILS . . . . .	253
19.33 HTTP_SERVER_RESPONSE_SEND . . . . .	253
<b>20 LEASE</b>	<b>255</b>
20.1 LEASE_CMDS_ADD4 . . . . .	255
20.2 LEASE_CMDS_ADD4_CONFLICT . . . . .	255
20.3 LEASE_CMDS_ADD4_FAILED . . . . .	255
20.4 LEASE_CMDS_ADD6 . . . . .	255
20.5 LEASE_CMDS_ADD6_CONFLICT . . . . .	256
20.6 LEASE_CMDS_ADD6_FAILED . . . . .	256
20.7 LEASE_CMDS_BULK_APPLY6 . . . . .	256
20.8 LEASE_CMDS_BULK_APPLY6_FAILED . . . . .	256
20.9 LEASE_CMDS_DEINIT_OK . . . . .	256
20.10 LEASE_CMDS_DEL4 . . . . .	256
20.11 LEASE_CMDS_DEL4_FAILED . . . . .	257
20.12 LEASE_CMDS_DEL6 . . . . .	257
20.13 LEASE_CMDS_DEL6_FAILED . . . . .	257
20.14 LEASE_CMDS_GET4_FAILED . . . . .	257
20.15 LEASE_CMDS_GET6_FAILED . . . . .	257

20.16	LEASE_CMDS_INIT_OK	257
20.17	LEASE_CMDS_RESEND_DDNS4	258
20.18	LEASE_CMDS_RESEND_DDNS4_FAILED	258
20.19	LEASE_CMDS_RESEND_DDNS6	258
20.20	LEASE_CMDS_RESEND_DDNS6_FAILED	258
20.21	LEASE_CMDS_UPDATE4	258
20.22	LEASE_CMDS_UPDATE4_CONFLICT	258
20.23	LEASE_CMDS_UPDATE4_FAILED	259
20.24	LEASE_CMDS_UPDATE6	259
20.25	LEASE_CMDS_UPDATE6_CONFLICT	259
20.26	LEASE_CMDS_UPDATE6_FAILED	259
20.27	LEASE_CMDS_WIPE4	259
20.28	LEASE_CMDS_WIPE4_DEPRECATED	259
20.29	LEASE_CMDS_WIPE4_FAILED	260
20.30	LEASE_CMDS_WIPE6	260
20.31	LEASE_CMDS_WIPE6_DEPRECATED	260
<b>21</b>	<b>LFC</b>	<b>261</b>
21.1	LFC_FAIL_PID_CREATE	261
21.2	LFC_FAIL_PID_DEL	261
21.3	LFC_FAIL_PROCESS	261
21.4	LFC_FAIL_ROTATE	261
21.5	LFC_PROCESSING	262
21.6	LFC_READ_STATS	262
21.7	LFC_ROTATING	262
21.8	LFC_RUNNING	262
21.9	LFC_START	262
21.10	LFC_TERMINATE	262
<b>22</b>	<b>LOGIMPL</b>	<b>263</b>
22.1	LOGIMPL_ABOVE_MAX_DEBUG	263
22.2	LOGIMPL_BAD_DEBUG_STRING	263
<b>23</b>	<b>LOG</b>	<b>265</b>
23.1	LOG_BAD_DESTINATION	265
23.2	LOG_BAD_SEVERITY	265
23.3	LOG_BAD_STREAM	265
23.4	LOG_DUPLICATE_MESSAGE_ID	265
23.5	LOG_DUPLICATE_NAMESPACE	266
23.6	LOG_INPUT_OPEN_FAIL	266
23.7	LOG_INVALID_MESSAGE_ID	266
23.8	LOG_NAMESPACE_EXTRA_ARGS	266
23.9	LOG_NAMESPACE_INVALID_ARG	266
23.10	LOG_NAMESPACE_NO_ARGS	267
23.11	LOG_NO_MESSAGE_ID	267
23.12	LOG_NO_MESSAGE_TEXT	267
23.13	LOG_NO_SUCH_MESSAGE	267
23.14	LOG_OPEN_OUTPUT_FAIL	267
23.15	LOG_PREFIX_EXTRA_ARGS	268
23.16	LOG_PREFIX_INVALID_ARG	268
23.17	LOG_READING_LOCAL_FILE	268
23.18	LOG_READ_ERROR	268
23.19	LOG_UNRECOGNIZED_DIRECTIVE	268
<b>24</b>	<b>MT</b>	<b>269</b>

24.1	MT_TCP_LISTENER_MGR_STARTED	269
24.2	MT_TCP_LISTENER_MGR_STOPPED	269
24.3	MT_TCP_LISTENER_MGR_STOPPING	269
<b>25</b>	<b>MYSQL</b>	<b>271</b>
25.1	MYSQL_CB_CREATE_UPDATE_BY_POOL_OPTION4	271
25.2	MYSQL_CB_CREATE_UPDATE_BY_POOL_OPTION6	271
25.3	MYSQL_CB_CREATE_UPDATE_BY_PREFIX_OPTION6	271
25.4	MYSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION4	271
25.5	MYSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION6	272
25.6	MYSQL_CB_CREATE_UPDATE_CLIENT_CLASS4	272
25.7	MYSQL_CB_CREATE_UPDATE_CLIENT_CLASS6	272
25.8	MYSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER4	272
25.9	MYSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER6	272
25.10	MYSQL_CB_CREATE_UPDATE_OPTION4	272
25.11	MYSQL_CB_CREATE_UPDATE_OPTION6	273
25.12	MYSQL_CB_CREATE_UPDATE_OPTION_DEF4	273
25.13	MYSQL_CB_CREATE_UPDATE_OPTION_DEF6	273
25.14	MYSQL_CB_CREATE_UPDATE_SERVER4	273
25.15	MYSQL_CB_CREATE_UPDATE_SERVER6	273
25.16	MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK4	273
25.17	MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK6	274
25.18	MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION4	274
25.19	MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION6	274
25.20	MYSQL_CB_CREATE_UPDATE_SUBNET4	274
25.21	MYSQL_CB_CREATE_UPDATE_SUBNET6	274
25.22	MYSQL_CB_DEINIT_OK	274
25.23	MYSQL_CB_DELETE_ALL_CLIENT_CLASSES4	275
25.24	MYSQL_CB_DELETE_ALL_CLIENT_CLASSES4_RESULT	275
25.25	MYSQL_CB_DELETE_ALL_CLIENT_CLASSES6	275
25.26	MYSQL_CB_DELETE_ALL_CLIENT_CLASSES6_RESULT	275
25.27	MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4	275
25.28	MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4_RESULT	275
25.29	MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6	276
25.30	MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6_RESULT	276
25.31	MYSQL_CB_DELETE_ALL_OPTION_DEFS4	276
25.32	MYSQL_CB_DELETE_ALL_OPTION_DEFS4_RESULT	276
25.33	MYSQL_CB_DELETE_ALL_OPTION_DEFS6	276
25.34	MYSQL_CB_DELETE_ALL_OPTION_DEFS6_RESULT	276
25.35	MYSQL_CB_DELETE_ALL_SERVERS4	277
25.36	MYSQL_CB_DELETE_ALL_SERVERS4_RESULT	277
25.37	MYSQL_CB_DELETE_ALL_SERVERS6	277
25.38	MYSQL_CB_DELETE_ALL_SERVERS6_RESULT	277
25.39	MYSQL_CB_DELETE_ALL_SHARED_NETWORKS4	277
25.40	MYSQL_CB_DELETE_ALL_SHARED_NETWORKS4_RESULT	277
25.41	MYSQL_CB_DELETE_ALL_SHARED_NETWORKS6	278
25.42	MYSQL_CB_DELETE_ALL_SHARED_NETWORKS6_RESULT	278
25.43	MYSQL_CB_DELETE_ALL_SUBNETS4	278
25.44	MYSQL_CB_DELETE_ALL_SUBNETS4_RESULT	278
25.45	MYSQL_CB_DELETE_ALL_SUBNETS6	278
25.46	MYSQL_CB_DELETE_ALL_SUBNETS6_RESULT	278
25.47	MYSQL_CB_DELETE_BY_POOL_OPTION4	279
25.48	MYSQL_CB_DELETE_BY_POOL_OPTION4_RESULT	279
25.49	MYSQL_CB_DELETE_BY_POOL_OPTION6	279

25.50	MYSQL_CB_DELETE_BY_POOL_OPTION6_RESULT	279
25.51	MYSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6	279
25.52	MYSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6_RESULT	279
25.53	MYSQL_CB_DELETE_BY_PREFIX_SUBNET4	280
25.54	MYSQL_CB_DELETE_BY_PREFIX_SUBNET4_RESULT	280
25.55	MYSQL_CB_DELETE_BY_PREFIX_SUBNET6	280
25.56	MYSQL_CB_DELETE_BY_PREFIX_SUBNET6_RESULT	280
25.57	MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION4	280
25.58	MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION4_RESULT	280
25.59	MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION6	281
25.60	MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION6_RESULT	281
25.61	MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4	281
25.62	MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4_RESULT	281
25.63	MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6	281
25.64	MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6_RESULT	281
25.65	MYSQL_CB_DELETE_CLIENT_CLASS4	282
25.66	MYSQL_CB_DELETE_CLIENT_CLASS4_RESULT	282
25.67	MYSQL_CB_DELETE_CLIENT_CLASS6	282
25.68	MYSQL_CB_DELETE_CLIENT_CLASS6_RESULT	282
25.69	MYSQL_CB_DELETE_GLOBAL_PARAMETER4	282
25.70	MYSQL_CB_DELETE_GLOBAL_PARAMETER4_RESULT	282
25.71	MYSQL_CB_DELETE_GLOBAL_PARAMETER6	283
25.72	MYSQL_CB_DELETE_GLOBAL_PARAMETER6_RESULT	283
25.73	MYSQL_CB_DELETE_OPTION4	283
25.74	MYSQL_CB_DELETE_OPTION4_RESULT	283
25.75	MYSQL_CB_DELETE_OPTION6	283
25.76	MYSQL_CB_DELETE_OPTION6_RESULT	283
25.77	MYSQL_CB_DELETE_OPTION_DEF4	284
25.78	MYSQL_CB_DELETE_OPTION_DEF4_RESULT	284
25.79	MYSQL_CB_DELETE_OPTION_DEF6	284
25.80	MYSQL_CB_DELETE_OPTION_DEF6_RESULT	284
25.81	MYSQL_CB_DELETE_SERVER4	284
25.82	MYSQL_CB_DELETE_SERVER4_RESULT	284
25.83	MYSQL_CB_DELETE_SERVER6	285
25.84	MYSQL_CB_DELETE_SERVER6_RESULT	285
25.85	MYSQL_CB_DELETE_SHARED_NETWORK4	285
25.86	MYSQL_CB_DELETE_SHARED_NETWORK4_RESULT	285
25.87	MYSQL_CB_DELETE_SHARED_NETWORK6	285
25.88	MYSQL_CB_DELETE_SHARED_NETWORK6_RESULT	285
25.89	MYSQL_CB_DELETE_SHARED_NETWORK_OPTION4	286
25.90	MYSQL_CB_DELETE_SHARED_NETWORK_OPTION4_RESULT	286
25.91	MYSQL_CB_DELETE_SHARED_NETWORK_OPTION6	286
25.92	MYSQL_CB_DELETE_SHARED_NETWORK_OPTION6_RESULT	286
25.93	MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4	286
25.94	MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	286
25.95	MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6	287
25.96	MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT	287
25.97	MYSQL_CB_GET_ALL_CLIENT_CLASSES4	287
25.98	MYSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT	287
25.99	MYSQL_CB_GET_ALL_CLIENT_CLASSES6	287
25.100	MYSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT	287
25.101	MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS4	288
25.102	MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT	288
25.103	MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS6	288

25.104	MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT	288
25.105	MYSQL_CB_GET_ALL_OPTIONS4	288
25.106	MYSQL_CB_GET_ALL_OPTIONS4_RESULT	288
25.107	MYSQL_CB_GET_ALL_OPTIONS6	289
25.108	MYSQL_CB_GET_ALL_OPTIONS6_RESULT	289
25.109	MYSQL_CB_GET_ALL_OPTION_DEFS4	289
25.110	MYSQL_CB_GET_ALL_OPTION_DEFS4_RESULT	289
25.111	MYSQL_CB_GET_ALL_OPTION_DEFS6	289
25.112	MYSQL_CB_GET_ALL_OPTION_DEFS6_RESULT	289
25.113	MYSQL_CB_GET_ALL_SERVERS4	290
25.114	MYSQL_CB_GET_ALL_SERVERS4_RESULT	290
25.115	MYSQL_CB_GET_ALL_SERVERS6	290
25.116	MYSQL_CB_GET_ALL_SERVERS6_RESULT	290
25.117	MYSQL_CB_GET_ALL_SHARED_NETWORKS4	290
25.118	MYSQL_CB_GET_ALL_SHARED_NETWORKS4_RESULT	290
25.119	MYSQL_CB_GET_ALL_SHARED_NETWORKS6	291
25.120	MYSQL_CB_GET_ALL_SHARED_NETWORKS6_RESULT	291
25.121	MYSQL_CB_GET_ALL_SUBNETS4	291
25.122	MYSQL_CB_GET_ALL_SUBNETS4_RESULT	291
25.123	MYSQL_CB_GET_ALL_SUBNETS6	291
25.124	MYSQL_CB_GET_ALL_SUBNETS6_RESULT	291
25.125	MYSQL_CB_GET_CLIENT_CLASS4	292
25.126	MYSQL_CB_GET_CLIENT_CLASS6	292
25.127	MYSQL_CB_GET_GLOBAL_PARAMETER4	292
25.128	MYSQL_CB_GET_GLOBAL_PARAMETER6	292
25.129	MYSQL_CB_GET_HOST4	292
25.130	MYSQL_CB_GET_HOST6	292
25.131	MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES4	293
25.132	MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES4_RESULT	293
25.133	MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES6	293
25.134	MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES6_RESULT	293
25.135	MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4	293
25.136	MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4_RESULT	293
25.137	MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6	294
25.138	MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6_RESULT	294
25.139	MYSQL_CB_GET_MODIFIED_OPTIONS4	294
25.140	MYSQL_CB_GET_MODIFIED_OPTIONS4_RESULT	294
25.141	MYSQL_CB_GET_MODIFIED_OPTIONS6	294
25.142	MYSQL_CB_GET_MODIFIED_OPTIONS6_RESULT	294
25.143	MYSQL_CB_GET_MODIFIED_OPTION_DEFS4	295
25.144	MYSQL_CB_GET_MODIFIED_OPTION_DEFS4_RESULT	295
25.145	MYSQL_CB_GET_MODIFIED_OPTION_DEFS6	295
25.146	MYSQL_CB_GET_MODIFIED_OPTION_DEFS6_RESULT	295
25.147	MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS4	295
25.148	MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS4_RESULT	295
25.149	MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS6	296
25.150	MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS6_RESULT	296
25.151	MYSQL_CB_GET_MODIFIED_SUBNETS4	296
25.152	MYSQL_CB_GET_MODIFIED_SUBNETS4_RESULT	296
25.153	MYSQL_CB_GET_MODIFIED_SUBNETS6	296
25.154	MYSQL_CB_GET_MODIFIED_SUBNETS6_RESULT	296
25.155	MYSQL_CB_GET_OPTION4	297
25.156	MYSQL_CB_GET_OPTION6	297
25.157	MYSQL_CB_GET_OPTION_DEF4	297

25.158	MYSQL_CB_GET_OPTION_DEF6	297
25.159	MYSQL_CB_GET_PORT4	297
25.160	MYSQL_CB_GET_PORT6	297
25.161	MYSQL_CB_GET_RECENT_AUDIT_ENTRIES4	298
25.162	MYSQL_CB_GET_RECENT_AUDIT_ENTRIES4_RESULT	298
25.163	MYSQL_CB_GET_RECENT_AUDIT_ENTRIES6	298
25.164	MYSQL_CB_GET_RECENT_AUDIT_ENTRIES6_RESULT	298
25.165	MYSQL_CB_GET_SERVER4	298
25.166	MYSQL_CB_GET_SERVER6	298
25.167	MYSQL_CB_GET_SHARED_NETWORK4	299
25.168	MYSQL_CB_GET_SHARED_NETWORK6	299
25.169	MYSQL_CB_GET_SHARED_NETWORK_SUBNETS4	299
25.170	MYSQL_CB_GET_SHARED_NETWORK_SUBNETS4_RESULT	299
25.171	MYSQL_CB_GET_SHARED_NETWORK_SUBNETS6	299
25.172	MYSQL_CB_GET_SHARED_NETWORK_SUBNETS6_RESULT	299
25.173	MYSQL_CB_GET_SUBNET4_BY_PREFIX	300
25.174	MYSQL_CB_GET_SUBNET4_BY_SUBNET_ID	300
25.175	MYSQL_CB_GET_SUBNET6_BY_PREFIX	300
25.176	MYSQL_CB_GET_SUBNET6_BY_SUBNET_ID	300
25.177	MYSQL_CB_GET_TYPE4	300
25.178	MYSQL_CB_GET_TYPE6	300
25.179	MYSQL_CB_INIT_OK	301
25.180	MYSQL_CB_NO_TLS	301
25.181	MYSQL_CB_RECONNECT_ATTEMPT_FAILED4	301
25.182	MYSQL_CB_RECONNECT_ATTEMPT_FAILED6	301
25.183	MYSQL_CB_RECONNECT_ATTEMPT_SCHEDULE4	301
25.184	MYSQL_CB_RECONNECT_ATTEMPT_SCHEDULE6	301
25.185	MYSQL_CB_RECONNECT_FAILED4	302
25.186	MYSQL_CB_RECONNECT_FAILED6	302
25.187	MYSQL_CB_REGISTER_BACKEND_TYPE4	302
25.188	MYSQL_CB_REGISTER_BACKEND_TYPE6	302
25.189	MYSQL_CB_TLS_CIPHER	302
25.190	MYSQL_CB_UNREGISTER_BACKEND_TYPE4	302
<b>26</b>	<b>NETCONF</b>	<b>303</b>
26.1	NETCONF_BOOT_UPDATE_COMPLETED	303
26.2	NETCONF_CONFIG_CHANGED_DETAIL	303
26.3	NETCONF_CONFIG_CHANGE_EVENT	303
26.4	NETCONF_CONFIG_CHECK_FAIL	303
26.5	NETCONF_CONFIG_FAIL	304
26.6	NETCONF_CONFIG_SYNTAX_WARNING	304
26.7	NETCONF_FAILED	304
26.8	NETCONF_GET_CONFIG	304
26.9	NETCONF_GET_CONFIG_FAILED	304
26.10	NETCONF_GET_CONFIG_STARTED	304
26.11	NETCONF_MODULE_CHANGE_INTERNAL_ERROR	305
26.12	NETCONF_MODULE_MISSING_ERR	305
26.13	NETCONF_MODULE_MISSING_WARN	305
26.14	NETCONF_MODULE_REVISION_ERR	305
26.15	NETCONF_MODULE_REVISION_WARN	305
26.16	NETCONF_NOTIFICATION_INTERNAL_ERROR	306
26.17	NETCONF_NOTIFICATION_RECEIVED	306
26.18	NETCONF_NOT_SUBSCRIBED_TO_NOTIFICATIONS	306
26.19	NETCONF_RUN_EXIT	306

26.20	NETCONF_SET_CONFIG	306
26.21	NETCONF_SET_CONFIG_FAILED	307
26.22	NETCONF_SET_CONFIG_STARTED	307
26.23	NETCONF_STARTED	307
26.24	NETCONF_SUBSCRIBE_CONFIG	307
26.25	NETCONF_SUBSCRIBE_CONFIG_FAILED	307
26.26	NETCONF_SUBSCRIBE_NOTIFICATIONS	307
26.27	NETCONF_UPDATE_CONFIG	308
26.28	NETCONF_UPDATE_CONFIG_COMPLETED	308
26.29	NETCONF_UPDATE_CONFIG_FAILED	308
26.30	NETCONF_UPDATE_CONFIG_STARTED	308
26.31	NETCONF_VALIDATE_CONFIG	308
26.32	NETCONF_VALIDATE_CONFIG_COMPLETED	308
26.33	NETCONF_VALIDATE_CONFIG_FAILED	309
26.34	NETCONF_VALIDATE_CONFIG_REJECTED	309
<b>27</b>	<b>PERFMON</b>	<b>311</b>
27.1	PERFMON_ALARM_CLEARED	311
27.2	PERFMON_ALARM_TRIGGERED	311
27.3	PERFMON_CMDS_CONTROL_ERROR	311
27.4	PERFMON_CMDS_CONTROL_OK	311
27.5	PERFMON_CMDS_GET_ALL_DURATIONS_ERROR	312
27.6	PERFMON_CMDS_GET_ALL_DURATIONS_OK	312
27.7	PERFMON_DEINIT_OK	312
27.8	PERFMON_DHCP4_PKT_EVENTS	312
27.9	PERFMON_DHCP4_PKT_PROCESS_ERROR	312
27.10	PERFMON_DHCP4_SOCKET_RECEIVED_TIME_SUPPORT	312
27.11	PERFMON_DHCP6_PKT_EVENTS	313
27.12	PERFMON_DHCP6_PKT_PROCESS_ERROR	313
27.13	PERFMON_DHCP6_SOCKET_RECEIVED_TIME_SUPPORT	313
27.14	PERFMON_INIT_FAILED	313
<b>28</b>	<b>PGSQL</b>	<b>315</b>
28.1	PGSQL_CB_CREATE_UPDATE_BY_POOL_OPTION4	315
28.2	PGSQL_CB_CREATE_UPDATE_BY_POOL_OPTION6	315
28.3	PGSQL_CB_CREATE_UPDATE_BY_PREFIX_OPTION6	315
28.4	PGSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION4	315
28.5	PGSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION6	316
28.6	PGSQL_CB_CREATE_UPDATE_CLIENT_CLASS4	316
28.7	PGSQL_CB_CREATE_UPDATE_CLIENT_CLASS6	316
28.8	PGSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER4	316
28.9	PGSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER6	316
28.10	PGSQL_CB_CREATE_UPDATE_OPTION4	316
28.11	PGSQL_CB_CREATE_UPDATE_OPTION6	317
28.12	PGSQL_CB_CREATE_UPDATE_OPTION_DEF4	317
28.13	PGSQL_CB_CREATE_UPDATE_OPTION_DEF6	317
28.14	PGSQL_CB_CREATE_UPDATE_SERVER4	317
28.15	PGSQL_CB_CREATE_UPDATE_SERVER6	317
28.16	PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK4	317
28.17	PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK6	318
28.18	PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION4	318
28.19	PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION6	318
28.20	PGSQL_CB_CREATE_UPDATE_SUBNET4	318
28.21	PGSQL_CB_CREATE_UPDATE_SUBNET6	318

28.22 PGSQL_CB_DEINIT_OK . . . . .	318
28.23 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES4 . . . . .	319
28.24 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES4_RESULT . . . . .	319
28.25 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES6 . . . . .	319
28.26 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES6_RESULT . . . . .	319
28.27 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4 . . . . .	319
28.28 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4_RESULT . . . . .	319
28.29 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6 . . . . .	320
28.30 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6_RESULT . . . . .	320
28.31 PGSQL_CB_DELETE_ALL_OPTION_DEFS4 . . . . .	320
28.32 PGSQL_CB_DELETE_ALL_OPTION_DEFS4_RESULT . . . . .	320
28.33 PGSQL_CB_DELETE_ALL_OPTION_DEFS6 . . . . .	320
28.34 PGSQL_CB_DELETE_ALL_OPTION_DEFS6_RESULT . . . . .	320
28.35 PGSQL_CB_DELETE_ALL_SERVERS4 . . . . .	321
28.36 PGSQL_CB_DELETE_ALL_SERVERS4_RESULT . . . . .	321
28.37 PGSQL_CB_DELETE_ALL_SERVERS6 . . . . .	321
28.38 PGSQL_CB_DELETE_ALL_SERVERS6_RESULT . . . . .	321
28.39 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS4 . . . . .	321
28.40 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS4_RESULT . . . . .	321
28.41 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS6 . . . . .	322
28.42 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS6_RESULT . . . . .	322
28.43 PGSQL_CB_DELETE_ALL_SUBNETS4 . . . . .	322
28.44 PGSQL_CB_DELETE_ALL_SUBNETS4_RESULT . . . . .	322
28.45 PGSQL_CB_DELETE_ALL_SUBNETS6 . . . . .	322
28.46 PGSQL_CB_DELETE_ALL_SUBNETS6_RESULT . . . . .	322
28.47 PGSQL_CB_DELETE_BY_POOL_OPTION4 . . . . .	323
28.48 PGSQL_CB_DELETE_BY_POOL_OPTION4_RESULT . . . . .	323
28.49 PGSQL_CB_DELETE_BY_POOL_OPTION6 . . . . .	323
28.50 PGSQL_CB_DELETE_BY_POOL_OPTION6_RESULT . . . . .	323
28.51 PGSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6 . . . . .	323
28.52 PGSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6_RESULT . . . . .	323
28.53 PGSQL_CB_DELETE_BY_PREFIX_SUBNET4 . . . . .	324
28.54 PGSQL_CB_DELETE_BY_PREFIX_SUBNET4_RESULT . . . . .	324
28.55 PGSQL_CB_DELETE_BY_PREFIX_SUBNET6 . . . . .	324
28.56 PGSQL_CB_DELETE_BY_PREFIX_SUBNET6_RESULT . . . . .	324
28.57 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION4 . . . . .	324
28.58 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION4_RESULT . . . . .	324
28.59 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION6 . . . . .	325
28.60 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION6_RESULT . . . . .	325
28.61 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4 . . . . .	325
28.62 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4_RESULT . . . . .	325
28.63 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6 . . . . .	325
28.64 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6_RESULT . . . . .	325
28.65 PGSQL_CB_DELETE_CLIENT_CLASS4 . . . . .	326
28.66 PGSQL_CB_DELETE_CLIENT_CLASS4_RESULT . . . . .	326
28.67 PGSQL_CB_DELETE_CLIENT_CLASS6 . . . . .	326
28.68 PGSQL_CB_DELETE_CLIENT_CLASS6_RESULT . . . . .	326
28.69 PGSQL_CB_DELETE_GLOBAL_PARAMETER4 . . . . .	326
28.70 PGSQL_CB_DELETE_GLOBAL_PARAMETER4_RESULT . . . . .	326
28.71 PGSQL_CB_DELETE_GLOBAL_PARAMETER6 . . . . .	327
28.72 PGSQL_CB_DELETE_GLOBAL_PARAMETER6_RESULT . . . . .	327
28.73 PGSQL_CB_DELETE_OPTION4 . . . . .	327
28.74 PGSQL_CB_DELETE_OPTION4_RESULT . . . . .	327
28.75 PGSQL_CB_DELETE_OPTION6 . . . . .	327



28.76	PGSQL_CB_DELETE_OPTION6_RESULT	327
28.77	PGSQL_CB_DELETE_OPTION_DEF4	328
28.78	PGSQL_CB_DELETE_OPTION_DEF4_RESULT	328
28.79	PGSQL_CB_DELETE_OPTION_DEF6	328
28.80	PGSQL_CB_DELETE_OPTION_DEF6_RESULT	328
28.81	PGSQL_CB_DELETE_SERVER4	328
28.82	PGSQL_CB_DELETE_SERVER4_RESULT	328
28.83	PGSQL_CB_DELETE_SERVER6	329
28.84	PGSQL_CB_DELETE_SERVER6_RESULT	329
28.85	PGSQL_CB_DELETE_SHARED_NETWORK4	329
28.86	PGSQL_CB_DELETE_SHARED_NETWORK4_RESULT	329
28.87	PGSQL_CB_DELETE_SHARED_NETWORK6	329
28.88	PGSQL_CB_DELETE_SHARED_NETWORK6_RESULT	329
28.89	PGSQL_CB_DELETE_SHARED_NETWORK_OPTION4	330
28.90	PGSQL_CB_DELETE_SHARED_NETWORK_OPTION4_RESULT	330
28.91	PGSQL_CB_DELETE_SHARED_NETWORK_OPTION6	330
28.92	PGSQL_CB_DELETE_SHARED_NETWORK_OPTION6_RESULT	330
28.93	PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4	330
28.94	PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	330
28.95	PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6	331
28.96	PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT	331
28.97	PGSQL_CB_GET_ALL_CLIENT_CLASSES4	331
28.98	PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT	331
28.99	PGSQL_CB_GET_ALL_CLIENT_CLASSES6	331
28.100	PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT	331
28.101	PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4	332
28.102	PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT	332
28.103	PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6	332
28.104	PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT	332
28.105	PGSQL_CB_GET_ALL_OPTIONS4	332
28.106	PGSQL_CB_GET_ALL_OPTIONS4_RESULT	332
28.107	PGSQL_CB_GET_ALL_OPTIONS6	333
28.108	PGSQL_CB_GET_ALL_OPTIONS6_RESULT	333
28.109	PGSQL_CB_GET_ALL_OPTION_DEFS4	333
28.110	PGSQL_CB_GET_ALL_OPTION_DEFS4_RESULT	333
28.111	PGSQL_CB_GET_ALL_OPTION_DEFS6	333
28.112	PGSQL_CB_GET_ALL_OPTION_DEFS6_RESULT	333
28.113	PGSQL_CB_GET_ALL_SERVERS4	334
28.114	PGSQL_CB_GET_ALL_SERVERS4_RESULT	334
28.115	PGSQL_CB_GET_ALL_SERVERS6	334
28.116	PGSQL_CB_GET_ALL_SERVERS6_RESULT	334
28.117	PGSQL_CB_GET_ALL_SHARED_NETWORKS4	334
28.118	PGSQL_CB_GET_ALL_SHARED_NETWORKS4_RESULT	334
28.119	PGSQL_CB_GET_ALL_SHARED_NETWORKS6	335
28.120	PGSQL_CB_GET_ALL_SHARED_NETWORKS6_RESULT	335
28.121	PGSQL_CB_GET_ALL_SUBNETS4	335
28.122	PGSQL_CB_GET_ALL_SUBNETS4_RESULT	335
28.123	PGSQL_CB_GET_ALL_SUBNETS6	335
28.124	PGSQL_CB_GET_ALL_SUBNETS6_RESULT	335
28.125	PGSQL_CB_GET_CLIENT_CLASS4	336
28.126	PGSQL_CB_GET_CLIENT_CLASS6	336
28.127	PGSQL_CB_GET_GLOBAL_PARAMETER4	336
28.128	PGSQL_CB_GET_GLOBAL_PARAMETER6	336
28.129	PGSQL_CB_GET_HOST4	336

28.130	PGSQL_CB_GET_HOST6	336
28.131	PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES4	337
28.132	PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES4_RESULT	337
28.133	PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES6	337
28.134	PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES6_RESULT	337
28.135	PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4	337
28.136	PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4_RESULT	337
28.137	PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6	338
28.138	PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6_RESULT	338
28.139	PGSQL_CB_GET_MODIFIED_OPTIONS4	338
28.140	PGSQL_CB_GET_MODIFIED_OPTIONS4_RESULT	338
28.141	PGSQL_CB_GET_MODIFIED_OPTIONS6	338
28.142	PGSQL_CB_GET_MODIFIED_OPTIONS6_RESULT	338
28.143	PGSQL_CB_GET_MODIFIED_OPTION_DEFS4	339
28.144	PGSQL_CB_GET_MODIFIED_OPTION_DEFS4_RESULT	339
28.145	PGSQL_CB_GET_MODIFIED_OPTION_DEFS6	339
28.146	PGSQL_CB_GET_MODIFIED_OPTION_DEFS6_RESULT	339
28.147	PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS4	339
28.148	PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS4_RESULT	339
28.149	PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS6	340
28.150	PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS6_RESULT	340
28.151	PGSQL_CB_GET_MODIFIED_SUBNETS4	340
28.152	PGSQL_CB_GET_MODIFIED_SUBNETS4_RESULT	340
28.153	PGSQL_CB_GET_MODIFIED_SUBNETS6	340
28.154	PGSQL_CB_GET_MODIFIED_SUBNETS6_RESULT	340
28.155	PGSQL_CB_GET_OPTION4	341
28.156	PGSQL_CB_GET_OPTION6	341
28.157	PGSQL_CB_GET_OPTION_DEF4	341
28.158	PGSQL_CB_GET_OPTION_DEF6	341
28.159	PGSQL_CB_GET_PORT4	341
28.160	PGSQL_CB_GET_PORT6	341
28.161	PGSQL_CB_GET_RECENT_AUDIT_ENTRIES4	342
28.162	PGSQL_CB_GET_RECENT_AUDIT_ENTRIES4_RESULT	342
28.163	PGSQL_CB_GET_RECENT_AUDIT_ENTRIES6	342
28.164	PGSQL_CB_GET_RECENT_AUDIT_ENTRIES6_RESULT	342
28.165	PGSQL_CB_GET_SERVER4	342
28.166	PGSQL_CB_GET_SERVER6	342
28.167	PGSQL_CB_GET_SHARED_NETWORK4	343
28.168	PGSQL_CB_GET_SHARED_NETWORK6	343
28.169	PGSQL_CB_GET_SHARED_NETWORK_SUBNETS4	343
28.170	PGSQL_CB_GET_SHARED_NETWORK_SUBNETS4_RESULT	343
28.171	PGSQL_CB_GET_SHARED_NETWORK_SUBNETS6	343
28.172	PGSQL_CB_GET_SHARED_NETWORK_SUBNETS6_RESULT	343
28.173	PGSQL_CB_GET_SUBNET4_BY_PREFIX	344
28.174	PGSQL_CB_GET_SUBNET4_BY_SUBNET_ID	344
28.175	PGSQL_CB_GET_SUBNET6_BY_PREFIX	344
28.176	PGSQL_CB_GET_SUBNET6_BY_SUBNET_ID	344
28.177	PGSQL_CB_GET_TYPE4	344
28.178	PGSQL_CB_GET_TYPE6	344
28.179	PGSQL_CB_INIT_OK	345
28.180	PGSQL_CB_NO_TLS_SUPPORT	345
28.181	PGSQL_CB_RECONNECT_ATTEMPT_FAILED4	345
28.182	PGSQL_CB_RECONNECT_ATTEMPT_FAILED6	345
28.183	PGSQL_CB_RECONNECT_ATTEMPT_SCHEDULE4	345

28.184	PGSQL_CB_RECONNECT_ATTEMPT_SCHEDULE6 . . . . .	345
28.185	PGSQL_CB_RECONNECT_FAILED4 . . . . .	346
28.186	PGSQL_CB_RECONNECT_FAILED6 . . . . .	346
28.187	PGSQL_CB_REGISTER_BACKEND_TYPE4 . . . . .	346
28.188	PGSQL_CB_REGISTER_BACKEND_TYPE6 . . . . .	346
28.189	PGSQL_CB_TLS_SUPPORT . . . . .	346
28.190	PGSQL_CB_UNREGISTER_BACKEND_TYPE4 . . . . .	346
<b>29</b>	<b>RUN</b>	<b>347</b>
29.1	RUN_SCRIPT_LOAD . . . . .	347
29.2	RUN_SCRIPT_LOAD_ERROR . . . . .	347
<b>30</b>	<b>STAT</b>	<b>349</b>
30.1	STAT_CMDS_DEINIT_OK . . . . .	349
30.2	STAT_CMDS_INIT_OK . . . . .	349
30.3	STAT_CMDS_LEASE4_FAILED . . . . .	349
30.4	STAT_CMDS_LEASE4_GET . . . . .	349
30.5	STAT_CMDS_LEASE4_GET_FAILED . . . . .	350
30.6	STAT_CMDS_LEASE4_GET_INVALID . . . . .	350
30.7	STAT_CMDS_LEASE4_GET_NO_SUBNETS . . . . .	350
30.8	STAT_CMDS_LEASE4_ORPHANED_STATS . . . . .	350
30.9	STAT_CMDS_LEASE6_FAILED . . . . .	350
30.10	STAT_CMDS_LEASE6_GET . . . . .	351
30.11	STAT_CMDS_LEASE6_GET_FAILED . . . . .	351
30.12	STAT_CMDS_LEASE6_GET_INVALID . . . . .	351
30.13	STAT_CMDS_LEASE6_GET_NO_SUBNETS . . . . .	351
<b>31</b>	<b>TCP</b>	<b>353</b>
31.1	TCP_CLIENT_REQUEST_RECEIVED . . . . .	353
31.2	TCP_CONNECTION_REJECTED_BY_FILTER . . . . .	353
31.3	TCP_CONNECTION_SHUTDOWN . . . . .	353
31.4	TCP_CONNECTION_SHUTDOWN_FAILED . . . . .	353
31.5	TCP_CONNECTION_STOP . . . . .	354
31.6	TCP_CONNECTION_STOP_FAILED . . . . .	354
31.7	TCP_DATA_RECEIVED . . . . .	354
31.8	TCP_DATA_SENT . . . . .	354
31.9	TCP_IDLE_CONNECTION_TIMEOUT_OCCURRED . . . . .	354
31.10	TCP_REQUEST_RECEIVED_FAILED . . . . .	355
31.11	TCP_REQUEST_RECEIVE_START . . . . .	355
31.12	TCP_SERVER_RESPONSE_SEND . . . . .	355
<b>32</b>	<b>TLS</b>	<b>357</b>
32.1	TLS_CONNECTION_HANDSHAKE_FAILED . . . . .	357
32.2	TLS_CONNECTION_HANDSHAKE_START . . . . .	357
32.3	TLS_REQUEST_RECEIVE_START . . . . .	357
<b>33</b>	<b>USER</b>	<b>359</b>
33.1	USER_CHK_HOOK_LOAD_ERROR . . . . .	359
33.2	USER_CHK_HOOK_UNLOAD_ERROR . . . . .	359
33.3	USER_CHK_SUBNET4_SELECT_ERROR . . . . .	359
33.4	USER_CHK_SUBNET4_SELECT_REGISTRY_NULL . . . . .	359
33.5	USER_CHK_SUBNET6_SELECT_ERROR . . . . .	360
<b>34</b>	<b>Kea Debug Messages By Log Level</b>	<b>361</b>
34.1	Messages printed on debuglevel 0 . . . . .	361

34.2	Messages printed on debuglevel 10	361
34.3	Messages printed on debuglevel 15	362
34.4	Messages printed on debuglevel 20	363
34.5	Messages printed on debuglevel 40	363
34.6	Messages printed on debuglevel 45	380
34.7	Messages printed on debuglevel 50	381
34.8	Messages printed on debuglevel 55	387
34.9	Messages printed on debuglevel 70	390

Kea is an open source implementation of the Dynamic Host Configuration Protocol (DHCP) servers, developed and maintained by Internet Systems Consortium (ISC).

This is the reference guide for Kea version 2.7.2. Links to the most up-to-date version of this document (in PDF, HTML, and plain text formats), along with other useful information about Kea, can be found in ISC's [Knowledgebase](#).

Please note that in the messages below, the percent sign (%) followed by a number is used to indicate a placeholder for data that is provided by the Kea code during its operation.



## 1.1 ALLOC\_ENGINE\_IGNOREING\_UNSUITABLE\_GLOBAL\_ADDRESS

```
%1: ignoring globally reserved address %2, it falls outside %3
```

Logged at debug log level 40. This debug message is issued when the allocation engine determines that the globally reserved address falls outside the selected subnet or shared-network. The server should ignore the reserved address and attempt a dynamic allocation.

## 1.2 ALLOC\_ENGINE\_IGNOREING\_UNSUITABLE\_GLOBAL\_ADDRESS6

```
%1: ignoring globally reserved address %2, it falls outside %3
```

Logged at debug log level 40. This debug message is issued when the allocation engine determines that the globally reserved address falls outside the selected subnet or shared-network. The server should ignore the reserved address and attempt a dynamic allocation.

## 1.3 ALLOC\_ENGINE\_LEASE\_RECLAIMED

```
successfully reclaimed lease %1
```

Logged at debug log level 40. This debug message is logged when the allocation engine successfully reclaims a lease. The lease is now available for assignment.

## 1.4 ALLOC\_ENGINE\_V4\_ALLOC\_ERROR

```
%1: error during attempt to allocate an IPv4 address: %2
```

An error occurred during an attempt to allocate an IPv4 address, the reason for the failure being contained in the message. The server will return a message to the client refusing a lease. The first argument includes the client identification information.

## 1.5 ALLOC\_ENGINE\_V4\_ALLOC\_FAIL

```
%1: failed to allocate an IPv4 address after %2 attempt(s)
```

This is an old warning message issued when the allocation engine fails to allocate a lease for a client. This message includes a number of lease allocation attempts that the engine made before giving up. If the number of attempts is 0 because the engine was unable to use any of the address pools for the particular client, this message is not logged. Even though, several more detailed logs precede this message, it was left for backward compatibility. This message may indicate that your address pool is too small for the number of clients you are trying to service and should be expanded. Alternatively, if you know that the number of concurrently active clients is less than the addresses you have available, you may want to consider reducing the lease lifetime. This way, addresses allocated to clients that are no longer active on the network will become available sooner.

## 1.6 ALLOC\_ENGINE\_V4\_ALLOC\_FAIL\_CLASSES

```
%1: Failed to allocate an IPv4 address for client with classes: %2
```

This warning message is printed when Kea failed to allocate an address and the client's packet belongs to one or more classes. There may be several reasons why a lease was not assigned. One of them may be a case when all pools require packet to belong to certain classes and the incoming packet didn't belong to any of them. Another case where this information may be useful is to point out that the pool reserved to a given class has ran out of addresses. When you see this message, you may consider checking your pool size and your classification definitions.

## 1.7 ALLOC\_ENGINE\_V4\_ALLOC\_FAIL\_NO\_POOLS

```
%1: no pools were available for the address allocation
```

This warning message is issued when the allocation engine fails to allocate a lease because it could not use any configured pools for the particular client. It is also possible that all of the subnets from which the allocation engine attempted to assign an address lack address pools. In this case, it should be considered misconfiguration if an operator expects that some clients should be assigned dynamic addresses. A subnet may lack any pools only when all clients should be assigned reserved IP addresses. Suppose the subnets connected to a shared network or a single subnet to which the client belongs have pools configured. In that case, this message is an indication that none of the pools could be used for the client because the client does not belong to appropriate client classes.

## 1.8 ALLOC\_ENGINE\_V4\_ALLOC\_FAIL\_SHARED\_NETWORK

```
%1: failed to allocate an IPv4 address in the shared network %2: %3 subnets have no_
↪available addresses, %4 subnets have no matching pools
```

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a shared network. The shared network should contain at least one subnet, but typically it aggregates multiple subnets. This log message indicates that the allocation engine could not find and allocate any suitable lease in any of the subnets within the shared network. The first argument includes the client identification information. The second argument specifies the shared network name. The remaining two arguments provide additional information useful for debugging why the allocation engine could not assign a lease. The allocation engine tries to allocate addresses from different subnets in the shared network, and it may fail for some subnets because there are no leases available in those subnets or the free



leases are reserved to other clients. The number of such subnets is specified in the third argument. For other subnets the allocation may fail because their pools may not be available to the particular client. These pools are guarded by client classes that the client does not belong to. The fourth argument specifies the number of such subnets. By looking at the values in the third and fourth argument, an operator can identify the situations when there are no addresses left in some of the pools. He or she can also identify a client classification misconfigurations causing some clients to be refused the service.

## 1.9 ALLOC\_ENGINE\_V4\_ALLOC\_FAIL\_SUBNET

```
%1: failed to allocate an IPv4 lease in the subnet %2, subnet-id %3, shared network %4
```

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a subnet. The first argument includes the client identification information. The second and third arguments identify the subnet. The fourth argument specifies the shared network, if the subnet belongs to a shared network. There are many reasons for failing lease allocations. One of them may be the pools exhaustion or existing reservations for the free leases. However, in some cases, the allocation engine may fail to find a suitable pool for the client when the pools are only available to certain client classes, but the requesting client does not belong to them. Further log messages provide more information to distinguish between these different cases.

## 1.10 ALLOC\_ENGINE\_V4\_DECLINED\_RECOVERED

```
IPv4 address %1 was recovered after %2 seconds of probation-period
```

This informational message indicates that the specified address was reported as duplicate (client sent DECLINE) and the server marked this address as unavailable for a period of time. This time now has elapsed and the address has been returned to the available pool. This step concludes the decline recovery process.

## 1.11 ALLOC\_ENGINE\_V4\_DISCOVER\_ADDRESS\_CONFLICT

```
%1: conflicting reservation for address %2 with existing lease %3
```

This warning message is issued when the DHCP server finds that the address reserved for the client can't be offered because this address is currently allocated to another client. The server will try to allocate a different address to the client to use until the conflict is resolved. The first argument includes the client identification information.

## 1.12 ALLOC\_ENGINE\_V4\_DISCOVER\_HR

```
client %1 sending DHCPDISCOVER has reservation for the address %2
```

Logged at debug log level 40. This message is issued when the allocation engine determines that the client sending the DHCPDISCOVER has a reservation for the specified address. The allocation engine will try to offer this address to the client.

## 1.13 ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_COMPLETE

```
reclaimed %1 leases in %2
```

Logged at debug log level 40. This debug message is logged when the allocation engine completes reclamation of a set of expired leases. The maximum number of leases to be reclaimed in a single pass of the lease reclamation routine is configurable using 'max-reclaim-leases' parameter. However, the number of reclaimed leases may also be limited by the timeout value, configured with 'max-reclaim-time'. The message includes the number of reclaimed leases and the total time.

## 1.14 ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_FAILED

```
reclamation of expired leases failed: %1
```

This error message is issued when the reclamation of the expired leases failed. The error message is displayed.

## 1.15 ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_SLOW

```
expired leases still exist after %1 reclamations
```

This warning message is issued when the server has been unable to reclaim all expired leases in a specified number of consecutive attempts. This indicates that the value of "reclaim-timer-wait-time" may be too high. However, if this is just a short burst of leases' expirations the value does not have to be modified and the server should deal with this in subsequent reclamation attempts. If this is a result of a permanent increase of the server load, the value of "reclaim-timer-wait-time" should be decreased, or the values of "max-reclaim-leases" and "max-reclaim-time" should be increased to allow processing more leases in a single cycle. Alternatively, these values may be set to 0 to remove the limitations on the number of leases and duration. However, this may result in longer periods of server's unresponsiveness to DHCP packets, while it processes the expired leases.

## 1.16 ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_START

```
starting reclamation of expired leases (limit = %1 leases or %2 milliseconds)
```

Logged at debug log level 40. This debug message is issued when the allocation engine starts the reclamation of the expired leases. The maximum number of leases to be reclaimed and the timeout is included in the message. If any of these values is 0, it means "unlimited".

## 1.17 ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_TIMEOUT

```
timeout of %1 ms reached while reclaiming IPv4 leases
```

Logged at debug log level 40. This debug message is issued when the allocation engine hits the timeout for performing reclamation of the expired leases. The reclamation will now be interrupted and all leases which haven't been reclaimed, because of the timeout, will be reclaimed when the next scheduled reclamation is started. The argument is the timeout value expressed in milliseconds.

## 1.18 ALLOC\_ENGINE\_V4\_LEASE\_RECLAIM

```
%1: reclaiming expired lease for address %2
```

Logged at debug log level 40. This debug message is issued when the server begins reclamation of the expired DHCPv4 lease. The first argument specifies the client identification information. The second argument holds the leased IPv4 address.

## 1.19 ALLOC\_ENGINE\_V4\_LEASE\_RECLAMATION\_FAILED

```
failed to reclaim the lease %1: %2
```

This error message is logged when the allocation engine fails to reclaim an expired lease. The reason for the failure is included in the message. The error may be triggered in the lease expiration hook or while performing the operation on the lease database.

## 1.20 ALLOC\_ENGINE\_V4\_NO\_MORE\_EXPIRED\_LEASES

```
all expired leases have been reclaimed
```

Logged at debug log level 40. This debug message is issued when the server reclaims all expired DHCPv4 leases in the database.

## 1.21 ALLOC\_ENGINE\_V4\_OFFER\_EXISTING\_LEASE

```
allocation engine will try to offer existing lease to the client %1
```

Logged at debug log level 40. This message is issued when the allocation engine determines that the client has a lease in the lease database, it doesn't have reservation for any other lease, and the leased address is not reserved for any other client. The allocation engine will try to offer the same lease to the client.

## 1.22 ALLOC\_ENGINE\_V4\_OFFER\_NEW\_LEASE

```
allocation engine will try to offer new lease to the client %1
```

Logged at debug log level 40. This message is issued when the allocation engine will try to offer a new lease to the client. This is the case when the client doesn't have any existing lease, it has no reservation or the existing or reserved address is leased to another client. Also, the client didn't specify a hint, or the address in the hint is in use.

## 1.23 ALLOC\_ENGINE\_V4\_OFFER\_REQUESTED\_LEASE

```
allocation engine will try to offer requested lease %1 to the client %2
```

Logged at debug log level 40. This message is issued when the allocation engine will try to offer the lease specified in the hint. This situation may occur when: (a) client doesn't have any reservations, (b) client has reservation but the reserved address is leased to another client.

## 1.24 ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE

```
begin deletion of reclaimed leases expired more than %1 seconds ago
```

Logged at debug log level 40. This debug message is issued when the allocation engine begins deletion of the reclaimed leases which have expired more than a specified number of seconds ago. This operation is triggered periodically according to the "flush-reclaimed-timer-wait-time" parameter. The "hold-reclaimed-time" parameter defines a number of seconds for which the leases are stored before they are removed.

## 1.25 ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE\_COMPLETE

```
successfully deleted %1 expired-reclaimed leases
```

Logged at debug log level 40. This debug message is issued when the server successfully deletes "expired-reclaimed" leases from the lease database. The number of deleted leases is included in the log message.

## 1.26 ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE\_FAILED

```
deletion of expired-reclaimed leases failed: %1
```

This error message is issued when the deletion of "expired-reclaimed" leases from the database failed. The error message is appended to the log message.

## 1.27 ALLOC\_ENGINE\_V4\_REQUEST\_ADDRESS\_RESERVED

```
%1: requested address %2 is reserved
```

Logged at debug log level 40. This message is issued when the allocation engine refused to allocate address requested by the client because this address is reserved for another client. The first argument includes the client identification information.

## 1.28 ALLOC\_ENGINE\_V4\_REQUEST\_ALLOC\_REQUESTED

```
%1: trying to allocate requested address %2
```

Logged at debug log level 40. This message is issued when the allocation engine is trying to allocate (or reuse an expired) address which has been requested by the client. The first argument includes the client identification information.

## 1.29 ALLOC\_ENGINE\_V4\_REQUEST\_EXTEND\_LEASE

```
%1: extending lifetime of the lease for address %2
```

Logged at debug log level 40. This message is issued when the allocation engine determines that the client already has a lease whose lifetime can be extended, and which can be returned to the client. The first argument includes the client identification information.

## 1.30 ALLOC\_ENGINE\_V4\_REQUEST\_INVALID

```
client %1 having a reservation for address %2 is requesting invalid address %3
```

Logged at debug log level 40. This message is logged when the client, having a reservation for one address, is requesting a different address. The client is only allowed to do this when the reserved address is in use by another client. However, the allocation engine has determined that the reserved address is available and the client should request the reserved address.

## 1.31 ALLOC\_ENGINE\_V4\_REQUEST\_IN\_USE

```
%1: requested address %2 is in use
```

Logged at debug log level 40. This message is issued when the client is requesting or has a reservation for an address which is in use. The first argument includes the client identification information.

## 1.32 ALLOC\_ENGINE\_V4\_REQUEST\_OUT\_OF\_POOL

```
client %1, which doesn't have a reservation, requested address %2 out of the dynamic pool
```

Logged at debug log level 40. This message is issued when the client has requested allocation of the address which doesn't belong to any address pool from which addresses are dynamically allocated. The client also doesn't have reservation for this address. This address could only be allocated if the client had reservation for it.

### 1.33 ALLOC\_ENGINE\_V4\_REQUEST\_PICK\_ADDRESS

```
client %1 hasn't specified an address - picking available address from the pool
```

Logged at debug log level 40. This message is logged when the client hasn't specified any preferred address (the client should always do it, but Kea tries to be forgiving). The allocation engine will try to pick an available address from the dynamic pool and allocate it to the client.

### 1.34 ALLOC\_ENGINE\_V4\_REQUEST\_REMOVE\_LEASE

```
%1: removing previous client's lease %2
```

Logged at debug log level 40. This message is logged when the allocation engine removes previous lease for the client because the client has been allocated new one.

### 1.35 ALLOC\_ENGINE\_V4\_REQUEST\_USE\_HR

```
client %1 hasn't requested specific address, using reserved address %2
```

Logged at debug log level 40. This message is issued when the client is not requesting any specific address but the allocation engine has determined that there is a reservation for this client. The allocation engine will try to allocate the reserved address.

### 1.36 ALLOC\_ENGINE\_V4\_REUSE\_EXPIRED\_LEASE\_DATA

```
%1: reusing expired lease, updated lease information: %2
```

Logged at debug log level 55. This message is logged when the allocation engine is reusing an existing lease. The details of the updated lease are printed. The first argument includes the client identification information.

### 1.37 ALLOC\_ENGINE\_V6\_ALLOC\_ERROR

```
%1: error during attempt to allocate an IPv6 address: %2
```

An error occurred during an attempt to allocate an IPv6 address, the reason for the failure being contained in the message. The server will return a message to the client refusing a lease. The first argument includes the client identification information.

## 1.38 ALLOC\_ENGINE\_V6\_ALLOC\_FAIL

```
%1: failed to allocate an IPv6 lease after %2 attempt(s)
```

This is an old warning message issued when the allocation engine fails to allocate a lease for a client. This message includes a number of lease allocation attempts that the engine made before giving up. If the number of attempts is 0 because the engine was unable to use any of the pools for the particular client, this message is not logged. Even though, several more detailed logs precede this message, it was left for backward compatibility. This message may indicate that your pool is too small for the number of clients you are trying to service and should be expanded. Alternatively, if the you know that the number of concurrently active clients is less than the leases you have available, you may want to consider reducing the lease lifetime. This way, leases allocated to clients that are no longer active on the network will become available sooner.

## 1.39 ALLOC\_ENGINE\_V6\_ALLOC\_FAIL\_CLASSES

```
%1: Failed to allocate an IPv6 address for client with classes: %2
```

This warning message is printed when Kea failed to allocate an address and the client's packet belongs to one or more classes. There may be several reasons why a lease was not assigned. One of them may be a case when all pools require packet to belong to certain classes and the incoming packet didn't belong to any of them. Another case where this information may be useful is to point out that the pool reserved to a given class has ran out of addresses. When you see this message, you may consider checking your pool size and your classification definitions.

## 1.40 ALLOC\_ENGINE\_V6\_ALLOC\_FAIL\_NO\_POOLS

```
%1: no pools were available for the lease allocation
```

This warning message is issued when the allocation engine fails to allocate a lease because it could not use any configured pools for the particular client. It is also possible that all of the subnets from which the allocation engine attempted to assign an address lack address pools. In this case, it should be considered misconfiguration if an operator expects that some clients should be assigned dynamic addresses. A subnet may lack any pools only when all clients should be assigned reserved leases. Suppose the subnets connected to a shared network or a single subnet to which the client belongs have pools configured. In that case, this message is an indication that none of the pools could be used for the client because the client does not belong to appropriate client classes.

## 1.41 ALLOC\_ENGINE\_V6\_ALLOC\_FAIL\_SHARED\_NETWORK

```
%1: failed to allocate a lease in the shared network %2: %3 subnets have no available_
↳leases, %4 subnets have no matching pools
```

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a shared network. The shared network should contain at least one subnet, but typically it aggregates multiple subnets. This log message indicates that the allocation engine could not find and allocate any suitable lease in any of the subnets within the shared network. The first argument includes the client identification information. The second argument specifies the shared network name. The remaining two arguments provide additional information useful for debugging why the allocation engine could not assign a lease. The allocation engine tries to allocate leases from different subnets in the shared network, and it may fail for some subnets because there are no leases available in those subnets or the free leases

are reserved to other clients. The number of such subnets is specified in the third argument. For other subnets the allocation may fail because their pools may not be available to the particular client. These pools are guarded by client classes that the client does not belong to. The fourth argument specifies the number of such subnets. By looking at the values in the third and fourth argument, an operator can identify the situations when there are no leases left in some of the pools. He or she can also identify client classification misconfigurations causing some clients to be refused the service.

## 1.42 ALLOC\_ENGINE\_V6\_ALLOC\_FAIL\_SUBNET

```
%1: failed to allocate an IPv6 lease in the subnet %2, subnet-id %3, shared network %4
```

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a subnet. The first argument includes the client identification information. The second and third arguments identify the subnet. The fourth argument specifies the shared network, if the subnet belongs to a shared network. There are many reasons for failing lease allocations. One of them may be the pools exhaustion or existing reservations for the free leases. However, in some cases, the allocation engine may fail to find a suitable pool for the client when the pools are only available to certain client classes, but the requesting client does not belong to them. Further log messages provide more information to distinguish between these different cases.

## 1.43 ALLOC\_ENGINE\_V6\_ALLOC\_HR\_LEASE\_EXISTS

```
%1: lease type %2 for reserved address/prefix %3 already exists
```

Logged at debug log level 40. This debug message is issued when the allocation engine determines that the lease for the IPv6 address or prefix has already been allocated for the client and the client can continue using it. The first argument includes the client identification information.

## 1.44 ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_HR

```
leases and static reservations found for client %1
```

Logged at debug log level 40. This message is logged when the allocation engine is in the process of allocating leases for the client, it found existing leases and static reservations for the client. The allocation engine will verify if existing leases match reservations. Those leases that are reserved for other clients and those that are not reserved for the client will be removed. All leases matching the reservations will be renewed and returned.

## 1.45 ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_NO\_HR

```
no reservations found but leases exist for client %1
```

Logged at debug log level 40. This message is logged when the allocation engine is in the process of allocating leases for the client, there are no static reservations, but lease(s) exist for the client. The allocation engine will remove leases which are reserved for other clients, and return all remaining leases to the client.



## 1.46 ALLOC\_ENGINE\_V6\_ALLOC\_NO\_LEASES\_HR

```
no leases found but reservations exist for client %1
```

Logged at debug log level 40. This message is logged when the allocation engine is in the process of allocating leases for the client. It hasn't found any existing leases for this client, but the client appears to have static reservations. The allocation engine will try to allocate the reserved resources for the client.

## 1.47 ALLOC\_ENGINE\_V6\_ALLOC\_NO\_V6\_HR

```
%1: unable to allocate reserved leases - no IPv6 reservations
```

Logged at debug log level 40. This message is logged when the allocation engine determines that the client has no IPv6 reservations and thus the allocation engine will have to try to allocate allocating leases from the dynamic pool or stop the allocation process if none can be allocated. The first argument includes the client identification information.

## 1.48 ALLOC\_ENGINE\_V6\_ALLOC\_UNRESERVED

```
no static reservations available - trying to dynamically allocate leases for client %1
```

Logged at debug log level 40. This debug message is issued when the allocation engine will attempt to allocate leases from the dynamic pools. This may be due to one of (a) there are no reservations for this client, (b) there are reservations for the client but they are not usable because the addresses are in use by another client or (c) we had a reserved lease but that has now been allocated to another client.

## 1.49 ALLOC\_ENGINE\_V6\_CALCULATED\_PREFERRED\_LIFETIME

```
%1: using a calculated preferred-lifetime of %2
```

Logged at debug log level 40. This debug message indicates that the preferred-lifetime being returned to the client is defaulting to 62.5% of the valid-lifetime. This may occur if either the preferred-lifetime has not been explicitly configured, or the configured value is larger than the valid-lifetime. The arguments detail the client and the preferred-lifetime that will be used.

## 1.50 ALLOC\_ENGINE\_V6\_DECLINED\_RECOVERED

```
IPv6 address %1 was recovered after %2 seconds of probation-period
```

This informational message indicates that the specified address was reported as duplicate (client sent DECLINE) and the server marked this address as unavailable for a period of time. This time now has elapsed and the address has been returned to the available pool. This step concludes the decline recovery process.

## 1.51 ALLOC\_ENGINE\_V6\_EXPIRED\_HINT\_RESERVED

`%1: expired lease for the client's hint %2 is reserved for another client`

Logged at debug log level 40. This message is logged when the allocation engine finds that the expired lease for the client's hint can't be reused because it is reserved for another client. The first argument includes the client identification information.

## 1.52 ALLOC\_ENGINE\_V6\_EXTEND\_ALLOC\_UNRESERVED

`allocate new (unreserved) leases for the renewing client %1`

Logged at debug log level 40. This debug message is issued when the allocation engine is trying to allocate new leases for the renewing client because it was unable to renew any of the existing client's leases, e.g. because leases are reserved for another client or for any other reason.

## 1.53 ALLOC\_ENGINE\_V6\_EXTEND\_ERROR

`%1: allocation engine experienced error with attempting to extend lease lifetime: %2`

This error message indicates that an error was experienced during Renew or Rebind processing. Additional explanation is provided with this message. Depending on its nature, manual intervention may be required to continue processing messages from this particular client; other clients will be unaffected. The first argument includes the client identification information.

## 1.54 ALLOC\_ENGINE\_V6\_EXTEND\_LEASE

`%1: extending lifetime of the lease type %2, address %3`

Logged at debug log level 50. This debug message is issued when the allocation engine is trying to extend lifetime of the lease. The first argument includes the client identification information.

## 1.55 ALLOC\_ENGINE\_V6\_EXTEND\_LEASE\_DATA

`%1: detailed information about the lease being extended: %2`

Logged at debug log level 55. This debug message prints detailed information about the lease which lifetime is being extended (renew or rebind). The first argument includes the client identification information.

## 1.56 ALLOC\_ENGINE\_V6\_EXTEND\_NEW\_LEASE\_DATA

```
%1: new lease information for the lease being extended: %2
```

Logged at debug log level 55. This debug message prints updated information about the lease to be extended. If the lease update is successful, the information printed by this message will be stored in the database. The first argument includes the client identification information.

## 1.57 ALLOC\_ENGINE\_V6\_HINT\_RESERVED

```
%1: lease for the client's hint %2 is reserved for another client
```

Logged at debug log level 40. This message is logged when the allocation engine cannot allocate the lease using the client's hint because the lease for this hint is reserved for another client. The first argument includes the client identification information.

## 1.58 ALLOC\_ENGINE\_V6\_HR\_ADDR\_GRANTED

```
reserved address %1 was assigned to client %2
```

This informational message signals that the specified client was assigned the address reserved for it.

## 1.59 ALLOC\_ENGINE\_V6\_HR\_PREFIX\_GRANTED

```
reserved prefix %1/%2 was assigned to client %3
```

This informational message signals that the specified client was assigned the prefix reserved for it.

## 1.60 ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_COMPLETE

```
reclaimed %1 leases in %2
```

Logged at debug log level 40. This debug message is logged when the allocation engine completes reclamation of a set of expired leases. The maximum number of leases to be reclaimed in a single pass of the lease reclamation routine is configurable using 'max-reclaim-leases' parameter. However, the number of reclaimed leases may also be limited by the timeout value, configured with 'max-reclaim-time'. The message includes the number of reclaimed leases and the total time.

## 1.61 ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_FAILED

```
reclamation of expired leases failed: %1
```

This error message is issued when the reclamation of the expired leases failed. The error message is displayed.

## 1.62 ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_SLOW

```
expired leases still exist after %1 reclamations
```

This warning message is issued when the server has been unable to reclaim all expired leases in a specified number of consecutive attempts. This indicates that the value of "reclaim-timer-wait-time" may be too high. However, if this is just a short burst of leases' expirations the value does not have to be modified and the server should deal with this in subsequent reclamation attempts. If this is a result of a permanent increase of the server load, the value of "reclaim-timer-wait-time" should be decreased, or the values of "max-reclaim-leases" and "max-reclaim-time" should be increased to allow processing more leases in a single cycle. Alternatively, these values may be set to 0 to remove the limitations on the number of leases and duration. However, this may result in longer periods of server's unresponsiveness to DHCP packets, while it processes the expired leases.

## 1.63 ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_START

```
starting reclamation of expired leases (limit = %1 leases or %2 milliseconds)
```

Logged at debug log level 40. This debug message is issued when the allocation engine starts the reclamation of the expired leases. The maximum number of leases to be reclaimed and the timeout is included in the message. If any of these values is 0, it means "unlimited".

## 1.64 ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_TIMEOUT

```
timeout of %1 ms reached while reclaiming IPv6 leases
```

Logged at debug log level 40. This debug message is issued when the allocation engine hits the timeout for performing reclamation of the expired leases. The reclamation will now be interrupted and all leases which haven't been reclaimed, because of the timeout, will be reclaimed when the next scheduled reclamation is started. The argument is the timeout value expressed in milliseconds.

## 1.65 ALLOC\_ENGINE\_V6\_LEASE\_RECLAIM

```
%1: reclaiming expired lease for prefix %2/%3
```

Logged at debug log level 40. This debug message is issued when the server begins reclamation of the expired DHCPv6 lease. The reclaimed lease may either be an address lease or delegated prefix. The first argument provides the client identification information. The other arguments specify the prefix and the prefix length for the lease. The prefix length for address lease is equal to 128.

## 1.66 ALLOC\_ENGINE\_V6\_LEASE\_RECLAMATION\_FAILED

```
failed to reclaim the lease %1: %2
```

This error message is logged when the allocation engine fails to reclaim an expired lease. The reason for the failure is included in the message. The error may be triggered in the lease expiration hook or while performing the operation on the lease database.

## 1.67 ALLOC\_ENGINE\_V6\_NO\_MORE\_EXPIRED\_LEASES

```
all expired leases have been reclaimed
```

Logged at debug log level 40. This debug message is issued when the server reclaims all expired DHCPv6 leases in the database.

## 1.68 ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE

```
begin deletion of reclaimed leases expired more than %1 seconds ago
```

Logged at debug log level 40. This debug message is issued when the allocation engine begins deletion of the reclaimed leases which have expired more than a specified number of seconds ago. This operation is triggered periodically according to the "flush-reclaimed-timer-wait-time" parameter. The "hold-reclaimed-time" parameter defines a number of seconds for which the leases are stored before they are removed.

## 1.69 ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE\_COMPLETE

```
successfully deleted %1 expired-reclaimed leases
```

Logged at debug log level 40. This debug message is issued when the server successfully deletes "expired-reclaimed" leases from the lease database. The number of deleted leases is included in the log message.

## 1.70 ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE\_FAILED

```
deletion of expired-reclaimed leases failed: %1
```

This error message is issued when the deletion of "expired-reclaimed" leases from the database failed. The error message is appended to the log message.

## 1.71 ALLOC\_ENGINE\_V6\_RENEW\_HR

allocating leases reserved for the client %1 as a result of Renew

Logged at debug log level 40. This debug message is issued when the allocation engine tries to allocate reserved leases for the client sending a Renew message. The server will also remove any leases that the client is trying to renew that are not reserved for the client.

## 1.72 ALLOC\_ENGINE\_V6\_RENEW\_REMOVE\_RESERVED

%1: checking if existing client's leases are reserved for another client

Logged at debug log level 40. This message is logged when the allocation engine finds leases for the client and will check if these leases are reserved for another client. If they are, they will not be renewed for the client requesting their renewal. The first argument includes the client identification information.

## 1.73 ALLOC\_ENGINE\_V6\_REUSE\_EXPIRED\_LEASE\_DATA

%1: reusing expired lease, updated lease information: %2

Logged at debug log level 55. This message is logged when the allocation engine is reusing an existing lease. The details of the updated lease are printed. The first argument includes the client identification information.

## 1.74 ALLOC\_ENGINE\_V6\_REVOKED\_ADDR\_LEASE

%1: address %2 was revoked from client %3 as it is reserved for client %4

This informational message is an indication that the specified IPv6 address was used by client A but it is now reserved for client B. Client A has been told to stop using it so that it can be leased to client B. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding a reservation for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their addresses.

## 1.75 ALLOC\_ENGINE\_V6\_REVOKED\_PREFIX\_LEASE

%1: prefix %2/%3 was revoked from client %4 as it is reserved for client %5

This informational message is an indication that the specified IPv6 prefix was used by client A but it is now reserved for client B. Client A has been told to stop using it so that it can be leased to client B. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding a reservation for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their prefixes.

## 1.76 ALLOC\_ENGINE\_V6\_REVOKED\_SHARED\_ADDR\_LEASE

%1: address %2 was revoked from client %3 as it is reserved for %4 other clients

This informational message is an indication that the specified IPv6 address was used by client A but it is now reserved for multiple other clients. Client A has been told to stop using it so that it can be leased to one of the clients having the reservation for it. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding reservations for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their addresses.





## ASIODNS

### 2.1 ASIODNS\_FETCH\_COMPLETED

```
upstream fetch to %1(%2) has now completed
```

Logged at debug log level 70. A debug message, this records that the upstream fetch (a query made by the resolver on behalf of its client) to the specified address has completed.

### 2.2 ASIODNS\_FETCH\_STOPPED

```
upstream fetch to %1(%2) has been stopped
```

Logged at debug log level 40. An external component has requested the halting of an upstream fetch. This is an allowed operation, and the message should only appear if debug is enabled.

### 2.3 ASIODNS\_OPEN\_SOCKET

```
error %1 opening %2 socket to %3(%4)
```

The asynchronous I/O code encountered an error when trying to open a socket of the specified protocol in order to send a message to the target address. The number of the system error that caused the problem is given in the message.

### 2.4 ASIODNS\_READ\_DATA

```
error %1 reading %2 data from %3(%4)
```

The asynchronous I/O code encountered an error when trying to read data from the specified address on the given protocol. The number of the system error that caused the problem is given in the message.

## 2.5 ASIODNS\_READ\_TIMEOUT

receive timeout while waiting for data from %1(%2)

Logged at debug log level 50. An upstream fetch from the specified address timed out. This may happen for any number of reasons and is most probably a problem at the remote server or a problem on the network. The message will only appear if debug is enabled.

## 2.6 ASIODNS\_SEND\_DATA

error %1 sending data using %2 to %3(%4)

The asynchronous I/O code encountered an error when trying to send data to the specified address on the given protocol. The number of the system error that caused the problem is given in the message.

## 2.7 ASIODNS\_UNKNOWN\_ORIGIN

unknown origin for ASIO error code %1 (protocol: %2, address %3)

An internal consistency check on the origin of a message from the asynchronous I/O module failed. This may indicate an internal error; please submit a bug report.

### 3.1 BOOTP\_BOOTP\_QUERY

```
recognized a BOOTP query: %1
```

Logged at debug log level 40. This debug message is printed when the BOOTP query was recognized. The BOOTP client class was added and the message type set to DHCPREQUEST. The query client and transaction identification are displayed.

### 3.2 BOOTP\_LOAD

```
Bootp hooks library has been loaded
```

This info message indicates that the Bootp hooks library has been loaded.

### 3.3 BOOTP\_PACKET\_OPTIONS\_SKIPPED

```
an error unpacking an option, caused subsequent options to be skipped: %1
```

Logged at debug log level 40. A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv4 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

### 3.4 BOOTP\_PACKET\_PACK

```
%1: preparing on-wire format of the packet to be sent
```

Logged at debug log level 40. This debug message is issued when the server starts preparing the on-wire format of the packet to be sent back to the client. The argument specifies the client and the transaction identification information.

## 3.5 BOOTP\_PACKET\_PACK\_FAIL

```
%1: preparing on-wire-format of the packet to be sent failed %2
```

This error message is issued when preparing an on-wire format of the packet has failed. The first argument identifies the client and the BOOTP transaction. The second argument includes the error string.

## 3.6 BOOTP\_PACKET\_UNPACK\_FAILED

```
failed to parse query from %1 to %2, received over interface %3, reason: %4
```

Logged at debug log level 40. This debug message is issued when received DHCPv4 query is malformed and can't be parsed by the `buffer4_receive` callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

## COMMAND

### 4.1 COMMAND\_ACCEPTOR\_START

```
Starting to accept connections via unix domain socket bound to %1
```

This informational message is issued when the Kea server starts an acceptor via which it is going to accept new control connections. The acceptor is bound to the endpoint associated with the filename provided as an argument. If starting the acceptor fails, subsequent error messages will provide a reason for failure.

### 4.2 COMMAND\_DEREGISTERED

```
Command %1 deregistered
```

Logged at debug log level 10. This debug message indicates that the daemon stopped supporting specified command. This command can no longer be issued. If the command socket is open and this command is issued, the daemon will not be able to process it.

### 4.3 COMMAND\_EXTENDED\_REGISTERED

```
Command %1 registered
```

Logged at debug log level 10. This debug message indicates that the daemon started supporting specified command. The handler for the registered command includes a parameter holding entire command to be processed.

### 4.4 COMMAND\_HTTP\_LISTENER\_COMMAND\_REJECTED

```
Command HTTP listener rejected command '%1' from '%2'
```

Logged at debug log level 10. This debug messages is issued when a command is rejected. Arguments detail the command and the address the request was received from.

## 4.5 COMMAND\_HTTP\_LISTENER\_STARTED

```
Command HTTP listener started with %1 threads, listening on %2:%3, use TLS: %4
```

Logged at debug log level 10. This debug messages is issued when an HTTP listener has been started to accept connections from Command API clients through which commands can be received and responses sent. Arguments detail the number of threads that the listener is using, the address and port at which it is listening, and if HTTPS/TLS is used or not.

## 4.6 COMMAND\_HTTP\_LISTENER\_STOPPED

```
Command HTTP listener for %1:%2 stopped.
```

Logged at debug log level 10. This debug messages is issued when the Command HTTP listener, listening at the given address and port, has completed shutdown.

## 4.7 COMMAND\_HTTP\_LISTENER\_STOPPING

```
Stopping Command HTTP listener for %1:%2
```

Logged at debug log level 10. This debug messages is issued when the Command HTTP listener, listening at the given address and port, has begun to shutdown.

## 4.8 COMMAND\_PROCESS\_ERROR1

```
Error while processing command: %1
```

This warning message indicates that the server encountered an error while processing received command. Additional information will be provided, if available. Additional log messages may provide more details.

## 4.9 COMMAND\_PROCESS\_ERROR2

```
Error while processing command: %1
```

This warning message indicates that the server encountered an error while processing received command. The difference, compared to COMMAND\_PROCESS\_ERROR1 is that the initial command was well formed and the error occurred during logic processing, not the command parsing. Additional information will be provided, if available. Additional log messages may provide more details.

## 4.10 COMMAND\_RECEIVED

```
Received command '%1'
```

This informational message indicates that a command was received over command socket. The nature of this command and its possible results will be logged with separate messages.

## 4.11 COMMAND\_REGISTERED

```
Command %1 registered
```

Logged at debug log level 10. This debug message indicates that the daemon started supporting specified command. If the command socket is open, this command can now be issued.

## 4.12 COMMAND\_RESPONSE\_ERROR

```
Server failed to generate response for command: %1
```

This error message indicates that the server failed to generate response for specified command. This likely indicates a server logic error, as the server is expected to generate valid responses for all commands, even malformed ones.

## 4.13 COMMAND\_SOCKET\_ACCEPT\_FAIL

```
Failed to accept incoming connection on command socket %1: %2
```

This error indicates that the server detected incoming connection and executed accept system call on said socket, but this call returned an error. Additional information may be provided by the system as second parameter.

## 4.14 COMMAND\_SOCKET\_CLOSED\_BY\_FOREIGN\_HOST

```
Closed command socket %1 by foreign host, %2
```

This is an information message indicating that the command connection has been closed by a command control client, and whether any partially read data was discarded.

## 4.15 COMMAND\_SOCKET\_CONNECTION\_CANCEL\_FAIL

```
Failed to cancel read operation on socket %1: %2
```

This error message is issued to indicate an error to cancel asynchronous read of the control command over the control socket. The cancel operation is performed when the timeout occurs during communication with a client. The error message includes details about the reason for failure.

## 4.16 COMMAND\_SOCKET\_CONNECTION\_CLOSED

```
Closed socket %1 for existing command connection
```

Logged at debug log level 10. This is a debug message indicating that the socket created for handling client's connection is closed. This usually means that the client disconnected, but may also mean a timeout.

## 4.17 COMMAND\_SOCKET\_CONNECTION\_CLOSE\_FAIL

```
Failed to close command connection: %1
```

This error message is issued when an error occurred when closing a command connection and/or removing it from the connections pool. The detailed error is provided as an argument.

## 4.18 COMMAND\_SOCKET\_CONNECTION\_OPENED

```
Opened socket %1 for incoming command connection
```

Logged at debug log level 10. This is a debug message indicating that a new incoming command connection was detected and a dedicated socket was opened for that connection.

## 4.19 COMMAND\_SOCKET\_CONNECTION\_SHUTDOWN\_FAIL

```
Encountered error %1 while trying to gracefully shutdown socket
```

This message indicates an error while trying to gracefully shutdown command connection. The type of the error is included in the message.

## 4.20 COMMAND\_SOCKET\_CONNECTION\_TIMEOUT

```
Timeout occurred for connection over socket %1
```

This is an informational message that indicates that the timeout has occurred for one of the command channel connections. The response sent by the server indicates a timeout and is then closed.

## 4.21 COMMAND\_SOCKET\_READ

```
Received %1 bytes over command socket %2
```

Logged at debug log level 10. This debug message indicates that specified number of bytes was received over command socket identified by specified file descriptor.



## 4.22 COMMAND\_SOCKET\_READ\_FAIL

```
Encountered error %1 while reading from command socket %2
```

This error message indicates that an error was encountered while reading from command socket.

## 4.23 COMMAND\_SOCKET\_WRITE

```
Sent response of %1 bytes (%2 bytes left to send) over command socket %3
```

Logged at debug log level 10. This debug message indicates that the specified number of bytes was sent over command socket identifier by the specified file descriptor.

## 4.24 COMMAND\_SOCKET\_WRITE\_FAIL

```
Error while writing to command socket %1 : %2
```

This error message indicates that an error was encountered while attempting to send a response to the command socket.

## 4.25 COMMAND\_WATCH\_SOCKET\_CLEAR\_ERROR

```
watch socket failed to clear: %1
```

This error message is issued when the command manager was unable to reset the ready status after completing a send. This is a programmatic error that should be reported. The command manager may or may not continue to operate correctly.

## 4.26 COMMAND\_WATCH\_SOCKET\_CLOSE\_ERROR

```
watch socket failed to close: %1
```

This error message is issued when command manager attempted to close the socket used for indicating the ready status for send operations. This should not have any negative impact on the operation of the command manager as it happens when the connection is being terminated.

## 4.27 COMMAND\_WATCH\_SOCKET\_MARK\_READY\_ERROR

```
watch socket failed to mark ready: %1
```

This error message is issued when the command manager was unable to set ready status after scheduling asynchronous send. This is programmatic error that should be reported. The command manager may or may not continue to operate correctly.



## 5.1 CTRL\_AGENT\_COMMAND\_FORWARDED

```
command %1 successfully forwarded to the service %2 from remote address %3
```

This informational message is issued when the CA successfully forwards the control message to the specified Kea service and receives a response.

## 5.2 CTRL\_AGENT\_COMMAND\_FORWARD\_BEGIN

```
begin forwarding command %1 to service %2
```

Logged at debug log level 10. This debug message is issued when the Control Agent starts forwarding a received command to one of the Kea servers.

## 5.3 CTRL\_AGENT\_COMMAND\_FORWARD\_FAILED

```
failed forwarding command %1: %2
```

Logged at debug log level 10. This debug message is issued when the Control Agent failed forwarding a received command to one of the Kea servers. The second argument provides the details of the error.

## 5.4 CTRL\_AGENT\_COMMAND\_RECEIVED

```
command %1 received from remote address %2
```

This informational message is issued when the CA receives a control message, whether it is destined to the control agent itself, or to be forwarded on.

## 5.5 CTRL\_AGENT\_CONFIG\_CHECK\_FAIL

```
Control Agent configuration check failed: %1
```

This error message indicates that the CA had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

## 5.6 CTRL\_AGENT\_CONFIG\_FAIL

```
Control Agent configuration failed: %1
```

This error message indicates that the CA had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

## 5.7 CTRL\_AGENT\_CONFIG\_SYNTAX\_WARNING

```
Control Agent configuration syntax warning: %1
```

This warning message indicates that the CA configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

## 5.8 CTRL\_AGENT\_FAILED

```
application experienced a fatal error: %1
```

This is a fatal error message issued when the Control Agent application encounters an unrecoverable error from within the event loop.

## 5.9 CTRL\_AGENT\_HTTPS\_SERVICE\_STARTED

```
HTTPS service bound to address %1:%2
```

This informational message indicates that the server has started HTTPS service on the specified address and port. All control commands should be sent to this address and port over a TLS channel.

## 5.10 CTRL\_AGENT\_HTTP\_SERVICE\_STARTED

```
HTTP service bound to address %1:%2
```

This informational message indicates that the server has started HTTP service on the specified address and port. All control commands should be sent to this address and port.

## 5.11 CTRL\_AGENT\_RUN\_EXIT

application is exiting the event loop

Logged at debug log level 0. This is a debug message issued when the Control Agent exits its event loop.



## DATABASE

## 6.1 DATABASE\_INVALID\_ACCESS

```
invalid database access string: %1
```

This is logged when an attempt has been made to parse a database access string and the attempt ended in error. The access string in question - which should be of the form 'keyword=value keyword=value...' is included in the message.

## 6.2 DATABASE\_MYSQL\_COMMIT

```
committing to MySQL database
```

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the committal may not include a write to disk.

## 6.3 DATABASE\_MYSQL\_FATAL\_ERROR

```
Unrecoverable MySQL error occurred: %1 for <%2>, reason: %3 (error code: %4).
```

An error message indicating that communication with the MySQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover connectivity. If not, then the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the MySQL server has gone down.

## 6.4 DATABASE\_MYSQL\_INITIALIZE\_SCHEMA

```
Initializing the MySQL schema with command: %1.
```

This is logged before running the kea-admin command to automatically initialize the schema from Kea after getting the schema version initially failed. The full kea-admin command is shown.

## 6.5 DATABASE\_MYSQL\_ROLLBACK

rolling back MySQL database

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

## 6.6 DATABASE\_MYSQL\_START\_TRANSACTION

starting new MySQL transaction

A debug message issued when a new MySQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

## 6.7 DATABASE\_PGSQL\_COMMIT

committing to PostgreSQL database

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the committal may not include a write to disk.

## 6.8 DATABASE\_PGSQL\_CREATE\_SAVEPOINT

creating a new PostgreSQL savepoint: %1

The code is issuing a call to create a savepoint within the current transaction. Database modifications made up to this point will be preserved should a subsequent call to rollback to this savepoint occurs prior to the transaction being committed.

## 6.9 DATABASE\_PGSQL\_DEALLOC\_ERROR

An error occurred deallocating SQL statements while closing the PostgreSQL lease.  
↪database: %1

This is an error message issued when a DHCP server (either V4 or V6) experienced an error freeing database SQL resources as part of closing its connection to the PostgreSQL database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.



## 6.10 DATABASE\_PGSQL\_FATAL\_ERROR

```
Unrecoverable PostgreSQL error occurred: Statement: <%1>, reason: %2 (error code: %3).
```

An error message indicating that communication with the PostgreSQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover the connectivity. If not, then the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the PostgreSQL server has gone down.

## 6.11 DATABASE\_PGSQL\_INITIALIZE\_SCHEMA

```
Initializing the PostgreSQL schema with command: %1.
```

This is logged before running the kea-admin command to automatically initialize the schema from Kea after getting the schema version initially failed. The full kea-admin command is shown.

## 6.12 DATABASE\_PGSQL\_ROLLBACK

```
rolling back PostgreSQL database
```

The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

## 6.13 DATABASE\_PGSQL\_ROLLBACK\_SAVEPOINT

```
rolling back PostgreSQL database to savepoint: $1
```

The code is issuing a call to rollback to the given savepoint. Any database modifications that were made after the savepoint was created will be rolled back and not committed to the database.

## 6.14 DATABASE\_PGSQL\_START\_TRANSACTION

```
starting a new PostgreSQL transaction
```

A debug message issued when a new PostgreSQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

## 6.15 DATABASE\_PGSQL\_TCP\_USER\_TIMEOUT\_UNSUPPORTED

tcp\_user\_timeout is not supported in this PostgreSQL version

This warning message is issued when a user has configured the `tcp_user_timeout` parameter in the connection to the PostgreSQL database but the installed database does not support this parameter. It is supported by the PostgreSQL version 12 or later. The parameter setting will be ignored.

## 6.16 DATABASE\_TO\_JSON\_BOOLEAN\_ERROR

Internal logic error: invalid boolean value found in database connection parameters: %1=  
↔%2

This error message is printed when conversion to JSON of the internal state is requested, but the connection string contains a boolean parameter with invalid value. It is a programming error. The software will continue operation, but the returned JSON data will be syntactically valid, but incomplete. The culprit parameter will not be converted.

## 6.17 DATABASE\_TO\_JSON\_INTEGER\_ERROR

Internal logic error: invalid integer value found in database connection parameters: %1=  
↔%2

This error message is printed when conversion to JSON of the internal state is requested, but the connection string contains the integer parameter with a wrong value. It is a programming error. The software will continue operation, but the returned JSON data will be syntactically valid, but incomplete. The culprit parameter will not be converted.

## 7.1 DCTL\_ALREADY\_RUNNING

```
%1 already running? %2
```

This is an error message that occurs when a module encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of a module using the same configuration file. It is possible, though unlikely, that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than Kea process. In such an event, it would be necessary to manually remove the PID file. The first argument is the process name, the second contains the PID and PID file.

## 7.2 DCTL\_CFG\_FILE\_RELOAD\_ERROR

```
configuration reload failed: %1, reverting to current configuration.
```

This is an error message indicating that the application attempted to reload its configuration from file and encountered an error. This is likely due to invalid content in the configuration file. The application should continue to operate under its current configuration.

## 7.3 DCTL\_CFG\_FILE\_RELOAD\_SIGNAL\_RECVD

```
OS signal %1 received, reloading configuration from file: %2
```

This is an informational message indicating the application has received a signal instructing it to reload its configuration from file.

## 7.4 DCTL\_CONFIG\_CHECK\_COMPLETE

```
server has completed configuration check: %1, result: %2
```

This is an informational message announcing the successful processing of a new configuration check is complete. The result of that check is printed. This informational message is printed when configuration check is requested.

## 7.5 DCTL\_CONFIG\_COMPLETE

```
server has completed configuration: %1
```

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

## 7.6 DCTL\_CONFIG\_DEPRECATED

```
server configuration includes a deprecated object: %1
```

This error message is issued when the configuration includes a deprecated object (i.e. a top level element) which will be ignored.

## 7.7 DCTL\_CONFIG\_FETCH

```
Fetching configuration data from config backends.
```

This is an informational message emitted when the Kea server is about to begin retrieving configuration data from one or more configuration backends.

## 7.8 DCTL\_CONFIG\_FILE\_LOAD\_FAIL

```
%1 reason: %2
```

This fatal error message indicates that the application attempted to load its initial configuration from file and has failed. The service will exit.

## 7.9 DCTL\_CONFIG\_START

```
parsing new configuration: %1
```

Logged at debug log level 10. A debug message indicating that the application process has received an updated configuration and has passed it to its configuration manager for parsing.

## 7.10 DCTL\_DB\_OPEN\_CONNECTION\_WITH\_RETRY\_FAILED

```
Failed to connect to database: %1 with error: %2
```

This is an informational message issued when the server failed to connect to the configuration database. The operation started a retry to connect procedure. The database access string with password redacted is logged, along with the error and details for the reconnect procedure.

## 7.11 DCTL\_DEVELOPMENT\_VERSION

```
This software is a development branch of Kea. It is not recommended for production use.
```

This warning message is displayed when the version is a development (vs stable) one: the second number of the version is odd.

## 7.12 DCTL\_INIT\_PROCESS

```
%1 initializing the application
```

Logged at debug log level 0. This debug message is issued just before the controller attempts to create and initialize its application instance.

## 7.13 DCTL\_INIT\_PROCESS\_FAIL

```
%1 application initialization failed: %2
```

This error message is issued if the controller could not initialize the application and will exit.

## 7.14 DCTL\_NOT\_RUNNING

```
%1 application instance is not running
```

A warning message is issued when an attempt is made to shut down the application when it is not running.

## 7.15 DCTL\_OPEN\_CONFIG\_DB

```
Opening configuration database: %1
```

This message is printed when the Kea server is attempting to open a configuration database. The database access string with password redacted is logged.

## 7.16 DCTL\_PARSER\_FAIL

```
Parser error: %1
```

On receipt of a new configuration, the server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

## 7.17 DCTL\_PID\_FILE\_ERROR

```
%1 could not create a PID file: %2
```

This is an error message that occurs when the server is unable to create its PID file. The log message should contain details sufficient to determine the underlying cause. The most likely culprits are that some portion of the pathname does not exist or a permissions issue. The default path is determined by `--localstatedir` or `--runstatedir` configure parameters but may be overridden by setting environment variable, `KEA_PIDFILE_DIR`. The first argument is the process name.

## 7.18 DCTL\_PROCESS\_FAILED

```
%1 application execution failed: %2
```

The controller has encountered a fatal error while running the application and is terminating. The reason for the failure is included in the message.

## 7.19 DCTL\_RUN\_PROCESS

```
%1 starting application event loop
```

Logged at debug log level 0. This debug message is issued just before the controller invokes the application run method.

## 7.20 DCTL\_SHUTDOWN

```
%1 has shut down, pid: %2, version: %3
```

Logged at debug log level 0. This is an informational message indicating that the service has shut down. The argument specifies a name of the service.

## 7.21 DCTL\_SHUTDOWN\_SIGNAL\_RECVD

```
OS signal %1 received, starting shutdown
```

Logged at debug log level 0. This is a debug message indicating the application has received a signal instructing it to shutdown.

## 7.22 DCTL\_STANDALONE

```
%1 skipping message queue, running standalone
```

Logged at debug log level 0. This is a debug message indicating that the controller is running in the application in standalone mode. This means it will not be connected to the Kea message queue. Standalone mode is only useful during program development, and should not be used in a production environment.

## 7.23 DCTL\_STARTING

```
%1 starting, pid: %2, version: %3 (%4)
```

This is an informational message issued when the controller for the service first starts. Version is also reported.

## 7.24 DCTL\_UNLOAD\_LIBRARIES\_ERROR

```
error unloading hooks libraries during shutdown: %1
```

This error message indicates that during shutdown, unloading hooks libraries failed to close them. If the list of libraries is empty it is a programmatic error in the server code. If it is not empty it could be a programmatic error in one of the hooks libraries which could lead to a crash during finalization.





## 8.1 DHCP4\_ALREADY\_RUNNING

```
%1 already running? %2
```

This is an error message that occurs when the DHCPv4 server encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of the server using the same configuration file. It is possible, though unlikely that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than the server. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCPv4 process name, the second contains the PID and PID file.

## 8.2 DHCP4\_BUFFER\_RECEIVED

```
received buffer from %1:%2 to %3:%4 over interface %5
```

Logged at debug log level 40. This debug message is logged when the server has received a packet over the socket. When the message is logged the contents of the received packet hasn't been parsed yet. The only available information is the interface and the source and destination IPv4 addresses/ports.

## 8.3 DHCP4\_BUFFER\_RECEIVE\_FAIL

```
error on attempt to receive packet: %1
```

The DHCPv4 server tried to receive a packet but an error occurred during this attempt. The reason for the error is included in the message.

## 8.4 DHCP4\_BUFFER\_UNPACK

```
parsing buffer received from %1 to %2 over interface %3
```

Logged at debug log level 50. This debug message is issued when the server starts parsing the received buffer holding the DHCPv4 message. The arguments specify the source and destination IPv4 addresses as well as the interface over which the buffer has been received.

## 8.5 DHCP4\_BUFFER\_WAIT\_SIGNAL

```
signal received while waiting for next packet
```

Logged at debug log level 50. This debug message is issued when the server was waiting for the packet, but the wait has been interrupted by the signal received by the process. The signal will be handled before the server starts waiting for next packets.

## 8.6 DHCP4\_CB\_ON\_DEMAND\_FETCH\_UPDATES\_FAIL

```
error on demand attempt to fetch configuration updates from the configuration_
↳backend(s): %1
```

This error message is issued when the server attempted to fetch configuration updates from the database and this on demand attempt failed. The sole argument which is returned to the config-backend-pull command caller too contains the reason for failure.

## 8.7 DHCP4\_CB\_PERIODIC\_FETCH\_UPDATES\_FAIL

```
error on periodic attempt to fetch configuration updates from the configuration_
↳backend(s): %1
```

This error message is issued when the server attempted to fetch configuration updates from the database and this periodic attempt failed. The server will re-try according to the configured value of the config-fetch-wait-time parameter. The sole argument contains the reason for failure.

## 8.8 DHCP4\_CB\_PERIODIC\_FETCH\_UPDATES\_RETRIES\_EXHAUSTED

```
maximum number of configuration fetch attempts: 10, has been exhausted without success
```

This error indicates that the server has made a number of unsuccessful periodic attempts to fetch configuration updates from a configuration backend. The server will continue to operate but won't make any further attempts to fetch configuration updates. The administrator must fix the configuration in the database and reload (or restart) the server.

## 8.9 DHCP4\_CLASSES\_ASSIGNED

```
%1: client packet has been assigned on %2 message to the following classes: %3
```

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument specifies the DHCPv4 message type. The third argument includes all classes to which the packet has been assigned.

## 8.10 DHCP4\_CLASSES\_ASSIGNED\_AFTER\_SUBNET\_SELECTION

```
%1: client packet has been assigned to the following classes: %2
```

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes all classes to which the packet has been assigned.

## 8.11 DHCP4\_CLASS\_ASSIGNED

```
%1: client packet has been assigned to the following class: %2
```

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified class. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes the new class to which the packet has been assigned.

## 8.12 DHCP4\_CLASS\_UNCONFIGURED

```
%1: client packet belongs to an unconfigured class: %2
```

Logged at debug log level 40. This debug message informs that incoming packet belongs to a class which cannot be found in the configuration. Either a hook written before the classification was added to Kea is used, or class naming is inconsistent.

## 8.13 DHCP4\_CLASS\_UNDEFINED

```
required class %1 has no definition
```

Logged at debug log level 40. This debug message informs that a class is listed for required evaluation but has no definition.

## 8.14 DHCP4\_CLASS\_UNTESTABLE

required class %1 has no test expression

Logged at debug log level 40. This debug message informs that a class was listed for required evaluation but its definition does not include a test expression to evaluate.

## 8.15 DHCP4\_CLIENTID\_IGNORED\_FOR\_LEASES

%1: not using client identifier for lease allocation for subnet %2

Logged at debug log level 50. This debug message is issued when the server is processing the DHCPv4 message for which client identifier will not be used when allocating new lease or renewing existing lease. The server is explicitly configured to not use client identifier to lookup existing leases for the client and will not record client identifier in the lease database. This mode of operation is useful when clients don't use stable client identifiers, e.g. multi stage booting. The first argument includes the client and transaction identification information. The second argument specifies the identifier of the subnet where the client is connected and for which this mode of operation is configured on the server.

## 8.16 DHCP4\_CLIENT\_FQDN\_DATA

%1: Client sent FQDN option: %2

Logged at debug log level 55. This debug message includes the detailed information extracted from the Client FQDN option sent in the query. The first argument includes the client and transaction identification information. The second argument specifies the detailed information about the FQDN option received by the server.

## 8.17 DHCP4\_CLIENT\_FQDN\_PROCESS

%1: processing Client FQDN option

Logged at debug log level 50. This debug message is issued when the server starts processing the Client FQDN option sent in the client's query. The argument includes the client and transaction identification information.

## 8.18 DHCP4\_CLIENT\_HOSTNAME\_DATA

%1: client sent Hostname option: %2

Logged at debug log level 55. This debug message includes the detailed information extracted from the Hostname option sent in the query. The first argument includes the client and transaction identification information. The second argument specifies the hostname carried in the Hostname option sent by the client.

## 8.19 DHCP4\_CLIENT\_HOSTNAME\_MALFORMED

```
%1: client hostname option malformed: %2
```

Logged at debug log level 50. This debug message is issued when the DHCP server was unable to process the the hostname option sent by the client because the content is malformed. The first argument includes the client and transaction identification information. The second argument contains a description of the data error.

## 8.20 DHCP4\_CLIENT\_HOSTNAME\_PROCESS

```
%1: processing client's Hostname option
```

Logged at debug log level 50. This debug message is issued when the server starts processing the Hostname option sent in the client's query. The argument includes the client and transaction identification information.

## 8.21 DHCP4\_CLIENT\_NAME\_PROC\_FAIL

```
%1: failed to process the fqdn or hostname sent by a client: %2
```

Logged at debug log level 55. This debug message is issued when the DHCP server was unable to process the FQDN or Hostname option sent by a client. This is likely because the client's name was malformed or due to internal server error. The first argument contains the client and transaction identification information. The second argument holds the detailed description of the error.

## 8.22 DHCP4\_CONFIG\_COMPLETE

```
DHCPv4 server has completed configuration: %1
```

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

## 8.23 DHCP4\_CONFIG\_LOAD\_FAIL

```
configuration error using file: %1, reason: %2
```

This error message indicates that the DHCPv4 configuration has failed. If this is an initial configuration (during server's startup) the server will fail to start. If this is a dynamic reconfiguration attempt the server will continue to use an old configuration.

## 8.24 DHCP4\_CONFIG\_PACKET\_QUEUE

```
DHCPv4 packet queue info after configuration: %1
```

This informational message is emitted during DHCPv4 server configuration, immediately after configuring the DHCPv4 packet queue. The information shown depends upon the packet queue type selected.

## 8.25 DHCP4\_CONFIG\_RECEIVED

```
received configuration %1
```

Logged at debug log level 10. A debug message listing the configuration received by the DHCPv4 server. The source of that configuration depends on used configuration backend.

## 8.26 DHCP4\_CONFIG\_START

```
DHCPv4 server is processing the following configuration: %1
```

Logged at debug log level 10. This is a debug message that is issued every time the server receives a configuration. That happens at start up and also when a server configuration change is committed by the administrator.

## 8.27 DHCP4\_CONFIG\_SYNTAX\_WARNING

```
configuration syntax warning: %1
```

This warning message indicates that the DHCPv4 configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

## 8.28 DHCP4\_CONFIG\_UNRECOVERABLE\_ERROR

```
DHCPv4 server new configuration failed with an error which cannot be recovered
```

This fatal error message is issued when a new configuration raised an error which cannot be recovered. A correct configuration must be applied as soon as possible as the server is no longer working. The configuration can be fixed in several ways. If the control channel is open, config-set with a valid configuration can be used. Alternatively, the original config file on disk could be fixed and SIGHUP signal could be sent (or the config-reload command issued). Finally, the server could be restarted completely.

## 8.29 DHCP4\_CONFIG\_UNSUPPORTED\_OBJECT

```
DHCPv4 server configuration includes an unsupported object: %1
```

This error message is issued when the configuration includes an unsupported object (i.e. a top level element).

## 8.30 DHCP4\_DB\_RECONNECT\_DISABLED

```
database reconnect is disabled: max-reconnect-tries %1, reconnect-wait-time %2
```

This is an informational message indicating that connectivity to either the lease or host database or both and that automatic reconnect is not enabled.

## 8.31 DHCP4\_DB\_RECONNECT\_FAILED

```
maximum number of database reconnect attempts: %1, has been exhausted without success
```

This error indicates that the server failed to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. This might cause the server to shut down as specified in the configuration. Loss of connectivity is typically a network or database server issue.

## 8.32 DHCP4\_DB\_RECONNECT\_LOST\_CONNECTION

```
database connection lost.
```

This info message indicates that the connection has been lost and the dhcp service might have been disabled, as specified in the configuration, in order to try to recover the connection.

## 8.33 DHCP4\_DB\_RECONNECT\_NO\_DB\_CTL

```
unexpected error in database reconnect
```

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to reconnect to its databases if connectivity is lost, and the server exits. This error should be reported.

## 8.34 DHCP4\_DB\_RECONNECT\_SUCCEEDED

```
database connection recovered.
```

This info message indicates that the connection has been recovered and the dhcp service has been restored.

## 8.35 DHCP4\_DDNS\_REQUEST\_SEND\_FAILED

```
failed sending a request to kea-dhcp-ddns, error: %1, ncr: %2
```

This error message indicates that DHCP4 server attempted to send a DDNS update request to the DHCP-DDNS server. This is most likely a configuration or networking error.

## 8.36 DHCP4\_DECLINE\_FAIL

```
%1: error on decline lease for address %2: %3
```

This error message indicates that the software failed to decline a lease from the lease database due to an error during a database operation. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address which decline was attempted. The last one contains the reason for failure.

## 8.37 DHCP4\_DECLINE\_LEASE

```
Received DHCPDECLINE for addr %1 from client %2. The lease will be unavailable for %3.  
↪seconds.
```

This informational message is printed when a client received an address, but discovered that it is being used by some other device and notified the server by sending a DHCPDECLINE message. The server checked that this address really was leased to the client and marked this address as unusable for a certain amount of time. This message may indicate a misconfiguration in a network, as there is either a buggy client or more likely a device that is using an address that it is not supposed to. The server will fully recover from this situation, but if the underlying problem of a misconfigured or rogue device is not solved, this address may be declined again in the future.

## 8.38 DHCP4\_DECLINE\_LEASE\_MISMATCH

```
Received DHCPDECLINE for addr %1 from client %2, but the data doesn't match: received_  
↪hwaddr: %3, lease hwaddr: %4, received client-id: %5, lease client-id: %6
```

This informational message means that a client attempted to report his address as declined (i.e. used by unknown entity). The server has information about a lease for that address, but the client's hardware address or client identifier does not match the server's stored information. The client's request will be ignored.

## 8.39 DHCP4\_DECLINE\_LEASE\_NOT\_FOUND

```
Received DHCPDECLINE for addr %1 from client %2, but no such lease found.
```

This warning message indicates that a client reported that his address was detected as a duplicate (i.e. another device in the network is using this address). However, the server does not have a record for this address. This may indicate a client's error or a server's purged database.



## 8.40 DHCP4\_DEFERRED\_OPTION\_MISSING

```
%1: cannot find deferred option code %2 in the query
```

Logged at debug log level 50. This debug message is printed when a deferred option cannot be found in the query.

## 8.41 DHCP4\_DEFERRED\_OPTION\_UNPACK\_FAIL

```
%1: An error unpacking the deferred option %2: %3
```

Logged at debug log level 50. A debug message issued when deferred unpacking of an option failed, making it to be left unpacked in the packet. The first argument is the option code, the second the error.

## 8.42 DHCP4\_DEVELOPMENT\_VERSION

```
This software is a development branch of Kea. It is not recommended for production use.
```

This warning message is displayed when the version is a development (vs stable) one: the second number of the version is odd.

## 8.43 DHCP4\_DHCP4O6\_BAD\_PACKET

```
%1: received malformed DHCPv4o6 packet: %2
```

Logged at debug log level 50. A malformed DHCPv4o6 packet was received.

## 8.44 DHCP4\_DHCP4O6\_HOOK\_SUBNET4\_SELECT\_DROP

```
%1: packet was dropped, because a callout set the next step to 'drop'
```

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to 'drop' value. For this particular hook point, the setting to that value instructs the server to drop the received packet. The argument specifies the client and transaction identification information.

## 8.45 DHCP4\_DHCP4O6\_HOOK\_SUBNET4\_SELECT\_SKIP

```
%1: no subnet was selected, because a callout set the next skip flag
```

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to SKIP value. For this particular hook point, the setting of the flag instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses will be assigned. The argument specifies the client and transaction identification information.

## 8.46 DHCP4\_DHCP4O6\_PACKET\_RECEIVED

```
received DHCPv4o6 packet from DHCPv4 server (type %1) for %2 on interface %3
```

Logged at debug log level 40. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication.

## 8.47 DHCP4\_DHCP4O6\_PACKET\_SEND

```
%1: trying to send packet %2 (type %3) to %4 port %5 on interface %6 encapsulating %7:  
->%8 (type %9)
```

Logged at debug log level 40. The arguments specify the client identification information (HW address and client identifier), DHCPv6 message name and type, source IPv6 address and port, and interface name, DHCPv4 client identification, message name and type.

## 8.48 DHCP4\_DHCP4O6\_PACKET\_SEND\_FAIL

```
%1: failed to send DHCPv4o6 packet: %2
```

This error is output if the IPv4 DHCP server fails to send an DHCPv4o6 message to the IPv6 DHCP server. The reason for the error is included in the message.

## 8.49 DHCP4\_DHCP4O6\_RECEIVE\_FAIL

```
failed to receive DHCPv4o6: %1
```

Logged at debug log level 50. This debug message indicates the inter-process communication with the DHCPv6 server failed. The reason for the error is included in the message.

## 8.50 DHCP4\_DHCP4O6\_RECEIVING

```
receiving DHCPv4o6 packet from DHCPv6 server
```

Logged at debug log level 50. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv6 server over inter-process communication socket.

## 8.51 DHCP4\_DHCP4O6\_RESPONSE\_DATA

```
%1: responding with packet %2 (type %3), packet details: %4
```

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the DHCPv6 server to be forwarded to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

## 8.52 DHCP4\_DHCP4O6\_SUBNET\_DATA

```
%1: the selected subnet details: %2
```

Logged at debug log level 55. This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second arguments includes the subnet details.

## 8.53 DHCP4\_DHCP4O6\_SUBNET\_SELECTED

```
%1: the subnet with ID %2 was selected for client assignments
```

Logged at debug log level 45. This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

## 8.54 DHCP4\_DHCP4O6\_SUBNET\_SELECTION\_FAILED

```
%1: failed to select subnet for the client
```

Logged at debug log level 50. This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The server will not be able to offer any lease to the client and will drop its message if the received message was DHCPDISCOVER, and will send DHCPNAK if the received message was DHCPREQUEST. The argument includes the client and the transaction identification information.

## 8.55 DHCP4\_DISCOVER

```
%1: server is processing DHCPDISCOVER with hint=%2
```

Logged at debug log level 50. This is a debug message that indicates the processing of a received DHCPDISCOVER message. The first argument contains the client and the transaction identification information. The second argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

## 8.56 DHCP4\_DYNAMIC\_RECONFIGURATION

```
initiate server reconfiguration using file: %1, after receiving SIGHUP signal or config-  
→reload command
```

This is the info message logged when the DHCPv4 server starts reconfiguration as a result of receiving SIGHUP signal or config-reload command.

## 8.57 DHCP4\_DYNAMIC\_RECONFIGURATION\_FAIL

```
dynamic server reconfiguration failed with file: %1
```

This is a fatal error message logged when the dynamic reconfiguration of the DHCP server failed.

## 8.58 DHCP4\_DYNAMIC\_RECONFIGURATION\_SUCCESS

```
dynamic server reconfiguration succeeded with file: %1
```

This is info message logged when the dynamic reconfiguration of the DHCP server succeeded.

## 8.59 DHCP4\_EMPTY\_HOSTNAME

```
%1: received empty hostname from the client, skipping processing of this option
```

Logged at debug log level 50. This debug message is issued when the server received an empty Hostname option from a client. Server does not process empty Hostname options and therefore option is skipped. The argument holds the client and transaction identification information.

## 8.60 DHCP4\_FLEX\_ID

```
%1: flexible identifier generated for incoming packet: %2
```

Logged at debug log level 40. This debug message is printed when host reservation type is set to flexible identifier and the expression specified in its configuration generated (was evaluated to) an identifier for incoming packet. This debug message is mainly intended as a debugging assistance for flexible identifier.

## 8.61 DHCP4\_GENERATE\_FQDN

```
%1: client did not send a FQDN or hostname; FQDN will be generated for the client
```

Logged at debug log level 55. This debug message is issued when the server did not receive a Hostname option from the client and hostname generation is enabled. This provides a means to create DNS entries for unsophisticated clients.

## 8.62 DHCP4\_HOOK\_BUFFER\_RCVD\_DROP

```
received buffer from %1 to %2 over interface %3 was dropped because a callout set the
↳drop flag
```

Logged at debug log level 15. This debug message is printed when a callout installed on buffer4\_receive hook point set the drop flag. For this particular hook point, the setting of the flag by a callout instructs the server to drop the packet. The arguments specify the source and destination IPv4 address as well as the name of the interface over which the buffer has been received.

## 8.63 DHCP4\_HOOK\_BUFFER\_RCVD\_SKIP

```
received buffer from %1 to %2 over interface %3 is not parsed because a callout set the
↳next step to SKIP.
```

Logged at debug log level 50. This debug message is printed when a callout installed on buffer4\_receive hook point set the next step to SKIP. For this particular hook point, this value set by a callout instructs the server to not parse the buffer because it was already parsed by the hook. The arguments specify the source and destination IPv4 address as well as the name of the interface over which the buffer has been received.

## 8.64 DHCP4\_HOOK\_BUFFER\_SEND\_SKIP

```
%1: prepared response is dropped because a callout set the next step to SKIP.
```

Logged at debug log level 40. This debug message is printed when a callout installed on buffer4\_send hook point set the next step to SKIP. For this particular hook point, the SKIP value set by a callout instructs the server to drop the packet. Server completed all the processing (e.g. may have assigned, updated or released leases), but the response will not be sent to the client.

## 8.65 DHCP4\_HOOK\_DDNS\_UPDATE

```
A hook has updated the DDNS parameters: hostname %1=>%2, forward update %3=>%4, reverse
↳update %5=>%6
```

Logged at debug log level 15. This message indicates that there was a hook called on ddns4\_update hook point and that hook updated the DDNS update parameters: hostname, or whether to conduct forward (A record) or reverse (PTR record) DDNS updates.

## 8.66 DHCP4\_HOOK\_DECLINE\_SKIP

Decline4 hook callouts set status to DROP, ignoring packet.

Logged at debug log level 15. This message indicates that the server received DHCPDECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for decline4 hook point and one of the callouts set next step status to DROP. The server will now abort processing of the packet as if it was never received. The lease will continue to be assigned to this client.

## 8.67 DHCP4\_HOOK\_LEASE4\_OFFER\_ARGUMENT\_MISSING

hook callouts did not set an argument as expected %1 for %2

This error message is printed when none of the callouts installed on the lease4\_offer hook point set an expected argument in the callout status. This is a programming error in the installed hook libraries. Details of the argument and the query in process at the time are provided log arguments.

## 8.68 DHCP4\_HOOK\_LEASE4\_OFFER\_DROP

%1: packet is dropped, because a callout set the next step to DROP

This debug message is printed when a callout installed on the lease4\_offer hook point sets the next step to DROP.

## 8.69 DHCP4\_HOOK\_LEASE4\_OFFER\_PARK

%1: packet is parked, because a callout set the next step to PARK

This debug message is printed when a callout installed on the lease4\_offer hook point sets the next step to PARK.

## 8.70 DHCP4\_HOOK\_LEASE4\_OFFER\_PARKING\_LOT\_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. ping-check) that implement the "lease4\_offer" callout and client queries are arriving faster than those callouts can fulfill them.

## 8.71 DHCP4\_HOOK\_LEASE4\_RELEASE\_SKIP

```
%1: lease was not released because a callout set the next step to SKIP
```

Logged at debug log level 15. This debug message is printed when a callout installed on lease4\_release hook point set the next step status to SKIP. For this particular hook point, the value set by a callout instructs the server to not release a lease.

## 8.72 DHCP4\_HOOK\_LEASES4\_COMMITTED\_DROP

```
%1: packet is dropped, because a callout set the next step to DROP
```

This debug message is printed when a callout installed on the leases4\_committed hook point sets the next step to DROP.

## 8.73 DHCP4\_HOOK\_LEASES4\_COMMITTED\_PARK

```
%1: packet is parked, because a callout set the next step to PARK
```

This debug message is printed when a callout installed on the leases4\_committed hook point sets the next step to PARK.

## 8.74 DHCP4\_HOOK\_LEASES4\_COMMITTED\_PARKING\_LOT\_FULL

```
The parked-packet-limit %1, has been reached, dropping query: %2
```

This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. HA) that implement the "leases4-committed" callout and client queries are arriving faster than those callouts can fulfill them.

## 8.75 DHCP4\_HOOK\_PACKET\_RCVD\_SKIP

```
%1: packet is dropped, because a callout set the next step to SKIP
```

Logged at debug log level 40. This debug message is printed when a callout installed on the pkt4\_receive hook point sets the next step to SKIP. For this particular hook point, the value setting of the flag instructs the server to drop the packet.

## 8.76 DHCP4\_HOOK\_PACKET\_SEND\_DROP

`%1: prepared DHCPv4 response was not sent because a callout set the next step to DROP`

Logged at debug log level 15. This debug message is printed when a callout installed on the `pkt4_send` hook point set the next step to `DROP`. For this particular hook point, the setting of the value by a callout instructs the server to drop the packet. This effectively means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease). The argument specifies the client and transaction identification information.

## 8.77 DHCP4\_HOOK\_PACKET\_SEND\_SKIP

`%1: prepared response is not sent, because a callout set the next step to SKIP`

Logged at debug log level 40. This debug message is printed when a callout installed on the `pkt4_send` hook point sets the next step to `SKIP`. For this particular hook point, this setting instructs the server to drop the packet. This means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease).

## 8.78 DHCP4\_HOOK\_SUBNET4\_SELECT\_4O6\_PARKING\_LOT\_FULL

`The parked-packet-limit %1, has been reached, dropping query: %2`

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the `parked-packet-limit` global parameter. This can occur when `kea-dhcp4` is using hook libraries (e.g. `radius`) that implement the `"subnet4_select"` callout and DHCP4O6 client queries are arriving faster than those callouts can fulfill them.

## 8.79 DHCP4\_HOOK\_SUBNET4\_SELECT\_DROP

`%1: packet was dropped, because a callout set the next step to 'drop'`

Logged at debug log level 40. This debug message is printed when a callout installed on the `subnet4_select` hook point sets the next step to `'drop'` value. For this particular hook point, the setting to that value instructs the server to drop the received packet. The argument specifies the client and transaction identification information.

## 8.80 DHCP4\_HOOK\_SUBNET4\_SELECT\_PARK

`%1: packet was parked`

Logged at debug log level 40. This debug message is printed when a callout installed on the `subnet4_select` hook point set the park flag. The argument holds the client and transaction identification information.



## 8.81 DHCP4\_HOOK\_SUBNET4\_SELECT\_PARKING\_LOT\_FULL

```
The parked-packet-limit %1, has been reached, dropping query: %2
```

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. radius) that implement the "subnet4\_select" callout and client queries are arriving faster than those callouts can fulfill them.

## 8.82 DHCP4\_HOOK\_SUBNET4\_SELECT\_SKIP

```
%1: no subnet was selected, because a callout set the next skip flag
```

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4\_select hook point sets the next step to SKIP value. For this particular hook point, the setting of the flag instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses will be assigned. The argument specifies the client and transaction identification information.

## 8.83 DHCP4\_HOOK\_SUBNET6\_SELECT\_PARKING\_LOT\_FULL

```
The parked-packet-limit %1, has been reached, dropping query: %2
```

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. radius) that implement the "subnet6\_select" callout and client queries are arriving faster than those callouts can fulfill them.

## 8.84 DHCP4\_INFORM\_DIRECT\_REPLY

```
%1: DHCPACK in reply to the DHCPINFORM will be sent directly to %2 over %3
```

Logged at debug log level 50. This debug message is issued when the DHCPACK will be sent directly to the client, rather than via a relay. The first argument contains the client and transaction identification information. The second argument contains the client's IPv4 address to which the response will be sent. The third argument contains the local interface name.

## 8.85 DHCP4\_INIT\_FAIL

```
failed to initialize Kea server: %1
```

The server has failed to initialize. This may be because the configuration was not successful, or it encountered any other critical error on startup. Attached error message provides more details about the issue.

## 8.86 DHCP4\_INIT\_REBOOT

```
%1: client is in INIT-REBOOT state and requests address %2
```

This informational message is issued when the client is in the INIT-REBOOT state and is requesting an IPv4 address it is using to be allocated for it. The first argument includes the client and transaction identification information. The second argument specifies the requested IPv4 address.

## 8.87 DHCP4\_LEASE\_ALLOC

```
%1: lease %2 has been allocated for %3 seconds
```

This informational message indicates that the server successfully granted a lease in response to client's DHCPREQUEST message. The lease information will be sent to the client in the DHCPACK message. The first argument contains the client and the transaction identification information. The second argument contains the allocated IPv4 address. The third argument is the validity lifetime.

## 8.88 DHCP4\_LEASE\_OFFER

```
%1: lease %2 will be offered
```

This informational message indicates that the server has found the lease to be offered to the client. It is up to the client to choose one server out of those which offered leases and continue allocation with that server. The first argument specifies the client and the transaction identification information. The second argument specifies the IPv4 address to be offered.

## 8.89 DHCP4\_LEASE\_REUSE

```
%1: lease %2 has been reused for %3 seconds
```

This informational message indicates that the server successfully reused a lease in response to client's message. The lease information will be sent to the client in the DHCPACK message. The first argument contains the client and the transaction identification information. The second argument contains the allocated IPv4 address. The third argument is the validity lifetime.

## 8.90 DHCP4\_MULTI\_THREADING\_INFO

```
enabled: %1, number of threads: %2, queue size: %3
```

This is a message listing some information about the multi-threading parameters with which the server is running.

## 8.91 DHCP4\_NCR\_CREATION\_FAILED

```
%1: failed to generate name change requests for DNS: %2
```

This message indicates that server was unable to generate NameChangeRequests which should be sent to the kea-dhcp\_ddns module to create new DNS records for the lease being acquired or to update existing records for the renewed lease. The first argument contains the client and transaction identification information. The second argument includes the reason for the failure.

## 8.92 DHCP4\_NOT\_RUNNING

```
DHCPv4 server is not running
```

A warning message is issued when an attempt is made to shut down the DHCPv4 server but it is not running.

## 8.93 DHCP4\_NO\_LEASE\_INIT\_REBOOT

```
%1: no lease for address %2 requested by INIT-REBOOT client
```

Logged at debug log level 50. This debug message is issued when the client being in the INIT-REBOOT state requested an IPv4 address but this client is unknown. The server will not respond. The first argument includes the client and the transaction id identification information. The second argument includes the IPv4 address requested by the client.

## 8.94 DHCP4\_OPEN\_SOCKET

```
opening service sockets on port %1
```

Logged at debug log level 0. A debug message issued during startup, this indicates that the DHCPv4 server is about to open sockets on the specified port.

## 8.95 DHCP4\_OPEN\_SOCKETS\_FAILED

```
maximum number of open service sockets attempts: %1, has been exhausted without success
```

This error indicates that the server failed to bind service sockets after making the maximum configured number of reconnect attempts. This might cause the server to shut down as specified in the configuration.

## 8.96 DHCP4\_OPEN\_SOCKETS\_NO\_RECONNECT\_CTL

unexpected error in bind service sockets.

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to bind to its service sockets if they are unavailable, and the server exits. This error should be reported.

## 8.97 DHCP4\_PACKET\_DROP\_0001

%1: failed to parse packet from %2 to %3, received over interface %4, reason: %5, %6

Logged at debug log level 15. The DHCPv4 server has received a packet that it is unable to interpret. The reason why the packet is invalid is included in the message.

## 8.98 DHCP4\_PACKET\_DROP\_0002

%1, from interface %2: no suitable subnet configured for a direct client

Logged at debug log level 15. This info message is logged when received a message from a directly connected client but there is no suitable subnet configured for the interface on which this message has been received. The IPv4 address assigned on this interface must belong to one of the configured subnets. Otherwise received message is dropped.

## 8.99 DHCP4\_PACKET\_DROP\_0003

%1, from interface %2: it contains a foreign server identifier

Logged at debug log level 15. This debug message is issued when received DHCPv4 message is dropped because it is addressed to a different server, i.e. a server identifier held by this message doesn't match the identifier used by our server. The arguments of this message hold the name of the transaction id and interface on which the message has been received.

## 8.100 DHCP4\_PACKET\_DROP\_0004

%1, from interface %2: missing msg-type option

Logged at debug log level 15. This is a debug message informing that incoming DHCPv4 packet did not have mandatory DHCP message type option and thus was dropped. The arguments specify the client and transaction identification information, as well as the interface on which the message has been received.

## 8.101 DHCP4\_PACKET\_DROP\_0005

```
%1: unrecognized type %2 in option 53
```

Logged at debug log level 15. This debug message indicates that the message type carried in DHCPv4 option 53 is unrecognized by the server. The valid message types are listed on the IANA website: <http://www.iana.org/assignments/bootp-dhcp-parameters/bootp-dhcp-parameters.xhtml#message-type-53>. The message will not be processed by the server. The arguments specify the client and transaction identification information, as well as the received message type.

## 8.102 DHCP4\_PACKET\_DROP\_0006

```
%1: unsupported DHCPv4 message type %2
```

Logged at debug log level 15. This debug message indicates that the message type carried in DHCPv4 option 53 is valid but the message will not be processed by the server. This includes messages being normally sent by the server to the client, such as DHCPOFFER, DHCPACK, DHCPNAK etc. The first argument specifies the client and transaction identification information. The second argument specifies the message type.

## 8.103 DHCP4\_PACKET\_DROP\_0007

```
%1: failed to process packet: %2
```

Logged at debug log level 15. This is a general catch-all message indicating that the processing of a received packet failed. The reason is given in the message. The server will not send a response but will instead ignore the packet. The first argument contains the client and transaction identification information. The second argument includes the details of the error.

## 8.104 DHCP4\_PACKET\_DROP\_0008

```
%1: DHCP service is globally disabled
```

Logged at debug log level 15. This debug message is issued when a packet is dropped because the DHCP service has been temporarily disabled. This affects all received DHCP packets. The service may be enabled by the "dhcp-enable" control command or automatically after a specified amount of time since receiving "dhcp-disable" command.

## 8.105 DHCP4\_PACKET\_DROP\_0009

```
%1: Option 53 missing (no DHCP message type), is this a BOOTP packet?
```

Logged at debug log level 15. This debug message is issued when a packet is dropped because it did contain option 53 and thus has no DHCP message type. The most likely explanation is that it was BOOTP packet.

## 8.106 DHCP4\_PACKET\_DROP\_0010

```
dropped as member of the special class 'DROP': %1, %2
```

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified into the special class 'DROP' and dropped. The packet details are displayed.

## 8.107 DHCP4\_PACKET\_DROP\_0011

```
dropped as sent by the same client than a packet being processed by another thread:↵  
↵dropped %1, %2 by thread %3 as duplicate of %4, %5 processed by %6
```

Logged at debug log level 15. Currently multi-threading processing avoids races between packets sent by a client using the same client id option by dropping new packets until processing is finished. Packet details and thread identifiers are included for both packets in this warning message.

## 8.108 DHCP4\_PACKET\_DROP\_0012

```
dropped as sent by the same client than a packet being processed by another thread:↵  
↵dropped %1, %2 by thread %3 as duplicate of %4, %5 processed by %6
```

Logged at debug log level 15. Currently multi-threading processing avoids races between packets sent by a client using the same hardware address by dropping new packets until processing is finished. Packet details and thread identifiers are included for both packets in this warning message.

## 8.109 DHCP4\_PACKET\_DROP\_0013

```
dropped as member of the special class 'DROP' after host reservation lookup: %1, %2
```

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after host reservation lookup into the special class 'DROP' and dropped. The packet details are displayed.

## 8.110 DHCP4\_PACKET\_DROP\_0014

```
dropped as member of the special class 'DROP' after early global host reservations.↵  
↵lookup: %1, %2
```

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after early global host reservations lookup into the special class 'DROP' and dropped. The packet details are displayed.

## 8.111 DHCP4\_PACKET\_NAK\_0001

```
%1: failed to select a subnet for incoming packet, src %2, type %3
```

This error message is output when a packet was received from a subnet for which the DHCPv4 server has not been configured. The most probable cause is a misconfiguration of the server. The first argument contains the client and transaction identification information. The second argument contains the source IPv4 address of the packet. The third argument contains the name of the received packet.

## 8.112 DHCP4\_PACKET\_NAK\_0002

```
%1: invalid address %2 requested by INIT-REBOOT
```

Logged at debug log level 50. This debug message is issued when the client being in the INIT-REBOOT state requested an IPv4 address which is not assigned to him. The server will respond to this client with DHCPNAK. The first argument contains the client and the transaction identification information. The second arguments holds the IPv4 address requested by the client.

## 8.113 DHCP4\_PACKET\_NAK\_0003

```
%1: failed to advertise a lease, client sent ciaddr %2, requested-ip-address %3
```

Logged at debug log level 50. This message indicates that the server has failed to offer a lease to the specified client after receiving a DISCOVER message from it. There are many possible reasons for such a failure. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

## 8.114 DHCP4\_PACKET\_NAK\_0004

```
%1: failed to grant a lease, client sent ciaddr %2, requested-ip-address %3
```

Logged at debug log level 50. This message indicates that the server failed to grant a lease to the specified client after receiving a REQUEST message from it. There are many possible reasons for such a failure. Additional messages will indicate the reason. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

## 8.115 DHCP4\_PACKET\_OPTIONS\_SKIPPED

```
%1: An error unpacking an option, caused subsequent options to be skipped: %2
```

Logged at debug log level 50. A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the packet. The server will server will still attempt to service the packet.

## 8.116 DHCP4\_PACKET\_PACK

```
%1: preparing on-wire format of the packet to be sent
```

Logged at debug log level 50. This debug message is issued when the server starts preparing the on-wire format of the packet to be sent back to the client. The argument specifies the client and the transaction identification information.

## 8.117 DHCP4\_PACKET\_PACK\_FAIL

```
%1: preparing on-wire-format of the packet to be sent failed %2
```

This error message is issued when preparing an on-wire format of the packet has failed. The first argument identifies the client and the DHCP transaction. The second argument includes the error string.

## 8.118 DHCP4\_PACKET\_PROCESS\_EXCEPTION

```
%1: exception occurred during packet processing
```

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

## 8.119 DHCP4\_PACKET\_PROCESS\_EXCEPTION\_MAIN

```
exception occurred during packet processing
```

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

## 8.120 DHCP4\_PACKET\_PROCESS\_STD\_EXCEPTION

```
%1: exception occurred during packet processing: %2
```

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.



## 8.121 DHCP4\_PACKET\_PROCESS\_STD\_EXCEPTION\_MAIN

```
exception occurred during packet processing: %1
```

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

## 8.122 DHCP4\_PACKET\_QUEUE\_FULL

```
multi-threading packet queue is full
```

Logged at debug log level 40. A debug message noting that the multi-threading packet queue is full so the oldest packet of the queue was dropped to make room for the received one.

## 8.123 DHCP4\_PACKET\_RECEIVED

```
%1: %2 (type %3) received from %4 to %5 on interface %6
```

An INFO message noting that the server has received the specified type of packet on the specified interface. The first argument specifies the client and transaction identification information. The second and third argument specify the name of the DHCPv4 message and its numeric type respectively. The remaining arguments specify the source IPv4 address, destination IPv4 address and the name of the interface on which the message has been received.

## 8.124 DHCP4\_PACKET\_SEND

```
%1: trying to send packet %2 (type %3) from %4:%5 to %6:%7 on interface %8
```

An INFO message noting that the server is attempting to send the specified type of packet. The arguments specify the client identification information (HW address and client identifier), DHCP message name and type, source IPv4 address and port, destination IPv4 address and port and the interface name. This debug message is issued when the server is trying to send the response to the client. When the server is using an UDP socket to send the packet there are cases when this operation may be unsuccessful and no error message will be displayed. One such situation occurs when the server is unicasting the response to the 'ciaddr' of a DHCPINFORM message. This often requires broadcasting an ARP message to obtain the link layer address of the unicast destination. If broadcast ARP messages are blocked in the network, according to the firewall policy, the ARP message will not cause a response. Consequently, the response to the DHCPINFORM will not be sent. Since the ARP communication is under the OS control, Kea is not notified about the drop of the packet which it is trying to send and it has no means to display an error message.

## 8.125 DHCP4\_PACKET\_SEND\_FAIL

```
%1: failed to send DHCPv4 packet: %2
```

This error is output if the DHCPv4 server fails to send an assembled DHCP message to a client. The first argument includes the client and the transaction identification information. The second argument includes the reason for failure.

## 8.126 DHCP4\_PARSER\_COMMIT\_EXCEPTION

```
parser failed to commit changes
```

On receipt of message containing details to a change of the DHCPv4 server configuration, a set of parsers were successfully created, but one of them failed to commit its changes due to a low-level system exception being raised. Additional messages may be output indicating the reason.

## 8.127 DHCP4\_PARSER\_COMMIT\_FAIL

```
parser failed to commit changes: %1
```

On receipt of message containing details to a change of the DHCPv4 server configuration, a set of parsers were successfully created, but one of them failed to commit its changes. The reason for the failure is given in the message.

## 8.128 DHCP4\_PARSER\_EXCEPTION

```
failed to create or run parser for configuration element %1
```

On receipt of message containing details to a change of its configuration, the DHCPv4 server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The message has been output in response to a non-Kea exception being raised. Additional messages may give further information.

## 8.129 DHCP4\_PARSER\_FAIL

```
failed to create or run parser for configuration element %1: %2
```

On receipt of message containing details to a change of its configuration, the DHCPv4 server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

## 8.130 DHCP4\_POST\_ALLOCATION\_NAME\_UPDATE\_FAIL

```
%1: failed to update hostname %2 in a lease after address allocation: %3
```

This message indicates the failure when trying to update the lease and/or options in the server's response with the hostname generated by the server or reserved for the client belonging to a shared network. The latter is the case when the server dynamically switches to another subnet (than initially selected for allocation) from the same shared network.

## 8.131 DHCP4\_QUERY\_DATA

```
%1, packet details: %2
```

Logged at debug log level 55. A debug message printing the details of the received packet. The first argument includes the client and the transaction identification information.

## 8.132 DHCP4\_QUERY\_LABEL

```
received query: %1
```

This information message indicates that a query was received. It displays the client and the transaction identification information.

## 8.133 DHCP4\_RECLAIM\_EXPIRED\_LEASES\_FAIL

```
failed to reclaim expired leases: %1
```

This error message indicates that the reclaim expired leases operation failed and provides the cause of failure.

## 8.134 DHCP4\_RECOVERED\_STASHED\_RELAY\_AGENT\_INFO

```
recovered for query %1 relay agent option from lease %2: %3
```

Logged at debug log level 55. This debug message indicates that agent options were stashed in the lease for the client address of the request and were recovered. The first argument includes the request information, the second the client address and the last argument the content of the dhcp-agent-options option.

## 8.135 DHCP4\_RELEASE

```
%1: address %2 was released properly.
```

Logged at debug log level 50. This informational message indicates that an address was released properly. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

## 8.136 DHCP4\_RELEASE\_DELETED

```
%1: address %2 was deleted on release.
```

This informational message indicates that an address was deleted on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

## 8.137 DHCP4\_RELEASE\_EXCEPTION

```
%1: while trying to release address %2 an exception occurred: %3
```

This message is output when an error was encountered during an attempt to process a DHCPRELEASE message. The error will not affect the client, which does not expect any response from the server for DHCPRELEASE messages. Depending on the nature of problem, it may affect future server operation. The first argument includes the client and the transaction identification information. The second argument includes the IPv4 address which release was attempted. The last argument includes the detailed error description.

## 8.138 DHCP4\_RELEASE\_EXPIRED

```
%1: address %2 expired on release.
```

This informational message indicates that an address expired on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

## 8.139 DHCP4\_RELEASE\_FAIL

```
%1: failed to remove lease for address %2
```

Logged at debug log level 50. This error message indicates that the software failed to remove a lease from the lease database. It is probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address which release was attempted.

## 8.140 DHCP4\_RELEASE\_FAIL\_NO\_LEASE

```
%1: client is trying to release non-existing lease %2
```

Logged at debug log level 50. This debug message is printed when client attempts to release a lease, but no such lease is known to the server. The first argument contains the client and transaction identification information. The second argument contains the IPv4 address which the client is trying to release.

## 8.141 DHCP4\_RELEASE\_FAIL\_WRONG\_CLIENT

```
%1: client is trying to release the lease %2 which belongs to a different client
```

Logged at debug log level 50. This debug message is issued when a client is trying to release the lease for the address which is currently used by another client, i.e. the 'client identifier' or 'chaddr' doesn't match between the client and the lease. The first argument includes the client and the transaction identification information. The second argument specifies the leased address.

## 8.142 DHCP4\_REQUEST

```
%1: server is processing DHCPREQUEST with hint=%2
```

Logged at debug log level 50. This is a debug message that indicates the processing of a received DHCPREQUEST message. The first argument contains the client and the transaction identification information. The second argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

## 8.143 DHCP4\_REQUIRED\_CLASS\_EVAL\_ERROR

```
%1: Expression '%2' evaluated to %3
```

This error message indicates that there a problem was encountered while evaluating an expression of a required client class that was marked as required. A description of the problem is printed.

## 8.144 DHCP4\_REQUIRED\_CLASS\_EVAL\_RESULT

```
%1: Expression '%2' evaluated to %3
```

Logged at debug log level 50. This debug message indicates that the expression of a required client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

## 8.145 DHCP4\_RESERVATIONS\_LOOKUP\_FIRST\_ENABLED

Multi-threading is enabled and host reservations lookup is always performed first.

This is a message informing that host reservations lookup is performed before lease lookup when multi-threading is enabled overwriting configured value.

## 8.146 DHCP4\_RESERVED\_HOSTNAME\_ASSIGNED

%1: server assigned reserved hostname %2

Logged at debug log level 55. This debug message is issued when the server found a hostname reservation for a client and uses this reservation in a hostname option sent back to this client. The reserved hostname is qualified with a value of 'ddns-qualifying-suffix' parameter, if this parameter is specified.

## 8.147 DHCP4\_RESPONSE\_DATA

%1: responding with packet %2 (type %3), packet details: %4

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

## 8.148 DHCP4\_RESPONSE\_FQDN\_DATA

%1: including FQDN option in the server's response: %2

Logged at debug log level 55. This debug message is issued when the server is adding the Client FQDN option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the FQDN option may be modified by the server when the lease is acquired for the client.

## 8.149 DHCP4\_RESPONSE\_HOSTNAME\_DATA

%1: including Hostname option in the server's response: %2

Logged at debug log level 55. This debug message is issued when the server is adding the Hostname option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the Hostname option may be modified by the server when the lease is acquired for the client.

## 8.150 DHCP4\_RESPONSE\_HOSTNAME\_GENERATE

```
%1: server has generated hostname %2 for the client
```

Logged at debug log level 50. This debug message includes the auto-generated hostname which will be used for the client which message is processed. Hostnames may need to be generated when required by the server's configuration or when the client hasn't supplied its hostname. The first argument includes the client and the transaction identification information. The second argument holds the generated hostname.

## 8.151 DHCP4\_SERVER\_FAILED

```
server failed: %1
```

The DHCPv4 server has encountered a fatal error and is terminating. The reason for the failure is included in the message.

## 8.152 DHCP4\_SERVER\_INITIATED\_DECLINE

```
%1: Lease for addr %2 has been found to be already in use. The lease will be unavailable ↵  
↵ for %3 seconds.
```

This informational message is printed when the server has detected via ICMP ECHO (i.e. ping check) or other means that a lease which should be free to offer is actually in use. This message may indicate a misconfiguration in a network or more likely a device that is using an address that it is not supposed to use. The server will fully recover from this situation, but if the underlying problem of a misconfigured or rogue device is not solved, this address may be declined again in the future.

## 8.153 DHCP4\_SERVER\_INITIATED\_DECLINE\_ADD\_FAILED

```
%1: error adding a lease for address %2
```

This error message indicates that the server failed to add a DECLINED lease to the lease store. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address for which the decline was attempted.

## 8.154 DHCP4\_SERVER\_INITIATED\_DECLINE\_RESOURCE\_BUSY

```
%1: error declining a lease for address %2
```

This error message indicates that while one server thread was attempting to mark a lease as DECLINED, it was already locked by another thread. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address for which the decline was attempted.

## 8.155 DHCP4\_SERVER\_INITIATED\_DECLINE\_UPDATE\_FAILED

```
%1: error updating lease for address %2
```

This error message indicates that the server failed to update a lease in the lease store to the DECLINED state. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address for which the decline was attempted.

## 8.156 DHCP4\_SHUTDOWN

```
server shutdown
```

Logged at debug log level 40. The DHCPv4 server has terminated normally.

## 8.157 DHCP4\_SHUTDOWN\_REQUEST

```
shutdown of server requested
```

Logged at debug log level 40. This debug message indicates that a shutdown of the DHCPv4 server has been requested via a call to the 'shutdown' method of the core Dhcpv4Srv object.

## 8.158 DHCP4\_SRV\_CONSTRUCT\_ERROR

```
error creating Dhcpv4Srv object, reason: %1
```

This error message indicates that during startup, the construction of a core component within the DHCPv4 server (the Dhcpv4 server object) has failed. As a result, the server will exit. The reason for the failure is given within the message.

## 8.159 DHCP4\_SRV\_D2STOP\_ERROR

```
error stopping IO with DHCP_DDNS during shutdown: %1
```

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv4 server and the DHCP\_DDNS server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.



## 8.160 DHCP4\_SRV\_DHCP4O6\_ERROR

```
error stopping IO with DHCPv4o6 during shutdown: %1
```

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv4 server and the DHCPv4o6 server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

## 8.161 DHCP4\_SRV\_UNLOAD\_LIBRARIES\_ERROR

```
error unloading hooks libraries during shutdown: %1
```

This error message indicates that during shutdown, unloading hooks libraries failed to close them. If the list of libraries is empty it is a programmatic error in the server code. If it is not empty it could be a programmatic error in one of the hooks libraries which could lead to a crash during finalization.

## 8.162 DHCP4\_STARTED

```
Kea DHCPv4 server version %1 started
```

This informational message indicates that the DHCPv4 server has processed all configuration information and is ready to process DHCPv4 packets. The version is also printed.

## 8.163 DHCP4\_STARTING

```
Kea DHCPv4 server version %1 (%2) starting
```

This informational message indicates that the DHCPv4 server has processed any command-line switches and is starting. The version is also printed.

## 8.164 DHCP4\_START\_INFO

```
pid: %1, server port: %2, client port: %3, verbose: %4
```

Logged at debug log level 0. This is a debug message issued during the DHCPv4 server startup. It lists some information about the parameters with which the server is running.

## 8.165 DHCP4\_SUBNET\_DATA

```
%1: the selected subnet details: %2
```

Logged at debug log level 55. This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second arguments includes the subnet details.

## 8.166 DHCP4\_SUBNET\_DYNAMICALLY\_CHANGED

```
%1: changed selected subnet %2 to subnet %3 from shared network %4 for client assignments
```

Logged at debug log level 45. This debug message indicates that the server is using another subnet than initially selected for client assignments. This newly selected subnet belongs to the same shared network as the original subnet. Some reasons why the new subnet was selected include: address pool exhaustion in the original subnet or the fact that the new subnet includes some static reservations for this client.

## 8.167 DHCP4\_SUBNET\_SELECTED

```
%1: the subnet with ID %2 was selected for client assignments
```

Logged at debug log level 45. This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

## 8.168 DHCP4\_SUBNET\_SELECTION\_FAILED

```
%1: failed to select subnet for the client
```

Logged at debug log level 50. This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The server will not be able to offer any lease to the client and will drop its message if the received message was DHCPDISCOVER, and will send DHCPNAK if the received message was DHCPREQUEST. The argument includes the client and the transaction identification information.

## 8.169 DHCP4\_TESTING\_MODE\_SEND\_TO\_SOURCE\_ENABLED

```
All packets will be send to source address of an incoming packet - use only for testing
```

This message is printed then KEA\_TEST\_SEND\_RESPONSES\_TO\_SOURCE environment variable is set. It's causing Kea to send packets to source address of incoming packet. Usable just in testing environment to simulate multiple subnet traffic from single source.

## 8.170 DHCP4\_UNKNOWN\_ADDRESS\_REQUESTED

```
%1: client requested an unknown address, client sent ciaddr %2, requested-ip-address %3
```

Logged at debug log level 50. This message indicates that the client requested an address that does not belong to any dynamic pools managed by this server. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

## 8.171 DHCP4\_V6\_ONLY\_PREFERRED\_MISSING\_IN\_ACK

```
v6-only-preferred option missing in 0.0.0.0 reply to query: %1
```

An DHCPACK for the 0.0.0.0 address was generated for a client requesting the v6-only-preferred (108) option but the option is not in the response as expected: the erroneous response is dropped, the request query is displayed.



## 9.1 DHCP6\_ADD\_GLOBAL\_STATUS\_CODE

```
%1: adding Status Code to DHCPv6 packet: %2
```

Logged at debug log level 50. This message is logged when the server is adding the top-level Status Code option. The first argument includes the client and the transaction identification information. The second argument includes the details of the status code.

## 9.2 DHCP6\_ADD\_STATUS\_CODE\_FOR\_IA

```
%1: adding Status Code to IA with iaid=%2: %3
```

Logged at debug log level 50. This message is logged when the server is adding the Status Code option to an IA. The first argument includes the client and the transaction identification information. The second argument specifies the IAID. The third argument includes the details of the status code.

## 9.3 DHCP6\_ALREADY\_RUNNING

```
%1 already running? %2
```

This is an error message that occurs when the DHCPv6 server encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of the server using the same configuration file. It is possible, though unlikely that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than the server. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCPv6 process name, the second contains the PID and PID file.

## 9.4 DHCP6\_BUFFER\_RECEIVED

```
received buffer from %1:%2 to %3:%4 over interface %5
```

Logged at debug log level 40. This debug message is logged when the server has received a packet over the socket. When the message is logged the contents of the received packet hasn't been parsed yet. The only available information is the interface and the source and destination addresses/ports.

## 9.5 DHCP6\_BUFFER\_UNPACK

```
parsing buffer received from %1 to %2 over interface %3
```

Logged at debug log level 50. This debug message is issued when the server starts parsing the received buffer holding the DHCPv6 message. The arguments specify the source and destination addresses as well as the interface over which the buffer has been received.

## 9.6 DHCP6\_BUFFER\_WAIT\_SIGNAL

```
signal received while waiting for next packet
```

Logged at debug log level 50. This debug message is issued when the server was waiting for the packet, but the wait has been interrupted by the signal received by the process. The signal will be handled before the server starts waiting for next packets.

## 9.7 DHCP6\_CB\_ON\_DEMAND\_FETCH\_UPDATES\_FAIL

```
error on demand attempt to fetch configuration updates from the configuration_
↪backend(s): %1
```

This error message is issued when the server attempted to fetch configuration updates from the database and this on demand attempt failed. The sole argument which is returned to the config-backend-pull command caller too contains the reason for failure.

## 9.8 DHCP6\_CB\_PERIODIC\_FETCH\_UPDATES\_FAIL

```
error on periodic attempt to fetch configuration updates from the configuration_
↪backend(s): %1
```

This error message is issued when the server attempted to fetch configuration updates from the database and this periodic attempt failed. The server will re-try according to the configured value of the config-fetch-wait-time parameter. The sole argument contains the reason for failure.

## 9.9 DHCP6\_CB\_PERIODIC\_FETCH\_UPDATES\_RETRIES\_EXHAUSTED

```
maximum number of configuration fetch attempts: 10, has been exhausted without success
```

This error indicates that the server has made a number of unsuccessful periodic attempts to fetch configuration updates from a configuration backend. The server will continue to operate but won't make any further attempts to fetch configuration updates. The administrator must fix the configuration in the database and reload (or restart) the server.

## 9.10 DHCP6\_CLASSES\_ASSIGNED

```
%1: client packet has been assigned on %2 message to the following classes: %3
```

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument specifies the DHCPv6 message type. The third argument includes all classes to which the packet has been assigned.

## 9.11 DHCP6\_CLASSES\_ASSIGNED\_AFTER\_SUBNET\_SELECTION

```
%1: client packet has been assigned to the following classes: %2
```

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes all classes to which the packet has been assigned.

## 9.12 DHCP6\_CLASS\_ASSIGNED

```
%1: client packet has been assigned to the following class: %2
```

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified class. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes the new class to which the packet has been assigned.

## 9.13 DHCP6\_CLASS\_UNCONFIGURED

```
%1: client packet belongs to an unconfigured class: %2
```

Logged at debug log level 40. This debug message informs that incoming packet belongs to a class which cannot be found in the configuration. Either a hook written before the classification was added to Kea is used, or class naming is inconsistent.

## 9.14 DHCP6\_CLASS\_UNDEFINED

```
required class %1 has no definition
```

Logged at debug log level 40. This debug message informs that a class is listed for required evaluation but has no definition.

## 9.15 DHCP6\_CLASS\_UNTESTABLE

```
required class %1 has no test expression
```

Logged at debug log level 40. This debug message informs that a class was listed for required evaluation but its definition does not include a test expression to evaluate.

## 9.16 DHCP6\_CONFIG\_COMPLETE

```
DHCPv6 server has completed configuration: %1
```

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

## 9.17 DHCP6\_CONFIG\_LOAD\_FAIL

```
configuration error using file: %1, reason: %2
```

This error message indicates that the DHCPv6 configuration has failed. If this is an initial configuration (during server's startup) the server will fail to start. If this is a dynamic reconfiguration attempt the server will continue to use an old configuration.

## 9.18 DHCP6\_CONFIG\_PACKET\_QUEUE

```
DHCPv6 packet queue info after configuration: %1
```

This informational message is emitted during DHCPv6 server configuration, immediately after configuring the DHCPv6 packet queue. The information shown depends upon the packet queue type selected.



## 9.19 DHCP6\_CONFIG\_RECEIVED

```
received configuration: %1
```

Logged at debug log level 10. A debug message listing the configuration received by the DHCPv6 server. The source of that configuration depends on used configuration backend.

## 9.20 DHCP6\_CONFIG\_START

```
DHCPv6 server is processing the following configuration: %1
```

Logged at debug log level 10. This is a debug message that is issued every time the server receives a configuration. That happens start up and also when a server configuration change is committed by the administrator.

## 9.21 DHCP6\_CONFIG\_SYNTAX\_WARNING

```
configuration syntax warning: %1
```

This warning message indicates that the DHCPv6 configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

## 9.22 DHCP6\_CONFIG\_UNRECOVERABLE\_ERROR

```
DHCPv6 server new configuration failed with an error which cannot be recovered
```

This fatal error message is issued when a new configuration raised an error which cannot be recovered. A correct configuration must be applied as soon as possible as the server is no longer working. The configuration can be fixed in several ways. If the control channel is open, config-set with a valid configuration can be used. Alternatively, the original config file on disk could be fixed and SIGHUP signal could be sent (or the config-reload command issued). Finally, the server could be restarted completely.

## 9.23 DHCP6\_CONFIG\_UNSUPPORTED\_OBJECT

```
DHCPv6 server configuration includes an unsupported object: %1
```

This error message is issued when the configuration includes an unsupported object (i.e. a top level element).

## 9.24 DHCP6\_DB\_RECONNECT\_DISABLED

```
database reconnect is disabled: max-reconnect-tries %1, reconnect-wait-time %2
```

This is an informational message indicating that connectivity to either the lease or host database or both and that automatic reconnect is not enabled.

## 9.25 DHCP6\_DB\_RECONNECT\_FAILED

```
maximum number of database reconnect attempts: %1, has been exhausted without success
```

This error indicates that the server failed to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. This might cause the server to shut down as specified in the configuration. Loss of connectivity is typically a network or database server issue.

## 9.26 DHCP6\_DB\_RECONNECT\_LOST\_CONNECTION

```
database connection lost.
```

This info message indicates that the connection has been lost and the dhcp service might have been disabled, as specified in the configuration, in order to try to recover the connection.

## 9.27 DHCP6\_DB\_RECONNECT\_NO\_DB\_CTL

```
unexpected error in database reconnect
```

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to reconnect to its databases if connectivity is lost, and the server exits. This error should be reported.

## 9.28 DHCP6\_DB\_RECONNECT\_SUCCEEDED

```
database connection recovered.
```

This info message indicates that the connection has been recovered and the dhcp service has been restored.

## 9.29 DHCP6\_DDNS\_CREATE\_ADD\_NAME\_CHANGE\_REQUEST

```
%1: created name change request: %2
```

Logged at debug log level 50. This debug message is logged when the new NameChangeRequest has been created to perform the DNS Update, which adds new RRs.

## 9.30 DHCP6\_DDNS\_FQDN\_GENERATED

```
%1: generated FQDN for the client: %2
```

Logged at debug log level 55. This debug message is logged when the server generated FQDN (name) for the client which message is processed. The names may be generated by the server when required by the server's policy or when the client doesn't provide any specific FQDN in its message to the server. The first argument includes the client and transaction identification information. The second argument includes the generated FQDN.

## 9.31 DHCP6\_DDNS\_GENERATED\_FQDN\_UPDATE\_FAIL

```
%1: failed to update the lease using address %2, after generating FQDN for a client,↵
↵reason: %3
```

This message indicates the failure when trying to update the lease and/or options in the server's response with the hostname generated by the server from the acquired address. The first argument includes the client and the transaction identification information. The second argument is a leased address. The third argument includes the reason for the failure.

## 9.32 DHCP6\_DDNS\_GENERATE\_FQDN

```
%1: client did not send a FQDN option; FQDN will be
```

Logged at debug log level 50. generated for the client. This debug message is issued when the server did not receive a FQDN option from the client and client name replacement is enabled. This provides a means to create DNS entries for unsophisticated clients.

## 9.33 DHCP6\_DDNS\_RECEIVE\_FQDN

```
%1: received DHCPv6 Client FQDN option: %2
```

Logged at debug log level 50. This debug message is logged when server has found the DHCPv6 Client FQDN Option sent by a client and started processing it. The first argument includes the client and transaction identification information. The second argument includes the received FQDN.

## 9.34 DHCP6\_DDNS\_REMOVE\_OLD\_LEASE\_FQDN

```
%1: FQDN for a lease: %2 has changed. New values: hostname = %3, reverse mapping = %4,↵
↵forward mapping = %5
```

Logged at debug log level 50. This debug message is logged during lease renewal when an old lease that is no longer being offered has a different FQDN than the renewing lease. Thus the old DNS entries need to be removed. The first argument includes the client and the transaction identification information. The second argument holds the details about the lease for which the FQDN information and/or mappings have changed. The remaining arguments hold the new FQDN information and flags for mappings.

## 9.35 DHCP6\_DDNS\_REQUEST\_SEND\_FAILED

failed sending a request to kea-dhcp-ddns, error: %1, ncr: %2

This error message indicates that IPv6 DHCP server failed to send a DDNS update request to the DHCP-DDNS server. This is most likely a configuration or networking error.

## 9.36 DHCP6\_DDNS\_RESPONSE\_FQDN\_DATA

%1: including FQDN option in the server's response: %2

Logged at debug log level 50. This debug message is issued when the server is adding the Client FQDN option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the FQDN option may be modified by the server when the lease is acquired for the client.

## 9.37 DHCP6\_DECLINE\_FAIL

%1: error on decline lease for address %2: %3

This error message indicates that the software failed to decline a lease from the lease database due to an error during a database operation. The first argument includes the client and the transaction identification information. The second argument holds the IPv6 address which decline was attempted. The last one contains the reason for failure.

## 9.38 DHCP6\_DECLINE\_FAIL\_DUID\_MISMATCH

Client %1 sent DECLINE for address %2, but it belongs to client with DUID %3

This informational message is printed when a client attempts to decline a lease, but that lease belongs to a different client. The decline request will be rejected.

## 9.39 DHCP6\_DECLINE\_FAIL\_IAID\_MISMATCH

Client %1 sent DECLINE for address %2, but used a wrong IAID (%3), instead of expected %4

This informational message is printed when a client attempts to decline a lease. The server has a lease for this address, it belongs to this client, but the recorded IAID does not match what client has sent. This means the server will reject this Decline.

## 9.40 DHCP6\_DECLINE\_FAIL\_LEASE\_WITHOUT\_DUID

```
Client %1 sent DECLINE for address %2, but the associated lease has no DUID
```

This error condition likely indicates database corruption, as every IPv6 lease is supposed to have a DUID, even if it is an empty one.

## 9.41 DHCP6\_DECLINE\_FAIL\_NO\_LEASE

```
Client %1 sent DECLINE for address %2, but there's no lease for it
```

This informational message is printed when a client tried to decline an address, but the server has no lease for said address. This means that the server's and client's perception of the leases are different. The likely causes of this could be: a confused (e.g. skewed clock) or broken client (e.g. client moved to a different location and didn't notice) or possibly an attack (a rogue client is trying to decline random addresses). The server will inform the client that his decline request was rejected and client should be able to recover from that.

## 9.42 DHCP6\_DECLINE\_LEASE

```
Client %1 sent DECLINE for address %2 and the server marked it as declined. The lease_↵  
↵will be recovered in %3 seconds.
```

This informational message indicates that the client leased an address, but discovered that it is being used by some other device and reported this to the server by sending a Decline message. The server marked the lease as declined. This likely indicates a misconfiguration in the network. Either the server is configured with an incorrect pool or there are devices that have statically assigned addresses that are supposed to be assigned by the DHCP server. Both client (will request a different address) and server (will recover the lease after decline-probation-time elapses) will recover automatically. However, if the underlying problem is not solved, the conditions leading to this message may reappear.

## 9.43 DHCP6\_DECLINE\_PROCESS\_IA

```
Processing of IA (IAID: %1) from client %2 started.
```

Logged at debug log level 50. This debug message is printed when the server starts processing an IA\_NA option received in Decline message. It's expected that the option will contain an address that is being declined. Specific information will be printed in a separate message.

## 9.44 DHCP6\_DEVELOPMENT\_VERSION

```
This software is a development branch of Kea. It is not recommended for production use.
```

This warning message is displayed when the version is a development (vs stable) one: the second number of the version is odd.

## 9.45 DHCP6\_DHCP4O6\_PACKET\_RECEIVED

```
received DHCPv4o6 packet from DHCPv4 server (type %1) for %2 port %3 on interface %4
```

Logged at debug log level 40. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication.

## 9.46 DHCP6\_DHCP4O6\_RECEIVE\_FAIL

```
failed to receive DHCPv4o6: %1
```

Logged at debug log level 50. This debug message indicates the inter-process communication with the DHCPv4 server failed. The reason for the error is included in the message.

## 9.47 DHCP6\_DHCP4O6\_RECEIVING

```
receiving DHCPv4o6 packet from DHCPv4 server
```

Logged at debug log level 50. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication socket.

## 9.48 DHCP6\_DHCP4O6\_RESPONSE\_DATA

```
%1: responding with packet %2 (type %3), packet details: %4
```

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

## 9.49 DHCP6\_DHCP4O6\_SEND\_FAIL

```
%1: failed to send DHCPv4o6 packet: %2
```

This error is output if the IPv6 DHCP server fails to send an assembled DHCPv4o6 message to a client. The reason for the error is included in the message.

## 9.50 DHCP6\_DYNAMIC\_RECONFIGURATION

```
initiate server reconfiguration using file: %1, after receiving SIGHUP signal or config-  
↪reload command
```

This is the info message logged when the DHCPv6 server starts reconfiguration as a result of receiving SIGHUP signal or config-reload command.

## 9.51 DHCP6\_DYNAMIC\_RECONFIGURATION\_FAIL

```
dynamic server reconfiguration failed with file: %1
```

This is a fatal error message logged when the dynamic reconfiguration of the DHCP server failed.

## 9.52 DHCP6\_DYNAMIC\_RECONFIGURATION\_SUCCESS

```
dynamic server reconfiguration succeeded with file: %1
```

This is info message logged when the dynamic reconfiguration of the DHCP server succeeded.

## 9.53 DHCP6\_FLEX\_ID

```
%1: flexible identifier generated for incoming packet: %2
```

Logged at debug log level 40. This debug message is printed when host reservation type is set to flexible identifier and the expression specified in its configuration generated (was evaluated to) an identifier for incoming packet. This debug message is mainly intended as a debugging assistance for flexible identifier.

## 9.54 DHCP6\_HOOK\_BUFFER\_RCVD\_DROP

```
received buffer from %1 to %2 over interface %3 was dropped because a callout set the_  
↪drop flag
```

Logged at debug log level 15. This debug message is printed when a callout installed on buffer6\_receive hook point set the drop flag. For this particular hook point, the setting of the flag by a callout instructs the server to drop the packet. The arguments specify the source and destination address as well as the name of the interface over which the buffer has been received.

## 9.55 DHCP6\_HOOK\_BUFFER\_RCVD\_SKIP

```
received buffer from %1 to %2 over interface %3 is not parsed because a callout set the  
↪next step to SKIP
```

Logged at debug log level 50. This debug message is printed when a callout installed on `buffer6_receive` hook point set the next step status to skip. For this particular hook point, this value set by a callout instructs the server to not parse the buffer because it was already parsed by the hook. The arguments specify the source and destination address as well as the name of the interface over which the buffer has been received.

## 9.56 DHCP6\_HOOK\_BUFFER\_SEND\_SKIP

```
%1: prepared DHCPv6 response was dropped because a callout set the next step to SKIP
```

Logged at debug log level 40. This debug message is printed when a callout installed on `buffer6_send` hook point set the next step to SKIP value. For this particular hook point, the SKIP setting a callout instructs the server to drop the packet. Server completed all the processing (e.g. may have assigned, updated or released leases), but the response will not be sent to the client. The argument includes the client and transaction identification information.

## 9.57 DHCP6\_HOOK\_DDNS\_UPDATE

```
A hook has updated the DDNS parameters: hostname %1=>%2, forward update %3=>%4, reverse  
↪update %5=>%6
```

Logged at debug log level 15. This message indicates that there was a hook called on `ddns6_update` hook point and that hook updated the DDNS update parameters: hostname, or whether to conduct forward (A record) or reverse (PTR record) DDNS updates.

## 9.58 DHCP6\_HOOK\_DECLINE\_DROP

```
During Decline processing (client=%1, interface=%2, addr=%3) hook callout set next step  
↪to DROP, dropping packet.
```

Logged at debug log level 15. This message indicates that the server received DECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for the `lease6_decline` hook point and one of the callouts set next step status to DROP. The server will now abort processing of the packet as if it was never received. The lease will continue to be assigned to this client.



## 9.59 DHCP6\_HOOK\_DECLINE\_SKIP

During Decline processing (client=%1, interface=%2, addr=%3) hook callout set status to SKIP, skipping decline.

Logged at debug log level 50. This message indicates that the server received DECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for the lease6\_decline hook point and one of the callouts set next step status to SKIP. The server will skip the operation of moving the lease to the declined state and will continue processing the packet. In particular, it will send a REPLY message as if the decline actually took place.

## 9.60 DHCP6\_HOOK\_LEASE6\_RELEASE\_NA\_SKIP

%1: DHCPv6 address lease was not released because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the lease6\_release hook point set the next step to SKIP. For this particular hook point, this setting by a callout instructs the server to not release a lease. If a client requested the release of multiples leases (by sending multiple IA options), the server will retain this particular lease and proceed with other releases as usual. The argument holds the client and transaction identification information.

## 9.61 DHCP6\_HOOK\_LEASE6\_RELEASE\_PD\_SKIP

%1: prefix lease was not released because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on lease6\_release hook point set the next step to SKIP value. For this particular hook point, that setting by a callout instructs the server to not release a lease. If client requested release of multiples leases (by sending multiple IA options), the server will retains this particular lease and will proceed with other renewals as usual. The argument holds the client and transaction identification information.

## 9.62 DHCP6\_HOOK\_LEASES6\_COMMITTED\_DROP

%1: packet is dropped, because a callout set the next step to DROP

Logged at debug log level 15. This debug message is printed when a callout installed on the leases6\_committed hook point sets the next step to DROP.

## 9.63 DHCP6\_HOOK\_LEASES6\_COMMITTED\_PARK

%1: packet is parked, because a callout set the next step to PARK

Logged at debug log level 40. This debug message is printed when a callout installed on the leases6\_committed hook point sets the next step to PARK.

## 9.64 DHCP6\_HOOK\_LEASES6\_PARKING\_LOT\_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp6 is using hook libraries (e.g. HA) that implement the "leases6-committed" callout and client queries are arriving faster than those callouts can fulfill them.

## 9.65 DHCP6\_HOOK\_PACKET\_RCVD\_SKIP

%1: packet is dropped, because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the pkt6\_receive hook point sets the next step to SKIP. For this particular hook point, the value setting instructs the server to drop the packet.

## 9.66 DHCP6\_HOOK\_PACKET\_SEND\_DROP

%1: prepared DHCPv6 response was not sent because a callout set the next ste to DROP

Logged at debug log level 15. This debug message is printed when a callout installed on the pkt6\_send hook point set the next step to DROP. For this particular hook point, the setting of the value by a callout instructs the server to drop the packet. This effectively means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease). The argument specifies the client and transaction identification information.

## 9.67 DHCP6\_HOOK\_PACKET\_SEND\_SKIP

%1: prepared DHCPv6 response is not built because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the pkt6\_send hook point set the next step to SKIP. For this particular hook point, the setting of the value by a callout instructs the server to not build the wire data (pack) because it was already done by the book. The argument specifies the client and transaction identification information.

## 9.68 DHCP6\_HOOK\_SUBNET6\_SELECT\_DROP

%1: packet was dropped because a callout set the drop flag

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet6\_select hook point set the drop flag. For this particular hook point, the setting of the flag instructs the server to drop the received packet. The argument holds the client and transaction identification information.

## 9.69 DHCP6\_HOOK\_SUBNET6\_SELECT\_PARK

```
%1: packet was parked
```

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet6\_select hook point set the park flag. The argument holds the client and transaction identification information.

## 9.70 DHCP6\_HOOK\_SUBNET6\_SELECT\_SKIP

```
%1: no subnet was selected because a callout set the next step to SKIP
```

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet6\_select hook point set the next step to SKIP value. For this particular hook point, the setting of this value instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses or prefixes will be assigned. The argument holds the client and transaction identification information.

## 9.71 DHCP6\_INIT\_FAIL

```
failed to initialize Kea server: %1
```

The server has failed to establish communication with the rest of Kea, failed to read JSON configuration file or encountered any other critical issue that prevents it from starting up properly. Attached error message provides more details about the issue.

## 9.72 DHCP6\_LEASE\_ADVERT

```
%1: lease for address %2 and iaid=%3 will be advertised
```

Logged at debug log level 50. This informational message indicates that the server will advertise an address to the client in the ADVERTISE message. The client will request allocation of this address with the REQUEST message sent in the next message exchange. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

## 9.73 DHCP6\_LEASE\_ADVERT\_FAIL

```
%1: failed to advertise an address lease for iaid=%2
```

Logged at debug log level 50. This message indicates that in response to a received SOLICIT, the server failed to advertise a non-temporary lease for a given client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

## 9.74 DHCP6\_LEASE\_ALLOC

```
%1: lease for address %2 and iaid=%3 has been allocated for %4 seconds
```

Logged at debug log level 50. This informational message indicates that in response to a client's REQUEST message, the server successfully granted a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address, IAID and validity lifetime.

## 9.75 DHCP6\_LEASE\_ALLOC\_FAIL

```
%1: failed to grant an address lease for iaid=%2
```

Logged at debug log level 50. This message indicates that in response to a received REQUEST, the server failed to grant a non-temporary address lease for the client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

## 9.76 DHCP6\_LEASE\_DATA

```
%1: detailed lease information for iaid=%2: %3
```

Logged at debug log level 55. This debug message is used to print the detailed information about the allocated lease or a lease which will be advertised to the client. The first argument holds the client and the transaction identification information. The second argument holds the IAID. The third argument holds the detailed lease information.

## 9.77 DHCP6\_LEASE\_NA\_WITHOUT\_DUID

```
%1: address lease for address %2 does not have a DUID
```

This error message indicates a database consistency problem. The lease database has an entry indicating that the given address is in use, but the lease does not contain any client identification. This is most likely due to a software error: please raise a bug report. As a temporary workaround, manually remove the lease entry from the database. The first argument includes the client and transaction identification information. The second argument holds the address to be released.

## 9.78 DHCP6\_LEASE\_PD\_WITHOUT\_DUID

```
%1: lease for prefix %2/%3 does not have a DUID
```

This error message indicates a database consistency failure. The lease database has an entry indicating that the given prefix is in use, but the lease does not contain any client identification. This is most likely due to a software error: please raise a bug report. As a temporary workaround, manually remove the lease entry from the database. The first argument includes client and transaction identification information. The second and third argument hold the prefix and the prefix length.

## 9.79 DHCP6\_LEASE\_RENEW

```
%1: lease for address %2 and iaid=%3 has been allocated
```

This informational message indicates that in response to a client's REQUEST message, the server successfully renewed a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

## 9.80 DHCP6\_LEASE\_REUSE

```
%1: lease for address %2 and iaid=%3 has been reused for %4 seconds
```

This informational message indicates that in response to a client's message, the server successfully reused a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address, IAID and validity lifetime.

## 9.81 DHCP6\_MULTI\_THREADING\_INFO

```
enabled: %1, number of threads: %2, queue size: %3
```

This is a message listing some information about the multi-threading parameters with which the server is running.

## 9.82 DHCP6\_NOT\_RUNNING

```
IPv6 DHCP server is not running
```

A warning message is issued when an attempt is made to shut down the IPv6 DHCP server but it is not running.

## 9.83 DHCP6\_NO\_INTERFACES

```
failed to detect any network interfaces
```

During startup the IPv6 DHCP server failed to detect any network interfaces and is therefore shutting down.

## 9.84 DHCP6\_OPEN\_SOCKET

opening service sockets on port %1

Logged at debug log level 0. A debug message issued during startup, this indicates that the IPv6 DHCP server is about to open sockets on the specified port.

## 9.85 DHCP6\_OPEN\_SOCKETS\_FAILED

maximum number of open service sockets attempts: %1, has been exhausted without success

This error indicates that the server failed to bind service sockets after making the maximum configured number of reconnect attempts. This might cause the server to shut down as specified in the configuration.

## 9.86 DHCP6\_OPEN\_SOCKETS\_NO\_RECONNECT\_CTL

unexpected error in bind service sockets.

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to bind to its service sockets if they are unavailable, and the server exits. This error should be reported.

## 9.87 DHCP6\_PACKET\_DROP\_DHCP\_DISABLED

%1: DHCP service is globally disabled

Logged at debug log level 15. This debug message is issued when a packet is dropped because the DHCP service has been temporarily disabled. This affects all received DHCP packets. The service may be enabled by the "dhcp-enable" control command or automatically after a specified amount of time since receiving "dhcp-disable" command.

## 9.88 DHCP6\_PACKET\_DROP\_DROP\_CLASS

dropped as member of the special class 'DROP': %1 %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified into the special class 'DROP' and dropped. The packet details are displayed.

## 9.89 DHCP6\_PACKET\_DROP\_DROP\_CLASS2

```
dropped as member of the special class 'DROP' after host reservation lookup: %1 %2
```

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after host reservation lookup into the special class 'DROP' and dropped. The packet details are displayed.

## 9.90 DHCP6\_PACKET\_DROP\_DROP\_CLASS\_EARLY

```
dropped as member of the special class 'DROP' after early global host reservations_↵  
↵lookup: %1 %2
```

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after early global host reservations lookup into the special class 'DROP' and dropped. The packet details are displayed.

## 9.91 DHCP6\_PACKET\_DROP\_DUPLICATE

```
dropped as sent by the same client than a packet being processed by another thread:↵  
↵dropped %1 %2 by thread %3 as duplicate of %4 %5 processed by %6
```

Logged at debug log level 15. Currently multi-threading processing avoids races between packets sent by the same client by dropping new packets until processing is finished. Packet details and thread identifiers are included for both packets in this warning message.

## 9.92 DHCP6\_PACKET\_DROP\_PARSE\_FAIL

```
%1: failed to parse packet from %2 to %3, received over interface %4, reason: %5, %6
```

Logged at debug log level 15. The DHCPv6 server has received a packet that it is unable to interpret. The reason why the packet is invalid is included in the message.

## 9.93 DHCP6\_PACKET\_DROP\_SERVERID\_MISMATCH

```
%1: dropping packet with server identifier: %2, server is using: %3
```

Logged at debug log level 15. A debug message noting that server has received message with server identifier option that not matching server identifier that server is using.

## 9.94 DHCP6\_PACKET\_DROP\_UNICAST

`%1: dropping unicast %2 packet as this packet should be sent to multicast`

Logged at debug log level 15. This debug message is issued when the server drops the unicast packet, because packets of this type must be sent to multicast. The first argument specifies the client and transaction identification information, the second argument specifies packet type.

## 9.95 DHCP6\_PACKET\_OPTIONS\_SKIPPED

`%1: An error unpacking an option, caused subsequent options to be skipped: %2`

Logged at debug log level 50. A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the packet. The server will server will still attempt to service the packet.

## 9.96 DHCP6\_PACKET\_PROCESS\_EXCEPTION

`%1: exception occurred during packet processing`

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

## 9.97 DHCP6\_PACKET\_PROCESS\_EXCEPTION\_MAIN

`exception occurred during packet processing`

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

## 9.98 DHCP6\_PACKET\_PROCESS\_FAIL

`%1: processing of %2 message received from %3 failed: %4`

Logged at debug log level 40. This is a general catch-all message indicating that the processing of the specified packet type from the indicated address failed. The reason is given in the message. The server will not send a response but will instead ignore the packet.



## 9.99 DHCP6\_PACKET\_PROCESS\_STD\_EXCEPTION

```
%1: exception occurred during packet processing: %2
```

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

## 9.100 DHCP6\_PACKET\_PROCESS\_STD\_EXCEPTION\_MAIN

```
exception occurred during packet processing: %1
```

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

## 9.101 DHCP6\_PACKET\_QUEUE\_FULL

```
multi-threading packet queue is full
```

Logged at debug log level 40. A debug message noting that the multi-threading packet queue is full so the oldest packet of the queue was dropped to make room for the received one.

## 9.102 DHCP6\_PACKET\_RECEIVED

```
%1: %2 (type %3) received from %4 to %5 on interface %6
```

An INFO message noting that the server has received the specified type of packet on the specified interface. The first argument specifies the client and transaction identification information. The second and third argument specify the name of the DHCPv6 message and its numeric type respectively. The remaining arguments specify the source address, destination IP address and the name of the interface on which the message has been received.

## 9.103 DHCP6\_PACKET\_RECEIVE\_FAIL

```
error on attempt to receive packet: %1
```

The IPv6 DHCP server tried to receive a packet but an error occurred during this attempt. The reason for the error is included in the message.

## 9.104 DHCP6\_PACKET\_SEND

```
%1: trying to send packet %2 (type %3) from [%4]:%5 to [%6]:%7 on interface %8
```

An INFO message noting that the server is attempting to send the specified type of packet. The arguments specify the client identification information (HW address and client identifier), DHCP message name and type, source IPv6 address and port, destination IPv6 address and port and the interface name.

## 9.105 DHCP6\_PACKET\_SEND\_FAIL

```
%1: failed to send DHCPv6 packet: %2
```

This error is output if the IPv6 DHCP server fails to send an assembled DHCP message to a client. The reason for the error is included in the message.

## 9.106 DHCP6\_PACK\_FAIL

```
%1: failed to assemble response correctly: %2
```

This error is output if the server failed to assemble the data to be returned to the client into a valid packet. The reason is most likely to be to a programming error: please raise a bug report.

## 9.107 DHCP6\_PARSER\_COMMIT\_EXCEPTION

```
parser failed to commit changes
```

On receipt of message containing details to a change of the IPv6 DHCP server configuration, a set of parsers were successfully created, but one of them failed to commit its changes due to a low-level system exception being raised. Additional messages may be output indicating the reason.

## 9.108 DHCP6\_PARSER\_COMMIT\_FAIL

```
parser failed to commit changes: %1
```

On receipt of message containing details to a change of the IPv6 DHCP server configuration, a set of parsers were successfully created, but one of them failed to commit its changes. The reason for the failure is given in the message.

## 9.109 DHCP6\_PARSER\_EXCEPTION

```
failed to create or run parser for configuration element %1
```

On receipt of message containing details to a change of its configuration, the IPv6 DHCP server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The message has been output in response to a non-Kea exception being raised. Additional messages may give further information. The most likely cause of this is that the specification file for the server (which details the allowable contents of the configuration) is not correct for this version of Kea. This may be the result of an interrupted installation of an update to Kea.

## 9.110 DHCP6\_PARSER\_FAIL

```
failed to create or run parser for configuration element %1: %2
```

On receipt of message containing details to a change of its configuration, the IPv6 DHCP server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

## 9.111 DHCP6\_PD\_LEASE\_ADVERT

```
%1: lease for prefix %2/%3 and iaid=%4 will be advertised
```

Logged at debug log level 50. This informational message indicates that the server will advertise a prefix to the client in the ADVERTISE message. The client will request allocation of this prefix with the REQUEST message sent in the next message exchange. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and IAID.

## 9.112 DHCP6\_PD\_LEASE\_ADVERT\_FAIL

```
%1: failed to advertise a prefix lease for iaid=%2
```

Logged at debug log level 50. This message indicates that in response to a received SOLICIT, the server failed to advertise a prefix lease for a given client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

## 9.113 DHCP6\_PD\_LEASE\_ALLOC

```
%1: lease for prefix %2/%3 and iaid=%4 has been allocated for %5 seconds
```

Logged at debug log level 50. This informational message indicates that in response to a client's REQUEST message, the server successfully granted a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length, IAID and validity lifetime.

## 9.114 DHCP6\_PD\_LEASE\_ALLOC\_FAIL

```
%1: failed to grant a prefix lease for iaid=%2
```

Logged at debug log level 50. This message indicates that in response to a received REQUEST, the server failed to grant a prefix lease for the client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

## 9.115 DHCP6\_PD\_LEASE\_RENEW

```
%1: lease for prefix %2/%3 and iaid=%4 has been allocated
```

This informational message indicates that in response to a client's REQUEST message, the server successfully renewed a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and IAID.

## 9.116 DHCP6\_PD\_LEASE\_REUSE

```
%1: lease for prefix %2/%3 and iaid=%4 has been reused for %5 seconds
```

This informational message indicates that in response to a client's message, the server successfully reused a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length, IAID and validity lifetime.

## 9.117 DHCP6\_PROCESS\_IA\_NA\_EXTEND

```
%1: extending lease lifetime for IA_NA option with iaid=%2
```

Logged at debug log level 50. This message is logged when the server is starting to extend the lifetime of the address lease associated with the particular IAID. The first argument includes the client and transaction identification information. The second argument contains the IAID.

## 9.118 DHCP6\_PROCESS\_IA\_NA\_RELEASE

```
%1: releasing lease for IA_NA option with iaid=%2
```

Logged at debug log level 50. This message is logged when the server is trying to release the client's as a result of receiving the RELEASE message. The first argument includes the client and transaction identification information. The second argument contains the IAID.

## 9.119 DHCP6\_PROCESS\_IA\_NA\_REQUEST

```
%1: server is processing IA_NA option with iaid=%2 and hint=%3
```

Logged at debug log level 50. This is a debug message that indicates the processing of a received IA\_NA option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_NA option. The third argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

## 9.120 DHCP6\_PROCESS\_IA\_NA\_SOLICIT

```
%1: server is processing IA_NA option with iaid=%2 and hint=%3
```

Logged at debug log level 50. This is a debug message that indicates the processing of a received IA\_NA option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_NA option. The third argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

## 9.121 DHCP6\_PROCESS\_IA\_PD\_EXTEND

```
%1: extending lease lifetime for IA_PD option with iaid=%2
```

Logged at debug log level 50. This message is logged when the server is starting to extend the lifetime of the prefix lease associated with the particular IAID. The first argument includes the client and transaction identification information. The second argument contains the IAID.

## 9.122 DHCP6\_PROCESS\_IA\_PD\_REQUEST

```
%1: server is processing IA_PD option with iaid=%2 and hint=%3
```

Logged at debug log level 50. This is a debug message that indicates a processing of received IA\_PD option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_PD option. The third argument may hold the hint for the server about the prefix that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

## 9.123 DHCP6\_PROCESS\_IA\_PD\_SOLICIT

```
%1: server is processing IA_PD option with iaid=%2 and hint=%3
```

Logged at debug log level 50. This is a debug message that indicates a processing of received IA\_PD option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA\_PD option. The third argument may hold the hint for the server about the prefix that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

## 9.124 DHCP6\_QUERY\_DATA

```
%1, packet details: %2
```

Logged at debug log level 55. A debug message printing the details of the received packet. The first argument includes the client and the transaction identification information.

## 9.125 DHCP6\_QUERY\_LABEL

```
received query: %1
```

This information message indicates that a query was received. It displays the client and the transaction identification information.

## 9.126 DHCP6\_RAPID\_COMMIT

```
%1: Rapid Commit option received, following 2-way exchange
```

Logged at debug log level 50. This debug message is issued when the server found a Rapid Commit option in the client's message and 2-way exchanges are supported by the server for the subnet on which the client is connected. The argument specifies the client and transaction identification information.

## 9.127 DHCP6\_RECLAIM\_EXPIRED\_LEASES\_FAIL

```
failed to reclaim expired leases: %1
```

This error message indicates that the reclaim expired leases operation failed and provides the cause of failure.

## 9.128 DHCP6\_RELEASE\_NA

```
%1: binding for address %2 and iaid=%3 was released properly
```

This informational message indicates that an address was released properly. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second and third argument hold the released IPv6 address and IAID respectively.

## 9.129 DHCP6\_RELEASE\_NA\_DELETED

```
%1: binding for address %2 and iaid=%3 was deleted on release
```

This informational message indicates that an address was deleted on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second and third argument hold the released IPv6 address and IAID respectively.

## 9.130 DHCP6\_RELEASE\_NA\_EXPIRED

```
%1: binding for address %2 and iaid=%3 expired on release
```

This informational message indicates that an address expired on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second and third argument hold the released IPv6 address and IAID respectively.

## 9.131 DHCP6\_RELEASE\_NA\_FAIL

```
%1: failed to remove address lease for address %2 and iaid=%3
```

This error message indicates that the software failed to remove an address lease from the lease database. It probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument holds the client and transaction identification information. The second and third argument hold the released address and IAID respectively.

## 9.132 DHCP6\_RELEASE\_NA\_FAIL\_WRONG\_DUID

```
%1: client tried to release address %2, but it belongs to another client using duid=%3
```

This warning message indicates that a client tried to release an address that belongs to a different client. This should not happen in normal circumstances and may indicate a misconfiguration of the client. However, since the client releasing the address will stop using it anyway, there is a good chance that the situation will correct itself.

## 9.133 DHCP6\_RELEASE\_NA\_FAIL\_WRONG\_IAID

```
%1: client tried to release address %2, but it used wrong IAID (expected %3, but got %4)
```

This warning message indicates that client tried to release an address that does belong to it, but the address was expected to be in a different IA (identity association) container. This probably means that the client's support for multiple addresses is flawed.

## 9.134 DHCP6\_RELEASE\_PD

```
%1: prefix %2/%3 for iaid=%4 was released properly
```

This informational message indicates that a prefix was released properly. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument hold the prefix and its length. The fourth argument holds IAID.

## 9.135 DHCP6\_RELEASE\_PD\_DELETED

```
%1: prefix %2/%3 for iaid=%4 was deleted on release
```

This informational message indicates that a prefix was deleted on release. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument hold the prefix and its length. The fourth argument holds IAID.

## 9.136 DHCP6\_RELEASE\_PD\_EXPIRED

```
%1: prefix %2/%3 for iaid=%4 expired on release
```

This informational message indicates that a prefix expired on release. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument hold the prefix and its length. The fourth argument holds IAID.

## 9.137 DHCP6\_RELEASE\_PD\_FAIL

```
%1: failed to release prefix %2/%3 for iaid=%4
```

This error message indicates that the software failed to remove a prefix lease from the lease database. It probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument hold the client and transaction identification information. The second and third argument define the prefix and its length. The fourth argument holds the IAID.

## 9.138 DHCP6\_RELEASE\_PD\_FAIL\_WRONG\_DUID

```
%1: client tried to release prefix %2/%3, but it belongs to another client (duid=%4)
```

This warning message indicates that client tried to release a prefix that belongs to a different client. This should not happen in normal circumstances and may indicate a misconfiguration of the client. However, since the client releasing the prefix will stop using it anyway, there is a good chance that the situation will correct itself. The first argument includes the client and the transaction identification information. The second and third argument include the prefix and prefix length. The last argument holds the DUID of the client holding the lease.



## 9.139 DHCP6\_RELEASE\_PD\_FAIL\_WRONG\_IAID

```
%1: client tried to release prefix %2/%3, but it used wrong IAID (expected %4, but got  
->%5)
```

This warning message indicates that client tried to release a prefix that does belong to it, but the address was expected to be in a different IA (identity association) container. This probably means that the client's support for multiple prefixes is flawed. The first argument includes the client and transaction identification information. The second and third argument identify the prefix. The fourth and fifth argument hold the expected IAID and IAID found respectively.

## 9.140 DHCP6\_REQUIRED\_CLASS\_EVAL\_ERROR

```
%1: Expression '%2' evaluated to %3
```

This error message indicates that there a problem was encountered while evaluating an expression of a required client class that was marked as required. A description of the problem is printed.

## 9.141 DHCP6\_REQUIRED\_CLASS\_EVAL\_RESULT

```
%1: Expression '%2' evaluated to %3
```

Logged at debug log level 50. This debug message indicates that the expression of a required client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

## 9.142 DHCP6\_REQUIRED\_OPTIONS\_CHECK\_FAIL

```
%1: %2 message received from %3 failed the following check: %4
```

Logged at debug log level 40. This message indicates that received DHCPv6 packet is invalid. This may be due to a number of reasons, e.g. the mandatory client-id option is missing, the server-id forbidden in that particular type of message is present, there is more than one instance of client-id or server-id present, etc. The exact reason for rejecting the packet is included in the message.

## 9.143 DHCP6\_RESERVATIONS\_LOOKUP\_FIRST\_ENABLED

```
Multi-threading is enabled and host reservations lookup is always performed first.
```

This is a message informing that host reservations lookup is performed before lease lookup when multi-threading is enabled overwriting configured value.

## 9.144 DHCP6\_RESPONSE\_DATA

```
%1: responding with packet %2 (type %3), packet details: %4
```

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

## 9.145 DHCP6\_SERVER\_FAILED

```
server failed: %1
```

The IPv6 DHCP server has encountered a fatal error and is terminating. The reason for the failure is included in the message.

## 9.146 DHCP6\_SHUTDOWN

```
server shutdown
```

Logged at debug log level 40. The IPv6 DHCP server has terminated normally.

## 9.147 DHCP6\_SHUTDOWN\_REQUEST

```
shutdown of server requested
```

Logged at debug log level 40. This debug message indicates that a shutdown of the IPv6 server has been requested via a call to the 'shutdown' method of the core Dhcpv6Srv object.

## 9.148 DHCP6\_SRV\_CONSTRUCT\_ERROR

```
error creating Dhcpv6Srv object, reason: %1
```

This error message indicates that during startup, the construction of a core component within the IPv6 DHCP server (the Dhcpv6 server object) has failed. As a result, the server will exit. The reason for the failure is given within the message.

## 9.149 DHCP6\_SRV\_D2STOP\_ERROR

```
error stopping IO with DHCP_DDNS during shutdown: %1
```

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv6 server and the DHCP\_DDNS server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

## 9.150 DHCP6\_SRV\_UNLOAD\_LIBRARIES\_ERROR

```
error unloading hooks libraries during shutdown: %1
```

This error message indicates that during shutdown, unloading hooks libraries failed to close them. If the list of libraries is empty it is a programmatic error in the server code. If it is not empty it could be a programmatic error in one of the hooks libraries which could lead to a crash during finalization.

## 9.151 DHCP6\_STARTED

```
Kea DHCPv6 server version %1 started
```

This informational message indicates that the IPv6 DHCP server has processed all configuration information and is ready to process DHCPv6 packets. The version is also printed.

## 9.152 DHCP6\_STARTING

```
Kea DHCPv6 server version %1 (%2) starting
```

This informational message indicates that the IPv6 DHCP server has processed any command-line switches and is starting. The version is also printed.

## 9.153 DHCP6\_START\_INFO

```
pid: %1, server port: %2, client port: %3, verbose: %4
```

Logged at debug log level 0. This is a debug message issued during the IPv6 DHCP server startup. It lists some information about the parameters with which the server is running.

## 9.154 DHCP6\_SUBNET\_DATA

%1: the selected subnet details: %2

Logged at debug log level 55. This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second argument includes the subnet details.

## 9.155 DHCP6\_SUBNET\_DYNAMICALLY\_CHANGED

%1: changed selected subnet %2 to subnet %3 from shared network %4 for client assignments

Logged at debug log level 45. This debug message indicates that the server is using another subnet than initially selected for client assignments. This newly selected subnet belongs to the same shared network as the original subnet. Some reasons why the new subnet was selected include: address pool exhaustion in the original subnet or the fact that the new subnet includes some static reservations for this client.

## 9.156 DHCP6\_SUBNET\_SELECTED

%1: the subnet with ID %2 was selected for client assignments

Logged at debug log level 45. This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

## 9.157 DHCP6\_SUBNET\_SELECTION\_FAILED

%1: failed to select subnet for the client

Logged at debug log level 50. This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The cause is likely due to a misconfiguration of the server. The packet processing will continue, but the response will only contain generic configuration and no addresses or prefixes. The argument includes the client and the transaction identification information.

## 9.158 DHCP6\_UNKNOWN\_MSG\_RECEIVED

%1: received unknown message (type %2) on interface %3

Logged at debug log level 40. This debug message is printed when server receives a message of unknown type. That could either mean missing functionality or invalid or broken relay or client. The list of formally defined message types is available here: <http://www.iana.org/assignments/dhcpv6-parameters>.

## 10.1 DHCPSRV\_CFGMGR\_ADD\_IFACE

```
listening on interface %1
```

An info message issued when a new interface is being added to the collection of interfaces on which the server listens to DHCP messages.

## 10.2 DHCPSRV\_CFGMGR\_ADD\_SUBNET4

```
adding subnet %1
```

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is adding the specified IPv4 subnet to its database.

## 10.3 DHCPSRV\_CFGMGR\_ADD\_SUBNET6

```
adding subnet %1
```

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is adding the specified IPv6 subnet to its database.

## 10.4 DHCPSRV\_CFGMGR\_ALL\_IFACES\_ACTIVE

```
enabling listening on all interfaces
```

Logged at debug log level 40. A debug message issued when the server is being configured to listen on all interfaces.

## 10.5 DHCPDRV\_CFGMGR\_CFG\_DHCP\_DDNS

```
Setting DHCP-DDNS configuration to: %1
```

Logged at debug log level 40. A debug message issued when the server's DHCP-DDNS settings are changed.

## 10.6 DHCPDRV\_CFGMGR\_CONFIG4\_MERGED

```
Configuration backend data has been merged.
```

This is an informational message emitted when the DHCPv4 server has successfully merged configuration data retrieved from its configuration backends into the current configuration.

## 10.7 DHCPDRV\_CFGMGR\_CONFIG6\_MERGED

```
Configuration backend data has been merged.
```

This is an informational message emitted when the DHCPv6 server has successfully merged configuration data retrieved from its configuration backends into the current configuration.

## 10.8 DHCPDRV\_CFGMGR\_CONFIGURE\_SERVERID

```
server configuration includes specification of a server identifier
```

This warning message is issued when the server specified configuration of a server identifier. If this new configuration overrides an existing server identifier, this will affect existing bindings of the clients. Clients will use old server identifier when they renew their bindings. The server will not respond to those renews, and the clients will eventually transition to rebinding state. The server should reassign existing bindings and the clients will subsequently use new server identifier. It is recommended to not modify the server identifier, unless there is a good reason for it, to avoid increased number of renewals and a need for rebinding (increase of multicast traffic, which may be received by multiple servers).

## 10.9 DHCPDRV\_CFGMGR\_DEL\_SUBNET4

```
IPv4 subnet %1 removed
```

Logged at debug log level 40. This debug message is issued when a subnet is successfully removed from the server configuration. The argument identifies the removed subnet.

## 10.10 DHCPDRV\_CFGMGR\_DEL\_SUBNET6

```
IPv6 subnet %1 removed
```

Logged at debug log level 40. This debug message is issued when a subnet is successfully removed from the server configuration. The argument identifies the removed subnet.

## 10.11 DHCPDRV\_CFGMGR\_FLQ\_POPULATE\_FREE\_ADDRESS\_LEASES

```
populating free address leases for the FLQ allocator in subnet %1; it can take a while!
```

This informational message is issued when the server begins building a queue of free address leases for the given subnet. It can take a considerable amount of time, depending on the size of the address pools.

## 10.12 DHCPDRV\_CFGMGR\_FLQ\_POPULATE\_FREE\_ADDRESS\_LEASES\_DONE

```
populated %1 free address leases for the FLQ allocator in subnet %2 in %3
```

This informational message is issued when the server ends building a queue of free address leases for a given subnet. The first argument logs the number of free leases, the second argument logs the subnet, and the third argument logs a duration.

## 10.13 DHCPDRV\_CFGMGR\_FLQ\_POPULATE\_FREE\_PREFIX\_LEASES

```
populating free prefix leases for the FLQ allocator in subnet %1; it can take a while!
```

This informational message is issued when the server begins building a queue of free leases for the given subnet. It can take a considerable amount of time, depending on the size of the delegated prefix pools.

## 10.14 DHCPDRV\_CFGMGR\_FLQ\_POPULATE\_FREE\_PREFIX\_LEASES\_DONE

```
populated %1 free prefix leases for the FLQ allocator in subnet %2 completed in %3
```

This informational message is issued when the server ends building a queue of free prefix leases for a given subnet. The first argument logs the number of free leases, the second argument logs the subnet, and the third argument logs a duration.

## 10.15 DHCPDRV\_CFGMGR\_IPV4\_RESERVATIONS\_NON\_UNIQUE\_IGNORED

```
ignoring "ip-reservations-unique" setting because at least one of the host database_
↳backends does not support non-unique IP reservations in a subnet
```

This warning message is issued when the server failed to use the new setting of the ip-reservations-unique global parameter configured via the configuration backend. Some host database backends used apparently do not support specifying several reservations for the same IP address in a subnet. The administrator should either stop using the backend that does not support this setting or set the value of the ip-reservations-unique to true to resolve the configuration issue.

## 10.16 DHCPDRV\_CFGMGR\_IPV6\_RESERVATIONS\_NON\_UNIQUE\_IGNORED

```
ignoring "ip-reservations-unique" setting because at least one of the host database_
↳backends does not support non unique IP reservations in a subnet
```

This warning message is issued when the server failed to use the new setting of the ip-reservations-unique global parameter configured via the configuration backend. Some host database backends used apparently do not support specifying several reservations for the same IP address or delegated prefix in a subnet. The administrator should either stop using the backend that does not support this setting or set the value of the ip-reservations-unique to true to resolve the configuration issue.

## 10.17 DHCPDRV\_CFGMGR\_IP\_RESERVATIONS\_UNIQUE\_DUPLICATES\_DETECTED

```
the "ip-reservations-unique" flag is set to true and multiple reservations for the IP_
↳address %1 in subnet %2 are not allowed causing error: %3
```

This warning message is issued when the DHCP server is configured to not allow multiple reservations for the same IP address. However, the host database backend contains multiple reservations for the IP address logged as the first argument, in the subnet logged as second argument, causing problems with lease allocation logged as third argument.

## 10.18 DHCPDRV\_CFGMGR\_IP\_RESERVATIONS\_UNIQUE\_DUPLICATES\_POSSIBLE

```
setting "ip-reservations-unique" from false to true poses a risk that some host backends_
↳may still contain multiple reservations for the same IP address
```

This warning message is issued when the DHCP server is configured to not allow multiple reservations for the same IP address. However, the host database backends may still contain multiple reservations for the same IP addresses causing problems with lease allocation for certain addresses. Please ensure that all such duplicates are removed.



## 10.19 DHCPDRV\_CFGMGR\_NEW\_SUBNET4

```
a new subnet has been added to configuration: %1
```

This is an informational message reporting that the configuration has been extended to include the specified IPv4 subnet.

## 10.20 DHCPDRV\_CFGMGR\_NEW\_SUBNET6

```
a new subnet has been added to configuration: %1
```

This is an informational message reporting that the configuration has been extended to include the specified subnet.

## 10.21 DHCPDRV\_CFGMGR\_OPTION\_DUPLICATE

```
multiple options with the code: %1 added to the subnet: %2
```

This warning message is issued on an attempt to configure multiple options with the same option code for the particular subnet. Adding multiple options is uncommon for DHCPv6, but it is not prohibited.

## 10.22 DHCPDRV\_CFGMGR\_RENEW\_GTR\_REBIND

```
in %1, the value of renew-timer %2 is greater than the value of rebind-timer %3,   
↳ ignoring renew-timer
```

A warning message that indicates the configured renew-timer is greater than the configured rebind-timer. The server will ignore the renew timer value and send the rebind timer value only. This is considered a non-fatal configuration error.

## 10.23 DHCPDRV\_CFGMGR\_SOCKET\_RAW\_UNSUPPORTED

```
use of raw sockets is unsupported on this OS, UDP sockets will be used
```

This warning message is logged when the user specified that the DHCPv4 server should use the raw sockets to receive the DHCP messages and respond to the clients, but the use of raw sockets is not supported on the particular environment. The raw sockets are useful when the server must respond to the directly connected clients which don't have an address yet. If the raw sockets are not supported by Kea on the particular platform, Kea will fall back to use of the IP/UDP sockets. The responses to the directly connected clients will be broadcast. The responses to relayed clients will be unicast as usual.

## 10.24 DHCPDRV\_CFGMGR\_SOCKET\_TYPE\_DEFAULT

```
"dhcp-socket-type" not specified , using default socket type %1
```

This informational message is logged when the administrator hasn't specified the "dhcp-socket-type" parameter in configuration for interfaces. In such case, the default socket type will be used.

## 10.25 DHCPDRV\_CFGMGR\_SOCKET\_TYPE\_SELECT

```
using socket type %1
```

This informational message is logged when the DHCPv4 server selects the socket type to be used for all sockets that will be opened on the interfaces. Typically, the socket type is specified by the server administrator. If the socket type hasn't been specified, the raw socket will be selected. If the raw socket has been selected but Kea doesn't support the use of raw sockets on the particular OS, it will use an UDP socket instead.

## 10.26 DHCPDRV\_CFGMGR\_SUBNET4

```
retrieved subnet %1 for address hint %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet when given the address hint specified as the address is within the subnet.

## 10.27 DHCPDRV\_CFGMGR\_SUBNET4\_ADDR

```
selected subnet %1 for packet received by matching address %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet for a received packet. This particular subnet was selected, because an IPv4 address was matched which belonged to that subnet.

## 10.28 DHCPDRV\_CFGMGR\_SUBNET4\_IFACE

```
selected subnet %1 for packet received over interface %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet for a packet received over the given interface. This particular subnet was selected, because it was specified as being directly reachable over the given interface. (see 'interface' parameter in the subnet4 definition).

## 10.29 DHCPDRV\_CFGMGR\_SUBNET4\_RELAY

```
selected subnet %1, because of matching relay addr %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet, because detected relay agent address matches value specified for this subnet.

## 10.30 DHCPDRV\_CFGMGR\_SUBNET6

```
retrieved subnet %1 for address hint %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet when given the address hint specified as the address is within the subnet.

## 10.31 DHCPDRV\_CFGMGR\_SUBNET6\_IFACE

```
selected subnet %1 for packet received over interface %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet for a packet received over given interface. This particular subnet was selected, because it was specified as being directly reachable over given interface. (see 'interface' parameter in the subnet6 definition).

## 10.32 DHCPDRV\_CFGMGR\_SUBNET6\_IFACE\_ID

```
selected subnet %1 (interface-id match) for incoming packet
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet for a received packet. This particular subnet was selected, because value of interface-id option matched what was configured in the server's interface-id option for that selected subnet6. (see 'interface-id' parameter in the subnet6 definition).

## 10.33 DHCPDRV\_CFGMGR\_SUBNET6\_RELAY

```
selected subnet %1, because of matching relay addr %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet, because detected relay agent address matches value specified for this subnet.

## 10.34 DHCPDRV\_CFGMGR\_UNICAST\_LINK\_LOCAL

```
specified link local address %1 for unicast traffic on interface %2
```

This warning message is logged when user specified a link-local address to receive unicast traffic. The warning message is issued because it is an uncommon use.

## 10.35 DHCPDRV\_CFGMGR\_UPDATE\_SUBNET4

```
updating subnet %1 (result %2)
```

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is updating the specified IPv4 subnet in its current configuration. Subnet ID and result (expected to be true) are displayed.

## 10.36 DHCPDRV\_CFGMGR\_UPDATE\_SUBNET6

```
updating subnet %1 (result %2)
```

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is replacing the specified IPv6 subnet in its current configuration. Subnet ID and result (expected to be true) are displayed.

## 10.37 DHCPDRV\_CFGMGR\_USE\_ADDRESS

```
listening on address %1, on interface %2
```

A message issued when the server is configured to listen on the explicitly specified IP address on the given interface.

## 10.38 DHCPDRV\_CFGMGR\_USE\_ALLOCATOR

```
using the %1 allocator for %2 leases in subnet %3
```

A message issued when the configuration manager starts using a given allocator for a subnet.

## 10.39 DHCPDRV\_CFGMGR\_USE\_UNICAST

```
listening on unicast address %1, on interface %2
```

An info message issued when configuring the DHCP server to listen on the unicast address on the specific interface.

## 10.40 DHCP\_SRV\_CLOSE\_DB

```
closing currently open %1 database
```

Logged at debug log level 40. This is a debug message, issued when the DHCP server closes the currently open lease database. It is issued at program shutdown and whenever the database access parameters are changed: in the latter case, the server closes the currently open database, and opens a database using the new parameters.

## 10.41 DHCP\_SRV\_DDNS\_TTL\_PERCENT\_TOO\_SMALL

```
ddns-ttl-percent %1 of lease lifetime %2 is too small, ignoring it
```

Logged at debug log level 55. A debug message issued when the DDNS TTL value calculated using the `ddns-ttl-percent` is zero. Kea will ignore the value and calculate the DDNS TTL as though `ddns-ttl-percent` were not specified. The value of `ddns-ttl-percent` and the lease lifetime are shown in the message details.

## 10.42 DHCP\_SRV\_DHCP4O6\_RECEIVED\_BAD\_PACKET

```
received bad DHCPv4o6 packet: %1
```

A bad DHCPv4o6 packet was received.

## 10.43 DHCP\_SRV\_DHCP\_DDNS\_ERROR\_EXCEPTION

```
error handler for DHCP_DDNS IO generated an expected exception: %1
```

This is an error message that occurs when an attempt to send a request to `kea-dhcp-ddns` fails there registered error handler threw an uncaught exception. This is a programmatic error which should not occur. By convention, the error handler should not propagate exceptions. Please report this error.

## 10.44 DHCP\_SRV\_DHCP\_DDNS\_HANDLER\_NULL

```
error handler for DHCP_DDNS IO is not set.
```

This is an error message that occurs when an attempt to send a request to `kea-dhcp-ddns` fails and there is no registered error handler. This is a programmatic error which should never occur and should be reported.

## 10.45 DHCPDRV\_DHCP\_DDNS\_NCR\_REJECTED

```
NameChangeRequest rejected by the sender: %1, ncr: %2
```

This is an error message indicating that NameChangeSender used to deliver DDNS update requests to kea-dhcp-ddns rejected the request. This most likely cause is the sender's queue has reached maximum capacity. This would imply that requests are being generated faster than they can be delivered.

## 10.46 DHCPDRV\_DHCP\_DDNS\_NCR\_SENT

```
NameChangeRequest sent to kea-dhcp-ddns: %1
```

Logged at debug log level 50. A debug message issued when a NameChangeRequest has been successfully sent to kea-dhcp-ddns.

## 10.47 DHCPDRV\_DHCP\_DDNS\_SENDER\_STARTED

```
NameChangeRequest sender has been started: %1
```

An informational message issued when a communication with kea-dhcp-ddns has been successfully started.

## 10.48 DHCPDRV\_DHCP\_DDNS\_SENDER\_STOPPED

```
NameChangeRequest sender has been stopped.
```

An informational message issued when a communication with kea-dhcp-ddns has been stopped. This normally occurs during reconfiguration and as part of normal shutdown. It may occur if kea-dhcp-ddns communications break down.

## 10.49 DHCPDRV\_DHCP\_DDNS\_SUSPEND\_UPDATES

```
DHCP_DDNS updates are being suspended.
```

This is a warning message indicating the DHCP\_DDNS updates have been turned off. This should only occur if IO errors communicating with kea-dhcp-ddns have been experienced. Any such errors should have preceding entries in the log with details. No further attempts to communicate with kea-dhcp-ddns will be made without intervention.

## 10.50 DHCPDRV\_EVAL\_ERROR

```
%1: Expression '%2' evaluated to %3
```

This error message indicates that there a problem was encountered while evaluating an expression of a client class. A description of the problem is printed.

## 10.51 DHCPDRV\_EVAL\_RESULT

```
%1: Expression '%2' evaluated to %3
```

Logged at debug log level 50. This debug message indicates that the expression of a client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

## 10.52 DHCPDRV\_HOOK\_LEASE4\_RECOVER\_SKIP

```
DHCPv4 lease %1 was not recovered from the declined state because a callout set the skip_↵  
↵status.
```

Logged at debug log level 40. This debug message is printed when a callout installed on lease4\_recover hook point set the next step status to SKIP. For this particular hook point, this indicates that the server should not recover the lease from declined state. The server will leave the lease as it is, in the declined state. The server will attempt to recover it the next time decline recovery procedure takes place.

## 10.53 DHCPDRV\_HOOK\_LEASE4\_RENEW\_SKIP

```
DHCPv4 lease was not renewed because a callout set the skip flag.
```

Logged at debug log level 40. This debug message is printed when a callout installed on lease4\_renew hook point set the skip flag. For this particular hook point, the setting of the flag by a callout instructs the server to not renew a lease. The server will use existing lease as it is, without extending its lifetime.

## 10.54 DHCPDRV\_HOOK\_LEASE4\_SELECT\_SKIP

```
Lease4 creation was skipped, because of callout skip flag.
```

Logged at debug log level 40. This debug message is printed when a callout installed on lease4\_select hook point sets the skip flag. It means that the server was told that no lease4 should be assigned. The server will not put that lease in its database and the client will get a NAK packet.

## 10.55 DHCPDRV\_HOOK\_LEASE6\_EXTEND\_SKIP

DHCPv6 lease lifetime was not extended because a callout set the skip flag for message %1

Logged at debug log level 40. This debug message is printed when a callout installed on lease6\_renew or the lease6\_rebind hook point set the skip flag. For this particular hook point, the setting of the flag by a callout instructs the server to not extend the lifetime for a lease. If the client requested renewal of multiple leases (by sending multiple IA options), the server will skip the renewal of the one in question and will proceed with other renewals as usual.

## 10.56 DHCPDRV\_HOOK\_LEASE6\_RECOVER\_SKIP

DHCPv6 lease %1 was not recovered from declined state because a callout set the skip\_↵  
↵status.

Logged at debug log level 40. This debug message is printed when a callout installed on lease6\_recover hook point set the next step status to SKIP. For this particular hook point, this indicates that the server should not recover the lease from declined state. The server will leave the lease as it is, in the declined state. The server will attempt to recover it the next time decline recovery procedure takes place.

## 10.57 DHCPDRV\_HOOK\_LEASE6\_SELECT\_SKIP

Lease6 (non-temporary) creation was skipped, because of callout skip flag.

Logged at debug log level 40. This debug message is printed when a callout installed on lease6\_select hook point sets the skip flag. It means that the server was told that no lease6 should be assigned. The server will not put that lease in its database and the client will get a NoAddrsAvail for that IA\_NA option.

## 10.58 DHCPDRV\_HOST\_MGR\_DB\_OPEN\_CONNECTION\_WITH\_RETRY\_FAILED

Failed to connect to database: %1 with error: %2

This is an informational message issued when the server failed to connect to the host database. The operation started a retry to connect procedure. The database access string with password redacted is logged, along with the error and details for the reconnect procedure.

## 10.59 DHCPDRV\_LEASE4\_EXTENDED\_INFO\_SANITY\_FAIL

extended info for lease %1 failed checks (%2)

This error message is printed when a lease extended info failed to pass sanity checks. The detail of the found problem was displayed and the extended info deleted from the lease user context.



## 10.60 DHCPDRV\_LEASE4\_EXTENDED\_INFO\_UPGRADED

```
extended info for lease %1 was upgraded
```

Logged at debug log level 40. This debug message is printed when a lease extended info was upgraded.

## 10.61 DHCPDRV\_LEASE6\_EXTENDED\_INFO\_SANITY\_FAIL

```
extended info for lease %1 failed checks (%2)
```

This error message is printed when a lease extended info failed to pass sanity checks. The detail of the found problem was displayed and the extended info deleted from the lease user context.

## 10.62 DHCPDRV\_LEASE6\_EXTENDED\_INFO\_UPGRADED

```
extended info for lease %1 was upgraded
```

Logged at debug log level 40. This debug message is printed when a lease extended info was upgraded.

## 10.63 DHCPDRV\_LEASE\_MGR\_CALLBACK\_EXCEPTION

```
exception occurred in a lease manager callback for callback type %1, subnet id %2, and  
↳lease %3: %4
```

This warning message is printed when one of the callback functions registered in the lease manager causes an error. The callback functions can serve different purposes and they likely log the detailed error messages. This error message possibly indicates an unhandled error. The first argument indicates a callback type. The second argument prints the subnet id. The third argument prints the lease for which the error has occurred. The last argument prints the error text.

## 10.64 DHCPDRV\_LEASE\_MGR\_CALLBACK\_UNKNOWN\_EXCEPTION

```
unknown exception occurred in a lease manager callback for callback type %1, subnet id  
↳%2, and lease %3
```

This warning message is printed when one of the callback functions registered in the lease manager causes an unknown error. The callback functions can serve different purposes and they likely log the detailed error messages. This error message possibly indicates an unhandled error. The first argument indicates a callback type. The second argument prints the subnet id. The third argument prints the lease for which the error has occurred. This log message variant contains no error text because it is triggered by an unknown exception.

## 10.65 DHCPDRV\_LEASE\_MGR\_DB\_OPEN\_CONNECTION\_WITH\_RETRY\_FAILED

Failed to connect to database: %1 with error: %2

This is an informational message issued when the server failed to connect to the lease database. The operation started a retry to connect procedure. The database access string with password redacted is logged, along with the error and details for the reconnect procedure.

## 10.66 DHCPDRV\_LEASE\_SANITY\_FAIL

The lease %1 with subnet-id %2 failed subnet-id checks (%3).

This warning message is printed when the lease being loaded does not match the configuration. Due to lease-checks value, the lease will be loaded, but it will most likely be unused by Kea, as there is no subnet that matches the IP address associated with the lease.

## 10.67 DHCPDRV\_LEASE\_SANITY\_FAIL\_DISCARD

The lease %1 with subnet-id %2 failed subnet-id checks (%3) and was dropped.

This warning message is printed when a lease was loaded, but Kea was told (by setting lease-checks parameter) to discard leases with inconsistent data. The lease was discarded, because either there is no subnet configured with matching subnet-id or the address of the lease does not belong to the subnet.

## 10.68 DHCPDRV\_LEASE\_SANITY\_FIXED

The lease %1 with subnet-id %2 failed subnet-id checks, but was corrected to subnet-id ↔%3.

This informational message is printed when a lease was loaded, but had incorrect subnet-id value. The lease-checks parameter was set to a value that told Kea to try to correct the problem. There is a matching subnet, so Kea updated subnet-id and loaded the lease successfully.

## 10.69 DHCPDRV\_MEMFILE\_ADD\_ADDR4

adding IPv4 lease with address %1

Logged at debug log level 50. A debug message issued when the server is about to add an IPv4 lease with the specified address to the memory file backend database.

## 10.70 DHCPDRV\_MEMFILE\_ADD\_ADDR6

```
adding IPv6 lease with address %1
```

Logged at debug log level 50. A debug message issued when the server is about to add an IPv6 lease with the specified address to the memory file backend database.

## 10.71 DHCPDRV\_MEMFILE\_BEGIN\_BUILD\_EXTENDED\_INFO\_TABLES6

```
building extended info tables with %1 sanity check level, tables %2
```

Logged at debug log level 40. A debug message issued when the server is building extended info tables. The extended info sanity check level and the fact tables are enabled or disabled are displayed.

## 10.72 DHCPDRV\_MEMFILE\_BEGIN\_EXTRACT\_EXTENDED\_INFO4

```
extract extended info with %1 sanity check level%2
```

Logged at debug log level 40. A debug message issued when the server is extracting extended info. The extended info sanity check level and update in file when requested are displayed.

## 10.73 DHCPDRV\_MEMFILE\_BUILD\_EXTENDED\_INFO\_TABLES6

```
building extended info tables saw %1 leases, extended info sanity checks modified %2,
↳ leases and %3 leases were entered into tables
```

Extended info tables build was finished. Some statistics are displayed, the updated in database is returned to the command interface.

## 10.74 DHCPDRV\_MEMFILE\_BUILD\_EXTENDED\_INFO\_TABLES6\_ERROR

```
building extended info tables got an exception on the lease for %1: %2
```

An error message issued when the server is building extended info tables and receives an exception processing a lease.

## 10.75 DHCPDRV\_MEMFILE\_COMMIT

```
committing to memory file database
```

Logged at debug log level 50. The code has issued a commit call. For the memory file database this is a no-op.

## 10.76 DHCPDRV\_MEMFILE\_CONVERTING\_LEASE\_FILES

```
running LFC now to convert lease files to the current schema: %1.%2
```

A warning message issued when the server has detected lease files that need to be either upgraded or downgraded to match the server's schema, and that the server is automatically running the LFC process to perform the conversion. This should only occur the first time the server is launched following a Kea installation upgrade (or downgrade).

## 10.77 DHCPDRV\_MEMFILE\_DB

```
opening memory file lease database: %1
```

This informational message is logged when a DHCP server (either V4 or V6) is about to open a memory file lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

## 10.78 DHCPDRV\_MEMFILE\_DELETE\_ADDR

```
deleting lease for address %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to delete a lease for the specified address from the memory file database for the specified address.

## 10.79 DHCPDRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED4

```
deleting reclaimed IPv4 leases that expired more than %1 seconds ago
```

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

## 10.80 DHCPDRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED6

```
deleting reclaimed IPv6 leases that expired more than %1 seconds ago
```

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

## 10.81 DHCPDRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED\_START

```
starting deletion of %1 expired-reclaimed leases
```

Logged at debug log level 50. A debug message issued when the server has found expired-reclaimed leases to be removed. The number of leases to be removed is logged in the message.

## 10.82 DHCPDRV\_MEMFILE\_EXTRACT\_EXTENDED\_INFO4

```
extracting extended info saw %1 leases, extended info sanity checks modified %2 /_
↳updated %3 leases and %4 leases have relay or remote id
```

Logged at debug log level 40. Extended info extraction was finished. Some statistics are displayed, the updated in database is returned to the command interface.

## 10.83 DHCPDRV\_MEMFILE\_EXTRACT\_EXTENDED\_INFO4\_ERROR

```
extracting extended info got an exception on the lease for %1: %2
```

Logged at debug log level 40. A debug message issued when the server is extracting extended info and receives an exception processing a lease.

## 10.84 DHCPDRV\_MEMFILE\_GET4

```
obtaining all IPv4 leases
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases from the memory file database.

## 10.85 DHCPDRV\_MEMFILE\_GET6

```
obtaining all IPv6 leases
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases from the memory file database.

## 10.86 DHCPDRV\_MEMFILE\_GET6\_DUID

obtaining IPv6 leases for DUID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain IPv6 leases from the memory file database for the DUID.

## 10.87 DHCPDRV\_MEMFILE\_GET\_ADDR4

obtaining IPv4 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for the specified address.

## 10.88 DHCPDRV\_MEMFILE\_GET\_ADDR6

obtaining IPv6 lease for address %1 and lease type %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the memory file database for the specified address.

## 10.89 DHCPDRV\_MEMFILE\_GET\_CLIENTID

obtaining IPv4 leases for client ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified client identification.

## 10.90 DHCPDRV\_MEMFILE\_GET\_EXPIRED4

obtaining maximum %1 of expired IPv4 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

## 10.91 DHCPDRV\_MEMFILE\_GET\_EXPIRED6

obtaining maximum %1 of expired IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

## 10.92 DHCPDRV\_MEMFILE\_GET\_HOSTNAME4

```
obtaining IPv4 leases for hostname %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified hostname.

## 10.93 DHCPDRV\_MEMFILE\_GET\_HOSTNAME6

```
obtaining IPv6 leases for hostname %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the memory file database for a client with the specified hostname.

## 10.94 DHCPDRV\_MEMFILE\_GET\_HWADDR

```
obtaining IPv4 leases for hardware address %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified hardware address.

## 10.95 DHCPDRV\_MEMFILE\_GET\_IAID\_DUID

```
obtaining IPv6 leases for IAID %1 and DUID %2 and lease type %3
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the memory file database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

## 10.96 DHCPDRV\_MEMFILE\_GET\_IAID\_SUBID\_DUID

```
obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3 and lease type %4
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the memory file database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

## 10.97 DHCPDRV\_MEMFILE\_GET\_PAGE4

```
obtaining at most %1 IPv4 leases starting from address %2
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

## 10.98 DHCPDRV\_MEMFILE\_GET\_PAGE6

```
obtaining at most %1 IPv6 leases starting from address %2
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

## 10.99 DHCPDRV\_MEMFILE\_GET\_RELAYID4

```
obtaining at most %1 IPv4 leases starting from address %2 with relay id %3 and cltt_↵  
↵between %4 and %5
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a relay id and client transaction time between start and end dates.

## 10.100 DHCPDRV\_MEMFILE\_GET\_RELAYID6

```
obtaining at most %1 IPv6 leases starting from address %2 with relay id %3
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a relay id.

## 10.101 DHCPDRV\_MEMFILE\_GET\_REMOTEID4

```
obtaining at most %1 IPv4 leases starting from address %2 with remote id %3 and cltt_↵  
↵between %4 and %5
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a remote id and client transaction time between start and end dates.



## 10.102 DHCPDRV\_MEMFILE\_GET\_REMOTEID6

obtaining at most %1 IPv6 leases starting from address %2 with remote id %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a remote id.

## 10.103 DHCPDRV\_MEMFILE\_GET\_SUBID4

obtaining IPv4 leases for subnet ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the memory file database.

## 10.104 DHCPDRV\_MEMFILE\_GET\_SUBID6

obtaining IPv6 leases for subnet ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the memory file database.

## 10.105 DHCPDRV\_MEMFILE\_GET\_SUBID\_CLIENTID

obtaining IPv4 lease for subnet ID %1 and client ID %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified subnet ID and client ID.

## 10.106 DHCPDRV\_MEMFILE\_GET\_SUBID\_HWADDR

obtaining IPv4 lease for subnet ID %1 and hardware address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified subnet ID and hardware address.

## 10.107 DHCPDRV\_MEMFILE\_GET\_SUBID\_PAGE6

obtaining at most %1 IPv6 leases starting from address %2 for subnet ID %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases from the memory file database beginning with the specified address for a given subnet identifier.

## 10.108 DHCPDRV\_MEMFILE\_LEASE\_FILE\_LOAD

```
loading leases from file %1
```

An info message issued when the server is about to start reading DHCP leases from the lease file. All leases currently held in the memory will be replaced by those read from the file.

## 10.109 DHCPDRV\_MEMFILE\_LEASE\_LOAD

```
loading lease %1
```

Logged at debug log level 55. A debug message issued when DHCP lease is being loaded from the file to memory.

## 10.110 DHCPDRV\_MEMFILE\_LEASE\_LOAD\_ROW\_ERROR

```
discarding row %1, error: %2
```

An error message issued if the DHCP lease being loaded from the given row of the lease file fails. The log message should contain the specific reason the row was discarded. The server continues loading the remaining data. This may indicate a corrupt lease file.

## 10.111 DHCPDRV\_MEMFILE\_LFC\_EXECUTE

```
executing Lease File Cleanup using: %1
```

An informational message issued when the memfile lease database backend starts a new process to perform Lease File Cleanup.

## 10.112 DHCPDRV\_MEMFILE\_LFC\_LEASE\_FILE\_RENAME\_FAIL

```
failed to rename the current lease file %1 to %2, reason: %3
```

An error message logged when the memfile lease database backend fails to move the current lease file to a new file on which the cleanup should be performed. This effectively means that the lease file cleanup does not take place.

## 10.113 DHCPDRV\_MEMFILE\_LFC\_LEASE\_FILE\_REOPEN\_FAIL

```
failed to reopen lease file %1 after preparing input file for lease file cleanup,↵  
↵reason: %2, new leases will not persist!
```

An error message logged when the memfile lease database backend failed to re-open or re-create the lease file after renaming the lease file for lease file cleanup. The server continues to operate but leases do not persist to disk.

## 10.114 DHCPDRV\_MEMFILE\_LFC\_SETUP

```
setting up the Lease File Cleanup interval to %1 sec
```

An informational message logged when the memfile lease database backend configures the LFC to be executed periodically. The argument holds the interval in seconds in which the LFC will be executed.

## 10.115 DHCPDRV\_MEMFILE\_LFC\_SPAWN\_FAIL

```
lease file cleanup failed to run because kea-lfc process couldn't be spawned
```

This error message is logged when the Kea server fails to run kea-lfc, the program that cleans up the lease file. The server will try again the next time a lease file cleanup is scheduled. Although this message should not appear and the reason why it did investigated, the occasional failure to start the lease file cleanup will not impact operations. Should the failure persist however, the size of the lease file will increase without bound.

## 10.116 DHCPDRV\_MEMFILE\_LFC\_START

```
starting Lease File Cleanup
```

An informational message issued when the Memfile lease database backend starts the periodic Lease File Cleanup.

## 10.117 DHCPDRV\_MEMFILE\_LFC\_UNREGISTER\_TIMER\_FAILED

```
failed to unregister timer 'memfile-lfc': %1
```

Logged at debug log level 40. This debug message is logged when Memfile backend fails to unregister timer used for lease file cleanup scheduling. There are several reasons why this could occur, although the most likely cause is that the system is being shut down and some other component has unregistered the timer. The message includes the reason for this error.

## 10.118 DHCPDRV\_MEMFILE\_NEEDS\_DOWNGRADING

```
version of lease file: %1 schema is later than version %2
```

A warning message issued when the schema of the lease file loaded by the server is newer than the memfile schema of the server. The server converts the lease data from newer schemas to its schema as it is read, therefore the lease information in use by the server will be correct. Note though, that any data stored in newer schema fields will be dropped. What remains is for the file itself to be rewritten using the current schema.

## 10.119 DHCPDRV\_MEMFILE\_NEEDS\_UPGRADING

```
version of lease file: %1 schema is earlier than version %2
```

A warning message issued when the schema of the lease file loaded by the server pre-dates the memfile schema of the server. Note that the server converts the lease data from older schemas to the current schema as it is read, therefore the lease information in use by the server will be correct. What remains is for the file itself to be rewritten using the current schema.

## 10.120 DHCPDRV\_MEMFILE\_NO\_STORAGE

```
running in non-persistent mode, leases will be lost after restart
```

A warning message issued when writes of leases to disk have been disabled in the configuration. This mode is useful for some kinds of performance testing but should not be enabled in normal circumstances. Non-persistence mode is enabled when 'persist4=no persist6=no' parameters are specified in the database access string.

## 10.121 DHCPDRV\_MEMFILE\_READ\_HWADDR\_FAIL

```
failed to read hardware address from lease file: %1
```

A warning message issued when read attempt of the hardware address stored in a disk file failed. The parameter should provide the exact nature of the failure. The database read will continue, but that particular lease will no longer have hardware address associated with it.

## 10.122 DHCPDRV\_MEMFILE\_ROLLBACK

```
rolling back memory file database
```

Logged at debug log level 50. The code has issued a rollback call. For the memory file database this is a no-op.

## 10.123 DHCPDRV\_MEMFILE\_UPDATE\_ADDR4

```
updating IPv4 lease for address %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv4 lease from the memory file database for the specified address.

## 10.124 DHCPDRV\_MEMFILE\_UPDATE\_ADDR6

```
updating IPv6 lease for address %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv6 lease from the memory file database for the specified address.

## 10.125 DHCPDRV\_MEMFILE\_WIPE\_LEASES4

```
removing all IPv4 leases from subnet %1
```

This informational message is printed when removal of all leases from specified IPv4 subnet is commencing. This is a result of receiving administrative command.

## 10.126 DHCPDRV\_MEMFILE\_WIPE\_LEASES4\_FINISHED

```
removing all IPv4 leases from subnet %1 finished, removed %2 leases
```

This informational message is printed when removal of all leases from a specified IPv4 subnet has finished. The number of removed leases is printed.

## 10.127 DHCPDRV\_MEMFILE\_WIPE\_LEASES6

```
removing all IPv6 leases from subnet %1
```

This informational message is printed when removal of all leases from specified IPv6 subnet is commencing. This is a result of receiving administrative command.

## 10.128 DHCPDRV\_MEMFILE\_WIPE\_LEASES6\_FINISHED

```
removing all IPv6 leases from subnet %1 finished, removed %2 leases
```

This informational message is printed when removal of all leases from a specified IPv6 subnet has finished. The number of removed leases is printed.

## 10.129 DHCPDRV\_MT\_DISABLED\_QUEUE\_CONTROL

```
disabling dhcp queue control when multi-threading is enabled.
```

This warning message is issued when dhcp queue control is disabled automatically if multi-threading is enabled. These two options are incompatible and can not both be enabled at the same time.

## 10.130 DHCPDRV\_MULTIPLE\_RAW\_SOCKETS\_PER\_IFACE

current configuration will result in opening multiple broadcast capable sockets on some\_↵  
↵interfaces and some DHCP messages may be duplicated

A warning message issued when the current configuration indicates that multiple sockets, capable of receiving broadcast traffic, will be opened on some of the interfaces. It must be noted that this may lead to receiving and processing the same DHCP message multiple times, as it will be received by each socket individually.

## 10.131 DHCPDRV\_MYSQL\_ADD\_ADDR4

adding IPv4 lease with address %1

Logged at debug log level 50. A debug message issued when the server is about to add an IPv4 lease with the specified address to the MySQL backend database.

## 10.132 DHCPDRV\_MYSQL\_ADD\_ADDR6

adding IPv6 lease with address %1, lease type %2

Logged at debug log level 50. A debug message issued when the server is about to add an IPv6 lease with the specified address to the MySQL backend database.

## 10.133 DHCPDRV\_MYSQL\_COMMIT

committing to MySQL database

Logged at debug log level 50. The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the commit may not include a write to disk.

## 10.134 DHCPDRV\_MYSQL\_DB

opening MySQL lease database: %1

This informational message is logged when a DHCP server (either V4 or V6) is about to open a MySQL lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

## 10.135 DHCPDRV\_MYSQL\_DELETED\_EXPIRED\_RECLAIMED

```
deleted %1 reclaimed leases from the database
```

Logged at debug log level 50. A debug message issued when the server has removed a number of reclaimed leases from the database. The number of removed leases is included in the message.

## 10.136 DHCPDRV\_MYSQL\_DELETE\_ADDR

```
deleting lease for address %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to delete a lease for the specified address from the MySQL database for the specified address.

## 10.137 DHCPDRV\_MYSQL\_DELETE\_EXPIRED\_RECLAIMED4

```
deleting reclaimed IPv4 leases that expired more than %1 seconds ago
```

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

## 10.138 DHCPDRV\_MYSQL\_DELETE\_EXPIRED\_RECLAIMED6

```
deleting reclaimed IPv6 leases that expired more than %1 seconds ago
```

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

## 10.139 DHCPDRV\_MYSQL\_GET4

```
obtaining all IPv4 leases
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases from the MySQL database.

## 10.140 DHCPDRV\_MYSQL\_GET6

obtaining all IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases from the MySQL database.

## 10.141 DHCPDRV\_MYSQL\_GET\_ADDR4

obtaining IPv4 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for the specified address.

## 10.142 DHCPDRV\_MYSQL\_GET\_ADDR6

obtaining IPv6 lease for address %1, lease type %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for the specified address.

## 10.143 DHCPDRV\_MYSQL\_GET\_CLIENTID

obtaining IPv4 leases for client ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified client identification.

## 10.144 DHCPDRV\_MYSQL\_GET\_DUID

obtaining IPv6 lease for duid %1,

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for the specified duid.

## 10.145 DHCPDRV\_MYSQL\_GET\_EXPIRED4

obtaining maximum %1 of expired IPv4 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.



## 10.146 DHCPDRV\_MYSQL\_GET\_EXPIRED6

obtaining maximum %1 of expired IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

## 10.147 DHCPDRV\_MYSQL\_GET\_HOSTNAME4

obtaining IPv4 leases for hostname %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified hostname.

## 10.148 DHCPDRV\_MYSQL\_GET\_HOSTNAME6

obtaining IPv6 leases for hostname %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database for a client with the specified hostname.

## 10.149 DHCPDRV\_MYSQL\_GET\_HWADDR

obtaining IPv4 leases for hardware address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified hardware address.

## 10.150 DHCPDRV\_MYSQL\_GET\_IAID\_DUID

obtaining IPv6 leases for IAID %1, DUID %2, lease type %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

## 10.151 DHCPDRV\_MYSQL\_GET\_IAID\_SUBID\_DUID

```
obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3, lease type %4
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the MySQL database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

## 10.152 DHCPDRV\_MYSQL\_GET\_PAGE4

```
obtaining at most %1 IPv4 leases starting from address %2
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

## 10.153 DHCPDRV\_MYSQL\_GET\_PAGE6

```
obtaining at most %1 IPv6 leases starting from address %2
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

## 10.154 DHCPDRV\_MYSQL\_GET\_RELAYID4

```
obtaining at most %1 IPv4 leases starting from address %2 with relay id %3 and cltt_↵  
↵between %4 and %5
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a relay id and client transaction time between start and end dates.

## 10.155 DHCPDRV\_MYSQL\_GET\_RELAYID6

```
obtaining at most %1 IPv6 leases starting from address %2 with relay id %3
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a relay id.

## 10.156 DHCPDRV\_MYSQL\_GET\_REMOTEID4

```
obtaining at most %1 IPv4 leases starting from address %2 with remote id %3 and cltt_
->between %4 and %5
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a remote id and client transaction time between start and end dates.

## 10.157 DHCPDRV\_MYSQL\_GET\_REMOTEID6

```
obtaining at most %1 IPv6 leases starting from address %2 with remote id %3
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a remote id.

## 10.158 DHCPDRV\_MYSQL\_GET\_SUBID4

```
obtaining IPv4 leases for subnet ID %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the MySQL database.

## 10.159 DHCPDRV\_MYSQL\_GET\_SUBID6

```
obtaining IPv6 leases for subnet ID %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the MySQL database.

## 10.160 DHCPDRV\_MYSQL\_GET\_SUBID\_CLIENTID

```
obtaining IPv4 lease for subnet ID %1 and client ID %2
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for a client with the specified subnet ID and client ID.

## 10.161 DHCPDRV\_MYSQL\_GET\_SUBID\_HWADDR

```
obtaining IPv4 lease for subnet ID %1 and hardware address %2
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the MySQL database for a client with the specified subnet ID and hardware address.

## 10.162 DHCPDRV\_MYSQL\_GET\_SUBID\_PAGE6

```
obtaining at most %1 IPv6 leases starting from address %2 for subnet ID %3
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases from the MySQL database beginning with the specified address for the specified subnet identifier.

## 10.163 DHCPDRV\_MYSQL\_GET\_VERSION

```
obtaining schema version information
```

Logged at debug log level 50. A debug message issued when the server is about to obtain schema version information from the MySQL database.

## 10.164 DHCPDRV\_MYSQL\_HOST\_DB

```
opening MySQL hosts database: %1
```

Logged at debug log level 50. This informational message is logged when a DHCP server (either V4 or V6) is about to open a MySQL hosts database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

## 10.165 DHCPDRV\_MYSQL\_HOST\_DB\_GET\_VERSION

```
obtaining schema version information for the MySQL hosts database
```

Logged at debug log level 50. A debug message issued when the server is about to obtain schema version information from the MySQL hosts database.

## 10.166 DHCPDRV\_MYSQL\_HOST\_DB\_READONLY

```
MySQL host database opened for read access only
```

This informational message is issued when the user has configured the MySQL database in read-only mode. Kea will not be able to insert or modify host reservations but will be able to retrieve existing ones and assign them to the clients communicating with the server.

## 10.167 DHCPDRV\_MYSQL\_HOST\_DB\_RECONNECT\_ATTEMPT\_FAILED

```
database reconnect failed: %1
```

An error message issued when an attempt to reconnect has failed.

## 10.168 DHCPDRV\_MYSQL\_HOST\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE

```
scheduling attempt %1 of %2 in %3 milliseconds
```

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

## 10.169 DHCPDRV\_MYSQL\_HOST\_DB\_RECONNECT\_FAILED

```
maximum number of database reconnect attempts: %1, has been exhausted without success
```

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 10.170 DHCPDRV\_MYSQL\_LEASE\_DB\_RECONNECT\_ATTEMPT\_FAILED

```
database reconnect failed: %1
```

An error message issued when an attempt to reconnect has failed.

## 10.171 DHCPDRV\_MYSQL\_LEASE\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE

```
scheduling attempt %1 of %2 in %3 milliseconds
```

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

## 10.172 DHCPDRV\_MYSQL\_LEASE\_DB\_RECONNECT\_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 10.173 DHCPDRV\_MYSQL\_NEGATIVE\_LEASES\_STAT

recount of leases returned a negative value

This warning message is issued when the recount of leases using counters in the MySQL database returned a negative value. This shows a problem which can be fixed only by an offline direct recount on the database. This message is issued only once.

## 10.174 DHCPDRV\_MYSQL\_NO\_TLS

TLS was required but is not used

This error message is issued when TLS for the connection was required but TLS is not used.

## 10.175 DHCPDRV\_MYSQL\_ROLLBACK

rolling back MySQL database

Logged at debug log level 50. The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

## 10.176 DHCPDRV\_MYSQL\_TLS\_CIPHER

TLS cipher: %1

Logged at debug log level 40. A debug message issued when a new MySQL connection is created with TLS. The TLS cipher name is logged.

## 10.177 DHCPDRV\_MYSQL\_UPDATE\_ADDR4

updating IPv4 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv4 lease from the MySQL database for the specified address.

## 10.178 DHCPDRV\_MYSQL\_UPDATE\_ADDR6

```
updating IPv6 lease for address %1, lease type %2
```

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv6 lease from the MySQL database for the specified address.

## 10.179 DHCPDRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO4

```
upgrading IPv4 leases done in %1 pages with %2 updated leases
```

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

## 10.180 DHCPDRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO4\_ERROR

```
upgrading extending info for IPv4 lease at %1 failed with %2
```

Logged at debug log level 40. A debug message issued when the server failed to upgrade an extended info. The address of the lease and the error message are displayed.

## 10.181 DHCPDRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO4\_PAGE

```
upgrading IPv4 lease extended info at page %1 starting at %2 (updated %3)
```

Logged at debug log level 50. A debug message issued when the server upgrades IPv4 lease extended info. The page number and started address, and the count of already updated leases are displayed.

## 10.182 DHCPDRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO6

```
upgrading IPv6 leases done in %1 pages with %2 updated leases
```

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

## 10.183 DHCPDRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO6\_ERROR

```
upgrading extending info for IPv6 lease at %1 failed with %2
```

Logged at debug log level 40. A debug message issued when the server failed to upgrade the extended info for a lease. The address of the lease and the error message are displayed.

## 10.184 DHCPDRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO6\_PAGE

```
upgrading IPv6 lease extended info at page %1 starting at %2 (updated %3)
```

Logged at debug log level 50. A debug message issued when the server upgrades IPv6 lease extended info. The page number and started address, and the count of already updated leases are displayed.

## 10.185 DHCPDRV\_NOTYPE\_DB

```
no 'type' keyword to determine database backend: %1
```

This is an error message, logged when an attempt has been made to access a database backend, but where no 'type' keyword has been included in the access string. The access string (less any passwords) is included in the message.

## 10.186 DHCPDRV\_NO\_SOCKETS\_OPEN

```
no interface configured to listen to DHCP traffic
```

This warning message is issued when the current server configuration specifies no interfaces that the server should listen on, or when the specified interfaces are not configured to receive the traffic.

## 10.187 DHCPDRV\_OPEN\_SOCKET\_FAIL

```
failed to open socket: %1
```

A warning message issued when IfaceMgr fails to open and bind a socket. The reason for the failure is appended as an argument of the log message.

## 10.188 DHCPDRV\_PGSQL\_ADD\_ADDR4

```
adding IPv4 lease with address %1
```

Logged at debug log level 50. A debug message issued when the server is about to add an IPv4 lease with the specified address to the PostgreSQL backend database.

## 10.189 DHCPDRV\_PGSQL\_ADD\_ADDR6

```
adding IPv6 lease with address %1, lease type %2
```

Logged at debug log level 50. A debug message issued when the server is about to add an IPv6 lease with the specified address to the PostgreSQL backend database.



## 10.190 DHCPDRV\_PGSQL\_COMMIT

```
committing to PostgreSQL database
```

Logged at debug log level 50. The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the commit may not include a write to disk.

## 10.191 DHCPDRV\_PGSQL\_DB

```
opening PostgreSQL lease database: %1
```

This informational message is logged when a DHCP server (either V4 or V6) is about to open a PostgreSQL lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

## 10.192 DHCPDRV\_PGSQL\_DELETE\_ADDR

```
deleting lease for address %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to delete a lease for the specified address from the PostgreSQL database for the specified address.

## 10.193 DHCPDRV\_PGSQL\_DELETE\_EXPIRED\_RECLAIMED4

```
deleting reclaimed IPv4 leases that expired more than %1 seconds ago
```

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

## 10.194 DHCPDRV\_PGSQL\_DELETE\_EXPIRED\_RECLAIMED6

```
deleting reclaimed IPv6 leases that expired more than %1 seconds ago
```

Logged at debug log level 50. A debug message issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

## 10.195 DHCPDRV\_PGSQL\_GET4

obtaining all IPv4 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases from the PostgreSQL database.

## 10.196 DHCPDRV\_PGSQL\_GET6

obtaining all IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases from the PostgreSQL database.

## 10.197 DHCPDRV\_PGSQL\_GET\_ADDR4

obtaining IPv4 lease for address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for the specified address.

## 10.198 DHCPDRV\_PGSQL\_GET\_ADDR6

obtaining IPv6 lease for address %1 (lease type %2)

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the PostgreSQL database for the specified address.

## 10.199 DHCPDRV\_PGSQL\_GET\_CLIENTID

obtaining IPv4 leases for client ID %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified client identification.

## 10.200 DHCPDRV\_PGSQL\_GET\_DUID

obtaining IPv6 leases for DUID %1,

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified DUID (DHCP Unique Identifier).

## 10.201 DHCPDRV\_PGSQL\_GET\_EXPIRED4

obtaining maximum %1 of expired IPv4 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

## 10.202 DHCPDRV\_PGSQL\_GET\_EXPIRED6

obtaining maximum %1 of expired IPv6 leases

Logged at debug log level 50. A debug message issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

## 10.203 DHCPDRV\_PGSQL\_GET\_HOSTNAME4

obtaining IPv4 leases for hostname %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified hostname.

## 10.204 DHCPDRV\_PGSQL\_GET\_HOSTNAME6

obtaining IPv6 leases for hostname %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified hostname.

## 10.205 DHCPDRV\_PGSQL\_GET\_HWADDR

obtaining IPv4 leases for hardware address %1

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified hardware address.

## 10.206 DHCPDRV\_PGSQL\_GET\_IAID\_DUID

obtaining IPv4 leases for IAID %1 and DUID %2, lease type %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

## 10.207 DHCPDRV\_PGSQL\_GET\_IAID\_SUBID\_DUID

obtaining IPv4 leases for IAID %1, Subnet ID %2, DUID %3, and lease type %4

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv6 lease from the PostgreSQL database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

## 10.208 DHCPDRV\_PGSQL\_GET\_PAGE4

obtaining at most %1 IPv4 leases starting from address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

## 10.209 DHCPDRV\_PGSQL\_GET\_PAGE6

obtaining at most %1 IPv6 leases starting from address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of leases beginning with the specified address.

## 10.210 DHCPDRV\_PGSQL\_GET\_RELAYID4

obtaining at most %1 IPv4 leases starting from address %2 with relay id %3 and cltt\_↵  
↵between %4 and %5

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a relay id and client transaction time between start and end dates.

## 10.211 DHCPDRV\_PGSQL\_GET\_RELAYID6

obtaining at most %1 IPv6 leases starting from address %2 with relay id %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a relay id.

## 10.212 DHCPDRV\_PGSQL\_GET\_REMOTEID4

```
obtaining at most %1 IPv4 leases starting from address %2 with remote id %3 and cltt_
->between %4 and %5
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a remote id and client transaction time between start and end dates.

## 10.213 DHCPDRV\_PGSQL\_GET\_REMOTEID6

```
obtaining at most %1 IPv6 leases starting from address %2 with remote id %3
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a remote id.

## 10.214 DHCPDRV\_PGSQL\_GET\_SUBID4

```
obtaining IPv4 leases for subnet ID %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the PostgreSQL database.

## 10.215 DHCPDRV\_PGSQL\_GET\_SUBID6

```
obtaining IPv6 leases for subnet ID %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the PostgreSQL database.

## 10.216 DHCPDRV\_PGSQL\_GET\_SUBID\_CLIENTID

```
obtaining IPv4 lease for subnet ID %1 and client ID %2
```

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for a client with the specified subnet ID and client ID.

## 10.217 DHCPDRV\_PGSQL\_GET\_SUBID\_HWADDR

obtaining IPv4 lease for subnet ID %1 and hardware address %2

Logged at debug log level 50. A debug message issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for a client with the specified subnet ID and hardware address.

## 10.218 DHCPDRV\_PGSQL\_GET\_SUBID\_PAGE6

obtaining at most %1 IPv6 leases starting from address %2 for subnet ID %3

Logged at debug log level 50. A debug message issued when the server is attempting to obtain a page of IPv6 leases from the PostgreSQL database beginning with the specified address for the specified subnet identifier.

## 10.219 DHCPDRV\_PGSQL\_GET\_VERSION

obtaining schema version information

Logged at debug log level 50. A debug message issued when the server is about to obtain schema version information from the PostgreSQL database.

## 10.220 DHCPDRV\_PGSQL\_HOST\_DB

opening PostgreSQL hosts database: %1

Logged at debug log level 50. This informational message is logged when a DHCP server (either V4 or V6) is about to open a PostgreSQL hosts database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

## 10.221 DHCPDRV\_PGSQL\_HOST\_DB\_GET\_VERSION

obtaining schema version information for the PostgreSQL hosts database

Logged at debug log level 50. A debug message issued when the server is about to obtain schema version information from the PostgreSQL hosts database.

## 10.222 DHCPDRV\_PGSQL\_HOST\_DB\_READONLY

```
PostgreSQL host database opened for read access only
```

This informational message is issued when the user has configured the PostgreSQL database in read-only mode. Kea will not be able to insert or modify host reservations but will be able to retrieve existing ones and assign them to the clients communicating with the server.

## 10.223 DHCPDRV\_PGSQL\_HOST\_DB\_RECONNECT\_ATTEMPT\_FAILED

```
database reconnect failed: %1
```

An error message issued when an attempt to reconnect has failed.

## 10.224 DHCPDRV\_PGSQL\_HOST\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE

```
scheduling attempt %1 of %2 in %3 milliseconds
```

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

## 10.225 DHCPDRV\_PGSQL\_HOST\_DB\_RECONNECT\_FAILED

```
maximum number of database reconnect attempts: %1, has been exhausted without success
```

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 10.226 DHCPDRV\_PGSQL\_LEASE\_DB\_RECONNECT\_ATTEMPT\_FAILED

```
database reconnect failed: %1
```

An error message issued when an attempt to reconnect has failed.

## 10.227 DHCPDRV\_PGSQL\_LEASE\_DB\_RECONNECT\_ATTEMPT\_SCHEDULE

```
scheduling attempt %1 of %2 in %3 milliseconds
```

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

## 10.228 DHCPDRV\_PGSQL\_LEASE\_DB\_RECONNECT\_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 10.229 DHCPDRV\_PGSQL\_NEGATIVE\_LEASES\_STAT

recount of leases returned a negative value

This warning message is issued when the recount of leases using counters in the PostgreSQL database returned a negative value. This shows a problem which can be fixed only by an offline direct recount on the database. This message is issued only once.

## 10.230 DHCPDRV\_PGSQL\_NO\_TLS\_SUPPORT

Attempt to configure TLS (unsupported for PostgreSQL): %1

This error message is printed when TLS support was required in the Kea configuration: Kea was built with this feature disabled for PostgreSQL. The parameters of the connection are logged.

## 10.231 DHCPDRV\_PGSQL\_ROLLBACK

rolling back PostgreSQL database

Logged at debug log level 50. The code has issued a rollback call. All outstanding transaction will be rolled back and not committed to the database.

## 10.232 DHCPDRV\_PGSQL\_TLS\_SUPPORT

Attempt to configure TLS: %1

This informational message is printed when TLS support was required in the Kea configuration: The TLS support in PostgreSQL will be initialized but its configuration is fully managed outside the C API. The parameters of the connection are logged.



### 10.233 DHCPDRV\_PGSQL\_UPDATE\_ADDR4

```
updating IPv4 lease for address %1
```

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv4 lease from the PostgreSQL database for the specified address.

### 10.234 DHCPDRV\_PGSQL\_UPDATE\_ADDR6

```
updating IPv6 lease for address %1, lease type %2
```

Logged at debug log level 50. A debug message issued when the server is attempting to update IPv6 lease from the PostgreSQL database for the specified address.

### 10.235 DHCPDRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO4

```
upgrading IPv4 leases done in %1 pages with %2 updated leases
```

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

### 10.236 DHCPDRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO4\_ERROR

```
upgrading extending info for IPv4 lease at %1 failed with %2
```

Logged at debug log level 40. A debug message issued when the server failed to upgrade an extended info. The address of the lease and the error message are displayed.

### 10.237 DHCPDRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO4\_PAGE

```
upgrading IPv4 lease extended info at page %1 starting at %2 (updated %3)
```

Logged at debug log level 50. A debug message issued when the server upgrades IPv4 lease extended info. The page number and started address, and the count of already updated leases are displayed.

### 10.238 DHCPDRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO6

```
upgrading IPv6 leases done in %1 pages with %2 updated leases
```

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

## 10.239 DHCPDRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO6\_ERROR

```
upgrading extending info for IPv6 lease at %1 failed with %2
```

Logged at debug log level 40. A debug message issued when the server failed to upgrade the extended info for a lease. The address of the lease and the error message are displayed.

## 10.240 DHCPDRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO6\_PAGE

```
upgrading IPv6 lease extended info at page %1 starting at %2 (updated %3)
```

Logged at debug log level 50. A debug message issued when the server upgrades IPv6 lease extended info. The page number and started address, and the count of already updated leases are displayed.

## 10.241 DHCPDRV\_QUEUE\_NCR

```
%1: Name change request to %2 DNS entry queued: %3
```

Logged at debug log level 50. A debug message which is logged when the NameChangeRequest to add or remove a DNS entries for a particular lease has been queued. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument carries the details of the NameChangeRequest.

## 10.242 DHCPDRV\_QUEUE\_NCR\_FAILED

```
%1: queuing %2 name change request failed for lease %3: %4
```

This error message is logged when sending a NameChangeRequest to DHCP DDNS failed. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument specifies the leased address. The last argument provides the reason for failure.

## 10.243 DHCPDRV\_QUEUE\_NCR\_SKIP

```
%1: skip queuing name change request for lease: %2
```

Logged at debug log level 50. This debug message is issued when the server decides to not queue the name change request because the lease doesn't include the FQDN, the forward and reverse update is disabled for this lease or the DNS updates are disabled in the configuration. The first argument includes the client identification information. The second argument includes the leased address.

## 10.244 DHCPDRV\_SUBNET4O6\_SELECT\_FAILED

```
Failed to select any subnet for the DHCPv4o6 packet
```

Logged at debug log level 40. A debug message issued when the server was unable to select any subnet for the DHCPv4o6 packet.

## 10.245 DHCPDRV\_SUBNET4\_SELECT\_BY\_ADDRESS\_NO\_MATCH

```
No subnet matches address: %1
```

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified address.

## 10.246 DHCPDRV\_SUBNET4\_SELECT\_BY\_INTERFACE\_NO\_MATCH

```
No subnet matches interface: %1
```

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified interface name.

## 10.247 DHCPDRV\_SUBNET4\_SELECT\_BY\_RELAY\_ADDRESS\_NO\_MATCH

```
No subnet matches relay address: %1
```

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified relay address.

## 10.248 DHCPDRV\_SUBNET4\_SELECT\_NO\_RAI\_OPTIONS

```
No RAI options found to use for subnet selection.
```

Logged at debug log level 40. A debug message issued by the server when the client query does not include RAI options suitable for use with subnet selection.

## 10.249 DHCPDRV\_SUBNET4\_SELECT\_NO\_RELAY\_ADDRESS

```
Relay address (giaddr) in client packet is empty.
```

Logged at debug log level 40. A debug message issued when no relay address was specified to use for subnet selection.

## 10.250 DHCPDRV\_SUBNET4\_SELECT\_NO\_USABLE\_ADDRESS

No subnet selected because no suitable address to use for subnet selection was found.

Logged at debug log level 40. A debug message issued when the server was find a suitable address to use for subnet selection.

## 10.251 DHCPDRV\_SUBNET6\_SELECT\_BY\_ADDRESS\_NO\_MATCH

No subnet matches address: %1

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified address.

## 10.252 DHCPDRV\_SUBNET6\_SELECT\_BY\_INTERFACE\_ID\_NO\_MATCH

No subnet matches interface id: %1

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified interface id.

## 10.253 DHCPDRV\_SUBNET6\_SELECT\_BY\_INTERFACE\_NO\_MATCH

No subnet matches interface: %1

Logged at debug log level 40. A debug message issued when the server was unable to select a subnet using the specified interface name.

## 10.254 DHCPDRV\_TEMPLATE\_EVAL\_ERROR

%1: Expression '%2' evaluated to %3

This error message indicates that there a problem was encountered while evaluating an expression of a template client class. A description of the problem is printed.

## 10.255 DHCPDRV\_TEMPLATE\_EVAL\_RESULT

%1: Expression '%2' evaluated to %3

Logged at debug log level 50. This debug message indicates that the expression of a template client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

## 10.256 DHCPDRV\_TIMERMGR\_CALLBACK\_FAILED

```
running handler for timer %1 caused exception: %2
```

This error message is emitted when the timer elapsed and the operation associated with this timer has thrown an exception. The timer name and the reason for exception is logged.

## 10.257 DHCPDRV\_TIMERMGR\_REGISTER\_TIMER

```
registering timer: %1, using interval: %2 ms
```

Logged at debug log level 40. A debug message issued when the new interval timer is registered in the Timer Manager. This timer will have a callback function associated with it, and this function will be executed according to the interval specified. The unique name of the timer and the interval at which the callback function will be executed is included in the message.

## 10.258 DHCPDRV\_TIMERMGR\_RUN\_TIMER\_OPERATION

```
running operation for timer: %1
```

Logged at debug log level 50. A debug message issued when the Timer Manager is about to run a periodic operation associated with the given timer. An example of such operation is a periodic cleanup of expired leases. The name of the timer is included in the message.

## 10.259 DHCPDRV\_TIMERMGR\_START\_TIMER

```
starting timer: %1
```

Logged at debug log level 40. A debug message issued when the registered interval timer is being started. If this operation is successful the timer will periodically execute the operation associated with it. The name of the started timer is included in the message.

## 10.260 DHCPDRV\_TIMERMGR\_STOP\_TIMER

```
stopping timer: %1
```

Logged at debug log level 40. A debug message issued when the registered interval timer is being stopped. The timer remains registered and can be restarted if necessary. The name of the timer is included in the message.

## 10.261 DHCPDRV\_TIMERMGR\_UNREGISTER\_ALL\_TIMERS

unregistering all timers

Logged at debug log level 40. A debug message issued when all registered interval timers are being unregistered from the Timer Manager.

## 10.262 DHCPDRV\_TIMERMGR\_UNREGISTER\_TIMER

unregistering timer: %1

Logged at debug log level 40. A debug message issued when one of the registered interval timers is unregistered from the Timer Manager. The name of the timer is included in the message.

## 11.1 DHCP\_DDNS\_ADD\_FAILED

```
DHCP_DDNS Request ID %1: Transaction outcome %2
```

This is an error message issued after DHCP\_DDNS attempts to submit DNS mapping entry additions have failed. The precise reason for the failure should be documented in preceding log entries.

## 11.2 DHCP\_DDNS\_ADD\_SUCCEEDED

```
DHCP_DDNS Request ID %1: successfully added the DNS mapping addition for this request: %2
```

This is an informational message issued after DHCP\_DDNS has submitted DNS mapping additions which were received and accepted by an appropriate DNS server.

## 11.3 DHCP\_DDNS\_AT\_MAX\_TRANSACTIONS

```
application has %1 queued requests but has reached maximum number of %2 concurrent_↵  
↵transactions
```

Logged at debug log level 55. This is a debug message that indicates that the application has DHCP\_DDNS requests in the queue but is working as many concurrent requests as allowed.

## 11.4 DHCP\_DDNS\_CLEARED\_FOR\_SHUTDOWN

```
application has met shutdown criteria for shutdown type: %1
```

Logged at debug log level 0. This is a debug message issued when the application has been instructed to shutdown and has met the required criteria to exit.

## 11.5 DHCP\_DDNS\_CONFIGURE

```
configuration %1 received: %2
```

Logged at debug log level 40. This is a debug message issued when the DHCP-DDNS application configure method has been invoked.

## 11.6 DHCP\_DDNS\_CONFIGURED\_CALLOUT\_DROP

```
configuration was rejected because a callout set the next step to 'drop': %1
```

This error message indicates that the DHCP-DDNS had failed configuration attempt because the next step of the configured callout was set to 'drop' by a hook library. The error message provided by the hook library is displayed.

## 11.7 DHCP\_DDNS\_CONFIG\_CHECK\_FAIL

```
DHCP-DDNS server configuration check failed: %1
```

This error message indicates that the DHCP-DDNS had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

## 11.8 DHCP\_DDNS\_CONFIG\_FAIL

```
DHCP-DDNS server configuration failed: %1
```

This error message indicates that the DHCP-DDNS had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

## 11.9 DHCP\_DDNS\_CONFIG\_SYNTAX\_WARNING

```
DHCP-DDNS server configuration syntax warning: %1
```

This warning message indicates that the DHCP-DDNS configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

## 11.10 DHCP\_DDNS\_FAILED

```
application experienced a fatal error: %1
```

This is a debug message issued when the DHCP-DDNS application encounters an unrecoverable error from within the event loop.



## 11.11 DHCP\_DDNS\_FORWARD\_ADD\_BAD\_DNSCLIENT\_STATUS

```
DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while adding a
↳forward address mapping for FQDN %3 to DNS server %4
```

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was adding a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

## 11.12 DHCP\_DDNS\_FORWARD\_ADD\_BUILD\_FAILURE

```
DNS Request ID %1: update message to add a forward DNS entry could not be constructed.
↳for this request: %2, reason: %3
```

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address addition. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

## 11.13 DHCP\_DDNS\_FORWARD\_ADD\_IO\_ERROR

```
DHCP_DDNS Request ID %1: encountered an IO error sending a forward mapping add for FQDN
↳%2 to DNS server %3
```

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward address add. The application will retry against the same server or others as appropriate.

## 11.14 DHCP\_DDNS\_FORWARD\_ADD\_REJECTED

```
DNS Request ID %1: Server, %2, rejected a DNS update request to add the address mapping.
↳for FQDN, %3, with an RCODE: %4
```

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

## 11.15 DHCP\_DDNS\_FORWARD\_ADD\_RESP\_CORRUPT

```
DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while
↳adding forward address mapping for FQDN, %3
```

This is an error message issued when the response received by DHCP\_DDNS, to a update request to add a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

## 11.16 DHCP\_DDNS\_FORWARD\_ADD\_TIMEOUT

```
DHCP_DDNS Request ID %1: timed out waiting for a response to forward mapping add for ↵  
↵FQDN %2 to DNS server %3
```

This is an error message issued when no response is received from the DNS server before exceeding `dns-server-timeout` while DHCP\_DDNS is carrying out a forward address add. The application will retry against the same server or others as appropriate.

## 11.17 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_BAD\_DNSCLIENT\_STATUS

```
DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while removing a ↵  
↵forward address mapping for FQDN %3 to DNS server %4
```

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

## 11.18 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_BUILD\_FAILURE

```
DNS Request ID %1: update message to remove a forward DNS Address entry could not be ↵  
↵constructed for this request: %2, reason: %3
```

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address (A or AAAA) removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue. */sar/*

## 11.19 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_IO\_ERROR

```
DHCP_DDNS Request ID %1: encountered an IO error sending a forward mapping address ↵  
↵removal for FQDN %2 to DNS server %3
```

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward address remove. The application will retry against the same server or others as appropriate.

## 11.20 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_REJECTED

```
DNS Request ID %1: Server, %2, rejected a DNS update request to remove the forward ↵  
↵address mapping for FQDN, %3, with an RCODE: %4
```

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

## 11.21 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_RESP\_CORRUPT

```
DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while
↔removing forward address mapping for FQDN, %3
```

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

## 11.22 DHCP\_DDNS\_FORWARD\_REMOVE\_ADDRS\_TIMEOUT

```
DHCP_DDNS Request ID %1: timed out waiting for a response to forward mapping address.
↔removal for FQDN %2 to DNS server %3
```

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP\_DDNS is carrying out a forward mapping address removal. The application will retry against the same server or others as appropriate.

## 11.23 DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_BAD\_DNSCLIENT\_STATUS

```
DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while removing
↔forward RRs for FQDN %3 to DNS server %4
```

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing forward RRs. The request will be aborted. This is most likely a programmatic issue and should be reported.

## 11.24 DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_BUILD\_FAILURE

```
DNS Request ID %1: update message to remove forward DNS RR entries could not be
↔constructed for this request: %2, reason: %3
```

This is an error message issued when an error occurs attempting to construct the server bound packet requesting forward RR (DHCID RR) removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

## 11.25 DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_IO\_ERROR

```
DHCP_DDNS Request ID %1: encountered an IO error sending a forward RR removal for FQDN
↔%2 to DNS server %3
```

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward RR remove. The application will retry against the same server.

## 11.26 DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_REJECTED

```
DNS Request ID %1: Server, %2, rejected a DNS update request to remove forward RR_
↳entries for FQDN, %3, with an RCODE: %4
```

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

## 11.27 DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_RESP\_CORRUPT

```
DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while_
↳removing forward RRs for FQDN, %3
```

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove forward RRs mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.  
*lsarl*

## 11.28 DHCP\_DDNS\_FORWARD\_REMOVE\_RRS\_TIMEOUT

```
DHCP_DDNS Request ID %1: timed out waiting for response to forward RR removal for FQDN
↳%2 to DNS server %3
```

This is an error message issued when no response is received from the DNS server before exceeding `dns-server-timeout` while DHCP\_DDNS is carrying out a forward RR removal. The application will retry against the same server or others as appropriate.

## 11.29 DHCP\_DDNS\_FORWARD\_REPLACE\_BAD\_DNSCLIENT\_STATUS

```
DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while replacing_
↳forward address mapping for FQDN %3 to DNS server %4
```

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was replacing a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

## 11.30 DHCP\_DDNS\_FORWARD\_REPLACE\_BUILD\_FAILURE

```
DNS Request ID %1: update message to replace a forward DNS entry could not be_
↳constructed from this request: %2, reason: %3
```

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address replacement. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

## 11.31 DHCP\_DDNS\_FORWARD\_REPLACE\_IO\_ERROR

```
DHCP_DDNS Request ID %1: encountered an IO error sending a forward mapping replace for
↳FQDN %2 to DNS server %3
```

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a forward mapping replace. The application will retry against the same server or others as appropriate.

## 11.32 DHCP\_DDNS\_FORWARD\_REPLACE\_REJECTED

```
DNS Request ID %1: Server, %2, rejected a DNS update request to replace the address
↳mapping for FQDN, %3, with an RCODE: %4
```

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

## 11.33 DHCP\_DDNS\_FORWARD\_REPLACE\_RESP\_CORRUPT

```
DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while
↳replacing forward address mapping for FQDN, %3
```

This is an error message issued when the response received by DHCP\_DDNS, to a update request to replace a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

## 11.34 DHCP\_DDNS\_FORWARD\_REPLACE\_TIMEOUT

```
DHCP_DDNS Request ID %1: timed out waiting for a response to forward mapping replace for
↳FQDN %2 to DNS server %3
```

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP\_DDNS is carrying out a forward mapping replace. The application will retry against the same server or others as appropriate.

## 11.35 DHCP\_DDNS\_FWD\_REQUEST\_IGNORED

```
Request ID %1: Forward updates are disabled, the forward portion of request will be
↳ignored: %2
```

Logged at debug log level 55. This is a debug message issued when forward DNS updates are disabled and DHCP\_DDNS receives an update request containing a forward DNS update. The forward update will not performed.

## 11.36 DHCP\_DDNS\_INVALID\_NCR

```
application received an invalid DNS update request: %1
```

This is an error message that indicates that an invalid request to update a DNS entry was received by the application. Either the format or the content of the request is incorrect. The request will be ignored.

## 11.37 DHCP\_DDNS\_INVALID\_RESPONSE

```
received response to DNS Update message is malformed: %1
```

Logged at debug log level 50. This is a debug message issued when the DHCP-DDNS application encountered an error while decoding a response to DNS Update message. Typically, this error will be encountered when a response message is malformed.

## 11.38 DHCP\_DDNS\_LISTENING\_ON\_ALL\_INTERFACES

```
the DHCP-DDNS server has been configured to listen on %1. This is an insecure ↵  
↵configuration supported for testing purposes only
```

This is a warning message issued when the DHCP-DDNS server is configured to listen at either *0.0.0.0* or *::*. It is possible for a malicious attacker to send bogus NameChangeRequests to it and change entries in the DNS. For this reason, listening on all interfaces should only be used when deploying in containers or for testing purposes. A future version of Kea will disable this ability by default.

## 11.39 DHCP\_DDNS\_NCR\_FLUSH\_IO\_ERROR

```
DHCP-DDNS Last send before stopping did not complete successfully: %1
```

This is an error message that indicates the DHCP-DDNS client was unable to complete the last send prior to exiting send mode. This is a programmatic error, highly unlikely to occur, and should not impair the application's ability to process requests.

## 11.40 DHCP\_DDNS\_NCR\_LISTEN\_CLOSE\_ERROR

```
application encountered an error while closing the listener used to receive ↵  
↵NameChangeRequests : %1
```

This is an error message that indicates the application was unable to close the listener connection used to receive NameChangeRequests. Closure may occur during the course of error recovery or during normal shutdown procedure. In either case the error is unlikely to impair the application's ability to process requests but it should be reported for analysis.

## 11.41 DHCP\_DDNS\_NCR\_RECV\_NEXT\_ERROR

application could not initiate the next read following a request receive.

This is an error message indicating that NameChangeRequest listener could not start another read after receiving a request. While possible, this is highly unlikely and is probably a programmatic error. The application should recover on its own.

## 11.42 DHCP\_DDNS\_NCR\_SEND\_CLOSE\_ERROR

DHCP-DDNS client encountered an error while closing the sender connection used to send.  
↔NameChangeRequests: %1

This is an error message that indicates the DHCP-DDNS client was unable to close the connection used to send NameChangeRequests. Closure may occur during the course of error recovery or during normal shutdown procedure. In either case the error is unlikely to impair the client's ability to send requests but it should be reported for analysis.

## 11.43 DHCP\_DDNS\_NCR\_SEND\_NEXT\_ERROR

DHCP-DDNS client could not initiate the next request send following send completion: %1

This is an error message indicating that NameChangeRequest sender could not start another send after completing the send of the previous request. While possible, this is highly unlikely and is probably a programmatic error. The application should recover on its own.

## 11.44 DHCP\_DDNS\_NCR\_UDP\_CLEAR\_READY\_ERROR

NCR UDP watch socket failed to clear: %1

This is an error message that indicates the application was unable to reset the UDP NCR sender ready status after completing a send. This is programmatic error that should be reported. The application may or may not continue to operate correctly.

## 11.45 DHCP\_DDNS\_NCR\_UDP\_RECV\_CANCELED

UDP socket receive was canceled while listening for DNS Update requests

Logged at debug log level 40. This is a debug message indicating that the listening on a UDP socket for DNS update requests has been canceled. This is a normal part of suspending listening operations.

## 11.46 DHCP\_DDNS\_NCR\_UDP\_RECV\_ERROR

```
UDP socket receive error while listening for DNS Update requests: %1
```

This is an error message indicating that an I/O error occurred while listening over a UDP socket for DNS update requests. This could indicate a network connectivity or system resource issue.

## 11.47 DHCP\_DDNS\_NCR\_UDP\_SEND\_CANCELED

```
UDP socket send was canceled while sending a DNS Update request to DHCP_DDNS: %1
```

This is an informational message indicating that sending requests via UDP socket to DHCP\_DDNS has been interrupted. This is a normal part of suspending send operations.

## 11.48 DHCP\_DDNS\_NCR\_UDP\_SEND\_ERROR

```
UDP socket send error while sending a DNS Update request: %1
```

This is an error message indicating that an IO error occurred while sending a DNS update request to DHCP\_DDNS over a UDP socket. This could indicate a network connectivity or system resource issue.

## 11.49 DHCP\_DDNS\_NOT\_ON\_LOOPBACK

```
the DHCP-DDNS server has been configured to listen on %1 which is not the local loopback.  
↪ This is an insecure configuration supported for testing purposes only
```

This is a warning message issued when the DHCP-DDNS server is configured to listen at an address other than the loopback address (127.0.0.1 or ::1). It is possible for a malicious attacker to send bogus NameChangeRequests to it and change entries in the DNS. For this reason, addresses other than the IPv4 or IPv6 loopback addresses should only be used for testing purposes. A future version of Kea will implement authentication to guard against such attacks.

## 11.50 DHCP\_DDNS\_NO\_ELIGIBLE\_JOBS

```
although there are queued requests, there are pending transactions for each, Queue_  
↪count: %1 Transaction count: %2
```

Logged at debug log level 55. This is a debug message issued when all of the queued requests represent clients for which there is an update already in progress. This may occur under normal operations but should be temporary situation.



## 11.51 DHCP\_DDNS\_NO\_FWD\_MATCH\_ERROR

```
Request ID %1: the configured list of forward DDNS domains does not contain a match for:  
↔%2 The request has been discarded.
```

This is an error message that indicates that DHCP\_DDNS received a request to update the forward DNS information for the given FQDN but for which there are no configured DDNS domains in the DHCP\_DDNS configuration. Either the DHCP\_DDNS configuration needs to be updated or the source of the FQDN itself should be investigated.

## 11.52 DHCP\_DDNS\_NO\_MATCH

```
No DNS servers match FQDN %1
```

This is warning message issued when there are no domains in the configuration which match the cited fully qualified domain name (FQDN). The DNS Update request for the FQDN cannot be processed.

## 11.53 DHCP\_DDNS\_NO\_REV\_MATCH\_ERROR

```
Request ID %1: the configured list of reverse DDNS domains does not contain a match for:  
↔%2 The request has been discarded.
```

This is an error message that indicates that DHCP\_DDNS received a request to update the reverse DNS information for the given FQDN but for which there are no configured DDNS domains in the DHCP\_DDNS configuration. Either the DHCP\_DDNS configuration needs to be updated or the source of the FQDN itself should be investigated.

## 11.54 DHCP\_DDNS\_QUEUE\_MGR\_QUEUE\_FULL

```
application request queue has reached maximum number of entries %1
```

This an error message indicating that DHCP-DDNS is receiving DNS update requests faster than they can be processed. This may mean the maximum queue needs to be increased, the DHCP-DDNS clients are simply generating too many requests too quickly, or perhaps upstream DNS servers are experiencing load issues.

## 11.55 DHCP\_DDNS\_QUEUE\_MGR\_QUEUE\_RECEIVE

```
Request ID %1: received and queued a request.
```

Logged at debug log level 55. This is an informational message indicating that the NameChangeRequest listener used by DHCP-DDNS to receive a request has received a request and queued it for further processing.

## 11.56 DHCP\_DDNS\_QUEUE\_MGR\_RECONFIGURING

```
application is reconfiguring the queue manager
```

Logged at debug log level 40. This is an informational message indicating that DHCP\_DDNS is reconfiguring the queue manager as part of normal startup or in response to a new configuration.

## 11.57 DHCP\_DDNS\_QUEUE\_MGR\_RECOVERING

```
application is attempting to recover from a queue manager IO error
```

This is an informational message indicating that DHCP\_DDNS is attempting to restart the queue manager after it suffered an IO error while receiving requests.

## 11.58 DHCP\_DDNS\_QUEUE\_MGR\_RECV\_ERROR

```
application's queue manager was notified of a request receive error by its listener.
```

This is an error message indicating that the NameChangeRequest listener used by DHCP-DDNS to receive requests encountered an IO error. There should be corresponding log messages from the listener layer with more details. This may indicate a network connectivity or system resource issue.

## 11.59 DHCP\_DDNS\_QUEUE\_MGR\_RESUME\_ERROR

```
application could not restart the queue manager, reason: %1
```

This is an error message indicating that DHCP\_DDNS's Queue Manager could not be restarted after stopping due to a full receive queue. This means that the application cannot receive requests. This is most likely due to DHCP\_DDNS configuration parameters referring to resources such as an IP address or port, that is no longer unavailable. DHCP\_DDNS will attempt to restart the queue manager if given a new configuration.

## 11.60 DHCP\_DDNS\_QUEUE\_MGR\_RESUMING

```
application is resuming listening for requests now that the request queue size has_  
↔reached %1 of a maximum %2 allowed
```

This is an informational message indicating that DHCP\_DDNS, which had stopped accepting new requests, has processed enough entries from the receive queue to resume accepting requests.

## 11.61 DHCP\_DDNS\_QUEUE\_MGR\_STARTED

application's queue manager has begun listening for requests.

Logged at debug log level 0. This is a debug message indicating that DHCP\_DDNS's Queue Manager has successfully started and is now listening for NameChangeRequests.

## 11.62 DHCP\_DDNS\_QUEUE\_MGR\_START\_ERROR

application could not start the queue manager, reason: %1

This is an error message indicating that DHCP\_DDNS's Queue Manager could not be started. This means that the application cannot receive requests. This is most likely due to DHCP\_DDNS configuration parameters referring to resources such as an IP address or port, that are unavailable. DHCP\_DDNS will attempt to restart the queue manager if given a new configuration.

## 11.63 DHCP\_DDNS\_QUEUE\_MGR\_STOPPED

application's queue manager has stopped listening for requests.

Logged at debug log level 40. This is a debug message indicating that DHCP\_DDNS's Queue Manager has stopped listening for NameChangeRequests. This may be because of normal event such as reconfiguration or as a result of an error. There should be log messages preceding this one to indicate why it has stopped.

## 11.64 DHCP\_DDNS\_QUEUE\_MGR\_STOPPING

application is stopping the queue manager for %1

Logged at debug log level 0. This is an informational message indicating that DHCP\_DDNS is stopping the queue manager either to reconfigure it or as part of application shutdown.

## 11.65 DHCP\_DDNS\_QUEUE\_MGR\_STOP\_ERROR

application encountered an error stopping the queue manager: %1

This is an error message indicating that DHCP\_DDNS encountered an error while trying to stop the queue manager. This error is unlikely to occur or to impair the application's ability to function but it should be reported for analysis.

## 11.66 DHCP\_DDNS\_QUEUE\_MGR\_UNEXPECTED\_HANDLER\_ERROR

```
application's queue manager request receive handler experienced an unexpected exception  
↔%1:
```

This is an error message indicating that an unexpected error occurred within the DHCP\_DDNS's Queue Manager request receive completion handler. This is most likely a programmatic issue that should be reported. The application may recover on its own.

## 11.67 DHCP\_DDNS\_QUEUE\_MGR\_UNEXPECTED\_STOP

```
application's queue manager receive was
```

aborted unexpectedly while queue manager state is: %1 This is an error message indicating that DHCP\_DDNS's Queue Manager request receive was unexpectedly interrupted. Normally, the read is receive is only interrupted as a normal part of stopping the queue manager. This is most likely a programmatic issue that should be reported.

## 11.68 DHCP\_DDNS\_REMOVE\_FAILED

```
DHCP_DDNS Request ID %1: Transaction outcome: %2
```

This is an error message issued after DHCP\_DDNS attempts to submit DNS mapping entry removals have failed. The precise reason for the failure should be documented in preceding log entries.

## 11.69 DHCP\_DDNS\_REMOVE\_SUCCEEDED

```
DHCP_DDNS Request ID %1: successfully removed the DNS mapping addition for this request:  
↔%2
```

This is an informational message issued after DHCP\_DDNS has submitted DNS mapping removals which were received and accepted by an appropriate DNS server.

## 11.70 DHCP\_DDNS\_REQUEST\_DROPPED

```
Request ID %1: Request contains no enabled update requests and will be dropped: %2
```

Logged at debug log level 55. This is a debug message issued when DHCP\_DDNS receives a request which does not contain updates in a direction that is enabled. In other words, if only forward updates are enabled and request is received that asks only for reverse updates then the request is dropped.

## 11.71 DHCP\_DDNS\_REVERSE\_REMOVE\_BAD\_DNSCLIENT\_STATUS

```
DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while removing_
↳reverse address mapping for FQDN %3 to DNS server %4
```

This is an error message issued when DNSClient returns an unrecognized status while DHCP\_DDNS was removing a reverse address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

## 11.72 DHCP\_DDNS\_REVERSE\_REMOVE\_BUILD\_FAILURE

```
DNS Request ID %1: update message to remove a reverse DNS entry could not be constructed_
↳from this request: %2, reason: %3
```

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a reverse PTR removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

## 11.73 DHCP\_DDNS\_REVERSE\_REMOVE\_IO\_ERROR

```
DHCP_DDNS Request ID %1: encountered an IO error sending a reverse mapping remove for_
↳FQDN %2 to DNS server %3
```

This is an error message issued when a communication error occurs while DHCP\_DDNS is carrying out a reverse mapping remove. The application will retry against the same server or others as appropriate.

## 11.74 DHCP\_DDNS\_REVERSE\_REMOVE\_REJECTED

```
DNS Request ID %1: Server, %2, rejected a DNS update request to remove the reverse_
↳mapping for FQDN, %3, with an RCODE: %4
```

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

## 11.75 DHCP\_DDNS\_REVERSE\_REMOVE\_RESP\_CORRUPT

```
DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while_
↳removing reverse address mapping for FQDN, %3
```

This is an error message issued when the response received by DHCP\_DDNS, to a update request to remove a reverse address, is mangled or malformed. The application will retry against the same server or others as appropriate.

## 11.76 DHCP\_DDNS\_REVERSE\_REMOVE\_TIMEOUT

```
DHCP_DDNS Request ID %1: timed out waiting for a response to reverse mapping remove for ↵  
↵FQDN %2 to DNS server %3
```

This is an error message issued when no response is received from the DNS server before exceeding `dns-server-timeout` while `DHCP_DDNS` is carrying out a reverse mapping remove. The application will retry against the same server or others as appropriate.

## 11.77 DHCP\_DDNS\_REVERSE\_REPLACE\_BAD\_DNSCLIENT\_STATUS

```
DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while replacing ↵  
↵reverse address mapping for FQDN %3 to DNS server %4
```

This is an error message issued when `DNSClient` returns an unrecognized status while `DHCP_DDNS` was replacing a reverse address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

## 11.78 DHCP\_DDNS\_REVERSE\_REPLACE\_BUILD\_FAILURE

```
DNS Request ID %1: update message to replace a reverse DNS entry could not be ↵  
↵constructed from this request: %2, reason: %3
```

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a reverse PTR replacement. This is due to invalid data contained in the `NameChangeRequest`. The request will be aborted. This is most likely a configuration issue.

## 11.79 DHCP\_DDNS\_REVERSE\_REPLACE\_IO\_ERROR

```
DHCP_DDNS Request ID %1: encountered an IO error sending a reverse mapping replacement ↵  
↵for FQDN %2 to DNS server %3
```

This is an error message issued when a communication error occurs while `DHCP_DDNS` is carrying out a reverse mapping replacement. The application will retry against the same server or others as appropriate.

## 11.80 DHCP\_DDNS\_REVERSE\_REPLACE\_REJECTED

```
DNS Request ID %1: Server, %2, rejected a DNS update request to replace the reverse ↵  
↵mapping for FQDN, %3, with an RCODE: %4
```

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the `RCODE`. The `rcode` values are defined in RFC 2136.

## 11.81 DHCP\_DDNS\_REVERSE\_REPLACE\_RESP\_CORRUPT

```
DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while  
↪replacing reverse address mapping for FQDN, %3
```

This is an error message issued when the response received by DHCP\_DDNS, to a update request to replace a reverse address, is mangled or malformed. The application will retry against the same server or others as appropriate.

## 11.82 DHCP\_DDNS\_REVERSE\_REPLACE\_TIMEOUT

```
DHCP_DDNS Request ID %1: timed out waiting for a response to reverse mapping replacement.  
↪for FQDN %2 to DNS server %3
```

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP\_DDNS is carrying out a reverse mapping replacement. The application will retry against the same server or others as appropriate.

## 11.83 DHCP\_DDNS\_REV\_REQUEST\_IGNORED

```
Request ID %1: Reverse updates are disabled, the reverse portion of request will be  
↪ignored: %2
```

Logged at debug log level 55. This is a debug message issued when reverse DNS updates are disabled and DHCP\_DDNS receives an update request containing a reverse DNS update. The reverse update will not performed.

## 11.84 DHCP\_DDNS\_RUN\_EXIT

```
application is exiting the event loop
```

Logged at debug log level 0. This is a debug message issued when the DHCP-DDNS server exits its event lo

## 11.85 DHCP\_DDNS\_SHUTDOWN\_COMMAND

```
application received shutdown command with args: %1
```

Logged at debug log level 0. This is a debug message issued when the application has been instructed to shut down by the controller.

## 11.86 DHCP\_DDNS\_STARTED

```
Kea DHCP-DDNS server version %1 started
```

This informational message indicates that the DHCP-DDNS server has processed all configuration information and is ready to begin processing. The version is also printed.

## 11.87 DHCP\_DDNS\_STARTING\_TRANSACTION

```
Request ID %1:
```

Logged at debug log level 50. This is a debug message issued when DHCP-DDNS has begun a transaction for a given request.

## 11.88 DHCP\_DDNS\_STATE\_MODEL\_UNEXPECTED\_ERROR

```
Request ID %1: application encountered an unexpected error while carrying out a  
↳NameChangeRequest: %2
```

This is error message issued when the application fails to process a NameChangeRequest correctly. Some or all of the DNS updates requested as part of this update did not succeed. This is a programmatic error and should be reported.

## 11.89 DHCP\_DDNS\_TRANS\_SEND\_ERROR

```
Request ID %1: application encountered an unexpected error while attempting to send a  
↳DNS update: %2
```

This is error message issued when the application is able to construct an update message but the attempt to send it suffered an unexpected error. This is most likely a programmatic error, rather than a communications issue. Some or all of the DNS updates requested as part of this request did not succeed.

## 11.90 DHCP\_DDNS\_UDP\_SENDER\_WATCH\_SOCKET\_CLOSE\_ERROR

```
watch socket failed to close: %1
```

This is an error message that indicates the application was unable to close the inbound or outbound side of a NCR sender's watch socket. While technically possible the error is highly unlikely to occur and should not impair the application's ability to process requests.



## 11.91 DHCP\_DDNS\_UNCAUGHT\_NCR\_RECV\_HANDLER\_ERROR

unexpected exception thrown from the application receive completion handler: %1

This is an error message that indicates that an exception was thrown but not caught in the application's request receive completion handler. This is a programmatic error that needs to be reported. Dependent upon the nature of the error the application may or may not continue operating normally.

## 11.92 DHCP\_DDNS\_UPDATE\_REQUEST\_SENT

Request ID %1: %2 to server: %3

Logged at debug log level 50. This is a debug message issued when DHCP\_DDNS sends a DNS request to a DNS server.



## 12.1 EVAL\_DEBUG\_AND

%1: Popping %2 and %3 pushing %4

Logged at debug log level 55. This debug message indicates that two values are popped from the value stack. Then are then combined via logical and and the result is pushed onto the value stack.

## 12.2 EVAL\_DEBUG\_BRANCH

Branching to %1

Logged at debug log level 55. This debug message indicates that an unconditional branch is performed to the displayed target.

## 12.3 EVAL\_DEBUG\_CONCAT

%1: Popping %2 and %3 pushing %4

Logged at debug log level 55. This debug message indicates that the two strings are being popped off of the stack. They are then concatenated and the resulting string is pushed onto the stack. The strings are displayed in hex.

## 12.4 EVAL\_DEBUG\_EQUAL

%1: Popping %2 and %3 pushing result %4

Logged at debug log level 55. This debug message indicates that the two strings are being popped off of the value stack and the result of comparing them is being pushed onto the value stack. The strings are displayed in hex.

## 12.5 EVAL\_DEBUG\_HEXSTRING

%1: Pushing hex string %2

Logged at debug log level 55. This debug message indicates that the given binary string is being pushed onto the value stack. The string is displayed in hex.

## 12.6 EVAL\_DEBUG\_IFELSE\_FALSE

%1: Popping %2 (false) and %3, leaving %4

Logged at debug log level 55. This debug message indicates that the condition is false so the iftrue branch value is removed and the ifelse branch value is left on the value stack.

## 12.7 EVAL\_DEBUG\_IFELSE\_TRUE

%1: Popping %2 (true) and %3, leaving %4

Logged at debug log level 55. This debug message indicates that the condition is true so the ifelse branch value is removed and the iftrue branch value is left on the value stack.

## 12.8 EVAL\_DEBUG\_INT16TOTEXT

%1: Pushing Int16 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 16 bit integer.

## 12.9 EVAL\_DEBUG\_INT32TOTEXT

%1: Pushing Int32 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 32 bit integer.

## 12.10 EVAL\_DEBUG\_INT8TOTEXT

%1: Pushing Int8 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents an 8 bit integer.

## 12.11 EVAL\_DEBUG\_IPADDRESS

```
%1: Pushing IPAddress %2
```

Logged at debug log level 55. This debug message indicates that the given binary string is being pushed onto the value stack. This represents either an IPv4 or IPv6 address. The string is displayed in hex.

## 12.12 EVAL\_DEBUG\_IPADDRESSTOTEXT

```
%1: Pushing IPAddress %2
```

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents either an IPv4 or IPv6 address.

## 12.13 EVAL\_DEBUG\_LCASE

```
%1: Popping string %2 and pushing converted value to lower case %3
```

Logged at debug log level 55. This debug message indicates that the given string representation is being converted to lower case and pushed onto the value stack.

## 12.14 EVAL\_DEBUG\_MATCH

```
Matching '%1' on %2, result %3
```

Logged at debug log level 55. This debug message indicates that the given regular expression was matched with the popped value. The result was pushed onto the value stack.

## 12.15 EVAL\_DEBUG\_MATCH\_ERROR

```
Matching '%1' on %2 raised an error: %3
```

This error message indicates that an error occurred while evaluating the given regular expression against the popped value.

## 12.16 EVAL\_DEBUG\_MEMBER

```
%1: Checking membership of '%2', pushing result %3
```

Logged at debug log level 55. This debug message indicates that the membership of the packet for the client class was checked.

## 12.17 EVAL\_DEBUG\_NOT

```
%1: Popping %2 pushing %3
```

Logged at debug log level 55. This debug message indicates that the first value is popped from the value stack, negated and then pushed onto the value stack. The string is displayed in text.

## 12.18 EVAL\_DEBUG\_OPTION

```
%1: Pushing option %2 with value %3
```

Logged at debug log level 55. This debug message indicates that the given string representing the value of the requested option is being pushed onto the value stack. The string may be the text or binary value of the string based on the representation type requested (.text or .hex) or "true" or "false" if the requested type is .exists. The option code may be for either an option or a sub-option as requested in the classification statement.

## 12.19 EVAL\_DEBUG\_OR

```
%1: Popping %2 and %3 pushing %4
```

Logged at debug log level 55. This debug message indicates that two values are popped from the value stack. Then are then combined via logical or and the result is pushed onto the value stack. The string is displayed in text.

## 12.20 EVAL\_DEBUG\_PKT

```
%1: Pushing PKT meta data %2 with value %3
```

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested meta data is being pushed onto the value stack. The string is displayed in hex at the exception of interface name.

## 12.21 EVAL\_DEBUG\_PKT4

```
%1: Pushing PKT4 field %2 with value %3
```

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

## 12.22 EVAL\_DEBUG\_PKT6

```
%1: Pushing PKT6 field %2 with value %3
```

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

## 12.23 EVAL\_DEBUG\_POP\_AND\_BRANCH\_FALSE

```
Value is false: branching to %1
```

Logged at debug log level 55. This debug message indicates that a branch on false condition is performed to the displayed target.

## 12.24 EVAL\_DEBUG\_POP\_OR\_BRANCH\_FALSE

```
Value is false: keeping it and branching to %1
```

Logged at debug log level 55. This debug message indicates that a branch on false condition is performed to the displayed target.

## 12.25 EVAL\_DEBUG\_POP\_OR\_BRANCH\_TRUE

```
Value is true: keeping it and branching to %1
```

Logged at debug log level 55. This debug message indicates that a branch on true condition is performed to the displayed target.

## 12.26 EVAL\_DEBUG\_RELAY6

```
%1: Pushing PKT6 relay field %2 nest %3 with value %4
```

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

## 12.27 EVAL\_DEBUG\_RELAY6\_RANGE

```
%1: Pushing PKT6 relay field %2 nest %3 with value %4
```

Logged at debug log level 55. This debug message is generated if the nest field is out of range. The empty string will always be the value pushed onto the stack.

## 12.28 EVAL\_DEBUG\_SPLIT

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that three values are being popped from the stack and a result is being pushed onto the stack. The values being popped are the field, delimiter and string. The result is the extracted field which is pushed onto the stack. The strings are displayed in hex.

## 12.29 EVAL\_DEBUG\_SPLIT\_DELIM\_EMPTY

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that the delimiter popped from the stack was empty and so the result will be the entire string. The field, delimiter and string are still popped from the stack and the result is still pushed.

## 12.30 EVAL\_DEBUG\_SPLIT\_EMPTY

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that the string popped from the stack was empty and so the result will also be empty. The field, delimiter and string are still popped from the stack and the result is still pushed.

## 12.31 EVAL\_DEBUG\_SPLIT\_FIELD\_OUT\_OF\_RANGE

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that the field is either less than one or larger than the number of fields in the string popped from the stack. The result will be empty. The field, delimiter and string are still popped from the stack and the result is still pushed.

## 12.32 EVAL\_DEBUG\_STRING

%1: Pushing text string %2

Logged at debug log level 55. This debug message indicates that the given text string is being pushed onto the value stack. The string is displayed in text.



## 12.33 EVAL\_DEBUG\_SUBSTRING

```
%1: Popping length %2, start %3, string %4 pushing result %5
```

Logged at debug log level 55. This debug message indicates that three values are being popped from the value stack and a result is being pushed onto the value stack. The values being popped are the starting point and length of a substring to extract from the given string. The resulting string is pushed onto the stack. The strings are displayed in hex.

## 12.34 EVAL\_DEBUG\_SUBSTRING\_EMPTY

```
%1: Popping length %2, start %3, string %4 pushing result %5
```

Logged at debug log level 55. This debug message indicates that the string popped from the stack was empty and so the result will also be empty. The start, length and string are still popped from the stack and the result is still pushed.

## 12.35 EVAL\_DEBUG\_SUBSTRING\_RANGE

```
%1: Popping length %2, start %3, string %4 pushing result %5
```

Logged at debug log level 55. This debug message indicates that the value of start is outside of the string and an empty result will be pushed onto the stack. The start, length and string are still popped from the stack and the result is still pushed. The strings are displayed in hex.

## 12.36 EVAL\_DEBUG\_SUB\_OPTION

```
%1: Pushing option %2 sub-option %3 with value %4
```

This debug message indicates that the given string representing the value of the requested sub-option of the requested parent option is being pushed onto the value stack. The string may be the text or binary value of the string based on the representation type requested (.text or .hex) or "true" or "false" if the requested type is .exists. The codes are the parent option and the sub-option codes as requested in the classification statement.

## 12.37 EVAL\_DEBUG\_SUB\_OPTION\_NO\_OPTION

```
%1: Requested option %2 sub-option %3, but the parent option is not present, pushing ↵  
↵result %4
```

This debug message indicates that the parent option was not found. The codes are the parent option and the sub-option codes as requested in the classification statement.

## 12.38 EVAL\_DEBUG\_TOHEXSTRING

%1: Popping binary value %2 and separator %3, pushing result %4

Logged at debug log level 55. This debug message indicates that two values are being popped from the value stack and a result is being pushed onto the value stack. The values being popped are the binary value to convert and the separator. The binary value is converted to its hexadecimal string representation and pushed onto the stack. The binary value is displayed in hex.

## 12.39 EVAL\_DEBUG\_UCASE

%1: Popping string %2 and pushing converted value to upper case %3

Logged at debug log level 55. This debug message indicates that the given string representation is being converted to upper case and pushed onto the value stack.

## 12.40 EVAL\_DEBUG\_UINT16TOTEXT

%1: Pushing UInt16 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 16 bit unsigned integer.

## 12.41 EVAL\_DEBUG\_UINT32TOTEXT

%1: Pushing UInt32 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 32 bit unsigned integer.

## 12.42 EVAL\_DEBUG\_UINT8TOTEXT

%1: Pushing UInt8 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents an 8 bit unsigned integer.

## 12.43 EVAL\_DEBUG\_VENDOR\_CLASS\_DATA

```
%1: Data %2 (out of %3 received) in vendor class found, pushing result '%4'
```

Logged at debug log level 55. This debug message indicates that vendor class option was found and passed enterprise-id checks and has sufficient number of data chunks. The total number of chunks and value pushed are reported as debugging aid.

## 12.44 EVAL\_DEBUG\_VENDOR\_CLASS\_DATA\_NOT\_FOUND

```
%1: Requested data index %2, but option with enterprise-id %3 has only %4 data tuple(s),  
↳ pushing result '%5'
```

Logged at debug log level 55. This debug message indicates that vendor class option was found and passed enterprise-id checks, but does not have sufficient number of data chunks. Note that the index starts at 0, so there has to be at least (index + 1) data chunks.

## 12.45 EVAL\_DEBUG\_VENDOR\_CLASS\_ENTERPRISE\_ID

```
%1: Pushing enterprise-id %2 as result 0x%3
```

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was found and its enterprise-id is being reported.

## 12.46 EVAL\_DEBUG\_VENDOR\_CLASS\_ENTERPRISE\_ID\_MISMATCH

```
%1: Was looking for %2, option had %3, pushing result '%4'
```

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was found, but has different enterprise-id than specified in the expression.

## 12.47 EVAL\_DEBUG\_VENDOR\_CLASS\_EXISTS

```
%1: Option with enterprise-id %2 found, pushing result '%3'
```

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was found.

## 12.48 EVAL\_DEBUG\_VENDOR\_CLASS\_NO\_OPTION

%1: Option with code %2 missing, pushing result '%3'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was not found.

## 12.49 EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID

%1: Pushing enterprise-id %2 as result 0x%3

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor option was found and its enterprise-id is being reported.

## 12.50 EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID\_MISMATCH

%1: Was looking for %2, option had %3, pushing result '%4'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor option was found, but has different enterprise-id than specified in the expression.

## 12.51 EVAL\_DEBUG\_VENDOR\_EXISTS

%1: Option with enterprise-id %2 found, pushing result '%3'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor option was found.

## 13.1 FLEX\_OPTION\_LOAD\_ERROR

```
loading Flex Option hooks library failed: %1
```

This error message indicates an error during loading the Flex Option hooks library. The details of the error are provided as argument of the log message.

## 13.2 FLEX\_OPTION\_PROCESS\_ADD

```
Added the option code %1 with value %2
```

Logged at debug log level 40. This debug message is printed when an option was added into the response packet. The option code and the value (between quotes if printable, in hexadecimal if not) are provided.

## 13.3 FLEX\_OPTION\_PROCESS\_CLIENT\_CLASS

```
Skip processing of the option code %1 for class '%2'
```

Logged at debug log level 40. This debug message is printed when the processing for an option is skipped because the query does not belongs to the client class. The option code and the client class name are provided.

## 13.4 FLEX\_OPTION\_PROCESS\_ERROR

```
An error occurred processing query %1: %2
```

This error message indicates an error during processing of a query by the Flex Option hooks library. The client identification information from the query and the details of the error are provided as arguments of the log message.

## 13.5 FLEX\_OPTION\_PROCESS\_REMOVE

```
Removed option code %1
```

Logged at debug log level 40. This debug message is printed when an option was removed from the response packet. The option code is provided.

## 13.6 FLEX\_OPTION\_PROCESS\_SUB\_ADD

```
Added the sub-option code %1 in option code %2 with value %3
```

Logged at debug log level 40. This debug message is printed when an sub-option was added into the response packet. The sub-option and container option codes, and the value (between quotes if printable, in hexadecimal if not) are provided.

## 13.7 FLEX\_OPTION\_PROCESS\_SUB\_CLIENT\_CLASS

```
Skip processing of the sub-option code %1 in option code %2 for class '%3'
```

Logged at debug log level 40. This debug message is printed when the processing for a sub-option is skipped because the query does not belongs to the client class. The sub-option and container option codes, and the client class name are provided.

## 13.8 FLEX\_OPTION\_PROCESS\_SUB\_REMOVE

```
Removed sub-option code %1 in option code %2
```

Logged at debug log level 40. This debug message is printed when a sub-option was removed from the response packet. The sub-option and container option codes are provided.

## 13.9 FLEX\_OPTION\_PROCESS\_SUB\_SUPERSEDE

```
Supersedes the sub-option code %1 in option code %2 with value %3
```

Logged at debug log level 40. This debug message is printed when a sub-option was superseded into the response packet. The sub-option and container option codes, and the value (between quotes if printable, in hexadecimal if not) are provided.

## 13.10 FLEX\_OPTION\_PROCESS\_SUPERSEDE

Supersedes the option code %1 with value %2

Logged at debug log level 40. This debug message is printed when an option was superseded into the response packet. The option code and the value (between quotes if printable, in hexadecimal if not) are provided.

## 13.11 FLEX\_OPTION\_PROCESS\_VENDOR\_ID\_MISMATCH

Skip processing of vendor option code %1 with vendor id %2 not matching wanted %3

Logged at debug log level 40. This debug message is printed when a sub-option of a vendor option is processed but vendor ids do not match. The code of the vendor option and the two vendor ids are provided.





## 14.1 FUZZ\_DATA\_READ

```
read %1 byte(s) from AFL via stdin
```

Logged at debug log level 50. A debug message output to indicate how much data has been received from the fuzzer via stdin

## 14.2 FUZZ\_INIT\_COMPLETE

```
fuzz initialization complete: interface %1, address %2, port %3, max loops %4
```

An informational message output when the fuzzing initialization function has completed successfully. The parameters listed are those which must be/can be set via environment variables.

## 14.3 FUZZ\_INIT\_FAIL

```
fuzz initialization failure, reason: %1
```

An error message reported if the fuzzing initialization failed. The reason for the failure is given in the message.

## 14.4 FUZZ\_READ\_FAIL

```
error reading input from fuzzer: %1
```

This error is reported if the read of data from the fuzzer (which is received over stdin) fails, or if a read returns zero bytes. If this occurs, the thread will sleep for a short period before retrying the read. The message includes the reason for the failure.

## 14.5 FUZZ\_SEND

sent %1 byte(s) to the socket connected to the Kea interface

Logged at debug log level 50. A debug message stating that the `sendto()` call in the main fuzzing function has successfully completed and reporting the number of bytes sent. This call sends data received from AFL to the port on which Kea is listening.

## 14.6 FUZZ\_SEND\_ERROR

failed to send data to Kea input socket: %1

This error will be reported if the `sendto()` call in the fuzzing thread (which sends data received from AFL to the socket on which Kea is listening) fails. The reason for the failure is given in the message. The fuzzing code will attempt to continue from this, but it may cause the fuzzing process to fail.

## 14.7 FUZZ\_SHORT\_SEND

expected to send %1 bytes to Kea input socket but only sent %2

A warning message that is output if the `sendto()` call (used to send data from the fuzzing thread to the main Kea processing) did not send as much data as that read from AFL. This may indicate a problem in the underlying communications between the fuzzing thread and the main Kea processing.

## 15.1 HA\_BUFFER4\_RECEIVE\_FAILED

```
buffer4_receive callout failed: %1
```

This error message is issued when the callout for the `buffer4_receive` hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

## 15.2 HA\_BUFFER4\_RECEIVE\_NOT\_FOR\_US

```
%1: dropping query to be processed by another server
```

Logged at debug log level 40. This debug message is issued when the received DHCPv4 query is dropped by this server because it should be served by another server. This is the case when the remote server was designated to process the packet as a result of load balancing or because it is a primary server in the hot standby configuration. The argument provides client identification information retrieved from the query.

## 15.3 HA\_BUFFER4\_RECEIVE\_PACKET\_OPTIONS\_SKIPPED

```
an error unpacking an option, caused subsequent options to be skipped: %1
```

Logged at debug log level 40. A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv4 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

## 15.4 HA\_BUFFER4\_RECEIVE\_UNPACK\_FAILED

```
failed to parse query from %1 to %2, received over interface %3, reason: %4
```

Logged at debug log level 40. This debug message is issued when received DHCPv4 query is malformed and can't be parsed by the `buffer4_receive` callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

## 15.5 HA\_BUFFER6\_RECEIVE\_FAILED

```
buffer6_receive callout failed: %1
```

This error message is issued when the callout for the `buffer6_receive` hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

## 15.6 HA\_BUFFER6\_RECEIVE\_NOT\_FOR\_US

```
%1: dropping query to be processed by another server
```

Logged at debug log level 40. This debug message is issued when the received DHCPv6 query is dropped by this server because it should be served by another server. This is the case when the remote server was designated to process the packet as a result of load balancing or because it is a primary server in the hot standby configuration. The argument provides client identification information retrieved from the query.

## 15.7 HA\_BUFFER6\_RECEIVE\_PACKET\_OPTIONS\_SKIPPED

```
an error unpacking an option, caused subsequent options to be skipped: %1
```

Logged at debug log level 40. A debug message issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv6 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

## 15.8 HA\_BUFFER6\_RECEIVE\_UNPACK\_FAILED

```
failed to parse query from %1 to %2, received over interface %3, reason: %4
```

Logged at debug log level 40. This debug message is issued when received DHCPv6 query is malformed and can't be parsed by the `buffer6_receive` callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

## 15.9 HA\_COMMAND\_PROCESSED\_FAILED

```
command_processed callout failed: %1
```

This error message is issued when the callout for the `command_processed` hook point failed. The argument contains a reason for the error.

## 15.10 HA\_COMMUNICATION\_INTERRUPTED

```
%1: communication with %2 is interrupted
```

This warning message is issued by the server which discovered that the communication to the active partner has been interrupted for a time period longer than the configured heartbeat-delay time. At this stage the server starts the failover procedure by monitoring the DHCP traffic sent to the partner and checking whether the partner server responds to this traffic. If the max-unacked-clients value is set to 0 such verification is disabled in which case the server will transition to the partner-down state.

## 15.11 HA\_COMMUNICATION\_INTERRUPTED\_CLIENT4

```
%1: new client %2 attempting to get a lease from the partner
```

This informational message is issued when the surviving server observes a DHCP packet sent to the partner with which the communication is interrupted. The client whose packet is observed is not yet considered "unacked" because the secs field value does not exceed the configured threshold specified with max-ack-delay.

## 15.12 HA\_COMMUNICATION\_INTERRUPTED\_CLIENT4\_UNACKED

```
%1: partner server failed to respond to %2, %3 clients unacked so far, %4 clients left.  
↪ before transitioning to the partner-down state
```

This informational message is issued when the surviving server determines that its partner failed to respond to the DHCP query and that this client is considered to not be served by the partner. The surviving server counts such clients and if the number of such clients exceeds the max-unacked-clients threshold, the server will transition to the partner-down state. The first argument specifies the relationship name. The second argument contains client identification information. The third argument specifies the number of clients to which the server has failed to respond. The fourth argument specifies the number of additional clients which, if not provisioned, will cause the server to transition to the partner-down state.

## 15.13 HA\_COMMUNICATION\_INTERRUPTED\_CLIENT6

```
%1: new client %2 attempting to get a lease from the partner
```

This informational message is issued when the surviving server observes a DHCP packet sent to the partner with which the communication is interrupted. The client whose packet is observed is not yet considered "unacked" because the elapsed time option value does not exceed the configured threshold specified with max-ack-delay. The sole argument specifies client identification information.

## 15.14 HA\_COMMUNICATION\_INTERRUPTED\_CLIENT6\_UNACKED

```
%1: partner server failed to respond to %2, %3 clients unacked so far, %4 clients left.  
↳before transitioning to the partner-down state
```

This informational message is issued when the surviving server determines that its partner failed to respond to the DHCP query and that this client is considered to not be served by the partner. The surviving server counts such clients and if the number of such clients exceeds the max-unacked-clients threshold, the server will transition to the partner-down state. The first argument specifies the relationship name. The second argument contains client identification information. The third argument specifies the number of clients to which the server has failed to respond. The fourth argument specifies the number of additional clients which, if not provisioned, will cause the server to transition to the partner-down state.

## 15.15 HA\_CONFIGURATION\_FAILED

```
failed to configure High Availability hooks library: %1
```

This error message is issued when there is an error configuring the HA hooks library. The argument provides the detailed error message.

## 15.16 HA\_CONFIGURATION\_SUCCESSFUL

```
HA hook library has been successfully configured
```

This informational message is issued when the HA hook library configuration parser successfully parses and validates the new configuration.

## 15.17 HA\_CONFIG\_AUTO\_FAILOVER\_DISABLED

```
%1: auto-failover disabled
```

This warning message is issued to indicate that the 'auto-failover' parameter was administratively disabled for the specified server. The server will not automatically start serving partner's scope when the partner failure is detected. The server administrator will need to enable this scope manually by sending appropriate ha-scopes command.

## 15.18 HA\_CONFIG\_DHCP\_MT\_DISABLED

```
%1: HA multi-threading has been disabled, it cannot be enabled when Kea global multi-  
↳threading is disabled
```

This informational message is issued when HA configuration has enabled multi-threading while Kea global configuration has multi-threading disabled.

## 15.19 HA\_CONFIG\_DHCP\_MT\_DISABLED\_AND\_KEA\_MT\_ENABLED

```
%1: HA multi-threading is disabled while Kea global multi-threading is enabled which
↳most likely cause performance degradation.
```

This warning message is issued when HA configuration has disabled multi-threading while Kea global configuration has multi-threading enabled. This will likely cause performance degradation.

## 15.20 HA\_CONFIG\_LEASE\_SYNCING\_DISABLED

```
%1: lease database synchronization between HA servers is disabled
```

This warning message is issued when the lease database synchronization is administratively disabled. This is valid configuration if the leases are replicated between lease databases via some other mechanism, e.g. SQL database replication.

## 15.21 HA\_CONFIG\_LEASE\_SYNCING\_DISABLED\_REMINDER

```
%1: bypassing SYNCING state because lease database synchronization is administratively
↳disabled
```

This informational message is issued as a reminder that lease database synchronization is administratively disabled and therefore the server transitions directly from the "waiting" to "ready" state.

## 15.22 HA\_CONFIG\_LEASE\_UPDATES\_AND\_SYNCING\_DIFFER

```
%1: unusual configuration where "send-lease-updates": %2 and "sync-leases": %3
```

This warning message is issued when the configuration values of the send-lease-updates and sync-leases parameters differ. This may be a valid configuration but is unusual. Normally, if the lease database with replication is in use, both values are set to false. If a lease database without replication is in use (e.g. memfile), both values are set to true. Providing different values for those parameters means that an administrator either wants the server to not synchronize leases upon startup but later send lease updates to the partner, or the lease database should be synchronized upon startup, but no lease updates are later sent as a result of leases allocation.

## 15.23 HA\_CONFIG\_LEASE\_UPDATES\_DISABLED

```
%1: lease updates will not be generated
```

This warning message is issued when the lease updates are administratively disabled. This is valid configuration if the leases are replicated to the partner's database via some other mechanism, e.g. SQL database replication.

## 15.24 HA\_CONFIG\_LEASE\_UPDATES\_DISABLED\_REMINDER

```
%1: lease updates are administratively disabled and will not be generated while in %2_  
↪state
```

This informational message is issued as a reminder that the lease updates are administratively disabled and will not be issued in the HA state to which the server has transitioned. The sole argument specifies the state into which the server has transitioned.

## 15.25 HA\_CONFIG\_SYSTEM\_MT\_UNSUPPORTED

```
%1: HA multi-threading has been disabled, auto-detection of thread support reports 0
```

This informational message is issued when HA multi-threading configuration has specified auto-detection for the number of threads to use and the system reports the number of concurrent threads as 0. If you know your system can support multiple threads, then you may override this condition by specifying explicit values for `http-listener-threads` and `http-client-threads`.

## 15.26 HA\_CONTINUE\_HANDLER\_FAILED

```
ha-continue command failed: %1
```

This error message is issued to indicate that the `ha-continue` command handler failed while processing the command. The argument provides the reason for failure.

## 15.27 HA\_DEINIT\_OK

```
unloading High Availability hooks library successful
```

This informational message indicates that the High Availability hooks library has been unloaded successfully.

## 15.28 HA\_DHCP4\_START\_SERVICE\_FAILED

```
failed to start DHCPv4 HA services in dhcp4_srv_configured callout: %1
```

This error message is issued when an attempt to start High Availability services for the DHCPv4 server failed in the `dhcp4_srv_configured` callout. This is internal server error and a bug report should be created.



## 15.29 HA\_DHCP6\_START\_SERVICE\_FAILED

```
failed to start DHCPv6 HA services in dhcp6_srv_configured callout: %1
```

This error message is issued when an attempt to start High Availability services for the DHCPv6 server failed in the dhcp6\_srv\_configured callout. This is internal server error and a bug report should be created.

## 15.30 HA\_DHCP\_DISABLE\_COMMUNICATIONS\_FAILED

```
%1: failed to send request to disable DHCP service of %2: %3
```

This warning message indicates that there was a problem in communication with a HA peer while sending the dhcp-disable command. The first argument specifies the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.31 HA\_DHCP\_DISABLE\_FAILED

```
%1: failed to disable DHCP service of %2: %3
```

This warning message indicates that a peer returned an error status code in response to a dhcp-disable command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.32 HA\_DHCP\_ENABLE\_COMMUNICATIONS\_FAILED

```
%1: failed to send request to enable DHCP service of %2: %3
```

This warning message indicates that there was a problem in communication with a HA peer while sending the dhcp-enable command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.33 HA\_DHCP\_ENABLE\_FAILED

```
%1: failed to enable DHCP service of %2: %3
```

This warning message indicates that a peer returned an error status code in response to a dhcp-enable command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.34 HA\_HEARTBEAT\_COMMUNICATIONS\_FAILED

```
%1: failed to send heartbeat to %2: %3
```

This warning message indicates that there was a problem in communication with a HA peer while sending a heartbeat. This is a first sign that the peer may be down. The server will keep trying to send heartbeats until it considers that communication is interrupted.

## 15.35 HA\_HEARTBEAT\_FAILED

```
%1: heartbeat to %2 failed: %3
```

This warning message indicates that a peer returned an error status code in response to a heartbeat. This is the sign that the peer may not function properly. The server will keep trying to send heartbeats until it considers that communication is interrupted.

## 15.36 HA\_HEARTBEAT\_HANDLER\_FAILED

```
heartbeat command failed: %1
```

This error message is issued to indicate that the heartbeat command handler failed while processing the command. The argument provides the reason for failure.

## 15.37 HA\_HIGH\_CLOCK\_SKEW

```
%1: %2, please synchronize clocks!
```

This warning message is issued when the clock skew between the active servers exceeds 30 seconds. The HA service continues to operate but may not function properly, especially for low lease lifetimes. The administrator should should synchronize the clocks, e.g. using NTP. If the clock skew exceeds 60 seconds, the HA service will terminate.

## 15.38 HA\_HIGH\_CLOCK\_SKEW\_CAUSED\_TERMINATION

```
%1: %2, causing HA service to terminate
```

This warning message is issued when the clock skew between the active servers exceeds 60 seconds. The HA service stops. The servers will continue to respond to the DHCP queries but won't exchange lease updates or send heartbeats. The administrator is required to synchronize the clocks and then restart the servers to resume the HA service.

## 15.39 HA\_INIT\_OK

```
loading High Availability hooks library successful
```

This informational message indicates that the High Availability hooks library has been loaded successfully. Enjoy!

## 15.40 HA\_INVALID\_PARTNER\_STATE\_COMMUNICATION\_RECOVERY

```
%1: partner is in the communication-recovery state unexpectedly
```

This warning message is issued when a partner is in the communication-recovery state, and this server is not running in the load balancing mode. The server may only transition to the communication-recovery state when it runs in the load balancing mode. The HA mode of both servers must be the same.

## 15.41 HA\_INVALID\_PARTNER\_STATE\_HOT\_STANDBY

```
%1: partner is in the hot-standby state unexpectedly
```

This warning message is issued when a partner is in the hot-standby state, and this server is not running in the hot standby mode. The server may only transition to the hot-standby state when it runs in the hot standby mode. The HA mode of both servers must be the same.

## 15.42 HA\_INVALID\_PARTNER\_STATE\_LOAD\_BALANCING

```
%1: partner is in the load-balancing state unexpectedly
```

This warning message is issued when a partner is in the load-balancing state, and this server is not running in the load balancing mode. The server may only transition to the load-balancing state when it runs in the load balancing mode. The HA mode of both servers must be the same.

## 15.43 HA\_LEASE4\_SERVER\_DECLINE\_FAILED

```
lease4_server_decline callout failed: %1
```

This error message is issued when the callout for the lease4\_server\_decline hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

## 15.44 HA\_LEASES4\_COMMITTED\_FAILED

```
leases4_committed callout failed: %1
```

This error message is issued when the callout for the leases4\_committed hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

## 15.45 HA\_LEASES4\_COMMITTED\_NOTHING\_TO\_UPDATE

```
%1: leases4_committed callout was invoked without any leases
```

Logged at debug log level 40. This debug message is issued when the "leases4\_committed" callout returns because there are neither new leases nor deleted leases for which updates should be sent. The sole argument specifies the details of the client which sent the packet.

## 15.46 HA\_LEASES4\_COMMITTED\_NO\_RELATIONSHIP

```
%1: HA relationship not found: %2
```

This error message is issued when the relationship for the server name provided by the earlier callouts was not found in the HA configuration. This error is highly unlikely and rather indicates some programming error. The first argument is the client identification information. The second argument holds a more detailed error message.

## 15.47 HA\_LEASES6\_COMMITTED\_FAILED

```
leases6_committed callout failed: %1
```

This error message is issued when the callout for the leases6\_committed hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

## 15.48 HA\_LEASES6\_COMMITTED\_NOTHING\_TO\_UPDATE

```
%1: leases6_committed callout was invoked without any leases
```

Logged at debug log level 40. This debug message is issued when the "leases6\_committed" callout returns because there are neither new leases nor deleted leases for which updates should be sent. The sole argument specifies the details of the client which sent the packet.

## 15.49 HA\_LEASES6\_COMMITTED\_NO\_RELATIONSHIP

```
%1: HA relationship not found: %2
```

This error message is issued when the relationship for the server name provided by the earlier callouts was not found in the HA configuration. This error is highly unlikely and rather indicates some programming error. The first argument is the client identification information. The second argument holds a more detailed error message.

## 15.50 HA\_LEASES\_BACKLOG\_COMMUNICATIONS\_FAILED

```
%1: failed to communicate with %2 while sending lease updates backlog: %3
```

This error message is issued to indicate that there was a communication error with a partner server while sending outstanding lease updates after resuming connection. The third argument contains a reason for the error.

## 15.51 HA\_LEASES\_BACKLOG\_FAILED

```
%1: failed to send lease updates backlog to %2: %3
```

This error message is issued to indicate that sending lease updates backlog to a partner server failed. The lease updates backlog is sent to the partner after resuming temporarily broken communication with the partner. If this operation fails the server will transition to the waiting state to initiate full lease database synchronization.

## 15.52 HA\_LEASES\_BACKLOG\_NOTHING\_TO\_SEND

```
%1: no leases in backlog after communication recovery
```

This informational message is issued when there are no outstanding leases to be sent after communication recovery with a partner. This means that the communication interruption was short enough that no DHCP clients obtained any leases from the server while it was in the communication-recovery state. The server may now transition to the load-balancing state.

## 15.53 HA\_LEASES\_BACKLOG\_START

```
%1: starting to send %2 outstanding lease updates to %3
```

This informational message is issued when the server starts to send outstanding lease updates to the partner after resuming communications. The first argument specifies the local server's name. The second argument specifies the number of lease updates to be sent. The name of the partner is specified with the third argument.

## 15.54 HA\_LEASES\_BACKLOG\_SUCCESS

%1: sending lease updates backlog to %2 successful in %3

This informational message is issued when server successfully completes sending lease updates backlog to the partner. The first argument specifies the local server's name. The second argument specifies the name of the remote server. The third argument specifies the duration of this operation.

## 15.55 HA\_LEASES\_SYNC\_APPLIED\_LEASES

%1: applied %2 leases received from the partner in the local lease database

This informational message outputs the number of leases received from the partner during the database synchronization and applied in the local database. A typical case when only some leases are applied is when the server has multiple relationships and some of the received leases belong to another relationship. The first argument specifies this server name. The second argument specifies the number of applied leases.

## 15.56 HA\_LEASES\_SYNC\_COMMUNICATIONS\_FAILED

%1: failed to communicate with %2 while syncing leases: %3

This error message is issued to indicate that there was a communication error with a partner server while trying to fetch leases from its lease database. The argument contains a reason for the error.

## 15.57 HA\_LEASES\_SYNC\_FAILED

%1: failed to synchronize leases with %2: %3

This error message is issued to indicate that there was a problem while parsing a response from the server from which leases have been fetched for local database synchronization. The third argument contains a reason for the error.

## 15.58 HA\_LEASES\_SYNC\_LEASE\_PAGE\_RECEIVED

%1: received %2 leases from %3

This informational message is issued during lease database synchronization to indicate that a bulk of leases have been received. The first argument specifies the local server's name. The second argument holds the count of leases received. The third argument specifies the partner server name.

## 15.59 HA\_LEASE\_SYNC\_FAILED

```
%1: synchronization failed for lease: %2, reason: %3
```

This warning message is issued when creating or updating a lease in the local lease database fails. The lease information in the JSON format is provided as a first argument. The third argument provides a reason for the failure.

## 15.60 HA\_LEASE\_SYNC\_STALE\_LEASE4\_SKIP

```
%1: skipping stale lease %2 in subnet %3
```

Logged at debug log level 40. This debug message is issued during lease database synchronization, when fetched IPv4 lease instance appears to be older than the instance in the local database. The newer instance is left in the database and the fetched lease is dropped. The remote server will still hold the older lease instance until it synchronizes its database with this server. The first argument specifies the local server's name. The second argument specifies leased address. The third argument specifies a subnet to which the lease belongs.

## 15.61 HA\_LEASE\_SYNC\_STALE\_LEASE6\_SKIP

```
%1: skipping stale lease %2 in subnet %3
```

Logged at debug log level 40. This debug message is issued during lease database synchronization, when fetched IPv6 lease instance appears to be older than the instance in the local database. The newer instance is left in the database and the fetched lease is dropped. The remote server will still hold the older lease instance until it synchronizes its database with this server. The first argument specifies the local server's name. The second argument specifies leased address. The second argument specifies a subnet to which the lease belongs.

## 15.62 HA\_LEASE\_UPDATES\_DISABLED

```
%1: lease updates will not be sent to the partner while in %2 state
```

This informational message is issued to indicate that lease updates will not be sent to the partner while the server is in the current state. The second argument specifies the server's current state name. The lease updates are still sent to the backup servers if they are configured but any possible errors in communication with the backup servers are ignored.

## 15.63 HA\_LEASE\_UPDATES\_ENABLED

```
%1: lease updates will be sent to the partner while in %2 state
```

This informational message is issued to indicate that lease updates will be sent to the partner while the server is in the current state. The second specifies the server's current state name.

## 15.64 HA\_LEASE\_UPDATE\_COMMUNICATIONS\_FAILED

```
%1: failed to send lease update %2 to %3: %4
```

This warning message indicates that there was a problem in communication with a HA peer while processing a DHCP client query and sending lease update. The client's DHCP message will be dropped.

## 15.65 HA\_LEASE\_UPDATE\_CONFLICT

```
%1: lease update %2 sent to %3 returned conflict status code: %4
```

This warning message indicates that the partner returned a conflict status code in response to a lease update. The client's DHCP message will be dropped. If the server is configured to track conflicting lease updates, it may eventually transition to the terminated state when the configured threshold is exceeded.

## 15.66 HA\_LEASE\_UPDATE\_CREATE\_UPDATE\_FAILED\_ON\_PEER

```
%1: failed to create or update the lease having type %2 for address %3, reason: %4
```

This informational message is issued when one of the leases failed to be created or updated on the HA peer while processing the lease updates sent from this server. This may indicate an issue with communication between the peer and its lease database.

## 15.67 HA\_LEASE\_UPDATE\_DELETE\_FAILED\_ON\_PEER

```
%1: failed to delete the lease having type %2 for address %3, reason: %4
```

This informational message is issued when one of the leases failed to delete on the HA peer while processing lease updates sent from this server. Typically, the lease fails to delete when it doesn't exist in the peer's database.

## 15.68 HA\_LEASE\_UPDATE\_FAILED

```
%1: lease update %2 sent to %3 failed: %4
```

This warning message indicates that a peer returned an error status code in response to a lease update. The client's DHCP message will be dropped.



## 15.69 HA\_LEASE\_UPDATE\_REJECTS\_CAUSED\_TERMINATION

```
%1: too many rejected lease updates cause the HA service to terminate
```

This error message is issued when the HA service terminates because the number of lease updates for which a conflict status code was returned by the partner exceeds the limit set with max-rejected-lease-updates configuration parameter.

## 15.70 HA\_LOAD\_BALANCING\_DUID\_MISSING

```
%1: load balancing failed for the DHCPv6 message (transaction id: %2) because DUID is
↳missing
```

Logged at debug log level 40. This debug message is issued when the HA hook library was unable to load balance an incoming DHCPv6 query because neither client identifier nor HW address was included in the query. The query will be dropped. The sole argument contains transaction id.

## 15.71 HA\_LOAD\_BALANCING\_IDENTIFIER\_MISSING

```
%1: load balancing failed for the DHCPv4 message (transaction id: %2) because HW address
↳and client identifier are missing
```

Logged at debug log level 40. This debug message is issued when the HA hook library was unable to load balance an incoming DHCPv4 query because neither client identifier nor HW address was included in the query. The query will be dropped. The sole argument contains transaction id.

## 15.72 HA\_LOCAL\_DHCP\_DISABLE

```
local DHCP service is disabled while the %1 is in the %2 state
```

This informational message is issued to indicate that the local DHCP service is disabled because the server remains in a state in which the server should not respond to DHCP clients, e.g. the server hasn't synchronized its lease database. The first argument specifies server name. The second argument specifies server's state.

## 15.73 HA\_LOCAL\_DHCP\_ENABLE

```
local DHCP service is enabled while the %1 is in the %2 state
```

This informational message is issued to indicate that the local DHCP service is enabled because the server remains in a state in which it should respond to the DHCP clients. The first argument specifies server name. The second argument specifies server's state.

## 15.74 HA\_MAINTENANCE\_CANCEL\_HANDLER\_FAILED

```
ha-maintenance-cancel command failed: %1
```

This error message is issued to indicate that the ha-maintenance-cancel command handler failed while processing the command. The argument provides the reason for failure.

## 15.75 HA\_MAINTENANCE\_NOTIFY\_CANCEL\_COMMUNICATIONS\_FAILED

```
%1: failed to send ha-maintenance-notify to %2 in attempt to cancel its maintenance: %3
```

This warning message indicates that there was a problem in communication with a HA peer while sending the ha-maintenance-notify command with the cancel flag set to true. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.76 HA\_MAINTENANCE\_NOTIFY\_CANCEL\_FAILED

```
%1: error returned while processing ha-maintenance-notify by %2 in attempt to cancel its_
↪maintenance: %3
```

This warning message indicates that a peer returned an error status code in response to a ha-maintenance-notify command with the cancel flag set to true. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.77 HA\_MAINTENANCE\_NOTIFY\_COMMUNICATIONS\_FAILED

```
%1: failed to send ha-maintenance-notify to %2: %3
```

This warning message indicates that there was a problem in communication with a HA peer while sending the ha-maintenance-notify command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.78 HA\_MAINTENANCE\_NOTIFY\_FAILED

```
%1: error returned while processing ha-maintenance-notify by %2: %3
```

This warning message indicates that a peer returned an error status code in response to a ha-maintenance-notify command. The first argument provides the remote server's name. The second argument provides a reason for failure.

## 15.79 HA\_MAINTENANCE\_NOTIFY\_HANDLER\_FAILED

```
ha-maintenance-notify command failed: %1
```

This error message is issued to indicate that the ha-maintenance-notify command handler failed while processing the command. The argument provides the reason for failure.

## 15.80 HA\_MAINTENANCE\_SHUTDOWN\_SAFE

```
%1: the server can now be shutdown for maintenance as the partner has taken over the  
↔DHCP traffic
```

This informational message is displayed after the server transitions to the in-maintenance state. This server no longer responds to any DHCP queries and its partner - in partner-in-maintenance state - has taken over the DHCP traffic. When the server in-maintenance state is shut down, the partner moves to the partner-down state immediately.

## 15.81 HA\_MAINTENANCE\_STARTED

```
%1: the server is now in the partner-in-maintenance state and the partner is in-  
↔maintenance state
```

This informational message is displayed when the server receiving the ha-maintenance-start command transitions to the partner-in-maintenance state. The server does it after sending the ha-maintenance-notify to its partner to put the partner in the in-maintenance state. From now on, the server in the partner-in-maintenance state will be responding to all queries and the partner will respond to no queries. The partner may be safely shut down for maintenance in which case this server will automatically transition from the partner-in-maintenance state to the partner-down state.

## 15.82 HA\_MAINTENANCE\_STARTED\_IN\_PARTNER\_DOWN

```
%1: the server is now in the partner-down mode as a result of requested maintenance
```

This informational message is displayed when the server receiving the ha-maintenance-start command transitions to the partner-down state because it was unable to communicate with the partner while receiving the command. It is assumed that in such situation the partner is already offline for the maintenance. Note that in this case the normal failover procedure does not take place. The server does not wait for a heartbeat to fail several times, nor it monitors the DHCP traffic for not responded queries. In the maintenance case the server transitions to the partner-down state when it first encounters a communication problem with the partner.

## 15.83 HA\_MAINTENANCE\_START\_HANDLER\_FAILED

```
ha-maintenance-start command failed: %1
```

This error message is issued to indicate that the ha-maintenance-start command handler failed while processing the command. The argument provides the reason for failure.

## 15.84 HA\_MISSING\_CONFIGURATION

```
high-availability parameter not specified for High Availability hooks library
```

This error message is issued to indicate that the configuration for the High Availability hooks library hasn't been specified. The 'high-availability' parameter must be specified for the hooks library to load properly.

## 15.85 HA\_PAUSE\_CLIENT\_LISTENER\_FAILED

```
%1: pausing multi-threaded HTTP processing failed: %2
```

This error message is emitted when attempting to pause HA's HTTP client and listener threads. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

## 15.86 HA\_PAUSE\_CLIENT\_LISTENER\_ILLEGAL

```
%1: pausing multi-threaded HTTP processing failed: %2
```

This error message is emitted when attempting to pause HA's HTTP client or listener thread pools from a worker thread. This error indicates that a command run on the listener threads is trying to use a critical section which would result in a dead-lock.

## 15.87 HA\_RESET\_COMMUNICATIONS\_FAILED

```
%1: failed to send ha-reset command to %2: %3
```

This warning message indicates a problem with communication with a HA peer while sending the ha-reset command. The first argument specifies the local server name. The second argument specifies a remote server name. The third argument specifies a reason for failure.

## 15.88 HA\_RESET\_FAILED

```
%1: failed to reset HA state machine of %2: %3
```

This warning message indicates that a peer returned an error status code in response to the ha-reset command. The first argument specifies a local server name. The second argument specifies a remote server name. The third argument specifies a reason for failure.

## 15.89 HA\_RESET\_HANDLER\_FAILED

```
ha-reset command failed: %1
```

This error message is issued to indicate that the ha-reset command handler failed while processing the command. The argument provides the reason for failure.

## 15.90 HA\_RESUME\_CLIENT\_LISTENER\_FAILED

```
%1: resuming multi-threaded HTTP processing failed: %2
```

This error message is emitted when attempting to resume HA's HTTP client and listener threads. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

## 15.91 HA\_SCOPES\_HANDLER\_FAILED

```
ha-scopes command failed: %1
```

This error message is issued to indicate that the ha-scopes command handler failed while processing the command. The argument provides reason for the failure.

## 15.92 HA\_SERVICE\_STARTED

```
%1: started high availability service in %2 mode as %3 server
```

This informational message is issued when the HA service is started as a result of server startup or reconfiguration. The first argument specifies a local server name. The second argument provides the HA mode. The third argument specifies the role of this server instance in this configuration.

## 15.93 HA\_STATE\_MACHINE\_CONTINUED

`%1: state machine is un-paused`

This informational message is issued when the HA state machine is un-paused. This unlocks the server from the current state. It may transition to any other state if it needs to do so, e.g. 'partner-down' if its partner appears to be offline. The server may also remain in the current state if the HA setup state warrants such behavior.

## 15.94 HA\_STATE\_MACHINE\_PAUSED

`%1: state machine paused in state %2`

This informational message is issued when the HA state machine is paused. HA state machine may be paused in certain states specified in the HA hooks library configuration. When the state machine is paused, the server remains in the given state until it is explicitly unpaused (via the ha-continue command). If the state machine is paused, the server operates normally but cannot transition to any other state.

## 15.95 HA\_STATE\_TRANSITION

`%1: server transitions from %2 to %3 state, partner state is %4`

This informational message is issued when the server transitions to a new state as a result of some interaction (or lack of thereof) with its partner. The arguments specify local server name, initial server state, new server state and the partner's state.

## 15.96 HA\_STATE\_TRANSITION\_PASSIVE\_BACKUP

`%1: server transitions from %2 to %3 state`

This informational message is issued when the server in passive-backup mode transitions to a new state. The arguments specify local server name, initial server state and a new server state.

## 15.97 HA\_SUBNET4\_SELECT\_FAILED

`subnet4_select callout failed: %1`

This error message is issued when the callout for the subnet4\_select hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

## 15.98 HA\_SUBNET4\_SELECT\_INVALID\_HA\_SERVER\_NAME

```
%1: invalid ha-server-name value for subnet %2
```

This error message is issued when the received DHCPv4 query is dropped by this server because the specified ha-server-name value in the subnet's user-context has non-string type or is empty. It is a server's misconfiguration. The first argument is the client identification information. The second argument is a subnet prefix.

## 15.99 HA\_SUBNET4\_SELECT\_NOT\_FOR\_US

```
%1: dropping query in relationship %2 to be processed by another server
```

Logged at debug log level 40. This debug message is issued when the received DHCPv4 query is dropped by this server because it should be served by another server. This is the case when a remote primary server is operational. The first argument is the client identification information. The second argument is the relationship name.

## 15.100 HA\_SUBNET4\_SELECT\_NO\_RELATIONSHIP\_FOR\_SUBNET

```
%1: HA relationship not found for %2
```

This error message is issued when the received DHCPv4 query is dropped by this server because the server could not find a relationship matching the specified ha-server-name for a subnet. The server name matches no relationship specified in the HA configuration. A typical reason for it is a typo. The first argument is the client identification information. The second argument is the relationship name.

## 15.101 HA\_SUBNET4\_SELECT\_NO\_RELATIONSHIP\_SELECTOR\_FOR\_SUBNET

```
%1: unable to determine HA relationship because selected subnet %2 lacks the ha-server-
↳name
```

This error message is issued when the received DHCPv4 query is dropped by this server because it was unable to determine the HA relationship to which the received query belongs. If there are multiple relationships, it is required to specify ha-server-name value in the user-context at the subnet or shared network level for each subnet and/or shared network. The server uses them as a relationship selector. If these selectors are unspecified for any of the subnets it is a configuration error. The first argument is the client identification information. The second argument is a subnet prefix.

## 15.102 HA\_SUBNET4\_SELECT\_NO\_SUBNET\_SELECTED

```
%1: unable to determine HA relationship because no subnet has been selected for the
↳client
```

Logged at debug log level 40. This debug message is issued when the received DHCPv4 query is dropped by this server because it could not select a subnet for this client. Selecting the subnet is required to find a suitable HA relationship. This message is not emitted when the server has only one relationship. The argument is the client identification information.

## 15.103 HA\_SUBNET6\_SELECT\_FAILED

```
subnet6_select callout failed: %1
```

This error message is issued when the callout for the `subnet6_select` hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

## 15.104 HA\_SUBNET6\_SELECT\_INVALID\_HA\_SERVER\_NAME

```
%1: invalid ha-server-name value for subnet %2
```

This error message is issued when the received DHCPv6 query is dropped by this server because the specified `ha-server-name` value in the subnet's user-context has non-string type or is empty. It is a server's misconfiguration. The first argument is the client identification information. The second argument is a subnet prefix.

## 15.105 HA\_SUBNET6\_SELECT\_NOT\_FOR\_US

```
%1: dropping query in relationship %2 to be processed by another server
```

Logged at debug log level 40. This debug message is issued when the received DHCPv6 query is dropped by this server because it should be served by another server. This is the case when a remote primary server is operational. The first argument is the client identification information. The second argument is the relationship name.

## 15.106 HA\_SUBNET6\_SELECT\_NO\_RELATIONSHIP\_FOR\_SUBNET

```
%1: HA relationship not found for %2
```

This error message is issued when the received DHCPv6 query is dropped by this server because the server could not find a relationship matching the specified `ha-server-name` for a subnet. The server name matches no relationship specified in the HA configuration. A typical reason for it is a typo. The first argument is the client identification information. The second argument is the relationship name.

## 15.107 HA\_SUBNET6\_SELECT\_NO\_RELATIONSHIP\_SELECTOR\_FOR\_SUBNET

```
%1: unable to determine HA relationship because selected subnet %2 lacks the ha-server-  
↪name
```

This error message is issued when the received DHCPv6 query is dropped by this server because it was unable to determine the HA relationship to which the received query belongs. If there are multiple relationships, it is required to specify `ha-server-name` value in the user-context at the subnet or shared network level for each subnet and/or shared network. The server uses them as a relationship selector. If these selectors are unspecified for any of the subnets it is a configuration error. The first argument is the client identification information. The second argument is a subnet prefix.



## 15.108 HA\_SUBNET6\_SELECT\_NO\_SUBNET\_SELECTED

```
%1: unable to determine HA relationship because no subnet has been selected for the_
↪client
```

Logged at debug log level 40. This debug message is issued when the received DHCPv6 query is dropped by this server because it could not select a subnet for this client. Selecting the subnet is required to find a suitable HA relationship. This message is not emitted when the server has only one relationship. The argument is the client identification information.

## 15.109 HA\_SYNC\_COMPLETE\_NOTIFY\_COMMUNICATIONS\_FAILED

```
%1: failed to send ha-sync-complete-notify to %2: %3
```

This warning message indicates that there was a problem in communication with an HA peer while sending the ha-sync-complete-notify command. The first argument provides a local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.110 HA\_SYNC\_COMPLETE\_NOTIFY\_FAILED

```
%1: error processing ha-sync-complete-notify command on %2: %3
```

This warning message indicates that a peer returned an error status code in response to the ha-sync-complete-notify command. The first argument provides a local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

## 15.111 HA\_SYNC\_COMPLETE\_NOTIFY\_HANDLER\_FAILED

```
ha-sync-complete-notify command failed: %1
```

This error message is issued to indicate that the ha-sync-complete-notify command handler failed while processing the command. The argument provides the reason for failure.

## 15.112 HA\_SYNC\_FAILED

```
%1: lease database synchronization with %2 failed: %3
```

This error message is issued to indicate that the lease database synchronization failed. The first argument provides the local server's name. The second argument provides the partner server's name. The third argument provides a reason for the failure.

## 15.113 HA\_SYNC\_HANDLER\_FAILED

```
ha-sync command failed: %1
```

This error message is issued to indicate that the ha-sync command handler failed while processing the command. The argument provides the reason for failure.

## 15.114 HA\_SYNC\_START

```
%1: starting lease database synchronization with %2
```

This informational message is issued when the server starts lease database synchronization with a partner. The arguments specify the local and remote server names.

## 15.115 HA\_SYNC\_SUCCESSFUL

```
%1: lease database synchronization with %2 completed successfully in %3
```

This informational message is issued when the server successfully completed lease database synchronization with the partner. The first argument specifies local server name. The second argument specifies the name of the partner server. The third argument specifies the duration of the synchronization.

## 15.116 HA\_TERMINATED

```
HA %1: service terminated due to an unrecoverable condition. Check previous error_↵  
↵message(s), address the problem and restart!
```

This error message is issued to indicate that the HA service has been stopped due to an unacceptable condition (e.g. too large of a clock skew). The exact cause should appear in a previous error message. Address the condition reported then restart the servers to resume service.

## 15.117 HA\_TERMINATED\_PARTNER\_DID\_NOT\_RESTART

```
%1: service is terminating because the terminated partner was not restarted within %2_↵  
↵minutes
```

This warning message is issued to indicate that the HA service is terminating because partner server is in the terminated state and was not restarted within an expected time frame. The terminated servers should be restarted after correcting the problem that caused the termination. They can be restarted sequentially but the duration between the restarts should not be too long. If it is long it may mean that the restart of one of the servers was unintentional (e.g., power outage). If the restarted server remains in the waiting state it cannot serve DHCP clients. Moving to the terminated state at least allows for responding to the DHCP traffic.

## 16.1 HOOKS\_ALL\_CALLOUTS\_DEREGISTERED

```
hook library at index %1 removed all callouts on hook %2
```

Logged at debug log level 55. A debug message issued when all callouts on the specified hook registered by the library with the given index were removed. This is similar to the `HOOKS_CALLOUTS_REMOVED` message (and the two are likely to be seen together), but is issued at a lower-level in the hook framework.

## 16.2 HOOKS\_CALLOUTS\_BEGIN

```
begin all callouts for hook %1
```

Logged at debug log level 45. This debug message is issued when callout manager begins to invoke callouts for the hook. The argument specifies the hook name.

## 16.3 HOOKS\_CALLOUTS\_COMPLETE

```
completed callouts for hook %1 (total callouts duration: %2)
```

Logged at debug log level 45. This debug message is issued when callout manager has completed execution of all callouts for the particular hook. The arguments specify the hook name and total execution time for all callouts in milliseconds.

## 16.4 HOOKS\_CALLOUTS\_REMOVED

```
callouts removed from hook %1 for library %2
```

Logged at debug log level 45. This is a debug message issued during library unloading. It notes that one or more callouts registered by that library have been removed from the specified hook. This is similar to the `HOOKS_DEREGISTER_ALL_CALLOUTS` message (and the two are likely to be seen together), but is issued at a higher-level in the hook framework.

## 16.5 HOOKS\_CALLOUT\_CALLED

```
hooks library with index %1 has called a callout on hook %2 that has address %3 (callout_
↳duration: %4)
```

Logged at debug log level 55. Only output at a high debugging level, this message indicates that a callout on the named hook registered by the library with the given index (in the list of loaded libraries) has been called and returned a success state. The address of the callout is given in the message. The message includes the callout execution time in milliseconds.

## 16.6 HOOKS\_CALLOUT\_DEREGISTERED

```
hook library at index %1 deregistered a callout on hook %2
```

Logged at debug log level 55. A debug message issued when all instances of a particular callouts on the hook identified in the message that were registered by the library with the given index have been removed.

## 16.7 HOOKS\_CALLOUT\_ERROR

```
error returned by callout on hook %1 registered by library with index %2 (callout_
↳address %3) (callout duration %4)
```

If a callout returns an error status when called, this error message is issued. It identifies the hook to which the callout is attached, the index of the library (in the list of loaded libraries) that registered it and the address of the callout. The error is otherwise ignored. The error message includes the callout execution time in milliseconds.

## 16.8 HOOKS\_CALLOUT\_EXCEPTION

```
exception thrown by callout on hook %1 registered by library with index %2 (callout_
↳address %3): %4 (callout duration: %5)
```

If a callout throws an exception when called, this error message is issued. It identifies the hook to which the callout is attached, the index of the library (in the list of loaded libraries) that registered it and the address of the callout. The error is otherwise ignored. The error message includes the callout execution time in milliseconds.

## 16.9 HOOKS\_CALLOUT\_REGISTRATION

```
hooks library with index %1 registering callout for hook '%2'
```

Logged at debug log level 45. This is a debug message, output when a library (whose index in the list of libraries (being) loaded is given) registers a callout.

## 16.10 HOOKS\_CLOSE\_ERROR

```
failed to close hook library %1: %2
```

Kea has failed to close the named hook library for the stated reason. Although this is an error, this should not affect the running system other than as a loss of resources. If this error persists, you should restart Kea.

## 16.11 HOOKS\_HOOK\_LIST\_RESET

```
the list of hooks has been reset
```

This is a message indicating that the list of hooks has been reset. While this is usual when running the Kea test suite, it should not be seen when running Kea in a production environment. If this appears, please report a bug through the usual channels.

## 16.12 HOOKS\_INCORRECT\_VERSION

```
hook library %1 is at version %2, require version %3
```

Kea has detected that the named hook library has been built against a version of Kea that is incompatible with the version of Kea running on your system. It has not loaded the library. This is most likely due to the installation of a new version of Kea without rebuilding the hook library. A rebuild and re-install of the library should fix the problem in most cases.

## 16.13 HOOKS\_LIBRARY\_CLOSED

```
hooks library %1 successfully closed
```

This information message is issued when a user-supplied hooks library has been successfully closed.

## 16.14 HOOKS\_LIBRARY\_LOADED

```
hooks library %1 successfully loaded
```

This information message is issued when a user-supplied hooks library has been successfully loaded.

## 16.15 HOOKS\_LIBRARY\_LOADING

```
loading hooks library %1
```

Logged at debug log level 40. This is a debug message output just before the specified library is loaded. If the action is successfully, it will be followed by the HOOKS\_LIBRARY\_LOADED informational message.

## 16.16 HOOKS\_LIBRARY\_MULTI\_THREADING\_COMPATIBLE

```
hooks library %1 reports its multi-threading compatibility as %2
```

Logged at debug log level 45. A debug message issued when the "multi\_threading\_compatible" function was called. The returned value (0 means not compatible, others compatible) is displayed.

## 16.17 HOOKS\_LIBRARY\_MULTI\_THREADING\_NOT\_COMPATIBLE

```
hooks library %1 is not compatible with multi-threading
```

When multi-threading is enabled and the library is not compatible (either because the "multi\_threading\_compatible" function returned 0 or was not implemented) this error message is issued. The library must be removed from the configuration or the multi-threading disabled.

## 16.18 HOOKS\_LIBRARY\_UNLOADED

```
hooks library %1 successfully unloaded
```

This information message is issued when a user-supplied hooks library has been successfully unloaded.

## 16.19 HOOKS\_LIBRARY\_UNLOADING

```
unloading library %1
```

Logged at debug log level 40. This is a debug message called when the specified library is being unloaded. If all is successful, it will be followed by the HOOKS\_LIBRARY\_UNLOADED informational message.

## 16.20 HOOKS\_LIBRARY\_VERSION

```
hooks library %1 reports its version as %2
```

Logged at debug log level 45. A debug message issued when the version check on the hooks library has succeeded.

## 16.21 HOOKS\_LOAD\_ERROR

```
'load' function in hook library %1 returned error %2
```

A "load" function was found in the library named in the message and was called. The function returned a non-zero status (also given in the message) which was interpreted as an error. The library has been unloaded and no callouts from it will be installed.

## 16.22 HOOKS\_LOAD\_EXCEPTION

```
'load' function in hook library %1 threw an exception
```

A "load" function was found in the library named in the message and was called. The function threw an exception (an error indication) during execution, which is an error condition. The library has been unloaded and no callouts from it will be installed.

## 16.23 HOOKS\_LOAD\_FRAMEWORK\_EXCEPTION

```
'load' function in hook library %1 threw an exception: reason %2
```

A "load" function was found in the library named in the message and was called. Either the hooks framework or the function threw an exception (an error indication) during execution, which is an error condition; the cause of the exception is recorded in the message. The library has been unloaded and no callouts from it will be installed.

## 16.24 HOOKS\_LOAD\_SUCCESS

```
'load' function in hook library %1 returned success
```

Logged at debug log level 40. This is a debug message issued when the "load" function has been found in a hook library and has been successfully called.

## 16.25 HOOKS\_MULTI\_THREADING\_COMPATIBLE\_EXCEPTION

```
'multi_threading_compatible' function in hook library %1 threw an exception
```

This error message is issued if the `multi_threading_compatible()` function in the specified hooks library was called and generated an exception. The library is considered unusable and will not be loaded.

## 16.26 HOOKS\_NO\_LOAD

```
no 'load' function found in hook library %1
```

Logged at debug log level 40. This is a debug message saying that the specified library was loaded but no function called "load" was found in it. Providing the library contained some "standard" functions (i.e. functions with the names of the hooks for the given server), this is not an issue.

## 16.27 HOOKS\_NO\_UNLOAD

```
no 'unload' function found in hook library %1
```

Logged at debug log level 40. This is a debug message issued when the library is being unloaded. It merely states that the library did not contain an "unload" function.

## 16.28 HOOKS\_NO\_VERSION

```
no 'version' function found in hook library %1
```

The shared library named in the message was found and successfully loaded, but Kea did not find a function named "version" in it. This function is required and should return the version of Kea against which the library was built. The value is used to check that the library was built against a compatible version of Kea. The library has not been loaded.

## 16.29 HOOKS\_OPEN\_ERROR

```
failed to open hook library %1: %2
```

Kea failed to open the specified hook library for the stated reason. The library has not been loaded. Kea will continue to function, but without the services offered by the library.

## 16.30 HOOKS\_STD\_CALLOUT\_REGISTERED

```
hooks library %1 registered standard callout for hook %2 at address %3
```

Logged at debug log level 45. This is a debug message, output when the library loading function has located a standard callout (a callout with the same name as a hook point) and registered it. The address of the callout is indicated.



## 16.31 HOOKS\_UNLOAD\_ERROR

```
'unload' function in hook library %1 returned error %2
```

During the unloading of a library, an "unload" function was found. It was called, but returned an error (non-zero) status, resulting in the issuing of this message. The unload process continued after this message and the library has been unloaded.

## 16.32 HOOKS\_UNLOAD\_EXCEPTION

```
'unload' function in hook library %1 threw an exception
```

During the unloading of a library, an "unload" function was found. It was called, but in the process generated an exception (an error indication). The unload process continued after this message and the library has been unloaded.

## 16.33 HOOKS\_UNLOAD\_FRAMEWORK\_EXCEPTION

```
'unload' function in hook library %1 threw an exception, reason %2
```

During the unloading of a library, an "unload" function was found. It was called, but in the process either it or the hooks framework generated an exception (an error indication); the cause of the error is recorded in the message. The unload process continued after this message and the library has been unloaded.

## 16.34 HOOKS\_UNLOAD\_SUCCESS

```
'unload' function in hook library %1 returned success
```

Logged at debug log level 40. This is a debug message issued when an "unload" function has been found in a hook library during the unload process, called, and returned success.



## 17.1 HOSTS\_BACKENDS\_REGISTERED

```
the following host backend types are available: %1
```

This informational message lists all possible host backends that could be used in hosts-database[s].

## 17.2 HOSTS\_BACKEND\_DEREGISTER

```
deregistered host backend type: %1
```

Logged at debug log level 40. This debug message is issued when a backend factory was deregistered. It is no longer possible to use host backend of this type.

## 17.3 HOSTS\_BACKEND\_REGISTER

```
registered host backend type: %1
```

Logged at debug log level 40. This debug message is issued when a backend factory was successfully registered. It is now possible to use host backend of this type.

## 17.4 HOSTS\_CFG\_ADD\_HOST

```
add the host for reservations: %1
```

Logged at debug log level 40. This debug message is issued when new host (with reservations) is added to the server's configuration. The argument describes the host and its reservations in detail.

## 17.5 HOSTS\_CFG\_CACHE\_HOST\_DATA\_SOURCE

```
get host cache data source: %1
```

This informational message is issued when a host cache data source is detected by the host manager.

## 17.6 HOSTS\_CFG\_CLOSE\_HOST\_DATA\_SOURCE

```
Closing host data source: %1
```

Logged at debug log level 40. This is a normal message being printed when the server closes host data source connection.

## 17.7 HOSTS\_CFG\_DEL

```
deleted %1 host(s) having %2 IPv6 reservation(s) for subnet id %3 and address %4
```

Logged at debug log level 40. This debug message is issued when reservations are deleted for the specified subnet and address. The first argument specifies how many hosts have been deleted. The second argument specifies how many reservations have been deleted. The third argument is the subnet identifier. The fourth argument is the IP address.

## 17.8 HOSTS\_CFG\_DEL4

```
deleted %1 host(s) for subnet id %2 and identifier %3
```

Logged at debug log level 40. This debug message is issued when IPv4 reservations are deleted for the specified subnet and identifier. The first argument specifies how many hosts have been deleted. The second argument is the subnet identifier. The third argument is the identifier.

## 17.9 HOSTS\_CFG\_DEL6

```
deleted %1 host(s) having %2 IPv6 reservation(s) for subnet id %3 and identifier %4
```

Logged at debug log level 40. This debug message is issued when IPv6 reservations are deleted for the specified subnet and identifier. The first argument specifies how many hosts have been deleted. The second argument specifies how many reservations have been deleted. The third argument is the subnet identifier. The fourth argument is the identifier.

## 17.10 HOSTS\_CFG\_DEL\_ALL\_SUBNET4

```
deleted all %1 host(s) for subnet id %2
```

Logged at debug log level 40. This debug message is issued when all IPv4 reservations are deleted for the specified subnet. The first argument specifies how many reservations have been deleted. The second argument is the subnet identifier.

## 17.11 HOSTS\_CFG\_DEL\_ALL\_SUBNET6

```
deleted all %1 host(s) having %2 IPv6 reservation(s) for subnet id %3
```

Logged at debug log level 40. This debug message is issued when all IPv6 reservations are deleted for the specified subnet. The first argument specifies how many hosts have been deleted. The second argument specifies how many IPv6 (addresses and prefixes) reservations have been deleted. The third argument is the subnet identifier.

## 17.12 HOSTS\_CFG\_GET\_ALL

```
get all hosts with reservations
```

Logged at debug log level 45. This debug message is issued when starting to retrieve all hosts.

## 17.13 HOSTS\_CFG\_GET\_ALL\_ADDRESS4

```
get all hosts with reservations for IPv4 address %1
```

Logged at debug log level 45. This debug message is issued when starting to retrieve all hosts, holding the reservation for the specific IPv4 address, from the configuration. The argument specifies the IPv4 address used to search the hosts.

## 17.14 HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_COUNT

```
using address %1, found %2 host(s)
```

Logged at debug log level 45. This debug message logs the number of hosts found using the specified IPv4 address. The arguments specify the IPv4 address used and the number of hosts found respectively.

## 17.15 HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_HOST

```
using address %1 found host: %2
```

Logged at debug log level 55. This debug message is issued when found host with the reservation for the specified IPv4 address. The arguments specify the IPv4 address and the detailed description of the host found.

## 17.16 HOSTS\_CFG\_GET\_ALL\_ADDRESS6

```
get all hosts with reservations for IPv6 address %1
```

Logged at debug log level 45. This debug message is issued when starting to retrieve all hosts, holding the reservation for the specific IPv6 address, from the configuration. The argument specifies the IPv6 address used to search the hosts.

## 17.17 HOSTS\_CFG\_GET\_ALL\_ADDRESS6\_COUNT

```
using address %1, found %2 host(s)
```

Logged at debug log level 45. This debug message logs the number of hosts found using the specified IPv6 address. The arguments specify the IPv6 address used and the number of hosts found respectively.

## 17.18 HOSTS\_CFG\_GET\_ALL\_ADDRESS6\_HOST

```
using address %1 found host: %2
```

Logged at debug log level 55. This debug message is issued when found host with the reservation for the specified IPv6 address. The arguments specify the IPv6 address and the detailed description of the host found.

## 17.19 HOSTS\_CFG\_GET\_ALL\_COUNT

```
found %1 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found. The argument specifies the number of hosts found.

## 17.20 HOSTS\_CFG\_GET\_ALL\_HOST

```
found host: %1
```

Logged at debug log level 45. This debug message includes the details of the host found. The argument specifies found host details.

## 17.21 HOSTS\_CFG\_GET\_ALL\_HOSTNAME

```
get all hosts with reservations for hostname %1
```

Logged at debug log level 45. This debug message is issued when starting to retrieve all hosts with the specific hostname. The argument specifies hostname.

## 17.22 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_COUNT

```
using hostname %1, found %2 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the hostname. The arguments specify hostname and the number of hosts found respectively.

## 17.23 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_HOST

```
using hostname %1, found host: %2
```

Logged at debug log level 55. This debug message includes the details of the host found using the hostname. The arguments specify hostname and found host details respectively.

## 17.24 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4

```
get all hosts with reservations for hostname %1 and IPv4 subnet %2
```

Logged at debug log level 45. This debug message is issued when starting to retrieve all hosts with the specific hostname connected to the specific DHCPv4 subnet. The argument specifies hostname and subnet id.

## 17.25 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4\_COUNT

```
using hostname %1 and IPv4 subnet %2, found %3 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the hostname and the DHCPv4 subnet id. The arguments specify hostname, subnet id and the number of hosts found respectively.

## 17.26 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4\_HOST

```
using hostname %1 and IPv4 subnet %2, found host: %3
```

Logged at debug log level 55. This debug message includes the details of the host found using the hostname and the DHCPv4 subnet id. The arguments specify hostname, subnet id and found host details respectively.

## 17.27 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID6

```
get all hosts with reservations for hostname %1 and IPv6 subnet %2
```

Logged at debug log level 45. This debug message is issued when starting to retrieve all hosts with the specific hostname connected to the specific DHCPv6 subnet. The argument specifies hostname and subnet id.

## 17.28 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID6\_COUNT

```
using hostname %1 and IPv6 subnet %2, found %3 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the hostname and the DHCPv6 subnet id. The arguments specify hostname, subnet id and the number of hosts found respectively.

## 17.29 HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID6\_HOST

```
using hostname %1 and IPv6 subnet %2, found host: %3
```

Logged at debug log level 55. This debug message includes the details of the host found using the hostname and the DHCPv6 subnet id. The arguments specify hostname, subnet id and found host details respectively.

## 17.30 HOSTS\_CFG\_GET\_ALL\_IDENTIFIER

```
get all hosts with reservations using identifier: %1
```

Logged at debug log level 45. This debug message is issued when starting to retrieve reservations for all hosts identified by HW address or DUID. The argument holds both the identifier type and the value.

## 17.31 HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_COUNT

```
using identifier %1, found %2 host(s)
```

Logged at debug log level 45. This debug message logs the number of hosts found using the specified identifier. The arguments specify the identifier used and the number of hosts found respectively.

## 17.32 HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_HOST

```
using identifier: %1, found host: %2
```

Logged at debug log level 55. This debug message is issued when found host identified by the specific identifier. The arguments specify the identifier and the detailed description of the host found.



### 17.33 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID4

```
get all hosts with reservations for IPv4 subnet %1
```

Logged at debug log level 45. This debug message is issued when starting to retrieve all hosts connected to the specific DHCPv4 subnet. The argument specifies subnet id.

### 17.34 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID4\_COUNT

```
using IPv4 subnet %1, found %2 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the DHCPv4 subnet id. The arguments specify subnet id and the number of hosts found respectively.

### 17.35 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID4\_HOST

```
using IPv4 subnet %1, found host: %2
```

Logged at debug log level 55. This debug message includes the details of the host found using the DHCPv4 subnet id. The arguments specify subnet id and found host details respectively.

### 17.36 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID6

```
get all hosts with reservations for IPv6 subnet %1
```

Logged at debug log level 45. This debug message is issued when starting to retrieve all hosts connected to the specific DHCPv6 subnet. The argument specifies subnet id.

### 17.37 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID6\_COUNT

```
using IPv6 subnet %1, found %2 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the DHCPv6 subnet id. The arguments specify subnet id and the number of hosts found respectively.

### 17.38 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID6\_HOST

```
using IPv6 subnet %1, found host: %2
```

Logged at debug log level 55. This debug message includes the details of the host found using the DHCPv6 subnet id. The arguments specify subnet id and found host details respectively.

## 17.39 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4

```
get all hosts with reservations for subnet id %1 and IPv4 address %2
```

Logged at debug log level 45. This debug message is issued when starting to retrieve all hosts having the reservation for the given IPv4 address within the given subnet. The first argument specifies subnet identifier. The second argument specifies the IPv4 address for which the reservation is to be returned.

## 17.40 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4\_COUNT

```
using IPv4 subnet %1 and IPv4 address %2, found %3 host(s)
```

Logged at debug log level 45. This debug message logs the number of hosts found having the reservation for the specified IPv4 address within the specified subnet. The first argument specifies the subnet identifier. The second argument specifies the reserved IPv4 address. The third argument specifies the number of hosts found.

## 17.41 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4\_HOST

```
using IPv4 subnet %1 and IPv4 address %2, found host: %3
```

Logged at debug log level 55. This debug message is issued when found host having the reservation for the specified IPv4 address in the specified subnet. The first argument specifies the subnet identifier. The second argument specifies the reserved IPv4 address. The third argument specifies host details.

## 17.42 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6

```
get all hosts with reservations for subnet id %1 and IPv6 address %2
```

Logged at debug log level 45. This debug message is issued when starting to retrieve all hosts connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

## 17.43 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6\_COUNT

```
using subnet id %1 and address %2, found %3 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the subnet id and address. The arguments specify subnet id, address and the number of hosts found respectively.

## 17.44 HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6\_HOST

```
using subnet id %1 and address %2, found host: %3
```

Logged at debug log level 55. This debug message includes the details of the host found using the subnet id and address. The arguments specify subnet id, address and the number of hosts found respectively. found host details respectively.

## 17.45 HOSTS\_CFG\_GET\_ONE\_PREFIX

```
get one host with reservation for prefix %1/%2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host having a reservation for a specified prefix. The arguments specify a prefix and prefix length.

## 17.46 HOSTS\_CFG\_GET\_ONE\_PREFIX\_HOST

```
using prefix %1/%2, found host: %3
```

Logged at debug log level 55. This debug message includes the details of the host found using the specific prefix/prefix length. The arguments specify prefix, prefix length and host details respectively.

## 17.47 HOSTS\_CFG\_GET\_ONE\_PREFIX\_NULL

```
host not found using prefix %1/%2
```

Logged at debug log level 55. This debug message is issued when no host was found for a specified prefix and prefix length.

## 17.48 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4

```
get one host with reservation for subnet id %1 and IPv4 address %2
```

Logged at debug log level 45. This debug message is issued when starting to retrieve a host connected to the specific subnet and having the specific IPv4 address reserved. The arguments specify subnet id and IPv4 address respectively.

## 17.49 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_HOST

```
using subnet id %1 and address %2, found host: %3
```

Logged at debug log level 45. This debug message logs the details of the host found using the subnet id and IPv4 address.

## 17.50 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_NULL

```
host not found using subnet id %1 and address %2
```

Logged at debug log level 45. This debug message is issued when no host was found for the specified subnet id and IPv4 address.

## 17.51 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6

```
get one host with reservation for subnet id %1 and having IPv6 address %2
```

Logged at debug log level 45. This debug message is issued when starting to retrieve a host connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

## 17.52 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_HOST

```
using subnet id %1 and address %2, found host: %3
```

Logged at debug log level 45. This debug message logs the details of the host found using the subnet id and IPv6 address.

## 17.53 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_NULL

```
host not found using subnet id %1 and address %2
```

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet id and IPv6 address.

## 17.54 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER

```
get one host with %1 reservation for subnet id %2, identified by %3
```

Logged at debug log level 45. This debug message is issued when starting to retrieve a host holding IPv4 or IPv6 reservations, which is connected to a specific subnet and is identified by a specific unique identifier. The first argument identifies if the IPv4 or IPv6 reservation is desired.

## 17.55 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_HOST

```
using subnet id %1 and identifier %2, found host: %3
```

Logged at debug log level 45. This debug message includes the details of a host found using a subnet id and specific host identifier.

## 17.56 HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_NULL

```
host not found using subnet id %1 and identifier %2
```

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet id and host identifier.

## 17.57 HOSTS\_CFG\_UPDATE\_ADD

```
add the host for reservations: %1
```

Logged at debug log level 40. This debug message is issued when a new host (with reservations) is added to the server's configuration during an update. The argument describes the host and its reservations in detail.

## 17.58 HOSTS\_CFG\_UPDATE\_DEL4

```
deleted %1 host(s) for subnet id %2 and identifier %3
```

Logged at debug log level 40. This debug message is issued when IPv4 reservations are deleted for the specified subnet and identifier during an update. The first argument specifies how many hosts have been deleted. The second argument is the subnet identifier. The third argument is the identifier.

## 17.59 HOSTS\_CFG\_UPDATE\_DEL6

```
deleted %1 host(s) having %2 IPv6 reservation(s) for subnet id %3 and identifier %4
```

Logged at debug log level 40. This debug message is issued when IPv6 reservations are deleted for the specified subnet and identifier during an update. The first argument specifies how many hosts have been deleted. The second argument specifies how many reservations have been deleted. The third argument is the subnet identifier. The fourth argument is the identifier.

## 17.60 HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_ADDRESS4

```
trying alternate sources for host using subnet id %1 and address %2
```

Logged at debug log level 40. This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specific IPv4 address, and it is starting to search for this host in alternate host data sources.

## 17.61 HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER

```
get one host with IPv4 reservation for subnet id %1, identified by %2
```

Logged at debug log level 45. This debug message is issued when starting to retrieve a host holding IPv4 reservation, which is connected to a specific subnet and is identified by a specific unique identifier.

## 17.62 HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_HOST

```
using subnet id %1 and identifier %2, found in %3 host: %4
```

Logged at debug log level 45. This debug message includes the details of a host returned by an alternate hosts data source using a subnet id and specific host identifier.

## 17.63 HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_NULL

```
host not found using subnet id %1 and identifier %2
```

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet id and host identifier.

## 17.64 HOSTS\_MGR\_ALTERNATE\_GET6\_PREFIX

```
trying alternate sources for host using prefix %1/%2
```

Logged at debug log level 40. This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specified prefix, and it is starting to search for this host in alternate host data sources.

## 17.65 HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_ADDRESS6

```
trying alternate sources for host using subnet id %1 and IPv6 address %2
```

Logged at debug log level 40. This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specified IPv6 address, and it is starting to search for this host in alternate host data sources.

## 17.66 HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER

```
get one host with IPv6 reservation for subnet id %1, identified by %2
```

Logged at debug log level 45. This debug message is issued when starting to retrieve a host holding IPv4 reservation, which is connected to a specific subnet and is identified by a specific unique identifier.

## 17.67 HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_HOST

```
using subnet id %1 and identifier %2, found in %3 host: %4
```

Logged at debug log level 45. This debug message includes the details of a host returned by an alternate host data source using a subnet id and specific host identifier.

## 17.68 HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_NULL

```
host not found using subnet id %1 and identifier %2
```

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet id and host identifier.

## 17.69 HOSTS\_MGR\_ALTERNATE\_GET\_ALL\_SUBNET\_ID\_ADDRESS4

```
trying alternate sources for hosts using subnet id %1 and address %2
```

Logged at debug log level 40. This debug message is issued when the Host Manager is starting to search for hosts in alternate host data sources by subnet ID and IPv4 address.

## 17.70 HOSTS\_MGR\_ALTERNATE\_GET\_ALL\_SUBNET\_ID\_ADDRESS6

```
trying alternate sources for hosts using subnet id %1 and address %2
```

Logged at debug log level 40. This debug message is issued when the Host Manager is starting to search for hosts in alternate host data sources by subnet ID and IPv6 address.



## 18.1 HTTPS\_REQUEST\_RECEIVE\_START

```
start receiving request from %1
```

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The argument specifies the address of the remote endpoint.



## 19.1 HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED

```
bad request received from %1: %2
```

Logged at debug log level 40. This debug message is issued when an HTTP client sends malformed request to the server. This includes HTTP requests using unexpected content types, including malformed JSON etc. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides a detailed error message.

## 19.2 HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED\_DETAILS

```
detailed information about bad request received from %1:\n%2
```

Logged at debug log level 45. This debug message is issued when an HTTP client sends malformed request to the server. It includes detailed information about the received request rejected by the server. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides a request in the textual format. The request is truncated by the logger if it is too large to be printed.

## 19.3 HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED

```
bad response received when communicating with %1: %2
```

Logged at debug log level 40. This debug message is issued when an HTTP client fails to receive a response from the server or when this response is malformed. The first argument specifies the server URL. The second argument provides a detailed error message.

## 19.4 HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED\_DETAILS

```
detailed information about bad response received from %1:\n%2
```

Logged at debug log level 45. This debug message is issued when an HTTP client receives malformed response from the server. The first argument specifies an URL of the server. The second argument provides a response in the textual format. The request is truncated by the logger if it is too large to be printed.

## 19.5 HTTP\_CLIENT\_MT\_STARTED

```
HttpClient has been started in multi-threaded mode running %1 threads
```

Logged at debug log level 40. This debug message is issued when a multi-threaded HTTP client instance has been created. The argument specifies the maximum number of threads.

## 19.6 HTTP\_CLIENT\_QUEUE\_SIZE\_GROWING

```
queue for URL: %1, now has %2 entries and may be growing too quickly
```

This warning message is issued when the queue of pending requests for the given URL appears to be growing more quickly than the requests can be handled. It will be emitted periodically as long as the queue size continues to grow. This may occur with a surge of client traffic creating a momentary backlog which then subsides as the surge subsides. If it happens continually then it most likely indicates a deployment configuration that cannot sustain the client load.

## 19.7 HTTP\_CLIENT\_REQUEST\_AUTHORIZED

```
received HTTP request authorized for '%1'
```

This information message is issued when the server receives with a matching authentication header. The argument provides the user id.

## 19.8 HTTP\_CLIENT\_REQUEST\_BAD\_AUTH\_HEADER

```
received HTTP request with malformed authentication header: %1
```

This information message is issued when the server receives a request with a malformed authentication header. The argument explains the problem.

## 19.9 HTTP\_CLIENT\_REQUEST\_NOT\_AUTHORIZED

```
received HTTP request with not matching authentication header
```

This information message is issued when the server receives a request with authentication header carrying not recognized credential: the user provided incorrect user id and/or password.

## 19.10 HTTP\_CLIENT\_REQUEST\_RECEIVED

```
received HTTP request from %1
```

Logged at debug log level 40. This debug message is issued when the server finished receiving a HTTP request from the remote endpoint. The address of the remote endpoint is specified as an argument.

## 19.11 HTTP\_CLIENT\_REQUEST\_RECEIVED\_DETAILS

```
detailed information about well-formed request received from %1:\n%2
```

Logged at debug log level 45. This debug message is issued when the HTTP server receives a well-formed request. It includes detailed information about the received request. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides the request in the textual format. The request is truncated by the logger if it is too large to be printed.

## 19.12 HTTP\_CLIENT\_REQUEST\_SEND

```
sending HTTP request %1 to %2
```

Logged at debug log level 50. This debug message is issued when the client is starting to send a HTTP request to a server. The first argument holds basic information about the request (HTTP version number and status code). The second argument specifies a URL of the server.

## 19.13 HTTP\_CLIENT\_REQUEST\_SEND\_DETAILS

```
detailed information about request sent to %1:\n%2
```

Logged at debug log level 55. This debug message is issued right before the client sends an HTTP request to the server. It includes detailed information about the request. The first argument specifies an URL of the server to which the request is being sent. The second argument provides the request in the textual form. The request is truncated by the logger if it is too large to be printed.

## 19.14 HTTP\_CLIENT\_REQUEST\_TIMEOUT\_OCCURRED

HTTP request timeout occurred when communicating with %1

Logged at debug log level 50. This debug message is issued when the HTTP request timeout has occurred and the server is going to send a response with Http Request timeout status code.

## 19.15 HTTP\_COMMAND\_MGR\_IGNORED\_TLS\_SETUP\_CHANGES

ignore a change in TLS setup of the http control socket

The warning message is issued when the HTTP/HTTPS control socket was reconfigured with a different TLS setup but keeping the address and port. These changes are ignored because they can't be applied without opening a new socket which will conflict with the existing one.

## 19.16 HTTP\_COMMAND\_MGR\_SERVICE\_STARTED

started %1 service bound to address %2 port %3

This informational message indicates that the server has started HTTP/HTTPS service on the specified address and port for receiving control commands.

## 19.17 HTTP\_CONNECTION\_CLOSE\_CALLBACK\_FAILED

Connection close callback threw an exception

This is an error message emitted when the close connection callback registered on the connection failed unexpectedly. This is a programmatic error that should be submitted as a bug.

## 19.18 HTTP\_CONNECTION\_HANDSHAKE\_FAILED

TLS handshake with %1 failed with %2

This information message is issued when the TLS handshake failed at the server side. The client address and the error message are displayed.

## 19.19 HTTP\_CONNECTION\_HANDSHAKE\_START

```
start TLS handshake with %1 with timeout %2
```

Logged at debug log level 50. This debug message is issued when the server starts the TLS handshake with the remote endpoint. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

## 19.20 HTTP\_CONNECTION\_SHUTDOWN

```
shutting down HTTP connection from %1
```

Logged at debug log level 40. This debug message is issued when one of the HTTP connections is shut down. The connection can be stopped as a result of an error or after the successful message exchange with a client.

## 19.21 HTTP\_CONNECTION\_SHUTDOWN\_FAILED

```
shutting down HTTP connection failed
```

This error message is issued when an error occurred during shutting down a HTTP connection with a client.

## 19.22 HTTP\_CONNECTION\_STOP

```
stopping HTTP connection from %1
```

Logged at debug log level 40. This debug message is issued when one of the HTTP connections is stopped. The connection can be stopped as a result of an error or after the successful message exchange with a client.

## 19.23 HTTP\_CONNECTION\_STOP\_FAILED

```
stopping HTTP connection failed
```

This error message is issued when an error occurred during closing a HTTP connection with a client.

## 19.24 HTTP\_CONNECTION\_WATCH\_SOCKET\_CLEAR\_ERROR

```
clearing connection watch socket failed: %1
```

This error message is issued when an error occurred during clearing the watch socket associated with a HTTP connection with a client. The error is displayed.

## 19.25 HTTP\_CONNECTION\_WATCH\_SOCKET\_CLOSE\_ERROR

```
closing connection watch socket failed: %1
```

This error message is issued when an error occurred during closing the watch socket associated with a HTTP connection with a client. The error is displayed.

## 19.26 HTTP\_CONNECTION\_WATCH\_SOCKET\_MARK\_READY\_ERROR

```
marking ready connection watch socket failed: %1
```

This error message is issued when an error occurred during marking as ready the watch socket associated with a HTTP connection with a client. The error is displayed.

## 19.27 HTTP\_DATA\_RECEIVED

```
received %1 bytes from %2
```

Logged at debug log level 55. This debug message is issued when the server receives a chunk of data from the remote endpoint. This may include the whole request or only a part of the request. The first argument specifies the amount of received data. The second argument specifies an address of the remote endpoint which produced the data.

## 19.28 HTTP\_IDLE\_CONNECTION\_TIMEOUT\_OCCURRED

```
closing persistent connection with %1 as a result of a timeout
```

Logged at debug log level 50. This debug message is issued when the persistent HTTP connection is being closed as a result of being idle.

## 19.29 HTTP\_PREMATURE\_CONNECTION\_TIMEOUT\_OCCURRED

```
premature connection timeout occurred: in transaction ? %1, transid: %2, current_  
↪transid: %3
```

This warning message is issued when unexpected timeout occurred during the transaction. This is proven to occur when the system clock is moved manually or as a result of synchronization with a time server. Any ongoing transactions will be interrupted. New transactions should be conducted normally.



## 19.30 HTTP\_REQUEST\_RECEIVE\_START

```
start receiving request from %1 with timeout %2
```

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

## 19.31 HTTP\_SERVER\_RESPONSE\_RECEIVED

```
received HTTP response from %1
```

Logged at debug log level 40. This debug message is issued when the client finished receiving an HTTP response from the server. The URL of the server is specified as an argument.

## 19.32 HTTP\_SERVER\_RESPONSE\_RECEIVED\_DETAILS

```
detailed information about well-formed response received from %1:\n%2
```

Logged at debug log level 45. This debug message is issued when the HTTP client receives a well-formed response from the server. It includes detailed information about the received response. The first argument specifies a URL of the server which sent the response. The second argument provides the response in the textual format. The response is truncated by the logger if it is too large to be printed.

## 19.33 HTTP\_SERVER\_RESPONSE\_SEND

```
sending HTTP response %1 to %2
```

Logged at debug log level 40. This debug message is issued when the server is starting to send a HTTP response to a remote endpoint. The first argument holds basic information about the response (HTTP version number and status code). The second argument specifies an address of the remote endpoint.



## 20.1 LEASE\_CMDS\_ADD4

```
lease4-add command successful (address: %1)
```

Logged at debug log level 20. The lease4-add command has been successful. Lease IPv4 address is logged.

## 20.2 LEASE\_CMDS\_ADD4\_CONFLICT

```
lease4-add command failed due to conflict (parameters: %1, reason: %2)
```

The received lease4-add is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

## 20.3 LEASE\_CMDS\_ADD4\_FAILED

```
lease4-add command failed (parameters: %1, reason: %2)
```

The lease4-add command has failed. Both the reason as well as the parameters passed are logged.

## 20.4 LEASE\_CMDS\_ADD6

```
lease6-add command successful (address: %1)
```

Logged at debug log level 20. The lease6-add command has been successful. Lease IPv6 address is logged.

## 20.5 LEASE\_CMDS\_ADD6\_CONFLICT

```
lease6-add command failed due to conflict (parameters: %1, reason: %2)
```

The received lease6-add is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

## 20.6 LEASE\_CMDS\_ADD6\_FAILED

```
lease6-add command failed (parameters: %1, reason: %2)
```

The lease6-add command has failed. Both the reason as well as the parameters passed are logged.

## 20.7 LEASE\_CMDS\_BULK\_APPLY6

```
lease6-bulk-apply command successful (applied addresses count: %1)
```

Logged at debug log level 20. The lease6-bulk-apply command has been successful. The number of applied addresses is logged.

## 20.8 LEASE\_CMDS\_BULK\_APPLY6\_FAILED

```
lease6-bulk-apply command failed (parameters: %1, reason: %2)
```

The lease6-bulk-apply command has failed. Both the reason as well as the parameters passed are logged.

## 20.9 LEASE\_CMDS\_DEINIT\_OK

```
unloading Lease Commands hooks library successful
```

This info message indicates that the Lease Commands hooks library has been removed successfully.

## 20.10 LEASE\_CMDS\_DEL4

```
lease4-del command successful (address: %1)
```

Logged at debug log level 20. The attempt to delete an IPv4 lease (lease4-del command) has been successful. Lease IPv4 address is logged.

## 20.11 LEASE\_CMDS\_DEL4\_FAILED

```
lease4-del command failed (parameters: %1, reason: %2)
```

The attempt to delete an IPv4 lease (lease4-del command) has failed. Both the reason as well as the parameters passed are logged.

## 20.12 LEASE\_CMDS\_DEL6

```
lease4-del command successful (address: %1)
```

Logged at debug log level 20. The attempt to delete an IPv4 lease (lease4-del command) has been successful. Lease IPv6 address is logged.

## 20.13 LEASE\_CMDS\_DEL6\_FAILED

```
lease6-del command failed (parameters: %1, reason: %2)
```

The attempt to delete an IPv6 lease (lease4-del command) has failed. Both the reason as well as the parameters passed are logged.

## 20.14 LEASE\_CMDS\_GET4\_FAILED

```
lease4-get command failed (parameters: %1, reason: %2)
```

The lease4-get command has failed. Both the reason as well as the parameters passed are logged.

## 20.15 LEASE\_CMDS\_GET6\_FAILED

```
lease6-get command failed (parameters: %1, reason: %2)
```

The lease4-get command has failed. Both the reason as well as the parameters passed are logged.

## 20.16 LEASE\_CMDS\_INIT\_OK

```
loading Lease Commands hooks library successful
```

This info message indicates that the Lease Commands hooks library has been loaded successfully. Enjoy!

## 20.17 LEASE\_CMDS\_RESEND\_DDNS4

```
lease4-resend-ddns command successful: %1
```

A request to update DNS for the requested IPv4 lease has been successfully queued for transmission to kea-dhcp-ddns.

## 20.18 LEASE\_CMDS\_RESEND\_DDNS4\_FAILED

```
lease4-resend-ddns command failed: %1
```

A request to update DNS for the requested IPv4 lease has failed. The reason for the failure is logged.

## 20.19 LEASE\_CMDS\_RESEND\_DDNS6

```
lease6-resend-ddns command successful: %1
```

A request to update DNS for the requested IPv6 lease has been successfully queued for transmission to kea-dhcp-ddns.

## 20.20 LEASE\_CMDS\_RESEND\_DDNS6\_FAILED

```
lease6-resend-ddns command failed: %1
```

A request to update DNS for the requested IPv6 lease has failed. The reason for the failure is logged.

## 20.21 LEASE\_CMDS\_UPDATE4

```
lease4-update command successful (address: %1)
```

Logged at debug log level 20. The lease4-update command has been successful. Lease IPv4 address is logged.

## 20.22 LEASE\_CMDS\_UPDATE4\_CONFLICT

```
lease4-update command failed due to conflict (parameters: %1, reason: %2)
```

The received lease4-update is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

## 20.23 LEASE\_CMDS\_UPDATE4\_FAILED

```
lease4-update command failed (parameters: %1, reason: %2)
```

The lease4-update command has failed. Both the reason as well as the parameters passed are logged.

## 20.24 LEASE\_CMDS\_UPDATE6

```
lease6-update command successful (address: %1)
```

Logged at debug log level 20. The lease6-update command has been successful. Lease IPv6 address is logged.

## 20.25 LEASE\_CMDS\_UPDATE6\_CONFLICT

```
lease6-update command failed due to conflict (parameters: %1, reason: %2)
```

The received lease6-update is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

## 20.26 LEASE\_CMDS\_UPDATE6\_FAILED

```
lease6-add command failed (parameters: %1, reason: %2)
```

The lease6-update command has failed. Both the reason as well as the parameters passed are logged.

## 20.27 LEASE\_CMDS\_WIPE4

```
lease4-wipe command successful (parameters: %1)
```

The lease4-wipe command has been successful. Parameters of the command are logged.

## 20.28 LEASE\_CMDS\_WIPE4\_DEPRECATED

```
lease4-wipe command is deprecated and it will be removed in the future.
```

The lease4-wipe command is deprecated and it will be removed in the future.

## 20.29 LEASE\_CMDS\_WIPE4\_FAILED

```
lease4-wipe command failed (parameters: %1, reason: %2)
```

The lease4-wipe command has failed. Both the reason as well as the parameters passed are logged.

## 20.30 LEASE\_CMDS\_WIPE6

```
lease6-wipe command successful (parameters: %1)
```

The lease6-wipe command has been successful. Parameters of the command are logged.

## 20.31 LEASE\_CMDS\_WIPE6\_DEPRECATED

```
lease6-wipe command is deprecated and it will be removed in the future.
```

The lease6-wipe command is deprecated and it will be removed in the future.



## 21.1 LFC\_FAIL\_PID\_CREATE

: %1

This message is issued if LFC detected a failure when trying to create the PID file. It includes a more specific error string.

## 21.2 LFC\_FAIL\_PID\_DEL

: %1

This message is issued if LFC detected a failure when trying to delete the PID file. It includes a more specific error string.

## 21.3 LFC\_FAIL\_PROCESS

: %1

This message is issued if LFC detected a failure when trying to process the files. It includes a more specific error string.

## 21.4 LFC\_FAIL\_ROTATE

: %1

This message is issued if LFC detected a failure when trying to rotate the files. It includes a more specific error string.

## 21.5 LFC\_PROCESSING

```
Previous file: %1, copy file: %2
```

This message is issued just before LFC starts processing the lease files.

## 21.6 LFC\_READ\_STATS

```
Leases: %1, attempts: %2, errors: %3.
```

This message prints out the number of leases that were read, the number of attempts to read leases and the number of errors encountered while reading.

## 21.7 LFC\_ROTATING

```
LFC rotating files
```

This message is issued just before LFC starts rotating the lease files - removing the old and replacing them with the new.

## 21.8 LFC\_RUNNING

```
LFC instance already running
```

This message is issued if LFC detects that a previous copy of LFC may still be running via the PID check.

## 21.9 LFC\_START

```
Starting lease file cleanup
```

This message is issued as the LFC process starts.

## 21.10 LFC\_TERMINATE

```
LFC finished processing
```

This message is issued when the LFC process completes. It does not indicate that the process was successful only that it has finished.

## 22.1 LOGIMPL\_ABOVE\_MAX\_DEBUG

```
debug level of %1 is too high and will be set to the maximum of %2
```

A message from the interface to the underlying logger implementation reporting that the debug level (as set by an internally-created string `DEBUGn`, where `n` is an integer, e.g. `DEBUG22`) is above the maximum allowed value and has been reduced to that value. The appearance of this message may indicate a programming error - please submit a bug report.

## 22.2 LOGIMPL\_BAD\_DEBUG\_STRING

```
debug string '%1' has invalid format
```

A message from the interface to the underlying logger implementation reporting that an internally-created string used to set the debug level is not of the correct format (it should be of the form `DEBUGn`, where `n` is an integer, e.g. `DEBUG22`). The appearance of this message indicates a programming error - please submit a bug report.



## 23.1 LOG\_BAD\_DESTINATION

```
unrecognized log destination: %1
```

This error message is printed when a logger destination value was given that was not recognized. The destination should be one of "console", "file", or "syslog".

## 23.2 LOG\_BAD\_SEVERITY

```
unrecognized log severity: %1
```

This error message is printed when a logger severity value was given that was not recognized. The severity should be one of "DEBUG", "INFO", "WARN", "ERROR", "FATAL" or "NONE".

## 23.3 LOG\_BAD\_STREAM

```
bad log console output stream: %1
```

Logging has been configured so that output is written to the terminal (console) but the stream on which it is to be written is not recognized. Allowed values are "stdout" and "stderr".

## 23.4 LOG\_DUPLICATE\_MESSAGE\_ID

```
duplicate message ID (%1) in compiled code
```

During start-up, Kea detected that the given message identification had been defined multiple times in the Kea code. This indicates a programming error; please submit a bug report.

## 23.5 LOG\_DUPLICATE\_NAMESPACE

```
line %1: duplicate $NAMESPACE directive found
```

When reading a message file, more than one \$NAMESPACE directive was found. (This directive is used to set a C++ namespace when generating header files during software development.) Such a condition is regarded as an error and the read will be abandoned.

## 23.6 LOG\_INPUT\_OPEN\_FAIL

```
unable to open message file %1 for input: %2
```

The program was not able to open the specified input message file for the reason given.

## 23.7 LOG\_INVALID\_MESSAGE\_ID

```
line %1: invalid message identification '%2'
```

An invalid message identification (ID) has been found during the read of a message file. Message IDs should comprise only alphanumeric characters and the underscore, and should not start with a digit.

## 23.8 LOG\_NAMESPACE\_EXTRA\_ARGS

```
line %1: $NAMESPACE directive has too many arguments
```

The \$NAMESPACE directive in a message file takes a single argument, a namespace in which all the generated symbol names are placed. This error is generated when the compiler finds a \$NAMESPACE directive with more than one argument.

## 23.9 LOG\_NAMESPACE\_INVALID\_ARG

```
line %1: $NAMESPACE directive has an invalid argument ('%2')
```

The \$NAMESPACE argument in a message file should be a valid C++ namespace. This message is output if the simple check on the syntax of the string carried out by the reader fails.

## 23.10 LOG\_NAMESPACE\_NO\_ARGS

```
line %1: no arguments were given to the $NAMESPACE directive
```

The `$NAMESPACE` directive in a message file takes a single argument, a C++ namespace in which all the generated symbol names are placed. This error is generated when the compiler finds a `$NAMESPACE` directive with no arguments.

## 23.11 LOG\_NO\_MESSAGE\_ID

```
line %1: message definition line found without a message ID
```

Within a message file, message are defined by lines starting with a `"%"`. The rest of the line should comprise the message ID and text describing the message. This error indicates the message compiler found a line in the message file comprising just the `"%"` and nothing else.

## 23.12 LOG\_NO\_MESSAGE\_TEXT

```
line %1: line found containing a message ID ('%2') and no text
```

Within a message file, message are defined by lines starting with a `"%"`. The rest of the line should comprise the message ID and text describing the message. This error indicates the message compiler found a line in the message file comprising just the `"%"` and message identification, but no text.

## 23.13 LOG\_NO\_SUCH\_MESSAGE

```
could not replace message text for '%1': no such message
```

During start-up a local message file was read. A line with the listed message identification was found in the file, but the identification is not one contained in the compiled-in message dictionary. This message may appear a number of times in the file, once for every such unknown message identification. There are several reasons why this message may appear: - The message ID has been misspelled in the local message file. - The program outputting the message may not use that particular message (e.g. it originates in a module not used by the program). - The local file was written for an earlier version of the Kea software and the later version no longer generates that message. Whatever the reason, there is no impact on the operation of Kea.

## 23.14 LOG\_OPEN\_OUTPUT\_FAIL

```
unable to open %1 for output: %2
```

Originating within the logging code, the program was not able to open the specified output file for the reason given.

## 23.15 LOG\_PREFIX\_EXTRA\_ARGS

```
line %1: $PREFIX directive has too many arguments
```

Within a message file, the \$PREFIX directive takes a single argument, a prefix to be added to the symbol names when a C++ file is created. This error is generated when the compiler finds a \$PREFIX directive with more than one argument. Note: the \$PREFIX directive is deprecated and will be removed in a future version of Kea.

## 23.16 LOG\_PREFIX\_INVALID\_ARG

```
line %1: $PREFIX directive has an invalid argument ('%2')
```

Within a message file, the \$PREFIX directive takes a single argument, a prefix to be added to the symbol names when a C++ file is created. As such, it must adhere to restrictions on C++ symbol names (e.g. may only contain alphanumeric characters or underscores, and may not start with a digit). A \$PREFIX directive was found with an argument (given in the message) that violates those restrictions. Note: the \$PREFIX directive is deprecated and will be removed in a future version of Kea.

## 23.17 LOG\_READING\_LOCAL\_FILE

```
reading local message file %1
```

This is an informational message output by Kea when it starts to read a local message file. (A local message file may replace the text of one or more messages; the ID of the message will not be changed though.)

## 23.18 LOG\_READ\_ERROR

```
error reading from message file %1: %2
```

The specified error was encountered reading from the named message file.

## 23.19 LOG\_UNRECOGNIZED\_DIRECTIVE

```
line %1: unrecognized directive '%2'
```

Within a message file, a line starting with a dollar symbol was found (indicating the presence of a directive) but the first word on the line (shown in the message) was not recognized.



## 24.1 MT\_TCP\_LISTENER\_MGR\_STARTED

```
MtTcpListenerMgr started with %1 threads, listening on %2:%3, use TLS: %4
```

Logged at debug log level 40. This debug messages is issued when an MtTcpListenerMgr has been started to accept connections. Arguments detail the number of threads that the listener is using, the address and port at which it is listening, and if TLS is used or not.

## 24.2 MT\_TCP\_LISTENER\_MGR\_STOPPED

```
MtTcpListenerMgr for %1:%2 stopped.
```

Logged at debug log level 40. This debug messages is issued when the MtTcpListenerMgr, listening at the given address and port, has completed shutdown.

## 24.3 MT\_TCP\_LISTENER\_MGR\_STOPPING

```
Stopping MtTcpListenerMgr for %1:%2
```

Logged at debug log level 40. This debug messages is issued when the MtTcpListenerMgr, listening at the given address and port, has begun to shutdown.



**MYSQL**

### 25.1 MYSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION4

```
create or update option pool start: %1 pool end: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

### 25.2 MYSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION6

```
create or update option pool start: %1 pool end: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

### 25.3 MYSQL\_CB\_CREATE\_UPDATE\_BY\_PREFIX\_OPTION6

```
create or update option prefix: %1 prefix len: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by prefix

### 25.4 MYSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION4

```
create or update option by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

## 25.5 MYSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION6

```
create or update option by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

## 25.6 MYSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS4

```
create or update client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

## 25.7 MYSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS6

```
create or update client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

## 25.8 MYSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER4

```
create or update global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

## 25.9 MYSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER6

```
create or update global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

## 25.10 MYSQL\_CB\_CREATE\_UPDATE\_OPTION4

```
create or update option
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

## 25.11 MYSQL\_CB\_CREATE\_UPDATE\_OPTION6

create or update option

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

## 25.12 MYSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF4

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

## 25.13 MYSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF6

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

## 25.14 MYSQL\_CB\_CREATE\_UPDATE\_SERVER4

create or update server: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv4 server information.

## 25.15 MYSQL\_CB\_CREATE\_UPDATE\_SERVER6

create or update server: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv6 server information.

## 25.16 MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK4

create or update shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

## 25.17 MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK6

```
create or update shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

## 25.18 MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION4

```
create or update shared network: %1 option
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

## 25.19 MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION6

```
create or update shared network: %1 option
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

## 25.20 MYSQL\_CB\_CREATE\_UPDATE\_SUBNET4

```
create or update subnet: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

## 25.21 MYSQL\_CB\_CREATE\_UPDATE\_SUBNET6

```
create or update subnet: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

## 25.22 MYSQL\_CB\_DEINIT\_OK

```
unloading MYSQL CB hooks library successful
```

This informational message indicates that the MySQL Configuration Backend hooks library has been unloaded successfully.

## 25.23 MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4

```
delete all client classes
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

## 25.24 MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

## 25.25 MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6

```
delete all client classes
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

## 25.26 MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

## 25.27 MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4

```
delete all global parameters
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

## 25.28 MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

## 25.29 MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6

```
delete all global parameters
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

## 25.30 MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

## 25.31 MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4

```
delete all option definitions
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

## 25.32 MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

## 25.33 MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6

```
delete all option definitions
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

## 25.34 MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions



## 25.35 MYSQL\_CB\_DELETE\_ALL\_SERVERS4

```
delete all DHCPv4 servers
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

## 25.36 MYSQL\_CB\_DELETE\_ALL\_SERVERS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

## 25.37 MYSQL\_CB\_DELETE\_ALL\_SERVERS6

```
delete all DHCPv6 servers
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

## 25.38 MYSQL\_CB\_DELETE\_ALL\_SERVERS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

## 25.39 MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4

```
delete all shared networks
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

## 25.40 MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

## 25.41 MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6

```
delete all shared networks
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

## 25.42 MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

## 25.43 MYSQL\_CB\_DELETE\_ALL\_SUBNETS4

```
delete all subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

## 25.44 MYSQL\_CB\_DELETE\_ALL\_SUBNETS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

## 25.45 MYSQL\_CB\_DELETE\_ALL\_SUBNETS6

```
delete all subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

## 25.46 MYSQL\_CB\_DELETE\_ALL\_SUBNETS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

## 25.47 MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION4

```
delete pool start: %1 pool end: %2 option code: %3 space: %4
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

## 25.48 MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

## 25.49 MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION6

```
delete pool start: %1 pool end: %2 option code: %3 space: %4
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

## 25.50 MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

## 25.51 MYSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6

```
delete prefix: %1 prefix len: %2 option code: %3 space: %4
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by prefix

## 25.52 MYSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by prefix

## 25.53 MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4

```
delete subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

## 25.54 MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

## 25.55 MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6

```
delete subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

## 25.56 MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

## 25.57 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4

```
delete by subnet id: %1 option code: %2 space: %3
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

## 25.58 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

## 25.59 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6

```
delete by subnet id: %1 option code: %2 space: %3
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

## 25.60 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

## 25.61 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4

```
delete subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

## 25.62 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

## 25.63 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6

```
delete subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

## 25.64 MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

## 25.65 MYSQL\_CB\_DELETE\_CLIENT\_CLASS4

```
delete client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

## 25.66 MYSQL\_CB\_DELETE\_CLIENT\_CLASS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

## 25.67 MYSQL\_CB\_DELETE\_CLIENT\_CLASS6

```
delete client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

## 25.68 MYSQL\_CB\_DELETE\_CLIENT\_CLASS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

## 25.69 MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4

```
delete global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

## 25.70 MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

## 25.71 MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6

```
delete global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

## 25.72 MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

## 25.73 MYSQL\_CB\_DELETE\_OPTION4

```
delete option code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option

## 25.74 MYSQL\_CB\_DELETE\_OPTION4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option

## 25.75 MYSQL\_CB\_DELETE\_OPTION6

```
delete option code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option

## 25.76 MYSQL\_CB\_DELETE\_OPTION6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option

## 25.77 MYSQL\_CB\_DELETE\_OPTION\_DEF4

```
delete option definition code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

## 25.78 MYSQL\_CB\_DELETE\_OPTION\_DEF4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

## 25.79 MYSQL\_CB\_DELETE\_OPTION\_DEF6

```
delete option definition code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

## 25.80 MYSQL\_CB\_DELETE\_OPTION\_DEF6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

## 25.81 MYSQL\_CB\_DELETE\_SERVER4

```
delete DHCPv4 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

## 25.82 MYSQL\_CB\_DELETE\_SERVER4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.



## 25.83 MYSQL\_CB\_DELETE\_SERVER6

```
delete DHCPv6 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

## 25.84 MYSQL\_CB\_DELETE\_SERVER6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

## 25.85 MYSQL\_CB\_DELETE\_SHARED\_NETWORK4

```
delete shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

## 25.86 MYSQL\_CB\_DELETE\_SHARED\_NETWORK4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

## 25.87 MYSQL\_CB\_DELETE\_SHARED\_NETWORK6

```
delete shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

## 25.88 MYSQL\_CB\_DELETE\_SHARED\_NETWORK6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

## 25.89 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4

```
delete shared network: %1 option code: %2 space: %3
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

## 25.90 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

## 25.91 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6

```
delete shared network: %1 option code: %2 space: %3
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

## 25.92 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

## 25.93 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4

```
delete shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

## 25.94 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

## 25.95 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6

```
delete shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

## 25.96 MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

## 25.97 MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4

```
retrieving all client classes
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

## 25.98 MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

## 25.99 MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6

```
retrieving all client classes
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

## 25.100 MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

## 25.101 MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4

```
retrieving all global parameters
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

## 25.102 MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

## 25.103 MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6

```
retrieving all global parameters
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

## 25.104 MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

## 25.105 MYSQL\_CB\_GET\_ALL\_OPTIONS4

```
retrieving all options
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

## 25.106 MYSQL\_CB\_GET\_ALL\_OPTIONS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

## 25.107 MYSQL\_CB\_GET\_ALL\_OPTIONS6

```
retrieving all options
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

## 25.108 MYSQL\_CB\_GET\_ALL\_OPTIONS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

## 25.109 MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS4

```
retrieving all option definitions
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

## 25.110 MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

## 25.111 MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS6

```
retrieving all option definitions
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

## 25.112 MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

## 25.113 MYSQL\_CB\_GET\_ALL\_SERVERS4

```
retrieving all servers
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv4 servers

## 25.114 MYSQL\_CB\_GET\_ALL\_SERVERS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv4 servers

## 25.115 MYSQL\_CB\_GET\_ALL\_SERVERS6

```
retrieving all DHCPv6 servers
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv6 servers

## 25.116 MYSQL\_CB\_GET\_ALL\_SERVERS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv6 servers

## 25.117 MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4

```
retrieving all shared networks
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

## 25.118 MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

## 25.119 MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6

```
retrieving all shared networks
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

## 25.120 MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

## 25.121 MYSQL\_CB\_GET\_ALL\_SUBNETS4

```
retrieving all subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

## 25.122 MYSQL\_CB\_GET\_ALL\_SUBNETS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

## 25.123 MYSQL\_CB\_GET\_ALL\_SUBNETS6

```
retrieving all subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

## 25.124 MYSQL\_CB\_GET\_ALL\_SUBNETS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

## 25.125 MYSQL\_CB\_GET\_CLIENT\_CLASS4

```
retrieving client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

## 25.126 MYSQL\_CB\_GET\_CLIENT\_CLASS6

```
retrieving client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

## 25.127 MYSQL\_CB\_GET\_GLOBAL\_PARAMETER4

```
retrieving global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

## 25.128 MYSQL\_CB\_GET\_GLOBAL\_PARAMETER6

```
retrieving global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

## 25.129 MYSQL\_CB\_GET\_HOST4

```
get host
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

## 25.130 MYSQL\_CB\_GET\_HOST6

```
get host
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host



## 25.131 MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4

```
retrieving modified client classes from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

## 25.132 MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

## 25.133 MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6

```
retrieving modified client classes from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

## 25.134 MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

## 25.135 MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4

```
retrieving modified global parameters from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

## 25.136 MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

## 25.137 MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6

```
retrieving modified global parameters from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

## 25.138 MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

## 25.139 MYSQL\_CB\_GET\_MODIFIED\_OPTIONS4

```
retrieving modified options from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

## 25.140 MYSQL\_CB\_GET\_MODIFIED\_OPTIONS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

## 25.141 MYSQL\_CB\_GET\_MODIFIED\_OPTIONS6

```
retrieving modified options from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

## 25.142 MYSQL\_CB\_GET\_MODIFIED\_OPTIONS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

## 25.143 MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4

```
retrieving modified option definitions from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

## 25.144 MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

## 25.145 MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6

```
retrieving modified option definitions from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

## 25.146 MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

## 25.147 MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4

```
retrieving modified shared networks from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

## 25.148 MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

## 25.149 MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6

```
retrieving modified shared networks from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

## 25.150 MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

## 25.151 MYSQL\_CB\_GET\_MODIFIED\_SUBNETS4

```
retrieving modified subnets from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

## 25.152 MYSQL\_CB\_GET\_MODIFIED\_SUBNETS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

## 25.153 MYSQL\_CB\_GET\_MODIFIED\_SUBNETS6

```
retrieving modified subnets from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

## 25.154 MYSQL\_CB\_GET\_MODIFIED\_SUBNETS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

## 25.155 MYSQL\_CB\_GET\_OPTION4

```
retrieving option code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

## 25.156 MYSQL\_CB\_GET\_OPTION6

```
retrieving option code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

## 25.157 MYSQL\_CB\_GET\_OPTION\_DEF4

```
retrieving option definition code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

## 25.158 MYSQL\_CB\_GET\_OPTION\_DEF6

```
retrieving option definition code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

## 25.159 MYSQL\_CB\_GET\_PORT4

```
get port
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

## 25.160 MYSQL\_CB\_GET\_PORT6

```
get port
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

## 25.161 MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4

```
retrieving audit entries from: %1 %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id.

## 25.162 MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

## 25.163 MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6

```
retrieving audit entries from: %1 %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id

## 25.164 MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

## 25.165 MYSQL\_CB\_GET\_SERVER4

```
retrieving DHCPv4 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv4 server information.

## 25.166 MYSQL\_CB\_GET\_SERVER6

```
retrieving DHCPv6 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv6 server information.

## 25.167 MYSQL\_CB\_GET\_SHARED\_NETWORK4

```
retrieving shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

## 25.168 MYSQL\_CB\_GET\_SHARED\_NETWORK6

```
retrieving shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

## 25.169 MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4

```
retrieving shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

## 25.170 MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

## 25.171 MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6

```
retrieving shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

## 25.172 MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

## 25.173 MYSQL\_CB\_GET\_SUBNET4\_BY\_PREFIX

```
retrieving subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

## 25.174 MYSQL\_CB\_GET\_SUBNET4\_BY\_SUBNET\_ID

```
retrieving subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

## 25.175 MYSQL\_CB\_GET\_SUBNET6\_BY\_PREFIX

```
retrieving subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

## 25.176 MYSQL\_CB\_GET\_SUBNET6\_BY\_SUBNET\_ID

```
retrieving subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

## 25.177 MYSQL\_CB\_GET\_TYPE4

```
get type
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

## 25.178 MYSQL\_CB\_GET\_TYPE6

```
get type
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type



## 25.179 MYSQL\_CB\_INIT\_OK

```
loading MYSQL CB hooks library successful
```

This informational message indicates that the MySQL Configuration Backend hooks library has been loaded successfully. Enjoy!

## 25.180 MYSQL\_CB\_NO\_TLS

```
TLS was required but is not used
```

This error message is issued when TLS for the connection was required but TLS is not used.

## 25.181 MYSQL\_CB\_RECONNECT\_ATTEMPT\_FAILED4

```
database reconnect failed: %1
```

Error message issued when an attempt to reconnect has failed.

## 25.182 MYSQL\_CB\_RECONNECT\_ATTEMPT\_FAILED6

```
database reconnect failed: %1
```

Error message issued when an attempt to reconnect has failed.

## 25.183 MYSQL\_CB\_RECONNECT\_ATTEMPT\_SCHEDULE4

```
scheduling attempt %1 of %2 in %3 milliseconds
```

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

## 25.184 MYSQL\_CB\_RECONNECT\_ATTEMPT\_SCHEDULE6

```
scheduling attempt %1 of %2 in %3 milliseconds
```

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

## 25.185 MYSQL\_CB\_RECONNECT\_FAILED4

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 25.186 MYSQL\_CB\_RECONNECT\_FAILED6

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 25.187 MYSQL\_CB\_REGISTER\_BACKEND\_TYPE4

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

## 25.188 MYSQL\_CB\_REGISTER\_BACKEND\_TYPE6

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

## 25.189 MYSQL\_CB\_TLS\_CIPHER

TLS cipher: %1

Logged at debug log level 40. A debug message issued when a new MySQL connected is created with TLS. The TLS cipher name is logged.

## 25.190 MYSQL\_CB\_UNREGISTER\_BACKEND\_TYPE4

unregister backend

Logged at debug log level 40. Debug message issued when triggered an action to unregister backend

## 26.1 NETCONF\_BOOT\_UPDATE\_COMPLETED

```
Boot-update configuration completed for server %1
```

This informational message is issued when the initial configuration was retrieved using NETCONF and successfully applied to Kea server.

## 26.2 NETCONF\_CONFIG\_CHANGED\_DETAIL

```
YANG configuration changed: %1
```

Logged at debug log level 55. This debug message indicates a YANG configuration change. The format is the change operation (created, modified, deleted or moved) followed by xpaths and values of old and new nodes.

## 26.3 NETCONF\_CONFIG\_CHANGE\_EVENT

```
Received YANG configuration change %1 event
```

This informational message is issued when kea-netconf receives a YANG configuration change event. The type of event is printed.

## 26.4 NETCONF\_CONFIG\_CHECK\_FAIL

```
NETCONF configuration check failed: %1
```

This error message indicates that kea-netconf had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

## 26.5 NETCONF\_CONFIG\_FAIL

```
NETCONF configuration failed: %1
```

This error message indicates that kea-netconf had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

## 26.6 NETCONF\_CONFIG\_SYNTAX\_WARNING

```
NETCONF configuration syntax warning: %1
```

This warning message indicates that the NETCONF configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

## 26.7 NETCONF\_FAILED

```
application experienced a fatal error: %1
```

This is a fatal error message issued when kea-netconf got an unrecoverable error from within the event loop.

## 26.8 NETCONF\_GET\_CONFIG

```
got configuration from %1 server: %2
```

Logged at debug log level 55. This debug message indicates that kea-netconf got the configuration from a Kea server. The server name and the retrieved configuration are printed.

## 26.9 NETCONF\_GET\_CONFIG\_FAILED

```
getting configuration from %1 server failed: %2
```

The error message indicates that kea-netconf got an error getting the configuration from a Kea server. Make sure that the server is up and running, has appropriate control socket defined and that the controls socket configuration on the server matches that of kea-netconf. The name of the server and the error are printed.

## 26.10 NETCONF\_GET\_CONFIG\_STARTED

```
getting configuration from %1 server
```

This informational message indicates that kea-netconf is trying to get the configuration from a Kea server.

## 26.11 NETCONF\_MODULE\_CHANGE\_INTERNAL\_ERROR

```
an internal error occurred while processing changes for module %1: %2
```

The error message indicates that kea-netconf got an error while sysrepo was processing modules changes. This usually follows a config validation failure, and can be recovered from. The name of the module and the internal error message are printed.

## 26.12 NETCONF\_MODULE\_MISSING\_ERR

```
Missing essential module %1 in sysrepo
```

This fatal error message indicates that a module required by Netconf configuration is not available in the sysrepo repository. The name of the module is printed.

## 26.13 NETCONF\_MODULE\_MISSING\_WARN

```
Missing module %1 in sysrepo
```

This warning message indicates that a module used by Kea is not available in the sysrepo repository. The name of the module is printed.

## 26.14 NETCONF\_MODULE\_REVISION\_ERR

```
Essential module %1 does NOT have the right revision: expected %2, got %3
```

This fatal error message indicates that a module required by Netconf configuration is not at the right revision in the sysrepo repository. The name, expected and available revisions of the module are printed.

## 26.15 NETCONF\_MODULE\_REVISION\_WARN

```
Module %1 does NOT have the right revision: expected %2, got %3
```

This warning message indicates that a module used by Kea is not at the right revision in the sysrepo repository. The name, expected and available revisions of the module are printed.

## 26.16 NETCONF\_NOTIFICATION\_INTERNAL\_ERROR

```
an internal error occurred while sending an event notification for module %1: %2
```

The error message indicates that kea-netconf got an error while sysrepo was sending an event notification. This error is not fatal and can be recovered from. The name of the module and the internal error message are printed.

## 26.17 NETCONF\_NOTIFICATION\_RECEIVED

```
Received notification of type %1 for module %2: '%3'
```

This informational message logs any YANG notification that has been signaled by the server, sent to kea-netconf which then was forwarded to subscribed clients. To achieve this, kea-netconf subscribes itself as a client to all notifications for the configured module.

## 26.18 NETCONF\_NOT\_SUBSCRIBED\_TO\_NOTIFICATIONS

```
subscribing to notifications for %1 server with %2 module failed: %3
```

The warning message indicates that kea-netconf got an error subscribing to notifications for a Kea server. The most probable cause is probably that the model that kea-netconf subscribed to does not have any notification nodes, but there may be other more unexpected causes as well. The server name, module name and the error are printed.

## 26.19 NETCONF\_RUN\_EXIT

```
application is exiting the event loop
```

Logged at debug log level 0. This is a debug message issued when kea-netconf exits its event loop. This is a normal step during kea-netconf shutdown.

## 26.20 NETCONF\_SET\_CONFIG

```
set configuration to %1 server: %2
```

Logged at debug log level 55. This debug message indicates that kea-netconf set the configuration to a Kea server. The server name and the applied configuration are printed.

## 26.21 NETCONF\_SET\_CONFIG\_FAILED

```
setting configuration to %1 server failed: %2
```

The error message indicates that kea-netconf got an error setting the configuration to a Kea server. Make sure that the server is up and running, has appropriate control socket defined and that the controls socket configuration on the server matches that of kea-netconf. The name of the server and the error are printed.

## 26.22 NETCONF\_SET\_CONFIG\_STARTED

```
setting configuration to %1 server
```

This informational message indicates that kea-netconf is trying to set the configuration to a Kea server.

## 26.23 NETCONF\_STARTED

```
kea-netconf (version %1) started
```

This informational message indicates that kea-netconf has processed all configuration information and is ready to begin processing. The version is also printed.

## 26.24 NETCONF\_SUBSCRIBE\_CONFIG

```
subscribing configuration changes for %1 server with %2 module
```

This information message indicates that kea-netconf is trying to subscribe configuration changes for a Kea server. The names of the server and the module are printed.

## 26.25 NETCONF\_SUBSCRIBE\_CONFIG\_FAILED

```
subscribe configuration changes for %1 server with %2 module failed: %3
```

The error message indicates that kea-netconf got an error subscribing configuration changes for a Kea server. The names of the server and the module, and the error are printed.

## 26.26 NETCONF\_SUBSCRIBE\_NOTIFICATIONS

```
subscribing to notifications for %1 server with %2 module
```

This information message indicates that kea-netconf is trying to subscribe to notifications for a Kea server. The server name and module name are printed.

## 26.27 NETCONF\_UPDATE\_CONFIG

```
updating configuration with %1 server: %2
```

Logged at debug log level 55. This debug message indicates that kea-netconf update the configuration of a Kea server. The server name and the updated configuration are printed.

## 26.28 NETCONF\_UPDATE\_CONFIG\_COMPLETED

```
completed updating configuration for %1 server
```

This informational message indicates that kea-netconf updated with success the configuration of a Kea server.

## 26.29 NETCONF\_UPDATE\_CONFIG\_FAILED

```
updating configuration with %1 server: %2
```

The error message indicates that kea-netconf got an error updating the configuration of a Kea server. This includes a configuration rejected by a Kea server when it tried to apply it. The name of the server and the error are printed.

## 26.30 NETCONF\_UPDATE\_CONFIG\_STARTED

```
started updating configuration for %1 server
```

This informational message indicates that kea-netconf is trying to update the configuration of a Kea server.

## 26.31 NETCONF\_VALIDATE\_CONFIG

```
validating configuration with %1 server: %2
```

Logged at debug log level 55. This debug message indicates that kea-netconf is validating the configuration with a Kea server. The server name and the validated configuration are printed.

## 26.32 NETCONF\_VALIDATE\_CONFIG\_COMPLETED

```
completed validating configuration for %1 server
```

This informational message indicates that kea-netconf validated with success the configuration with a Kea server.



## 26.33 NETCONF\_VALIDATE\_CONFIG\_FAILED

```
validating configuration with %1 server got an error: %2
```

The error message indicates that kea-netconf got an error validating the configuration with a Kea server. This message is produced when exception is thrown during an attempt to validate received configuration. Additional explanation may be provided as a parameter. You may also take a look at earlier log messages. The name of the server and the error are printed.

## 26.34 NETCONF\_VALIDATE\_CONFIG\_REJECTED

```
validating configuration with %1 server was rejected: %2
```

The warning message indicates that kea-netconf got an error validating the configuration with a Kea server. This message is printed when the configuration was rejected during normal processing. Additional explanation may be provided as a parameter. You may also take a look at earlier log messages. The name of the server and the error are printed.



## 27.1 PERFMON\_ALARM\_CLEARED

```
Alarm for %1 has been cleared, reported mean duration %2 is now below low-water-ms: %3
```

This info message is emitted when the reported mean duration for an alarm that has been triggered has fallen below the value of its low-water-ms parameter. The arguments detail the alarm's key and the most recently reported mean.

## 27.2 PERFMON\_ALARM\_TRIGGERED

```
Alarm for %1 has been triggered since %2, reported mean duration %3 exceeds high-water-  
ms: %4
```

This warning message is emitted when the reported mean duration for an alarm exceeds its high-water-ms value. As long as the reported averages remain above the low-water-ms value, the alarm will remain triggered and this message will be repeated every alarm-report-secs. Arguments detail the alarm's key, the time the alarm was first triggered, the most recent reported mean, and the high-water-ms value.

## 27.3 PERFMON\_CMDS\_CONTROL\_ERROR

```
perfmon-control command processing failed: %1
```

This error message is issued when the PerfMon hook library encounters an error processing a perfmon-control command. The argument explains the command error.

## 27.4 PERFMON\_CMDS\_CONTROL\_OK

```
perfmon-control command success: active monitoring: %1, stats-mgr-reporting: %2
```

This info log is issued when perfmon-control command has successfully enabled/disabled active monitoring and/or statistics mgr reporting. Arguments reflect the current state of both.

## 27.5 PERFMON\_CMDS\_GET\_ALL\_DURATIONS\_ERROR

```
perfmon-get-all-durations command processing failed: %1
```

This error message is issued when the PerfMon hook library encounters an error processing a perfmon-get-all-durations command. The argument explains the command error.

## 27.6 PERFMON\_CMDS\_GET\_ALL\_DURATIONS\_OK

```
perfmon-get-all-durations returning %1 durations
```

This info log is issued when perfmon-get-all-durations command has completed successfully. The argument contains the number of durations returned.

## 27.7 PERFMON\_DEINIT\_OK

```
unloading PerfMon hooks library successful
```

This info message indicates that the PerfMon hooks library has been removed successfully.

## 27.8 PERFMON\_DHCP4\_PKT\_EVENTS

```
query: %1 events=[%2]
```

Logged at debug log level 50. This debug message is emitted after an inbound DHCPv4 query has been processed, the arguments are the query label and the dump of the query's packet event stack.

## 27.9 PERFMON\_DHCP4\_PKT\_PROCESS\_ERROR

```
Packet event stack was not processed for query %1, reason %2
```

Logged at debug log level 50. This debug message is emitted when the query's event stack could not be processed. This is most likely a programmatic error and should be reported. The arguments identify the query and the reason it could not be processed. These errors should not affect server's normal operations.

## 27.10 PERFMON\_DHCP4\_SOCKET\_RECEIVED\_TIME\_SUPPORT

```
Kernel supports socket received time? %1
```

Logged at debug log level 40. This debug message is emitted after a (re)configuration and indicates whether or not the packet filter being used by kea-dhcp4 can supply the timestamp a packet was received by the kernel for recording SOCKET\_RECEIVED events. If it does not, perfmon will still function but will not have data available to determine kernel buffer wait times.

## 27.11 PERFMON\_DHCP6\_PKT\_EVENTS

```
query: %1 events=[%2]
```

Logged at debug log level 50. The debug message is emitted after an inbound DHCPv6 query has been processed, the arguments are the query label and the dump of the query's packet event stack.

## 27.12 PERFMON\_DHCP6\_PKT\_PROCESS\_ERROR

```
Packet event stack was not processed for query %1, reason %2
```

Logged at debug log level 50. This debug message is emitted when the query's event stack could not be processed. This is most likely a programmatic error and should be reported. The arguments identify the query and the reason it could not be processed. These errors should not affect server's normal operations.

## 27.13 PERFMON\_DHCP6\_SOCKET\_RECEIVED\_TIME\_SUPPORT

```
Kernel supports socket received time? %1
```

Logged at debug log level 40. This debug message is emitted after a (re)configuration and indicates whether or not the packet filter being used by kea-dhcp6 can supply the timestamp a packet was received by the kernel for recording SOCKET\_RECEIVED events. If it does not, perfmon will still function but will not have data available to determine kernel buffer wait times.

## 27.14 PERFMON\_INIT\_FAILED

```
loading PerfMon hooks library failed: %1
```

This error message indicates an error during loading the PerfMon hooks library. The details of the error are provided as argument of the log message.



## 28.1 PGSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION4

```
create or update option pool start: %1 pool end: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

## 28.2 PGSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION6

```
create or update option pool start: %1 pool end: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

## 28.3 PGSQL\_CB\_CREATE\_UPDATE\_BY\_PREFIX\_OPTION6

```
create or update option prefix: %1 prefix len: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by prefix

## 28.4 PGSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION4

```
create or update option by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

## 28.5 PGSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION6

```
create or update option by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

## 28.6 PGSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS4

```
create or update client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

## 28.7 PGSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS6

```
create or update client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

## 28.8 PGSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER4

```
create or update global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

## 28.9 PGSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER6

```
create or update global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

## 28.10 PGSQL\_CB\_CREATE\_UPDATE\_OPTION4

```
create or update option
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update option



## 28.11 PGSQL\_CB\_CREATE\_UPDATE\_OPTION6

create or update option

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

## 28.12 PGSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF4

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

## 28.13 PGSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF6

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

## 28.14 PGSQL\_CB\_CREATE\_UPDATE\_SERVER4

create or update server: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv4 server information.

## 28.15 PGSQL\_CB\_CREATE\_UPDATE\_SERVER6

create or update server: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv6 server information.

## 28.16 PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK4

create or update shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

## 28.17 PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK6

```
create or update shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

## 28.18 PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION4

```
create or update shared network: %1 option
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

## 28.19 PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION6

```
create or update shared network: %1 option
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

## 28.20 PGSQL\_CB\_CREATE\_UPDATE\_SUBNET4

```
create or update subnet: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

## 28.21 PGSQL\_CB\_CREATE\_UPDATE\_SUBNET6

```
create or update subnet: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

## 28.22 PGSQL\_CB\_DEINIT\_OK

```
unloading Postgres CB hooks library successful
```

This informational message indicates that the Postgres Configuration Backend hooks library has been unloaded successfully.

## 28.23 PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4

```
delete all client classes
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

## 28.24 PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

## 28.25 PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6

```
delete all client classes
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

## 28.26 PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

## 28.27 PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4

```
delete all global parameters
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

## 28.28 PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

## 28.29 PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6

```
delete all global parameters
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

## 28.30 PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

## 28.31 PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4

```
delete all option definitions
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

## 28.32 PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

## 28.33 PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6

```
delete all option definitions
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

## 28.34 PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

## 28.35 PGSQL\_CB\_DELETE\_ALL\_SERVERS4

```
delete all DHCPv4 servers
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

## 28.36 PGSQL\_CB\_DELETE\_ALL\_SERVERS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

## 28.37 PGSQL\_CB\_DELETE\_ALL\_SERVERS6

```
delete all DHCPv6 servers
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

## 28.38 PGSQL\_CB\_DELETE\_ALL\_SERVERS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

## 28.39 PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4

```
delete all shared networks
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

## 28.40 PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

## 28.41 PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6

```
delete all shared networks
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

## 28.42 PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

## 28.43 PGSQL\_CB\_DELETE\_ALL\_SUBNETS4

```
delete all subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

## 28.44 PGSQL\_CB\_DELETE\_ALL\_SUBNETS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

## 28.45 PGSQL\_CB\_DELETE\_ALL\_SUBNETS6

```
delete all subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

## 28.46 PGSQL\_CB\_DELETE\_ALL\_SUBNETS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

## 28.47 PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION4

```
delete pool start: %1 pool end: %2 option code: %3 space: %4
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

## 28.48 PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

## 28.49 PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION6

```
delete pool start: %1 pool end: %2 option code: %3 space: %4
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

## 28.50 PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

## 28.51 PGSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6

```
delete prefix: %1 prefix len: %2 option code: %3 space: %4
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by prefix

## 28.52 PGSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by prefix

## 28.53 PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4

```
delete subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

## 28.54 PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

## 28.55 PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6

```
delete subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

## 28.56 PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

## 28.57 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4

```
delete by subnet id: %1 option code: %2 space: %3
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

## 28.58 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id



## 28.59 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6

```
delete by subnet id: %1 option code: %2 space: %3
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

## 28.60 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

## 28.61 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4

```
delete subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

## 28.62 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

## 28.63 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6

```
delete subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

## 28.64 PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

## 28.65 PGSQL\_CB\_DELETE\_CLIENT\_CLASS4

```
delete client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

## 28.66 PGSQL\_CB\_DELETE\_CLIENT\_CLASS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

## 28.67 PGSQL\_CB\_DELETE\_CLIENT\_CLASS6

```
delete client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

## 28.68 PGSQL\_CB\_DELETE\_CLIENT\_CLASS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

## 28.69 PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4

```
delete global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

## 28.70 PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

## 28.71 PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6

```
delete global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

## 28.72 PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

## 28.73 PGSQL\_CB\_DELETE\_OPTION4

```
delete option code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option

## 28.74 PGSQL\_CB\_DELETE\_OPTION4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option

## 28.75 PGSQL\_CB\_DELETE\_OPTION6

```
delete option code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option

## 28.76 PGSQL\_CB\_DELETE\_OPTION6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option

## 28.77 PGSQL\_CB\_DELETE\_OPTION\_DEF4

```
delete option definition code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

## 28.78 PGSQL\_CB\_DELETE\_OPTION\_DEF4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

## 28.79 PGSQL\_CB\_DELETE\_OPTION\_DEF6

```
delete option definition code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

## 28.80 PGSQL\_CB\_DELETE\_OPTION\_DEF6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

## 28.81 PGSQL\_CB\_DELETE\_SERVER4

```
delete DHCPv4 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

## 28.82 PGSQL\_CB\_DELETE\_SERVER4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

## 28.83 PGSQL\_CB\_DELETE\_SERVER6

```
delete DHCPv6 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

## 28.84 PGSQL\_CB\_DELETE\_SERVER6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

## 28.85 PGSQL\_CB\_DELETE\_SHARED\_NETWORK4

```
delete shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

## 28.86 PGSQL\_CB\_DELETE\_SHARED\_NETWORK4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

## 28.87 PGSQL\_CB\_DELETE\_SHARED\_NETWORK6

```
delete shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

## 28.88 PGSQL\_CB\_DELETE\_SHARED\_NETWORK6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

## 28.89 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4

```
delete shared network: %1 option code: %2 space: %3
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

## 28.90 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

## 28.91 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6

```
delete shared network: %1 option code: %2 space: %3
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

## 28.92 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

## 28.93 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4

```
delete shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

## 28.94 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

## 28.95 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6

```
delete shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

## 28.96 PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6\_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

## 28.97 PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4

```
retrieving all client classes
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

## 28.98 PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

## 28.99 PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6

```
retrieving all client classes
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

## 28.100 PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

## 28.101 PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4

```
retrieving all global parameters
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

## 28.102 PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

## 28.103 PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6

```
retrieving all global parameters
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

## 28.104 PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

## 28.105 PGSQL\_CB\_GET\_ALL\_OPTIONS4

```
retrieving all options
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

## 28.106 PGSQL\_CB\_GET\_ALL\_OPTIONS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options



## 28.107 PGSQL\_CB\_GET\_ALL\_OPTIONS6

```
retrieving all options
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

## 28.108 PGSQL\_CB\_GET\_ALL\_OPTIONS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

## 28.109 PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS4

```
retrieving all option definitions
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

## 28.110 PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

## 28.111 PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS6

```
retrieving all option definitions
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

## 28.112 PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

## 28.113 PGSQL\_CB\_GET\_ALL\_SERVERS4

```
retrieving all servers
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv4 servers

## 28.114 PGSQL\_CB\_GET\_ALL\_SERVERS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv4 servers

## 28.115 PGSQL\_CB\_GET\_ALL\_SERVERS6

```
retrieving all DHCPv6 servers
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv6 servers

## 28.116 PGSQL\_CB\_GET\_ALL\_SERVERS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv6 servers

## 28.117 PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4

```
retrieving all shared networks
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

## 28.118 PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

## 28.119 PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6

```
retrieving all shared networks
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

## 28.120 PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

## 28.121 PGSQL\_CB\_GET\_ALL\_SUBNETS4

```
retrieving all subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

## 28.122 PGSQL\_CB\_GET\_ALL\_SUBNETS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

## 28.123 PGSQL\_CB\_GET\_ALL\_SUBNETS6

```
retrieving all subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

## 28.124 PGSQL\_CB\_GET\_ALL\_SUBNETS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

## 28.125 PGSQL\_CB\_GET\_CLIENT\_CLASS4

```
retrieving client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

## 28.126 PGSQL\_CB\_GET\_CLIENT\_CLASS6

```
retrieving client class: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

## 28.127 PGSQL\_CB\_GET\_GLOBAL\_PARAMETER4

```
retrieving global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

## 28.128 PGSQL\_CB\_GET\_GLOBAL\_PARAMETER6

```
retrieving global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

## 28.129 PGSQL\_CB\_GET\_HOST4

```
get host
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

## 28.130 PGSQL\_CB\_GET\_HOST6

```
get host
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

## 28.131 PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4

retrieving modified client classes from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

## 28.132 PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

## 28.133 PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6

retrieving modified client classes from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

## 28.134 PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

## 28.135 PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4

retrieving modified global parameters from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

## 28.136 PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4\_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

## 28.137 PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6

```
retrieving modified global parameters from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

## 28.138 PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

## 28.139 PGSQL\_CB\_GET\_MODIFIED\_OPTIONS4

```
retrieving modified options from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

## 28.140 PGSQL\_CB\_GET\_MODIFIED\_OPTIONS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

## 28.141 PGSQL\_CB\_GET\_MODIFIED\_OPTIONS6

```
retrieving modified options from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

## 28.142 PGSQL\_CB\_GET\_MODIFIED\_OPTIONS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

## 28.143 PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4

```
retrieving modified option definitions from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

## 28.144 PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

## 28.145 PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6

```
retrieving modified option definitions from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

## 28.146 PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

## 28.147 PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4

```
retrieving modified shared networks from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

## 28.148 PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

## 28.149 PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6

```
retrieving modified shared networks from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

## 28.150 PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

## 28.151 PGSQL\_CB\_GET\_MODIFIED\_SUBNETS4

```
retrieving modified subnets from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

## 28.152 PGSQL\_CB\_GET\_MODIFIED\_SUBNETS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

## 28.153 PGSQL\_CB\_GET\_MODIFIED\_SUBNETS6

```
retrieving modified subnets from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

## 28.154 PGSQL\_CB\_GET\_MODIFIED\_SUBNETS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time



## 28.155 PGSQL\_CB\_GET\_OPTION4

```
retrieving option code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

## 28.156 PGSQL\_CB\_GET\_OPTION6

```
retrieving option code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

## 28.157 PGSQL\_CB\_GET\_OPTION\_DEF4

```
retrieving option definition code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

## 28.158 PGSQL\_CB\_GET\_OPTION\_DEF6

```
retrieving option definition code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

## 28.159 PGSQL\_CB\_GET\_PORT4

```
get port
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

## 28.160 PGSQL\_CB\_GET\_PORT6

```
get port
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

## 28.161 PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4

```
retrieving audit entries from: %1 %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id.

## 28.162 PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

## 28.163 PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6

```
retrieving audit entries from: %1 %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id

## 28.164 PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

## 28.165 PGSQL\_CB\_GET\_SERVER4

```
retrieving DHCPv4 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv4 server information.

## 28.166 PGSQL\_CB\_GET\_SERVER6

```
retrieving DHCPv6 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv6 server information.

## 28.167 PGSQL\_CB\_GET\_SHARED\_NETWORK4

```
retrieving shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

## 28.168 PGSQL\_CB\_GET\_SHARED\_NETWORK6

```
retrieving shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

## 28.169 PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4

```
retrieving shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

## 28.170 PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

## 28.171 PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6

```
retrieving shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

## 28.172 PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6\_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

## 28.173 PGSQL\_CB\_GET\_SUBNET4\_BY\_PREFIX

```
retrieving subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

## 28.174 PGSQL\_CB\_GET\_SUBNET4\_BY\_SUBNET\_ID

```
retrieving subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

## 28.175 PGSQL\_CB\_GET\_SUBNET6\_BY\_PREFIX

```
retrieving subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

## 28.176 PGSQL\_CB\_GET\_SUBNET6\_BY\_SUBNET\_ID

```
retrieving subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

## 28.177 PGSQL\_CB\_GET\_TYPE4

```
get type
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

## 28.178 PGSQL\_CB\_GET\_TYPE6

```
get type
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

## 28.179 PGSQL\_CB\_INIT\_OK

```
loading Postgres CB hooks library successful
```

This informational message indicates that the Postgres Configuration Backend hooks library has been loaded successfully. Enjoy!

## 28.180 PGSQL\_CB\_NO\_TLS\_SUPPORT

```
Attempt to configure TLS (unsupported for PostgreSQL): %1
```

This error message is printed when TLS support was required in the Kea configuration: Kea was built with this feature disabled for PostgreSQL. The parameters of the connection are logged.

## 28.181 PGSQL\_CB\_RECONNECT\_ATTEMPT\_FAILED4

```
database reconnect failed: %1
```

Error message issued when an attempt to reconnect has failed.

## 28.182 PGSQL\_CB\_RECONNECT\_ATTEMPT\_FAILED6

```
database reconnect failed: %1
```

Error message issued when an attempt to reconnect has failed.

## 28.183 PGSQL\_CB\_RECONNECT\_ATTEMPT\_SCHEDULE4

```
scheduling attempt %1 of %2 in %3 milliseconds
```

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

## 28.184 PGSQL\_CB\_RECONNECT\_ATTEMPT\_SCHEDULE6

```
scheduling attempt %1 of %2 in %3 milliseconds
```

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

## 28.185 PGSQL\_CB\_RECONNECT\_FAILED4

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 28.186 PGSQL\_CB\_RECONNECT\_FAILED6

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

## 28.187 PGSQL\_CB\_REGISTER\_BACKEND\_TYPE4

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

## 28.188 PGSQL\_CB\_REGISTER\_BACKEND\_TYPE6

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

## 28.189 PGSQL\_CB\_TLS\_SUPPORT

Attempt to configure TLS: %1

This informational message is printed when TLS support was required in the Kea configuration: The TLS support in PostgreSQL will be initialized but its configuration is fully managed outside the C API. The parameters of the connection are logged.

## 28.190 PGSQL\_CB\_UNREGISTER\_BACKEND\_TYPE4

unregister backend

Logged at debug log level 40. Debug message issued when triggered an action to unregister backend

## 29.1 RUN\_SCRIPT\_LOAD

```
Run Script hooks library has been loaded
```

This info message indicates that the Run Script hooks library has been loaded.

## 29.2 RUN\_SCRIPT\_LOAD\_ERROR

```
Run Script hooks library failed: %1
```

This error message indicates an error during loading the Run Script hooks library. The details of the error are provided as argument of the log message.





### 30.1 STAT\_CMDS\_DEINIT\_OK

```
unloading Stat Commands hooks library successful
```

This info message indicates that the Stat Commands hooks library has been removed successfully.

### 30.2 STAT\_CMDS\_INIT\_OK

```
loading Stat Commands hooks library successful
```

This info message indicates that the Stat Commands hooks library has been loaded successfully. Enjoy!

### 30.3 STAT\_CMDS\_LEASE4\_FAILED

```
stat-lease4-get command failed: reason: %1
```

The stat-lease4-get command has failed. The reason for failure is logged.

### 30.4 STAT\_CMDS\_LEASE4\_GET

```
stat-lease4-get command successful, parameters: %1 rows found: %2
```

The stat-lease4-get command has been successful. The log will contain the parameters supplied and the number of rows found.

## 30.5 STAT\_CMDS\_LEASE4\_GET\_FAILED

```
stat-lease4-get command failed: parameters: %1, reason: %2
```

The stat-lease4-get command has failed. Both the parameters supplied and the reason for failure are logged.

## 30.6 STAT\_CMDS\_LEASE4\_GET\_INVALID

```
stat-lease4-get command is malformed or invalid, reason: %1
```

The stat-lease4-get command was either malformed or contained invalid parameters. A detailed explanation should be logged.

## 30.7 STAT\_CMDS\_LEASE4\_GET\_NO\_SUBNETS

```
stat-lease4-get, parameters: %1, %2"
```

The parameters submitted with stat-lease4-get were valid but excluded all known subnets. The parameters supplied along with an explanation should be logged.

## 30.8 STAT\_CMDS\_LEASE4\_ORPHANED\_STATS

```
stat-lease4-get command omitted statistics for one or more non-existent subnets
```

Logged at debug log level 40. During processing the stat-lease4-get found statistics for subnet IDs for non-existent subnets. These values were omitted from the command response returned to the user. This may occur when subnets have been removed from the configuration in a manner that did not also remove the statistics. While the existence of such statistics is not harmful, steps should be considered to remove them. For memfile lease storage, the problem should disappear upon configuration reload or server restart. For database lease storage the issue is more complicated and as of Kea 2.0.0 we do not yet have a clean solution.

## 30.9 STAT\_CMDS\_LEASE6\_FAILED

```
stat-lease6-get command failed: reason: %1
```

The stat-lease6-get command has failed. The reason for failure is logged.

## 30.10 STAT\_CMDS\_LEASE6\_GET

```
stat-lease6-get command successful, parameters: %1 rows found: %2
```

The stat-lease6-get command has been successful. The log will contain the parameters supplied and the number of rows found.

## 30.11 STAT\_CMDS\_LEASE6\_GET\_FAILED

```
stat-lease6-get command failed: parameters: %1, reason: %2
```

The stat-lease6-get command has failed. Both the parameters supplied and the reason for failure are logged.

## 30.12 STAT\_CMDS\_LEASE6\_GET\_INVALID

```
stat-lease6-get command is malformed or invalid, reason: %1
```

The stat-lease6-get command was either malformed or contained invalid parameters. A detailed explanation should be logged.

## 30.13 STAT\_CMDS\_LEASE6\_GET\_NO\_SUBNETS

```
stat-lease6-get, parameters: %1, %2"
```

The parameters submitted with stat-lease6-get were valid but excluded all known subnets. The parameters supplied along with an explanation should be logged.



## 31.1 TCP\_CLIENT\_REQUEST\_RECEIVED

```
received TCP request from %1
```

Logged at debug log level 40. This debug message is issued when the server finished receiving a TCP request from the remote endpoint. The address of the remote endpoint is specified as an argument.

## 31.2 TCP\_CONNECTION\_REJECTED\_BY\_FILTER

```
connection from %1 has been denied by the connection filter.
```

Logged at debug log level 50. This debug message is issued when the server's connection filter rejects a new connection based on the client's ip address.

## 31.3 TCP\_CONNECTION\_SHUTDOWN

```
shutting down TCP connection from %1
```

Logged at debug log level 40. This debug message is issued when one of the TCP connections is shut down. The connection can be stopped as a result of an error or after the successful message exchange with a client.

## 31.4 TCP\_CONNECTION\_SHUTDOWN\_FAILED

```
shutting down TCP connection failed
```

This error message is issued when an error occurred during shutting down a TCP connection with a client.

## 31.5 TCP\_CONNECTION\_STOP

```
stopping TCP connection from %1
```

Logged at debug log level 40. This debug message is issued when one of the TCP connections is stopped. The connection can be stopped as a result of an error or after the successful message exchange with a client.

## 31.6 TCP\_CONNECTION\_STOP\_FAILED

```
stopping TCP connection failed
```

This error message is issued when an error occurred during closing a TCP connection with a client.

## 31.7 TCP\_DATA\_RECEIVED

```
received %1 bytes from %2
```

Logged at debug log level 55. This debug message is issued when the server receives a chunk of data from the remote endpoint. This may include the whole request or only a part of the request. The first argument specifies the amount of received data. The second argument specifies an address of the remote endpoint which produced the data.

## 31.8 TCP\_DATA\_SENT

```
send %1 bytes to %2
```

Logged at debug log level 55. This debug message is issued when the server sends a chunk of data to the remote endpoint. This may include the whole response or only a part of the response. The first argument specifies the amount of sent data. The second argument specifies an address of the remote endpoint.

## 31.9 TCP\_IDLE\_CONNECTION\_TIMEOUT\_OCCURRED

```
closing connection with %1 as a result of a timeout
```

Logged at debug log level 50. This debug message is issued when the TCP connection is being closed as a result of being idle.

## 31.10 TCP\_REQUEST\_RECEIVED\_FAILED

An unexpected error occurred processing a request from %1, error: %2

This error message is issued when an unexpected error occurred while the server attempted to process a received request. The first argument specifies the address of the remote endpoint. The second argument describes the nature error.

## 31.11 TCP\_REQUEST\_RECEIVE\_START

start receiving request from %1 with timeout %2

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

## 31.12 TCP\_SERVER\_RESPONSE\_SEND

sending TCP response to %1

Logged at debug log level 40. This debug message is issued when the server is starting to send a TCP response to a remote endpoint. The argument specifies an address of the remote endpoint.





### 32.1 TLS\_CONNECTION\_HANDSHAKE\_FAILED

```
TLS handshake with %1 failed with %2
```

This information message is issued when the TLS handshake failed at the server side. The client address and the error message are displayed.

### 32.2 TLS\_CONNECTION\_HANDSHAKE\_START

```
start TLS handshake with %1 with timeout %2
```

Logged at debug log level 50. This debug message is issued when the server starts the TLS handshake with the remote endpoint. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

### 32.3 TLS\_REQUEST\_RECEIVE\_START

```
start receiving request from %1 with timeout %2
```

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.



### 33.1 USER\_CHK\_HOOK\_LOAD\_ERROR

DHCP UserCheckHook could not be loaded: %1

This is an error message issued when the DHCP UserCheckHook could not be loaded. The exact cause should be explained in the log message. User subnet selection will revert to default processing.

### 33.2 USER\_CHK\_HOOK\_UNLOAD\_ERROR

DHCP UserCheckHook an error occurred unloading the library: %1

This is an error message issued when an error occurs while unloading the UserCheckHook library. This is unlikely to occur and normal operations of the library will likely resume when it is next loaded.

### 33.3 USER\_CHK\_SUBNET4\_SELECT\_ERROR

DHCP UserCheckHook an unexpected error occurred in subnet4\_select callout: %1

This is an error message issued when the DHCP UserCheckHook subnet4\_select hook encounters an unexpected error. The message should contain a more detailed explanation.

### 33.4 USER\_CHK\_SUBNET4\_SELECT\_REGISTRY\_NULL

DHCP UserCheckHook UserRegistry has not been created.

This is an error message issued when the DHCP UserCheckHook subnet4\_select hook has been invoked but the UserRegistry has not been created. This is a programmatic error and should not occur.

## 33.5 USER\_CHK\_SUBNET6\_SELECT\_ERROR

DHCP UserCheckHook an unexpected error occurred in subnet6\_select callout: %1

This is an error message issued when the DHCP UserCheckHook subnet6\_select hook encounters an unexpected error. The message should contain a more detailed explanation.

## KEA DEBUG MESSAGES BY LOG LEVEL

### 34.1 Messages printed on debuglevel 0

- CTRL\_AGENT\_RUN\_EXIT
- DCTL\_INIT\_PROCESS
- DCTL\_RUN\_PROCESS
- DCTL\_SHUTDOWN
- DCTL\_SHUTDOWN\_SIGNAL\_RECVD
- DCTL\_STANDALONE
- DHCP4\_OPEN\_SOCKET
- DHCP4\_START\_INFO
- DHCP6\_OPEN\_SOCKET
- DHCP6\_START\_INFO
- DHCP\_DDNS\_CLEARED\_FOR\_SHUTDOWN
- DHCP\_DDNS\_QUEUE\_MGR\_STARTED
- DHCP\_DDNS\_QUEUE\_MGR\_STOPPING
- DHCP\_DDNS\_RUN\_EXIT
- DHCP\_DDNS\_SHUTDOWN\_COMMAND
- NETCONF\_RUN\_EXIT

### 34.2 Messages printed on debuglevel 10

- COMMAND\_DEREGISTERED
- COMMAND\_EXTENDED\_REGISTERED
- COMMAND\_HTTP\_LISTENER\_COMMAND\_REJECTED
- COMMAND\_HTTP\_LISTENER\_STARTED
- COMMAND\_HTTP\_LISTENER\_STOPPED
- COMMAND\_HTTP\_LISTENER\_STOPPING
- COMMAND\_REGISTERED

- COMMAND\_SOCKET\_CONNECTION\_CLOSED
- COMMAND\_SOCKET\_CONNECTION\_OPENED
- COMMAND\_SOCKET\_READ
- COMMAND\_SOCKET\_WRITE
- CTRL\_AGENT\_COMMAND\_FORWARD\_BEGIN
- CTRL\_AGENT\_COMMAND\_FORWARD\_FAILED
- DCTL\_CONFIG\_START
- DHCP4\_CONFIG\_RECEIVED
- DHCP4\_CONFIG\_START
- DHCP6\_CONFIG\_RECEIVED
- DHCP6\_CONFIG\_START

### 34.3 Messages printed on debuglevel 15

- DHCP4\_HOOK\_BUFFER\_RCVD\_DROP
- DHCP4\_HOOK\_DDNS\_UPDATE
- DHCP4\_HOOK\_DECLINE\_SKIP
- DHCP4\_HOOK\_LEASE4\_RELEASE\_SKIP
- DHCP4\_HOOK\_PACKET\_SEND\_DROP
- DHCP4\_HOOK\_SUBNET4\_SELECT\_406\_PARKING\_LOT\_FULL
- DHCP4\_HOOK\_SUBNET4\_SELECT\_PARKING\_LOT\_FULL
- DHCP4\_HOOK\_SUBNET6\_SELECT\_PARKING\_LOT\_FULL
- DHCP4\_PACKET\_DROP\_0001
- DHCP4\_PACKET\_DROP\_0002
- DHCP4\_PACKET\_DROP\_0003
- DHCP4\_PACKET\_DROP\_0004
- DHCP4\_PACKET\_DROP\_0005
- DHCP4\_PACKET\_DROP\_0006
- DHCP4\_PACKET\_DROP\_0007
- DHCP4\_PACKET\_DROP\_0008
- DHCP4\_PACKET\_DROP\_0009
- DHCP4\_PACKET\_DROP\_0010
- DHCP4\_PACKET\_DROP\_0011
- DHCP4\_PACKET\_DROP\_0012
- DHCP4\_PACKET\_DROP\_0013
- DHCP4\_PACKET\_DROP\_0014

- DHCP6\_HOOK\_BUFFER\_RCVD\_DROP
- DHCP6\_HOOK\_DDNS\_UPDATE
- DHCP6\_HOOK\_DECLINE\_DROP
- DHCP6\_HOOK\_LEASES6\_COMMITTED\_DROP
- DHCP6\_HOOK\_LEASES6\_PARKING\_LOT\_FULL
- DHCP6\_HOOK\_PACKET\_SEND\_DROP
- DHCP6\_PACKET\_DROP\_DHCP\_DISABLED
- DHCP6\_PACKET\_DROP\_DROP\_CLASS
- DHCP6\_PACKET\_DROP\_DROP\_CLASS2
- DHCP6\_PACKET\_DROP\_DROP\_CLASS\_EARLY
- DHCP6\_PACKET\_DROP\_DUPLICATE
- DHCP6\_PACKET\_DROP\_PARSE\_FAIL
- DHCP6\_PACKET\_DROP\_SERVERID\_MISMATCH
- DHCP6\_PACKET\_DROP\_UNICAST

## 34.4 Messages printed on debuglevel 20

- LEASE\_CMDS\_ADD4
- LEASE\_CMDS\_ADD6
- LEASE\_CMDS\_BULK\_APPLY6
- LEASE\_CMDS\_DEL4
- LEASE\_CMDS\_DEL6
- LEASE\_CMDS\_UPDATE4
- LEASE\_CMDS\_UPDATE6

## 34.5 Messages printed on debuglevel 40

- ALLOC\_ENGINE\_IGNOREING\_UNSUITABLE\_GLOBAL\_ADDRESS
- ALLOC\_ENGINE\_IGNOREING\_UNSUITABLE\_GLOBAL\_ADDRESS6
- ALLOC\_ENGINE\_LEASE\_RECLAIMED
- ALLOC\_ENGINE\_V4\_DISCOVER\_HR
- ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_COMPLETE
- ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_START
- ALLOC\_ENGINE\_V4\_LEASES\_RECLAMATION\_TIMEOUT
- ALLOC\_ENGINE\_V4\_LEASE\_RECLAIM
- ALLOC\_ENGINE\_V4\_NO\_MORE\_EXPIRED\_LEASES
- ALLOC\_ENGINE\_V4\_OFFER\_EXISTING\_LEASE

- ALLOC\_ENGINE\_V4\_OFFER\_NEW\_LEASE
- ALLOC\_ENGINE\_V4\_OFFER\_REQUESTED\_LEASE
- ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE
- ALLOC\_ENGINE\_V4\_RECLAIMED\_LEASES\_DELETE\_COMPLETE
- ALLOC\_ENGINE\_V4\_REQUEST\_ADDRESS\_RESERVED
- ALLOC\_ENGINE\_V4\_REQUEST\_ALLOC\_REQUESTED
- ALLOC\_ENGINE\_V4\_REQUEST\_EXTEND\_LEASE
- ALLOC\_ENGINE\_V4\_REQUEST\_INVALID
- ALLOC\_ENGINE\_V4\_REQUEST\_IN\_USE
- ALLOC\_ENGINE\_V4\_REQUEST\_OUT\_OF\_POOL
- ALLOC\_ENGINE\_V4\_REQUEST\_PICK\_ADDRESS
- ALLOC\_ENGINE\_V4\_REQUEST\_REMOVE\_LEASE
- ALLOC\_ENGINE\_V4\_REQUEST\_USE\_HR
- ALLOC\_ENGINE\_V6\_ALLOC\_HR\_LEASE\_EXISTS
- ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_HR
- ALLOC\_ENGINE\_V6\_ALLOC\_LEASES\_NO\_HR
- ALLOC\_ENGINE\_V6\_ALLOC\_NO\_LEASES\_HR
- ALLOC\_ENGINE\_V6\_ALLOC\_NO\_V6\_HR
- ALLOC\_ENGINE\_V6\_ALLOC\_UNRESERVED
- ALLOC\_ENGINE\_V6\_CALCULATED\_PREFERRED\_LIFETIME
- ALLOC\_ENGINE\_V6\_EXPIRED\_HINT\_RESERVED
- ALLOC\_ENGINE\_V6\_EXTEND\_ALLOC\_UNRESERVED
- ALLOC\_ENGINE\_V6\_HINT\_RESERVED
- ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_COMPLETE
- ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_START
- ALLOC\_ENGINE\_V6\_LEASES\_RECLAMATION\_TIMEOUT
- ALLOC\_ENGINE\_V6\_LEASE\_RECLAIM
- ALLOC\_ENGINE\_V6\_NO\_MORE\_EXPIRED\_LEASES
- ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE
- ALLOC\_ENGINE\_V6\_RECLAIMED\_LEASES\_DELETE\_COMPLETE
- ALLOC\_ENGINE\_V6\_RENEW\_HR
- ALLOC\_ENGINE\_V6\_RENEW\_REMOVE\_RESERVED
- ASIODNS\_FETCH\_STOPPED
- BOOTP\_BOOTP\_QUERY
- BOOTP\_PACKET\_OPTIONS\_SKIPPED
- BOOTP\_PACKET\_PACK



- BOOTP\_PACKET\_UNPACK\_FAILED
- DHCP4\_BUFFER\_RECEIVED
- DHCP4\_CLASSES\_ASSIGNED
- DHCP4\_CLASSES\_ASSIGNED\_AFTER\_SUBNET\_SELECTION
- DHCP4\_CLASS\_ASSIGNED
- DHCP4\_CLASS\_UNCONFIGURED
- DHCP4\_CLASS\_UNDEFINED
- DHCP4\_CLASS\_UNTESTABLE
- DHCP4\_DHCP4O6\_HOOK\_SUBNET4\_SELECT\_DROP
- DHCP4\_DHCP4O6\_HOOK\_SUBNET4\_SELECT\_SKIP
- DHCP4\_DHCP4O6\_PACKET\_RECEIVED
- DHCP4\_DHCP4O6\_PACKET\_SEND
- DHCP4\_FLEX\_ID
- DHCP4\_HOOK\_BUFFER\_SEND\_SKIP
- DHCP4\_HOOK\_PACKET\_RCVD\_SKIP
- DHCP4\_HOOK\_PACKET\_SEND\_SKIP
- DHCP4\_HOOK\_SUBNET4\_SELECT\_DROP
- DHCP4\_HOOK\_SUBNET4\_SELECT\_PARK
- DHCP4\_HOOK\_SUBNET4\_SELECT\_SKIP
- DHCP4\_PACKET\_QUEUE\_FULL
- DHCP4\_SHUTDOWN
- DHCP4\_SHUTDOWN\_REQUEST
- DHCP6\_BUFFER\_RECEIVED
- DHCP6\_CLASSES\_ASSIGNED
- DHCP6\_CLASSES\_ASSIGNED\_AFTER\_SUBNET\_SELECTION
- DHCP6\_CLASS\_ASSIGNED
- DHCP6\_CLASS\_UNCONFIGURED
- DHCP6\_CLASS\_UNDEFINED
- DHCP6\_CLASS\_UNTESTABLE
- DHCP6\_DHCP4O6\_PACKET\_RECEIVED
- DHCP6\_FLEX\_ID
- DHCP6\_HOOK\_BUFFER\_SEND\_SKIP
- DHCP6\_HOOK\_LEASE6\_RELEASE\_NA\_SKIP
- DHCP6\_HOOK\_LEASE6\_RELEASE\_PD\_SKIP
- DHCP6\_HOOK\_LEASES6\_COMMITTED\_PARK
- DHCP6\_HOOK\_PACKET\_RCVD\_SKIP

- DHCP6\_HOOK\_PACKET\_SEND\_SKIP
- DHCP6\_HOOK\_SUBNET6\_SELECT\_DROP
- DHCP6\_HOOK\_SUBNET6\_SELECT\_PARK
- DHCP6\_HOOK\_SUBNET6\_SELECT\_SKIP
- DHCP6\_PACKET\_PROCESS\_FAIL
- DHCP6\_PACKET\_QUEUE\_FULL
- DHCP6\_REQUIRED\_OPTIONS\_CHECK\_FAIL
- DHCP6\_SHUTDOWN
- DHCP6\_SHUTDOWN\_REQUEST
- DHCP6\_UNKNOWN\_MSG\_RECEIVED
- DHCPSRV\_CFGMGR\_ADD\_SUBNET4
- DHCPSRV\_CFGMGR\_ADD\_SUBNET6
- DHCPSRV\_CFGMGR\_ALL\_IFACES\_ACTIVE
- DHCPSRV\_CFGMGR\_CFG\_DHCP\_DDNS
- DHCPSRV\_CFGMGR\_DEL\_SUBNET4
- DHCPSRV\_CFGMGR\_DEL\_SUBNET6
- DHCPSRV\_CFGMGR\_SUBNET4
- DHCPSRV\_CFGMGR\_SUBNET4\_ADDR
- DHCPSRV\_CFGMGR\_SUBNET4\_IFACE
- DHCPSRV\_CFGMGR\_SUBNET4\_RELAY
- DHCPSRV\_CFGMGR\_SUBNET6
- DHCPSRV\_CFGMGR\_SUBNET6\_IFACE
- DHCPSRV\_CFGMGR\_SUBNET6\_IFACE\_ID
- DHCPSRV\_CFGMGR\_SUBNET6\_RELAY
- DHCPSRV\_CFGMGR\_UPDATE\_SUBNET4
- DHCPSRV\_CFGMGR\_UPDATE\_SUBNET6
- DHCPSRV\_CLOSE\_DB
- DHCPSRV\_HOOK\_LEASE4\_RECOVER\_SKIP
- DHCPSRV\_HOOK\_LEASE4\_RENEW\_SKIP
- DHCPSRV\_HOOK\_LEASE4\_SELECT\_SKIP
- DHCPSRV\_HOOK\_LEASE6\_EXTEND\_SKIP
- DHCPSRV\_HOOK\_LEASE6\_RECOVER\_SKIP
- DHCPSRV\_HOOK\_LEASE6\_SELECT\_SKIP
- DHCPSRV\_LEASE4\_EXTENDED\_INFO\_UPGRADED
- DHCPSRV\_LEASE6\_EXTENDED\_INFO\_UPGRADED
- DHCPSRV\_MEMFILE\_BEGIN\_BUILD\_EXTENDED\_INFO\_TABLES6

- DHCPSRV\_MEMFILE\_BEGIN\_EXTRACT\_EXTENDED\_INFO4
- DHCPSRV\_MEMFILE\_EXTRACT\_EXTENDED\_INFO4
- DHCPSRV\_MEMFILE\_EXTRACT\_EXTENDED\_INFO4\_ERROR
- DHCPSRV\_MEMFILE\_LFC\_UNREGISTER\_TIMER\_FAILED
- DHCPSRV\_MYSQL\_TLS\_CIPHER
- DHCPSRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO4
- DHCPSRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO4\_ERROR
- DHCPSRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO6
- DHCPSRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO6\_ERROR
- DHCPSRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO4
- DHCPSRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO4\_ERROR
- DHCPSRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO6
- DHCPSRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO6\_ERROR
- DHCPSRV\_SUBNET4O6\_SELECT\_FAILED
- DHCPSRV\_SUBNET4\_SELECT\_BY\_ADDRESS\_NO\_MATCH
- DHCPSRV\_SUBNET4\_SELECT\_BY\_INTERFACE\_NO\_MATCH
- DHCPSRV\_SUBNET4\_SELECT\_BY\_RELAY\_ADDRESS\_NO\_MATCH
- DHCPSRV\_SUBNET4\_SELECT\_NO\_RAI\_OPTIONS
- DHCPSRV\_SUBNET4\_SELECT\_NO\_RELAY\_ADDRESS
- DHCPSRV\_SUBNET4\_SELECT\_NO\_USABLE\_ADDRESS
- DHCPSRV\_SUBNET6\_SELECT\_BY\_ADDRESS\_NO\_MATCH
- DHCPSRV\_SUBNET6\_SELECT\_BY\_INTERFACE\_ID\_NO\_MATCH
- DHCPSRV\_SUBNET6\_SELECT\_BY\_INTERFACE\_NO\_MATCH
- DHCPSRV\_TIMERMGR\_REGISTER\_TIMER
- DHCPSRV\_TIMERMGR\_START\_TIMER
- DHCPSRV\_TIMERMGR\_STOP\_TIMER
- DHCPSRV\_TIMERMGR\_UNREGISTER\_ALL\_TIMERS
- DHCPSRV\_TIMERMGR\_UNREGISTER\_TIMER
- DHCP\_DDNS\_CONFIGURE
- DHCP\_DDNS\_NCR\_UDP\_RECV\_CANCELED
- DHCP\_DDNS\_QUEUE\_MGR\_RECONFIGURING
- DHCP\_DDNS\_QUEUE\_MGR\_STOPPED
- FLEX\_OPTION\_PROCESS\_ADD
- FLEX\_OPTION\_PROCESS\_CLIENT\_CLASS
- FLEX\_OPTION\_PROCESS\_REMOVE
- FLEX\_OPTION\_PROCESS\_SUB\_ADD

- FLEX\_OPTION\_PROCESS\_SUB\_CLIENT\_CLASS
- FLEX\_OPTION\_PROCESS\_SUB\_REMOVE
- FLEX\_OPTION\_PROCESS\_SUB\_SUPERSEDE
- FLEX\_OPTION\_PROCESS\_SUPERSEDE
- FLEX\_OPTION\_PROCESS\_VENDOR\_ID\_MISMATCH
- HA\_BUFFER4\_RECEIVE\_NOT\_FOR\_US
- HA\_BUFFER4\_RECEIVE\_PACKET\_OPTIONS\_SKIPPED
- HA\_BUFFER4\_RECEIVE\_UNPACK\_FAILED
- HA\_BUFFER6\_RECEIVE\_NOT\_FOR\_US
- HA\_BUFFER6\_RECEIVE\_PACKET\_OPTIONS\_SKIPPED
- HA\_BUFFER6\_RECEIVE\_UNPACK\_FAILED
- HA\_LEASES4\_COMMITTED\_NOTHING\_TO\_UPDATE
- HA\_LEASES6\_COMMITTED\_NOTHING\_TO\_UPDATE
- HA\_LEASE\_SYNC\_STALE\_LEASE4\_SKIP
- HA\_LEASE\_SYNC\_STALE\_LEASE6\_SKIP
- HA\_LOAD\_BALANCING\_DUID\_MISSING
- HA\_LOAD\_BALANCING\_IDENTIFIER\_MISSING
- HA\_SUBNET4\_SELECT\_NOT\_FOR\_US
- HA\_SUBNET4\_SELECT\_NO\_SUBNET\_SELECTED
- HA\_SUBNET6\_SELECT\_NOT\_FOR\_US
- HA\_SUBNET6\_SELECT\_NO\_SUBNET\_SELECTED
- HOOKS\_LIBRARY\_LOADING
- HOOKS\_LIBRARY\_UNLOADING
- HOOKS\_LOAD\_SUCCESS
- HOOKS\_NO\_LOAD
- HOOKS\_NO\_UNLOAD
- HOOKS\_UNLOAD\_SUCCESS
- HOSTS\_BACKEND\_DEREGISTER
- HOSTS\_BACKEND\_REGISTER
- HOSTS\_CFG\_ADD\_HOST
- HOSTS\_CFG\_CLOSE\_HOST\_DATA\_SOURCE
- HOSTS\_CFG\_DEL
- HOSTS\_CFG\_DEL4
- HOSTS\_CFG\_DEL6
- HOSTS\_CFG\_DEL\_ALL\_SUBNET4
- HOSTS\_CFG\_DEL\_ALL\_SUBNET6

- HOSTS\_CFG\_GET\_ONE\_PREFIX
- HOSTS\_CFG\_UPDATE\_ADD
- HOSTS\_CFG\_UPDATE\_DEL4
- HOSTS\_CFG\_UPDATE\_DEL6
- HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_ADDRESS4
- HOSTS\_MGR\_ALTERNATE\_GET6\_PREFIX
- HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_ADDRESS6
- HOSTS\_MGR\_ALTERNATE\_GET\_ALL\_SUBNET\_ID\_ADDRESS4
- HOSTS\_MGR\_ALTERNATE\_GET\_ALL\_SUBNET\_ID\_ADDRESS6
- HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED
- HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED
- HTTP\_CLIENT\_MT\_STARTED
- HTTP\_CLIENT\_REQUEST\_RECEIVED
- HTTP\_CONNECTION\_SHUTDOWN
- HTTP\_CONNECTION\_STOP
- HTTP\_SERVER\_RESPONSE\_RECEIVED
- HTTP\_SERVER\_RESPONSE\_SEND
- MT\_TCP\_LISTENER\_MGR\_STARTED
- MT\_TCP\_LISTENER\_MGR\_STOPPED
- MT\_TCP\_LISTENER\_MGR\_STOPPING
- MYSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION4
- MYSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION6
- MYSQL\_CB\_CREATE\_UPDATE\_BY\_PREFIX\_OPTION6
- MYSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION4
- MYSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION6
- MYSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS4
- MYSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS6
- MYSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER4
- MYSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER6
- MYSQL\_CB\_CREATE\_UPDATE\_OPTION4
- MYSQL\_CB\_CREATE\_UPDATE\_OPTION6
- MYSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF4
- MYSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF6
- MYSQL\_CB\_CREATE\_UPDATE\_SERVER4
- MYSQL\_CB\_CREATE\_UPDATE\_SERVER6
- MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK4

- MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK6
- MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION4
- MYSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION6
- MYSQL\_CB\_CREATE\_UPDATE\_SUBNET4
- MYSQL\_CB\_CREATE\_UPDATE\_SUBNET6
- MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4
- MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6
- MYSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4
- MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6
- MYSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4
- MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6
- MYSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_SERVERS4
- MYSQL\_CB\_DELETE\_ALL\_SERVERS4\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_SERVERS6
- MYSQL\_CB\_DELETE\_ALL\_SERVERS6\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4
- MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6
- MYSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_SUBNETS4
- MYSQL\_CB\_DELETE\_ALL\_SUBNETS4\_RESULT
- MYSQL\_CB\_DELETE\_ALL\_SUBNETS6
- MYSQL\_CB\_DELETE\_ALL\_SUBNETS6\_RESULT
- MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION4
- MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION4\_RESULT
- MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION6
- MYSQL\_CB\_DELETE\_BY\_POOL\_OPTION6\_RESULT
- MYSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6
- MYSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6\_RESULT
- MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4

- MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4\_RESULT
- MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6
- MYSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6\_RESULT
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4\_RESULT
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6\_RESULT
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4\_RESULT
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6
- MYSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6\_RESULT
- MYSQL\_CB\_DELETE\_CLIENT\_CLASS4
- MYSQL\_CB\_DELETE\_CLIENT\_CLASS4\_RESULT
- MYSQL\_CB\_DELETE\_CLIENT\_CLASS6
- MYSQL\_CB\_DELETE\_CLIENT\_CLASS6\_RESULT
- MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4
- MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4\_RESULT
- MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6
- MYSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6\_RESULT
- MYSQL\_CB\_DELETE\_OPTION4
- MYSQL\_CB\_DELETE\_OPTION4\_RESULT
- MYSQL\_CB\_DELETE\_OPTION6
- MYSQL\_CB\_DELETE\_OPTION6\_RESULT
- MYSQL\_CB\_DELETE\_OPTION\_DEF4
- MYSQL\_CB\_DELETE\_OPTION\_DEF4\_RESULT
- MYSQL\_CB\_DELETE\_OPTION\_DEF6
- MYSQL\_CB\_DELETE\_OPTION\_DEF6\_RESULT
- MYSQL\_CB\_DELETE\_SERVER4
- MYSQL\_CB\_DELETE\_SERVER4\_RESULT
- MYSQL\_CB\_DELETE\_SERVER6
- MYSQL\_CB\_DELETE\_SERVER6\_RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK4
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK4\_RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK6
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK6\_RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4

- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4\_RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6\_RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4\_RESULT
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6
- MYSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6\_RESULT
- MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4
- MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4\_RESULT
- MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6
- MYSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6\_RESULT
- MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4
- MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6
- MYSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6\_RESULT
- MYSQL\_CB\_GET\_ALL\_OPTIONS4
- MYSQL\_CB\_GET\_ALL\_OPTIONS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_OPTIONS6
- MYSQL\_CB\_GET\_ALL\_OPTIONS6\_RESULT
- MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS4
- MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS6
- MYSQL\_CB\_GET\_ALL\_OPTION\_DEFS6\_RESULT
- MYSQL\_CB\_GET\_ALL\_SERVERS4
- MYSQL\_CB\_GET\_ALL\_SERVERS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_SERVERS6
- MYSQL\_CB\_GET\_ALL\_SERVERS6\_RESULT
- MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4
- MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6
- MYSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6\_RESULT
- MYSQL\_CB\_GET\_ALL\_SUBNETS4
- MYSQL\_CB\_GET\_ALL\_SUBNETS4\_RESULT
- MYSQL\_CB\_GET\_ALL\_SUBNETS6
- MYSQL\_CB\_GET\_ALL\_SUBNETS6\_RESULT
- MYSQL\_CB\_GET\_CLIENT\_CLASS4



- MYSQL\_CB\_GET\_CLIENT\_CLASS6
- MYSQL\_CB\_GET\_GLOBAL\_PARAMETER4
- MYSQL\_CB\_GET\_GLOBAL\_PARAMETER6
- MYSQL\_CB\_GET\_HOST4
- MYSQL\_CB\_GET\_HOST6
- MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4
- MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6
- MYSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4
- MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6
- MYSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_OPTIONS4
- MYSQL\_CB\_GET\_MODIFIED\_OPTIONS4\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_OPTIONS6
- MYSQL\_CB\_GET\_MODIFIED\_OPTIONS6\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4
- MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6
- MYSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4
- MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6
- MYSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_SUBNETS4
- MYSQL\_CB\_GET\_MODIFIED\_SUBNETS4\_RESULT
- MYSQL\_CB\_GET\_MODIFIED\_SUBNETS6
- MYSQL\_CB\_GET\_MODIFIED\_SUBNETS6\_RESULT
- MYSQL\_CB\_GET\_OPTION4
- MYSQL\_CB\_GET\_OPTION6
- MYSQL\_CB\_GET\_OPTION\_DEF4
- MYSQL\_CB\_GET\_OPTION\_DEF6
- MYSQL\_CB\_GET\_PORT4
- MYSQL\_CB\_GET\_PORT6
- MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4

- MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4\_RESULT
- MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6
- MYSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6\_RESULT
- MYSQL\_CB\_GET\_SERVER4
- MYSQL\_CB\_GET\_SERVER6
- MYSQL\_CB\_GET\_SHARED\_NETWORK4
- MYSQL\_CB\_GET\_SHARED\_NETWORK6
- MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4
- MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4\_RESULT
- MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6
- MYSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6\_RESULT
- MYSQL\_CB\_GET\_SUBNET4\_BY\_PREFIX
- MYSQL\_CB\_GET\_SUBNET4\_BY\_SUBNET\_ID
- MYSQL\_CB\_GET\_SUBNET6\_BY\_PREFIX
- MYSQL\_CB\_GET\_SUBNET6\_BY\_SUBNET\_ID
- MYSQL\_CB\_GET\_TYPE4
- MYSQL\_CB\_GET\_TYPE6
- MYSQL\_CB\_REGISTER\_BACKEND\_TYPE4
- MYSQL\_CB\_REGISTER\_BACKEND\_TYPE6
- MYSQL\_CB\_TLS\_CIPHER
- MYSQL\_CB\_UNREGISTER\_BACKEND\_TYPE4
- MYSQL\_CB\_UNREGISTER\_BACKEND\_TYPE6
- PERFMON\_DHCP4\_SOCKET\_RECEIVED\_TIME\_SUPPORT
- PERFMON\_DHCP6\_SOCKET\_RECEIVED\_TIME\_SUPPORT
- PGSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION4
- PGSQL\_CB\_CREATE\_UPDATE\_BY\_POOL\_OPTION6
- PGSQL\_CB\_CREATE\_UPDATE\_BY\_PREFIX\_OPTION6
- PGSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION4
- PGSQL\_CB\_CREATE\_UPDATE\_BY\_SUBNET\_ID\_OPTION6
- PGSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS4
- PGSQL\_CB\_CREATE\_UPDATE\_CLIENT\_CLASS6
- PGSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER4
- PGSQL\_CB\_CREATE\_UPDATE\_GLOBAL\_PARAMETER6
- PGSQL\_CB\_CREATE\_UPDATE\_OPTION4
- PGSQL\_CB\_CREATE\_UPDATE\_OPTION6
- PGSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF4

- PGSQL\_CB\_CREATE\_UPDATE\_OPTION\_DEF6
- PGSQL\_CB\_CREATE\_UPDATE\_SERVER4
- PGSQL\_CB\_CREATE\_UPDATE\_SERVER6
- PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK4
- PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK6
- PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION4
- PGSQL\_CB\_CREATE\_UPDATE\_SHARED\_NETWORK\_OPTION6
- PGSQL\_CB\_CREATE\_UPDATE\_SUBNET4
- PGSQL\_CB\_CREATE\_UPDATE\_SUBNET6
- PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4
- PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES4\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6
- PGSQL\_CB\_DELETE\_ALL\_CLIENT\_CLASSES6\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4
- PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS4\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6
- PGSQL\_CB\_DELETE\_ALL\_GLOBAL\_PARAMETERS6\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4
- PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS4\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6
- PGSQL\_CB\_DELETE\_ALL\_OPTION\_DEFS6\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_SERVERS4
- PGSQL\_CB\_DELETE\_ALL\_SERVERS4\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_SERVERS6
- PGSQL\_CB\_DELETE\_ALL\_SERVERS6\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4
- PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS4\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6
- PGSQL\_CB\_DELETE\_ALL\_SHARED\_NETWORKS6\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_SUBNETS4
- PGSQL\_CB\_DELETE\_ALL\_SUBNETS4\_RESULT
- PGSQL\_CB\_DELETE\_ALL\_SUBNETS6
- PGSQL\_CB\_DELETE\_ALL\_SUBNETS6\_RESULT
- PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION4
- PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION4\_RESULT
- PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION6

- PGSQL\_CB\_DELETE\_BY\_POOL\_OPTION6\_RESULT
- PGSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6
- PGSQL\_CB\_DELETE\_BY\_POOL\_PREFIX\_OPTION6\_RESULT
- PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4
- PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET4\_RESULT
- PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6
- PGSQL\_CB\_DELETE\_BY\_PREFIX\_SUBNET6\_RESULT
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION4\_RESULT
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_OPTION6\_RESULT
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET4\_RESULT
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6
- PGSQL\_CB\_DELETE\_BY\_SUBNET\_ID\_SUBNET6\_RESULT
- PGSQL\_CB\_DELETE\_CLIENT\_CLASS4
- PGSQL\_CB\_DELETE\_CLIENT\_CLASS4\_RESULT
- PGSQL\_CB\_DELETE\_CLIENT\_CLASS6
- PGSQL\_CB\_DELETE\_CLIENT\_CLASS6\_RESULT
- PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4
- PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER4\_RESULT
- PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6
- PGSQL\_CB\_DELETE\_GLOBAL\_PARAMETER6\_RESULT
- PGSQL\_CB\_DELETE\_OPTION4
- PGSQL\_CB\_DELETE\_OPTION4\_RESULT
- PGSQL\_CB\_DELETE\_OPTION6
- PGSQL\_CB\_DELETE\_OPTION6\_RESULT
- PGSQL\_CB\_DELETE\_OPTION\_DEF4
- PGSQL\_CB\_DELETE\_OPTION\_DEF4\_RESULT
- PGSQL\_CB\_DELETE\_OPTION\_DEF6
- PGSQL\_CB\_DELETE\_OPTION\_DEF6\_RESULT
- PGSQL\_CB\_DELETE\_SERVER4
- PGSQL\_CB\_DELETE\_SERVER4\_RESULT
- PGSQL\_CB\_DELETE\_SERVER6
- PGSQL\_CB\_DELETE\_SERVER6\_RESULT
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK4

- PGSQL\_CB\_DELETE\_SHARED\_NETWORK4\_RESULT
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK6
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK6\_RESULT
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION4\_RESULT
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_OPTION6\_RESULT
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS4\_RESULT
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6
- PGSQL\_CB\_DELETE\_SHARED\_NETWORK\_SUBNETS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4
- PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES4\_RESULT
- PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6
- PGSQL\_CB\_GET\_ALL\_CLIENT\_CLASSES6\_RESULT
- PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4
- PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS4\_RESULT
- PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6
- PGSQL\_CB\_GET\_ALL\_GLOBAL\_PARAMETERS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_OPTIONS4
- PGSQL\_CB\_GET\_ALL\_OPTIONS4\_RESULT
- PGSQL\_CB\_GET\_ALL\_OPTIONS6
- PGSQL\_CB\_GET\_ALL\_OPTIONS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS4
- PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS4\_RESULT
- PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS6
- PGSQL\_CB\_GET\_ALL\_OPTION\_DEFS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_SERVERS4
- PGSQL\_CB\_GET\_ALL\_SERVERS4\_RESULT
- PGSQL\_CB\_GET\_ALL\_SERVERS6
- PGSQL\_CB\_GET\_ALL\_SERVERS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4
- PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS4\_RESULT
- PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6
- PGSQL\_CB\_GET\_ALL\_SHARED\_NETWORKS6\_RESULT
- PGSQL\_CB\_GET\_ALL\_SUBNETS4

- PGSQL\_CB\_GET\_ALL\_SUBNETS4\_RESULT
- PGSQL\_CB\_GET\_ALL\_SUBNETS6
- PGSQL\_CB\_GET\_ALL\_SUBNETS6\_RESULT
- PGSQL\_CB\_GET\_CLIENT\_CLASS4
- PGSQL\_CB\_GET\_CLIENT\_CLASS6
- PGSQL\_CB\_GET\_GLOBAL\_PARAMETER4
- PGSQL\_CB\_GET\_GLOBAL\_PARAMETER6
- PGSQL\_CB\_GET\_HOST4
- PGSQL\_CB\_GET\_HOST6
- PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4
- PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6
- PGSQL\_CB\_GET\_MODIFIED\_CLIENT\_CLASSES6\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4
- PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6
- PGSQL\_CB\_GET\_MODIFIED\_GLOBAL\_PARAMETERS6\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_OPTIONS4
- PGSQL\_CB\_GET\_MODIFIED\_OPTIONS4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_OPTIONS6
- PGSQL\_CB\_GET\_MODIFIED\_OPTIONS6\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4
- PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6
- PGSQL\_CB\_GET\_MODIFIED\_OPTION\_DEFS6\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4
- PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6
- PGSQL\_CB\_GET\_MODIFIED\_SHARED\_NETWORKS6\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_SUBNETS4
- PGSQL\_CB\_GET\_MODIFIED\_SUBNETS4\_RESULT
- PGSQL\_CB\_GET\_MODIFIED\_SUBNETS6
- PGSQL\_CB\_GET\_MODIFIED\_SUBNETS6\_RESULT
- PGSQL\_CB\_GET\_OPTION4
- PGSQL\_CB\_GET\_OPTION6
- PGSQL\_CB\_GET\_OPTION\_DEF4

- PGSQL\_CB\_GET\_OPTION\_DEF6
- PGSQL\_CB\_GET\_PORT4
- PGSQL\_CB\_GET\_PORT6
- PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4
- PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES4\_RESULT
- PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6
- PGSQL\_CB\_GET\_RECENT\_AUDIT\_ENTRIES6\_RESULT
- PGSQL\_CB\_GET\_SERVER4
- PGSQL\_CB\_GET\_SERVER6
- PGSQL\_CB\_GET\_SHARED\_NETWORK4
- PGSQL\_CB\_GET\_SHARED\_NETWORK6
- PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4
- PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS4\_RESULT
- PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6
- PGSQL\_CB\_GET\_SHARED\_NETWORK\_SUBNETS6\_RESULT
- PGSQL\_CB\_GET\_SUBNET4\_BY\_PREFIX
- PGSQL\_CB\_GET\_SUBNET4\_BY\_SUBNET\_ID
- PGSQL\_CB\_GET\_SUBNET6\_BY\_PREFIX
- PGSQL\_CB\_GET\_SUBNET6\_BY\_SUBNET\_ID
- PGSQL\_CB\_GET\_TYPE4
- PGSQL\_CB\_GET\_TYPE6
- PGSQL\_CB\_REGISTER\_BACKEND\_TYPE4
- PGSQL\_CB\_REGISTER\_BACKEND\_TYPE6
- PGSQL\_CB\_UNREGISTER\_BACKEND\_TYPE4
- PGSQL\_CB\_UNREGISTER\_BACKEND\_TYPE6
- STAT\_CMDS\_LEASE4\_ORPHANED\_STATS
- STAT\_CMDS\_LEASE6\_ORPHANED\_STATS
- TCP\_CLIENT\_REQUEST\_RECEIVED
- TCP\_CONNECTION\_SHUTDOWN
- TCP\_CONNECTION\_STOP
- TCP\_SERVER\_RESPONSE\_SEND
- TLS\_SERVER\_RESPONSE\_SEND

## 34.6 Messages printed on debuglevel 45

- DHCP4\_DHCP4O6\_SUBNET\_SELECTED
- DHCP4\_SUBNET\_DYNAMICALLY\_CHANGED
- DHCP4\_SUBNET\_SELECTED
- DHCP6\_SUBNET\_DYNAMICALLY\_CHANGED
- DHCP6\_SUBNET\_SELECTED
- HOOKS\_CALLOUTS\_BEGIN
- HOOKS\_CALLOUTS\_COMPLETE
- HOOKS\_CALLOUTS\_REMOVED
- HOOKS\_CALLOUT\_REGISTRATION
- HOOKS\_LIBRARY\_MULTI\_THREADING\_COMPATIBLE
- HOOKS\_LIBRARY\_VERSION
- HOOKS\_STD\_CALLOUT\_REGISTERED
- HOSTS\_CFG\_GET\_ALL
- HOSTS\_CFG\_GET\_ALL\_ADDRESS4
- HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_COUNT
- HOSTS\_CFG\_GET\_ALL\_ADDRESS6
- HOSTS\_CFG\_GET\_ALL\_ADDRESS6\_COUNT
- HOSTS\_CFG\_GET\_ALL\_COUNT
- HOSTS\_CFG\_GET\_ALL\_HOST
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_COUNT
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4\_COUNT
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID6
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID6\_COUNT
- HOSTS\_CFG\_GET\_ALL\_IDENTIFIER
- HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_COUNT
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID4
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID4\_COUNT
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID6
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID6\_COUNT
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4\_COUNT
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6



- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6\_COUNT
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_HOST
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS4\_NULL
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_HOST
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_ADDRESS6\_NULL
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_HOST
- HOSTS\_CFG\_GET\_ONE\_SUBNET\_ID\_IDENTIFIER\_NULL
- HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER
- HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_HOST
- HOSTS\_MGR\_ALTERNATE\_GET4\_SUBNET\_ID\_IDENTIFIER\_NULL
- HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER
- HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_HOST
- HOSTS\_MGR\_ALTERNATE\_GET6\_SUBNET\_ID\_IDENTIFIER\_NULL
- HTTP\_BAD\_CLIENT\_REQUEST\_RECEIVED\_DETAILS
- HTTP\_BAD\_SERVER\_RESPONSE\_RECEIVED\_DETAILS
- HTTP\_CLIENT\_REQUEST\_RECEIVED\_DETAILS
- HTTP\_SERVER\_RESPONSE\_RECEIVED\_DETAILS
- HTTP\_SERVER\_RESPONSE\_SEND\_DETAILS

## 34.7 Messages printed on debuglevel 50

- ALLOC\_ENGINE\_V6\_EXTEND\_LEASE
- ASIODNS\_READ\_TIMEOUT
- DHCP4\_BUFFER\_UNPACK
- DHCP4\_BUFFER\_WAIT\_SIGNAL
- DHCP4\_CLIENTID\_IGNORED\_FOR\_LEASES
- DHCP4\_CLIENT\_FQDN\_PROCESS
- DHCP4\_CLIENT\_HOSTNAME\_MALFORMED
- DHCP4\_CLIENT\_HOSTNAME\_PROCESS
- DHCP4\_DEFERRED\_OPTION\_MISSING
- DHCP4\_DEFERRED\_OPTION\_UNPACK\_FAIL
- DHCP4\_DHCP4O6\_BAD\_PACKET
- DHCP4\_DHCP4O6\_RECEIVE\_FAIL

- DHCP4\_DHCP4O6\_RECEIVING
- DHCP4\_DHCP4O6\_SUBNET\_SELECTION\_FAILED
- DHCP4\_DISCOVER
- DHCP4\_EMPTY\_HOSTNAME
- DHCP4\_HOOK\_BUFFER\_RCVD\_SKIP
- DHCP4\_INFORM\_DIRECT\_REPLY
- DHCP4\_NO\_LEASE\_INIT\_REBOOT
- DHCP4\_PACKET\_NAK\_0002
- DHCP4\_PACKET\_NAK\_0003
- DHCP4\_PACKET\_NAK\_0004
- DHCP4\_PACKET\_OPTIONS\_SKIPPED
- DHCP4\_PACKET\_PACK
- DHCP4\_RELEASE
- DHCP4\_RELEASE\_FAIL
- DHCP4\_RELEASE\_FAIL\_NO\_LEASE
- DHCP4\_RELEASE\_FAIL\_WRONG\_CLIENT
- DHCP4\_REQUEST
- DHCP4\_REQUIRED\_CLASS\_EVAL\_RESULT
- DHCP4\_RESPONSE\_HOSTNAME\_GENERATE
- DHCP4\_SUBNET\_SELECTION\_FAILED
- DHCP4\_UNKNOWN\_ADDRESS\_REQUESTED
- DHCP6\_ADD\_GLOBAL\_STATUS\_CODE
- DHCP6\_ADD\_STATUS\_CODE\_FOR\_IA
- DHCP6\_BUFFER\_UNPACK
- DHCP6\_BUFFER\_WAIT\_SIGNAL
- DHCP6\_DDNS\_CREATE\_ADD\_NAME\_CHANGE\_REQUEST
- DHCP6\_DDNS\_GENERATE\_FQDN
- DHCP6\_DDNS\_RECEIVE\_FQDN
- DHCP6\_DDNS\_REMOVE\_OLD\_LEASE\_FQDN
- DHCP6\_DDNS\_RESPONSE\_FQDN\_DATA
- DHCP6\_DECLINE\_PROCESS\_IA
- DHCP6\_DHCP4O6\_RECEIVE\_FAIL
- DHCP6\_DHCP4O6\_RECEIVING
- DHCP6\_HOOK\_BUFFER\_RCVD\_SKIP
- DHCP6\_HOOK\_DECLINE\_SKIP
- DHCP6\_LEASE\_ADVERT

- DHCP6\_LEASE\_ADVERT\_FAIL
- DHCP6\_LEASE\_ALLOC
- DHCP6\_LEASE\_ALLOC\_FAIL
- DHCP6\_PACKET\_OPTIONS\_SKIPPED
- DHCP6\_PD\_LEASE\_ADVERT
- DHCP6\_PD\_LEASE\_ADVERT\_FAIL
- DHCP6\_PD\_LEASE\_ALLOC
- DHCP6\_PD\_LEASE\_ALLOC\_FAIL
- DHCP6\_PROCESS\_IA\_NA\_EXTEND
- DHCP6\_PROCESS\_IA\_NA\_RELEASE
- DHCP6\_PROCESS\_IA\_NA\_REQUEST
- DHCP6\_PROCESS\_IA\_NA\_SOLICIT
- DHCP6\_PROCESS\_IA\_PD\_EXTEND
- DHCP6\_PROCESS\_IA\_PD\_REQUEST
- DHCP6\_PROCESS\_IA\_PD\_SOLICIT
- DHCP6\_RAPID\_COMMIT
- DHCP6\_REQUIRED\_CLASS\_EVAL\_RESULT
- DHCP6\_SUBNET\_SELECTION\_FAILED
- DHCPSRV\_DHCP\_DDNS\_NCR\_SENT
- DHCPSRV\_EVAL\_RESULT
- DHCPSRV\_MEMFILE\_ADD\_ADDR4
- DHCPSRV\_MEMFILE\_ADD\_ADDR6
- DHCPSRV\_MEMFILE\_COMMIT
- DHCPSRV\_MEMFILE\_DELETE\_ADDR
- DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED4
- DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED6
- DHCPSRV\_MEMFILE\_DELETE\_EXPIRED\_RECLAIMED\_START
- DHCPSRV\_MEMFILE\_GET4
- DHCPSRV\_MEMFILE\_GET6
- DHCPSRV\_MEMFILE\_GET6\_DUID
- DHCPSRV\_MEMFILE\_GET\_ADDR4
- DHCPSRV\_MEMFILE\_GET\_ADDR6
- DHCPSRV\_MEMFILE\_GET\_CLIENTID
- DHCPSRV\_MEMFILE\_GET\_EXPIRED4
- DHCPSRV\_MEMFILE\_GET\_EXPIRED6
- DHCPSRV\_MEMFILE\_GET\_HOSTNAME4

- DHCPSRV\_MEMFILE\_GET\_HOSTNAME6
- DHCPSRV\_MEMFILE\_GET\_HWADDR
- DHCPSRV\_MEMFILE\_GET\_IAID\_DUID
- DHCPSRV\_MEMFILE\_GET\_IAID\_SUBID\_DUID
- DHCPSRV\_MEMFILE\_GET\_PAGE4
- DHCPSRV\_MEMFILE\_GET\_PAGE6
- DHCPSRV\_MEMFILE\_GET\_RELAYID4
- DHCPSRV\_MEMFILE\_GET\_RELAYID6
- DHCPSRV\_MEMFILE\_GET\_REMOTEID4
- DHCPSRV\_MEMFILE\_GET\_REMOTEID6
- DHCPSRV\_MEMFILE\_GET\_SUBID4
- DHCPSRV\_MEMFILE\_GET\_SUBID6
- DHCPSRV\_MEMFILE\_GET\_SUBID\_CLIENTID
- DHCPSRV\_MEMFILE\_GET\_SUBID\_HWADDR
- DHCPSRV\_MEMFILE\_GET\_SUBID\_PAGE6
- DHCPSRV\_MEMFILE\_ROLLBACK
- DHCPSRV\_MEMFILE\_UPDATE\_ADDR4
- DHCPSRV\_MEMFILE\_UPDATE\_ADDR6
- DHCPSRV\_MYSQL\_ADD\_ADDR4
- DHCPSRV\_MYSQL\_ADD\_ADDR6
- DHCPSRV\_MYSQL\_COMMIT
- DHCPSRV\_MYSQL\_DELETED\_EXPIRED\_RECLAIMED
- DHCPSRV\_MYSQL\_DELETE\_ADDR
- DHCPSRV\_MYSQL\_DELETE\_EXPIRED\_RECLAIMED4
- DHCPSRV\_MYSQL\_DELETE\_EXPIRED\_RECLAIMED6
- DHCPSRV\_MYSQL\_GET4
- DHCPSRV\_MYSQL\_GET6
- DHCPSRV\_MYSQL\_GET\_ADDR4
- DHCPSRV\_MYSQL\_GET\_ADDR6
- DHCPSRV\_MYSQL\_GET\_CLIENTID
- DHCPSRV\_MYSQL\_GET\_DUID
- DHCPSRV\_MYSQL\_GET\_EXPIRED4
- DHCPSRV\_MYSQL\_GET\_EXPIRED6
- DHCPSRV\_MYSQL\_GET\_HOSTNAME4
- DHCPSRV\_MYSQL\_GET\_HOSTNAME6
- DHCPSRV\_MYSQL\_GET\_HWADDR

- DHCPSRV\_MYSQL\_GET\_IAID\_DUID
- DHCPSRV\_MYSQL\_GET\_IAID\_SUBID\_DUID
- DHCPSRV\_MYSQL\_GET\_PAGE4
- DHCPSRV\_MYSQL\_GET\_PAGE6
- DHCPSRV\_MYSQL\_GET\_RELAYID4
- DHCPSRV\_MYSQL\_GET\_RELAYID6
- DHCPSRV\_MYSQL\_GET\_REMOTEID4
- DHCPSRV\_MYSQL\_GET\_REMOTEID6
- DHCPSRV\_MYSQL\_GET\_SUBID4
- DHCPSRV\_MYSQL\_GET\_SUBID6
- DHCPSRV\_MYSQL\_GET\_SUBID\_CLIENTID
- DHCPSRV\_MYSQL\_GET\_SUBID\_HWADDR
- DHCPSRV\_MYSQL\_GET\_SUBID\_PAGE6
- DHCPSRV\_MYSQL\_GET\_VERSION
- DHCPSRV\_MYSQL\_HOST\_DB
- DHCPSRV\_MYSQL\_HOST\_DB\_GET\_VERSION
- DHCPSRV\_MYSQL\_ROLLBACK
- DHCPSRV\_MYSQL\_UPDATE\_ADDR4
- DHCPSRV\_MYSQL\_UPDATE\_ADDR6
- DHCPSRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO4\_PAGE
- DHCPSRV\_MYSQL\_UPGRADE\_EXTENDED\_INFO6\_PAGE
- DHCPSRV\_PGSQL\_ADD\_ADDR4
- DHCPSRV\_PGSQL\_ADD\_ADDR6
- DHCPSRV\_PGSQL\_COMMIT
- DHCPSRV\_PGSQL\_DELETE\_ADDR
- DHCPSRV\_PGSQL\_DELETE\_EXPIRED\_RECLAIMED4
- DHCPSRV\_PGSQL\_DELETE\_EXPIRED\_RECLAIMED6
- DHCPSRV\_PGSQL\_GET4
- DHCPSRV\_PGSQL\_GET6
- DHCPSRV\_PGSQL\_GET\_ADDR4
- DHCPSRV\_PGSQL\_GET\_ADDR6
- DHCPSRV\_PGSQL\_GET\_CLIENTID
- DHCPSRV\_PGSQL\_GET\_DUID
- DHCPSRV\_PGSQL\_GET\_EXPIRED4
- DHCPSRV\_PGSQL\_GET\_EXPIRED6
- DHCPSRV\_PGSQL\_GET\_HOSTNAME4

- DHCPSRV\_PGSQL\_GET\_HOSTNAME6
- DHCPSRV\_PGSQL\_GET\_HWADDR
- DHCPSRV\_PGSQL\_GET\_IAID\_DUID
- DHCPSRV\_PGSQL\_GET\_IAID\_SUBID\_DUID
- DHCPSRV\_PGSQL\_GET\_PAGE4
- DHCPSRV\_PGSQL\_GET\_PAGE6
- DHCPSRV\_PGSQL\_GET\_RELAYID4
- DHCPSRV\_PGSQL\_GET\_RELAYID6
- DHCPSRV\_PGSQL\_GET\_REMOTEID4
- DHCPSRV\_PGSQL\_GET\_REMOTEID6
- DHCPSRV\_PGSQL\_GET\_SUBID4
- DHCPSRV\_PGSQL\_GET\_SUBID6
- DHCPSRV\_PGSQL\_GET\_SUBID\_CLIENTID
- DHCPSRV\_PGSQL\_GET\_SUBID\_HWADDR
- DHCPSRV\_PGSQL\_GET\_SUBID\_PAGE6
- DHCPSRV\_PGSQL\_GET\_VERSION
- DHCPSRV\_PGSQL\_HOST\_DB
- DHCPSRV\_PGSQL\_HOST\_DB\_GET\_VERSION
- DHCPSRV\_PGSQL\_ROLLBACK
- DHCPSRV\_PGSQL\_UPDATE\_ADDR4
- DHCPSRV\_PGSQL\_UPDATE\_ADDR6
- DHCPSRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO4\_PAGE
- DHCPSRV\_PGSQL\_UPGRADE\_EXTENDED\_INFO6\_PAGE
- DHCPSRV\_QUEUE\_NCR
- DHCPSRV\_QUEUE\_NCR\_SKIP
- DHCPSRV\_TEMPLATE\_EVAL\_RESULT
- DHCPSRV\_TIMERMGR\_RUN\_TIMER\_OPERATION
- DHCP\_DDNS\_INVALID\_RESPONSE
- DHCP\_DDNS\_STARTING\_TRANSACTION
- DHCP\_DDNS\_UPDATE\_REQUEST\_SENT
- DHCP\_DDNS\_UPDATE\_RESPONSE\_RECEIVED
- FUZZ\_DATA\_READ
- FUZZ\_SEND
- HTTPS\_REQUEST\_RECEIVE\_START
- HTTP\_CLIENT\_REQUEST\_SEND
- HTTP\_CLIENT\_REQUEST\_TIMEOUT\_OCCURRED

- HTTP\_CONNECTION\_HANDSHAKE\_START
- HTTP\_IDLE\_CONNECTION\_TIMEOUT\_OCCURRED
- HTTP\_REQUEST\_RECEIVE\_START
- PERFMON\_DHCP4\_PKT\_EVENTS
- PERFMON\_DHCP4\_PKT\_PROCESS\_ERROR
- PERFMON\_DHCP6\_PKT\_EVENTS
- PERFMON\_DHCP6\_PKT\_PROCESS\_ERROR
- TCP\_CONNECTION\_REJECTED\_BY\_FILTER
- TCP\_IDLE\_CONNECTION\_TIMEOUT\_OCCURRED
- TCP\_REQUEST\_RECEIVE\_START
- TLS\_CONNECTION\_HANDSHAKE\_START
- TLS\_REQUEST\_RECEIVE\_START

## 34.8 Messages printed on debuglevel 55

- ALLOC\_ENGINE\_V4\_REUSE\_EXPIRED\_LEASE\_DATA
- ALLOC\_ENGINE\_V6\_EXTEND\_LEASE\_DATA
- ALLOC\_ENGINE\_V6\_EXTEND\_NEW\_LEASE\_DATA
- ALLOC\_ENGINE\_V6\_REUSE\_EXPIRED\_LEASE\_DATA
- DHCP4\_CLIENT\_FQDN\_DATA
- DHCP4\_CLIENT\_HOSTNAME\_DATA
- DHCP4\_CLIENT\_NAME\_PROC\_FAIL
- DHCP4\_DHCP4O6\_RESPONSE\_DATA
- DHCP4\_DHCP4O6\_SUBNET\_DATA
- DHCP4\_GENERATE\_FQDN
- DHCP4\_QUERY\_DATA
- DHCP4\_RECOVERED\_STASHED\_RELAY\_AGENT\_INFO
- DHCP4\_RESERVED\_HOSTNAME\_ASSIGNED
- DHCP4\_RESPONSE\_DATA
- DHCP4\_RESPONSE\_FQDN\_DATA
- DHCP4\_RESPONSE\_HOSTNAME\_DATA
- DHCP4\_SUBNET\_DATA
- DHCP6\_DDNS\_FQDN\_GENERATED
- DHCP6\_DHCP4O6\_RESPONSE\_DATA
- DHCP6\_LEASE\_DATA
- DHCP6\_QUERY\_DATA

- DHCP6\_RESPONSE\_DATA
- DHCP6\_SUBNET\_DATA
- DHCP6\_SRV\_DDNS\_TTL\_PERCENT\_TOO\_SMALL
- DHCP6\_SRV\_MEMFILE\_LEASE\_LOAD
- DHCP6\_DDNS\_AT\_MAX\_TRANSACTIONS
- DHCP6\_DDNS\_FWD\_REQUEST\_IGNORED
- DHCP6\_DDNS\_NO\_ELIGIBLE\_JOBS
- DHCP6\_DDNS\_QUEUE\_MGR\_QUEUE\_RECEIVE
- DHCP6\_DDNS\_REQUEST\_DROPPED
- DHCP6\_DDNS\_REV\_REQUEST\_IGNORED
- EVAL\_DEBUG\_AND
- EVAL\_DEBUG\_BRANCH
- EVAL\_DEBUG\_CONCAT
- EVAL\_DEBUG\_EQUAL
- EVAL\_DEBUG\_HEXSTRING
- EVAL\_DEBUG\_IFELSE\_FALSE
- EVAL\_DEBUG\_IFELSE\_TRUE
- EVAL\_DEBUG\_INT16TOTEXT
- EVAL\_DEBUG\_INT32TOTEXT
- EVAL\_DEBUG\_INT8TOTEXT
- EVAL\_DEBUG\_IPADDRESS
- EVAL\_DEBUG\_IPADDRESSSTOTEXT
- EVAL\_DEBUG\_LCASE
- EVAL\_DEBUG\_MATCH
- EVAL\_DEBUG\_MEMBER
- EVAL\_DEBUG\_NOT
- EVAL\_DEBUG\_OPTION
- EVAL\_DEBUG\_OR
- EVAL\_DEBUG\_PKT
- EVAL\_DEBUG\_PKT4
- EVAL\_DEBUG\_PKT6
- EVAL\_DEBUG\_POP\_AND\_BRANCH\_FALSE
- EVAL\_DEBUG\_POP\_OR\_BRANCH\_FALSE
- EVAL\_DEBUG\_POP\_OR\_BRANCH\_TRUE
- EVAL\_DEBUG\_RELAY6
- EVAL\_DEBUG\_RELAY6\_RANGE



- EVAL\_DEBUG\_SPLIT
- EVAL\_DEBUG\_SPLIT\_DELIM\_EMPTY
- EVAL\_DEBUG\_SPLIT\_EMPTY
- EVAL\_DEBUG\_SPLIT\_FIELD\_OUT\_OF\_RANGE
- EVAL\_DEBUG\_STRING
- EVAL\_DEBUG\_SUBSTRING
- EVAL\_DEBUG\_SUBSTRING\_EMPTY
- EVAL\_DEBUG\_SUBSTRING\_RANGE
- EVAL\_DEBUG\_TOHEXSTRING
- EVAL\_DEBUG\_UCASE
- EVAL\_DEBUG\_UINT16TOTEXT
- EVAL\_DEBUG\_UINT32TOTEXT
- EVAL\_DEBUG\_UINT8TOTEXT
- EVAL\_DEBUG\_VENDOR\_CLASS\_DATA
- EVAL\_DEBUG\_VENDOR\_CLASS\_DATA\_NOT\_FOUND
- EVAL\_DEBUG\_VENDOR\_CLASS\_ENTERPRISE\_ID
- EVAL\_DEBUG\_VENDOR\_CLASS\_ENTERPRISE\_ID\_MISMATCH
- EVAL\_DEBUG\_VENDOR\_CLASS\_EXISTS
- EVAL\_DEBUG\_VENDOR\_CLASS\_NO\_OPTION
- EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID
- EVAL\_DEBUG\_VENDOR\_ENTERPRISE\_ID\_MISMATCH
- EVAL\_DEBUG\_VENDOR\_EXISTS
- EVAL\_DEBUG\_VENDOR\_NO\_OPTION
- HOOKS\_ALL\_CALLOUTS\_DEREGISTERED
- HOOKS\_CALLOUT\_CALLED
- HOOKS\_CALLOUT\_DEREGISTERED
- HOSTS\_CFG\_GET\_ALL\_ADDRESS4\_HOST
- HOSTS\_CFG\_GET\_ALL\_ADDRESS6\_HOST
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_HOST
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID4\_HOST
- HOSTS\_CFG\_GET\_ALL\_HOSTNAME\_SUBNET\_ID6\_HOST
- HOSTS\_CFG\_GET\_ALL\_IDENTIFIER\_HOST
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID4\_HOST
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID6\_HOST
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS4\_HOST
- HOSTS\_CFG\_GET\_ALL\_SUBNET\_ID\_ADDRESS6\_HOST

- HOSTS\_CFG\_GET\_ONE\_PREFIX\_HOST
- HOSTS\_CFG\_GET\_ONE\_PREFIX\_NULL
- HTTP\_CLIENT\_REQUEST\_SEND\_DETAILS
- HTTP\_DATA\_RECEIVED
- NETCONF\_CONFIG\_CHANGED\_DETAIL
- NETCONF\_GET\_CONFIG
- NETCONF\_SET\_CONFIG
- NETCONF\_UPDATE\_CONFIG
- NETCONF\_VALIDATE\_CONFIG
- TCP\_DATA\_RECEIVED
- TCP\_DATA\_SENT

## 34.9 Messages printed on debuglevel 70

- ASIODNS\_FETCH\_COMPLETED