



Kea Messages Manual

Release 3.3.3

Internet Systems Consortium

Oct 26, 2026

CONTENTS

1	ALLOC	3
1.1	ALLOC_ENGINE_IGNOREING_UNSUITABLE_GLOBAL_ADDRESS	3
1.2	ALLOC_ENGINE_IGNOREING_UNSUITABLE_GLOBAL_ADDRESS6	3
1.3	ALLOC_ENGINE_LEASE_RECLAIMED	3
1.4	ALLOC_ENGINE_V4_ALLOC_ERROR	3
1.5	ALLOC_ENGINE_V4_ALLOC_FAIL	3
1.6	ALLOC_ENGINE_V4_ALLOC_FAIL_CLASSES	4
1.7	ALLOC_ENGINE_V4_ALLOC_FAIL_NO_POOLS	4
1.8	ALLOC_ENGINE_V4_ALLOC_FAIL_SHARED_NETWORK	4
1.9	ALLOC_ENGINE_V4_ALLOC_FAIL_SUBNET	4
1.10	ALLOC_ENGINE_V4_DECLINED_RECOVERED	5
1.11	ALLOC_ENGINE_V4_DISCOVER_ADDRESS_CONFLICT	5
1.12	ALLOC_ENGINE_V4_DISCOVER_HR	5
1.13	ALLOC_ENGINE_V4_LEASES_RECLAMATION_COMPLETE	5
1.14	ALLOC_ENGINE_V4_LEASES_RECLAMATION_FAILED	5
1.15	ALLOC_ENGINE_V4_LEASES_RECLAMATION_SLOW	5
1.16	ALLOC_ENGINE_V4_LEASES_RECLAMATION_START	6
1.17	ALLOC_ENGINE_V4_LEASES_RECLAMATION_TIMEOUT	6
1.18	ALLOC_ENGINE_V4_LEASE_RECLAIM	6
1.19	ALLOC_ENGINE_V4_LEASE_RECLAMATION_FAILED	6
1.20	ALLOC_ENGINE_V4_NO_MORE_EXPIRED_LEASES	6
1.21	ALLOC_ENGINE_V4_OFFER_EXISTING_LEASE	6
1.22	ALLOC_ENGINE_V4_OFFER_NEW_LEASE	7
1.23	ALLOC_ENGINE_V4_OFFER_REQUESTED_LEASE	7
1.24	ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE	7
1.25	ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE_COMPLETE	7
1.26	ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE_FAILED	7
1.27	ALLOC_ENGINE_V4_REQUEST_ADDRESS_RESERVED	7
1.28	ALLOC_ENGINE_V4_REQUEST_ALLOC_REQUESTED	7
1.29	ALLOC_ENGINE_V4_REQUEST_EXTEND_LEASE	8
1.30	ALLOC_ENGINE_V4_REQUEST_INVALID	8
1.31	ALLOC_ENGINE_V4_REQUEST_IN_USE	8
1.32	ALLOC_ENGINE_V4_REQUEST_OUT_OF_POOL	8
1.33	ALLOC_ENGINE_V4_REQUEST_PICK_ADDRESS	8
1.34	ALLOC_ENGINE_V4_REQUEST_REMOVE_LEASE	8
1.35	ALLOC_ENGINE_V4_REQUEST_USE_HR	8
1.36	ALLOC_ENGINE_V4_REUSE_EXPIRED_LEASE_DATA	9
1.37	ALLOC_ENGINE_V6_ALLOC_ERROR	9
1.38	ALLOC_ENGINE_V6_ALLOC_FAIL	9
1.39	ALLOC_ENGINE_V6_ALLOC_FAIL_CLASSES	9

1.40	ALLOC_ENGINE_V6_ALLOC_FAIL_NO_POOLS	9
1.41	ALLOC_ENGINE_V6_ALLOC_FAIL_SHARED_NETWORK	10
1.42	ALLOC_ENGINE_V6_ALLOC_FAIL_SUBNET	10
1.43	ALLOC_ENGINE_V6_ALLOC_HR_LEASE_EXISTS	10
1.44	ALLOC_ENGINE_V6_ALLOC_LEASES_HR	10
1.45	ALLOC_ENGINE_V6_ALLOC_LEASES_NO_HR	10
1.46	ALLOC_ENGINE_V6_ALLOC_NO_LEASES_HR	11
1.47	ALLOC_ENGINE_V6_ALLOC_NO_V6_HR	11
1.48	ALLOC_ENGINE_V6_ALLOC_UNRESERVED	11
1.49	ALLOC_ENGINE_V6_CALCULATED_PREFERRED_LIFETIME	11
1.50	ALLOC_ENGINE_V6_DECLINED_RECOVERED	11
1.51	ALLOC_ENGINE_V6_EXPIRED_HINT_RESERVED	11
1.52	ALLOC_ENGINE_V6_EXTEND_ALLOC_UNRESERVED	12
1.53	ALLOC_ENGINE_V6_EXTEND_ERROR	12
1.54	ALLOC_ENGINE_V6_EXTEND_LEASE	12
1.55	ALLOC_ENGINE_V6_EXTEND_LEASE_DATA	12
1.56	ALLOC_ENGINE_V6_EXTEND_NEW_LEASE_DATA	12
1.57	ALLOC_ENGINE_V6_HINT_RESERVED	12
1.58	ALLOC_ENGINE_V6_HR_ADDR_GRANTED	13
1.59	ALLOC_ENGINE_V6_HR_PREFIX_GRANTED	13
1.60	ALLOC_ENGINE_V6_LEASES_RECLAMATION_COMPLETE	13
1.61	ALLOC_ENGINE_V6_LEASES_RECLAMATION_FAILED	13
1.62	ALLOC_ENGINE_V6_LEASES_RECLAMATION_SLOW	13
1.63	ALLOC_ENGINE_V6_LEASES_RECLAMATION_START	13
1.64	ALLOC_ENGINE_V6_LEASES_RECLAMATION_TIMEOUT	14
1.65	ALLOC_ENGINE_V6_LEASE_RECLAIM	14
1.66	ALLOC_ENGINE_V6_LEASE_RECLAMATION_FAILED	14
1.67	ALLOC_ENGINE_V6_NO_MORE_EXPIRED_LEASES	14
1.68	ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE	14
1.69	ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE_COMPLETE	14
1.70	ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE_FAILED	15
1.71	ALLOC_ENGINE_V6_RENEW_HR	15
1.72	ALLOC_ENGINE_V6_RENEW_REMOVE_RESERVED	15
1.73	ALLOC_ENGINE_V6_REUSE_EXPIRED_LEASE_DATA	15
1.74	ALLOC_ENGINE_V6_REVOKED_ADDR_LEASE	15
1.75	ALLOC_ENGINE_V6_REVOKED_PREFIX_LEASE	15
1.76	ALLOC_ENGINE_V6_REVOKED_SHARED_ADDR_LEASE	16
1.77	ALLOC_ENGINE_V6_REVOKED_SHARED_PREFIX_LEASE	16
2	ASIODNS	17
2.1	ASIODNS_FETCH_COMPLETED	17
2.2	ASIODNS_FETCH_STOPPED	17
2.3	ASIODNS_OPEN_SOCKET	17
2.4	ASIODNS_READ_DATA	17
2.5	ASIODNS_READ_TIMEOUT	17
2.6	ASIODNS_SEND_DATA	18
2.7	ASIODNS_UNKNOWN_ORIGIN	18
2.8	ASIODNS_UNKNOWN_RESULT	18
3	BAD	19
3.1	BAD_CLIENT_CREDENTIALS	19
4	BOOTP	21
4.1	BOOTP_BOOTP_QUERY	21

4.2	BOOTP_LOAD	21
4.3	BOOTP_PACKET_OPTIONS_SKIPPED	21
4.4	BOOTP_PACKET_PACK	21
4.5	BOOTP_PACKET_PACK_FAIL	21
4.6	BOOTP_PACKET_UNPACK_FAILED	22
4.7	BOOTP_UNLOAD	22
5	BULK	23
5.1	BULK_LEASE_QUERY4_UNSUPPORTED_MSG_TYPE	23
5.2	BULK_LEASE_QUERY6_UNSUPPORTED_MSG_TYPE	23
5.3	BULK_LEASE_QUERY_AT_MAX_CONCURRENT_QUERIES	23
5.4	BULK_LEASE_QUERY_DEQUEUED	23
5.5	BULK_LEASE_QUERY_DUPLICATE_XID	23
5.6	BULK_LEASE_QUERY_EMPTY_REQUEST	24
5.7	BULK_LEASE_QUERY_INVALID_REQUEST	24
5.8	BULK_LEASE_QUERY_LISTENER_START_FAILED	24
5.9	BULK_LEASE_QUERY_PAUSE_CHECK_PERMISSIONS_FAILED	24
5.10	BULK_LEASE_QUERY_PAUSE_LISTENER_FAILED	24
5.11	BULK_LEASE_QUERY_PAUSE_LISTENER_ILLEGAL	24
5.12	BULK_LEASE_QUERY_PROCESSING_UNEXPECTED_FAILURE	24
5.13	BULK_LEASE_QUERY_QUERY_RECEIVED	25
5.14	BULK_LEASE_QUERY_REJECTED_CONNECTION	25
5.15	BULK_LEASE_QUERY_RESPONSE_SEND_ERROR	25
5.16	BULK_LEASE_QUERY_RESPONSE_SENT	25
5.17	BULK_LEASE_QUERY_RESUME_LISTENER_FAILED	25
5.18	BULK_LEASE_QUERY_UNPACK_ERROR	25
6	CB	27
6.1	CB_CMDS_CLASS4_DEL_HANDLER_FAILED	27
6.2	CB_CMDS_CLASS4_GET_ALL_HANDLER_FAILED	27
6.3	CB_CMDS_CLASS4_GET_HANDLER_FAILED	27
6.4	CB_CMDS_CLASS4_SET_HANDLER_FAILED	27
6.5	CB_CMDS_CLASS6_DEL_HANDLER_FAILED	27
6.6	CB_CMDS_CLASS6_GET_ALL_HANDLER_FAILED	28
6.7	CB_CMDS_CLASS6_GET_HANDLER_FAILED	28
6.8	CB_CMDS_CLASS6_SET_HANDLER_FAILED	28
6.9	CB_CMDS_DEINIT_OK	28
6.10	CB_CMDS_GLOBAL_PARAMETER4_DEL_HANDLER_FAILED	28
6.11	CB_CMDS_GLOBAL_PARAMETER4_GET_ALL_HANDLER_FAILED	28
6.12	CB_CMDS_GLOBAL_PARAMETER4_GET_HANDLER_FAILED	28
6.13	CB_CMDS_GLOBAL_PARAMETER4_SET_HANDLER_FAILED	29
6.14	CB_CMDS_GLOBAL_PARAMETER6_DEL_HANDLER_FAILED	29
6.15	CB_CMDS_GLOBAL_PARAMETER6_GET_ALL_HANDLER_FAILED	29
6.16	CB_CMDS_GLOBAL_PARAMETER6_GET_HANDLER_FAILED	29
6.17	CB_CMDS_GLOBAL_PARAMETER6_SET_HANDLER_FAILED	29
6.18	CB_CMDS_INIT_OK	29
6.19	CB_CMDS_NETWORK4_DEL_HANDLER_FAILED	29
6.20	CB_CMDS_NETWORK4_GET_HANDLER_FAILED	30
6.21	CB_CMDS_NETWORK4_LIST_HANDLER_FAILED	30
6.22	CB_CMDS_NETWORK4_SET_HANDLER_FAILED	30
6.23	CB_CMDS_NETWORK6_DEL_HANDLER_FAILED	30
6.24	CB_CMDS_NETWORK6_GET_HANDLER_FAILED	30
6.25	CB_CMDS_NETWORK6_LIST_HANDLER_FAILED	30
6.26	CB_CMDS_NETWORK6_SET_HANDLER_FAILED	30

6.27	CB_CMDS_OPTION4_GLOBAL_DEL_HANDLER_FAILED	31
6.28	CB_CMDS_OPTION4_GLOBAL_GET_ALL_HANDLER_FAILED	31
6.29	CB_CMDS_OPTION4_GLOBAL_GET_HANDLER_FAILED	31
6.30	CB_CMDS_OPTION4_GLOBAL_SET_HANDLER_FAILED	31
6.31	CB_CMDS_OPTION4_NETWORK_DEL_HANDLER_FAILED	31
6.32	CB_CMDS_OPTION4_NETWORK_SET_HANDLER_FAILED	31
6.33	CB_CMDS_OPTION4_POOL_DEL_HANDLER_FAILED	31
6.34	CB_CMDS_OPTION4_POOL_SET_HANDLER_FAILED	32
6.35	CB_CMDS_OPTION4_SUBNET_DEL_HANDLER_FAILED	32
6.36	CB_CMDS_OPTION4_SUBNET_SET_HANDLER_FAILED	32
6.37	CB_CMDS_OPTION6_GLOBAL_DEL_HANDLER_FAILED	32
6.38	CB_CMDS_OPTION6_GLOBAL_GET_ALL_HANDLER_FAILED	32
6.39	CB_CMDS_OPTION6_GLOBAL_GET_HANDLER_FAILED	32
6.40	CB_CMDS_OPTION6_GLOBAL_SET_HANDLER_FAILED	32
6.41	CB_CMDS_OPTION6_NETWORK_DEL_HANDLER_FAILED	33
6.42	CB_CMDS_OPTION6_NETWORK_SET_HANDLER_FAILED	33
6.43	CB_CMDS_OPTION6_PD_POOL_DEL_HANDLER_FAILED	33
6.44	CB_CMDS_OPTION6_PD_POOL_SET_HANDLER_FAILED	33
6.45	CB_CMDS_OPTION6_POOL_DEL_HANDLER_FAILED	33
6.46	CB_CMDS_OPTION6_POOL_SET_HANDLER_FAILED	33
6.47	CB_CMDS_OPTION6_SUBNET_DEL_HANDLER_FAILED	33
6.48	CB_CMDS_OPTION6_SUBNET_SET_HANDLER_FAILED	34
6.49	CB_CMDS_OPTION_DEF4_DEL_HANDLER_FAILED	34
6.50	CB_CMDS_OPTION_DEF4_GET_ALL_HANDLER_FAILED	34
6.51	CB_CMDS_OPTION_DEF4_GET_HANDLER_FAILED	34
6.52	CB_CMDS_OPTION_DEF4_SET_HANDLER_FAILED	34
6.53	CB_CMDS_OPTION_DEF6_DEL_HANDLER_FAILED	34
6.54	CB_CMDS_OPTION_DEF6_GET_ALL_HANDLER_FAILED	34
6.55	CB_CMDS_OPTION_DEF6_GET_HANDLER_FAILED	35
6.56	CB_CMDS_OPTION_DEF6_SET_HANDLER_FAILED	35
6.57	CB_CMDS_SERVER4_DEL_HANDLER_FAILED	35
6.58	CB_CMDS_SERVER4_GET_ALL_HANDLER_FAILED	35
6.59	CB_CMDS_SERVER4_GET_HANDLER_FAILED	35
6.60	CB_CMDS_SERVER4_SET_HANDLER_FAILED	35
6.61	CB_CMDS_SERVER6_DEL_HANDLER_FAILED	35
6.62	CB_CMDS_SERVER6_GET_ALL_HANDLER_FAILED	36
6.63	CB_CMDS_SERVER6_GET_HANDLER_FAILED	36
6.64	CB_CMDS_SERVER6_SET_HANDLER_FAILED	36
6.65	CB_CMDS_SUBNET4_DEL_BY_ID_HANDLER_FAILED	36
6.66	CB_CMDS_SUBNET4_DEL_BY_PREFIX_HANDLER_FAILED	36
6.67	CB_CMDS_SUBNET4_GET_BY_ID_HANDLER_FAILED	36
6.68	CB_CMDS_SUBNET4_GET_BY_PREFIX_HANDLER_FAILED	36
6.69	CB_CMDS_SUBNET4_LIST_HANDLER_FAILED	37
6.70	CB_CMDS_SUBNET4_SET_HANDLER_FAILED	37
6.71	CB_CMDS_SUBNET6_DEL_BY_ID_HANDLER_FAILED	37
6.72	CB_CMDS_SUBNET6_DEL_BY_PREFIX_HANDLER_FAILED	37
6.73	CB_CMDS_SUBNET6_GET_BY_ID_HANDLER_FAILED	37
6.74	CB_CMDS_SUBNET6_GET_BY_PREFIX_HANDLER_FAILED	37
6.75	CB_CMDS_SUBNET6_LIST_HANDLER_FAILED	37
6.76	CB_CMDS_SUBNET6_SET_HANDLER_FAILED	38
7	CLASS	39
7.1	CLASS_CMDS_CLASS_ADD	39
7.2	CLASS_CMDS_CLASS_ADD_FAILED	39

7.3	CLASS_CMDS_CLASS_ADD_HANDLER_FAILED	39
7.4	CLASS_CMDS_CLASS_DEL	39
7.5	CLASS_CMDS_CLASS_DEL_EMPTY	39
7.6	CLASS_CMDS_CLASS_DEL_FAILED	39
7.7	CLASS_CMDS_CLASS_DEL_HANDLER_FAILED	40
7.8	CLASS_CMDS_CLASS_GET	40
7.9	CLASS_CMDS_CLASS_GET_EMPTY	40
7.10	CLASS_CMDS_CLASS_GET_FAILED	40
7.11	CLASS_CMDS_CLASS_GET_HANDLER_FAILED	40
7.12	CLASS_CMDS_CLASS_LIST	40
7.13	CLASS_CMDS_CLASS_LIST_EMPTY	40
7.14	CLASS_CMDS_CLASS_LIST_FAILED	40
7.15	CLASS_CMDS_CLASS_LIST_HANDLER_FAILED	41
7.16	CLASS_CMDS_CLASS_UPDATE	41
7.17	CLASS_CMDS_CLASS_UPDATE_EMPTY	41
7.18	CLASS_CMDS_CLASS_UPDATE_FAILED	41
7.19	CLASS_CMDS_CLASS_UPDATE_HANDLER_FAILED	41
7.20	CLASS_CMDS_DEINIT_OK	41
7.21	CLASS_CMDS_INIT_FAILED	41
7.22	CLASS_CMDS_INIT_OK	41
8	COMMAND	43
8.1	COMMAND_ACCEPTOR_START	43
8.2	COMMAND_DEREGISTERED	43
8.3	COMMAND_EXTENDED_REGISTERED	43
8.4	COMMAND_HTTP_LISTENER_COMMAND_REJECTED	43
8.5	COMMAND_HTTP_LISTENER_STARTED	43
8.6	COMMAND_HTTP_LISTENER_STOPPED	44
8.7	COMMAND_HTTP_LISTENER_STOPPING	44
8.8	COMMAND_HTTP_SOCKET_SECURITY_WARNING	44
8.9	COMMAND_PROCESS_ERROR1	44
8.10	COMMAND_PROCESS_ERROR2	44
8.11	COMMAND_RECEIVED	44
8.12	COMMAND_REGISTERED	44
8.13	COMMAND_RESPONSE_ERROR	45
8.14	COMMAND_SOCKET_ACCEPT_FAIL	45
8.15	COMMAND_SOCKET_CLOSED_BY_FOREIGN_HOST	45
8.16	COMMAND_SOCKET_CONNECTION_CANCEL_FAIL	45
8.17	COMMAND_SOCKET_CONNECTION_CLOSED	45
8.18	COMMAND_SOCKET_CONNECTION_CLOSE_FAIL	45
8.19	COMMAND_SOCKET_CONNECTION_OPENED	45
8.20	COMMAND_SOCKET_CONNECTION_SHUTDOWN_FAIL	46
8.21	COMMAND_SOCKET_CONNECTION_TIMEOUT	46
8.22	COMMAND_SOCKET_READ	46
8.23	COMMAND_SOCKET_READ_FAIL	46
8.24	COMMAND_SOCKET_WRITE	46
8.25	COMMAND_SOCKET_WRITE_FAIL	46
8.26	COMMAND_UNIX_SOCKET_PATH_SECURITY_WARNING	46
8.27	COMMAND_UNIX_SOCKET_PERMISSIONS_SECURITY_WARNING	47
8.28	COMMAND_WATCH_SOCKET_CLEAR_ERROR	47
8.29	COMMAND_WATCH_SOCKET_CLOSE_ERROR	47
8.30	COMMAND_WATCH_SOCKET_MARK_READY_ERROR	47
9	CONFIG	49

9.1	CONFIG_BACKENDS_REGISTERED	49
10	DATABASE	51
10.1	DATABASE_INVALID_ACCESS	51
10.2	DATABASE_MYSQL_COMMIT	51
10.3	DATABASE_MYSQL_FATAL_ERROR	51
10.4	DATABASE_MYSQL_INITIALIZE_SCHEMA	51
10.5	DATABASE_MYSQL_INITIAL_CONNECTION_FAIL	51
10.6	DATABASE_MYSQL_NO_INIT_NO_ADMIN	52
10.7	DATABASE_MYSQL_NO_INIT_NO_PASSWORD	52
10.8	DATABASE_MYSQL_NO_INIT_READONLY	52
10.9	DATABASE_MYSQL_ROLLBACK	52
10.10	DATABASE_MYSQL_START_TRANSACTION	52
10.11	DATABASE_PGSQL_COMMIT	52
10.12	DATABASE_PGSQL_CREATE_SAVEPOINT	52
10.13	DATABASE_PGSQL_DEALLOC_ERROR	53
10.14	DATABASE_PGSQL_FATAL_ERROR	53
10.15	DATABASE_PGSQL_INITIALIZE_SCHEMA	53
10.16	DATABASE_PGSQL_INITIAL_CONNECTION_FAIL	53
10.17	DATABASE_PGSQL_NO_INIT_NO_ADMIN	53
10.18	DATABASE_PGSQL_NO_INIT_NO_PASSWORD	53
10.19	DATABASE_PGSQL_NO_INIT_READONLY	53
10.20	DATABASE_PGSQL_ROLLBACK	54
10.21	DATABASE_PGSQL_ROLLBACK_SAVEPOINT	54
10.22	DATABASE_PGSQL_START_TRANSACTION	54
10.23	DATABASE_PGSQL_TCP_USER_TIMEOUT_UNSUPPORTED	54
10.24	DATABASE_TO_JSON_BOOLEAN_ERROR	54
10.25	DATABASE_TO_JSON_INTEGER_ERROR	54
10.26	DATABASE_TO_JSON_UNKNOWN_TYPE_ERROR	54
11	DCTL	57
11.1	DCTL_ALREADY_RUNNING	57
11.2	DCTL_CFG_FILE_RELOAD_ERROR	57
11.3	DCTL_CFG_FILE_RELOAD_SIGNAL_RECVD	57
11.4	DCTL_CONFIG_CHECK_COMPLETE	57
11.5	DCTL_CONFIG_COMPLETE	57
11.6	DCTL_CONFIG_DEPRECATED	58
11.7	DCTL_CONFIG_FETCH	58
11.8	DCTL_CONFIG_FILE_LOAD_FAIL	58
11.9	DCTL_CONFIG_START	58
11.10	DCTL_DB_OPEN_CONNECTION_WITH_RETRY_FAILED	58
11.11	DCTL_DEPRECATED_OUTPUT_OPTIONS	58
11.12	DCTL_DEVELOPMENT_VERSION	58
11.13	DCTL_INIT_PROCESS	59
11.14	DCTL_INIT_PROCESS_FAIL	59
11.15	DCTL_LOG_PATH_SECURITY_WARNING	59
11.16	DCTL_NOT_RUNNING	59
11.17	DCTL_OPEN_CONFIG_DB	59
11.18	DCTL_PARSER_FAIL	59
11.19	DCTL_PID_FILE_ERROR	59
11.20	DCTL_PROCESS_FAILED	60
11.21	DCTL_ROOT_USER_SECURITY_WARNING	60
11.22	DCTL_RUN_PROCESS	60
11.23	DCTL_SHUTDOWN	60

11.24	DCTL_SHUTDOWN_SIGNAL_RECVD	60
11.25	DCTL_STANDALONE	60
11.26	DCTL_STARTING	60
11.27	DCTL_UNLOAD_LIBRARIES_ERROR	61
11.28	DCTL_UNSUPPORTED_SIGNAL	61
12	DDNS	63
12.1	DDNS_TUNING4_CALCULATED_HOSTNAME	63
12.2	DDNS_TUNING4_PROCESS_ERROR	63
12.3	DDNS_TUNING4_SKIPPING_DDNS	63
12.4	DDNS_TUNING6_CALCULATED_HOSTNAME	63
12.5	DDNS_TUNING6_PROCESS_ERROR	63
12.6	DDNS_TUNING6_SKIPPING_DDNS	64
12.7	DDNS_TUNING_GLOBAL_EXPR_SET	64
12.8	DDNS_TUNING_LOAD_ERROR	64
12.9	DDNS_TUNING_LOAD_OK	64
12.10	DDNS_TUNING_SUBNET_EXPRESSION_PARSE	64
12.11	DDNS_TUNING_SUBNET_EXPRESSION_PARSE_ERROR	64
12.12	DDNS_TUNING_SUBNET_EXPR_CACHED	64
12.13	DDNS_TUNING_UNLOAD	65
13	DHCP4	67
13.1	DHCP4_ADDITIONAL_CLASS_EVAL_ERROR	67
13.2	DHCP4_ADDITIONAL_CLASS_EVAL_RESULT	67
13.3	DHCP4_ADDITIONAL_CLASS_NO_TEST	67
13.4	DHCP4_ADDITIONAL_CLASS_UNDEFINED	67
13.5	DHCP4_ALREADY_RUNNING	67
13.6	DHCP4_BUFFER_RECEIVED	68
13.7	DHCP4_BUFFER_RECEIVE_FAIL	68
13.8	DHCP4_BUFFER_UNPACK	68
13.9	DHCP4_BUFFER_WAIT_SIGNAL	68
13.10	DHCP4_CB_ON_DEMAND_FETCH_UPDATES_FAIL	68
13.11	DHCP4_CB_PERIODIC_FETCH_UPDATES_FAIL	68
13.12	DHCP4_CB_PERIODIC_FETCH_UPDATES_RETRIES_EXHAUSTED	68
13.13	DHCP4_CB_REPAIR_MODE_ENABLED	69
13.14	DHCP4_CLASSES_ASSIGNED	69
13.15	DHCP4_CLASSES_ASSIGNED_AFTER_SUBNET_SELECTION	69
13.16	DHCP4_CLASS_ASSIGNED	69
13.17	DHCP4_CLASS_UNCONFIGURED	69
13.18	DHCP4_CLIENTID_FORCED_USE_FOR_LEASES	69
13.19	DHCP4_CLIENTID_IGNORED_FOR_LEASES	70
13.20	DHCP4_CLIENT_FQDN_DATA	70
13.21	DHCP4_CLIENT_FQDN_PROCESS	70
13.22	DHCP4_CLIENT_FQDN_SCRUBBED_EMPTY	70
13.23	DHCP4_CLIENT_HOSTNAME_DATA	70
13.24	DHCP4_CLIENT_HOSTNAME_MALFORMED	70
13.25	DHCP4_CLIENT_HOSTNAME_PROCESS	71
13.26	DHCP4_CLIENT_HOSTNAME_SCRUBBED_EMPTY	71
13.27	DHCP4_CLIENT_NAME_PROC_FAIL	71
13.28	DHCP4_CONFIG_COMPLETE	71
13.29	DHCP4_CONFIG_HOSTS_DATABASE_DEPRECATED	71
13.30	DHCP4_CONFIG_LOAD_FAIL	71
13.31	DHCP4_CONFIG_PACKET_QUEUE	72
13.32	DHCP4_CONFIG_RECEIVED	72

13.33 DHCP4_CONFIG_START	72
13.34 DHCP4_CONFIG_SYNTAX_WARNING	72
13.35 DHCP4_CONFIG_UNRECOVERABLE_ERROR	72
13.36 DHCP4_CONFIG_UNSUPPORTED_OBJECT	72
13.37 DHCP4_DB_RECONNECT_DISABLED	72
13.38 DHCP4_DB_RECONNECT_FAILED	73
13.39 DHCP4_DB_RECONNECT_LOST_CONNECTION	73
13.40 DHCP4_DB_RECONNECT_NO_DB_CTL	73
13.41 DHCP4_DB_RECONNECT_SUCCEEDED	73
13.42 DHCP4_DDNS_REQUEST_SEND_FAILED	73
13.43 DHCP4_DECLINE_FAIL	73
13.44 DHCP4_DECLINE_LEASE	73
13.45 DHCP4_DECLINE_LEASE_MISMATCH	74
13.46 DHCP4_DECLINE_LEASE_NOT_FOUND	74
13.47 DHCP4_DEFERRED_OPTION_MISSING	74
13.48 DHCP4_DEFERRED_OPTION_UNPACK_FAIL	74
13.49 DHCP4_DEVELOPMENT_VERSION	74
13.50 DHCP4_DHCP4O6_BAD_PACKET	74
13.51 DHCP4_DHCP4O6_HOOK_SUBNET4_SELECT_DROP	74
13.52 DHCP4_DHCP4O6_HOOK_SUBNET4_SELECT_SKIP	75
13.53 DHCP4_DHCP4O6_PACKET_RECEIVED	75
13.54 DHCP4_DHCP4O6_PACKET_SEND	75
13.55 DHCP4_DHCP4O6_PACKET_SEND_FAIL	75
13.56 DHCP4_DHCP4O6_RECEIVE_FAIL	75
13.57 DHCP4_DHCP4O6_RECEIVING	75
13.58 DHCP4_DHCP4O6_RESPONSE_DATA	75
13.59 DHCP4_DHCP4O6_SUBNET_DATA	76
13.60 DHCP4_DHCP4O6_SUBNET_SELECTED	76
13.61 DHCP4_DHCP4O6_SUBNET_SELECTION_FAILED	76
13.62 DHCP4_DISCOVER	76
13.63 DHCP4_DYNAMIC_RECONFIGURATION	76
13.64 DHCP4_DYNAMIC_RECONFIGURATION_FAIL	76
13.65 DHCP4_DYNAMIC_RECONFIGURATION_SUCCESS	76
13.66 DHCP4_EMPTY_HOSTNAME	77
13.67 DHCP4_FATAL_DB_RECONNECT_DISABLED	77
13.68 DHCP4_FATAL_DB_RECONNECT_FAILED	77
13.69 DHCP4_FATAL_DYNAMIC_RECONFIGURATION_FAIL	77
13.70 DHCP4_FATAL_OPEN_SOCKETS_FAILED	77
13.71 DHCP4_FLEX_ID	77
13.72 DHCP4_GENERATE_FQDN	77
13.73 DHCP4_HOOK_BUFFER_RCVD_DROP	78
13.74 DHCP4_HOOK_BUFFER_RCVD_SKIP	78
13.75 DHCP4_HOOK_BUFFER_SEND_SKIP	78
13.76 DHCP4_HOOK_DDNS_UPDATE	78
13.77 DHCP4_HOOK_DECLINE_SKIP	78
13.78 DHCP4_HOOK_LEASE4_OFFER_ARGUMENT_MISSING	78
13.79 DHCP4_HOOK_LEASE4_OFFER_DROP	79
13.80 DHCP4_HOOK_LEASE4_OFFER_PARK	79
13.81 DHCP4_HOOK_LEASE4_OFFER_PARKING_LOT_FULL	79
13.82 DHCP4_HOOK_LEASE4_RELEASE_SKIP	79
13.83 DHCP4_HOOK_LEASES4_COMMITTED_DROP	79
13.84 DHCP4_HOOK_LEASES4_COMMITTED_PARK	79
13.85 DHCP4_HOOK_LEASES4_COMMITTED_PARKING_LOT_FULL	79
13.86 DHCP4_HOOK_PACKET_RCVD_SKIP	80

13.87	DHCP4_HOOK_PACKET_SEND_DROP	80
13.88	DHCP4_HOOK_PACKET_SEND_SKIP	80
13.89	DHCP4_HOOK_SUBNET4_SELECT_406_PARKING_LOT_FULL	80
13.90	DHCP4_HOOK_SUBNET4_SELECT_DROP	80
13.91	DHCP4_HOOK_SUBNET4_SELECT_PARK	80
13.92	DHCP4_HOOK_SUBNET4_SELECT_PARKING_LOT_FULL	81
13.93	DHCP4_HOOK_SUBNET4_SELECT_SKIP	81
13.94	DHCP4_HOOK_SUBNET6_SELECT_PARKING_LOT_FULL	81
13.95	DHCP4_INFORM_DIRECT_REPLY	81
13.96	DHCP4_INIT_FAIL	81
13.97	DHCP4_INIT_REBOOT	81
13.98	DHCP4_LEASE_ALLOC	82
13.99	DHCP4_LEASE_OFFER	82
13.100	DHCP4_LEASE_QUERY_PACKET_PACK_FAILED	82
13.101	DHCP4_LEASE_QUERY_PACKET_UNPACK_FAILED	82
13.102	DHCP4_LEASE_QUERY_PROCESS_FAILED	82
13.103	DHCP4_LEASE_QUERY_RECEIVED	82
13.104	DHCP4_LEASE_QUERY_RESPONSE_SENT	82
13.105	DHCP4_LEASE_QUERY_SEND_FAILED	83
13.106	DHCP4_LEASE_REUSE	83
13.107	DHCP4_MULTI_THREADING_INFO	83
13.108	DHCP4_NCR_CREATION_FAILED	83
13.109	DHCP4_NOT_RUNNING	83
13.110	DHCP4_NO_LEASE_INIT_REBOOT	83
13.111	DHCP4_OPEN_SOCKET	84
13.112	DHCP4_OPEN_SOCKETS_FAILED	84
13.113	DHCP4_OPEN_SOCKETS_NO_RECONNECT_CTL	84
13.114	DHCP4_PACKET_DROP_0001	84
13.115	DHCP4_PACKET_DROP_0002	84
13.116	DHCP4_PACKET_DROP_0003	84
13.117	DHCP4_PACKET_DROP_0004	84
13.118	DHCP4_PACKET_DROP_0005	85
13.119	DHCP4_PACKET_DROP_0006	85
13.120	DHCP4_PACKET_DROP_0007	85
13.121	DHCP4_PACKET_DROP_0008	85
13.122	DHCP4_PACKET_DROP_0009	85
13.123	DHCP4_PACKET_DROP_0010	85
13.124	DHCP4_PACKET_DROP_0011	86
13.125	DHCP4_PACKET_DROP_0012	86
13.126	DHCP4_PACKET_DROP_0013	86
13.127	DHCP4_PACKET_DROP_0014	86
13.128	DHCP4_PACKET_NAK_0001	86
13.129	DHCP4_PACKET_NAK_0002	86
13.130	DHCP4_PACKET_NAK_0003	87
13.131	DHCP4_PACKET_NAK_0004	87
13.132	DHCP4_PACKET_NAK_0005	87
13.133	DHCP4_PACKET_OPTIONS_SKIPPED	87
13.134	DHCP4_PACKET_PACK	87
13.135	DHCP4_PACKET_PACK_FAIL	87
13.136	DHCP4_PACKET_PROCESS_EXCEPTION	87
13.137	DHCP4_PACKET_PROCESS_EXCEPTION_MAIN	88
13.138	DHCP4_PACKET_PROCESS_STD_EXCEPTION	88
13.139	DHCP4_PACKET_PROCESS_STD_EXCEPTION_MAIN	88
13.140	DHCP4_PACKET_QUEUE_FULL	88

13.14	IDHCP4_PACKET_RECEIVED	88
13.142	DHCP4_PACKET_SEND	88
13.143	DHCP4_PACKET_SEND_FAIL	89
13.144	DHCP4_PARSER_COMMIT_EXCEPTION	89
13.145	DHCP4_PARSER_COMMIT_FAIL	89
13.146	DHCP4_PARSER_EXCEPTION	89
13.147	DHCP4_PARSER_FAIL	89
13.148	DHCP4_POST_ALLOCATION_NAME_UPDATE_FAIL	89
13.149	DHCP4_QUERY_DATA	89
13.150	DHCP4_QUERY_LABEL	90
13.151	IDHCP4_RECLAIM_EXPIRED_LEASES_FAIL	90
13.152	DHCP4_RECLAIM_EXPIRED_LEASES_SKIPPED	90
13.153	DHCP4_RECOVERED_STASHED_RELAY_AGENT_INFO	90
13.154	DHCP4_RELEASE	90
13.155	DHCP4_RELEASE_DELETED	90
13.156	DHCP4_RELEASE_EXCEPTION	91
13.157	DHCP4_RELEASE_EXPIRED	91
13.158	DHCP4_RELEASE_FAIL	91
13.159	DHCP4_RELEASE_FAIL_NOT_ASSIGNED	91
13.160	DHCP4_RELEASE_FAIL_NO_LEASE	91
13.161	IDHCP4_RELEASE_FAIL_WRONG_CLIENT	91
13.162	DHCP4_REQUEST	92
13.163	DHCP4_RESERVATIONS_LOOKUP_FIRST_ENABLED	92
13.164	DHCP4_RESERVED_HOSTNAME_ASSIGNED	92
13.165	DHCP4_RESPONSE_DATA	92
13.166	DHCP4_RESPONSE_FQDN_DATA	92
13.167	DHCP4_RESPONSE_HOSTNAME_DATA	92
13.168	DHCP4_RESPONSE_HOSTNAME_GENERATE	93
13.169	DHCP4_ROOT_USER_SECURITY_WARNING	93
13.170	DHCP4_SANITIZED_HOSTNAME_MALFORMED	93
13.171	IDHCP4_SECURITY_CHECKS_DISABLED	93
13.172	DHCP4_SERVER_FAILED	93
13.173	DHCP4_SERVER_INITIATED_DECLINE	93
13.174	DHCP4_SERVER_INITIATED_DECLINE_ADD_FAILED	94
13.175	DHCP4_SERVER_INITIATED_DECLINE_RESOURCE_BUSY	94
13.176	DHCP4_SERVER_INITIATED_DECLINE_UPDATE_FAILED	94
13.177	DHCP4_SHUTDOWN	94
13.178	DHCP4_SHUTDOWN_REQUEST	94
13.179	DHCP4_SRV_CONSTRUCT_ERROR	94
13.180	DHCP4_SRV_D2STOP_ERROR	94
13.181	IDHCP4_SRV_DHCP4O6_ERROR	95
13.182	DHCP4_SRV_UNLOAD_LIBRARIES_ERROR	95
13.183	DHCP4_STARTED	95
13.184	DHCP4_STARTING	95
13.185	DHCP4_START_INFO	95
13.186	DHCP4_SUBNET_DATA	95
13.187	DHCP4_SUBNET_DYNAMICALLY_CHANGED	95
13.188	DHCP4_SUBNET_SELECTED	96
13.189	DHCP4_SUBNET_SELECTION_FAILED	96
13.190	DHCP4_TESTING_MODE_SEND_TO_SOURCE_ENABLED	96
13.191	IDHCP4_UNKNOWN_ADDRESS_REQUESTED	96
13.192	DHCP4_V6_ONLY_PREFERRED_MISSING_IN_ACK	96
13.193	DHCP4_V6_ONLY_PREFERRED_MISSING_IN_OFFER	96

14	DHCP6	97
14.1	DHCP6_ADDITIONAL_CLASS_EVAL_ERROR	97
14.2	DHCP6_ADDITIONAL_CLASS_EVAL_RESULT	97
14.3	DHCP6_ADDITIONAL_CLASS_NO_TEST	97
14.4	DHCP6_ADDITIONAL_CLASS_UNDEFINED	97
14.5	DHCP6_ADDR6_REGISTER_DISABLED_DROP	97
14.6	DHCP6_ADDR_REG_INFORM_CLIENT_CHANGE	98
14.7	DHCP6_ADDR_REG_INFORM_FAIL	98
14.8	DHCP6_ADD_DEPRECATED_UNICAST	98
14.9	DHCP6_ADD_GLOBAL_STATUS_CODE	98
14.10	DHCP6_ADD_STATUS_CODE_FOR_IA	98
14.11	DHCP6_ALREADY_RUNNING	98
14.12	DHCP6_BUFFER_RECEIVED	99
14.13	DHCP6_BUFFER_UNPACK	99
14.14	DHCP6_BUFFER_WAIT_SIGNAL	99
14.15	DHCP6_CB_ON_DEMAND_FETCH_UPDATES_FAIL	99
14.16	DHCP6_CB_PERIODIC_FETCH_UPDATES_FAIL	99
14.17	DHCP6_CB_PERIODIC_FETCH_UPDATES_RETRIES_EXHAUSTED	99
14.18	DHCP6_CB_REPAIR_MODE_ENABLED	100
14.19	DHCP6_CLASSES_ASSIGNED	100
14.20	DHCP6_CLASSES_ASSIGNED_AFTER_SUBNET_SELECTION	100
14.21	DHCP6_CLASS_ASSIGNED	100
14.22	DHCP6_CLASS_UNCONFIGURED	100
14.23	DHCP6_CLIENT_FQDN_SCRUBBED_EMPTY	100
14.24	DHCP6_CONFIG_COMPLETE	101
14.25	DHCP6_CONFIG_HOSTS_DATABASE_DEPRECATED	101
14.26	DHCP6_CONFIG_LOAD_FAIL	101
14.27	DHCP6_CONFIG_PACKET_QUEUE	101
14.28	DHCP6_CONFIG_RECEIVED	101
14.29	DHCP6_CONFIG_START	101
14.30	DHCP6_CONFIG_SYNTAX_WARNING	101
14.31	DHCP6_CONFIG_UNRECOVERABLE_ERROR	102
14.32	DHCP6_CONFIG_UNSUPPORTED_OBJECT	102
14.33	DHCP6_DATA_DIRECTORY_DEPRECATED	102
14.34	DHCP6_DB_RECONNECT_DISABLED	102
14.35	DHCP6_DB_RECONNECT_FAILED	102
14.36	DHCP6_DB_RECONNECT_LOST_CONNECTION	102
14.37	DHCP6_DB_RECONNECT_NO_DB_CTL	102
14.38	DHCP6_DB_RECONNECT_SUCCEEDED	103
14.39	DHCP6_DDNS_CREATE_ADD_NAME_CHANGE_REQUEST	103
14.40	DHCP6_DDNS_FQDN_GENERATED	103
14.41	DHCP6_DDNS_GENERATED_FQDN_UPDATE_FAIL	103
14.42	DHCP6_DDNS_GENERATE_FQDN	103
14.43	DHCP6_DDNS_RECEIVE_FQDN	103
14.44	DHCP6_DDNS_REMOVE_OLD_LEASE_FQDN	103
14.45	DHCP6_DDNS_REQUEST_SEND_FAILED	104
14.46	DHCP6_DDNS_RESPONSE_FQDN_DATA	104
14.47	DHCP6_DECLINE_FAIL	104
14.48	DHCP6_DECLINE_FAIL_DUID_MISMATCH	104
14.49	DHCP6_DECLINE_FAIL_IAID_MISMATCH	104
14.50	DHCP6_DECLINE_FAIL_LEASE_WITHOUT_DUID	104
14.51	DHCP6_DECLINE_FAIL_NO_LEASE	105
14.52	DHCP6_DECLINE_LEASE	105
14.53	DHCP6_DECLINE_PROCESS_IA	105

14.54	DHCP6_DEVELOPMENT_VERSION	105
14.55	DHCP6_DHCP4O6_PACKET_RECEIVED	105
14.56	DHCP6_DHCP4O6_RECEIVE_FAIL	105
14.57	DHCP6_DHCP4O6_RECEIVING	106
14.58	DHCP6_DHCP4O6_RESPONSE_DATA	106
14.59	DHCP6_DHCP4O6_SEND_FAIL	106
14.60	DHCP6_DYNAMIC_RECONFIGURATION	106
14.61	DHCP6_DYNAMIC_RECONFIGURATION_FAIL	106
14.62	DHCP6_DYNAMIC_RECONFIGURATION_SUCCESS	106
14.63	DHCP6_FATAL_DB_RECONNECT_DISABLED	106
14.64	DHCP6_FATAL_DB_RECONNECT_FAILED	107
14.65	DHCP6_FATAL_DYNAMIC_RECONFIGURATION_FAIL	107
14.66	DHCP6_FATAL_OPEN_SOCKETS_FAILED	107
14.67	DHCP6_FLEX_ID	107
14.68	DHCP6_HOOK_ADDR6_REGISTER_DROP	107
14.69	DHCP6_HOOK_ADDR6_REGISTER_SKIP	107
14.70	DHCP6_HOOK_BUFFER_RCVD_DROP	107
14.71	DHCP6_HOOK_BUFFER_RCVD_SKIP	108
14.72	DHCP6_HOOK_BUFFER_SEND_SKIP	108
14.73	DHCP6_HOOK_DDNS_UPDATE	108
14.74	DHCP6_HOOK_DECLINE_DROP	108
14.75	DHCP6_HOOK_DECLINE_SKIP	108
14.76	DHCP6_HOOK_LEASE6_RELEASE_NA_SKIP	108
14.77	DHCP6_HOOK_LEASE6_RELEASE_PD_SKIP	109
14.78	DHCP6_HOOK_LEASES6_COMMITTED_DROP	109
14.79	DHCP6_HOOK_LEASES6_COMMITTED_PARK	109
14.80	DHCP6_HOOK_LEASES6_PARKING_LOT_FULL	109
14.81	DHCP6_HOOK_PACKET_RCVD_SKIP	109
14.82	DHCP6_HOOK_PACKET_SEND_DROP	109
14.83	DHCP6_HOOK_PACKET_SEND_SKIP	110
14.84	DHCP6_HOOK_SUBNET6_SELECT_DROP	110
14.85	DHCP6_HOOK_SUBNET6_SELECT_PARK	110
14.86	DHCP6_HOOK_SUBNET6_SELECT_SKIP	110
14.87	DHCP6_INIT_FAIL	110
14.88	DHCP6_LEASE_ADVERT	110
14.89	DHCP6_LEASE_ADVERT_FAIL	111
14.90	DHCP6_LEASE_ALLOC	111
14.91	DHCP6_LEASE_ALLOC_FAIL	111
14.92	DHCP6_LEASE_DATA	111
14.93	DHCP6_LEASE_NA_WITHOUT_DUID	111
14.94	DHCP6_LEASE_PD_WITHOUT_DUID	111
14.95	DHCP6_LEASE_QUERY_ERROR_GETTING_RELAY_INFO	112
14.96	DHCP6_LEASE_QUERY_PACKET_PACK	112
14.97	DHCP6_LEASE_QUERY_PACKET_PACK_FAILED	112
14.98	DHCP6_LEASE_QUERY_PACKET_UNPACK_FAILED	112
14.99	DHCP6_LEASE_QUERY_PREFIX_LENGTH_LIST	112
14.100	DHCP6_LEASE_QUERY_PROCESS_FAILED	112
14.101	DHCP6_LEASE_QUERY_RECEIVED	113
14.102	DHCP6_LEASE_QUERY_REPLY_SEND_FAILED	113
14.103	DHCP6_LEASE_QUERY_REPLY_SENT	113
14.104	DHCP6_LEASE_RENEW	113
14.105	DHCP6_LEASE_REUSE	113
14.106	DHCP6_MULTI_THREADING_INFO	113
14.107	DHCP6_NOT_RUNNING	113

14.108	DHCP6_NO_INTERFACES	114
14.109	DHCP6_OPEN_SOCKET	114
14.110	DHCP6_OPEN_SOCKETS_FAILED	114
14.111	DHCP6_OPEN_SOCKETS_NO_RECONNECT_CTL	114
14.112	DHCP6_PACKET_DROP_DHCP_DISABLED	114
14.113	DHCP6_PACKET_DROP_DROP_CLASS	114
14.114	DHCP6_PACKET_DROP_DROP_CLASS2	114
14.115	DHCP6_PACKET_DROP_DROP_CLASS_EARLY	115
14.116	DHCP6_PACKET_DROP_DUPLICATE	115
14.117	DHCP6_PACKET_DROP_PARSE_FAIL	115
14.118	DHCP6_PACKET_DROP_SERVERID_MISMATCH	115
14.119	DHCP6_PACKET_DROP_UNICAST	115
14.120	DHCP6_PACKET_OPTIONS_SKIPPED	115
14.121	DHCP6_PACKET_PROCESS_EXCEPTION	115
14.122	DHCP6_PACKET_PROCESS_EXCEPTION_MAIN	116
14.123	DHCP6_PACKET_PROCESS_FAIL	116
14.124	DHCP6_PACKET_PROCESS_STD_EXCEPTION	116
14.125	DHCP6_PACKET_PROCESS_STD_EXCEPTION_MAIN	116
14.126	DHCP6_PACKET_QUEUE_FULL	116
14.127	DHCP6_PACKET_RECEIVED	116
14.128	DHCP6_PACKET_RECEIVE_FAIL	116
14.129	DHCP6_PACKET_REJECT_CLASS	117
14.130	DHCP6_PACKET_SEND	117
14.131	DHCP6_PACKET_SEND_FAIL	117
14.132	DHCP6_PACK_FAIL	117
14.133	DHCP6_PARSER_COMMIT_EXCEPTION	117
14.134	DHCP6_PARSER_COMMIT_FAIL	117
14.135	DHCP6_PARSER_EXCEPTION	117
14.136	DHCP6_PARSER_FAIL	118
14.137	DHCP6_PD_LEASE_ADVERT	118
14.138	DHCP6_PD_LEASE_ADVERT_FAIL	118
14.139	DHCP6_PD_LEASE_ALLOC	118
14.140	DHCP6_PD_LEASE_ALLOC_FAIL	118
14.141	DHCP6_PD_LEASE_RENEW	118
14.142	DHCP6_PD_LEASE_REUSE	119
14.143	DHCP6_PROCESS_IA_NA_EXTEND	119
14.144	DHCP6_PROCESS_IA_NA_RELEASE	119
14.145	DHCP6_PROCESS_IA_NA_REQUEST	119
14.146	DHCP6_PROCESS_IA_NA_SOLICIT	119
14.147	DHCP6_PROCESS_IA_PD_EXTEND	119
14.148	DHCP6_PROCESS_IA_PD_REQUEST	120
14.149	DHCP6_PROCESS_IA_PD_SOLICIT	120
14.150	DHCP6_QUERY_DATA	120
14.151	DHCP6_QUERY_LABEL	120
14.152	DHCP6_RAPID_COMMIT	120
14.153	DHCP6_RECLAIM_EXPIRED_LEASES_FAIL	120
14.154	DHCP6_RECLAIM_EXPIRED_LEASES_SKIPPED	121
14.155	DHCP6_REGISTERED_LEASE_ADD_FAIL	121
14.156	DHCP6_REGISTERED_LEASE_UPDATE_FAIL	121
14.157	DHCP6_RELEASE_NA	121
14.158	DHCP6_RELEASE_NA_DELETED	121
14.159	DHCP6_RELEASE_NA_EXPIRED	121
14.160	DHCP6_RELEASE_NA_FAIL	121
14.161	DHCP6_RELEASE_NA_FAIL_NOT_ASSIGNED	122

14.162	DHCP6_RELEASE_NA_FAIL_WRONG_DUID	122
14.163	DHCP6_RELEASE_NA_FAIL_WRONG_IAID	122
14.164	DHCP6_RELEASE_PD	122
14.165	DHCP6_RELEASE_PD_DELETED	122
14.166	DHCP6_RELEASE_PD_EXPIRED	122
14.167	DHCP6_RELEASE_PD_FAIL	123
14.168	DHCP6_RELEASE_PD_FAIL_NOT_ASSIGNED	123
14.169	DHCP6_RELEASE_PD_FAIL_WRONG_DUID	123
14.170	DHCP6_RELEASE_PD_FAIL_WRONG_IAID	123
14.171	DHCP6_REQUIRED_OPTIONS_CHECK_FAIL	123
14.172	DHCP6_RESERVATIONS_LOOKUP_FIRST_ENABLED	123
14.173	DHCP6_RESPONSE_DATA	124
14.174	DHCP6_ROOT_USER_SECURITY_WARNING	124
14.175	DHCP6_SECURITY_CHECKS_DISABLED	124
14.176	DHCP6_SERVER_FAILED	124
14.177	DHCP6_SHUTDOWN	124
14.178	DHCP6_SHUTDOWN_REQUEST	124
14.179	DHCP6_SRV_CONSTRUCT_ERROR	124
14.180	DHCP6_SRV_D2STOP_ERROR	125
14.181	DHCP6_SRV_UNLOAD_LIBRARIES_ERROR	125
14.182	DHCP6_STARTED	125
14.183	DHCP6_STARTING	125
14.184	DHCP6_START_INFO	125
14.185	DHCP6_SUBNET_DATA	125
14.186	DHCP6_SUBNET_DYNAMICALLY_CHANGED	125
14.187	DHCP6_SUBNET_SELECTED	126
14.188	DHCP6_SUBNET_SELECTION_FAILED	126
14.189	DHCP6_UNKNOWN_MSG_RECEIVED	126
14.190	DHCP6_USING_SERVERID	126
15	DHCP6SRV	127
15.1	DHCP6SRV_CFGMGR_ADD_IFACE	127
15.2	DHCP6SRV_CFGMGR_ADD_SUBNET4	127
15.3	DHCP6SRV_CFGMGR_ADD_SUBNET6	127
15.4	DHCP6SRV_CFGMGR_ALL_IFACES_ACTIVE	127
15.5	DHCP6SRV_CFGMGR_CFG_DHCP_DDNS	127
15.6	DHCP6SRV_CFGMGR_CONFIG4_MERGED	127
15.7	DHCP6SRV_CFGMGR_CONFIG6_MERGED	128
15.8	DHCP6SRV_CFGMGR_CONFIGURE_SERVERID	128
15.9	DHCP6SRV_CFGMGR_DEL_SUBNET4	128
15.10	DHCP6SRV_CFGMGR_DEL_SUBNET6	128
15.11	DHCP6SRV_CFGMGR_FLQ_POPULATE_FREE_ADDRESS_LEASES	128
15.12	DHCP6SRV_CFGMGR_FLQ_POPULATE_FREE_ADDRESS_LEASES_DONE	128
15.13	DHCP6SRV_CFGMGR_FLQ_POPULATE_FREE_PREFIX_LEASES	128
15.14	DHCP6SRV_CFGMGR_FLQ_POPULATE_FREE_PREFIX_LEASES_DONE	129
15.15	DHCP6SRV_CFGMGR_IPV4_RESERVATIONS_NON_UNIQUE_IGNORED	129
15.16	DHCP6SRV_CFGMGR_IPV6_RESERVATIONS_NON_UNIQUE_IGNORED	129
15.17	DHCP6SRV_CFGMGR_IP_RESERVATIONS_UNIQUE_DUPLICATES_DETECTED	129
15.18	DHCP6SRV_CFGMGR_IP_RESERVATIONS_UNIQUE_DUPLICATES_POSSIBLE	129
15.19	DHCP6SRV_CFGMGR_NEW_SUBNET4	129
15.20	DHCP6SRV_CFGMGR_NEW_SUBNET6	130
15.21	DHCP6SRV_CFGMGR_OPTION_DEFINITION_MISMATCH	130
15.22	DHCP6SRV_CFGMGR_OPTION_DUPLICATE	130
15.23	DHCP6SRV_CFGMGR_RENEW_GTR_REBIND	130

15.24	DHCPSRV_CFGMGR_SOCKET_RAW_UNSUPPORTED	130
15.25	DHCPSRV_CFGMGR_SOCKET_TYPE_DEFAULT	130
15.26	DHCPSRV_CFGMGR_SOCKET_TYPE_SELECT	131
15.27	DHCPSRV_CFGMGR_SUBNET4	131
15.28	DHCPSRV_CFGMGR_SUBNET4_ADDR	131
15.29	DHCPSRV_CFGMGR_SUBNET4_IFACE	131
15.30	DHCPSRV_CFGMGR_SUBNET4_RELAY	131
15.31	DHCPSRV_CFGMGR_SUBNET6	131
15.32	DHCPSRV_CFGMGR_SUBNET6_IFACE	131
15.33	DHCPSRV_CFGMGR_SUBNET6_IFACE_ID	132
15.34	DHCPSRV_CFGMGR_SUBNET6_RELAY	132
15.35	DHCPSRV_CFGMGR_UNICAST_LINK_LOCAL	132
15.36	DHCPSRV_CFGMGR_UPDATE_SUBNET4	132
15.37	DHCPSRV_CFGMGR_UPDATE_SUBNET6	132
15.38	DHCPSRV_CFGMGR_USE_ADDRESS	132
15.39	DHCPSRV_CFGMGR_USE_ALLOCATOR	132
15.40	DHCPSRV_CFGMGR_USE_UNICAST	133
15.41	DHCPSRV_CLASS_BAD_NAME	133
15.42	DHCPSRV_CLASS_WITH_ADDITIONAL_AND_LIFETIMES	133
15.43	DHCPSRV_CLIENT_CLASS_DEPRECATED	133
15.44	DHCPSRV_CLOSE_DB	133
15.45	DHCPSRV_DDNS_TTL_TOO_LARGE	133
15.46	DHCPSRV_DDNS_TTL_TOO_SMALL	133
15.47	DHCPSRV_DHCP4O6_RECEIVED_BAD_PACKET	134
15.48	DHCPSRV_DHCP_DDNS_ERROR_EXCEPTION	134
15.49	DHCPSRV_DHCP_DDNS_HANDLER_NULL	134
15.50	DHCPSRV_DHCP_DDNS_NCR_REJECTED	134
15.51	DHCPSRV_DHCP_DDNS_NCR_SENT	134
15.52	DHCPSRV_DHCP_DDNS_SENDER_STARTED	134
15.53	DHCPSRV_DHCP_DDNS_SENDER_STOPPED	134
15.54	DHCPSRV_DHCP_DDNS_SUSPEND_UPDATES	135
15.55	DHCPSRV_EVAL_ERROR	135
15.56	DHCPSRV_EVAL_RESULT	135
15.57	DHCPSRV_FORENSIC_BACKENDS_REGISTERED	135
15.58	DHCPSRV_FORENSIC_BACKEND_DEREGISTER	135
15.59	DHCPSRV_FORENSIC_BACKEND_REGISTER	135
15.60	DHCPSRV_GENERATE_NCR4_FAILED	135
15.61	DHCPSRV_GENERATE_NCR6_FAILED	136
15.62	DHCPSRV_HOOK_LEASE4_RECOVER_SKIP	136
15.63	DHCPSRV_HOOK_LEASE4_RENEW_SKIP	136
15.64	DHCPSRV_HOOK_LEASE4_SELECT_SKIP	136
15.65	DHCPSRV_HOOK_LEASE6_EXTEND_SKIP	136
15.66	DHCPSRV_HOOK_LEASE6_RECOVER_SKIP	136
15.67	DHCPSRV_HOOK_LEASE6_SELECT_SKIP	137
15.68	DHCPSRV_HOST_MGR_DB_OPEN_CONNECTION_WITH_RETRY_FAILED	137
15.69	DHCPSRV_LEASE4_EXTENDED_INFO_SANITY_FAIL	137
15.70	DHCPSRV_LEASE4_EXTENDED_INFO_UPGRADED	137
15.71	DHCPSRV_LEASE6_EXTENDED_INFO_SANITY_FAIL	137
15.72	DHCPSRV_LEASE6_EXTENDED_INFO_UPGRADED	137
15.73	DHCPSRV_LEASE_MGR_BACKENDS_REGISTERED	137
15.74	DHCPSRV_LEASE_MGR_BACKEND_DEREGISTER	138
15.75	DHCPSRV_LEASE_MGR_BACKEND_REGISTER	138
15.76	DHCPSRV_LEASE_MGR_CALLBACK_EXCEPTION	138
15.77	DHCPSRV_LEASE_MGR_CALLBACK_UNKNOWN_EXCEPTION	138

15.78	DHCPSRV_LEASE_MGR_DB_OPEN_CONNECTION_WITH_RETRY_FAILED	138
15.79	DHCPSRV_LEASE_SANITY_FAIL	138
15.80	DHCPSRV_LEASE_SANITY_FAIL_DISCARD	139
15.81	DHCPSRV_LEASE_SANITY_FIXED	139
15.82	DHCPSRV_MEMFILE_ADD_ADDR4	139
15.83	DHCPSRV_MEMFILE_ADD_ADDR6	139
15.84	DHCPSRV_MEMFILE_BEGIN_BUILD_EXTENDED_INFO_TABLES6	139
15.85	DHCPSRV_MEMFILE_BEGIN_EXTRACT_EXTENDED_INFO4	139
15.86	DHCPSRV_MEMFILE_BUILD_EXTENDED_INFO_TABLES6	139
15.87	DHCPSRV_MEMFILE_BUILD_EXTENDED_INFO_TABLES6_ERROR	140
15.88	DHCPSRV_MEMFILE_COMMIT	140
15.89	DHCPSRV_MEMFILE_CONVERTING_LEASE_FILES	140
15.90	DHCPSRV_MEMFILE_DB	140
15.91	DHCPSRV_MEMFILE_DELETE_ADDR4	140
15.92	DHCPSRV_MEMFILE_DELETE_ADDR6	140
15.93	DHCPSRV_MEMFILE_DELETE_EXPIRED_RECLAIMED4	140
15.94	DHCPSRV_MEMFILE_DELETE_EXPIRED_RECLAIMED6	141
15.95	DHCPSRV_MEMFILE_DELETE_EXPIRED_RECLAIMED_START	141
15.96	DHCPSRV_MEMFILE_EXTRACT_EXTENDED_INFO4	141
15.97	DHCPSRV_MEMFILE_EXTRACT_EXTENDED_INFO4_ERROR	141
15.98	DHCPSRV_MEMFILE_FAILED_TO_OPEN	141
15.99	DHCPSRV_MEMFILE_GET4	141
15.100	DHCPSRV_MEMFILE_GET6	141
15.101	DHCPSRV_MEMFILE_GET6_DUID	142
15.102	DHCPSRV_MEMFILE_GET_ADDR4	142
15.103	DHCPSRV_MEMFILE_GET_ADDR6	142
15.104	DHCPSRV_MEMFILE_GET_CLIENTID	142
15.105	DHCPSRV_MEMFILE_GET_EXPIRED4	142
15.106	DHCPSRV_MEMFILE_GET_EXPIRED6	142
15.107	DHCPSRV_MEMFILE_GET_HOSTNAME4	142
15.108	DHCPSRV_MEMFILE_GET_HOSTNAME6	143
15.109	DHCPSRV_MEMFILE_GET_HWADDR4	143
15.110	DHCPSRV_MEMFILE_GET_HWADDR6	143
15.111	DHCPSRV_MEMFILE_GET_IAID_DUID	143
15.112	DHCPSRV_MEMFILE_GET_IAID_SUBID_DUID	143
15.113	DHCPSRV_MEMFILE_GET_PAGE4	143
15.114	DHCPSRV_MEMFILE_GET_PAGE6	143
15.115	DHCPSRV_MEMFILE_GET_RELAYID4	144
15.116	DHCPSRV_MEMFILE_GET_RELAYID6	144
15.117	DHCPSRV_MEMFILE_GET_REMOTEID4	144
15.118	DHCPSRV_MEMFILE_GET_REMOTEID6	144
15.119	DHCPSRV_MEMFILE_GET_SUBID4	144
15.120	DHCPSRV_MEMFILE_GET_SUBID6	144
15.121	DHCPSRV_MEMFILE_GET_SUBID_CLIENTID	144
15.122	DHCPSRV_MEMFILE_GET_SUBID_HWADDR	145
15.123	DHCPSRV_MEMFILE_GET_SUBID_PAGE6	145
15.124	DHCPSRV_MEMFILE_LEASE_FILE_LOAD	145
15.125	DHCPSRV_MEMFILE_LEASE_LOAD	145
15.126	DHCPSRV_MEMFILE_LEASE_LOAD_ROW_ERROR	145
15.127	DHCPSRV_MEMFILE_LFC_EXECUTE	145
15.128	DHCPSRV_MEMFILE_LFC_FAIL_PID_CREATE	145
15.129	DHCPSRV_MEMFILE_LFC_LEASE_FILE_RENAME_FAIL	146
15.130	DHCPSRV_MEMFILE_LFC_LEASE_FILE_REOPEN_FAIL	146
15.131	DHCPSRV_MEMFILE_LFC_RESCHEDULED	146

15.132	DHCP_SRV_MEMFILE_LFC_RUNNING	146
15.133	DHCP_SRV_MEMFILE_LFC_SETUP	146
15.134	DHCP_SRV_MEMFILE_LFC_SPAWN_FAIL	146
15.135	DHCP_SRV_MEMFILE_LFC_START	146
15.136	DHCP_SRV_MEMFILE_LFC_UNREGISTER_TIMER_FAILED	147
15.137	DHCP_SRV_MEMFILE_NEEDS_DOWNGRADING	147
15.138	DHCP_SRV_MEMFILE_NEEDS_UPGRADING	147
15.139	DHCP_SRV_MEMFILE_NO_STORAGE	147
15.140	DHCP_SRV_MEMFILE_PATH_SECURITY_WARNING	147
15.141	DHCP_SRV_MEMFILE_READ_HWADDR_FAIL	147
15.142	DHCP_SRV_MEMFILE_ROLLBACK	148
15.143	DHCP_SRV_MEMFILE_UPDATE_ADDR4	148
15.144	DHCP_SRV_MEMFILE_UPDATE_ADDR6	148
15.145	DHCP_SRV_MEMFILE_WIPE_LEASES4	148
15.146	DHCP_SRV_MEMFILE_WIPE_LEASES4_FINISHED	148
15.147	DHCP_SRV_MEMFILE_WIPE_LEASES6	148
15.148	DHCP_SRV_MEMFILE_WIPE_LEASES6_FINISHED	148
15.149	DHCP_SRV_MT_DISABLED_QUEUE_CONTROL	149
15.150	DHCP_SRV_MULTIPLE_RAW_SOCKETS_PER_IFACE	149
15.151	DHCP_SRV_NOTYPE_DB	149
15.152	DHCP_SRV_NO_SOCKETS_OPEN	149
15.153	DHCP_SRV_ONLY_IF_REQUIRED_DEPRECATED	149
15.154	DHCP_SRV_OPEN_SOCKET_FAIL	149
15.155	DHCP_SRV_QUEUE_NCR	149
15.156	DHCP_SRV_QUEUE_NCR_FAILED	150
15.157	DHCP_SRV_QUEUE_NCR_SKIP	150
15.158	DHCP_SRV_REQUIRE_CLIENT_CLASSES_DEPRECATED	150
15.159	DHCP_SRV_SUBNET4O6_SELECT_FAILED	150
15.160	DHCP_SRV_SUBNET4_SELECT_BY_ADDRESS_NO_MATCH	150
15.161	DHCP_SRV_SUBNET4_SELECT_BY_INTERFACE_NO_MATCH	150
15.162	DHCP_SRV_SUBNET4_SELECT_BY_RELAY_ADDRESS_NO_MATCH	150
15.163	DHCP_SRV_SUBNET4_SELECT_NO_RA_OPTIONS	151
15.164	DHCP_SRV_SUBNET4_SELECT_NO_RELAY_ADDRESS	151
15.165	DHCP_SRV_SUBNET4_SELECT_NO_USABLE_ADDRESS	151
15.166	DHCP_SRV_SUBNET6_SELECT_BY_ADDRESS_NO_MATCH	151
15.167	DHCP_SRV_SUBNET6_SELECT_BY_INTERFACE_ID_NO_MATCH	151
15.168	DHCP_SRV_SUBNET6_SELECT_BY_INTERFACE_NO_MATCH	151
15.169	DHCP_SRV_TEMPLATE_EVAL_ERROR	151
15.170	DHCP_SRV_TEMPLATE_EVAL_RESULT	152
15.171	DHCP_SRV_TIMERMGR_CALLBACK_FAILED	152
15.172	DHCP_SRV_TIMERMGR_REGISTER_TIMER	152
15.173	DHCP_SRV_TIMERMGR_RUN_TIMER_OPERATION	152
15.174	DHCP_SRV_TIMERMGR_START_TIMER	152
15.175	DHCP_SRV_TIMERMGR_STOP_TIMER	152
15.176	DHCP_SRV_TIMERMGR_UNREGISTER_ALL_TIMERS	152
15.177	DHCP_SRV_TIMERMGR_UNREGISTER_TIMER	153
15.178	DHCP_SRV_UNKNOWN_DB	153
16	DHCP	155
16.1	DHCP_ADD_EXTERNAL_SOCKET_ALREADY_EXISTS	155
16.2	DHCP_ADD_EXTERNAL_SOCKET_BAD_THREAD	155
16.3	DHCP_DDNS_ADD_FAILED	155
16.4	DHCP_DDNS_ADD_SUCCEEDED	155
16.5	DHCP_DDNS_AT_MAX_TRANSACTIONS	155

16.6	DHCP_DDNS_CLEARED_FOR_SHUTDOWN	156
16.7	DHCP_DDNS_CONFIGURE	156
16.8	DHCP_DDNS_CONFIGURED_CALLOUT_DROP	156
16.9	DHCP_DDNS_CONFIG_CHECK_FAIL	156
16.10	DHCP_DDNS_CONFIG_FAIL	156
16.11	DHCP_DDNS_CONFIG_SYNTAX_WARNING	156
16.12	DHCP_DDNS_FAILED	156
16.13	DHCP_DDNS_FORWARD_ADD_BAD_DNSCLIENT_STATUS	157
16.14	DHCP_DDNS_FORWARD_ADD_BUILD_FAILURE	157
16.15	DHCP_DDNS_FORWARD_ADD_IO_ERROR	157
16.16	DHCP_DDNS_FORWARD_ADD_REJECTED	157
16.17	DHCP_DDNS_FORWARD_ADD_RESP_CORRUPT	157
16.18	DHCP_DDNS_FORWARD_ADD_TIMEOUT	157
16.19	DHCP_DDNS_FORWARD_REMOVE_ADDRS_BAD_DNSCLIENT_STATUS	157
16.20	DHCP_DDNS_FORWARD_REMOVE_ADDRS_BUILD_FAILURE	158
16.21	DHCP_DDNS_FORWARD_REMOVE_ADDRS_IO_ERROR	158
16.22	DHCP_DDNS_FORWARD_REMOVE_ADDRS_REJECTED	158
16.23	DHCP_DDNS_FORWARD_REMOVE_ADDRS_RESP_CORRUPT	158
16.24	DHCP_DDNS_FORWARD_REMOVE_ADDRS_TIMEOUT	158
16.25	DHCP_DDNS_FORWARD_REMOVE_RRS_BAD_DNSCLIENT_STATUS	158
16.26	DHCP_DDNS_FORWARD_REMOVE_RRS_BUILD_FAILURE	158
16.27	DHCP_DDNS_FORWARD_REMOVE_RRS_IO_ERROR	159
16.28	DHCP_DDNS_FORWARD_REMOVE_RRS_REJECTED	159
16.29	DHCP_DDNS_FORWARD_REMOVE_RRS_RESP_CORRUPT	159
16.30	DHCP_DDNS_FORWARD_REMOVE_RRS_TIMEOUT	159
16.31	DHCP_DDNS_FORWARD_REPLACE_BAD_DNSCLIENT_STATUS	159
16.32	DHCP_DDNS_FORWARD_REPLACE_BUILD_FAILURE	159
16.33	DHCP_DDNS_FORWARD_REPLACE_IO_ERROR	159
16.34	DHCP_DDNS_FORWARD_REPLACE_REJECTED	160
16.35	DHCP_DDNS_FORWARD_REPLACE_RESP_CORRUPT	160
16.36	DHCP_DDNS_FORWARD_REPLACE_TIMEOUT	160
16.37	DHCP_DDNS_FWD_REQUEST_IGNORED	160
16.38	DHCP_DDNS_INVALID_NCR	160
16.39	DHCP_DDNS_INVALID_RESPONSE	160
16.40	DHCP_DDNS_IO_FETCH_RESULT	160
16.41	DHCP_DDNS_LISTENING_ON_ALL_INTERFACES	161
16.42	DHCP_DDNS_NCR_FLUSH_IO_ERROR	161
16.43	DHCP_DDNS_NCR_LISTEN_CLOSE_ERROR	161
16.44	DHCP_DDNS_NCR_RECV_NEXT_ERROR	161
16.45	DHCP_DDNS_NCR_SEND_CLOSE_ERROR	161
16.46	DHCP_DDNS_NCR_SEND_NEXT_ERROR	161
16.47	DHCP_DDNS_NCR_UDP_CLEAR_READY_ERROR	162
16.48	DHCP_DDNS_NCR_UDP_RECV_CANCELED	162
16.49	DHCP_DDNS_NCR_UDP_RECV_ERROR	162
16.50	DHCP_DDNS_NCR_UDP_SEND_CANCELED	162
16.51	DHCP_DDNS_NCR_UDP_SEND_ERROR	162
16.52	DHCP_DDNS_NOT_ON_LOOPBACK	162
16.53	DHCP_DDNS_NO_ELIGIBLE_JOBS	162
16.54	DHCP_DDNS_NO_FWD_MATCH_ERROR	163
16.55	DHCP_DDNS_NO_MATCH	163
16.56	DHCP_DDNS_NO_REV_MATCH_ERROR	163
16.57	DHCP_DDNS_QUEUE_MGR_QUEUE_FULL	163
16.58	DHCP_DDNS_QUEUE_MGR_QUEUE_RECEIVE	163
16.59	DHCP_DDNS_QUEUE_MGR_RECONFIGURING	163

16.60	DHCP_DDNS_QUEUE_MGR_RECOVERING	163
16.61	DHCP_DDNS_QUEUE_MGR_RECV_ERROR	164
16.62	DHCP_DDNS_QUEUE_MGR_RESUME_ERROR	164
16.63	DHCP_DDNS_QUEUE_MGR_RESUMING	164
16.64	DHCP_DDNS_QUEUE_MGR_STARTED	164
16.65	DHCP_DDNS_QUEUE_MGR_START_ERROR	164
16.66	DHCP_DDNS_QUEUE_MGR_STOPPED	164
16.67	DHCP_DDNS_QUEUE_MGR_STOPPING	165
16.68	DHCP_DDNS_QUEUE_MGR_STOP_ERROR	165
16.69	DHCP_DDNS_QUEUE_MGR_UNEXPECTED_HANDLER_ERROR	165
16.70	DHCP_DDNS_QUEUE_MGR_UNEXPECTED_STOP	165
16.71	DHCP_DDNS_REMOVE_FAILED	165
16.72	DHCP_DDNS_REMOVE_SUCCEEDED	165
16.73	DHCP_DDNS_REQUEST_DROPPED	165
16.74	DHCP_DDNS_REVERSE_REMOVE_BAD_DNSCLIENT_STATUS	166
16.75	DHCP_DDNS_REVERSE_REMOVE_BUILD_FAILURE	166
16.76	DHCP_DDNS_REVERSE_REMOVE_IO_ERROR	166
16.77	DHCP_DDNS_REVERSE_REMOVE_REJECTED	166
16.78	DHCP_DDNS_REVERSE_REMOVE_RESP_CORRUPT	166
16.79	DHCP_DDNS_REVERSE_REMOVE_TIMEOUT	166
16.80	DHCP_DDNS_REVERSE_REPLACE_BAD_DNSCLIENT_STATUS	166
16.81	DHCP_DDNS_REVERSE_REPLACE_BUILD_FAILURE	167
16.82	DHCP_DDNS_REVERSE_REPLACE_IO_ERROR	167
16.83	DHCP_DDNS_REVERSE_REPLACE_REJECTED	167
16.84	DHCP_DDNS_REVERSE_REPLACE_RESP_CORRUPT	167
16.85	DHCP_DDNS_REVERSE_REPLACE_TIMEOUT	167
16.86	DHCP_DDNS_REV_REQUEST_IGNORED	167
16.87	DHCP_DDNS_RUN_EXIT	167
16.88	DHCP_DDNS_SECURITY_CHECKS_DISABLED	168
16.89	DHCP_DDNS_SHUTDOWN_COMMAND	168
16.90	DHCP_DDNS_STARTED	168
16.91	DHCP_DDNS_STARTING_TRANSACTION	168
16.92	DHCP_DDNS_STATE_MODEL_UNEXPECTED_ERROR	168
16.93	DHCP_DDNS_TRANS_SEND_ERROR	168
16.94	DHCP_DDNS_TSIG_SECRET_SECURITY_WARNING	168
16.95	DHCP_DDNS_UDP_SENDER_WATCH_SOCKET_CLOSE_ERROR	169
16.96	DHCP_DDNS_UNCAUGHT_NCR_RECV_HANDLER_ERROR	169
16.97	DHCP_DDNS_UNCAUGHT_NCR_SEND_HANDLER_ERROR	169
16.98	DHCP_DDNS_UPDATE_REQUEST_SENT	169
16.99	DHCP_DDNS_UPDATE_RESPONSE_RECEIVED	169
16.100	DHCP_DELETE_ALL_EXTERNAL_SOCKETS_BAD_THREAD	169
16.101	DHCP_DELETE_EXTERNAL_SOCKET_BAD_THREAD	169
16.102	DHCP_DELETE_EXTERNAL_SOCKET_NOT_FOUND	170
16.103	DHCP_IFACE_OPEN_SOCKET	170
16.104	DHCP_IFACE_SOCKET_ERROR	170
16.105	DHCP_RECEIVE4_UNKNOWN	170
16.106	DHCP_RECEIVE6_UNKNOWN	170
17	EVAL	171
17.1	EVAL_DEBUG_AND	171
17.2	EVAL_DEBUG_BRANCH	171
17.3	EVAL_DEBUG_CONCAT	171
17.4	EVAL_DEBUG_EQUAL	171
17.5	EVAL_DEBUG_HEXSTRING	171

17.6	EVAL_DEBUG_IFELSE_FALSE	172
17.7	EVAL_DEBUG_IFELSE_TRUE	172
17.8	EVAL_DEBUG_INT16TOTEXT	172
17.9	EVAL_DEBUG_INT32TOTEXT	172
17.10	EVAL_DEBUG_INT8TOTEXT	172
17.11	EVAL_DEBUG_IPADDRESS	172
17.12	EVAL_DEBUG_IPADDRESSTOTEXT	172
17.13	EVAL_DEBUG_LCASE	173
17.14	EVAL_DEBUG_MATCH	173
17.15	EVAL_DEBUG_MATCH_ERROR	173
17.16	EVAL_DEBUG_MEMBER	173
17.17	EVAL_DEBUG_NOT	173
17.18	EVAL_DEBUG_OPTION	173
17.19	EVAL_DEBUG_OR	173
17.20	EVAL_DEBUG_PKT	174
17.21	EVAL_DEBUG_PKT4	174
17.22	EVAL_DEBUG_PKT6	174
17.23	EVAL_DEBUG_POP_AND_BRANCH_FALSE	174
17.24	EVAL_DEBUG_POP_OR_BRANCH_FALSE	174
17.25	EVAL_DEBUG_POP_OR_BRANCH_TRUE	174
17.26	EVAL_DEBUG_RELAY6	174
17.27	EVAL_DEBUG_RELAY6_RANGE	175
17.28	EVAL_DEBUG_SPLIT	175
17.29	EVAL_DEBUG_SPLIT_DELIM_EMPTY	175
17.30	EVAL_DEBUG_SPLIT_EMPTY	175
17.31	EVAL_DEBUG_SPLIT_FIELD_OUT_OF_RANGE	175
17.32	EVAL_DEBUG_STRING	175
17.33	EVAL_DEBUG_SUBSTRING	175
17.34	EVAL_DEBUG_SUBSTRING_EMPTY	176
17.35	EVAL_DEBUG_SUBSTRING_RANGE	176
17.36	EVAL_DEBUG_TOHEXSTRING	176
17.37	EVAL_DEBUG_UCASE	176
17.38	EVAL_DEBUG_UINT16TOTEXT	176
17.39	EVAL_DEBUG_UINT32TOTEXT	176
17.40	EVAL_DEBUG_UINT8TOTEXT	176
17.41	EVAL_DEBUG_VENDOR_CLASS_DATA	177
17.42	EVAL_DEBUG_VENDOR_CLASS_DATA_NOT_FOUND	177
17.43	EVAL_DEBUG_VENDOR_CLASS_ENTERPRISE_ID	177
17.44	EVAL_DEBUG_VENDOR_CLASS_ENTERPRISE_ID_MISMATCH	177
17.45	EVAL_DEBUG_VENDOR_CLASS_EXISTS	177
17.46	EVAL_DEBUG_VENDOR_CLASS_NO_OPTION	177
17.47	EVAL_DEBUG_VENDOR_ENTERPRISE_ID	177
17.48	EVAL_DEBUG_VENDOR_ENTERPRISE_ID_MISMATCH	178
17.49	EVAL_DEBUG_VENDOR_EXISTS	178
17.50	EVAL_DEBUG_VENDOR_NO_OPTION	178
18	FLEX	179
18.1	FLEX_ID_CID_AS_RFC4361_DUID_ENABLED	179
18.2	FLEX_ID_CID_AS_RFC4361_DUID_JSON_TYPE	179
18.3	FLEX_ID_EXPRESSION_EVALUATED	179
18.4	FLEX_ID_EXPRESSION_EVALUATED_NP	179
18.5	FLEX_ID_EXPRESSION_HEX	179
18.6	FLEX_ID_EXPRESSION_INVALID_JSON_TYPE	180
18.7	FLEX_ID_EXPRESSION_PARSE_FAILED	180

18.8	FLEX_ID_IGNORE_IAID_APPLIED_ON_NA	180
18.9	FLEX_ID_IGNORE_IAID_APPLIED_ON_PD	180
18.10	FLEX_ID_IGNORE_IAID_ENABLED	180
18.11	FLEX_ID_IGNORE_IAID_JSON_TYPE	180
18.12	FLEX_ID_IGNORE_IAID_NOT_APPLIED_ON_NA	180
18.13	FLEX_ID_IGNORE_IAID_NOT_APPLIED_ON_PD	181
18.14	FLEX_ID_LOAD_ERROR	181
18.15	FLEX_ID_NO_IDENTIFIER_EXPRESSION	181
18.16	FLEX_ID_REPLACE_CLIENT_ID_JSON_TYPE	181
18.17	FLEX_ID_RESTORE_CLIENT_ID	181
18.18	FLEX_ID_RESTORE_DUID	181
18.19	FLEX_ID_UNLOAD	181
18.20	FLEX_ID_USED_AS_CLIENT_ID	182
18.21	FLEX_ID_USED_AS_DUID	182
18.22	FLEX_OPTION_CONFIG_SUB_USELESS_CLASS	182
18.23	FLEX_OPTION_CONFIG_SUB_USELESS_MEMBER	182
18.24	FLEX_OPTION_CONFIG_USELESS_CLASS	182
18.25	FLEX_OPTION_CONFIG_USELESS_MEMBER	182
18.26	FLEX_OPTION_LOAD_ERROR	183
18.27	FLEX_OPTION_PROCESS_ADD	183
18.28	FLEX_OPTION_PROCESS_CLIENT_CLASS	183
18.29	FLEX_OPTION_PROCESS_ERROR	183
18.30	FLEX_OPTION_PROCESS_REMOVE	183
18.31	FLEX_OPTION_PROCESS_SUB_ADD	183
18.32	FLEX_OPTION_PROCESS_SUB_CLIENT_CLASS	183
18.33	FLEX_OPTION_PROCESS_SUB_REMOVE	184
18.34	FLEX_OPTION_PROCESS_SUB_SUPERSEDE	184
18.35	FLEX_OPTION_PROCESS_SUPERSEDE	184
18.36	FLEX_OPTION_PROCESS_VENDOR_ID_MISMATCH	184
18.37	FLEX_OPTION_UNLOAD	184
19	FUZZ	185
19.1	FUZZ_DATA_READ	185
19.2	FUZZ_INIT_COMPLETE	185
19.3	FUZZ_INIT_FAIL	185
19.4	FUZZ_READ_FAIL	185
19.5	FUZZ_SEND	185
19.6	FUZZ_SEND_ERROR	186
19.7	FUZZ_SHORT_SEND	186
19.8	FUZZ_SOCKET_CREATE_FAIL	186
20	GSS	187
20.1	GSS_TSIG_COMMAND_PROCESSED_FAILED	187
20.2	GSS_TSIG_IGNORED_BAD_DIRECTION	187
20.3	GSS_TSIG_LOAD_FAILED	187
20.4	GSS_TSIG_LOAD_OK	187
20.5	GSS_TSIG_MANAGER_STARTED	187
20.6	GSS_TSIG_MANAGER_STOPPED	187
20.7	GSS_TSIG_MANAGER_STOP_ERROR	188
20.8	GSS_TSIG_MANAGER_STOP_GENERAL_ERROR	188
20.9	GSS_TSIG_NEW_KEY	188
20.10	GSS_TSIG_NEW_KEY_SETUP_FAILED	188
20.11	GSS_TSIG_NEW_KEY_SETUP_SUCCEED	188
20.12	GSS_TSIG_OLD_KEY_REMOVED	188

20.13	GSS_TSIG_UNLOAD_OK	188
20.14	GSS_TSIG_VERIFIED	188
20.15	GSS_TSIG_VERIFY_FAILED	189
21	HA	191
21.1	HA_BUFFER4_RECEIVE_FAILED	191
21.2	HA_BUFFER4_RECEIVE_NOT_FOR_US	191
21.3	HA_BUFFER4_RECEIVE_PACKET_OPTIONS_SKIPPED	191
21.4	HA_BUFFER4_RECEIVE_UNPACK_FAILED	191
21.5	HA_BUFFER6_RECEIVE_FAILED	191
21.6	HA_BUFFER6_RECEIVE_NOT_FOR_US	192
21.7	HA_BUFFER6_RECEIVE_PACKET_OPTIONS_SKIPPED	192
21.8	HA_BUFFER6_RECEIVE_UNPACK_FAILED	192
21.9	HA_COMMAND_PROCESSED_FAILED	192
21.10	HA_COMMUNICATION_INTERRUPTED	192
21.11	HA_COMMUNICATION_INTERRUPTED_CLIENT4	192
21.12	HA_COMMUNICATION_INTERRUPTED_CLIENT4_UNACKED	193
21.13	HA_COMMUNICATION_INTERRUPTED_CLIENT6	193
21.14	HA_COMMUNICATION_INTERRUPTED_CLIENT6_UNACKED	193
21.15	HA_CONFIGURATION_FAILED	193
21.16	HA_CONFIGURATION_SUCCESSFUL	193
21.17	HA_CONFIG_AUTO_FAILOVER_DISABLED	193
21.18	HA_CONFIG_DHCP_MT_DISABLED	194
21.19	HA_CONFIG_DHCP_MT_DISABLED_AND_KEA_MT_ENABLED	194
21.20	HA_CONFIG_LEASE_SYNCING_DISABLED	194
21.21	HA_CONFIG_LEASE_SYNCING_DISABLED_REMINDER	194
21.22	HA_CONFIG_LEASE_UPDATES_AND_SYNCING_DIFFER	194
21.23	HA_CONFIG_LEASE_UPDATES_DISABLED	194
21.24	HA_CONFIG_LEASE_UPDATES_DISABLED_REMINDER	195
21.25	HA_CONFIG_SYSTEM_MT_UNSUPPORTED	195
21.26	HA_CONTINUE_HANDLER_FAILED	195
21.27	HA_DEINIT_OK	195
21.28	HA_DHCP4_START_SERVICE_FAILED	195
21.29	HA_DHCP6_START_SERVICE_FAILED	195
21.30	HA_DHCP_DISABLE_COMMUNICATIONS_FAILED	195
21.31	HA_DHCP_DISABLE_FAILED	196
21.32	HA_DHCP_ENABLE_COMMUNICATIONS_FAILED	196
21.33	HA_DHCP_ENABLE_FAILED	196
21.34	HA_HEARTBEAT_COMMUNICATIONS_FAILED	196
21.35	HA_HEARTBEAT_FAILED	196
21.36	HA_HEARTBEAT_HANDLER_FAILED	196
21.37	HA_HIGH_CLOCK_SKEW	196
21.38	HA_HIGH_CLOCK_SKEW_CAUSED_TERMINATION	197
21.39	HA_INIT_OK	197
21.40	HA_INVALID_PARTNER_STATE_COMMUNICATION_RECOVERY	197
21.41	HA_INVALID_PARTNER_STATE_HOT_STANDBY	197
21.42	HA_INVALID_PARTNER_STATE_LOAD_BALANCING	197
21.43	HA_LEASE4_EXPIRE_FAILED	197
21.44	HA_LEASE4_EXPIRE_INVALID_HA_SERVER_NAME	198
21.45	HA_LEASE4_EXPIRE_RECLAMATION_SKIP	198
21.46	HA_LEASE4_SERVER_DECLINE_FAILED	198
21.47	HA_LEASE6_EXPIRE_FAILED	198
21.48	HA_LEASE6_EXPIRE_INVALID_HA_SERVER_NAME	198
21.49	HA_LEASE6_EXPIRE_RECLAMATION_SKIP	198

21.50	HA_LEASES4_COMMITTED_FAILED	199
21.51	HA_LEASES4_COMMITTED_NOHING_TO_UPDATE	199
21.52	HA_LEASES4_COMMITTED_NO_RELATIONSHIP	199
21.53	HA_LEASES6_COMMITTED_FAILED	199
21.54	HA_LEASES6_COMMITTED_NOHING_TO_UPDATE	199
21.55	HA_LEASES6_COMMITTED_NO_RELATIONSHIP	199
21.56	HA_LEASES_BACKLOG_COMMUNICATIONS_FAILED	200
21.57	HA_LEASES_BACKLOG_FAILED	200
21.58	HA_LEASES_BACKLOG_NOHING_TO_SEND	200
21.59	HA_LEASES_BACKLOG_START	200
21.60	HA_LEASES_BACKLOG_SUCCESS	200
21.61	HA_LEASES_SYNC_APPLIED_LEASES	200
21.62	HA_LEASES_SYNC_COMMUNICATIONS_FAILED	201
21.63	HA_LEASES_SYNC_FAILED	201
21.64	HA_LEASES_SYNC_LEASE_PAGE_RECEIVED	201
21.65	HA_LEASE_SYNC_FAILED	201
21.66	HA_LEASE_SYNC_STALE_LEASE4_SKIP	201
21.67	HA_LEASE_SYNC_STALE_LEASE6_SKIP	201
21.68	HA_LEASE_UPDATES_DISABLED	202
21.69	HA_LEASE_UPDATES_ENABLED	202
21.70	HA_LEASE_UPDATE_COMMUNICATIONS_FAILED	202
21.71	HA_LEASE_UPDATE_CONFLICT	202
21.72	HA_LEASE_UPDATE_CREATE_UPDATE_FAILED_ON_PEER	202
21.73	HA_LEASE_UPDATE_DELETE_FAILED_ON_PEER	202
21.74	HA_LEASE_UPDATE_FAILED	202
21.75	HA_LEASE_UPDATE_REJECTS_CAUSED_TERMINATION	203
21.76	HA_LOAD_BALANCING_DUID_MISSING	203
21.77	HA_LOAD_BALANCING_IDENTIFIER_MISSING	203
21.78	HA_LOAD_BALANCING_LEASE_DUID_MISSING	203
21.79	HA_LOAD_BALANCING_LEASE_IDENTIFIER_MISSING	203
21.80	HA_LOCAL_DHCP_DISABLE	203
21.81	HA_LOCAL_DHCP_ENABLE	203
21.82	HA_MAINTENANCE_CANCEL_HANDLER_FAILED	204
21.83	HA_MAINTENANCE_NOTIFY_CANCEL_COMMUNICATIONS_FAILED	204
21.84	HA_MAINTENANCE_NOTIFY_CANCEL_FAILED	204
21.85	HA_MAINTENANCE_NOTIFY_COMMUNICATIONS_FAILED	204
21.86	HA_MAINTENANCE_NOTIFY_FAILED	204
21.87	HA_MAINTENANCE_NOTIFY_HANDLER_FAILED	204
21.88	HA_MAINTENANCE_SHUTDOWN_SAFE	204
21.89	HA_MAINTENANCE_STARTED	205
21.90	HA_MAINTENANCE_STARTED_IN_PARTNER_DOWN	205
21.91	HA_MAINTENANCE_START_HANDLER_FAILED	205
21.92	HA_MISSING_CONFIGURATION	205
21.93	HA_PAUSE_CLIENT_LISTENER_FAILED	205
21.94	HA_PAUSE_CLIENT_LISTENER_ILLEGAL	205
21.95	HA_RESET_COMMUNICATIONS_FAILED	206
21.96	HA_RESET_FAILED	206
21.97	HA_RESET_HANDLER_FAILED	206
21.98	HA_RESUME_CLIENT_LISTENER_FAILED	206
21.99	HA_SCOPES_HANDLER_FAILED	206
21.100	HA_SERVICE_STARTED	206
21.101	HA_STATE_MACHINE_CONTINUED	206
21.102	HA_STATE_MACHINE_PAUSED	207
21.103	HA_STATE_TRANSITION	207

21.104	HA_STATE_TRANSITION_PASSIVE_BACKUP	207
21.105	HA_SUBNET4_SELECT_FAILED	207
21.106	HA_SUBNET4_SELECT_INVALID_HA_SERVER_NAME	207
21.107	HA_SUBNET4_SELECT_NOT_FOR_US	207
21.108	HA_SUBNET4_SELECT_NO_RELATIONSHIP_FOR_SUBNET	207
21.109	HA_SUBNET4_SELECT_NO_RELATIONSHIP_SELECTOR_FOR_SUBNET	208
21.110	HA_SUBNET4_SELECT_NO_SUBNET_SELECTED	208
21.111	HA_SUBNET6_SELECT_FAILED	208
21.112	HA_SUBNET6_SELECT_INVALID_HA_SERVER_NAME	208
21.113	HA_SUBNET6_SELECT_NOT_FOR_US	208
21.114	HA_SUBNET6_SELECT_NO_RELATIONSHIP_FOR_SUBNET	208
21.115	HA_SUBNET6_SELECT_NO_RELATIONSHIP_SELECTOR_FOR_SUBNET	209
21.116	HA_SUBNET6_SELECT_NO_SUBNET_SELECTED	209
21.117	HA_SYNC_COMPLETE_NOTIFY_COMMUNICATIONS_FAILED	209
21.118	HA_SYNC_COMPLETE_NOTIFY_FAILED	209
21.119	HA_SYNC_COMPLETE_NOTIFY_HANDLER_FAILED	209
21.120	HA_SYNC_FAILED	209
21.121	HA_SYNC_HANDLER_FAILED	210
21.122	HA_SYNC_START	210
21.123	HA_SYNC_SUCCESSFUL	210
21.124	HA_TERMINATED	210
21.125	HA_TERMINATED_PARTNER_DID_NOT_RESTART	210
21.126	HA_TERMINATED_RESTART_PARTNER	210
22	HOOKS	211
22.1	HOOKS_ALL_CALLOUTS_DEREGISTERED	211
22.2	HOOKS_CALLOUTS_BEGIN	211
22.3	HOOKS_CALLOUTS_COMPLETE	211
22.4	HOOKS_CALLOUTS_REMOVED	211
22.5	HOOKS_CALLOUT_CALLED	211
22.6	HOOKS_CALLOUT_DEREGISTERED	212
22.7	HOOKS_CALLOUT_ERROR	212
22.8	HOOKS_CALLOUT_EXCEPTION	212
22.9	HOOKS_CALLOUT_REGISTRATION	212
22.10	HOOKS_CLOSE_ERROR	212
22.11	HOOKS_HOOK_LIST_RESET	212
22.12	HOOKS_INCORRECT_VERSION	212
22.13	HOOKS_LIBPATH_SECURITY_WARNING	213
22.14	HOOKS_LIBRARY_CLOSED	213
22.15	HOOKS_LIBRARY_LOADED	213
22.16	HOOKS_LIBRARY_LOADING	213
22.17	HOOKS_LIBRARY_MULTI_THREADING_COMPATIBLE	213
22.18	HOOKS_LIBRARY_MULTI_THREADING_NOT_COMPATIBLE	213
22.19	HOOKS_LIBRARY_UNLOADED	213
22.20	HOOKS_LIBRARY_UNLOADING	214
22.21	HOOKS_LIBRARY_VERSION	214
22.22	HOOKS_LOAD_ERROR	214
22.23	HOOKS_LOAD_EXCEPTION	214
22.24	HOOKS_LOAD_FRAMEWORK_EXCEPTION	214
22.25	HOOKS_LOAD_SUCCESS	214
22.26	HOOKS_MULTI_THREADING_COMPATIBLE_EXCEPTION	214
22.27	HOOKS_NO_LOAD	215
22.28	HOOKS_NO_UNLOAD	215
22.29	HOOKS_NO_VERSION	215

22.30	HOOKS_OPEN_ERROR	215
22.31	HOOKS_STD_CALLOUT_REGISTERED	215
22.32	HOOKS_UNLOAD_ERROR	215
22.33	HOOKS_UNLOAD_EXCEPTION	215
22.34	HOOKS_UNLOAD_FRAMEWORK_EXCEPTION	216
22.35	HOOKS_UNLOAD_SUCCESS	216
22.36	HOOKS_VERSION_EXCEPTION	216
23	HOSTS	217
23.1	HOSTS_BACKENDS_REGISTERED	217
23.2	HOSTS_BACKEND_DEREGISTER	217
23.3	HOSTS_BACKEND_REGISTER	217
23.4	HOSTS_CFG_ADD_HOST	217
23.5	HOSTS_CFG_CACHE_HOST_DATA_SOURCE	217
23.6	HOSTS_CFG_CLOSE_HOST_DATA_SOURCE	217
23.7	HOSTS_CFG_DEL	218
23.8	HOSTS_CFG_DEL4	218
23.9	HOSTS_CFG_DEL6	218
23.10	HOSTS_CFG_DEL_ALL_SUBNET4	218
23.11	HOSTS_CFG_DEL_ALL_SUBNET6	218
23.12	HOSTS_CFG_GET_ALL	218
23.13	HOSTS_CFG_GET_ALL_ADDRESS4	218
23.14	HOSTS_CFG_GET_ALL_ADDRESS4_COUNT	219
23.15	HOSTS_CFG_GET_ALL_ADDRESS4_HOST	219
23.16	HOSTS_CFG_GET_ALL_ADDRESS6	219
23.17	HOSTS_CFG_GET_ALL_ADDRESS6_COUNT	219
23.18	HOSTS_CFG_GET_ALL_ADDRESS6_HOST	219
23.19	HOSTS_CFG_GET_ALL_COUNT	219
23.20	HOSTS_CFG_GET_ALL_HOST	219
23.21	HOSTS_CFG_GET_ALL_HOSTNAME	220
23.22	HOSTS_CFG_GET_ALL_HOSTNAME_COUNT	220
23.23	HOSTS_CFG_GET_ALL_HOSTNAME_HOST	220
23.24	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4	220
23.25	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4_COUNT	220
23.26	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4_HOST	220
23.27	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6	220
23.28	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6_COUNT	221
23.29	HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6_HOST	221
23.30	HOSTS_CFG_GET_ALL_IDENTIFIER	221
23.31	HOSTS_CFG_GET_ALL_IDENTIFIER_COUNT	221
23.32	HOSTS_CFG_GET_ALL_IDENTIFIER_HOST	221
23.33	HOSTS_CFG_GET_ALL_SUBNET_ID4	221
23.34	HOSTS_CFG_GET_ALL_SUBNET_ID4_COUNT	221
23.35	HOSTS_CFG_GET_ALL_SUBNET_ID4_HOST	222
23.36	HOSTS_CFG_GET_ALL_SUBNET_ID6	222
23.37	HOSTS_CFG_GET_ALL_SUBNET_ID6_COUNT	222
23.38	HOSTS_CFG_GET_ALL_SUBNET_ID6_HOST	222
23.39	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4	222
23.40	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4_COUNT	222
23.41	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4_HOST	222
23.42	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6	223
23.43	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6_COUNT	223
23.44	HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6_HOST	223
23.45	HOSTS_CFG_GET_ONE_PREFIX	223

23.46	HOSTS_CFG_GET_ONE_PREFIX_HOST	223
23.47	HOSTS_CFG_GET_ONE_PREFIX_NULL	223
23.48	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4	223
23.49	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4_HOST	224
23.50	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4_NULL	224
23.51	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6	224
23.52	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6_HOST	224
23.53	HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6_NULL	224
23.54	HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER	224
23.55	HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER_HOST	224
23.56	HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER_NULL	225
23.57	HOSTS_CFG_UPDATE_ADD	225
23.58	HOSTS_CFG_UPDATE_DEL4	225
23.59	HOSTS_CFG_UPDATE_DEL6	225
23.60	HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_ADDRESS4	225
23.61	HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER	225
23.62	HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER_HOST	225
23.63	HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER_NULL	226
23.64	HOSTS_MGR_ALTERNATE_GET6_PREFIX	226
23.65	HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_ADDRESS6	226
23.66	HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER	226
23.67	HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER_HOST	226
23.68	HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER_NULL	226
23.69	HOSTS_MGR_ALTERNATE_GET_ALL_SUBNET_ID_ADDRESS4	226
23.70	HOSTS_MGR_ALTERNATE_GET_ALL_SUBNET_ID_ADDRESS6	227
23.71	HOSTS_MGR_NON_UNIQUE_IP_UNSUPPORTED	227
24	HOST	229
24.1	HOST_CACHE_ADD	229
24.2	HOST_CACHE_ADD_DUPLICATE	229
24.3	HOST_CACHE_COMMAND_CLEAR	229
24.4	HOST_CACHE_COMMAND_CLEAR_FAILED	229
24.5	HOST_CACHE_COMMAND_FLUSH	229
24.6	HOST_CACHE_COMMAND_FLUSH_FAILED	229
24.7	HOST_CACHE_COMMAND_GET	230
24.8	HOST_CACHE_COMMAND_GET_BY_ID	230
24.9	HOST_CACHE_COMMAND_GET_BY_ID_FAILED	230
24.10	HOST_CACHE_COMMAND_GET_FAILED	230
24.11	HOST_CACHE_COMMAND_INSERT	230
24.12	HOST_CACHE_COMMAND_INSERT_FAILED	230
24.13	HOST_CACHE_COMMAND_LOAD	230
24.14	HOST_CACHE_COMMAND_LOAD_FAILED	230
24.15	HOST_CACHE_COMMAND_REMOVE	231
24.16	HOST_CACHE_COMMAND_REMOVE_FAILED	231
24.17	HOST_CACHE_COMMAND_SIZE	231
24.18	HOST_CACHE_COMMAND_SIZE_FAILED	231
24.19	HOST_CACHE_COMMAND_WRITE	231
24.20	HOST_CACHE_COMMAND_WRITE_FAILED	231
24.21	HOST_CACHE_CONFIGURATION_FAILED	231
24.22	HOST_CACHE_DEINIT_OK	231
24.23	HOST_CACHE_DEL_SUBNET_ID_ADDRESS4	232
24.24	HOST_CACHE_DEL_SUBNET_ID_ADDRESS6	232
24.25	HOST_CACHE_DEL_SUBNET_ID_IDENTIFIER4	232
24.26	HOST_CACHE_DEL_SUBNET_ID_IDENTIFIER6	232

24.27	HOST_CACHE_GET_ONE_PREFIX	232
24.28	HOST_CACHE_GET_ONE_PREFIX_HOST	232
24.29	HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS4	232
24.30	HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS4_HOST	233
24.31	HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS6	233
24.32	HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS6_HOST	233
24.33	HOST_CACHE_GET_ONE_SUBNET_ID_IDENTIFIER	233
24.34	HOST_CACHE_GET_ONE_SUBNET_ID_IDENTIFIER_HOST	233
24.35	HOST_CACHE_INIT_OK	233
24.36	HOST_CACHE_PATH_SECURITY_WARNING	233
24.37	HOST_CMDS_DEINIT_OK	234
24.38	HOST_CMDS_INIT_FAILED	234
24.39	HOST_CMDS_INIT_OK	234
24.40	HOST_CMDS_RESERV_ADD	234
24.41	HOST_CMDS_RESERV_ADD_FAILED	234
24.42	HOST_CMDS_RESERV_ADD_SUCCESS	234
24.43	HOST_CMDS_RESERV_DEL	234
24.44	HOST_CMDS_RESERV_DEL_FAILED	234
24.45	HOST_CMDS_RESERV_DEL_SUCCESS	235
24.46	HOST_CMDS_RESERV_GET	235
24.47	HOST_CMDS_RESERV_GET_ALL	235
24.48	HOST_CMDS_RESERV_GET_ALL_FAILED	235
24.49	HOST_CMDS_RESERV_GET_ALL_SUCCESS	235
24.50	HOST_CMDS_RESERV_GET_BY_ADDRESS	235
24.51	HOST_CMDS_RESERV_GET_BY_ADDRESS_FAILED	235
24.52	HOST_CMDS_RESERV_GET_BY_ADDRESS_SUCCESS	235
24.53	HOST_CMDS_RESERV_GET_BY_HOSTNAME	236
24.54	HOST_CMDS_RESERV_GET_BY_HOSTNAME_FAILED	236
24.55	HOST_CMDS_RESERV_GET_BY_HOSTNAME_SUCCESS	236
24.56	HOST_CMDS_RESERV_GET_BY_ID	236
24.57	HOST_CMDS_RESERV_GET_BY_ID_FAILED	236
24.58	HOST_CMDS_RESERV_GET_BY_ID_SUCCESS	236
24.59	HOST_CMDS_RESERV_GET_FAILED	236
24.60	HOST_CMDS_RESERV_GET_PAGE	236
24.61	HOST_CMDS_RESERV_GET_PAGE_FAILED	237
24.62	HOST_CMDS_RESERV_GET_PAGE_SUCCESS	237
24.63	HOST_CMDS_RESERV_GET_SUCCESS	237
24.64	HOST_CMDS_RESERV_UPDATE	237
24.65	HOST_CMDS_RESERV_UPDATE_FAILED	237
24.66	HOST_CMDS_RESERV_UPDATE_SUCCESS	237
25	HTTPS	239
25.1	HTTPS_REQUEST_RECEIVE_START	239
26	HTTP	241
26.1	HTTP_BAD_CLIENT_REQUEST_RECEIVED	241
26.2	HTTP_BAD_CLIENT_REQUEST_RECEIVED_DETAILS	241
26.3	HTTP_BAD_SERVER_RESPONSE_RECEIVED	241
26.4	HTTP_BAD_SERVER_RESPONSE_RECEIVED_DETAILS	241
26.5	HTTP_CLIENT_MT_STARTED	241
26.6	HTTP_CLIENT_PASSWORD_SECURITY_WARNING	242
26.7	HTTP_CLIENT_QUEUE_SIZE_GROWING	242
26.8	HTTP_CLIENT_REQUEST_AUTHORIZED	242
26.9	HTTP_CLIENT_REQUEST_BAD_AUTH_HEADER	242

26.10	HTTP_CLIENT_REQUEST_NOT_AUTHORIZED	242
26.11	HTTP_CLIENT_REQUEST_NO_AUTH_HEADER	242
26.12	HTTP_CLIENT_REQUEST_RECEIVED	242
26.13	HTTP_CLIENT_REQUEST_RECEIVED_DETAILS	243
26.14	HTTP_CLIENT_REQUEST_SEND	243
26.15	HTTP_CLIENT_REQUEST_SEND_DETAILS	243
26.16	HTTP_CLIENT_REQUEST_TIMEOUT_OCCURRED	243
26.17	HTTP_CLIENT_USER_SECURITY_WARNING	243
26.18	HTTP_COMMAND_MGR_HTTPS_SERVICE_REUSE_FAILED	243
26.19	HTTP_COMMAND_MGR_HTTPS_SERVICE_UPDATED	244
26.20	HTTP_COMMAND_MGR_HTTP_SERVICE_REUSE_FAILED	244
26.21	HTTP_COMMAND_MGR_HTTP_SERVICE_UPDATED	244
26.22	HTTP_COMMAND_MGR_SERVICE_STARTED	244
26.23	HTTP_COMMAND_MGR_SERVICE_STOPPING	244
26.24	HTTP_CONNECTION_CLOSE_CALLBACK_FAILED	244
26.25	HTTP_CONNECTION_HANDSHAKE_FAILED	244
26.26	HTTP_CONNECTION_HANDSHAKE_START	245
26.27	HTTP_CONNECTION_SHUTDOWN	245
26.28	HTTP_CONNECTION_SHUTDOWN_FAILED	245
26.29	HTTP_CONNECTION_STOP	245
26.30	HTTP_CONNECTION_STOP_FAILED	245
26.31	HTTP_CONNECTION_WATCH_SOCKET_CLEAR_ERROR	245
26.32	HTTP_CONNECTION_WATCH_SOCKET_CLOSE_ERROR	245
26.33	HTTP_CONNECTION_WATCH_SOCKET_MARK_READY_ERROR	246
26.34	HTTP_DATA_RECEIVED	246
26.35	HTTP_IDLE_CONNECTION_TIMEOUT_OCCURRED	246
26.36	HTTP_PREMATURE_CONNECTION_TIMEOUT_OCCURRED	246
26.37	HTTP_REQUEST_RECEIVE_START	246
26.38	HTTP_SERVER_RESPONSE_RECEIVED	246
26.39	HTTP_SERVER_RESPONSE_RECEIVED_DETAILS	246
26.40	HTTP_SERVER_RESPONSE_SEND	247
26.41	HTTP_SERVER_RESPONSE_SEND_DETAILS	247
27	KEY	249
27.1	KEY_LOOKUP_DISABLED	249
27.2	KEY_LOOKUP_FOUND	249
27.3	KEY_LOOKUP_NONE	249
27.4	KEY_PROCESSING_FAILED	249
27.5	KEY_PROCESSING_FAILED_UNSPECIFIED_ERROR	249
28	LEASE	251
28.1	LEASE_CMDS_ADD4	251
28.2	LEASE_CMDS_ADD4_CONFLICT	251
28.3	LEASE_CMDS_ADD4_FAILED	251
28.4	LEASE_CMDS_ADD6	251
28.5	LEASE_CMDS_ADD6_CONFLICT	251
28.6	LEASE_CMDS_ADD6_FAILED	251
28.7	LEASE_CMDS_BULK_APPLY6	252
28.8	LEASE_CMDS_BULK_APPLY6_FAILED	252
28.9	LEASE_CMDS_DEINIT_OK	252
28.10	LEASE_CMDS_DEL4	252
28.11	LEASE_CMDS_DEL4_FAILED	252
28.12	LEASE_CMDS_DEL6	252
28.13	LEASE_CMDS_DEL6_FAILED	252

28.14	LEASE_CMDS_FATAL_WRITE_LEASES4	252
28.15	LEASE_CMDS_FATAL_WRITE_LEASES6	253
28.16	LEASE_CMDS_GET4_FAILED	253
28.17	LEASE_CMDS_GET6_FAILED	253
28.18	LEASE_CMDS_INIT_OK	253
28.19	LEASE_CMDS_LEASE4_OFFER_FAILED	253
28.20	LEASE_CMDS_LEASES4_COMMITTED_FAILED	253
28.21	LEASE_CMDS_LEASES6_COMMITTED_CONFLICT	253
28.22	LEASE_CMDS_LEASES6_COMMITTED_FAILED	253
28.23	LEASE_CMDS_LEASES6_COMMITTED_LEASE_ERROR	254
28.24	LEASE_CMDS_LOAD_ERROR	254
28.25	LEASE_CMDS_PATH_SECURITY_WARNING	254
28.26	LEASE_CMDS_RESEND_DDNS4	254
28.27	LEASE_CMDS_RESEND_DDNS4_FAILED	254
28.28	LEASE_CMDS_RESEND_DDNS6	254
28.29	LEASE_CMDS_RESEND_DDNS6_FAILED	254
28.30	LEASE_CMDS_UPDATE4	254
28.31	LEASE_CMDS_UPDATE4_CONFLICT	255
28.32	LEASE_CMDS_UPDATE4_FAILED	255
28.33	LEASE_CMDS_UPDATE6	255
28.34	LEASE_CMDS_UPDATE6_CONFLICT	255
28.35	LEASE_CMDS_UPDATE6_FAILED	255
28.36	LEASE_CMDS_WIPE4	255
28.37	LEASE_CMDS_WIPE4_FAILED	255
28.38	LEASE_CMDS_WIPE6	255
28.39	LEASE_CMDS_WIPE6_FAILED	256
28.40	LEASE_QUERY_LOAD_FAILED	256
28.41	LEASE_QUERY_LOAD_OK	256
28.42	LEASE_QUERY_UNLOAD_OK	256
29	LEGAL	257
29.1	LEGAL_LOG_COMMAND_NO_LEGAL_STORE	257
29.2	LEGAL_LOG_COMMAND_WRITE_ERROR	257
29.3	LEGAL_LOG_DB_OPEN_CONNECTION_WITH_RETRY_FAILED	257
29.4	LEGAL_LOG_LEASE4_NO_LEGAL_STORE	257
29.5	LEGAL_LOG_LEASE4_RENDER_ERROR	257
29.6	LEGAL_LOG_LEASE4_WRITE_ERROR	258
29.7	LEGAL_LOG_LEASE6_NO_LEGAL_STORE	258
29.8	LEGAL_LOG_LEASE6_RENDER_ERROR	258
29.9	LEGAL_LOG_LEASE6_WRITE_ERROR	258
29.10	LEGAL_LOG_LOAD_ERROR	258
29.11	LEGAL_LOG_MYSQL_COMMIT	258
29.12	LEGAL_LOG_MYSQL_DB_RECONNECT_ATTEMPT_FAILED	258
29.13	LEGAL_LOG_MYSQL_DB_RECONNECT_ATTEMPT_SCHEDULE	259
29.14	LEGAL_LOG_MYSQL_DB_RECONNECT_FAILED	259
29.15	LEGAL_LOG_MYSQL_FATAL_ERROR	259
29.16	LEGAL_LOG_MYSQL_GET_VERSION	259
29.17	LEGAL_LOG_MYSQL_INSERT_LOG	259
29.18	LEGAL_LOG_MYSQL_INVALID_ACCESS	259
29.19	LEGAL_LOG_MYSQL_NO_TLS	259
29.20	LEGAL_LOG_MYSQL_ROLLBACK	259
29.21	LEGAL_LOG_MYSQL_START_TRANSACTION	260
29.22	LEGAL_LOG_MYSQL_TLS_CIPHER	260
29.23	LEGAL_LOG_PATH_SECURITY_WARNING	260

29.24	LEGAL_LOG_PGSQL_COMMIT	260
29.25	LEGAL_LOG_PGSQL_DB_RECONNECT_ATTEMPT_FAILED	260
29.26	LEGAL_LOG_PGSQL_DB_RECONNECT_ATTEMPT_SCHEDULE	260
29.27	LEGAL_LOG_PGSQL_DB_RECONNECT_FAILED	260
29.28	LEGAL_LOG_PGSQL_DEALLOC_ERROR	261
29.29	LEGAL_LOG_PGSQL_FATAL_ERROR	261
29.30	LEGAL_LOG_PGSQL_GET_VERSION	261
29.31	LEGAL_LOG_PGSQL_INSERT_LOG	261
29.32	LEGAL_LOG_PGSQL_INVALID_ACCESS	261
29.33	LEGAL_LOG_PGSQL_ROLLBACK	261
29.34	LEGAL_LOG_PGSQL_START_TRANSACTION	261
29.35	LEGAL_LOG_STORE_CLOSED	262
29.36	LEGAL_LOG_STORE_CLOSE_ERROR	262
29.37	LEGAL_LOG_STORE_OPEN	262
29.38	LEGAL_LOG_STORE_OPENED	262
29.39	LEGAL_LOG_SYSLOG	262
29.40	LEGAL_LOG_SYSLOG_STORE_OPEN	262
29.41	LEGAL_LOG_UNLOAD_ERROR	262
30	LFC	263
30.1	LFC_FAIL_PID_CREATE	263
30.2	LFC_FAIL_PID_DEL	263
30.3	LFC_FAIL_PROCESS	263
30.4	LFC_FAIL_ROTATE	263
30.5	LFC_PROCESSING	263
30.6	LFC_READ_STATS	263
30.7	LFC_ROTATING	264
30.8	LFC_RUNNING	264
30.9	LFC_START	264
30.10	LFC_TERMINATE	264
30.11	LFC_WRITE_STATS	264
31	LIMITS	265
31.1	LIMITS_CONFIGURATION_LEASE_BACKEND_NOT_AVAILABLE	265
31.2	LIMITS_CONFIGURATION_LEASE_BACKEND_SHOULD_HAVE_BEEN_AVAILABLE	265
31.3	LIMITS_CONFIGURED_ADDRESS_LIMIT_BY_CLIENT_CLASS	265
31.4	LIMITS_CONFIGURED_ADDRESS_LIMIT_BY_SUBNET	265
31.5	LIMITS_CONFIGURED_PREFIX_LIMIT_BY_CLIENT_CLASS	265
31.6	LIMITS_CONFIGURED_PREFIX_LIMIT_BY_SUBNET	265
31.7	LIMITS_CONFIGURED_RATE_LIMIT_BY_CLIENT_CLASS	266
31.8	LIMITS_CONFIGURED_RATE_LIMIT_BY_SUBNET	266
31.9	LIMITS_LEASE_LIMIT_EXCEEDED	266
31.10	LIMITS_LEASE_WITHIN_LIMITS	266
31.11	LIMITS_PACKET_WIIH_SUBNET_ID_RATE_NO_SUBNET	266
31.12	LIMITS_PACKET_WITH_CLIENT_CLASSES_RATE_LIMIT_DROPPED	266
31.13	LIMITS_PACKET_WITH_CLIENT_CLASSES_RATE_LIMIT_HONORED	266
31.14	LIMITS_PACKET_WITH_SUBNET_ID_RATE_LIMIT_DROPPED	267
31.15	LIMITS_PACKET_WITH_SUBNET_ID_RATE_LIMIT_HONORED	267
32	LOGIMPL	269
32.1	LOGIMPL_ABOVE_MAX_DEBUG	269
32.2	LOGIMPL_BAD_DEBUG_STRING	269
32.3	LOGIMPL_BELOW_MIN_DEBUG	269
33	LOG	271

33.1	LOG_BAD_DESTINATION	271
33.2	LOG_BAD_SEVERITY	271
33.3	LOG_BAD_STREAM	271
33.4	LOG_DUPLICATE_MESSAGE_ID	271
33.5	LOG_DUPLICATE_NAMESPACE	271
33.6	LOG_INPUT_OPEN_FAIL	272
33.7	LOG_INVALID_MESSAGE_ID	272
33.8	LOG_LOCK_TEST_MESSAGE	272
33.9	LOG_NAMESPACE_EXTRA_ARGS	272
33.10	LOG_NAMESPACE_INVALID_ARG	272
33.11	LOG_NAMESPACE_NO_ARGS	272
33.12	LOG_NO_MESSAGE_ID	272
33.13	LOG_NO_MESSAGE_TEXT	273
33.14	LOG_NO_SUCH_MESSAGE	273
33.15	LOG_OPEN_OUTPUT_FAIL	273
33.16	LOG_PREFIX_EXTRA_ARGS	273
33.17	LOG_PREFIX_INVALID_ARG	273
33.18	LOG_READING_LOCAL_FILE	273
33.19	LOG_READ_ERROR	274
33.20	LOG_UNRECOGNIZED_DIRECTIVE	274
33.21	LOG_WRITE_ERROR	274
34	MT	275
34.1	MT_TCP_LISTENER_MGR_STARTED	275
34.2	MT_TCP_LISTENER_MGR_STOPPED	275
34.3	MT_TCP_LISTENER_MGR_STOPPING	275
35	MYSQL	277
35.1	MYSQL_CB_CREATE_UPDATE_BY_POOL_OPTION4	277
35.2	MYSQL_CB_CREATE_UPDATE_BY_POOL_OPTION6	277
35.3	MYSQL_CB_CREATE_UPDATE_BY_PREFIX_OPTION6	277
35.4	MYSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION4	277
35.5	MYSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION6	277
35.6	MYSQL_CB_CREATE_UPDATE_CLIENT_CLASS4	277
35.7	MYSQL_CB_CREATE_UPDATE_CLIENT_CLASS6	278
35.8	MYSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER4	278
35.9	MYSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER6	278
35.10	MYSQL_CB_CREATE_UPDATE_OPTION4	278
35.11	MYSQL_CB_CREATE_UPDATE_OPTION6	278
35.12	MYSQL_CB_CREATE_UPDATE_OPTION_DEF4	278
35.13	MYSQL_CB_CREATE_UPDATE_OPTION_DEF6	278
35.14	MYSQL_CB_CREATE_UPDATE_SERVER4	278
35.15	MYSQL_CB_CREATE_UPDATE_SERVER6	279
35.16	MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK4	279
35.17	MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK6	279
35.18	MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION4	279
35.19	MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION6	279
35.20	MYSQL_CB_CREATE_UPDATE_SUBNET4	279
35.21	MYSQL_CB_CREATE_UPDATE_SUBNET6	279
35.22	MYSQL_CB_DELETE_ALL_CLIENT_CLASSES4	279
35.23	MYSQL_CB_DELETE_ALL_CLIENT_CLASSES4_RESULT	280
35.24	MYSQL_CB_DELETE_ALL_CLIENT_CLASSES6	280
35.25	MYSQL_CB_DELETE_ALL_CLIENT_CLASSES6_RESULT	280
35.26	MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4	280

35.27 MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4_RESULT	280
35.28 MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6	280
35.29 MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6_RESULT	280
35.30 MYSQL_CB_DELETE_ALL_OPTION_DEFS4	280
35.31 MYSQL_CB_DELETE_ALL_OPTION_DEFS4_RESULT	281
35.32 MYSQL_CB_DELETE_ALL_OPTION_DEFS6	281
35.33 MYSQL_CB_DELETE_ALL_OPTION_DEFS6_RESULT	281
35.34 MYSQL_CB_DELETE_ALL_SERVERS4	281
35.35 MYSQL_CB_DELETE_ALL_SERVERS4_RESULT	281
35.36 MYSQL_CB_DELETE_ALL_SERVERS6	281
35.37 MYSQL_CB_DELETE_ALL_SERVERS6_RESULT	281
35.38 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS4	281
35.39 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS4_RESULT	282
35.40 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS6	282
35.41 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS6_RESULT	282
35.42 MYSQL_CB_DELETE_ALL_SUBNETS4	282
35.43 MYSQL_CB_DELETE_ALL_SUBNETS4_RESULT	282
35.44 MYSQL_CB_DELETE_ALL_SUBNETS6	282
35.45 MYSQL_CB_DELETE_ALL_SUBNETS6_RESULT	282
35.46 MYSQL_CB_DELETE_BY_POOL_OPTION4	282
35.47 MYSQL_CB_DELETE_BY_POOL_OPTION4_RESULT	283
35.48 MYSQL_CB_DELETE_BY_POOL_OPTION6	283
35.49 MYSQL_CB_DELETE_BY_POOL_OPTION6_RESULT	283
35.50 MYSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6	283
35.51 MYSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6_RESULT	283
35.52 MYSQL_CB_DELETE_BY_PREFIX_SUBNET4	283
35.53 MYSQL_CB_DELETE_BY_PREFIX_SUBNET4_RESULT	283
35.54 MYSQL_CB_DELETE_BY_PREFIX_SUBNET6	283
35.55 MYSQL_CB_DELETE_BY_PREFIX_SUBNET6_RESULT	284
35.56 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION4	284
35.57 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION4_RESULT	284
35.58 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION6	284
35.59 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION6_RESULT	284
35.60 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4	284
35.61 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4_RESULT	284
35.62 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6	284
35.63 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6_RESULT	285
35.64 MYSQL_CB_DELETE_CLIENT_CLASS4	285
35.65 MYSQL_CB_DELETE_CLIENT_CLASS4_RESULT	285
35.66 MYSQL_CB_DELETE_CLIENT_CLASS6	285
35.67 MYSQL_CB_DELETE_CLIENT_CLASS6_RESULT	285
35.68 MYSQL_CB_DELETE_GLOBAL_PARAMETER4	285
35.69 MYSQL_CB_DELETE_GLOBAL_PARAMETER4_RESULT	285
35.70 MYSQL_CB_DELETE_GLOBAL_PARAMETER6	285
35.71 MYSQL_CB_DELETE_GLOBAL_PARAMETER6_RESULT	286
35.72 MYSQL_CB_DELETE_OPTION4	286
35.73 MYSQL_CB_DELETE_OPTION4_RESULT	286
35.74 MYSQL_CB_DELETE_OPTION6	286
35.75 MYSQL_CB_DELETE_OPTION6_RESULT	286
35.76 MYSQL_CB_DELETE_OPTION_DEF4	286
35.77 MYSQL_CB_DELETE_OPTION_DEF4_RESULT	286
35.78 MYSQL_CB_DELETE_OPTION_DEF6	286
35.79 MYSQL_CB_DELETE_OPTION_DEF6_RESULT	287
35.80 MYSQL_CB_DELETE_SERVER4	287

35.81	MYSQL_CB_DELETE_SERVER4_RESULT	287
35.82	MYSQL_CB_DELETE_SERVER6	287
35.83	MYSQL_CB_DELETE_SERVER6_RESULT	287
35.84	MYSQL_CB_DELETE_SHARED_NETWORK4	287
35.85	MYSQL_CB_DELETE_SHARED_NETWORK4_RESULT	287
35.86	MYSQL_CB_DELETE_SHARED_NETWORK6	287
35.87	MYSQL_CB_DELETE_SHARED_NETWORK6_RESULT	288
35.88	MYSQL_CB_DELETE_SHARED_NETWORK_OPTION4	288
35.89	MYSQL_CB_DELETE_SHARED_NETWORK_OPTION4_RESULT	288
35.90	MYSQL_CB_DELETE_SHARED_NETWORK_OPTION6	288
35.91	MYSQL_CB_DELETE_SHARED_NETWORK_OPTION6_RESULT	288
35.92	MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4	288
35.93	MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	288
35.94	MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6	288
35.95	MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT	289
35.96	MYSQL_CB_GET_ALL_CLIENT_CLASSES4	289
35.97	MYSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT	289
35.98	MYSQL_CB_GET_ALL_CLIENT_CLASSES6	289
35.99	MYSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT	289
35.100	MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS4	289
35.101	MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT	289
35.102	MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS6	289
35.103	MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT	290
35.104	MYSQL_CB_GET_ALL_OPTIONS4	290
35.105	MYSQL_CB_GET_ALL_OPTIONS4_RESULT	290
35.106	MYSQL_CB_GET_ALL_OPTIONS6	290
35.107	MYSQL_CB_GET_ALL_OPTIONS6_RESULT	290
35.108	MYSQL_CB_GET_ALL_OPTION_DEFS4	290
35.109	MYSQL_CB_GET_ALL_OPTION_DEFS4_RESULT	290
35.110	MYSQL_CB_GET_ALL_OPTION_DEFS6	290
35.111	MYSQL_CB_GET_ALL_OPTION_DEFS6_RESULT	291
35.112	MYSQL_CB_GET_ALL_SERVERS4	291
35.113	MYSQL_CB_GET_ALL_SERVERS4_RESULT	291
35.114	MYSQL_CB_GET_ALL_SERVERS6	291
35.115	MYSQL_CB_GET_ALL_SERVERS6_RESULT	291
35.116	MYSQL_CB_GET_ALL_SHARED_NETWORKS4	291
35.117	MYSQL_CB_GET_ALL_SHARED_NETWORKS4_RESULT	291
35.118	MYSQL_CB_GET_ALL_SHARED_NETWORKS6	291
35.119	MYSQL_CB_GET_ALL_SHARED_NETWORKS6_RESULT	292
35.120	MYSQL_CB_GET_ALL_SUBNETS4	292
35.121	MYSQL_CB_GET_ALL_SUBNETS4_RESULT	292
35.122	MYSQL_CB_GET_ALL_SUBNETS6	292
35.123	MYSQL_CB_GET_ALL_SUBNETS6_RESULT	292
35.124	MYSQL_CB_GET_CLIENT_CLASS4	292
35.125	MYSQL_CB_GET_CLIENT_CLASS6	292
35.126	MYSQL_CB_GET_GLOBAL_PARAMETER4	292
35.127	MYSQL_CB_GET_GLOBAL_PARAMETER6	293
35.128	MYSQL_CB_GET_HOST4	293
35.129	MYSQL_CB_GET_HOST6	293
35.130	MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES4	293
35.131	MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES4_RESULT	293
35.132	MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES6	293
35.133	MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES6_RESULT	293
35.134	MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4	293

35.135	MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4_RESULT	294
35.136	MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6	294
35.137	MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6_RESULT	294
35.138	MYSQL_CB_GET_MODIFIED_OPTIONS4	294
35.139	MYSQL_CB_GET_MODIFIED_OPTIONS4_RESULT	294
35.140	MYSQL_CB_GET_MODIFIED_OPTIONS6	294
35.141	MYSQL_CB_GET_MODIFIED_OPTIONS6_RESULT	294
35.142	MYSQL_CB_GET_MODIFIED_OPTION_DEFS4	295
35.143	MYSQL_CB_GET_MODIFIED_OPTION_DEFS4_RESULT	295
35.144	MYSQL_CB_GET_MODIFIED_OPTION_DEFS6	295
35.145	MYSQL_CB_GET_MODIFIED_OPTION_DEFS6_RESULT	295
35.146	MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS4	295
35.147	MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS4_RESULT	295
35.148	MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS6	295
35.149	MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS6_RESULT	296
35.150	MYSQL_CB_GET_MODIFIED_SUBNETS4	296
35.151	MYSQL_CB_GET_MODIFIED_SUBNETS4_RESULT	296
35.152	MYSQL_CB_GET_MODIFIED_SUBNETS6	296
35.153	MYSQL_CB_GET_MODIFIED_SUBNETS6_RESULT	296
35.154	MYSQL_CB_GET_OPTION4	296
35.155	MYSQL_CB_GET_OPTION6	296
35.156	MYSQL_CB_GET_OPTION_DEF4	296
35.157	MYSQL_CB_GET_OPTION_DEF6	297
35.158	MYSQL_CB_GET_PORT4	297
35.159	MYSQL_CB_GET_PORT6	297
35.160	MYSQL_CB_GET_RECENT_AUDIT_ENTRIES4	297
35.161	MYSQL_CB_GET_RECENT_AUDIT_ENTRIES4_RESULT	297
35.162	MYSQL_CB_GET_RECENT_AUDIT_ENTRIES6	297
35.163	MYSQL_CB_GET_RECENT_AUDIT_ENTRIES6_RESULT	297
35.164	MYSQL_CB_GET_SERVER4	297
35.165	MYSQL_CB_GET_SERVER6	298
35.166	MYSQL_CB_GET_SHARED_NETWORK4	298
35.167	MYSQL_CB_GET_SHARED_NETWORK6	298
35.168	MYSQL_CB_GET_SHARED_NETWORK_SUBNETS4	298
35.169	MYSQL_CB_GET_SHARED_NETWORK_SUBNETS4_RESULT	298
35.170	MYSQL_CB_GET_SHARED_NETWORK_SUBNETS6	298
35.171	MYSQL_CB_GET_SHARED_NETWORK_SUBNETS6_RESULT	298
35.172	MYSQL_CB_GET_SUBNET4_BY_PREFIX	298
35.173	MYSQL_CB_GET_SUBNET4_BY_SUBNET_ID	299
35.174	MYSQL_CB_GET_SUBNET6_BY_PREFIX	299
35.175	MYSQL_CB_GET_SUBNET6_BY_SUBNET_ID	299
35.176	MYSQL_CB_GET_TYPE4	299
35.177	MYSQL_CB_GET_TYPE6	299
35.178	MYSQL_CB_NO_TLS	299
35.179	MYSQL_CB_RECONNECT_ATTEMPT_FAILED4	299
35.180	MYSQL_CB_RECONNECT_ATTEMPT_FAILED6	299
35.181	MYSQL_CB_RECONNECT_ATTEMPT_SCHEDULE4	300
35.182	MYSQL_CB_RECONNECT_ATTEMPT_SCHEDULE6	300
35.183	MYSQL_CB_RECONNECT_FAILED4	300
35.184	MYSQL_CB_RECONNECT_FAILED6	300
35.185	MYSQL_CB_REGISTER_BACKEND_TYPE4	300
35.186	MYSQL_CB_REGISTER_BACKEND_TYPE6	300
35.187	MYSQL_CB_TLS_CIPHER	300
35.188	MYSQL_CB_UNREGISTER_BACKEND_TYPE4	300

35.189	MYSQL_CB_UNREGISTER_BACKEND_TYPE6	301
35.190	MYSQL_DEINIT_OK	301
35.191	MYSQL_FB_DB	301
35.192	MYSQL_HB_DB	301
35.193	MYSQL_HB_DB_GET_VERSION	301
35.194	MYSQL_HB_DB_READONLY	301
35.195	MYSQL_HB_DB_RECONNECT_ATTEMPT_FAILED	301
35.196	MYSQL_HB_DB_RECONNECT_ATTEMPT_SCHEDULE	302
35.197	MYSQL_HB_DB_RECONNECT_FAILED	302
35.198	MYSQL_HB_NO_TLS	302
35.199	MYSQL_HB_TLS_CIPHER	302
35.200	MYSQL_INIT_OK	302
35.201	MYSQL_LB_ADD_ADDR4	302
35.202	MYSQL_LB_ADD_ADDR6	302
35.203	MYSQL_LB_COMMIT	302
35.204	MYSQL_LB_DB	303
35.205	MYSQL_LB_DB_RECONNECT_ATTEMPT_FAILED	303
35.206	MYSQL_LB_DB_RECONNECT_ATTEMPT_SCHEDULE	303
35.207	MYSQL_LB_DB_RECONNECT_FAILED	303
35.208	MYSQL_LB_DELETED_EXPIRED_RECLAIMED	303
35.209	MYSQL_LB_DELETED_SUBNET4_ID	303
35.210	MYSQL_LB_DELETED_SUBNET6_ID	303
35.211	MYSQL_LB_DELETE_ADDR4	304
35.212	MYSQL_LB_DELETE_ADDR6	304
35.213	MYSQL_LB_DELETE_EXPIRED_RECLAIMED4	304
35.214	MYSQL_LB_DELETE_EXPIRED_RECLAIMED6	304
35.215	MYSQL_LB_GET4	304
35.216	MYSQL_LB_GET6	304
35.217	MYSQL_LB_GET_ADDR4	304
35.218	MYSQL_LB_GET_ADDR6	305
35.219	MYSQL_LB_GET_CLIENTID	305
35.220	MYSQL_LB_GET_DUID	305
35.221	MYSQL_LB_GET_EXPIRED4	305
35.222	MYSQL_LB_GET_EXPIRED6	305
35.223	MYSQL_LB_GET_HOSTNAME4	305
35.224	MYSQL_LB_GET_HOSTNAME6	305
35.225	MYSQL_LB_GET_HWADDR4	306
35.226	MYSQL_LB_GET_HWADDR6	306
35.227	MYSQL_LB_GET_IAID_DUID	306
35.228	MYSQL_LB_GET_IAID_SUBID_DUID	306
35.229	MYSQL_LB_GET_PAGE4	306
35.230	MYSQL_LB_GET_PAGE6	306
35.231	MYSQL_LB_GET_RELAYID4	306
35.232	MYSQL_LB_GET_RELAYID6	307
35.233	MYSQL_LB_GET_REMOTEID4	307
35.234	MYSQL_LB_GET_REMOTEID6	307
35.235	MYSQL_LB_GET_STATE4	307
35.236	MYSQL_LB_GET_STATE6	307
35.237	MYSQL_LB_GET_STATE_SUBID4	307
35.238	MYSQL_LB_GET_STATE_SUBID6	307
35.239	MYSQL_LB_GET_SUBID4	308
35.240	MYSQL_LB_GET_SUBID6	308
35.241	MYSQL_LB_GET_SUBID_CLIENTID	308
35.242	MYSQL_LB_GET_SUBID_HWADDR	308

35.243	MYSQL_LB_GET_SUBID_PAGE6	308
35.244	MYSQL_LB_GET_VERSION	308
35.245	MYSQL_LB_NEGATIVE_LEASES_STAT	308
35.246	MYSQL_LB_NO_TLS	309
35.247	MYSQL_LB_ROLLBACK	309
35.248	MYSQL_LB_SFLQ_CREATE_POOL4	309
35.249	MYSQL_LB_SFLQ_CREATE_POOL6	309
35.250	MYSQL_LB_SFLQ_PICK_LEASE4	309
35.251	MYSQL_LB_SFLQ_PICK_LEASE6	309
35.252	MYSQL_LB_SFLQ_POOL4_DELETE	309
35.253	MYSQL_LB_SFLQ_POOL4_GET_ALL	310
35.254	MYSQL_LB_SFLQ_POOL4_GET_BY_RANGE	310
35.255	MYSQL_LB_SFLQ_POOL4_GET_BY_SUBNET	310
35.256	MYSQL_LB_SFLQ_POOL6_DELETE	310
35.257	MYSQL_LB_SFLQ_POOL6_GET_ALL	310
35.258	MYSQL_LB_SFLQ_POOL6_GET_BY_RANGE	310
35.259	MYSQL_LB_SFLQ_POOL6_GET_BY_SUBNET	310
35.260	MYSQL_LB_TLS_CIPHER	311
35.261	MYSQL_LB_UPDATE_ADDR4	311
35.262	MYSQL_LB_UPDATE_ADDR6	311
35.263	MYSQL_LB_UPGRADE_EXTENDED_INFO4	311
35.264	MYSQL_LB_UPGRADE_EXTENDED_INFO4_ERROR	311
35.265	MYSQL_LB_UPGRADE_EXTENDED_INFO4_PAGE	311
35.266	MYSQL_LB_UPGRADE_EXTENDED_INFO6	311
35.267	MYSQL_LB_UPGRADE_EXTENDED_INFO6_ERROR	312
35.268	MYSQL_LB_UPGRADE_EXTENDED_INFO6_PAGE	312
36	NETCONF	313
36.1	NETCONF_BOOT_UPDATE_COMPLETED	313
36.2	NETCONF_CONFIG_CHANGED_DETAIL	313
36.3	NETCONF_CONFIG_CHANGE_EVENT	313
36.4	NETCONF_CONFIG_CHECK_FAIL	313
36.5	NETCONF_CONFIG_FAIL	313
36.6	NETCONF_CONFIG_SYNTAX_WARNING	314
36.7	NETCONF_CONTROL_SOCKET_INFO	314
36.8	NETCONF_FAILED	314
36.9	NETCONF_GET_CONFIG	314
36.10	NETCONF_GET_CONFIG_FAILED	314
36.11	NETCONF_GET_CONFIG_STARTED	314
36.12	NETCONF_MODULE_CHANGE_INTERNAL_ERROR	314
36.13	NETCONF_MODULE_MISSING_ERR	315
36.14	NETCONF_MODULE_MISSING_WARN	315
36.15	NETCONF_MODULE_REVISION_ERR	315
36.16	NETCONF_MODULE_REVISION_WARN	315
36.17	NETCONF_NOTIFICATION_INTERNAL_ERROR	315
36.18	NETCONF_NOTIFICATION_RECEIVED	315
36.19	NETCONF_NOT_SUBSCRIBED_TO_NOTIFICATIONS	315
36.20	NETCONF_RUN_EXIT	316
36.21	NETCONF_SET_CONFIG	316
36.22	NETCONF_SET_CONFIG_FAILED	316
36.23	NETCONF_SET_CONFIG_STARTED	316
36.24	NETCONF_STARTED	316
36.25	NETCONF_SUBSCRIBE_CONFIG	316
36.26	NETCONF_SUBSCRIBE_CONFIG_FAILED	316

36.27	NETCONF_SUBSCRIBE_NOTIFICATIONS	317
36.28	NETCONF_UPDATE_CONFIG	317
36.29	NETCONF_UPDATE_CONFIG_COMPLETED	317
36.30	NETCONF_UPDATE_CONFIG_FAILED	317
36.31	NETCONF_UPDATE_CONFIG_STARTED	317
36.32	NETCONF_VALIDATE_CONFIG	317
36.33	NETCONF_VALIDATE_CONFIG_COMPLETED	317
36.34	NETCONF_VALIDATE_CONFIG_FAILED	317
36.35	NETCONF_VALIDATE_CONFIG_REJECTED	318
36.36	NETCONF_VALIDATE_CONFIG_STARTED	318
37	PERFMON	319
37.1	PERFMON_ALARM_CLEARED	319
37.2	PERFMON_ALARM_TRIGGERED	319
37.3	PERFMON_CMDS_CONTROL_ERROR	319
37.4	PERFMON_CMDS_CONTROL_OK	319
37.5	PERFMON_CMDS_GET_ALL_DURATIONS_ERROR	319
37.6	PERFMON_CMDS_GET_ALL_DURATIONS_OK	320
37.7	PERFMON_DEINIT_OK	320
37.8	PERFMON_DHCP4_PKT_EVENTS	320
37.9	PERFMON_DHCP4_PKT_PROCESS_ERROR	320
37.10	PERFMON_DHCP4_SOCKET_RECEIVED_TIME_SUPPORT	320
37.11	PERFMON_DHCP6_PKT_EVENTS	320
37.12	PERFMON_DHCP6_PKT_PROCESS_ERROR	320
37.13	PERFMON_DHCP6_SOCKET_RECEIVED_TIME_SUPPORT	321
37.14	PERFMON_INIT_FAILED	321
37.15	PERFMON_INIT_OK	321
38	PGSQL	323
38.1	PGSQL_CB_CREATE_UPDATE_BY_POOL_OPTION4	323
38.2	PGSQL_CB_CREATE_UPDATE_BY_POOL_OPTION6	323
38.3	PGSQL_CB_CREATE_UPDATE_BY_PREFIX_OPTION6	323
38.4	PGSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION4	323
38.5	PGSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION6	323
38.6	PGSQL_CB_CREATE_UPDATE_CLIENT_CLASS4	323
38.7	PGSQL_CB_CREATE_UPDATE_CLIENT_CLASS6	324
38.8	PGSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER4	324
38.9	PGSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER6	324
38.10	PGSQL_CB_CREATE_UPDATE_OPTION4	324
38.11	PGSQL_CB_CREATE_UPDATE_OPTION6	324
38.12	PGSQL_CB_CREATE_UPDATE_OPTION_DEF4	324
38.13	PGSQL_CB_CREATE_UPDATE_OPTION_DEF6	324
38.14	PGSQL_CB_CREATE_UPDATE_SERVER4	324
38.15	PGSQL_CB_CREATE_UPDATE_SERVER6	325
38.16	PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK4	325
38.17	PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK6	325
38.18	PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION4	325
38.19	PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION6	325
38.20	PGSQL_CB_CREATE_UPDATE_SUBNET4	325
38.21	PGSQL_CB_CREATE_UPDATE_SUBNET6	325
38.22	PGSQL_CB_DELETE_ALL_CLIENT_CLASSES4	325
38.23	PGSQL_CB_DELETE_ALL_CLIENT_CLASSES4_RESULT	326
38.24	PGSQL_CB_DELETE_ALL_CLIENT_CLASSES6	326
38.25	PGSQL_CB_DELETE_ALL_CLIENT_CLASSES6_RESULT	326

38.26 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4	326
38.27 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4_RESULT	326
38.28 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6	326
38.29 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6_RESULT	326
38.30 PGSQL_CB_DELETE_ALL_OPTION_DEFS4	326
38.31 PGSQL_CB_DELETE_ALL_OPTION_DEFS4_RESULT	327
38.32 PGSQL_CB_DELETE_ALL_OPTION_DEFS6	327
38.33 PGSQL_CB_DELETE_ALL_OPTION_DEFS6_RESULT	327
38.34 PGSQL_CB_DELETE_ALL_SERVERS4	327
38.35 PGSQL_CB_DELETE_ALL_SERVERS4_RESULT	327
38.36 PGSQL_CB_DELETE_ALL_SERVERS6	327
38.37 PGSQL_CB_DELETE_ALL_SERVERS6_RESULT	327
38.38 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS4	327
38.39 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS4_RESULT	328
38.40 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS6	328
38.41 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS6_RESULT	328
38.42 PGSQL_CB_DELETE_ALL_SUBNETS4	328
38.43 PGSQL_CB_DELETE_ALL_SUBNETS4_RESULT	328
38.44 PGSQL_CB_DELETE_ALL_SUBNETS6	328
38.45 PGSQL_CB_DELETE_ALL_SUBNETS6_RESULT	328
38.46 PGSQL_CB_DELETE_BY_POOL_OPTION4	328
38.47 PGSQL_CB_DELETE_BY_POOL_OPTION4_RESULT	329
38.48 PGSQL_CB_DELETE_BY_POOL_OPTION6	329
38.49 PGSQL_CB_DELETE_BY_POOL_OPTION6_RESULT	329
38.50 PGSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6	329
38.51 PGSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6_RESULT	329
38.52 PGSQL_CB_DELETE_BY_PREFIX_SUBNET4	329
38.53 PGSQL_CB_DELETE_BY_PREFIX_SUBNET4_RESULT	329
38.54 PGSQL_CB_DELETE_BY_PREFIX_SUBNET6	329
38.55 PGSQL_CB_DELETE_BY_PREFIX_SUBNET6_RESULT	330
38.56 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION4	330
38.57 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION4_RESULT	330
38.58 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION6	330
38.59 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION6_RESULT	330
38.60 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4	330
38.61 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4_RESULT	330
38.62 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6	330
38.63 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6_RESULT	331
38.64 PGSQL_CB_DELETE_CLIENT_CLASS4	331
38.65 PGSQL_CB_DELETE_CLIENT_CLASS4_RESULT	331
38.66 PGSQL_CB_DELETE_CLIENT_CLASS6	331
38.67 PGSQL_CB_DELETE_CLIENT_CLASS6_RESULT	331
38.68 PGSQL_CB_DELETE_GLOBAL_PARAMETER4	331
38.69 PGSQL_CB_DELETE_GLOBAL_PARAMETER4_RESULT	331
38.70 PGSQL_CB_DELETE_GLOBAL_PARAMETER6	331
38.71 PGSQL_CB_DELETE_GLOBAL_PARAMETER6_RESULT	332
38.72 PGSQL_CB_DELETE_OPTION4	332
38.73 PGSQL_CB_DELETE_OPTION4_RESULT	332
38.74 PGSQL_CB_DELETE_OPTION6	332
38.75 PGSQL_CB_DELETE_OPTION6_RESULT	332
38.76 PGSQL_CB_DELETE_OPTION_DEF4	332
38.77 PGSQL_CB_DELETE_OPTION_DEF4_RESULT	332
38.78 PGSQL_CB_DELETE_OPTION_DEF6	332
38.79 PGSQL_CB_DELETE_OPTION_DEF6_RESULT	333

38.80	PGSQL_CB_DELETE_SERVER4	333
38.81	PGSQL_CB_DELETE_SERVER4_RESULT	333
38.82	PGSQL_CB_DELETE_SERVER6	333
38.83	PGSQL_CB_DELETE_SERVER6_RESULT	333
38.84	PGSQL_CB_DELETE_SHARED_NETWORK4	333
38.85	PGSQL_CB_DELETE_SHARED_NETWORK4_RESULT	333
38.86	PGSQL_CB_DELETE_SHARED_NETWORK6	333
38.87	PGSQL_CB_DELETE_SHARED_NETWORK6_RESULT	334
38.88	PGSQL_CB_DELETE_SHARED_NETWORK_OPTION4	334
38.89	PGSQL_CB_DELETE_SHARED_NETWORK_OPTION4_RESULT	334
38.90	PGSQL_CB_DELETE_SHARED_NETWORK_OPTION6	334
38.91	PGSQL_CB_DELETE_SHARED_NETWORK_OPTION6_RESULT	334
38.92	PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4	334
38.93	PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT	334
38.94	PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6	334
38.95	PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT	335
38.96	PGSQL_CB_GET_ALL_CLIENT_CLASSES4	335
38.97	PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT	335
38.98	PGSQL_CB_GET_ALL_CLIENT_CLASSES6	335
38.99	PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT	335
38.100	PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4	335
38.101	PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT	335
38.102	PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6	335
38.103	PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT	336
38.104	PGSQL_CB_GET_ALL_OPTIONS4	336
38.105	PGSQL_CB_GET_ALL_OPTIONS4_RESULT	336
38.106	PGSQL_CB_GET_ALL_OPTIONS6	336
38.107	PGSQL_CB_GET_ALL_OPTIONS6_RESULT	336
38.108	PGSQL_CB_GET_ALL_OPTION_DEFS4	336
38.109	PGSQL_CB_GET_ALL_OPTION_DEFS4_RESULT	336
38.110	PGSQL_CB_GET_ALL_OPTION_DEFS6	336
38.111	PGSQL_CB_GET_ALL_OPTION_DEFS6_RESULT	337
38.112	PGSQL_CB_GET_ALL_SERVERS4	337
38.113	PGSQL_CB_GET_ALL_SERVERS4_RESULT	337
38.114	PGSQL_CB_GET_ALL_SERVERS6	337
38.115	PGSQL_CB_GET_ALL_SERVERS6_RESULT	337
38.116	PGSQL_CB_GET_ALL_SHARED_NETWORKS4	337
38.117	PGSQL_CB_GET_ALL_SHARED_NETWORKS4_RESULT	337
38.118	PGSQL_CB_GET_ALL_SHARED_NETWORKS6	337
38.119	PGSQL_CB_GET_ALL_SHARED_NETWORKS6_RESULT	338
38.120	PGSQL_CB_GET_ALL_SUBNETS4	338
38.121	PGSQL_CB_GET_ALL_SUBNETS4_RESULT	338
38.122	PGSQL_CB_GET_ALL_SUBNETS6	338
38.123	PGSQL_CB_GET_ALL_SUBNETS6_RESULT	338
38.124	PGSQL_CB_GET_CLIENT_CLASS4	338
38.125	PGSQL_CB_GET_CLIENT_CLASS6	338
38.126	PGSQL_CB_GET_GLOBAL_PARAMETER4	338
38.127	PGSQL_CB_GET_GLOBAL_PARAMETER6	339
38.128	PGSQL_CB_GET_HOST4	339
38.129	PGSQL_CB_GET_HOST6	339
38.130	PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES4	339
38.131	PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES4_RESULT	339
38.132	PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES6	339
38.133	PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES6_RESULT	339

38.134	PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4	339
38.135	PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4_RESULT	340
38.136	PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6	340
38.137	PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6_RESULT	340
38.138	PGSQL_CB_GET_MODIFIED_OPTIONS4	340
38.139	PGSQL_CB_GET_MODIFIED_OPTIONS4_RESULT	340
38.140	PGSQL_CB_GET_MODIFIED_OPTIONS6	340
38.141	PGSQL_CB_GET_MODIFIED_OPTIONS6_RESULT	340
38.142	PGSQL_CB_GET_MODIFIED_OPTION_DEFS4	341
38.143	PGSQL_CB_GET_MODIFIED_OPTION_DEFS4_RESULT	341
38.144	PGSQL_CB_GET_MODIFIED_OPTION_DEFS6	341
38.145	PGSQL_CB_GET_MODIFIED_OPTION_DEFS6_RESULT	341
38.146	PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS4	341
38.147	PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS4_RESULT	341
38.148	PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS6	341
38.149	PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS6_RESULT	342
38.150	PGSQL_CB_GET_MODIFIED_SUBNETS4	342
38.151	PGSQL_CB_GET_MODIFIED_SUBNETS4_RESULT	342
38.152	PGSQL_CB_GET_MODIFIED_SUBNETS6	342
38.153	PGSQL_CB_GET_MODIFIED_SUBNETS6_RESULT	342
38.154	PGSQL_CB_GET_OPTION4	342
38.155	PGSQL_CB_GET_OPTION6	342
38.156	PGSQL_CB_GET_OPTION_DEF4	342
38.157	PGSQL_CB_GET_OPTION_DEF6	343
38.158	PGSQL_CB_GET_PORT4	343
38.159	PGSQL_CB_GET_PORT6	343
38.160	PGSQL_CB_GET_RECENT_AUDIT_ENTRIES4	343
38.161	PGSQL_CB_GET_RECENT_AUDIT_ENTRIES4_RESULT	343
38.162	PGSQL_CB_GET_RECENT_AUDIT_ENTRIES6	343
38.163	PGSQL_CB_GET_RECENT_AUDIT_ENTRIES6_RESULT	343
38.164	PGSQL_CB_GET_SERVER4	343
38.165	PGSQL_CB_GET_SERVER6	344
38.166	PGSQL_CB_GET_SHARED_NETWORK4	344
38.167	PGSQL_CB_GET_SHARED_NETWORK6	344
38.168	PGSQL_CB_GET_SHARED_NETWORK_SUBNETS4	344
38.169	PGSQL_CB_GET_SHARED_NETWORK_SUBNETS4_RESULT	344
38.170	PGSQL_CB_GET_SHARED_NETWORK_SUBNETS6	344
38.171	PGSQL_CB_GET_SHARED_NETWORK_SUBNETS6_RESULT	344
38.172	PGSQL_CB_GET_SUBNET4_BY_PREFIX	344
38.173	PGSQL_CB_GET_SUBNET4_BY_SUBNET_ID	345
38.174	PGSQL_CB_GET_SUBNET6_BY_PREFIX	345
38.175	PGSQL_CB_GET_SUBNET6_BY_SUBNET_ID	345
38.176	PGSQL_CB_GET_TYPE4	345
38.177	PGSQL_CB_GET_TYPE6	345
38.178	PGSQL_CB_RECONNECT_ATTEMPT_FAILED4	345
38.179	PGSQL_CB_RECONNECT_ATTEMPT_FAILED6	345
38.180	PGSQL_CB_RECONNECT_ATTEMPT_SCHEDULE4	345
38.181	PGSQL_CB_RECONNECT_ATTEMPT_SCHEDULE6	346
38.182	PGSQL_CB_RECONNECT_FAILED4	346
38.183	PGSQL_CB_RECONNECT_FAILED6	346
38.184	PGSQL_CB_REGISTER_BACKEND_TYPE4	346
38.185	PGSQL_CB_REGISTER_BACKEND_TYPE6	346
38.186	PGSQL_CB_UNREGISTER_BACKEND_TYPE4	346
38.187	PGSQL_CB_UNREGISTER_BACKEND_TYPE6	346

38.18	PGSQL_DEINIT_OK	346
38.18	PGSQL_FB_DB	347
38.19	PGSQL_HB_DB	347
38.19	PGSQL_HB_DB_GET_VERSION	347
38.19	PGSQL_HB_DB_READONLY	347
38.19	PGSQL_HB_DB_RECONNECT_ATTEMPT_FAILED	347
38.19	PGSQL_HB_DB_RECONNECT_ATTEMPT_SCHEDULE	347
38.19	PGSQL_HB_DB_RECONNECT_FAILED	347
38.19	PGSQL_INIT_OK	348
38.19	PGSQL_LB_ADD_ADDR4	348
38.19	PGSQL_LB_ADD_ADDR6	348
38.19	PGSQL_LB_COMMIT	348
38.20	PGSQL_LB_DB	348
38.20	PGSQL_LB_DB_RECONNECT_ATTEMPT_FAILED	348
38.20	PGSQL_LB_DB_RECONNECT_ATTEMPT_SCHEDULE	348
38.20	PGSQL_LB_DB_RECONNECT_FAILED	349
38.20	PGSQL_LB_DELETED_SUBNET4_ID	349
38.20	PGSQL_LB_DELETED_SUBNET6_ID	349
38.20	PGSQL_LB_DELETE_ADDR4	349
38.20	PGSQL_LB_DELETE_ADDR6	349
38.20	PGSQL_LB_DELETE_EXPIRED_RECLAIMED4	349
38.20	PGSQL_LB_DELETE_EXPIRED_RECLAIMED6	349
38.21	PGSQL_LB_GET4	350
38.21	PGSQL_LB_GET6	350
38.21	PGSQL_LB_GET_ADDR4	350
38.21	PGSQL_LB_GET_ADDR6	350
38.21	PGSQL_LB_GET_CLIENTID	350
38.21	PGSQL_LB_GET_DUID	350
38.21	PGSQL_LB_GET_EXPIRED4	350
38.21	PGSQL_LB_GET_EXPIRED6	351
38.21	PGSQL_LB_GET_HOSTNAME4	351
38.21	PGSQL_LB_GET_HOSTNAME6	351
38.22	PGSQL_LB_GET_HWADDR4	351
38.22	PGSQL_LB_GET_HWADDR6	351
38.22	PGSQL_LB_GET_IAID_DUID	351
38.22	PGSQL_LB_GET_IAID_SUBID_DUID	351
38.22	PGSQL_LB_GET_PAGE4	352
38.22	PGSQL_LB_GET_PAGE6	352
38.22	PGSQL_LB_GET_RELAYID4	352
38.22	PGSQL_LB_GET_RELAYID6	352
38.22	PGSQL_LB_GET_REMOTEID4	352
38.22	PGSQL_LB_GET_REMOTEID6	352
38.23	PGSQL_LB_GET_STATE4	352
38.23	PGSQL_LB_GET_STATE6	353
38.23	PGSQL_LB_GET_STATE_SUBID4	353
38.23	PGSQL_LB_GET_STATE_SUBID6	353
38.23	PGSQL_LB_GET_SUBID4	353
38.23	PGSQL_LB_GET_SUBID6	353
38.23	PGSQL_LB_GET_SUBID_CLIENTID	353
38.23	PGSQL_LB_GET_SUBID_HWADDR	353
38.23	PGSQL_LB_GET_SUBID_PAGE6	354
38.23	PGSQL_LB_GET_VERSION	354
38.24	PGSQL_LB_NEGATIVE_LEASES_STAT	354
38.24	PGSQL_LB_ROLLBACK	354

38.242	PGSQL_LB_SFLQ_CREATE_POOL4	354
38.243	PGSQL_LB_SFLQ_CREATE_POOL6	354
38.244	PGSQL_LB_SFLQ_PICK_LEASE4	354
38.245	PGSQL_LB_SFLQ_PICK_LEASE6	355
38.246	PGSQL_LB_SFLQ_POOL4_DELETE	355
38.247	PGSQL_LB_SFLQ_POOL4_GET_ALL	355
38.248	PGSQL_LB_SFLQ_POOL4_GET_BY_RANGE	355
38.249	PGSQL_LB_SFLQ_POOL4_GET_BY_SUBNET	355
38.250	PGSQL_LB_SFLQ_POOL6_DELETE	355
38.251	PGSQL_LB_SFLQ_POOL6_GET_ALL	355
38.252	PGSQL_LB_SFLQ_POOL6_GET_BY_RANGE	356
38.253	PGSQL_LB_SFLQ_POOL6_GET_BY_SUBNET	356
38.254	PGSQL_LB_UPDATE_ADDR4	356
38.255	PGSQL_LB_UPDATE_ADDR6	356
38.256	PGSQL_LB_UPGRADE_EXTENDED_INFO4	356
38.257	PGSQL_LB_UPGRADE_EXTENDED_INFO4_ERROR	356
38.258	PGSQL_LB_UPGRADE_EXTENDED_INFO4_PAGE	356
38.259	PGSQL_LB_UPGRADE_EXTENDED_INFO6	357
38.260	PGSQL_LB_UPGRADE_EXTENDED_INFO6_ERROR	357
38.261	PGSQL_LB_UPGRADE_EXTENDED_INFO6_PAGE	357
39	PING	359
39.1	PING_CHECK_CB4_UPDATE_FAILED	359
39.2	PING_CHECK_CHANNEL_ECHO_REPLY_RECEIVED	359
39.3	PING_CHECK_CHANNEL_ECHO_REQUEST_SENT	359
39.4	PING_CHECK_CHANNEL_MALFORMED_PACKET_RECEIVED	359
39.5	PING_CHECK_CHANNEL_NETWORK_WRITE_ERROR	359
39.6	PING_CHECK_CHANNEL_SOCKET_CLOSED	360
39.7	PING_CHECK_CHANNEL_SOCKET_CLOSE_ERROR	360
39.8	PING_CHECK_CHANNEL_SOCKET_OPENED	360
39.9	PING_CHECK_CHANNEL_SOCKET_READ_FAILED	360
39.10	PING_CHECK_CHANNEL_SOCKET_WRITE_FAILED	360
39.11	PING_CHECK_CHANNEL_STOP	360
39.12	PING_CHECK_CHANNEL_WATCH_SOCKET_CLEAR_ERROR	360
39.13	PING_CHECK_CHANNEL_WATCH_SOCKET_CLOSE_ERROR	361
39.14	PING_CHECK_DHCP4_SRV_CONFIGURED_FAILED	361
39.15	PING_CHECK_DUPLICATE_CHECK	361
39.16	PING_CHECK_LEASE4_OFFER_FAILED	361
39.17	PING_CHECK_LOAD_ERROR	361
39.18	PING_CHECK_LOAD_OK	361
39.19	PING_CHECK_MGR_CHANNEL_DOWN	361
39.20	PING_CHECK_MGR_LEASE_FREE_TO_USE	362
39.21	PING_CHECK_MGR_NEXT_ECHO_SCHEDULED	362
39.22	PING_CHECK_MGR_RECEIVED_ECHO_REPLY	362
39.23	PING_CHECK_MGR_RECEIVED_UNEXPECTED_ECHO_REPLY	362
39.24	PING_CHECK_MGR_RECEIVED_UNEXPECTED_UNREACHABLE_MSG	362
39.25	PING_CHECK_MGR_RECEIVED_UNREACHABLE_MSG	362
39.26	PING_CHECK_MGR_REPLY_RECEIVED_ERROR	362
39.27	PING_CHECK_MGR_REPLY_TIMEOUT_EXPIRED	363
39.28	PING_CHECK_MGR_SEND_COMPLETED_ERROR	363
39.29	PING_CHECK_MGR_STARTED	363
39.30	PING_CHECK_MGR_STARTED_SINGLE_THREADED	363
39.31	PING_CHECK_MGR_START_PING_CHECK	363
39.32	PING_CHECK_MGR_STOPPED	363

39.33	PING_CHECK_MGR_STOPPING	363
39.34	PING_CHECK_MGR_SUBNET_CONFIG_FAILED	364
39.35	PING_CHECK_NO_LEASE_OR_LEASE_REUSED	364
39.36	PING_CHECK_PAUSE_FAILED	364
39.37	PING_CHECK_PAUSE_ILLEGAL	364
39.38	PING_CHECK_PAUSE_PERMISSIONS_FAILED	364
39.39	PING_CHECK_RESUME_FAILED	364
39.40	PING_CHECK_UNEXPECTED_READ_ERROR	364
39.41	PING_CHECK_UNEXPECTED_WRITE_ERROR	365
39.42	PING_CHECK_UNLOAD	365
40	RADIUS	367
40.1	RADIUS_ACCESS_BUILD_FAILED	367
40.2	RADIUS_ACCESS_CACHE_GET	367
40.3	RADIUS_ACCESS_CACHE_INSERT	367
40.4	RADIUS_ACCESS_CONFLICT	367
40.5	RADIUS_ACCESS_DROP_PARKED_QUERY	367
40.6	RADIUS_ACCESS_ERROR	367
40.7	RADIUS_ACCESS_GET_IDENTIFIER	368
40.8	RADIUS_ACCESS_GET_IDENTIFIER_FAILED	368
40.9	RADIUS_ACCESS_HOST_BACKEND_ERROR	368
40.10	RADIUS_ACCESS_MAX_PENDING_REQUESTS	368
40.11	RADIUS_ACCESS_NO_HOST_CACHE	368
40.12	RADIUS_ACCESS_ORPHAN	368
40.13	RADIUS_ACCESS_RESUME_PARKED_QUERY	368
40.14	RADIUS_ACCESS_SUBNET_RESELECT	369
40.15	RADIUS_ACCESS_TERMINATE_ERROR	369
40.16	RADIUS_ACCOUNTING_ASYNC	369
40.17	RADIUS_ACCOUNTING_ASYNC_FAILED	369
40.18	RADIUS_ACCOUNTING_ASYNC_SUCCEED	369
40.19	RADIUS_ACCOUNTING_ERROR	369
40.20	RADIUS_ACCOUNTING_HISTORY_UPDATE_FAILED	369
40.21	RADIUS_ACCOUNTING_NO_HISTORY	369
40.22	RADIUS_ACCOUNTING_STATUS	370
40.23	RADIUS_ACCOUNTING_STATUS_ERROR	370
40.24	RADIUS_ACCOUNTING_STATUS_FAILED	370
40.25	RADIUS_ACCOUNTING_STATUS_SUCCEED	370
40.26	RADIUS_ACCOUNTING_SYNC	370
40.27	RADIUS_ACCOUNTING_SYNC_FAILED	370
40.28	RADIUS_ACCOUNTING_SYNC_SUCCEED	370
40.29	RADIUS_AUTHENTICATION_ASYNC	370
40.30	RADIUS_AUTHENTICATION_ASYNC_ACCEPTED	371
40.31	RADIUS_AUTHENTICATION_ASYNC_FAILED	371
40.32	RADIUS_AUTHENTICATION_ASYNC_REJECTED	371
40.33	RADIUS_AUTHENTICATION_STATUS	371
40.34	RADIUS_AUTHENTICATION_STATUS_ERROR	371
40.35	RADIUS_AUTHENTICATION_STATUS_FAILED	371
40.36	RADIUS_AUTHENTICATION_STATUS_SUCCEED	371
40.37	RADIUS_AUTHENTICATION_SYNC	372
40.38	RADIUS_AUTHENTICATION_SYNC_ACCEPTED	372
40.39	RADIUS_AUTHENTICATION_SYNC_FAILED	372
40.40	RADIUS_AUTHENTICATION_SYNC_REJECTED	372
40.41	RADIUS_BACKEND_GET4	372
40.42	RADIUS_BACKEND_GET6	372

40.43	RADIUS_CLEANUP_EXCEPTION	372
40.44	RADIUS_CONFIGURATION_FAILED	373
40.45	RADIUS_DECODE_MESSAGE	373
40.46	RADIUS_DEINIT_OK	373
40.47	RADIUS_ENCODE_MESSAGE	373
40.48	RADIUS_EXCHANGE_RECEIVED_ACCESS_ACCEPT	373
40.49	RADIUS_EXCHANGE_RECEIVED_ACCESS_REJECT	373
40.50	RADIUS_EXCHANGE_RECEIVED_ACCOUNTING_RESPONSE	373
40.51	RADIUS_EXCHANGE_RECEIVED_BAD_RESPONSE	374
40.52	RADIUS_EXCHANGE_RECEIVED_MISMATCH	374
40.53	RADIUS_EXCHANGE_RECEIVED_RESPONSE	374
40.54	RADIUS_EXCHANGE_RECEIVED_UNEXPECTED	374
40.55	RADIUS_HOOK_FAILED	374
40.56	RADIUS_INIT_OK	374
40.57	RADIUS_INTEGER_ATTRIBUTE_FROM_BYTES_FAILED	374
40.58	RADIUS_INTEGER_ATTRIBUTE_FROM_TEXT_FAILED	374
40.59	RADIUS_IPADDR_ATTRIBUTE_FROM_BYTES_FAILED	375
40.60	RADIUS_IPADDR_ATTRIBUTE_FROM_TEXT_FAILED	375
40.61	RADIUS_IPV6ADDR_ATTRIBUTE_FROM_BYTES_FAILED	375
40.62	RADIUS_IPV6ADDR_ATTRIBUTE_FROM_TEXT_FAILED	375
40.63	RADIUS_IPV6PREFIX_ATTRIBUTE_FROM_BYTES_FAILED	375
40.64	RADIUS_IPV6PREFIX_ATTRIBUTE_FROM_TEXT_FAILED	375
40.65	RADIUS_PAUSE_FAILED	375
40.66	RADIUS_PAUSE_ILLEGAL	376
40.67	RADIUS_PAUSE_PERMISSIONS_FAILED	376
40.68	RADIUS_REPLY_MESSAGE_ATTRIBUTE	376
40.69	RADIUS_RESUME_FAILED	376
40.70	RADIUS_SERVER_CONFIGURED	376
40.71	RADIUS_SESSION_HISTORY_APPEND_FAILED	376
40.72	RADIUS_SESSION_HISTORY_LOADED	376
40.73	RADIUS_SESSION_HISTORY_LOAD_FAILED	377
40.74	RADIUS_SESSION_HISTORY_OPENED	377
40.75	RADIUS_SESSION_HISTORY_OPEN_FAILED	377
40.76	RADIUS_SESSION_HISTORY_STORED	377
40.77	RADIUS_SESSION_HISTORY_STORE_FAILED	377
40.78	RADIUS_TCP_EXCHANGE_FAILURE	377
40.79	RADIUS_TCP_EXCHANGE_RECEIVED	377
40.80	RADIUS_TCP_EXCHANGE_RECEIVE_FAILED	378
40.81	RADIUS_TCP_EXCHANGE_SEND	378
40.82	RADIUS_TCP_EXCHANGE_START	378
40.83	RADIUS_TCP_EXCHANGE_START_ERROR	378
40.84	RADIUS_TCP_EXCHANGE_SUCCESS	378
40.85	RADIUS_THREAD_POOL_STARTED	378
40.86	RADIUS_TLS_STATUS	378
40.87	RADIUS_TLS_STATUS_ERROR	379
40.88	RADIUS_TLS_STATUS_FAILED	379
40.89	RADIUS_TLS_STATUS_SUCCEED	379
40.90	RADIUS_UDP_EXCHANGE_FAILED	379
40.91	RADIUS_UDP_EXCHANGE_MAX_PENDING	379
40.92	RADIUS_UDP_EXCHANGE_OPEN_FAILED	379
40.93	RADIUS_UDP_EXCHANGE_RECEIVED	379
40.94	RADIUS_UDP_EXCHANGE_RECEIVE_FAILED	380
40.95	RADIUS_UDP_EXCHANGE_SEND_FAILED	380
40.96	RADIUS_UDP_EXCHANGE_SEND_NEW	380

40.97	RADIUS_UDP_EXCHANGE_SEND_RETRY	380
40.98	RADIUS_UDP_EXCHANGE_SENT	380
40.99	RADIUS_UDP_EXCHANGE_START	380
40.100	RADIUS_UDP_EXCHANGE_SYNC_RETURN	380
40.101	RADIUS_UDP_EXCHANGE_TERMINATE	381
40.102	RADIUS_UDP_EXCHANGE_TIMEOUT	381
41	RBAC	383
41.1	RBAC_CONFIGURED_ACLS	383
41.2	RBAC_CONFIGURED_COMMANDS	383
41.3	RBAC_CONFIGURED_ROLES	383
41.4	RBAC_HTTP_AUTH_ERROR	383
41.5	RBAC_HTTP_AUTH_FAILED	383
41.6	RBAC_HTTP_AUTH_REJECT	384
41.7	RBAC_HTTP_AUTH_RESPONSE	384
41.8	RBAC_HTTP_RESPONSE_FAILED	384
41.9	RBAC_LOAD_FAILED	384
41.10	RBAC_LOAD_OK	384
41.11	RBAC_READ_API_FILES	384
41.12	RBAC_TRACE_HTTP_AUTH_ACCEPT	384
41.13	RBAC_TRACE_HTTP_AUTH_BAD_BODY_TYPE	385
41.14	RBAC_TRACE_HTTP_AUTH_BAD_COMMAND_TYPE	385
41.15	RBAC_TRACE_HTTP_AUTH_COMMAND	385
41.16	RBAC_TRACE_HTTP_AUTH_DISABLED	385
41.17	RBAC_TRACE_HTTP_AUTH_EMPTY_BODY	385
41.18	RBAC_TRACE_HTTP_AUTH_NO_COMMAND	385
41.19	RBAC_TRACE_HTTP_AUTH_NO_JSON	385
41.20	RBAC_TRACE_HTTP_AUTH_NO_REQUEST	386
41.21	RBAC_TRACE_HTTP_AUTH_NO_TLS_REJECT	386
41.22	RBAC_TRACE_HTTP_AUTH_RESPONSE	386
41.23	RBAC_TRACE_HTTP_AUTH_ROLE	386
41.24	RBAC_TRACE_HTTP_RESPONSE_BAD_BODY_TYPE	386
41.25	RBAC_TRACE_HTTP_RESPONSE_CONTEXT	386
41.26	RBAC_TRACE_HTTP_RESPONSE_DISABLED	386
41.27	RBAC_TRACE_HTTP_RESPONSE_EMPTY_BODY	386
41.28	RBAC_TRACE_HTTP_RESPONSE_EMPTY_BODY_LIST	387
41.29	RBAC_TRACE_HTTP_RESPONSE_MODIFIED	387
41.30	RBAC_TRACE_HTTP_RESPONSE_NO_ARGUMENTS	387
41.31	RBAC_UNLOAD_OK	387
42	RUN	389
42.1	RUN_SCRIPT_LOAD	389
42.2	RUN_SCRIPT_LOAD_ERROR	389
42.3	RUN_SCRIPT_UNLOAD	389
43	SFLQ	391
43.1	SFLQ_POOL4_DEL	391
43.2	SFLQ_POOL4_DEL_FAILED	391
43.3	SFLQ_POOL4_GET_ALL	391
43.4	SFLQ_POOL4_GET_ALL_FAILED	391
43.5	SFLQ_POOL4_GET_BY_RANGE	391
43.6	SFLQ_POOL4_GET_BY_RANGE_FAILED	391
43.7	SFLQ_POOL4_GET_BY_SUBNET	392
43.8	SFLQ_POOL4_GET_BY_SUBNET_FAILED	392

43.9	SFLQ_POOL4_REBUILD	392
43.10	SFLQ_POOL4_REBUILD_FAILED	392
43.11	SFLQ_POOL6_DEL	392
43.12	SFLQ_POOL6_DEL_FAILED	392
43.13	SFLQ_POOL6_GET_ALL	392
43.14	SFLQ_POOL6_GET_ALL_FAILED	392
43.15	SFLQ_POOL6_GET_BY_RANGE	393
43.16	SFLQ_POOL6_GET_BY_RANGE_FAILED	393
43.17	SFLQ_POOL6_GET_BY_SUBNET	393
43.18	SFLQ_POOL6_GET_BY_SUBNET_FAILED	393
43.19	SFLQ_POOL6_REBUILD	393
43.20	SFLQ_POOL6_REBUILD_FAILED	393
44	START	395
44.1	START_REKEY_TIMER	395
44.2	START_RETRY_TIMER	395
45	STAT	397
45.1	STAT_CMDS_DEINIT_OK	397
45.2	STAT_CMDS_INIT_OK	397
45.3	STAT_CMDS_LEASE4_FAILED	397
45.4	STAT_CMDS_LEASE4_GET	397
45.5	STAT_CMDS_LEASE4_GET_FAILED	397
45.6	STAT_CMDS_LEASE4_GET_INVALID	397
45.7	STAT_CMDS_LEASE4_GET_NO_SUBNETS	398
45.8	STAT_CMDS_LEASE4_ORPHANED_STATS	398
45.9	STAT_CMDS_LEASE6_FAILED	398
45.10	STAT_CMDS_LEASE6_GET	398
45.11	STAT_CMDS_LEASE6_GET_FAILED	398
45.12	STAT_CMDS_LEASE6_GET_INVALID	398
45.13	STAT_CMDS_LEASE6_GET_NO_SUBNETS	398
45.14	STAT_CMDS_LEASE6_ORPHANED_STATS	399
46	SUBNET	401
46.1	SUBNET_CMDS_DEINIT_OK	401
46.2	SUBNET_CMDS_INIT_FAILED	401
46.3	SUBNET_CMDS_INIT_OK	401
46.4	SUBNET_CMDS_NETWORK4_ADD_FAILED	401
46.5	SUBNET_CMDS_NETWORK4_DEL_FAILED	401
46.6	SUBNET_CMDS_NETWORK4_GET_FAILED	402
46.7	SUBNET_CMDS_NETWORK4_LIST_FAILED	402
46.8	SUBNET_CMDS_NETWORK4_SUBNET_ADD_FAILED	402
46.9	SUBNET_CMDS_NETWORK4_SUBNET_DEL_FAILED	402
46.10	SUBNET_CMDS_NETWORK6_ADD_FAILED	402
46.11	SUBNET_CMDS_NETWORK6_DEL_FAILED	402
46.12	SUBNET_CMDS_NETWORK6_GET_FAILED	403
46.13	SUBNET_CMDS_NETWORK6_LIST_FAILED	403
46.14	SUBNET_CMDS_NETWORK6_SUBNET_ADD_FAILED	403
46.15	SUBNET_CMDS_NETWORK6_SUBNET_DEL_FAILED	403
46.16	SUBNET_CMDS_NETWORK_ADD	403
46.17	SUBNET_CMDS_NETWORK_DEL	403
46.18	SUBNET_CMDS_NETWORK_GET	404
46.19	SUBNET_CMDS_NETWORK_GET_EMPTY	404
46.20	SUBNET_CMDS_NETWORK_LIST	404

46.21	SUBNET_CMDS_NETWORK_LIST_EMPTY	404
46.22	SUBNET_CMDS_NETWORK_SUBNET_ADD	404
46.23	SUBNET_CMDS_NETWORK_SUBNET_DEL	404
46.24	SUBNET_CMDS_SUBNET4_ADD_FAILED	404
46.25	SUBNET_CMDS_SUBNET4_DELTA_ADD_FAILED	405
46.26	SUBNET_CMDS_SUBNET4_DELTA_DEL_FAILED	405
46.27	SUBNET_CMDS_SUBNET4_DEL_FAILED	405
46.28	SUBNET_CMDS_SUBNET4_GET_FAILED	405
46.29	SUBNET_CMDS_SUBNET4_LIST_FAILED	405
46.30	SUBNET_CMDS_SUBNET4_UPDATE_FAILED	405
46.31	SUBNET_CMDS_SUBNET6_ADD_FAILED	406
46.32	SUBNET_CMDS_SUBNET6_DELTA_ADD_FAILED	406
46.33	SUBNET_CMDS_SUBNET6_DELTA_DEL_FAILED	406
46.34	SUBNET_CMDS_SUBNET6_DEL_FAILED	406
46.35	SUBNET_CMDS_SUBNET6_GET_FAILED	406
46.36	SUBNET_CMDS_SUBNET6_LIST_FAILED	406
46.37	SUBNET_CMDS_SUBNET6_UPDATE_FAILED	407
46.38	SUBNET_CMDS_SUBNET_ADD	407
46.39	SUBNET_CMDS_SUBNET_DEL	407
46.40	SUBNET_CMDS_SUBNET_GET	407
46.41	SUBNET_CMDS_SUBNET_GET_EMPTY	407
46.42	SUBNET_CMDS_SUBNET_LIST	407
46.43	SUBNET_CMDS_SUBNET_LIST_EMPTY	407
46.44	SUBNET_CMDS_SUBNET_UPDATE	408
47	TCP	409
47.1	TCP_CLIENT_BAD_SERVER_RESPONSE_RECEIVED	409
47.2	TCP_CLIENT_BAD_SERVER_RESPONSE_RECEIVED_DETAILS	409
47.3	TCP_CLIENT_CONNECTION_CLOSE_CALLBACK_FAILED	409
47.4	TCP_CLIENT_MT_STARTED	409
47.5	TCP_CLIENT_PREMATURE_CONNECTION_TIMEOUT_OCCURRED	409
47.6	TCP_CLIENT_QUEUE_SIZE_GROWING	410
47.7	TCP_CLIENT_REQUEST_SEND	410
47.8	TCP_CLIENT_SERVER_RESPONSE_RECEIVED	410
47.9	TCP_CONNECTION_REJECTED_BY_FILTER	410
47.10	TCP_CONNECTION_SHUTDOWN	410
47.11	TCP_CONNECTION_SHUTDOWN_FAILED	410
47.12	TCP_CONNECTION_STOP	410
47.13	TCP_CONNECTION_STOP_FAILED	411
47.14	TCP_DATA_RECEIVED	411
47.15	TCP_DATA_SENT	411
47.16	TCP_IDLE_CONNECTION_TIMEOUT_OCCURRED	411
47.17	TCP_REQUEST_RECEIVED_FAILED	411
47.18	TCP_REQUEST_RECEIVE_START	411
47.19	TCP_SERVER_CLIENT_REQUEST_RECEIVED	411
47.20	TCP_SERVER_RESPONSE_SEND	412
48	TKEY	413
48.1	TKEY_EXCHANGE_ANSWER_CLASS	413
48.2	TKEY_EXCHANGE_FAILED_TO_VERIFY	413
48.3	TKEY_EXCHANGE_FAIL_EMPTY_IN_TOKEN	413
48.4	TKEY_EXCHANGE_FAIL_EMPTY_OUT_TOKEN	413
48.5	TKEY_EXCHANGE_FAIL_EMPTY_RESPONSE	413
48.6	TKEY_EXCHANGE_FAIL_IO_ERROR	413

48.7	TKEY_EXCHANGE_FAIL_IO_STOPPED	414
48.8	TKEY_EXCHANGE_FAIL_IO_TIMEOUT	414
48.9	TKEY_EXCHANGE_FAIL_NOT_SIGNED	414
48.10	TKEY_EXCHANGE_FAIL_NO_RDATA	414
48.11	TKEY_EXCHANGE_FAIL_NO_RESPONSE_ANSWER	414
48.12	TKEY_EXCHANGE_FAIL_NULL_RESPONSE	414
48.13	TKEY_EXCHANGE_FAIL_RESPONSE_ERROR	414
48.14	TKEY_EXCHANGE_FAIL_TKEY_ERROR	414
48.15	TKEY_EXCHANGE_FAIL_TO_INIT	415
48.16	TKEY_EXCHANGE_FAIL_WRONG_RESPONSE_ANSWER_COUNT	415
48.17	TKEY_EXCHANGE_FAIL_WRONG_RESPONSE_ANSWER_TYPE	415
48.18	TKEY_EXCHANGE_FAIL_WRONG_RESPONSE_OPCODE	415
48.19	TKEY_EXCHANGE_IO_FETCH_RESULT	415
48.20	TKEY_EXCHANGE_NOT_A_RESPONSE	415
48.21	TKEY_EXCHANGE_OUT_TOKEN_NOT_EMPTY	415
48.22	TKEY_EXCHANGE_RDATA_COUNT	416
48.23	TKEY_EXCHANGE_RECEIVE_MESSAGE	416
48.24	TKEY_EXCHANGE_RESPONSE_TTL	416
48.25	TKEY_EXCHANGE_SEND_MESSAGE	416
48.26	TKEY_EXCHANGE_VALID	416
48.27	TKEY_EXCHANGE_VERIFIED	416
49	TLS	417
49.1	TLS_CONNECTION_HANDSHAKE_FAILED	417
49.2	TLS_CONNECTION_HANDSHAKE_START	417
49.3	TLS_REQUEST_RECEIVE_START	417
49.4	TLS_SERVER_RESPONSE_SEND	417
50	USER	419
50.1	USER_CHK_HOOK_LOAD_ERROR	419
50.2	USER_CHK_HOOK_UNLOAD_ERROR	419
50.3	USER_CHK_SUBNET4_SELECT_ERROR	419
50.4	USER_CHK_SUBNET4_SELECT_REGISTRY_NULL	419
50.5	USER_CHK_SUBNET6_SELECT_ERROR	419
50.6	USER_CHK_SUBNET6_SELECT_REGISTRY_NULL	420
51	Kea Debug Messages By Log Level	421
51.1	Messages printed on debuglevel 0	421
51.2	Messages printed on debuglevel 10	421
51.3	Messages printed on debuglevel 15	422
51.4	Messages printed on debuglevel 20	423
51.5	Messages printed on debuglevel 40	423
51.6	Messages printed on debuglevel 45	445
51.7	Messages printed on debuglevel 50	446
51.8	Messages printed on debuglevel 55	454
51.9	Messages printed on debuglevel 70	457

Kea is an open source implementation of the Dynamic Host Configuration Protocol (DHCP) servers, developed and maintained by Internet Systems Consortium (ISC).

This is the reference guide for Kea version 3.3.3. Links to the most up-to-date version of this document (in PDF, HTML, and plain text formats), along with other useful information about Kea, can be found in ISC's [Knowledgebase](#).

Please note that in the messages below, the percent sign (%) followed by a number is used to indicate a placeholder for data that is provided by the Kea code during its operation.

1.1 ALLOC_ENGINE_IGNOREING_UNSUITABLE_GLOBAL_ADDRESS

%1: ignoring globally reserved address %2, it falls outside %3

Logged at debug log level 40. This debug message is issued when the allocation engine determines that the globally reserved address falls outside the selected subnet or shared-network. The server should ignore the reserved address and attempt a dynamic allocation.

1.2 ALLOC_ENGINE_IGNOREING_UNSUITABLE_GLOBAL_ADDRESS6

%1: ignoring globally reserved address %2, it falls outside %3

Logged at debug log level 40. This debug message is issued when the allocation engine determines that the globally reserved address falls outside the selected subnet or shared-network. The server should ignore the reserved address and attempt a dynamic allocation.

1.3 ALLOC_ENGINE_LEASE_RECLAIMED

successfully reclaimed lease %1

Logged at debug log level 40. This debug message is logged when the allocation engine successfully reclaims a lease. The lease is now available for assignment.

1.4 ALLOC_ENGINE_V4_ALLOC_ERROR

%1: error during attempt to allocate an IPv4 address: %2

An error occurred during an attempt to allocate an IPv4 address, the reason for the failure being contained in the message. The server will return a message to the client refusing a lease. The first argument includes the client identification information.

1.5 ALLOC_ENGINE_V4_ALLOC_FAIL

%1: failed to allocate an IPv4 address after %2 attempt(s)

This is an old warning message issued when the allocation engine fails to allocate a lease for a client. This message includes a number of lease allocation attempts that the engine made before giving up. If the number of attempts is 0 because the engine was unable to use any of the address pools for the particular client, this message is not logged. Even though, several more detailed logs precede this message, it was left for backward compatibility. This message

may indicate that your address pool is too small for the number of clients you are trying to service and should be expanded. Alternatively, if you know that the number of concurrently active clients is less than the addresses you have available, you may want to consider reducing the lease lifetime. This way, addresses allocated to clients that are no longer active on the network will become available sooner.

1.6 ALLOC_ENGINE_V4_ALLOC_FAIL_CLASSES

%1: Failed to allocate an IPv4 address for client with classes: %2

This warning message is printed when Kea failed to allocate an address and the client's packet belongs to one or more classes. There may be several reasons why a lease was not assigned. One of them may be a case when all pools require packet to belong to certain classes and the incoming packet didn't belong to any of them. Another case where this information may be useful is to point out that the pool reserved to a given class has run out of addresses. If this message is displayed, consider checking the pool size and the classification definitions.

1.7 ALLOC_ENGINE_V4_ALLOC_FAIL_NO_POOLS

%1: no pools were available for the address allocation

This warning message is issued when the allocation engine fails to allocate a lease because it could not use any configured pools for the particular client. It is also possible that all of the subnets from which the allocation engine attempted to assign an address lack address pools. In this case, it should be considered misconfiguration if an operator expects that some clients should be assigned dynamic addresses. A subnet may lack any pools only when all clients should be assigned reserved IP addresses. Suppose the subnets connected to a shared network or a single subnet to which the client belongs have pools configured. In that case, this message is an indication that none of the pools could be used for the client because the client does not belong to appropriate client classes.

1.8 ALLOC_ENGINE_V4_ALLOC_FAIL_SHARED_NETWORK

%1: failed to allocate an IPv4 address in the shared network %2: %3 subnets have no available addresses, %4 subnets have no matching pools

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a shared network. The shared network should contain at least one subnet, but typically it aggregates multiple subnets. This log message indicates that the allocation engine could not find and allocate any suitable lease in any of the subnets within the shared network. The first argument includes the client identification information. The second argument specifies the shared network name. The remaining two arguments provide additional information useful for debugging why the allocation engine could not assign a lease. The allocation engine tries to allocate addresses from different subnets in the shared network, and it may fail for some subnets because there are no leases available in those subnets or the free leases are reserved to other clients. The number of such subnets is specified in the third argument. For other subnets the allocation may fail because their pools may not be available to the particular client. These pools are guarded by client classes that the client does not belong to. The fourth argument specifies the number of such subnets. By looking at the values in the third and fourth argument, an operator can identify the situations when there are no addresses left in some of the pools. He or she can also identify a client classification misconfigurations causing some clients to be refused the service.

1.9 ALLOC_ENGINE_V4_ALLOC_FAIL_SUBNET

%1: failed to allocate an IPv4 lease in the subnet %2, subnet-id %3, shared network %4

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a subnet. The first argument includes the client identification information. The second and third arguments identify the subnet. The fourth argument specifies the shared network, if the subnet belongs to a shared network. There are many reasons for failing lease allocations. One of them may be the pools exhaustion or existing reservations for the free leases.

However, in some cases, the allocation engine may fail to find a suitable pool for the client when the pools are only available to certain client classes, but the requesting client does not belong to them. Further log messages provide more information to distinguish between these different cases.

1.10 ALLOC_ENGINE_V4_DECLINED_RECOVERED

```
IPv4 address %1 was recovered after %2 seconds of probation-period
```

This informational message indicates that the specified address was reported as duplicate (client sent DECLINE) and the server marked this address as unavailable for a period of time. This time now has elapsed and the address has been returned to the available pool. This step concludes the decline recovery process.

1.11 ALLOC_ENGINE_V4_DISCOVER_ADDRESS_CONFLICT

```
%1: conflicting reservation for address %2 with existing lease %3
```

This warning message is issued when the DHCP server finds that the address reserved for the client can't be offered because this address is currently allocated to another client. The server will try to allocate a different address to the client to use until the conflict is resolved. The first argument includes the client identification information.

1.12 ALLOC_ENGINE_V4_DISCOVER_HR

```
client %1 sending DHCPDISCOVER has reservation for the address %2
```

Logged at debug log level 40. This message is issued when the allocation engine determines that the client sending the DHCPDISCOVER has a reservation for the specified address. The allocation engine will try to offer this address to the client.

1.13 ALLOC_ENGINE_V4_LEASES_RECLAMATION_COMPLETE

```
reclaimed %1 leases in %2
```

Logged at debug log level 40. This debug message is logged when the allocation engine completes reclamation of a set of expired leases. The maximum number of leases to be reclaimed in a single pass of the lease reclamation routine is configurable using 'max-reclaim-leases' parameter. However, the number of reclaimed leases may also be limited by the timeout value, configured with 'max-reclaim-time'. The message includes the number of reclaimed leases and the total time.

1.14 ALLOC_ENGINE_V4_LEASES_RECLAMATION_FAILED

```
reclamation of expired leases failed: %1
```

This error message is issued when the reclamation of the expired leases failed. The error message is displayed.

1.15 ALLOC_ENGINE_V4_LEASES_RECLAMATION_SLOW

```
expired leases still exist after %1 reclamations
```

This warning message is issued when the server has been unable to reclaim all expired leases in a specified number of consecutive attempts. This indicates that the value of "reclaim-timer-wait-time" may be too high. However, if this is just a short burst of leases' expirations the value does not have to be modified and the server should deal with this in subsequent reclamation attempts. If this is a result of a permanent increase of the server load, the value of

"reclaim-timer-wait-time" should be decreased, or the values of "max-reclaim-leases" and "max-reclaim-time" should be increased to allow processing more leases in a single cycle. Alternatively, these values may be set to 0 to remove the limitations on the number of leases and duration. However, this may result in longer periods of server's unresponsiveness to DHCP packets, while it processes the expired leases.

1.16 ALLOC_ENGINE_V4_LEASES_RECLAMATION_START

starting reclamation of expired leases (limit = %1 leases or %2 milliseconds)

Logged at debug log level 40. This debug message is issued when the allocation engine starts the reclamation of the expired leases. The maximum number of leases to be reclaimed and the timeout is included in the message. If any of these values is 0, it means "unlimited".

1.17 ALLOC_ENGINE_V4_LEASES_RECLAMATION_TIMEOUT

timeout of %1 ms reached while reclaiming IPv4 leases

Logged at debug log level 40. This debug message is issued when the allocation engine hits the timeout for performing reclamation of the expired leases. The reclamation will now be interrupted and all leases which haven't been reclaimed, because of the timeout, will be reclaimed when the next scheduled reclamation is started. The argument is the timeout value expressed in milliseconds.

1.18 ALLOC_ENGINE_V4_LEASE_RECLAIM

%1: reclaiming expired lease for address %2

Logged at debug log level 40. This debug message is issued when the server begins reclamation of the expired DHCPv4 lease. The first argument specifies the client identification information. The second argument holds the leased IPv4 address.

1.19 ALLOC_ENGINE_V4_LEASE_RECLAMATION_FAILED

failed to reclaim the lease %1: %2

This error message is logged when the allocation engine fails to reclaim an expired lease. The reason for the failure is included in the message. The error may be triggered in the lease expiration hook or while performing the operation on the lease database.

1.20 ALLOC_ENGINE_V4_NO_MORE_EXPIRED_LEASES

all expired leases have been reclaimed

Logged at debug log level 40. This debug message is issued when the server reclaims all expired DHCPv4 leases in the database.

1.21 ALLOC_ENGINE_V4_OFFER_EXISTING_LEASE

allocation engine will try to offer existing lease to the client %1

Logged at debug log level 40. This message is issued when the allocation engine determines that the client has a lease in the lease database, it doesn't have reservation for any other lease, and the leased address is not reserved for any other client. The allocation engine will try to offer the same lease to the client.

1.22 ALLOC_ENGINE_V4_OFFER_NEW_LEASE

allocation engine will try to offer new lease to the client %1

Logged at debug log level 40. This message is issued when the allocation engine will try to offer a new lease to the client. This is the case when the client doesn't have any existing lease, it has no reservation or the existing or reserved address is leased to another client. Also, the client didn't specify a hint, or the address in the hint is in use.

1.23 ALLOC_ENGINE_V4_OFFER_REQUESTED_LEASE

allocation engine will try to offer requested lease %1 to the client %2

Logged at debug log level 40. This message is issued when the allocation engine will try to offer the lease specified in the hint. This situation may occur when: (a) client doesn't have any reservations, (b) client has reservation but the reserved address is leased to another client.

1.24 ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE

begin deletion of reclaimed leases expired more than %1 seconds ago

Logged at debug log level 40. This debug message is issued when the allocation engine begins deletion of the reclaimed leases which have expired more than a specified number of seconds ago. This operation is triggered periodically according to the "flush-reclaimed-timer-wait-time" parameter. The "hold-reclaimed-time" parameter defines a number of seconds for which the leases are stored before they are removed.

1.25 ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE_COMPLETE

successfully deleted %1 expired-reclaimed leases

Logged at debug log level 40. This debug message is issued when the server successfully deletes "expired-reclaimed" leases from the lease database. The number of deleted leases is included in the log message.

1.26 ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE_FAILED

deletion of expired-reclaimed leases failed: %1

This error message is issued when the deletion of "expired-reclaimed" leases from the database failed. The error message is appended to the log message.

1.27 ALLOC_ENGINE_V4_REQUEST_ADDRESS_RESERVED

%1: requested address %2 is reserved

Logged at debug log level 40. This message is issued when the allocation engine refused to allocate address requested by the client because this address is reserved for another client. The first argument includes the client identification information.

1.28 ALLOC_ENGINE_V4_REQUEST_ALLOC_REQUESTED

%1: trying to allocate requested address %2

Logged at debug log level 40. This message is issued when the allocation engine is trying to allocate (or reuse an expired) address which has been requested by the client. The first argument includes the client identification information.

1.29 ALLOC_ENGINE_V4_REQUEST_EXTEND_LEASE

%1: extending lifetime of the lease for address %2

Logged at debug log level 40. This message is issued when the allocation engine determines that the client already has a lease whose lifetime can be extended, and which can be returned to the client. The first argument includes the client identification information.

1.30 ALLOC_ENGINE_V4_REQUEST_INVALID

client %1 having a reservation for address %2 is requesting invalid address %3

Logged at debug log level 40. This message is logged when the client, having a reservation for one address, is requesting a different address. The client is only allowed to do this when the reserved address is in use by another client. However, the allocation engine has determined that the reserved address is available and the client should request the reserved address.

1.31 ALLOC_ENGINE_V4_REQUEST_IN_USE

%1: requested address %2 is in use

Logged at debug log level 40. This message is issued when the client is requesting or has a reservation for an address which is in use. The first argument includes the client identification information.

1.32 ALLOC_ENGINE_V4_REQUEST_OUT_OF_POOL

client %1, which doesn't have a reservation, requested address %2 out of the dynamic pool

Logged at debug log level 40. This message is issued when the client has requested allocation of the address which doesn't belong to any address pool from which addresses are dynamically allocated. The client also doesn't have reservation for this address. This address could only be allocated if the client had reservation for it.

1.33 ALLOC_ENGINE_V4_REQUEST_PICK_ADDRESS

client %1 hasn't specified an address - picking available address from the pool

Logged at debug log level 40. This message is logged when the client hasn't specified any preferred address (the client should always do it, but Kea tries to be forgiving). The allocation engine will try to pick an available address from the dynamic pool and allocate it to the client.

1.34 ALLOC_ENGINE_V4_REQUEST_REMOVE_LEASE

%1: removing previous client's lease %2

Logged at debug log level 40. This message is logged when the allocation engine removes previous lease for the client because the client has been allocated new one.

1.35 ALLOC_ENGINE_V4_REQUEST_USE_HR

client %1 hasn't requested specific address, using reserved address %2

Logged at debug log level 40. This message is issued when the client is not requesting any specific address but the allocation engine has determined that there is a reservation for this client. The allocation engine will try to allocate the reserved address.

1.36 ALLOC_ENGINE_V4_REUSE_EXPIRED_LEASE_DATA

```
%1: reusing expired lease, updated lease information: %2
```

Logged at debug log level 55. This message is logged when the allocation engine is reusing an existing lease. The details of the updated lease are printed. The first argument includes the client identification information.

1.37 ALLOC_ENGINE_V6_ALLOC_ERROR

```
%1: error during attempt to allocate an IPv6 address: %2
```

An error occurred during an attempt to allocate an IPv6 address, the reason for the failure being contained in the message. The server will return a message to the client refusing a lease. The first argument includes the client identification information.

1.38 ALLOC_ENGINE_V6_ALLOC_FAIL

```
%1: failed to allocate an IPv6 lease after %2 attempt(s)
```

This is an old warning message issued when the allocation engine fails to allocate a lease for a client. This message includes a number of lease allocation attempts that the engine made before giving up. If the number of attempts is 0 because the engine was unable to use any of the pools for the particular client, this message is not logged. Even though, several more detailed logs precede this message, it was left for backward compatibility. This message may indicate that your pool is too small for the number of clients you are trying to service and should be expanded. Alternatively, if the you know that the number of concurrently active clients is less than the leases you have available, you may want to consider reducing the lease lifetime. This way, leases allocated to clients that are no longer active on the network will become available sooner.

1.39 ALLOC_ENGINE_V6_ALLOC_FAIL_CLASSES

```
%1: Failed to allocate an IPv6 address for client with classes: %2
```

This warning message is printed when Kea failed to allocate an address and the client's packet belongs to one or more classes. There may be several reasons why a lease was not assigned. One of them may be a case when all pools require packet to belong to certain classes and the incoming packet didn't belong to any of them. Another case where this information may be useful is to point out that the pool reserved to a given class has run out of addresses. If this message is displayed, you may consider checking the pool size and the classification definitions.

1.40 ALLOC_ENGINE_V6_ALLOC_FAIL_NO_POOLS

```
%1: no pools were available for the lease allocation
```

This warning message is issued when the allocation engine fails to allocate a lease because it could not use any configured pools for the particular client. It is also possible that all of the subnets from which the allocation engine attempted to assign an address lack address pools. In this case, it should be considered misconfiguration if an operator expects that some clients should be assigned dynamic addresses. A subnet may lack any pools only when all clients should be assigned reserved leases. Suppose the subnets connected to a shared network or a single subnet to which the client belongs have pools configured. In that case, this message is an indication that none of the pools could be used for the client because the client does not belong to appropriate client classes.

1.41 ALLOC_ENGINE_V6_ALLOC_FAIL_SHARED_NETWORK

%1: failed to allocate a lease in the shared network %2: %3 subnets have no available leases, %4 subnets have no matching pools

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a shared network. The shared network should contain at least one subnet, but typically it aggregates multiple subnets. This log message indicates that the allocation engine could not find and allocate any suitable lease in any of the subnets within the shared network. The first argument includes the client identification information. The second argument specifies the shared network name. The remaining two arguments provide additional information useful for debugging why the allocation engine could not assign a lease. The allocation engine tries to allocate leases from different subnets in the shared network, and it may fail for some subnets because there are no leases available in those subnets or the free leases are reserved to other clients. The number of such subnets is specified in the third argument. For other subnets the allocation may fail because their pools may not be available to the particular client. These pools are guarded by client classes that the client does not belong to. The fourth argument specifies the number of such subnets. By looking at the values in the third and fourth argument, an operator can identify the situations when there are no leases left in some of the pools. He or she can also identify client classification misconfigurations causing some clients to be refused the service.

1.42 ALLOC_ENGINE_V6_ALLOC_FAIL_SUBNET

%1: failed to allocate an IPv6 lease in the subnet %2, subnet-id %3, shared network %4

This warning message is issued when the allocation engine fails to allocate a lease for a client connected to a subnet. The first argument includes the client identification information. The second and third arguments identify the subnet. The fourth argument specifies the shared network, if the subnet belongs to a shared network. There are many reasons for failing lease allocations. One of them may be the pools exhaustion or existing reservations for the free leases. However, in some cases, the allocation engine may fail to find a suitable pool for the client when the pools are only available to certain client classes, but the requesting client does not belong to them. Further log messages provide more information to distinguish between these different cases.

1.43 ALLOC_ENGINE_V6_ALLOC_HR_LEASE_EXISTS

%1: lease type %2 for reserved address/prefix %3 already exists

Logged at debug log level 40. This debug message is issued when the allocation engine determines that the lease for the IPv6 address or prefix has already been allocated for the client and the client can continue using it. The first argument includes the client identification information.

1.44 ALLOC_ENGINE_V6_ALLOC_LEASES_HR

leases and static reservations found for client %1

Logged at debug log level 40. This message is logged when the allocation engine is in the process of allocating leases for the client, it found existing leases and static reservations for the client. The allocation engine will verify if existing leases match reservations. Those leases that are reserved for other clients and those that are not reserved for the client will be removed. All leases matching the reservations will be renewed and returned.

1.45 ALLOC_ENGINE_V6_ALLOC_LEASES_NO_HR

no reservations found but leases exist for client %1

Logged at debug log level 40. This message is logged when the allocation engine is in the process of allocating leases for the client and there are no static reservations, but lease(s) exist for the client. The allocation engine will remove leases which are reserved for other clients, and return all remaining leases to the client.

1.46 ALLOC_ENGINE_V6_ALLOC_NO_LEASES_HR

no leases found but reservations exist for client %1

Logged at debug log level 40. This message is logged when the allocation engine is in the process of allocating leases for the client. It hasn't found any existing leases for this client, but the client appears to have static reservations. The allocation engine will try to allocate the reserved resources for the client.

1.47 ALLOC_ENGINE_V6_ALLOC_NO_V6_HR

%1: unable to allocate reserved leases - no IPv6 reservations

Logged at debug log level 40. This message is logged when the allocation engine determines that the client has no IPv6 reservations and thus the allocation engine will have to try to allocate allocating leases from the dynamic pool or stop the allocation process if none can be allocated. The first argument includes the client identification information.

1.48 ALLOC_ENGINE_V6_ALLOC_UNRESERVED

no static reservations available - trying to dynamically allocate leases for client %1

Logged at debug log level 40. This debug message is issued when the allocation engine will attempt to allocate leases from the dynamic pools. This may be due to one of (a) there are no reservations for this client, (b) there are reservations for the client but they are not usable because the addresses are in use by another client or (c) we had a reserved lease but that has now been allocated to another client.

1.49 ALLOC_ENGINE_V6_CALCULATED_PREFERRED_LIFETIME

%1: using a calculated preferred-lifetime of %2

Logged at debug log level 40. This debug message indicates that the preferred-lifetime being returned to the client is defaulting to 62.5% of the valid-lifetime. This may occur if either the preferred-lifetime has not been explicitly configured, or the configured value is larger than the valid-lifetime. The arguments detail the client and the preferred-lifetime that will be used.

1.50 ALLOC_ENGINE_V6_DECLINED_RECOVERED

IPv6 address %1 was recovered after %2 seconds of probation-period

This informational message indicates that the specified address was reported as duplicate (client sent DECLINE) and the server marked this address as unavailable for a period of time. This time now has elapsed and the address has been returned to the available pool. This step concludes the decline recovery process.

1.51 ALLOC_ENGINE_V6_EXPIRED_HINT_RESERVED

%1: expired lease for the client's hint %2 is reserved for another client

Logged at debug log level 40. This message is logged when the allocation engine finds that the expired lease for the client's hint can't be reused because it is reserved for another client. The first argument includes the client identification information.

1.52 ALLOC_ENGINE_V6_EXTEND_ALLOC_UNRESERVED

allocate new (unreserved) leases for the renewing client %1

Logged at debug log level 40. This debug message is issued when the allocation engine is trying to allocate new leases for the renewing client because it was unable to renew any of the existing client's leases, e.g. because leases are reserved for another client or for any other reason.

1.53 ALLOC_ENGINE_V6_EXTEND_ERROR

%1: allocation engine experienced error with attempting to extend lease lifetime: %2

This error message indicates that an error was experienced during Renew or Rebind processing. Additional explanation is provided with this message. Depending on its nature, manual intervention may be required to continue processing messages from this particular client; other clients will be unaffected. The first argument includes the client identification information.

1.54 ALLOC_ENGINE_V6_EXTEND_LEASE

%1: extending lifetime of the lease type %2, address %3

Logged at debug log level 50. This debug message is issued when the allocation engine is trying to extend lifetime of the lease. The first argument includes the client identification information.

1.55 ALLOC_ENGINE_V6_EXTEND_LEASE_DATA

%1: detailed information about the lease being extended: %2

Logged at debug log level 55. This debug message prints detailed information about the lease which lifetime is being extended (renew or rebind). The first argument includes the client identification information.

1.56 ALLOC_ENGINE_V6_EXTEND_NEW_LEASE_DATA

%1: new lease information for the lease being extended: %2

Logged at debug log level 55. This debug message prints updated information about the lease to be extended. If the lease update is successful, the information printed by this message will be stored in the database. The first argument includes the client identification information.

1.57 ALLOC_ENGINE_V6_HINT_RESERVED

%1: lease for the client's hint %2 is reserved for another client

Logged at debug log level 40. This message is logged when the allocation engine cannot allocate the lease using the client's hint because the lease for this hint is reserved for another client. The first argument includes the client identification information.

1.58 ALLOC_ENGINE_V6_HR_ADDR_GRANTED

```
reserved address %1 was assigned to client %2
```

This informational message signals that the specified client was assigned the address reserved for it.

1.59 ALLOC_ENGINE_V6_HR_PREFIX_GRANTED

```
reserved prefix %1/%2 was assigned to client %3
```

This informational message signals that the specified client was assigned the prefix reserved for it.

1.60 ALLOC_ENGINE_V6_LEASES_RECLAMATION_COMPLETE

```
reclaimed %1 leases in %2
```

Logged at debug log level 40. This debug message is logged when the allocation engine completes reclamation of a set of expired leases. The maximum number of leases to be reclaimed in a single pass of the lease reclamation routine is configurable using 'max-reclaim-leases' parameter. However, the number of reclaimed leases may also be limited by the timeout value, configured with 'max-reclaim-time'. The message includes the number of reclaimed leases and the total time.

1.61 ALLOC_ENGINE_V6_LEASES_RECLAMATION_FAILED

```
reclamation of expired leases failed: %1
```

This error message is issued when the reclamation of the expired leases failed. The error message is displayed.

1.62 ALLOC_ENGINE_V6_LEASES_RECLAMATION_SLOW

```
expired leases still exist after %1 reclamations
```

This warning message is issued when the server has been unable to reclaim all expired leases in a specified number of consecutive attempts. This indicates that the value of "reclaim-timer-wait-time" may be too high. However, if this is just a short burst of leases' expirations the value does not have to be modified and the server should deal with this in subsequent reclamation attempts. If this is a result of a permanent increase of the server load, the value of "reclaim-timer-wait-time" should be decreased, or the values of "max-reclaim-leases" and "max-reclaim-time" should be increased to allow processing more leases in a single cycle. Alternatively, these values may be set to 0 to remove the limitations on the number of leases and duration. However, this may result in longer periods of server's unresponsiveness to DHCP packets, while it processes the expired leases.

1.63 ALLOC_ENGINE_V6_LEASES_RECLAMATION_START

```
starting reclamation of expired leases (limit = %1 leases or %2 milliseconds)
```

Logged at debug log level 40. This debug message is issued when the allocation engine starts the reclamation of the expired leases. The maximum number of leases to be reclaimed and the timeout is included in the message. If any of these values is 0, it means "unlimited".

1.64 ALLOC_ENGINE_V6_LEASES_RECLAMATION_TIMEOUT

timeout of %1 ms reached while reclaiming IPv6 leases

Logged at debug log level 40. This debug message is issued when the allocation engine hits the timeout for performing reclamation of the expired leases. The reclamation will now be interrupted and all leases which haven't been reclaimed, because of the timeout, will be reclaimed when the next scheduled reclamation is started. The argument is the timeout value expressed in milliseconds.

1.65 ALLOC_ENGINE_V6_LEASE_RECLAIM

%1: reclaiming expired lease for prefix %2/%3

Logged at debug log level 40. This debug message is issued when the server begins reclamation of the expired DHCPv6 lease. The reclaimed lease may either be an address lease or delegated prefix. The first argument provides the client identification information. The other arguments specify the prefix and the prefix length for the lease. The prefix length for address lease is equal to 128.

1.66 ALLOC_ENGINE_V6_LEASE_RECLAMATION_FAILED

failed to reclaim the lease %1: %2

This error message is logged when the allocation engine fails to reclaim an expired lease. The reason for the failure is included in the message. The error may be triggered in the lease expiration hook or while performing the operation on the lease database.

1.67 ALLOC_ENGINE_V6_NO_MORE_EXPIRED_LEASES

all expired leases have been reclaimed

Logged at debug log level 40. This debug message is issued when the server reclaims all expired DHCPv6 leases in the database.

1.68 ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE

begin deletion of reclaimed leases expired more than %1 seconds ago

Logged at debug log level 40. This debug message is issued when the allocation engine begins deletion of the reclaimed leases which have expired more than a specified number of seconds ago. This operation is triggered periodically according to the "flush-reclaimed-timer-wait-time" parameter. The "hold-reclaimed-time" parameter defines a number of seconds for which the leases are stored before they are removed.

1.69 ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE_COMPLETE

successfully deleted %1 expired-reclaimed leases

Logged at debug log level 40. This debug message is issued when the server successfully deletes "expired-reclaimed" leases from the lease database. The number of deleted leases is included in the log message.

1.70 ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE_FAILED

```
deletion of expired-reclaimed leases failed: %1
```

This error message is issued when the deletion of "expired-reclaimed" leases from the database failed. The error message is appended to the log message.

1.71 ALLOC_ENGINE_V6_RENEW_HR

```
allocating leases reserved for the client %1 as a result of Renew
```

Logged at debug log level 40. This debug message is issued when the allocation engine tries to allocate reserved leases for the client sending a Renew message. The server will also remove any leases that the client is trying to renew that are not reserved for the client.

1.72 ALLOC_ENGINE_V6_RENEW_REMOVE_RESERVED

```
%1: checking if existing client's leases are reserved for another client
```

Logged at debug log level 40. This message is logged when the allocation engine finds leases for the client and will check if these leases are reserved for another client. If they are, they will not be renewed for the client requesting their renewal. The first argument includes the client identification information.

1.73 ALLOC_ENGINE_V6_REUSE_EXPIRED_LEASE_DATA

```
%1: reusing expired lease, updated lease information: %2
```

Logged at debug log level 55. This message is logged when the allocation engine is reusing an existing lease. The details of the updated lease are printed. The first argument includes the client identification information.

1.74 ALLOC_ENGINE_V6_REVOKED_ADDR_LEASE

```
%1: address %2 was revoked from client %3 as it is reserved for client %4
```

This informational message is an indication that the specified IPv6 address was used by client A but it is now reserved for client B. Client A has been told to stop using it so that it can be leased to client B. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding a reservation for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their addresses.

1.75 ALLOC_ENGINE_V6_REVOKED_PREFIX_LEASE

```
%1: prefix %2/%3 was revoked from client %4 as it is reserved for client %5
```

This informational message is an indication that the specified IPv6 prefix was used by client A but it is now reserved for client B. Client A has been told to stop using it so that it can be leased to client B. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding a reservation for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their prefixes.

1.76 ALLOC_ENGINE_V6_REVOKED_SHARED_ADDR_LEASE

%1: address %2 was revoked from client %3 as it is reserved for %4 other clients

This informational message is an indication that the specified IPv6 address was used by client A but it is now reserved for multiple other clients. Client A has been told to stop using it so that it can be leased to one of the clients having the reservation for it. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding reservations for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their addresses.

1.77 ALLOC_ENGINE_V6_REVOKED_SHARED_PREFIX_LEASE

%1: prefix %2/%3 was revoked from client %4 as it is reserved for %5 other clients

This informational message is an indication that the specified IPv6 prefix was used by client A but it is now reserved for multiple other clients. Client A has been told to stop using it so that it can be leased to one of the clients having the reservation for it. This is a normal occurrence during conflict resolution, which can occur in cases such as the system administrator adding reservations for an address that is currently in use by another client. The server will fully recover from this situation, but clients will change their prefixes.

ASIODNS

2.1 ASIODNS_FETCH_COMPLETED

```
upstream fetch to %1(%2) has now completed
```

Logged at debug log level 70. A debug message, this records that the upstream fetch (a query made by the resolver on behalf of its client) to the specified address has completed.

2.2 ASIODNS_FETCH_STOPPED

```
upstream fetch to %1(%2) has been stopped
```

Logged at debug log level 40. An external component has requested the halting of an upstream fetch. This is an allowed operation, and the message should only appear if debug is enabled.

2.3 ASIODNS_OPEN_SOCKET

```
error %1 opening %2 socket to %3(%4)
```

The asynchronous I/O code encountered an error when trying to open a socket of the specified protocol in order to send a message to the target address. The number of the system error that caused the problem is given in the message.

2.4 ASIODNS_READ_DATA

```
error %1 reading %2 data from %3(%4)
```

The asynchronous I/O code encountered an error when trying to read data from the specified address on the given protocol. The number of the system error that caused the problem is given in the message.

2.5 ASIODNS_READ_TIMEOUT

```
receive timeout while waiting for data from %1(%2)
```

Logged at debug log level 50. An upstream fetch from the specified address timed out. This may happen for any number of reasons and is most probably a problem at the remote server or a problem on the network. The message will only appear if debug is enabled.

2.6 ASIODNS_SEND_DATA

error %1 sending data using %2 to %3(%4)

The asynchronous I/O code encountered an error when trying to send data to the specified address on the given protocol. The number of the system error that caused the problem is given in the message.

2.7 ASIODNS_UNKNOWN_ORIGIN

unknown origin for ASIO error code %1 (protocol: %2, address %3)

An internal consistency check on the origin of a message from the asynchronous I/O module failed. This may indicate an internal error; please submit a bug report.

2.8 ASIODNS_UNKNOWN_RESULT

unknown result (%1) when IOFetch::stop() was executed for I/O to %2(%3)

An internal error indicating that the termination method of the resolver's upstream fetch class was called with an unknown result code (which is given in the message). Please submit a bug report.

BAD

3.1 BAD_CLIENT_CREDENTIALS

bad client credentials: %1

This error message is issued when the client credential processing failed, including when the credential remaining lifetime is shorter than the TKEY lifetime. The argument details the error.

4.1 BOOTP_BOOTP_QUERY

recognized a BOOTP query: %1

Logged at debug log level 40. This debug message is printed when the BOOTP query was recognized. The BOOTP client class was added and the message type set to DHCPREQUEST. The query client and transaction identification are displayed.

4.2 BOOTP_LOAD

Bootp hooks library has been loaded

This info message indicates that the Bootp hooks library has been loaded.

4.3 BOOTP_PACKET_OPTIONS_SKIPPED

an error unpacking an option, caused subsequent options to be skipped: %1

Logged at debug log level 40. This debug message is issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv4 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

4.4 BOOTP_PACKET_PACK

%1: preparing on-wire format of the packet to be sent

Logged at debug log level 40. This debug message is issued when the server starts preparing the on-wire format of the packet to be sent back to the client. The argument specifies the client and the transaction identification information.

4.5 BOOTP_PACKET_PACK_FAIL

%1: preparing on-wire-format of the packet to be sent failed %2

This error message is issued when preparing an on-wire format of the packet has failed. The first argument identifies the client and the BOOTP transaction. The second argument includes the error string.

4.6 BOOTP_PACKET_UNPACK_FAILED

failed to parse query from %1 to %2, received over interface %3, reason: %4

Logged at debug log level 40. This debug message is issued when received DHCPv4 query is malformed and can't be parsed by the `buffer4_receive` callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

4.7 BOOTP_UNLOAD

Bootp hooks library has been unloaded

This info message indicates that the Bootp hooks library has been unloaded.

5.1 BULK_LEASE_QUERY4_UNSUPPORTED_MSG_TYPE

Dropping packet with an unsupported DHCPv4 message type %1 received from: %2

This error message is issued when a DHCPv4 packet type that the lease query hook does not support has been received. The first argument is the unsupported message type, the second the remote address of the connection which will be closed.

5.2 BULK_LEASE_QUERY6_UNSUPPORTED_MSG_TYPE

Dropping packet with an unsupported DHCPv6 message type %1 received from: %2

This error message is issued when a DHCPv6 packet type that the lease query hook does not support has been received. The first argument is the unsupported message type, the second the remote address of the connection which will be closed.

5.3 BULK_LEASE_QUERY_AT_MAX_CONCURRENT_QUERIES

Queuing query from: %1, details: %2, connection already has %3 queries in progress

Logged at debug log level 40. This debug message is issued when a requester sends a bulk lease query on a connection that already has the maximum number of queries allowed in progress. The first argument is the requester's address, the second details the query which has been queued, and the third is the value of max-concurrent-queries.

5.4 BULK_LEASE_QUERY_DEQUEUED

A query from %1, details: %2, dequeued.

Logged at debug log level 40. This debug message is issued when a query has been dequeued and will be processed. The first argument is the requester's address, the second details the query which has been dequeued.

5.5 BULK_LEASE_QUERY_DUPLICATE_XID

Dropping query from: %1, transaction id %2 is a duplicate

This warning message is issued when a requester sends a bulk lease query with the same transaction id while that requester already has a query with the same transaction id in-progress. The first argument is the requester's address, the second the duplicated transaction id.

5.6 BULK_LEASE_QUERY_EMPTY_REQUEST

A bulk lease query packet received from %1 is empty.

This error message is issued when received bulk lease query packet with no payload. The argument contains the remote address of the connection which will be closed.

5.7 BULK_LEASE_QUERY_INVALID_REQUEST

A bulk lease query packet received from %1 is invalid, query: %2, error: %3

This error message is issued when received invalid bulk lease query packet. The first argument is the remote address of the connection which will be closed, the second is the query, the last one is the error message.

5.8 BULK_LEASE_QUERY_LISTENER_START_FAILED

Bulk lease query listener thread pool could not be started, error %1

This error message is emitted when the bulk lease query listener's could (re)started following a reconfiguration event. This most likely cause would be a runtime configuration error, such an IP address that is invalid or already in-use as the service address. The argument details the error.

5.9 BULK_LEASE_QUERY_PAUSE_CHECK_PERMISSIONS_FAILED

An unexpected error occurred while checking pause permissions, error %1

This error message is emitted when attempting to pause Bulk Lease Query's listener. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

5.10 BULK_LEASE_QUERY_PAUSE_LISTENER_FAILED

Listener could not be paused, error %1

This error message is emitted when attempting to pause Bulk Lease Query's listener. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

5.11 BULK_LEASE_QUERY_PAUSE_LISTENER_ILLEGAL

Pausing multi-threaded processing failed: %1

This error message is emitted when attempting to pause the bulk lease query listener's thread pool from a worker thread. This error indicates that an action attempted on listener thread is trying to use a critical section which would result in a dead-lock. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

5.12 BULK_LEASE_QUERY_PROCESSING_UNEXPECTED_FAILURE

A bulk lease query packet processing throws unexpected exception: %1

This error message is issued when bulk lease query processing throws. The exception is displayed.

5.13 BULK_LEASE_QUERY_QUERY_RECEIVED

A bulk lease query packet received from %1, details: %2

Logged at debug log level 40. This debug message is issued when a bulk lease query has been received. The first argument is the address that sent the packet, the second details the packet.

5.14 BULK_LEASE_QUERY_REJECTED_CONNECTION

A new bulk lease query connection from %1 was rejected: %2

This debug message is issued when a new bulk lease query connection was rejected. The client address and the error message are displayed.

5.15 BULK_LEASE_QUERY_RESPONSE_SEND_ERROR

A bulk lease query response could not be sent to: %1, response: %2, error: %3

This debug message is issued when the server when an attempt to send a query response failed. The first argument is there address to which the response was destined, the second contains the response details, the third is the error explanation.

5.16 BULK_LEASE_QUERY_RESPONSE_SENT

A bulk lease query response sent to %1, details: %2

Logged at debug log level 40. This debug message is issued when a bulk lease query response has been sent. The first argument is the address that the packet has been sent to, the second details the packet.

5.17 BULK_LEASE_QUERY_RESUME_LISTENER_FAILED

Listener could not be resumed, error %1

This error message is emitted when attempting to resume Bulk Lease Query's listener. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

5.18 BULK_LEASE_QUERY_UNPACK_ERROR

A bulk lease query packet received from %1, could not be unpacked, error: %2

This error message is issued when received bulk lease query is malformed and could not be unpacked. The first argument is the remote address of the connection which will be closed, the second is the error explanation.

6.1 CB_CMDS_CLASS4_DEL_HANDLER_FAILED

```
remote-class4-del command failed: %1
```

This error message is issued to indicate that the remote-class4-del command handler failed while processing the command. The argument provides the reason for failure.

6.2 CB_CMDS_CLASS4_GET_ALL_HANDLER_FAILED

```
remote-class4-get-all command failed: %1
```

This error message is issued to indicate that the remote-class4-get-all command handler failed while processing the command. The argument provides the reason for failure.

6.3 CB_CMDS_CLASS4_GET_HANDLER_FAILED

```
remote-class4-get command failed: %1
```

This error message is issued to indicate that the remote-class4-get command handler failed while processing the command. The argument provides the reason for failure.

6.4 CB_CMDS_CLASS4_SET_HANDLER_FAILED

```
remote-class4-set command failed: %1
```

This error message is issued to indicate that the remote-class4-set command handler failed while processing the command. The argument provides the reason for failure.

6.5 CB_CMDS_CLASS6_DEL_HANDLER_FAILED

```
remote-class6-del command failed: %1
```

This error message is issued to indicate that the remote-class6-del command handler failed while processing the command. The argument provides the reason for failure.

6.6 CB_CMDS_CLASS6_GET_ALL_HANDLER_FAILED

```
remote-class6-get-all command failed: %1
```

This error message is issued to indicate that the remote-class6-get-all command handler failed while processing the command. The argument provides the reason for failure.

6.7 CB_CMDS_CLASS6_GET_HANDLER_FAILED

```
remote-class6-get command failed: %1
```

This error message is issued to indicate that the remote-class6-get command handler failed while processing the command. The argument provides the reason for failure.

6.8 CB_CMDS_CLASS6_SET_HANDLER_FAILED

```
remote-class6-set command failed: %1
```

This error message is issued to indicate that the remote-class6-set command handler failed while processing the command. The argument provides the reason for failure.

6.9 CB_CMDS_DEINIT_OK

```
unloading cb_cmds hooks library successful
```

This informational message indicates that the Config Commands hooks library has been unloaded successfully.

6.10 CB_CMDS_GLOBAL_PARAMETER4_DEL_HANDLER_FAILED

```
remote-global-parameter4-del command failed: %1
```

This error message is issued to indicate that the remote-global-parameter4-del command handler failed while processing the command. The argument provides the reason for failure.

6.11 CB_CMDS_GLOBAL_PARAMETER4_GET_ALL_HANDLER_FAILED

```
remote-global-parameter4-get-all command failed: %1
```

This error message is issued to indicate that the remote-global-parameter4-get-all command handler failed while processing the command. The argument provides the reason for failure.

6.12 CB_CMDS_GLOBAL_PARAMETER4_GET_HANDLER_FAILED

```
remote-global-parameter4-get command failed: %1
```

This error message is issued to indicate that the remote-global-parameter4-get command handler failed while processing the command. The argument provides the reason for failure.

6.13 CB_CMDS_GLOBAL_PARAMETER4_SET_HANDLER_FAILED

```
remote-global-parameter4-set command failed: %1
```

This error message is issued to indicate that the remote-global-parameter4-set command handler failed while processing the command. The argument provides the reason for failure.

6.14 CB_CMDS_GLOBAL_PARAMETER6_DEL_HANDLER_FAILED

```
remote-global-parameter6-del command failed: %1
```

This error message is issued to indicate that the remote-global-parameter6-del command handler failed while processing the command. The argument provides the reason for failure.

6.15 CB_CMDS_GLOBAL_PARAMETER6_GET_ALL_HANDLER_FAILED

```
remote-global-parameter6-get-all command failed: %1
```

This error message is issued to indicate that the remote-global-parameter6-get-all command handler failed while processing the command. The argument provides the reason for failure.

6.16 CB_CMDS_GLOBAL_PARAMETER6_GET_HANDLER_FAILED

```
remote-global-parameter6-get command failed: %1
```

This error message is issued to indicate that the remote-global-parameter6-get command handler failed while processing the command. The argument provides the reason for failure.

6.17 CB_CMDS_GLOBAL_PARAMETER6_SET_HANDLER_FAILED

```
remote-global-parameter6-set command failed: %1
```

This error message is issued to indicate that the remote-global-parameter6-set command handler failed while processing the command. The argument provides the reason for failure.

6.18 CB_CMDS_INIT_OK

```
loading cb_cmds hooks library successful
```

This informational message indicates that the Config Commands hooks library has been loaded successfully. Enjoy!

6.19 CB_CMDS_NETWORK4_DEL_HANDLER_FAILED

```
remote-network4-del command failed: %1
```

This error message is issued to indicate that the remote-network4-del command handler failed while processing the command. The argument provides the reason for failure.

6.20 CB_CMDS_NETWORK4_GET_HANDLER_FAILED

```
remote-network4-get command failed: %1
```

This error message is issued to indicate that the remote-network4-get command handler failed while processing the command. The argument provides the reason for failure.

6.21 CB_CMDS_NETWORK4_LIST_HANDLER_FAILED

```
remote-network4-list command failed: %1
```

This error message is issued to indicate that the remote-network4-list command handler failed while processing the command. The argument provides the reason for failure.

6.22 CB_CMDS_NETWORK4_SET_HANDLER_FAILED

```
remote-network4-set command failed: %1
```

This error message is issued to indicate that the remote-network4-set command handler failed while processing the command. The argument provides the reason for failure.

6.23 CB_CMDS_NETWORK6_DEL_HANDLER_FAILED

```
remote-network6-del command failed: %1
```

This error message is issued to indicate that the remote-network6-del command handler failed while processing the command. The argument provides the reason for failure.

6.24 CB_CMDS_NETWORK6_GET_HANDLER_FAILED

```
remote-network6-get command failed: %1
```

This error message is issued to indicate that the remote-network6-get command handler failed while processing the command. The argument provides the reason for failure.

6.25 CB_CMDS_NETWORK6_LIST_HANDLER_FAILED

```
remote-network6-list command failed: %1
```

This error message is issued to indicate that the remote-network6-list command handler failed while processing the command. The argument provides the reason for failure.

6.26 CB_CMDS_NETWORK6_SET_HANDLER_FAILED

```
remote-network6-set command failed: %1
```

This error message is issued to indicate that the remote-network6-set command handler failed while processing the command. The argument provides the reason for failure.

6.27 CB_CMDS_OPTION4_GLOBAL_DEL_HANDLER_FAILED

```
remote-global-option4-del command failed: %1
```

This error message is issued to indicate that the remote-global-option4-del command handler failed while processing the command. The argument provides the reason for failure.

6.28 CB_CMDS_OPTION4_GLOBAL_GET_ALL_HANDLER_FAILED

```
remote-global-option4-get-all command failed: %1
```

This error message is issued to indicate that the remote-global-option4-get-all command handler failed while processing the command. The argument provides the reason for failure.

6.29 CB_CMDS_OPTION4_GLOBAL_GET_HANDLER_FAILED

```
remote-global-option4-get command failed: %1
```

This error message is issued to indicate that the remote-global-option4-get command handler failed while processing the command. The argument provides the reason for failure.

6.30 CB_CMDS_OPTION4_GLOBAL_SET_HANDLER_FAILED

```
remote-global-option4-set command failed: %1
```

This error message is issued to indicate that the remote-global-option4-set command handler failed while processing the command. The argument provides the reason for failure.

6.31 CB_CMDS_OPTION4_NETWORK_DEL_HANDLER_FAILED

```
remote-network-option4-del command failed: %1
```

This error message is issued to indicate that the remote-network-option4-del command handler failed while processing the command. The argument provides the reason for failure.

6.32 CB_CMDS_OPTION4_NETWORK_SET_HANDLER_FAILED

```
remote-network-option4-set command failed: %1
```

This error message is issued to indicate that the remote-network-option4-set command handler failed while processing the command. The argument provides the reason for failure.

6.33 CB_CMDS_OPTION4_POOL_DEL_HANDLER_FAILED

```
remote-pool-option4-del command failed: %1
```

This error message is issued to indicate that the remote-pool-option4-del command handler failed while processing the command. The argument provides the reason for failure.

6.34 CB_CMDS_OPTION4_POOL_SET_HANDLER_FAILED

```
remote-pool-option4-set command failed: %1
```

This error message is issued to indicate that the remote-pool-option4-set command handler failed while processing the command. The argument provides the reason for failure.

6.35 CB_CMDS_OPTION4_SUBNET_DEL_HANDLER_FAILED

```
remote-subnet-option4-del command failed: %1
```

This error message is issued to indicate that the remote-subnet-option4-del command handler failed while processing the command. The argument provides the reason for failure.

6.36 CB_CMDS_OPTION4_SUBNET_SET_HANDLER_FAILED

```
remote-subnet-option4-set command failed: %1
```

This error message is issued to indicate that the remote-subnet-option4-set command handler failed while processing the command. The argument provides the reason for failure.

6.37 CB_CMDS_OPTION6_GLOBAL_DEL_HANDLER_FAILED

```
remote-global-option6-del command failed: %1
```

This error message is issued to indicate that the remote-global-option6-del command handler failed while processing the command. The argument provides the reason for failure.

6.38 CB_CMDS_OPTION6_GLOBAL_GET_ALL_HANDLER_FAILED

```
remote-global-option6-get-all command failed: %1
```

This error message is issued to indicate that the remote-global-option6-get-all command handler failed while processing the command. The argument provides the reason for failure.

6.39 CB_CMDS_OPTION6_GLOBAL_GET_HANDLER_FAILED

```
remote-global-option6-get command failed: %1
```

This error message is issued to indicate that the remote-global-option6-get command handler failed while processing the command. The argument provides the reason for failure.

6.40 CB_CMDS_OPTION6_GLOBAL_SET_HANDLER_FAILED

```
remote-global-option6-set command failed: %1
```

This error message is issued to indicate that the remote-global-option6-set command handler failed while processing the command. The argument provides the reason for failure.

6.41 CB_CMDS_OPTION6_NETWORK_DEL_HANDLER_FAILED

```
remote-network-option6-del command failed: %1
```

This error message is issued to indicate that the remote-network-option6-del command handler failed while processing the command. The argument provides the reason for failure.

6.42 CB_CMDS_OPTION6_NETWORK_SET_HANDLER_FAILED

```
remote-network-option6-set command failed: %1
```

This error message is issued to indicate that the remote-network-option6-set command handler failed while processing the command. The argument provides the reason for failure.

6.43 CB_CMDS_OPTION6_PD_POOL_DEL_HANDLER_FAILED

```
remote-pd-pool-option6-del command failed: %1
```

This error message is issued to indicate that the remote-pd-pool-option6-del command handler failed while processing the command. The argument provides the reason for failure.

6.44 CB_CMDS_OPTION6_PD_POOL_SET_HANDLER_FAILED

```
remote-pd-pool-option6-set command failed: %1
```

This error message is issued to indicate that the remote-pd-pool-option6-set command handler failed while processing the command. The argument provides the reason for failure.

6.45 CB_CMDS_OPTION6_POOL_DEL_HANDLER_FAILED

```
remote-pool-option6-del command failed: %1
```

This error message is issued to indicate that the remote-pool-option6-del command handler failed while processing the command. The argument provides the reason for failure.

6.46 CB_CMDS_OPTION6_POOL_SET_HANDLER_FAILED

```
remote-pool-option6-set command failed: %1
```

This error message is issued to indicate that the remote-pool-option6-set command handler failed while processing the command. The argument provides the reason for failure.

6.47 CB_CMDS_OPTION6_SUBNET_DEL_HANDLER_FAILED

```
remote-subnet-option6-del command failed: %1
```

This error message is issued to indicate that the remote-subnet-option6-del command handler failed while processing the command. The argument provides the reason for failure.

6.48 CB_CMDS_OPTION6_SUBNET_SET_HANDLER_FAILED

```
remote-subnet-option6-set command failed: %1
```

This error message is issued to indicate that the remote-subnet-option6-set command handler failed while processing the command. The argument provides the reason for failure.

6.49 CB_CMDS_OPTION_DEF4_DEL_HANDLER_FAILED

```
remote-option-def4-del command failed: %1
```

This error message is issued to indicate that the remote-option-def4-del command handler failed while processing the command. The argument provides the reason for failure.

6.50 CB_CMDS_OPTION_DEF4_GET_ALL_HANDLER_FAILED

```
remote-option-def4-get-all command failed: %1
```

This error message is issued to indicate that the remote-option-def4-get-all command handler failed while processing the command. The argument provides the reason for failure.

6.51 CB_CMDS_OPTION_DEF4_GET_HANDLER_FAILED

```
remote-option-def4-get command failed: %1
```

This error message is issued to indicate that the remote-option-def4-get command handler failed while processing the command. The argument provides the reason for failure.

6.52 CB_CMDS_OPTION_DEF4_SET_HANDLER_FAILED

```
remote-option-def4-set command failed: %1
```

This error message is issued to indicate that the remote-option-def4-set command handler failed while processing the command. The argument provides the reason for failure.

6.53 CB_CMDS_OPTION_DEF6_DEL_HANDLER_FAILED

```
remote-option-def6-del command failed: %1
```

This error message is issued to indicate that the remote-option-def6-del command handler failed while processing the command. The argument provides the reason for failure.

6.54 CB_CMDS_OPTION_DEF6_GET_ALL_HANDLER_FAILED

```
remote-option-def6-get-all command failed: %1
```

This error message is issued to indicate that the remote-option-def6-get-all command handler failed while processing the command. The argument provides the reason for failure.

6.55 CB_CMDS_OPTION_DEF6_GET_HANDLER_FAILED

```
remote-option-def6-get command failed: %1
```

This error message is issued to indicate that the remote-option-def6-get command handler failed while processing the command. The argument provides the reason for failure.

6.56 CB_CMDS_OPTION_DEF6_SET_HANDLER_FAILED

```
remote-option-def6-set command failed: %1
```

This error message is issued to indicate that the remote-option-def6-set command handler failed while processing the command. The argument provides the reason for failure.

6.57 CB_CMDS_SERVER4_DEL_HANDLER_FAILED

```
remote-server4-del command failed: %1
```

This error message is issued to indicate that the remote-server4-del command handler failed while processing the command. The argument provides the reason for failure.

6.58 CB_CMDS_SERVER4_GET_ALL_HANDLER_FAILED

```
remote-server4-get-all command failed: %1
```

This error message is issued to indicate that the remote-server4-get-all command handler failed while processing the command. The argument provides the reason for failure.

6.59 CB_CMDS_SERVER4_GET_HANDLER_FAILED

```
remote-server4-get command failed: %1
```

This error message is issued to indicate that the remote-server4-get command handler failed while processing the command. The argument provides the reason for failure.

6.60 CB_CMDS_SERVER4_SET_HANDLER_FAILED

```
remote-server4-set command failed: %1
```

This error message is issued to indicate that the remote-server4-set command handler failed while processing the command. The argument provides the reason for failure.

6.61 CB_CMDS_SERVER6_DEL_HANDLER_FAILED

```
remote-server6-del command failed: %1
```

This error message is issued to indicate that the remote-server6-del command handler failed while processing the command. The argument provides the reason for failure.

6.62 CB_CMDS_SERVER6_GET_ALL_HANDLER_FAILED

remote-server6-get-all command failed: %1

This error message is issued to indicate that the remote-server6-get-all command handler failed while processing the command. The argument provides the reason for failure.

6.63 CB_CMDS_SERVER6_GET_HANDLER_FAILED

remote-server6-get command failed: %1

This error message is issued to indicate that the remote-server6-get command handler failed while processing the command. The argument provides the reason for failure.

6.64 CB_CMDS_SERVER6_SET_HANDLER_FAILED

remote-server6-set command failed: %1

This error message is issued to indicate that the remote-server6-set command handler failed while processing the command. The argument provides the reason for failure.

6.65 CB_CMDS_SUBNET4_DEL_BY_ID_HANDLER_FAILED

remote-subnet4-del-by-id command failed: %1

This error message is issued to indicate that the remote-subnet4-del-by-id command handler failed while processing the command. The argument provides the reason for failure.

6.66 CB_CMDS_SUBNET4_DEL_BY_PREFIX_HANDLER_FAILED

remote-subnet4-del-by-prefix command failed: %1

This error message is issued to indicate that the remote-subnet4-del-by-prefix command handler failed while processing the command. The argument provides the reason for failure.

6.67 CB_CMDS_SUBNET4_GET_BY_ID_HANDLER_FAILED

remote-subnet4-get-by-id command failed: %1

This error message is issued to indicate that the remote-subnet4-get-by-id command handler failed while processing the command. The argument provides the reason for failure.

6.68 CB_CMDS_SUBNET4_GET_BY_PREFIX_HANDLER_FAILED

remote-subnet4-get-by-prefix command failed: %1

This error message is issued to indicate that the remote-subnet4-get-by-prefix command handler failed while processing the command. The argument provides the reason for failure.

6.69 CB_CMDS_SUBNET4_LIST_HANDLER_FAILED

```
remote-subnet4-list command failed: %1
```

This error message is issued to indicate that the remote-subnet4-list command handler failed while processing the command. The argument provides the reason for failure.

6.70 CB_CMDS_SUBNET4_SET_HANDLER_FAILED

```
remote-subnet4-set command failed: %1
```

This error message is issued to indicate that the remote-subnet4-set command handler failed while processing the command. The argument provides the reason for failure.

6.71 CB_CMDS_SUBNET6_DEL_BY_ID_HANDLER_FAILED

```
remote-subnet6-del-by-id command failed: %1
```

This error message is issued to indicate that the remote-subnet6-del-by-id command handler failed while processing the command. The argument provides the reason for failure.

6.72 CB_CMDS_SUBNET6_DEL_BY_PREFIX_HANDLER_FAILED

```
remote-subnet6-del-by-prefix command failed: %1
```

This error message is issued to indicate that the remote-subnet6-del-by-prefix command handler failed while processing the command. The argument provides the reason for failure.

6.73 CB_CMDS_SUBNET6_GET_BY_ID_HANDLER_FAILED

```
remote-subnet6-get-by-id command failed: %1
```

This error message is issued to indicate that the remote-subnet6-get-by-id command handler failed while processing the command. The argument provides the reason for failure.

6.74 CB_CMDS_SUBNET6_GET_BY_PREFIX_HANDLER_FAILED

```
remote-subnet6-get-by-prefix command failed: %1
```

This error message is issued to indicate that the remote-subnet6-get-by-prefix command handler failed while processing the command. The argument provides the reason for failure.

6.75 CB_CMDS_SUBNET6_LIST_HANDLER_FAILED

```
remote-subnet6-list command failed: %1
```

This error message is issued to indicate that the remote-subnet6-list command handler failed while processing the command. The argument provides the reason for failure.

6.76 CB_CMD5_SUBNET6_SET_HANDLER_FAILED

remote-subnet6-set command failed: %1

This error message is issued to indicate that the remote-subnet6-set command handler failed while processing the command. The argument provides the reason for failure.

7.1 CLASS_CMDS_CLASS_ADD

```
class added: %1
```

The class-add command has been successful. Definition of the added class is logged.

7.2 CLASS_CMDS_CLASS_ADD_FAILED

```
failed to add a new class: %1
```

The class-add command has failed. The reason for failure is provided within the error message.

7.3 CLASS_CMDS_CLASS_ADD_HANDLER_FAILED

```
failed to run handler for 'class-add' command
```

This error message is logged when the class_cmds hooks library experiences an unexpected error when 'class-add' command handler fails to execute.

7.4 CLASS_CMDS_CLASS_DEL

```
class deleted: %1
```

The class-del command has been successful. The name of the deleted class is logged.

7.5 CLASS_CMDS_CLASS_DEL_EMPTY

```
class not deleted (not found): %1
```

The class-del command found no matching class. The name of the to be deleted class is logged.

7.6 CLASS_CMDS_CLASS_DEL_FAILED

```
failed to delete a class: %1
```

The class-del command has failed. The reason for failure is provided within the error message.

7.7 CLASS_CMDS_CLASS_DEL_HANDLER_FAILED

failed to run handler for 'class-del' command

This error message is logged when the class_cmds hooks library experiences an unexpected error when 'class-del' command handler fails to execute.

7.8 CLASS_CMDS_CLASS_GET

successfully retrieved a class: %1

The class-get command has been successful. The name of the retrieved class is logged.

7.9 CLASS_CMDS_CLASS_GET_EMPTY

specified class was not found: %1

The class-get command found no matching class. The name of the searched class is logged.

7.10 CLASS_CMDS_CLASS_GET_FAILED

failed to retrieve a class: %1

The class-get command has failed. The reason for failure is provided within the error message.

7.11 CLASS_CMDS_CLASS_GET_HANDLER_FAILED

failed to run handler for 'class-get' command

This error message is logged when the class_cmds hooks library experiences an unexpected error when 'class-get' command handler fails to execute.

7.12 CLASS_CMDS_CLASS_LIST

successfully retrieved classes names

The class-list command has been successful.

7.13 CLASS_CMDS_CLASS_LIST_EMPTY

no class was found

The class-list command found no class.

7.14 CLASS_CMDS_CLASS_LIST_FAILED

failed to retrieve classes names: %1

The class-list command has failed. The reason for failure is provided within the error message.

7.15 CLASS_CMDS_CLASS_LIST_HANDLER_FAILED

```
failed to run handler for 'class-list' command
```

This error message is logged when the class_cmds hooks library experiences an unexpected error when 'class-list' command handler fails to execute.

7.16 CLASS_CMDS_CLASS_UPDATE

```
class updated: %1
```

The class-update command has been successful. Parameters of the updated class are logged.

7.17 CLASS_CMDS_CLASS_UPDATE_EMPTY

```
class not updated (not found): %1
```

The class-update command found no matching class. The name of the to be updated class is logged.

7.18 CLASS_CMDS_CLASS_UPDATE_FAILED

```
failed to update a class: %1
```

The class-update command has failed. The reason for failure is provided within the error message.

7.19 CLASS_CMDS_CLASS_UPDATE_HANDLER_FAILED

```
failed to run handler for 'class-update' command
```

This error message is logged when the class_cmds hooks library experiences an unexpected error when 'class-update' command handler fails to execute.

7.20 CLASS_CMDS_DEINIT_OK

```
unloading Class Commands hooks library successful
```

This info message indicates that the Class Commands hooks library has been removed successfully.

7.21 CLASS_CMDS_INIT_FAILED

```
loading Class Commands hooks library failed: %1
```

This error message indicates an error during loading the Class Commands hooks library. The details of the error are provided as argument of the log message.

7.22 CLASS_CMDS_INIT_OK

```
loading Class Commands hooks library successful
```

This info message indicates that the Class Commands hooks library has been loaded successfully. Enjoy!

COMMAND

8.1 COMMAND_ACCEPTOR_START

Starting to accept connections via unix domain socket bound to %1

This informational message is issued when the Kea server starts an acceptor via which it is going to accept new control connections. The acceptor is bound to the endpoint associated with the filename provided as an argument. If starting the acceptor fails, subsequent error messages will provide a reason for failure.

8.2 COMMAND_DEREGISTERED

Command %1 deregistered

Logged at debug log level 10. This debug message indicates that the daemon stopped supporting specified command. This command can no longer be issued. If the command socket is open and this command is issued, the daemon will not be able to process it.

8.3 COMMAND_EXTENDED_REGISTERED

Command %1 registered

Logged at debug log level 10. This debug message indicates that the daemon started supporting specified command. The handler for the registered command includes a parameter holding entire command to be processed.

8.4 COMMAND_HTTP_LISTENER_COMMAND_REJECTED

Command HTTP listener rejected command '%1' from '%2'

Logged at debug log level 10. This debug messages is issued when a command is rejected. Arguments detail the command and the address the request was received from.

8.5 COMMAND_HTTP_LISTENER_STARTED

Command HTTP listener started with %1 threads, listening on address: %2 port: %3, use TLS: %4

Logged at debug log level 10. This debug messages is issued when an HTTP listener has been started to accept connections from Command API clients through which commands can be received and responses sent. Arguments detail the number of threads that the listener is using, the address and port at which it is listening, and if HTTPS/TLS is used or not.

8.6 COMMAND_HTTP_LISTENER_STOPPED

Command HTTP listener for address: %1 port: %2 stopped.

Logged at debug log level 10. This debug messages is issued when the Command HTTP listener, listening at the given address and port, has completed shutdown.

8.7 COMMAND_HTTP_LISTENER_STOPPING

Stopping Command HTTP listener for address: %1 port: %2

Logged at debug log level 10. This debug messages is issued when the Command HTTP listener, listening at the given address and port, has begun to shutdown.

8.8 COMMAND_HTTP_SOCKET_SECURITY_WARNING

command socket configuration is NOT SECURE: %1

This warning message is issued when security enforcement is disabled and command socket configuration does not use HTTPS/TLS or basic HTTP authentication. The server will still use the socket as configured but is warning that doing so may pose a security risk.

8.9 COMMAND_PROCESS_ERROR1

Error while processing command: %1

This warning message indicates that the server encountered an error while processing received command. Additional information will be provided, if available. Additional log messages may provide more details.

8.10 COMMAND_PROCESS_ERROR2

Error while processing command: %1

This warning message indicates that the server encountered an error while processing received command. The difference, compared to COMMAND_PROCESS_ERROR1 is that the initial command was well formed and the error occurred during logic processing, not the command parsing. Additional information will be provided, if available. Additional log messages may provide more details.

8.11 COMMAND_RECEIVED

Received command '%1'

This informational message indicates that a command was received over command socket. The nature of this command and its possible results will be logged with separate messages.

8.12 COMMAND_REGISTERED

Command %1 registered

Logged at debug log level 10. This debug message indicates that the daemon started supporting specified command. If the command socket is open, this command can now be issued.

8.13 COMMAND_RESPONSE_ERROR

Server failed to generate response for command: %1

This error message indicates that the server failed to generate response for specified command. This likely indicates a server logic error, as the server is expected to generate valid responses for all commands, even malformed ones.

8.14 COMMAND_SOCKET_ACCEPT_FAIL

Failed to accept incoming connection on command socket %1: %2

This error indicates that the server detected incoming connection and executed accept system call on said socket, but this call returned an error. Additional information may be provided by the system as second parameter.

8.15 COMMAND_SOCKET_CLOSED_BY_FOREIGN_HOST

Closed command socket %1 by foreign host, %2

This is an information message indicating that the command connection has been closed by a command control client, and whether any partially read data was discarded.

8.16 COMMAND_SOCKET_CONNECTION_CANCEL_FAIL

Failed to cancel read operation on socket %1: %2

This error message is issued to indicate an error to cancel asynchronous read of the control command over the control socket. The cancel operation is performed when the timeout occurs during communication with a client. The error message includes details about the reason for failure.

8.17 COMMAND_SOCKET_CONNECTION_CLOSED

Closed socket %1 for existing command connection

Logged at debug log level 10. This is a debug message indicating that the socket created for handling client's connection is closed. This usually means that the client disconnected, but may also mean a timeout.

8.18 COMMAND_SOCKET_CONNECTION_CLOSE_FAIL

Failed to close command connection: %1

This error message is issued when an error occurred when closing a command connection and/or removing it from the connections pool. The detailed error is provided as an argument.

8.19 COMMAND_SOCKET_CONNECTION_OPENED

Opened socket %1 for incoming command connection

Logged at debug log level 10. This is a debug message indicating that a new incoming command connection was detected and a dedicated socket was opened for that connection.

8.20 COMMAND_SOCKET_CONNECTION_SHUTDOWN_FAIL

Encountered error %1 while trying to gracefully shutdown socket

This message indicates an error while trying to gracefully shutdown command connection. The type of the error is included in the message.

8.21 COMMAND_SOCKET_CONNECTION_TIMEOUT

Timeout occurred for connection over socket %1

This is an informational message that indicates that the timeout has occurred for one of the command channel connections. The response sent by the server indicates a timeout and is then closed.

8.22 COMMAND_SOCKET_READ

Received %1 bytes over command socket %2

Logged at debug log level 10. This debug message indicates that specified number of bytes was received over command socket identified by specified file descriptor.

8.23 COMMAND_SOCKET_READ_FAIL

Encountered error %1 while reading from command socket %2

This error message indicates that an error was encountered while reading from command socket.

8.24 COMMAND_SOCKET_WRITE

Sent response of %1 bytes (%2 bytes left to send) over command socket %3

Logged at debug log level 10. This debug message indicates that the specified number of bytes was sent over command socket identifier by the specified file descriptor.

8.25 COMMAND_SOCKET_WRITE_FAIL

Error while writing to command socket %1 : %2

This error message indicates that an error was encountered while attempting to send a response to the command socket.

8.26 COMMAND_UNIX_SOCKET_PATH_SECURITY_WARNING

unix socket path is NOT SECURE: %1

This warning message is issued when security enforcement is disabled and the path specified for a control channel unix socket-name does not comply with the supported path. The server will still use the specified path but is warning that doing so may pose a security risk.

8.27 COMMAND_UNIX_SOCKET_PERMISSIONS_SECURITY_WARNING

```
unix socket permissions are NOT SECURE: %1
```

This warning message is issued when security enforcement is disabled and the path specified for a control channel unix socket-name does not have the required socket permissions. The server will still use the specified path but is warning that doing so may pose a security risk.

8.28 COMMAND_WATCH_SOCKET_CLEAR_ERROR

```
watch socket failed to clear: %1
```

This error message is issued when the command manager was unable to reset the ready status after completing a send. This is a programmatic error that should be reported. The command manager may or may not continue to operate correctly.

8.29 COMMAND_WATCH_SOCKET_CLOSE_ERROR

```
watch socket failed to close: %1
```

This error message is issued when command manager attempted to close the socket used for indicating the ready status for send operations. This should not have any negative impact on the operation of the command manager as it happens when the connection is being terminated.

8.30 COMMAND_WATCH_SOCKET_MARK_READY_ERROR

```
watch socket failed to mark ready: %1
```

This error message is issued when the command manager was unable to set ready status after scheduling asynchronous send. This is programmatic error that should be reported. The command manager may or may not continue to operate correctly.

9.1 CONFIG_BACKENDS_REGISTERED

the following config backend types are available: %1

This informational message lists all possible config backends that could be used in config-database[s].

DATABASE

10.1 DATABASE_INVALID_ACCESS

```
invalid database access string: %1
```

This is logged when an attempt has been made to parse a database access string and the attempt ended in error. A redacted form of the access string - which should be of the form 'keyword=value keyword=value...' with any password replaced by asterisks - is included in the message.

10.2 DATABASE_MYSQL_COMMIT

```
committing to MySQL database
```

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the committal may not include a write to disk.

10.3 DATABASE_MYSQL_FATAL_ERROR

```
Unrecoverable MySQL error occurred: %1 for <%2>, reason: %3 (error code: %4).
```

An error message indicating that communication with the MySQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover connectivity. If not, then the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the MySQL server has gone down.

10.4 DATABASE_MYSQL_INITIALIZE_SCHEMA

```
Initializing the MySQL schema with command: %1.
```

This is logged before running the kea-admin command to automatically initialize the schema from Kea after getting the schema version initially failed. The full kea-admin command is shown.

10.5 DATABASE_MYSQL_INITIAL_CONNECTION_FAIL

```
The connection to the MySQL server is not yet established. Reason: %1
```

A warning message logged when the initial attempt to connect to MySQL was unsuccessful. If the reason for the unsuccessful attempt was the lack of a schema, there may still be a chance for the connection to succeed after the Kea DHCP server runs kea-admin db-init.

10.6 DATABASE_MYSQL_NO_INIT_NO_ADMIN

Not attempting to initialize the MySQL schema. kea-admin seems to be missing.

A warning message indicating that kea-admin is not available which makes db-init not possible.

10.7 DATABASE_MYSQL_NO_INIT_NO_PASSWORD

Not attempting to initialize the MySQL schema. Kea database password is not available.

A warning message indicating that the password required to connect to the Kea database is not available and db-init will not be attempted.

10.8 DATABASE_MYSQL_NO_INIT_READONLY

Not attempting to initialize the MySQL schema. Kea has the database configured as readonly.

A warning message indicating that the database is configured in Kea as readonly so db-init will not be attempted.

10.9 DATABASE_MYSQL_ROLLBACK

rolling back MySQL database

The code has issued a rollback call. All outstanding transactions will be rolled back and not committed to the database.

10.10 DATABASE_MYSQL_START_TRANSACTION

starting new MySQL transaction

This debug message is issued when a new MySQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

10.11 DATABASE_PGSQL_COMMIT

committing to PostgreSQL database

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the committal may not include a write to disk.

10.12 DATABASE_PGSQL_CREATE_SAVEPOINT

creating a new PostgreSQL savepoint: %1

The code is issuing a call to create a savepoint within the current transaction. Database modifications made up to this point will be preserved should a subsequent call to rollback to this savepoint occurs prior to the transaction being committed.

10.13 DATABASE_PGSQL_DEALLOC_ERROR

An error occurred deallocating SQL statements while closing the PostgreSQL lease database: %1

This is an error message issued when a DHCP server (either V4 or V6) experienced an error freeing database SQL resources as part of closing its connection to the PostgreSQL database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

10.14 DATABASE_PGSQL_FATAL_ERROR

Unrecoverable PostgreSQL error occurred: Statement: <%1>, reason: %2 (error code: %3).

An error message indicating that communication with the PostgreSQL database server has been lost. If automatic recovery has been enabled, then the server will attempt to recover the connectivity. If not, then the server will exit with a non-zero exit code. The cause of such an error is most likely a network issue or the PostgreSQL server has gone down.

10.15 DATABASE_PGSQL_INITIALIZE_SCHEMA

Initializing the PostgreSQL schema with command: %1.

This is logged before running the kea-admin command to automatically initialize the schema from Kea after getting the schema version initially failed. The full kea-admin command is shown.

10.16 DATABASE_PGSQL_INITIAL_CONNECTION_FAIL

The connection to the PostgreSQL server is not yet established. Reason: %1

A warning message logged when the initial attempt to connect to PostgreSQL was unsuccessful. If the reason for the unsuccessful attempt was the lack of a schema, there may still be a chance for the connection to succeed after the Kea DHCP server runs kea-admin db-init.

10.17 DATABASE_PGSQL_NO_INIT_NO_ADMIN

Not attempting to initialize the PostgreSQL schema. kea-admin seems to be missing.

A warning message indicating that kea-admin is not available which makes db-init not possible.

10.18 DATABASE_PGSQL_NO_INIT_NO_PASSWORD

Not attempting to initialize the PostgreSQL schema. Kea database password is not available.

A warning message indicating that the password required to connect to the Kea database is not available and db-init will not be attempted.

10.19 DATABASE_PGSQL_NO_INIT_READONLY

Not attempting to initialize the PostgreSQL schema. Kea has the database configured as readonly.

A warning message indicating that the database is configured in Kea as readonly so db-init will not be attempted.

10.20 DATABASE_PGSQL_ROLLBACK

rolling back PostgreSQL database

The code has issued a rollback call. All outstanding transactions will be rolled back and not committed to the database.

10.21 DATABASE_PGSQL_ROLLBACK_SAVEPOINT

rolling back PostgreSQL database to savepoint: \$1

The code is issuing a call to rollback to the given savepoint. Any database modifications that were made after the savepoint was created will be rolled back and not committed to the database.

10.22 DATABASE_PGSQL_START_TRANSACTION

starting a new PostgreSQL transaction

This debug message is issued when a new PostgreSQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

10.23 DATABASE_PGSQL_TCP_USER_TIMEOUT_UNSUPPORTED

tcp_user_timeout is not supported in this PostgreSQL version

This warning message is issued when a user has configured the tcp_user_timeout parameter in the connection to the PostgreSQL database but the installed database does not support this parameter. It is supported by the PostgreSQL version 12 or later. The parameter setting will be ignored.

10.24 DATABASE_TO_JSON_BOOLEAN_ERROR

Internal logic error: invalid boolean value found in database connection parameters: %1=%2

This error message is printed when conversion to JSON of the internal state is requested, but the connection string contains a boolean parameter with invalid value. It is a programming error. The software will continue operation, but the returned JSON data will be syntactically valid, but incomplete. The culprit parameter will not be converted.

10.25 DATABASE_TO_JSON_INTEGER_ERROR

Internal logic error: invalid integer value found in database connection parameters: %1=%2

This error message is printed when conversion to JSON of the internal state is requested, but the connection string contains the integer parameter with a wrong value. It is a programming error. The software will continue operation, but the returned JSON data will be syntactically valid, but incomplete. The culprit parameter will not be converted.

10.26 DATABASE_TO_JSON_UNKNOWN_TYPE_ERROR

Internal logic error: unknown element found in database connection parameters: %1=%2

This error message is printed when conversion to JSON of the internal state is requested, but the connection string contains unrecognized parameter. It is a programming error. The software will continue operation, but the returned JSON data will be syntactically valid, but incomplete. The unknown parameter will not be converted.

11.1 DCTL_ALREADY_RUNNING

```
%1 already running? %2
```

This is an error message that occurs when a module encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of a module using the same configuration file. It is possible, though unlikely, that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than Kea process. In such an event, it would be necessary to manually remove the PID file. The first argument is the process name, the second contains the PID and PID file.

11.2 DCTL_CFG_FILE_RELOAD_ERROR

```
configuration reload failed: %1, reverting to current configuration.
```

This is an error message indicating that the application attempted to reload its configuration from file and encountered an error. This is likely due to invalid content in the configuration file. The application should continue to operate under its current configuration.

11.3 DCTL_CFG_FILE_RELOAD_SIGNAL_RECVD

```
OS signal %1 received, reloading configuration from file: %2
```

This is an informational message indicating the application has received a signal instructing it to reload its configuration from file.

11.4 DCTL_CONFIG_CHECK_COMPLETE

```
server has completed configuration check: %1, result: %2
```

This is an informational message announcing the successful processing of a new configuration check is complete. The result of that check is printed. This informational message is printed when configuration check is requested.

11.5 DCTL_CONFIG_COMPLETE

```
server has completed configuration: %1
```

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

11.6 DCTL_CONFIG_DEPRECATED

server configuration includes a deprecated object: %1

This error message is issued when the configuration includes a deprecated object (i.e. a top level element) which will be ignored.

11.7 DCTL_CONFIG_FETCH

Fetching configuration data from config backends.

This is an informational message emitted when the Kea server is about to begin retrieving configuration data from one or more configuration backends.

11.8 DCTL_CONFIG_FILE_LOAD_FAIL

%1 reason: %2

This fatal error message indicates that the application attempted to load its initial configuration from file and has failed. The service will exit.

11.9 DCTL_CONFIG_START

parsing new configuration: %1

Logged at debug log level 10. A debug message indicating that the application process has received an updated configuration and has passed it to its configuration manager for parsing.

11.10 DCTL_DB_OPEN_CONNECTION_WITH_RETRY_FAILED

Failed to connect to database: %1 with error: %2

This is an informational message issued when the server failed to connect to the configuration database. The operation started a retry to connect procedure. The database access string with password redacted is logged, along with the error and details for the reconnect procedure.

11.11 DCTL_DEPRECATED_OUTPUT_OPTIONS

The output_options parameter is deprecated. Use output-options parameter instead.

This warning message is displayed when deprecated output_options is used instead of output-options.

11.12 DCTL_DEVELOPMENT_VERSION

This software is a development branch of Kea. It is not recommended for production use.

This warning message is displayed when the version is a development (vs stable) one: the second number of the version is odd.

11.13 DCTL_INIT_PROCESS

%1 initializing the application

Logged at debug log level 0. This debug message is issued just before the controller attempts to create and initialize its application instance.

11.14 DCTL_INIT_PROCESS_FAIL

%1 application initialization failed: %2

This error message is issued if the controller could not initialize the application and will exit.

11.15 DCTL_LOG_PATH_SECURITY_WARNING

Log output path specified is NOT SECURE: %1

This warning message is issued when security enforcement is disabled and the output path specified for a given logger does not comply with the supported path. The server will still use the specified path but is warning that doing so may pose a security risk.

11.16 DCTL_NOT_RUNNING

%1 application instance is not running

A warning message is issued when an attempt is made to shut down the application when it is not running.

11.17 DCTL_OPEN_CONFIG_DB

Opening configuration database: %1

This message is printed when the Kea server is attempting to open a configuration database. The database access string with password redacted is logged.

11.18 DCTL_PARSER_FAIL

Parser error: %1

On receipt of a new configuration, the server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

11.19 DCTL_PID_FILE_ERROR

%1 could not create a PID file: %2

This is an error message that occurs when the server is unable to create its PID file. The log message should contain details sufficient to determine the underlying cause. The most likely culprits are that some portion of the pathname does not exist or a permissions issue. The default path is determined by --localstatedir and --prefix meson setup options but may be overridden by setting environment variable KEA_PIDFILE_DIR. The first argument is the process name.

11.20 DCTL_PROCESS_FAILED

```
%1 application execution failed: %2
```

The controller has encountered a fatal error while running the application and is terminating. The reason for the failure is included in the message.

11.21 DCTL_ROOT_USER_SECURITY_WARNING

```
%1 running as root user!
```

This warning is emitted when the server is running as a root user. While the server will function fully, this mode of operation may expose your environment to security vulnerabilities and should only be used after careful consideration.

11.22 DCTL_RUN_PROCESS

```
%1 starting application event loop
```

Logged at debug log level 0. This debug message is issued just before the controller invokes the application run method.

11.23 DCTL_SHUTDOWN

```
%1 has shut down, pid: %2, version: %3
```

Logged at debug log level 0. This is an informational message indicating that the service has shut down. The argument specifies a name of the service.

11.24 DCTL_SHUTDOWN_SIGNAL_RECVD

```
OS signal %1 received, starting shutdown
```

Logged at debug log level 0. This is a debug message indicating the application has received a signal instructing it to shutdown.

11.25 DCTL_STANDALONE

```
%1 skipping message queue, running standalone
```

Logged at debug log level 0. This is a debug message indicating that the controller is running in the application in standalone mode. This means it will not be connected to the Kea message queue. Standalone mode is only useful during program development, and should not be used in a production environment.

11.26 DCTL_STARTING

```
%1 starting, pid: %2, version: %3 (%4)
```

This is an informational message issued when controller for the service first starts. Version is also reported.

11.27 DCTL_UNLOAD_LIBRARIES_ERROR

error unloading hooks libraries during shutdown: %l

This error message indicates that during shutdown, unloading hooks libraries failed to close them. If the list of libraries is empty it is a programmatic error in the server code. If it is not empty it could be a programmatic error in one of the hooks libraries which could lead to a crash during finalization.

11.28 DCTL_UNSUPPORTED_SIGNAL

ignoring reception of unsupported signal: %l

This is a debug message indicating that the application received an unsupported signal. This is a programming error indicating that the application has registered to receive the signal but no associated processing logic has been added.

12.1 DDNS_TUNING4_CALCULATED_HOSTNAME

```
Replacing host name: %1, with calculated host name: %2, for query: %3
```

Logged at debug log level 40. This debug message is emitted when the DDNS Tuning hooks library has calculated a new host name for the given client query. The original host name and the calculated host name are provided

12.2 DDNS_TUNING4_PROCESS_ERROR

```
An error occurred processing query %1: %2
```

This error message indicates an error during processing of a query by the DDNS Tuning hooks library. The client identification information from the query and the details of the error are provided as arguments of the log message.

12.3 DDNS_TUNING4_SKIPPING_DDNS

```
Client is a member matches SKIP_DDNS class, skipping DDNS updates, query: %1
```

Logged at debug log level 40. This debug message is emitted when during the ddns4-update callout, if the Client query matches the SKIP_DDNS class. The kea-dhcp4 server will not send DDNS update requests to kea-dhcp-ddns for this query. The query is shown in the log message.

12.4 DDNS_TUNING6_CALCULATED_HOSTNAME

```
Replacing host name: %1, with calculated host name: %2, for query: %3
```

Logged at debug log level 40. This debug message is emitted when the DDNS Tuning hooks library has calculated a new host name for the given client query. The original host name and the calculated host name are provided

12.5 DDNS_TUNING6_PROCESS_ERROR

```
An error occurred processing query %1: %2
```

This error message indicates an error during processing of a query by the DDNS Tuning hooks library. The client identification information from the query and the details of the error are provided as arguments of the log message.

12.6 DDNS_TUNING6_SKIPPING_DDNS

```
Client is a member matches SKIP_DDNS class, skipping DDNS updates, query: %1
```

Logged at debug log level 40. This debug message is emitted when during the ddns6-update callout, if the Client query matches the SKIP_DDNS class. The kea-dhcp6 server will not send DDNS update requests to kea-dhcp-ddns for this query. The query is shown in the log message.

12.7 DDNS_TUNING_GLOBAL_EXPR_SET

```
Global hostname expression set to: %1
```

This message indicates that the global hostname expression has been set and will be used everywhere, unless overridden by subnet level parameters.

12.8 DDNS_TUNING_LOAD_ERROR

```
loading DDNS Tuning hooks library failed: %1
```

This error message indicates an error during loading the DDNS Tuning hooks library. The details of the error are provided as argument of the log message.

12.9 DDNS_TUNING_LOAD_OK

```
DDNS Tuning hooks library loaded successfully.
```

This info message indicates that the DDNS Tuning hooks library has been loaded successfully.

12.10 DDNS_TUNING_SUBNET_EXPRESSION_PARSE

```
Parsing subnet expression (%1) for for subnet %2
```

Logged at debug log level 40. This debug message is emitted when the DDNS Tuning hooks library is attempting to parse the hostname expression for a subnet. Parsing occurs after configuration events (e.g. reconfigure command, config back end updates, subnet command updates).

12.11 DDNS_TUNING_SUBNET_EXPRESSION_PARSE_ERROR

```
An error occurred while parsing the hostname expression for subnet %1, %2
```

This error indicates that the hostname expression assigned to a subnet is not a valid expression. DHCP service will continue as though the subnet did not specify an expression. The subnet and the parsing error are included in the log message.

12.12 DDNS_TUNING_SUBNET_EXPR_CACHED

```
Using subnet expression stored in a cache for subnet %1
```

Logged at debug log level 40. The expression for this subnet has previously been used and cached. Using the cached version.

12.13 DDNS_TUNING_UNLOAD

DDNS Tuning hooks library has been unloaded

This info message indicates that the DDNS Tuning hooks library has been unloaded.

13.1 DHCP4_ADDITIONAL_CLASS_EVAL_ERROR

%1: Expression '%2' evaluated to %3

This error message indicates that a problem was encountered while evaluating the expression of an additional client class. A description of the problem is printed.

13.2 DHCP4_ADDITIONAL_CLASS_EVAL_RESULT

%1: Expression '%2' evaluated to %3

Logged at debug log level 50. This debug message indicates that the expression of an additional client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

13.3 DHCP4_ADDITIONAL_CLASS_NO_TEST

additional class %1 has no test expression, adding it to client's classes unconditionally

Logged at debug log level 40. This debug message informs that a class was listed for additional evaluation but its definition does not include a test expression to evaluate. The class is unconditionally added to the query.

13.4 DHCP4_ADDITIONAL_CLASS_UNDEFINED

additional class %1 has no definition

Logged at debug log level 40. This debug message informs that a class is listed for additional evaluation but has no definition. The class is ignored.

13.5 DHCP4_ALREADY_RUNNING

%1 already running? %2

This is an error message that occurs when the DHCPv4 server encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of the server using the same configuration file. It is possible, though unlikely that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than the server. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCPv4 process name, the second contains the PID and PID file.

13.6 DHCP4_BUFFER_RECEIVED

```
received buffer from %1:%2 to %3:%4 over interface %5
```

Logged at debug log level 40. This debug message is logged when the server has received a packet over the socket. When the message is logged the contents of the received packet hasn't been parsed yet. The only available information is the interface and the source and destination IPv4 addresses/ports.

13.7 DHCP4_BUFFER_RECEIVE_FAIL

```
error on attempt to receive packet: %1
```

The DHCPv4 server tried to receive a packet but an error occurred during this attempt. The reason for the error is included in the message.

13.8 DHCP4_BUFFER_UNPACK

```
parsing buffer received from %1 to %2 over interface %3
```

Logged at debug log level 50. This debug message is issued when the server starts parsing the received buffer holding the DHCPv4 message. The arguments specify the source and destination IPv4 addresses as well as the interface over which the buffer has been received.

13.9 DHCP4_BUFFER_WAIT_SIGNAL

```
signal received while waiting for next packet
```

Logged at debug log level 50. This debug message is issued when the server was waiting for the packet, but the wait has been interrupted by the signal received by the process. The signal will be handled before the server starts waiting for next packets.

13.10 DHCP4_CB_ON_DEMAND_FETCH_UPDATES_FAIL

```
error on demand attempt to fetch configuration updates from the configuration backend(s): %1
```

This error message is issued when the server attempted to fetch configuration updates from the database and this on demand attempt failed. The sole argument which is returned to the config-backend-pull command caller too contains the reason for failure.

13.11 DHCP4_CB_PERIODIC_FETCH_UPDATES_FAIL

```
error on periodic attempt to fetch configuration updates from the configuration backend(s): %1
```

This error message is issued when the server attempted to fetch configuration updates from the database and this periodic attempt failed. The server will re-try according to the configured value of the config-fetch-wait-time parameter. The sole argument contains the reason for failure.

13.12 DHCP4_CB_PERIODIC_FETCH_UPDATES_RETRIES_EXHAUSTED

```
maximum number of configuration fetch attempts: 10, has been exhausted without success
```

This error indicates that the server has made a number of unsuccessful periodic attempts to fetch configuration updates from a configuration backend. The server will continue to operate but won't make any further attempts to fetch configuration updates. The administrator must fix the configuration in the database and reload (or restart) the server.

13.13 DHCP4_CB_REPAIR_MODE_ENABLED

Server is running in config back end repair mode.

This warning is emitted when config back end repair mode is enabled. This allows the server to start and run without automatically fetching config back end data but can still process CB API commands. This allows admins to correct errors in config back end data.

13.14 DHCP4_CLASSES_ASSIGNED

%1: client packet has been assigned on %2 message to the following classes: %3

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument specifies the DHCPv4 message type. The third argument includes all classes to which the packet has been assigned.

13.15 DHCP4_CLASSES_ASSIGNED_AFTER_SUBNET_SELECTION

%1: client packet has been assigned to the following classes: %2

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes all classes to which the packet has been assigned.

13.16 DHCP4_CLASS_ASSIGNED

%1: client packet has been assigned to the following class: %2

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified class. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes the new class to which the packet has been assigned.

13.17 DHCP4_CLASS_UNCONFIGURED

%1: client packet belongs to an unconfigured class: %2

Logged at debug log level 40. This debug message informs that incoming packet belongs to a class which cannot be found in the configuration. Either a hook written before the classification was added to Kea is used, or class naming is inconsistent.

13.18 DHCP4_CLIENTID_FORCED_USE_FOR_LEASES

%1: forced using client identifier for lease allocation for subnet %2

Logged at debug log level 50. This debug message is issued when the server is processing the DHCPv4 message for which client identifier is used when allocating new lease or renewing existing lease. The server is explicitly configured to not use client identifier but the client hardware address was empty so was not available for identifying the client.

The first argument includes the client and transaction identification information. The second argument specifies the identifier of the subnet where the client is connected and for which the not matching client identifier mode of operation is configured on the server.

13.19 DHCP4_CLIENTID_IGNORED_FOR_LEASES

%1: not using client identifier for lease allocation for subnet %2

Logged at debug log level 50. This debug message is issued when the server is processing the DHCPv4 message for which client identifier will not be used when allocating new lease or renewing existing lease. The server is explicitly configured to not use client identifier to lookup existing leases for the client and will not record client identifier in the lease database. This mode of operation is useful when clients don't use stable client identifiers, e.g. multi stage booting. The first argument includes the client and transaction identification information. The second argument specifies the identifier of the subnet where the client is connected and for which this mode of operation is configured on the server.

13.20 DHCP4_CLIENT_FQDN_DATA

%1: Client sent FQDN option: %2

Logged at debug log level 55. This debug message includes the detailed information extracted from the Client FQDN option sent in the query. The first argument includes the client and transaction identification information. The second argument specifies the detailed information about the FQDN option received by the server.

13.21 DHCP4_CLIENT_FQDN_PROCESS

%1: processing Client FQDN option

Logged at debug log level 50. This debug message is issued when the server starts processing the Client FQDN option sent in the client's query. The argument includes the client and transaction identification information.

13.22 DHCP4_CLIENT_FQDN_SCRUBBED_EMPTY

%1: sanitizing client's FQDN option '%2' yielded an empty name or an empty label within the name

Logged at debug log level 50. This debug message is issued when the result of sanitizing the FQDN option(81) sent by the client is an empty name or an empty label within the name (e.g. "aaa.bbb.com"). When this occurs the server will ignore the FQDN option. The arguments include the client and the FQDN option it sent.

13.23 DHCP4_CLIENT_HOSTNAME_DATA

%1: client sent Hostname option: %2

Logged at debug log level 55. This debug message includes the detailed information extracted from the Hostname option sent in the query. The first argument includes the client and transaction identification information. The second argument specifies the hostname carried in the Hostname option sent by the client.

13.24 DHCP4_CLIENT_HOSTNAME_MALFORMED

%1: client hostname option malformed: %2

Logged at debug log level 50. This debug message is issued when the DHCP server was unable to process the the host-name option sent by the client because the content is malformed. The first argument includes the client and transaction identification information. The second argument contains a description of the data error.

13.25 DHCP4_CLIENT_HOSTNAME_PROCESS

```
%1: processing client's Hostname option
```

Logged at debug log level 50. This debug message is issued when the server starts processing the Hostname option sent in the client's query. The argument includes the client and transaction identification information.

13.26 DHCP4_CLIENT_HOSTNAME_SCRUBBED_EMPTY

```
%1: sanitizing client's Hostname option '%2' yielded an empty name or an empty label within the name
```

Logged at debug log level 50. This debug message is issued when the result of sanitizing the hostname option(12) sent by the client is an empty name or an empty label within the name (e.g. "aaa..bbb"). When this occurs the server will ignore the hostname option. The arguments include the client and the hostname option it sent.

13.27 DHCP4_CLIENT_NAME_PROC_FAIL

```
%1: failed to process the fqdn or hostname sent by a client: %2
```

Logged at debug log level 55. This debug message is issued when the DHCP server was unable to process the FQDN or Hostname option sent by a client. This is likely because the client's name was malformed or due to internal server error. The first argument contains the client and transaction identification information. The second argument holds the detailed description of the error.

13.28 DHCP4_CONFIG_COMPLETE

```
DHCPv4 server has completed configuration: %1
```

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

13.29 DHCP4_CONFIG_HOSTS_DATABASE_DEPRECATED

```
the "host-database" keyword will be deprecated
```

This warning message indicates the configuration still uses the "hosts-database", a keyword which is deprecated and will be rejected by a future release,. Please use "hosts-databases" instead and put the database configuration into a list.

13.30 DHCP4_CONFIG_LOAD_FAIL

```
configuration error using file: %1, reason: %2
```

This error message indicates that the DHCPv4 configuration has failed. If this is an initial configuration (during server's startup) the server will fail to start. If this is a dynamic reconfiguration attempt the server will continue to use an old configuration.

13.31 DHCP4_CONFIG_PACKET_QUEUE

DHCPv4 packet queue info after configuration: %1

This informational message is emitted during DHCPv4 server configuration, immediately after configuring the DHCPv4 packet queue. The information shown depends upon the packet queue type selected.

13.32 DHCP4_CONFIG_RECEIVED

received configuration %1

Logged at debug log level 10. A debug message listing the configuration received by the DHCPv4 server. The source of that configuration depends on used configuration backend.

13.33 DHCP4_CONFIG_START

DHCPv4 server is processing the following configuration: %1

Logged at debug log level 10. This is a debug message that is issued every time the server receives a configuration. That happens at start up and also when a server configuration change is committed by the administrator.

13.34 DHCP4_CONFIG_SYNTAX_WARNING

configuration syntax warning: %1

This warning message indicates that the DHCPv4 configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

13.35 DHCP4_CONFIG_UNRECOVERABLE_ERROR

DHCPv4 server new configuration failed with an error which cannot be recovered

This fatal error message is issued when a new configuration raised an error which cannot be recovered. A correct configuration must be applied as soon as possible as the server is no longer working. The configuration can be fixed in several ways. If the control channel is open, config-set with a valid configuration can be used. Alternatively, the original config file on disk could be fixed and SIGHUP signal could be sent (or the config-reload command issued). Finally, the server could be restarted completely.

13.36 DHCP4_CONFIG_UNSUPPORTED_OBJECT

DHCPv4 server configuration includes an unsupported object: %1

This error message is issued when the configuration includes an unsupported object (i.e. a top level element).

13.37 DHCP4_DB_RECONNECT_DISABLED

database reconnect is disabled: retries left: %1, reconnect wait time: %2, manager ID: %3, timer: %4

This is an error message indicating that connectivity to either the lease or host database or both was lost and that automatic reconnect is not enabled. Loss of connectivity is typically a network or database server issue.

13.38 DHCP4_DB_RECONNECT_FAILED

```
maximum number of database reconnect attempts: %1, has been exhausted without success, manager ID: %2, timer: %3
```

This error indicates that the server failed to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. Loss of connectivity is typically a network or database server issue.

13.39 DHCP4_DB_RECONNECT_LOST_CONNECTION

```
database connection lost: manager ID: %1, timer: %2.
```

This info message indicates that the connection has been lost and the dhcp service might have been disabled, as specified in the configuration, in order to try to recover the connection.

13.40 DHCP4_DB_RECONNECT_NO_DB_CTL

```
unexpected error in database reconnect
```

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to reconnect to its databases if connectivity is lost, and the server exits. This error should be reported.

13.41 DHCP4_DB_RECONNECT_SUCCEEDED

```
database connection recovered: manager ID: %1, timer: %2.
```

This info message indicates that the connection has been recovered and the dhcp service has been restored.

13.42 DHCP4_DDNS_REQUEST_SEND_FAILED

```
failed sending a request to kea-dhcp-ddns, error: %1, ncr: %2
```

This error message indicates that DHCP4 server attempted to send a DDNS update request to the DHCP-DDNS server. This is most likely a configuration or networking error.

13.43 DHCP4_DECLINE_FAIL

```
%1: error on decline lease for address %2: %3
```

This error message indicates that the software failed to decline a lease from the lease database due to an error during a database operation. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address which decline was attempted. The last one contains the reason for failure.

13.44 DHCP4_DECLINE_LEASE

```
Received DHCPDECLINE for addr %1 from client %2. The lease will be unavailable for %3 seconds.
```

This informational message is printed when a client received an address, but discovered that it is being used by some other device and notified the server by sending a DHCPDECLINE message. The server checked that this address really was leased to the client and marked this address as unusable for a certain amount of time. This message may indicate a misconfiguration in a network, as there is either a buggy client or more likely a device that is using an address that it is not supposed to. The server will fully recover from this situation, but if the underlying problem of a misconfigured or rogue device is not solved, this address may be declined again in the future.

13.45 DHCP4_DECLINE_LEASE_MISMATCH

Received DHCPDECLINE for addr %1 from client %2, but the data doesn't match: received hwaddr: %3, lease hwaddr: %4, received client-id: %5, lease client-id: %6

This informational message means that a client attempted to report his address as declined (i.e. used by unknown entity). The server has information about a lease for that address, but the client's hardware address or client identifier does not match the server's stored information. The client's request will be ignored.

13.46 DHCP4_DECLINE_LEASE_NOT_FOUND

Received DHCPDECLINE for addr %1 from client %2, but no such lease found.

This warning message indicates that a client reported that his address was detected as a duplicate (i.e. another device in the network is using this address). However, the server does not have a record for this address. This may indicate a client's error or a server's purged database.

13.47 DHCP4_DEFERRED_OPTION_MISSING

%1: cannot find deferred option code %2 in the query

Logged at debug log level 50. This debug message is printed when a deferred option cannot be found in the query.

13.48 DHCP4_DEFERRED_OPTION_UNPACK_FAIL

%1: An error unpacking the deferred option %2: %3

Logged at debug log level 50. This debug message is issued when deferred unpacking of an option failed, making it to be left unpacked in the packet. The first argument is the option code, the second the error.

13.49 DHCP4_DEVELOPMENT_VERSION

This software is a development branch of Kea. It is not recommended for production use.

This warning message is displayed when the version is a development (vs stable) one: the second number of the version is odd.

13.50 DHCP4_DHCP4O6_BAD_PACKET

%1: received malformed DHCPv4o6 packet: %2

Logged at debug log level 50. A malformed DHCPv4o6 packet was received.

13.51 DHCP4_DHCP4O6_HOOK_SUBNET4_SELECT_DROP

%1: packet was dropped, because a callout set the next step to 'drop'

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4_select hook point sets the next step to 'drop' value. For this particular hook point, the setting to that value instructs the server to drop the received packet. The argument specifies the client and transaction identification information.

13.52 DHCP4_DHCP4O6_HOOK_SUBNET4_SELECT_SKIP

```
%1: no subnet was selected, because a callout set the next skip flag
```

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4_select hook point sets the next step to SKIP value. For this particular hook point, the setting of the flag instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses will be assigned. The argument specifies the client and transaction identification information.

13.53 DHCP4_DHCP4O6_PACKET_RECEIVED

```
received DHCPv4o6 packet from DHCPv4 server (type %1) for %2 on interface %3
```

Logged at debug log level 40. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication.

13.54 DHCP4_DHCP4O6_PACKET_SEND

```
%1: trying to send packet %2 (type %3) to %4 port %5 on interface %6 encapsulating %7: %8 (type %9)
```

Logged at debug log level 40. The arguments specify the client identification information (HW address and client identifier), DHCPv6 message name and type, source IPv6 address and port, and interface name, DHCPv4 client identification, message name and type.

13.55 DHCP4_DHCP4O6_PACKET_SEND_FAIL

```
%1: failed to send DHCPv4o6 packet: %2
```

This error is output if the IPv4 DHCP server fails to send an DHCPv4o6 message to the IPv6 DHCP server. The reason for the error is included in the message.

13.56 DHCP4_DHCP4O6_RECEIVE_FAIL

```
failed to receive DHCPv4o6: %1
```

Logged at debug log level 50. This debug message indicates the inter-process communication with the DHCPv6 server failed. The reason for the error is included in the message.

13.57 DHCP4_DHCP4O6_RECEIVING

```
receiving DHCPv4o6 packet from DHCPv6 server
```

Logged at debug log level 50. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv6 server over inter-process communication socket.

13.58 DHCP4_DHCP4O6_RESPONSE_DATA

```
%1: responding with packet %2 (type %3), packet details: %4
```

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the DHCPv6 server to be forwarded to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

13.59 DHCP4_DHCP4O6_SUBNET_DATA

%1: the selected subnet details: %2

Logged at debug log level 55. This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second arguments includes the subnet details.

13.60 DHCP4_DHCP4O6_SUBNET_SELECTED

%1: the subnet with ID %2 was selected for client assignments

Logged at debug log level 45. This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

13.61 DHCP4_DHCP4O6_SUBNET_SELECTION_FAILED

%1: failed to select subnet for the client

Logged at debug log level 50. This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The server will not be able to offer any lease to the client and will drop its message if the received message was DHCPDISCOVER, and will send DHCPNAK if the received message was DHCPREQUEST. The argument includes the client and the transaction identification information.

13.62 DHCP4_DISCOVER

%1: server is processing DHCPDISCOVER with hint=%2

Logged at debug log level 50. This is a debug message that indicates the processing of a received DHCPDISCOVER message. The first argument contains the client and the transaction identification information. The second argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

13.63 DHCP4_DYNAMIC_RECONFIGURATION

initiate server reconfiguration using file: %1, after receiving SIGHUP signal or config-reload command

This is the info message logged when the DHCPv4 server starts reconfiguration as a result of receiving SIGHUP signal or config-reload command.

13.64 DHCP4_DYNAMIC_RECONFIGURATION_FAIL

dynamic server reconfiguration failed with file: %1

This is an error message logged when the dynamic reconfiguration of the DHCP server failed.

13.65 DHCP4_DYNAMIC_RECONFIGURATION_SUCCESS

dynamic server reconfiguration succeeded with file: %1

This is info message logged when the dynamic reconfiguration of the DHCP server succeeded.

13.66 DHCP4_EMPTY_HOSTNAME

```
%1: received empty hostname from the client, skipping processing of this option
```

Logged at debug log level 50. This debug message is issued when the server received an empty Hostname option from a client. Server does not process empty Hostname options and therefore option is skipped. The argument holds the client and transaction identification information.

13.67 DHCP4_FATAL_DB_RECONNECT_DISABLED

```
database reconnect is disabled: retries left: %1, reconnect wait time: %2, manager ID: %3, timer: %4
```

This is an error message indicating that connectivity to either the lease or host database or both was lost and that automatic reconnect is not enabled. This causes the server to shut down as specified in the configuration. Loss of connectivity is typically a network or database server issue.

13.68 DHCP4_FATAL_DB_RECONNECT_FAILED

```
maximum number of database reconnect attempts: %1, has been exhausted without success, manager ID: %2, timer: %3
```

This error indicates that the server failed to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. This causes the server to shut down as specified in the configuration. Loss of connectivity is typically a network or database server issue.

13.69 DHCP4_FATAL_DYNAMIC_RECONFIGURATION_FAIL

```
dynamic server reconfiguration failed with file: %1
```

This is a fatal error message logged when the dynamic reconfiguration of the DHCP server failed.

13.70 DHCP4_FATAL_OPEN_SOCKETS_FAILED

```
maximum number of open service sockets attempts: %1, has been exhausted without success
```

This error indicates that the server failed to bind service sockets after making the maximum configured number of open attempts. This causes the server to shut down as specified in the configuration.

13.71 DHCP4_FLEX_ID

```
%1: flexible identifier generated for incoming packet: %2
```

Logged at debug log level 40. This debug message is printed when host reservation type is set to flexible identifier and the expression specified in its configuration generated (was evaluated to) an identifier for incoming packet. This debug message is mainly intended as a debugging assistance for flexible identifier.

13.72 DHCP4_GENERATE_FQDN

```
%1: client did not send a FQDN or hostname; FQDN will be generated for the client
```

Logged at debug log level 55. This debug message is issued when the server did not receive a Hostname option from the client and hostname generation is enabled. This provides a means to create DNS entries for unsophisticated clients.

13.73 DHCP4_HOOK_BUFFER_RCVD_DROP

```
received buffer from %1 to %2 over interface %3 was dropped because a callout set the drop flag
```

Logged at debug log level 15. This debug message is printed when a callout installed on `buffer4_receive` hook point set the drop flag. For this particular hook point, the setting of the flag by a callout instructs the server to drop the packet. The arguments specify the source and destination IPv4 address as well as the name of the interface over which the buffer has been received.

13.74 DHCP4_HOOK_BUFFER_RCVD_SKIP

```
received buffer from %1 to %2 over interface %3 is not parsed because a callout set the next step to SKIP.
```

Logged at debug log level 50. This debug message is printed when a callout installed on `buffer4_receive` hook point set the next step to SKIP. For this particular hook point, this value set by a callout instructs the server to not parse the buffer because it was already parsed by the hook. The arguments specify the source and destination IPv4 address as well as the name of the interface over which the buffer has been received.

13.75 DHCP4_HOOK_BUFFER_SEND_SKIP

```
%1: prepared response is dropped because a callout set the next step to SKIP.
```

Logged at debug log level 40. This debug message is printed when a callout installed on `buffer4_send` hook point set the next step to SKIP. For this particular hook point, the SKIP value set by a callout instructs the server to drop the packet. Server completed all the processing (e.g. may have assigned, updated or released leases), but the response will not be sent to the client.

13.76 DHCP4_HOOK_DDNS_UPDATE

```
A hook has updated the DDNS parameters: hostname %1=>%2, forward update %3=>%4, reverse update %5=>%6
```

Logged at debug log level 15. This message indicates that there was a hook called on `ddns4_update` hook point and that hook updated the DDNS update parameters: hostname, or whether to conduct forward (A record) or reverse (PTR record) DDNS updates.

13.77 DHCP4_HOOK_DECLINE_SKIP

```
Decline4 hook callouts set status to DROP, ignoring packet.
```

Logged at debug log level 15. This message indicates that the server received DHCPDECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for decline4 hook point and one of the callouts set next step status to DROP. The server will now abort processing of the packet as if it was never received. The lease will continue to be assigned to this client.

13.78 DHCP4_HOOK_LEASE4_OFFER_ARGUMENT_MISSING

```
hook callouts did not set an argument as expected %1 for %2
```

This error message is printed when none of the callouts installed on the `lease4_offer` hook point set an expected argument in the callout status. This is a programming error in the installed hook libraries. Details of the argument and the query in process at the time are provided log arguments.

13.79 DHCP4_HOOK_LEASE4_OFFER_DROP

%1: packet is dropped, because a callout set the next step to DROP

This debug message is printed when a callout installed on the lease4_offer hook point sets the next step to DROP.

13.80 DHCP4_HOOK_LEASE4_OFFER_PARK

%1: packet is parked, because a callout set the next step to PARK

This debug message is printed when a callout installed on the lease4_offer hook point sets the next step to PARK.

13.81 DHCP4_HOOK_LEASE4_OFFER_PARKING_LOT_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. ping-check) that implement the "lease4_offer" callout and client queries are arriving faster than those callouts can fulfill them.

13.82 DHCP4_HOOK_LEASE4_RELEASE_SKIP

%1: lease was not released because a callout set the next step to SKIP

Logged at debug log level 15. This debug message is printed when a callout installed on lease4_release hook point set the next step status to SKIP. For this particular hook point, the value set by a callout instructs the server to not release a lease.

13.83 DHCP4_HOOK_LEASES4_COMMITTED_DROP

%1: packet is dropped, because a callout set the next step to DROP

This debug message is printed when a callout installed on the leases4_committed hook point sets the next step to DROP.

13.84 DHCP4_HOOK_LEASES4_COMMITTED_PARK

%1: packet is parked, because a callout set the next step to PARK

This debug message is printed when a callout installed on the leases4_committed hook point sets the next step to PARK.

13.85 DHCP4_HOOK_LEASES4_COMMITTED_PARKING_LOT_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. HA) that implement the "leases4-committed" callout and client queries are arriving faster than those callouts can fulfill them.

13.86 DHCP4_HOOK_PACKET_RCVD_SKIP

%1: packet is dropped, because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the `pkt4_receive` hook point sets the next step to SKIP. For this particular hook point, the value setting of the flag instructs the server to drop the packet.

13.87 DHCP4_HOOK_PACKET_SEND_DROP

%1: prepared DHCPv4 response was not sent because a callout set the next step to DROP

Logged at debug log level 15. This debug message is printed when a callout installed on the `pkt4_send` hook point set the next step to DROP. For this particular hook point, the setting of the value by a callout instructs the server to drop the packet. This effectively means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease). The argument specifies the client and transaction identification information.

13.88 DHCP4_HOOK_PACKET_SEND_SKIP

%1: prepared response is not sent, because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the `pkt4_send` hook point sets the next step to SKIP. For this particular hook point, this setting instructs the server to drop the packet. This means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease).

13.89 DHCP4_HOOK_SUBNET4_SELECT_406_PARKING_LOT_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the `parked-packet-limit` global parameter. This can occur when `kea-dhcp4` is using hook libraries (e.g. `radius`) that implement the `"subnet4_select"` callout and DHCP406 client queries are arriving faster than those callouts can fulfill them.

13.90 DHCP4_HOOK_SUBNET4_SELECT_DROP

%1: packet was dropped, because a callout set the next step to 'drop'

Logged at debug log level 40. This debug message is printed when a callout installed on the `subnet4_select` hook point sets the next step to 'drop' value. For this particular hook point, the setting to that value instructs the server to drop the received packet. The argument specifies the client and transaction identification information.

13.91 DHCP4_HOOK_SUBNET4_SELECT_PARK

%1: packet was parked

Logged at debug log level 40. This debug message is printed when a callout installed on the `subnet4_select` hook point set the park flag. The argument holds the client and transaction identification information.

13.92 DHCP4_HOOK_SUBNET4_SELECT_PARKING_LOT_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. radius) that implement the "subnet4_select" callout and client queries are arriving faster than those callouts can fulfill them.

13.93 DHCP4_HOOK_SUBNET4_SELECT_SKIP

%1: no subnet was selected, because a callout set the next skip flag

Logged at debug log level 40. This debug message is printed when a callout installed on the subnet4_select hook point sets the next step to SKIP value. For this particular hook point, the setting of the flag instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses will be assigned. The argument specifies the client and transaction identification information.

13.94 DHCP4_HOOK_SUBNET6_SELECT_PARKING_LOT_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp4 is using hook libraries (e.g. radius) that implement the "subnet6_select" callout and client queries are arriving faster than those callouts can fulfill them.

13.95 DHCP4_INFORM_DIRECT_REPLY

%1: DHCPACK in reply to the DHCPINFORM will be sent directly to %2 over %3

Logged at debug log level 50. This debug message is issued when the DHCPACK will be sent directly to the client, rather than via a relay. The first argument contains the client and transaction identification information. The second argument contains the client's IPv4 address to which the response will be sent. The third argument contains the local interface name.

13.96 DHCP4_INIT_FAIL

failed to initialize Kea server: %1

The server has failed to initialize. This may be because the configuration was not successful, or it encountered any other critical error on startup. Attached error message provides more details about the issue.

13.97 DHCP4_INIT_REBOOT

%1: client is in INIT-REBOOT state and requests address %2

This informational message is issued when the client is in the INIT-REBOOT state and is requesting an IPv4 address it is using to be allocated for it. The first argument includes the client and transaction identification information. The second argument specifies the requested IPv4 address.

13.98 DHCP4_LEASE_ALLOC

```
%1: lease %2 has been allocated for %3 seconds
```

This informational message indicates that the server successfully granted a lease in response to client's DHCPREQUEST message. The lease information will be sent to the client in the DHCPACK message. The first argument contains the client and the transaction identification information. The second argument contains the allocated IPv4 address. The third argument is the validity lifetime.

13.99 DHCP4_LEASE_OFFER

```
%1: lease %2 will be offered
```

This informational message indicates that the server has found the lease to be offered to the client. It is up to the client to choose one server out of those which offered leases and continue allocation with that server. The first argument specifies the client and the transaction identification information. The second argument specifies the IPv4 address to be offered.

13.100 DHCP4_LEASE_QUERY_PACKET_PACK_FAILED

```
preparing on-wire-format of the packet to be sent: %1, failed %2
```

This error message is issued when preparing an on-wire format of the packet has failed. The first argument provides packet details. the second the second explains the nature of the error.

13.101 DHCP4_LEASE_QUERY_PACKET_UNPACK_FAILED

```
failed to parse query from %1 to %2, received over interface %3, reason: %4
```

Logged at debug log level 40. This debug message is issued when received DHCPLEASEQUERY is malformed and can't be parsed by the buffer4_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

13.102 DHCP4_LEASE_QUERY_PROCESS_FAILED

```
processing failed for lease query: %1, reason: %2
```

Logged at debug log level 40. This error message is issued when the server encountered an error processing a DHCPLEASEQUERY. The first argument provides query details, the second an explanation of the error.

13.103 DHCP4_LEASE_QUERY_RECEIVED

```
received query: %1
```

Logged at debug log level 40. This debug message is printed when a DHCPLEASEQUERY query has been received. The argument provides query details.

13.104 DHCP4_LEASE_QUERY_RESPONSE_SENT

```
response: %1, sent to %2:%3
```

Logged at debug log level 40. This debug message is printed when a response to a DHCPLEASEQUERY has been sent to a requester. The first argument provides response details, the second and third arguments are the IP address and port to which the response was sent.

13.105 DHCP4_LEASE_QUERY_SEND_FAILED

```
unable to send response: %1, iface: %2, address %3:%4 error: %5
```

This error message is issued when the server was unable to send a lease query response back to the requester. a DHCPLEASEQUERY. The first argument provides query details, followed by the output interface, IP address and port, and finally the error itself.

13.106 DHCP4_LEASE_REUSE

```
%1: lease %2 has been reused for %3 seconds
```

This informational message indicates that the server successfully reused a lease in response to client's message. The lease information will be sent to the client in the DHCPACK message. The first argument contains the client and the transaction identification information. The second argument contains the allocated IPv4 address. The third argument is the validity lifetime.

13.107 DHCP4_MULTI_THREADING_INFO

```
enabled: %1, number of threads: %2, queue size: %3
```

This is a message listing some information about the multi-threading parameters with which the server is running.

13.108 DHCP4_NCR_CREATION_FAILED

```
%1: failed to generate name change requests for DNS: %2
```

This message indicates that server was unable to generate NameChangeRequests which should be sent to the kea-dhcp_ddns module to create new DNS records for the lease being acquired or to update existing records for the renewed lease. The first argument contains the client and transaction identification information. The second argument includes the reason for the failure.

13.109 DHCP4_NOT_RUNNING

```
DHCPv4 server is not running
```

A warning message is issued when an attempt is made to shut down the DHCPv4 server but it is not running.

13.110 DHCP4_NO_LEASE_INIT_REBOOT

```
%1: no lease for address %2 requested by INIT-REBOOT client
```

Logged at debug log level 50. This debug message is issued when the client being in the INIT-REBOOT state requested an IPv4 address but this client is unknown. The server will not respond. The first argument includes the client and the transaction id identification information. The second argument includes the IPv4 address requested by the client.

13.111 DHCP4_OPEN_SOCKET

opening service sockets on port %1

Logged at debug log level 0. This debug message is issued during startup, this indicates that the DHCPv4 server is about to open sockets on the specified port.

13.112 DHCP4_OPEN_SOCKETS_FAILED

maximum number of open service sockets attempts: %1, has been exhausted without success

This error indicates that the server failed to bind service sockets after making the maximum configured number of open attempts.

13.113 DHCP4_OPEN_SOCKETS_NO_RECONNECT_CTL

unexpected error in bind service sockets.

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to bind to its service sockets if they are unavailable, and the server exits. This error should be reported.

13.114 DHCP4_PACKET_DROP_0001

%1: failed to parse packet from %2 to %3, received over interface %4, reason: %5, %6

Logged at debug log level 15. The DHCPv4 server has received a packet that it is unable to interpret. The reason why the packet is invalid is included in the message.

13.115 DHCP4_PACKET_DROP_0002

%1, from interface %2: no suitable subnet configured for a direct client

Logged at debug log level 15. This info message is logged when received a message from a directly connected client but there is no suitable subnet configured for the interface on which this message has been received. The IPv4 address assigned on this interface must belong to one of the configured subnets. Otherwise received message is dropped.

13.116 DHCP4_PACKET_DROP_0003

%1, from interface %2: it contains a foreign server identifier

Logged at debug log level 15. This debug message is issued when received DHCPv4 message is dropped because it is addressed to a different server, i.e. a server identifier held by this message doesn't match the identifier used by our server. The arguments of this message hold the name of the transaction id and interface on which the message has been received.

13.117 DHCP4_PACKET_DROP_0004

%1, from interface %2: missing msg-type option

Logged at debug log level 15. This is a debug message informing that incoming DHCPv4 packet did not have mandatory DHCP message type option and thus was dropped. The arguments specify the client and transaction identification information, as well as the interface on which the message has been received.

13.118 DHCP4_PACKET_DROP_0005

%1: unrecognized type %2 in option 53

Logged at debug log level 15. This debug message indicates that the message type carried in DHCPv4 option 53 is unrecognized by the server. The valid message types are listed on the IANA website: <http://www.iana.org/assignments/bootp-dhcp-parameters/bootp-dhcp-parameters.xhtml#message-type-53>. The message will not be processed by the server. The arguments specify the client and transaction identification information, as well as the received message type.

13.119 DHCP4_PACKET_DROP_0006

%1: unsupported DHCPv4 message type %2

Logged at debug log level 15. This debug message indicates that the message type carried in DHCPv4 option 53 is valid but the message will not be processed by the server. This includes messages being normally sent by the server to the client, such as DHCPOFFER, DHCPACK, DHCPNAK etc. The first argument specifies the client and transaction identification information. The second argument specifies the message type.

13.120 DHCP4_PACKET_DROP_0007

%1: failed to process packet: %2

Logged at debug log level 15. This is a general catch-all message indicating that the processing of a received packet failed. The reason is given in the message. The server will not send a response but will instead ignore the packet. The first argument contains the client and transaction identification information. The second argument includes the details of the error.

13.121 DHCP4_PACKET_DROP_0008

%1: DHCP service is globally disabled

Logged at debug log level 15. This debug message is issued when a packet is dropped because the DHCP service has been temporarily disabled. This affects all received DHCP packets. The service may be enabled by the "dhcp-enable" control command or automatically after a specified amount of time since receiving "dhcp-disable" command.

13.122 DHCP4_PACKET_DROP_0009

%1: Option 53 missing (no DHCP message type), is this a BOOTP packet?

Logged at debug log level 15. This debug message is issued when a packet is dropped because it did contain option 53 and thus has no DHCP message type. The most likely explanation is that it was BOOTP packet.

13.123 DHCP4_PACKET_DROP_0010

dropped as member of the special class 'DROP': %1, %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified into the special class 'DROP' and dropped. The packet details are displayed.

13.124 DHCP4_PACKET_DROP_0011

dropped as sent by the same client as a packet being processed by another thread: dropped %1, %2 by thread %3 as duplicate of %4 processed by thread %5

Logged at debug log level 15. Currently multi-threading processing avoids races between packets sent by a client using the same client id option by dropping new packets until processing is finished. Packet details or summary, and thread identifiers are included for both packets in this warning message.

13.125 DHCP4_PACKET_DROP_0012

dropped as sent by the same client as a packet being processed by another thread: dropped %1, %2 by thread %3 as duplicate of %4 processed by thread %5

Logged at debug log level 15. Currently multi-threading processing avoids races between packets sent by a client using the same hardware address by dropping new packets until processing is finished. Packet details or summary, and thread identifiers are included for both packets in this warning message.

13.126 DHCP4_PACKET_DROP_0013

dropped as member of the special class 'DROP' after host reservation lookup: %1, %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after host reservation lookup into the special class 'DROP' and dropped. The packet details are displayed.

13.127 DHCP4_PACKET_DROP_0014

dropped as member of the special class 'DROP' after early global host reservations lookup: %1, %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after early global host reservations lookup into the special class 'DROP' and dropped. The packet details are displayed.

13.128 DHCP4_PACKET_NAK_0001

%1: failed to select a subnet for incoming packet, src %2, type %3

This error message is output when a packet was received from a subnet for which the DHCPv4 server has not been configured. The most probable cause is a misconfiguration of the server. The first argument contains the client and transaction identification information. The second argument contains the source IPv4 address of the packet. The third argument contains the name of the received packet.

13.129 DHCP4_PACKET_NAK_0002

%1: invalid address %2 requested by INIT-REBOOT

Logged at debug log level 50. This debug message is issued when the client being in the INIT-REBOOT state requested an IPv4 address which is not assigned to him. The server will respond to this client with DHCPNAK. The first argument contains the client and the transaction identification information. The second arguments holds the IPv4 address requested by the client.

13.130 DHCP4_PACKET_NAK_0003

%1: failed to advertise a lease, client sent ciaddr %2, requested-ip-address %3

Logged at debug log level 50. This message indicates that the server has failed to offer a lease to the specified client after receiving a DISCOVER message from it. There are many possible reasons for such a failure. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

13.131 DHCP4_PACKET_NAK_0004

%1: failed to grant a lease, client sent ciaddr %2, requested-ip-address %3

Logged at debug log level 50. This message indicates that the server failed to grant a lease to the specified client after receiving a REQUEST message from it. There are many possible reasons for such a failure. Additional messages will indicate the reason. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

13.132 DHCP4_PACKET_NAK_0005

nacked as member of the special class 'REJECT': %1, %2

Logged at debug log level 15. This message indicates that the server returned a DHCPNAK because the incoming query was classified into the special class 'REJECT'. The packet details are displayed.

13.133 DHCP4_PACKET_OPTIONS_SKIPPED

%1: An error unpacking an option, caused subsequent options to be skipped: %2

Logged at debug log level 50. This debug message is issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the packet. The server will still attempt to service the packet.

13.134 DHCP4_PACKET_PACK

%1: preparing on-wire format of the packet to be sent

Logged at debug log level 50. This debug message is issued when the server starts preparing the on-wire format of the packet to be sent back to the client. The argument specifies the client and the transaction identification information.

13.135 DHCP4_PACKET_PACK_FAIL

%1: preparing on-wire-format of the packet to be sent failed %2

This error message is issued when preparing an on-wire format of the packet has failed. The first argument identifies the client and the DHCP transaction. The second argument includes the error string.

13.136 DHCP4_PACKET_PROCESS_EXCEPTION

%1: exception occurred during packet processing

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

13.137 DHCP4_PACKET_PROCESS_EXCEPTION_MAIN

```
exception occurred during packet processing
```

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

13.138 DHCP4_PACKET_PROCESS_STD_EXCEPTION

```
%1: exception occurred during packet processing: %2
```

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

13.139 DHCP4_PACKET_PROCESS_STD_EXCEPTION_MAIN

```
exception occurred during packet processing: %1
```

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

13.140 DHCP4_PACKET_QUEUE_FULL

```
multi-threading packet queue is full
```

Logged at debug log level 40. A debug message noting that the multi-threading packet queue is full so the oldest packet of the queue was dropped to make room for the received one.

13.141 DHCP4_PACKET_RECEIVED

```
%1: %2 (type %3) received from %4 to %5 on interface %6
```

An INFO message noting that the server has received the specified type of packet on the specified interface. The first argument specifies the client and transaction identification information. The second and third argument specify the name of the DHCPv4 message and its numeric type respectively. The remaining arguments specify the source IPv4 address, destination IPv4 address and the name of the interface on which the message has been received.

13.142 DHCP4_PACKET_SEND

```
%1: trying to send packet %2 (type %3) from %4:%5 to %6:%7 on interface %8
```

An INFO message noting that the server is attempting to send the specified type of packet. The arguments specify the client identification information (HW address and client identifier), DHCP message name and type, source IPv4 address and port, destination IPv4 address and port and the interface name. This debug message is issued when the server is trying to send the response to the client. When the server is using a UDP socket to send the packet there are cases when this operation may be unsuccessful and no error message will be displayed. One such situation occurs when the server is unicasting the response to the 'ciaddr' of a DHCPINFORM message. This often requires broadcasting an ARP message to obtain the link layer address of the unicast destination. If broadcast ARP messages are blocked in the network, according to the firewall policy, the ARP message will not cause a response. Consequently, the response to the DHCPINFORM will not be sent. Since the ARP communication is under the OS control, Kea is not notified about the drop of the packet which it is trying to send and it has no means to display an error message.

13.143 DHCP4_PACKET_SEND_FAIL

```
%1: failed to send DHCPv4 packet: %2
```

This error is output if the DHCPv4 server fails to send an assembled DHCP message to a client. The first argument includes the client and the transaction identification information. The second argument includes the reason for failure.

13.144 DHCP4_PARSER_COMMIT_EXCEPTION

```
parser failed to commit changes
```

On receipt of message containing details to a change of the DHCPv4 server configuration, a set of parsers were successfully created, but one of them failed to commit its changes due to a low-level system exception being raised. Additional messages may be output indicating the reason.

13.145 DHCP4_PARSER_COMMIT_FAIL

```
parser failed to commit changes: %1
```

On receipt of message containing details to a change of the DHCPv4 server configuration, a set of parsers were successfully created, but one of them failed to commit its changes. The reason for the failure is given in the message.

13.146 DHCP4_PARSER_EXCEPTION

```
failed to create or run parser for configuration element %1
```

On receipt of message containing details to a change of its configuration, the DHCPv4 server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The message has been output in response to a non-Kea exception being raised. Additional messages may give further information.

13.147 DHCP4_PARSER_FAIL

```
failed to create or run parser for configuration element %1: %2
```

On receipt of message containing details to a change of its configuration, the DHCPv4 server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

13.148 DHCP4_POST_ALLOCATION_NAME_UPDATE_FAIL

```
%1: failed to update hostname %2 in a lease after address allocation: %3
```

This message indicates the failure when trying to update the lease and/or options in the server's response with the hostname generated by the server or reserved for the client belonging to a shared network. The latter is the case when the server dynamically switches to another subnet (than initially selected for allocation) from the same shared network.

13.149 DHCP4_QUERY_DATA

```
%1, packet details: %2
```

Logged at debug log level 55. A debug message printing the details of the received packet. The first argument includes the client and the transaction identification information. Packet fields ciaddr, yiaddr, siaddr, giaddr, sname, and file will be included when not empty.

13.150 DHCP4_QUERY_LABEL

```
received query: %1
```

This information message indicates that a query was received. It displays the client and the transaction identification information.

13.151 DHCP4_RECLAIM_EXPIRED_LEASES_FAIL

```
failed to reclaim expired leases: %1
```

This error message indicates that the reclaim expired leases operation failed and provides the cause of failure.

13.152 DHCP4_RECLAIM_EXPIRED_LEASES_SKIPPED

```
dhcp6 service is currently disabled. Try again in %1 seconds.
```

Logged at debug log level 40. This debug message is emitted when lease reclamation was scheduled to begin but skipped because DHCPv6 service was disabled. Reclamation will continue to be scheduled according to the configured value of reclaim-timer-wait-time.

13.153 DHCP4_RECOVERED_STASHED_RELAY_AGENT_INFO

```
recovered for query %1 relay agent option from lease %2: %3
```

Logged at debug log level 55. This debug message indicates that agent options were stashed in the lease for the client address of the request and were recovered. The first argument includes the request information, the second the client address and the last argument the content of the dhcp-agent-options option.

13.154 DHCP4_RELEASE

```
%1: address %2 was released properly.
```

Logged at debug log level 50. This informational message indicates that an address was released properly. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

13.155 DHCP4_RELEASE_DELETED

```
%1: address %2 was deleted on release.
```

This informational message indicates that an address was deleted on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

13.156 DHCP4_RELEASE_EXCEPTION

%1: while trying to release address %2 an exception occurred: %3

This message is output when an error was encountered during an attempt to process a DHCPRELEASE message. The error will not affect the client, which does not expect any response from the server for DHCPRELEASE messages. Depending on the nature of problem, it may affect future server operation. The first argument includes the client and the transaction identification information. The second argument includes the IPv4 address which release was attempted. The last argument includes the detailed error description.

13.157 DHCP4_RELEASE_EXPIRED

%1: address %2 expired on release.

This informational message indicates that an address expired on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second argument includes the released IPv4 address.

13.158 DHCP4_RELEASE_FAIL

%1: failed to remove lease for address %2

Logged at debug log level 50. This error message indicates that the software failed to remove a lease from the lease database. It is probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address which release was attempted.

13.159 DHCP4_RELEASE_FAIL_NOT_ASSIGNED

%1: client is trying to release the lease %2 which is in the %3 state

Logged at debug log level 50. This debug message is issued when a client is trying to release the lease which is not in the default / assigned state e.g. kept for the client by the lease affinity feature in the released state. The first argument includes the client and the transaction identification information. The second argument specifies the leased address, the last one the lease state.

13.160 DHCP4_RELEASE_FAIL_NO_LEASE

%1: client is trying to release non-existing lease %2

Logged at debug log level 50. This debug message is printed when client attempts to release a lease, but no such lease is known to the server. The first argument contains the client and transaction identification information. The second argument contains the IPv4 address which the client is trying to release.

13.161 DHCP4_RELEASE_FAIL_WRONG_CLIENT

%1: client is trying to release the lease %2 which belongs to a different client

Logged at debug log level 50. This debug message is issued when a client is trying to release the lease for the address which is currently used by another client, i.e. the 'client identifier' or 'chaddr' doesn't match between the client and

the lease. The first argument includes the client and the transaction identification information. The second argument specifies the leased address.

13.162 DHCP4_REQUEST

```
%1: server is processing DHCPREQUEST with hint=%2
```

Logged at debug log level 50. This is a debug message that indicates the processing of a received DHCPREQUEST message. The first argument contains the client and the transaction identification information. The second argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

13.163 DHCP4_RESERVATIONS_LOOKUP_FIRST_ENABLED

```
Multi-threading is enabled and host reservations lookup is always performed first.
```

This is a message informing that host reservations lookup is performed before lease lookup when multi-threading is enabled overwriting configured value.

13.164 DHCP4_RESERVED_HOSTNAME_ASSIGNED

```
%1: server assigned reserved hostname %2
```

Logged at debug log level 55. This debug message is issued when the server found a hostname reservation for a client and uses this reservation in a hostname option sent back to this client. The reserved hostname is qualified with a value of 'ddns-qualifying-suffix' parameter, if this parameter is specified.

13.165 DHCP4_RESPONSE_DATA

```
%1: responding with packet %2 (type %3), packet details: %4
```

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information. Packet fields ciaddr, yiaddr, siaddr, giaddr, sname, and file will be included when not empty.

13.166 DHCP4_RESPONSE_FQDN_DATA

```
%1: including FQDN option in the server's response: %2
```

Logged at debug log level 55. This debug message is issued when the server is adding the Client FQDN option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the FQDN option may be modified by the server when the lease is acquired for the client.

13.167 DHCP4_RESPONSE_HOSTNAME_DATA

```
%1: including Hostname option in the server's response: %2
```

Logged at debug log level 55. This debug message is issued when the server is adding the Hostname option in its response to the client. The first argument includes the client and transaction identification information. The second

argument includes the details of the FQDN option being included. Note that the name carried in the Hostname option may be modified by the server when the lease is acquired for the client.

13.168 DHCP4_RESPONSE_HOSTNAME_GENERATE

```
%1: server has generated hostname %2 for the client
```

Logged at debug log level 50. This debug message includes the auto-generated hostname which will be used for the client which message is processed. Hostnames may need to be generated when required by the server's configuration or when the client hasn't supplied its hostname. The first argument includes the client and the transaction identification information. The second argument holds the generated hostname.

13.169 DHCP4_ROOT_USER_SECURITY_WARNING

```
kea-dhcp4 running as root user!
```

This warning is emitted when kea-dhcp4 is running as a root user. While the server will function fully, this mode of operation may expose your environment to security vulnerabilities and should only be used after careful consideration.

13.170 DHCP4_SANITIZED_HOSTNAME_MALFORMED

```
%1: hostname after sanitizing is malformed: %2
```

Logged at debug log level 50. This debug message is issued when the value generated by the server after applying host name sanitization does not constitute a valid domain name. The first argument includes the client and transaction identification information. The second argument contains a description of the data error.

13.171 DHCP4_SECURITY_CHECKS_DISABLED

```
Invoked with command line option -X, Security checks are disabled!!
```

This warning is emitted when internal security checks normally performed by kea-dhcp4 have been disabled via command line option '-X'. This means the server is not enforcing restrictions on resource paths or permissions. This mode of operation may expose your environment to security vulnerabilities and should only be used after careful consideration.

13.172 DHCP4_SERVER_FAILED

```
server failed: %1
```

The DHCPv4 server has encountered a fatal error and is terminating. The reason for the failure is included in the message.

13.173 DHCP4_SERVER_INITIATED_DECLINE

```
%1: Lease for addr %2 has been found to be already in use. The lease will be unavailable for %3 seconds.
```

This informational message is printed when the server has detected via ICMP ECHO (i.e. ping check) or other means that a lease which should be free to offer is actually in use. This message may indicate a misconfiguration in a network or more likely a device that is using an address that it is not supposed to use. The server will fully recover from this situation, but if the underlying problem of a misconfigured or rogue device is not solved, this address may be declined again in the future.

13.174 DHCP4_SERVER_INITIATED_DECLINE_ADD_FAILED

%1: error adding a lease for address %2: %3

This error message indicates that the server failed to add a DECLINED lease to the lease store. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address for which the decline was attempted, the last one the error message.

13.175 DHCP4_SERVER_INITIATED_DECLINE_RESOURCE_BUSY

%1: error declining a lease for address %2

This error message indicates that while one server thread was attempting to mark a lease as DECLINED, it was already locked by another thread. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address for which the decline was attempted.

13.176 DHCP4_SERVER_INITIATED_DECLINE_UPDATE_FAILED

%1: error updating lease for address %2

This error message indicates that the server failed to update a lease in the lease store to the DECLINED state. The first argument includes the client and the transaction identification information. The second argument holds the IPv4 address for which the decline was attempted.

13.177 DHCP4_SHUTDOWN

server shutdown

Logged at debug log level 40. The DHCPv4 server has terminated normally.

13.178 DHCP4_SHUTDOWN_REQUEST

shutdown of server requested

Logged at debug log level 40. This debug message indicates that a shutdown of the DHCPv4 server has been requested via a call to the 'shutdown' method of the core Dhcpv4Srv object.

13.179 DHCP4_SRV_CONSTRUCT_ERROR

error creating Dhcpv4Srv object, reason: %1

This error message indicates that during startup, the construction of a core component within the DHCPv4 server (the Dhcpv4 server object) has failed. As a result, the server will exit. The reason for the failure is given within the message.

13.180 DHCP4_SRV_D2STOP_ERROR

error stopping IO with DHCP_DDNS during shutdown: %1

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv4 server and the DHCP_DDNS server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

13.181 DHCP4_SRV_DHCP4O6_ERROR

```
error stopping IO with DHCPv4o6 during shutdown: %1
```

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv4 server and the DHCPv4o6 server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

13.182 DHCP4_SRV_UNLOAD_LIBRARIES_ERROR

```
error unloading hooks libraries during shutdown: %1
```

This error message indicates that during shutdown, unloading hooks libraries failed to close them. If the list of libraries is empty it is a programmatic error in the server code. If it is not empty it could be a programmatic error in one of the hooks libraries which could lead to a crash during finalization.

13.183 DHCP4_STARTED

```
Kea DHCPv4 server version %1 started
```

This informational message indicates that the DHCPv4 server has processed all configuration information and is ready to process DHCPv4 packets. The version is also printed.

13.184 DHCP4_STARTING

```
Kea DHCPv4 server version %1 (%2) starting
```

This informational message indicates that the DHCPv4 server has processed any command-line switches and is starting. The version is also printed.

13.185 DHCP4_START_INFO

```
pid: %1, server port: %2, client port: %3, verbose: %4
```

Logged at debug log level 0. This is a debug message issued during the DHCPv4 server startup. It lists some information about the parameters with which the server is running.

13.186 DHCP4_SUBNET_DATA

```
%1: the selected subnet details: %2
```

Logged at debug log level 55. This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second arguments includes the subnet details.

13.187 DHCP4_SUBNET_DYNAMICALLY_CHANGED

```
%1: changed selected subnet %2 to subnet %3 from shared network %4 for client assignments
```

Logged at debug log level 45. This debug message indicates that the server is using another subnet than initially selected for client assignments. This newly selected subnet belongs to the same shared network as the original subnet. Some reasons why the new subnet was selected include: address pool exhaustion in the original subnet or the fact that the new subnet includes some static reservations for this client.

13.188 DHCP4_SUBNET_SELECTED

%1: the subnet with ID %2 was selected for client assignments

Logged at debug log level 45. This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

13.189 DHCP4_SUBNET_SELECTION_FAILED

%1: failed to select subnet for the client

Logged at debug log level 50. This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The server will not be able to offer any lease to the client and will drop its message if the received message was DHCPDISCOVER, and will send DHCPNAK if the received message was DHCPREQUEST. The argument includes the client and the transaction identification information.

13.190 DHCP4_TESTING_MODE_SEND_TO_SOURCE_ENABLED

All packets will be sent to the source address of an incoming packet - use only for testing

This message is printed when the KEA_TEST_SEND_RESPONSES_TO_SOURCE environment variable is set. It causes Kea to send packets to the source address of the incoming packet. It is only usable in a testing environment to simulate multiple subnet traffic from single source.

13.191 DHCP4_UNKNOWN_ADDRESS_REQUESTED

%1: client requested an unknown address, client sent ciaddr %2, requested-ip-address %3

Logged at debug log level 50. This message indicates that the client requested an address that does not belong to any dynamic pools managed by this server. The first argument contains the client and the transaction identification information. The second argument contains the IPv4 address in the ciaddr field. The third argument contains the IPv4 address in the requested-ip-address option (if present).

13.192 DHCP4_V6_ONLY_PREFERRED_MISSING_IN_ACK

v6-only-preferred option missing in 0.0.0.0 reply to query: %1

An DHCPACK for the 0.0.0.0 address was generated for a client requesting the v6-only-preferred (108) option but the option is not in the response as expected: the erroneous response is dropped, the request query is displayed.

13.193 DHCP4_V6_ONLY_PREFERRED_MISSING_IN_OFFER

v6-only-preferred option missing in 0.0.0.0 offer to query: %1

An DHCPOFFER for the 0.0.0.0 address was generated for a client requesting the v6-only-preferred (108) option but the option is not in the response as expected: the erroneous response is dropped, the discover query is displayed.

14.1 DHCP6_ADDITIONAL_CLASS_EVAL_ERROR

%1: Expression '%2' evaluated to %3

This error message indicates that a problem was encountered while evaluating the expression of an additional client class. A description of the problem is printed.

14.2 DHCP6_ADDITIONAL_CLASS_EVAL_RESULT

%1: Expression '%2' evaluated to %3

Logged at debug log level 50. This debug message indicates that the expression of an additional client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

14.3 DHCP6_ADDITIONAL_CLASS_NO_TEST

additional class %1 has no test expression, adding it to client's classes unconditionally

Logged at debug log level 40. This debug message informs that a class was listed for additional evaluation but its definition does not include a test expression to evaluate. The class is unconditionally added to the query.

14.4 DHCP6_ADDITIONAL_CLASS_UNDEFINED

additional class %1 has no definition

Logged at debug log level 40. This debug message informs that a class is listed for additional evaluation but has no definition. The class is ignored.

14.5 DHCP6_ADDR6_REGISTER_DISABLED_DROP

ADDR-REG-INFORM from %1 was dropped because address registration is disabled.

Logged at debug log level 40. This debug message is printed when the server drops an ADDR-REG-INFORM packet because 'allow-address-registration' is false.

14.6 DHCP6_ADDR_REG_INFORM_CLIENT_CHANGE

```
received an ADDR-REG-INFORM for %1 from client '%2' but the address was registered by another client '%3'
```

This information message is issued when a lease for another client already exists for an address being registered. The address, the new client and previous client identifiers are printed.

14.7 DHCP6_ADDR_REG_INFORM_FAIL

```
error on ADDR-REG-INFORM from client %1, %2
```

This information message is issued when the processing of an ADDR-REG-INFORM message failed. The address of the client, usually also the address to register, and the description of the problem are printed.

14.8 DHCP6_ADD_DEPRECATED_UNICAST

```
%1: adding deprecated unicast option
```

The warning is logged when the deprecated unicast option is added to the response. Outside testing purposes the server configuration should be fixed as direct unicast queries are no longer accepted.

14.9 DHCP6_ADD_GLOBAL_STATUS_CODE

```
%1: adding Status Code to DHCPv6 packet: %2
```

Logged at debug log level 50. This message is logged when the server is adding the top-level Status Code option. The first argument includes the client and the transaction identification information. The second argument includes the details of the status code.

14.10 DHCP6_ADD_STATUS_CODE_FOR_IA

```
%1: adding Status Code to IA with iaid=%2: %3
```

Logged at debug log level 50. This message is logged when the server is adding the Status Code option to an IA. The first argument includes the client and the transaction identification information. The second argument specifies the IAID. The third argument includes the details of the status code.

14.11 DHCP6_ALREADY_RUNNING

```
%1 already running? %2
```

This is an error message that occurs when the DHCPv6 server encounters a pre-existing PID file which contains the PID of a running process. This most likely indicates an attempt to start a second instance of the server using the same configuration file. It is possible, though unlikely that the PID file is a remnant left behind by a server crash or power failure and the PID it contains refers to a process other than the server. In such an event, it would be necessary to manually remove the PID file. The first argument is the DHCPv6 process name, the second contains the PID and PID file.

14.12 DHCP6_BUFFER_RECEIVED

```
received buffer from %1:%2 to %3:%4 over interface %5
```

Logged at debug log level 40. This debug message is logged when the server has received a packet over the socket. When the message is logged the contents of the received packet hasn't been parsed yet. The only available information is the interface and the source and destination addresses/ports.

14.13 DHCP6_BUFFER_UNPACK

```
parsing buffer received from %1 to %2 over interface %3
```

Logged at debug log level 50. This debug message is issued when the server starts parsing the received buffer holding the DHCPv6 message. The arguments specify the source and destination addresses as well as the interface over which the buffer has been received.

14.14 DHCP6_BUFFER_WAIT_SIGNAL

```
signal received while waiting for next packet
```

Logged at debug log level 50. This debug message is issued when the server was waiting for the packet, but the wait has been interrupted by the signal received by the process. The signal will be handled before the server starts waiting for next packets.

14.15 DHCP6_CB_ON_DEMAND_FETCH_UPDATES_FAIL

```
error on demand attempt to fetch configuration updates from the configuration backend(s): %1
```

This error message is issued when the server attempted to fetch configuration updates from the database and this on demand attempt failed. The sole argument which is returned to the config-backend-pull command caller too contains the reason for failure.

14.16 DHCP6_CB_PERIODIC_FETCH_UPDATES_FAIL

```
error on periodic attempt to fetch configuration updates from the configuration backend(s): %1
```

This error message is issued when the server attempted to fetch configuration updates from the database and this periodic attempt failed. The server will re-try according to the configured value of the config-fetch-wait-time parameter. The sole argument contains the reason for failure.

14.17 DHCP6_CB_PERIODIC_FETCH_UPDATES_RETRIES_EXHAUSTED

```
maximum number of configuration fetch attempts: 10, has been exhausted without success
```

This error indicates that the server has made a number of unsuccessful periodic attempts to fetch configuration updates from a configuration backend. The server will continue to operate but won't make any further attempts to fetch configuration updates. The administrator must fix the configuration in the database and reload (or restart) the server.

14.18 DHCP6_CB_REPAIR_MODE_ENABLED

Server is running in config back end repair mode.

This warning is emitted when config back end repair mode is enabled. This allows the server to start and run without automatically fetching config back end data but can still process CB API commands. This allows admins to correct errors in config back end data.

14.19 DHCP6_CLASSES_ASSIGNED

%1: client packet has been assigned on %2 message to the following classes: %3

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument specifies the DHCPv6 message type. The third argument includes all classes to which the packet has been assigned.

14.20 DHCP6_CLASSES_ASSIGNED_AFTER_SUBNET_SELECTION

%1: client packet has been assigned to the following classes: %2

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified classes. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes all classes to which the packet has been assigned.

14.21 DHCP6_CLASS_ASSIGNED

%1: client packet has been assigned to the following class: %2

Logged at debug log level 40. This debug message informs that incoming packet has been assigned to specified class. This is a normal behavior and indicates successful operation. The first argument specifies the client and transaction identification information. The second argument includes the new class to which the packet has been assigned.

14.22 DHCP6_CLASS_UNCONFIGURED

%1: client packet belongs to an unconfigured class: %2

Logged at debug log level 40. This debug message informs that incoming packet belongs to a class which cannot be found in the configuration. Either a hook written before the classification was added to Kea is used, or class naming is inconsistent.

14.23 DHCP6_CLIENT_FQDN_SCRUBBED_EMPTY

%1: sanitizing client's FQDN option '%2' yielded an empty name or an empty label within the name

Logged at debug log level 50. This debug message is issued when the result of sanitizing the FQDN option(39) sent by the client is an empty name or an empty label within the name (e.g. "aaa.bbb.com"). When this occurs the server will ignore the FQDN option. The arguments include the client and the FQDN option it sent.

14.24 DHCP6_CONFIG_COMPLETE

```
DHCPv6 server has completed configuration: %1
```

This is an informational message announcing the successful processing of a new configuration. It is output during server startup, and when an updated configuration is committed by the administrator. Additional information may be provided.

14.25 DHCP6_CONFIG_HOSTS_DATABASE_DEPRECATED

```
the "host-database" keyword will be deprecated
```

This warning message indicates the configuration still uses the "hosts-database", a keyword which is deprecated and will be rejected by a future release. Please use "hosts-databases" instead and put the database configuration into a list.

14.26 DHCP6_CONFIG_LOAD_FAIL

```
configuration error using file: %1, reason: %2
```

This error message indicates that the DHCPv6 configuration has failed. If this is an initial configuration (during server's startup) the server will fail to start. If this is a dynamic reconfiguration attempt the server will continue to use an old configuration.

14.27 DHCP6_CONFIG_PACKET_QUEUE

```
DHCPv6 packet queue info after configuration: %1
```

This informational message is emitted during DHCPv6 server configuration, immediately after configuring the DHCPv6 packet queue. The information shown depends upon the packet queue type selected.

14.28 DHCP6_CONFIG_RECEIVED

```
received configuration: %1
```

Logged at debug log level 10. A debug message listing the configuration received by the DHCPv6 server. The source of that configuration depends on used configuration backend.

14.29 DHCP6_CONFIG_START

```
DHCPv6 server is processing the following configuration: %1
```

Logged at debug log level 10. This is a debug message that is issued every time the server receives a configuration. That happens start up and also when a server configuration change is committed by the administrator.

14.30 DHCP6_CONFIG_SYNTAX_WARNING

```
configuration syntax warning: %1
```

This warning message indicates that the DHCPv6 configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

14.31 DHCP6_CONFIG_UNRECOVERABLE_ERROR

```
DHCPv6 server new configuration failed with an error which cannot be recovered
```

This fatal error message is issued when a new configuration raised an error which cannot be recovered. A correct configuration must be applied as soon as possible as the server is no longer working. The configuration can be fixed in several ways. If the control channel is open, config-set with a valid configuration can be used. Alternatively, the original config file on disk could be fixed and SIGHUP signal could be sent (or the config-reload command issued). Finally, the server could be restarted completely.

14.32 DHCP6_CONFIG_UNSUPPORTED_OBJECT

```
DHCPv6 server configuration includes an unsupported object: %1
```

This error message is issued when the configuration includes an unsupported object (i.e. a top level element).

14.33 DHCP6_DATA_DIRECTORY_DEPRECATED

```
'data-directory' has been deprecated and should no longer be used.
```

This warning message is emitted when the configuration parsing detects that the *data-directory* parameter has been specified. This parameter is no longer supported. This supported path, determined at compile time, may be overridden at runtime by setting the environment variable 'KEA_DHCP_DATA_DIR'.

14.34 DHCP6_DB_RECONNECT_DISABLED

```
database reconnect is disabled: retries left: %1, reconnect wait time: %2, manager ID: %3, timer: %4
```

This is an error message indicating that connectivity to either the lease or host database or both was lost and that automatic reconnect is not enabled. Loss of connectivity is typically a network or database server issue.

14.35 DHCP6_DB_RECONNECT_FAILED

```
maximum number of database reconnect attempts: %1, has been exhausted without success, manager ID: %2, timer: %3
```

This error indicates that the server failed to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. Loss of connectivity is typically a network or database server issue.

14.36 DHCP6_DB_RECONNECT_LOST_CONNECTION

```
database connection lost: manager ID: %1, timer: %2.
```

This info message indicates that the connection has been lost and the dhcp service might have been disabled, as specified in the configuration, in order to try to recover the connection.

14.37 DHCP6_DB_RECONNECT_NO_DB_CTL

```
unexpected error in database reconnect
```

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to reconnect to its databases if connectivity is lost, and the server exits. This error should be reported.

14.38 DHCP6_DB_RECONNECT_SUCCEEDED

```
database connection recovered: manager ID: %1, timer: %2.
```

This info message indicates that the connection has been recovered and the dhcp service has been restored.

14.39 DHCP6_DDNS_CREATE_ADD_NAME_CHANGE_REQUEST

```
%1: created name change request: %2
```

Logged at debug log level 50. This debug message is logged when the new NameChangeRequest has been created to perform the DNS Update, which adds new RRs.

14.40 DHCP6_DDNS_FQDN_GENERATED

```
%1: generated FQDN for the client: %2
```

Logged at debug log level 55. This debug message is logged when the server generated FQDN (name) for the client which message is processed. The names may be generated by the server when required by the server's policy or when the client doesn't provide any specific FQDN in its message to the server. The first argument includes the client and transaction identification information. The second argument includes the generated FQDN.

14.41 DHCP6_DDNS_GENERATED_FQDN_UPDATE_FAIL

```
%1: failed to update the lease using address %2, after generating FQDN for a client, reason: %3
```

This message indicates the failure when trying to update the lease and/or options in the server's response with the hostname generated by the server from the acquired address. The first argument includes the client and the transaction identification information. The second argument is a leased address. The third argument includes the reason for the failure.

14.42 DHCP6_DDNS_GENERATE_FQDN

```
%1: client did not send a FQDN option; FQDN will be
```

Logged at debug log level 50. generated for the client. This debug message is issued when the server did not receive a FQDN option from the client and client name replacement is enabled. This provides a means to create DNS entries for unsophisticated clients.

14.43 DHCP6_DDNS_RECEIVE_FQDN

```
%1: received DHCPv6 Client FQDN option: %2
```

Logged at debug log level 50. This debug message is logged when server has found the DHCPv6 Client FQDN Option sent by a client and started processing it. The first argument includes the client and transaction identification information. The second argument includes the received FQDN.

14.44 DHCP6_DDNS_REMOVE_OLD_LEASE_FQDN

```
%1: FQDN for a lease: %2 has changed. New values: hostname = %3, reverse mapping = %4, forward mapping = %5
```

Logged at debug log level 50. This debug message is logged during lease renewal when an old lease that is no longer being offered has a different FQDN than the renewing lease. Thus the old DNS entries need to be removed. The first argument includes the client and the transaction identification information. The second argument holds the details about the lease for which the FQDN information and/or mappings have changed. The remaining arguments hold the new FQDN information and flags for mappings.

14.45 DHCP6_DDNS_REQUEST_SEND_FAILED

```
failed sending a request to kea-dhcp-ddns, error: %1, ncr: %2
```

This error message indicates that IPv6 DHCP server failed to send a DDNS update request to the DHCP-DDNS server. This is most likely a configuration or networking error.

14.46 DHCP6_DDNS_RESPONSE_FQDN_DATA

```
%1: including FQDN option in the server's response: %2
```

Logged at debug log level 50. This debug message is issued when the server is adding the Client FQDN option in its response to the client. The first argument includes the client and transaction identification information. The second argument includes the details of the FQDN option being included. Note that the name carried in the FQDN option may be modified by the server when the lease is acquired for the client.

14.47 DHCP6_DECLINE_FAIL

```
%1: error on decline lease for address %2: %3
```

This error message indicates that the software failed to decline a lease from the lease database due to an error during a database operation. The first argument includes the client and the transaction identification information. The second argument holds the IPv6 address which decline was attempted. The last one contains the reason for failure.

14.48 DHCP6_DECLINE_FAIL_DUID_MISMATCH

```
Client %1 sent DECLINE for address %2, but it belongs to client with DUID %3
```

This informational message is printed when a client attempts to decline a lease, but that lease belongs to a different client. The decline request will be rejected.

14.49 DHCP6_DECLINE_FAIL_IAID_MISMATCH

```
Client %1 sent DECLINE for address %2, but used a wrong IAID (%3), instead of expected %4
```

This informational message is printed when a client attempts to decline a lease. The server has a lease for this address, it belongs to this client, but the recorded IAID does not match what client has sent. This means the server will reject this Decline.

14.50 DHCP6_DECLINE_FAIL_LEASE_WITHOUT_DUID

```
Client %1 sent DECLINE for address %2, but the associated lease has no DUID
```

This error condition likely indicates database corruption, as every IPv6 lease is supposed to have a DUID, even if it is an empty one.

14.51 DHCP6_DECLINE_FAIL_NO_LEASE

```
Client %1 sent DECLINE for address %2, but there's no lease for it
```

This informational message is printed when a client tried to decline an address, but the server has no lease for said address. This means that the server's and client's perception of the leases are different. The likely causes of this could be: a confused (e.g. skewed clock) or broken client (e.g. client moved to a different location and didn't notice) or possibly an attack (a rogue client is trying to decline random addresses). The server will inform the client that his decline request was rejected and client should be able to recover from that.

14.52 DHCP6_DECLINE_LEASE

```
Client %1 sent DECLINE for address %2 and the server marked it as declined. The lease will be recovered in %3 seconds.
```

This informational message indicates that the client leased an address, but discovered that it is being used by some other device and reported this to the server by sending a Decline message. The server marked the lease as declined. This likely indicates a misconfiguration in the network. Either the server is configured with an incorrect pool or there are devices that have statically assigned addresses that are supposed to be assigned by the DHCP server. Both client (will request a different address) and server (will recover the lease after decline-probation-time elapses) will recover automatically. However, if the underlying problem is not solved, the conditions leading to this message may reappear.

14.53 DHCP6_DECLINE_PROCESS_IA

```
Processing of IA (IAID: %1) from client %2 started.
```

Logged at debug log level 50. This debug message is printed when the server starts processing an IA_NA option received in Decline message. It's expected that the option will contain an address that is being declined. Specific information will be printed in a separate message.

14.54 DHCP6_DEVELOPMENT_VERSION

```
This software is a development branch of Kea. It is not recommended for production use.
```

This warning message is displayed when the version is a development (vs stable) one: the second number of the version is odd.

14.55 DHCP6_DHCP4O6_PACKET_RECEIVED

```
received DHCPv4o6 packet from DHCPv4 server (type %1) for %2 port %3 on interface %4
```

Logged at debug log level 40. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication.

14.56 DHCP6_DHCP4O6_RECEIVE_FAIL

```
failed to receive DHCPv4o6: %1
```

Logged at debug log level 50. This debug message indicates the inter-process communication with the DHCPv4 server failed. The reason for the error is included in the message.

14.57 DHCP6_DHCP4O6_RECEIVING

```
receiving DHCPv4o6 packet from DHCPv4 server
```

Logged at debug log level 50. This debug message is printed when the server is receiving a DHCPv4o6 from the DHCPv4 server over inter-process communication socket.

14.58 DHCP6_DHCP4O6_RESPONSE_DATA

```
%1: responding with packet %2 (type %3), packet details: %4
```

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

14.59 DHCP6_DHCP4O6_SEND_FAIL

```
%1: failed to send DHCPv4o6 packet: %2
```

This error is output if the IPv6 DHCP server fails to send an assembled DHCPv4o6 message to a client. The reason for the error is included in the message.

14.60 DHCP6_DYNAMIC_RECONFIGURATION

```
initiate server reconfiguration using file: %1, after receiving SIGHUP signal or config-reload command
```

This is the info message logged when the DHCPv6 server starts reconfiguration as a result of receiving SIGHUP signal or config-reload command.

14.61 DHCP6_DYNAMIC_RECONFIGURATION_FAIL

```
dynamic server reconfiguration failed with file: %1
```

This is an error message logged when the dynamic reconfiguration of the DHCP server failed.

14.62 DHCP6_DYNAMIC_RECONFIGURATION_SUCCESS

```
dynamic server reconfiguration succeeded with file: %1
```

This is info message logged when the dynamic reconfiguration of the DHCP server succeeded.

14.63 DHCP6_FATAL_DB_RECONNECT_DISABLED

```
database reconnect is disabled: retries left: %1, reconnect wait time: %2, manager ID: %3, timer: %4
```

This is an error message indicating that connectivity to either the lease or host database or both was lost and that automatic reconnect is not enabled. This causes the server to shut down as specified in the configuration. Loss of connectivity is typically a network or database server issue.

14.64 DHCP6_FATAL_DB_RECONNECT_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success, manager ID: %2, timer: %3

This error indicates that the server failed to reconnect to the lease and/or host database(s) after making the maximum configured number of reconnect attempts. This causes the server to shut down as specified in the configuration. Loss of connectivity is typically a network or database server issue.

14.65 DHCP6_FATAL_DYNAMIC_RECONFIGURATION_FAIL

dynamic server reconfiguration failed with file: %1

This is a fatal error message logged when the dynamic reconfiguration of the DHCP server failed.

14.66 DHCP6_FATAL_OPEN_SOCKETS_FAILED

maximum number of open service sockets attempts: %1, has been exhausted without success

This error indicates that the server failed to bind service sockets after making the maximum configured number of open attempts. This causes the server to shut down as specified in the configuration.

14.67 DHCP6_FLEX_ID

%1: flexible identifier generated for incoming packet: %2

Logged at debug log level 40. This debug message is printed when host reservation type is set to flexible identifier and the expression specified in its configuration generated (was evaluated to) an identifier for incoming packet. This debug message is mainly intended as a debugging assistance for flexible identifier.

14.68 DHCP6_HOOK_ADDR6_REGISTER_DROP

%1: ADDR-REG-INFORM for %2 is dropped, because a callout set the next step to DROP

Logged at debug log level 40. This debug message is printed when a callout installed on the `addr6_register` hook point sets the next step to DROP. For this particular hook point, the value setting instructs the server to cancel the address registration and drop the packet.

14.69 DHCP6_HOOK_ADDR6_REGISTER_SKIP

%1: lease %2 operation for %3 is skipped, because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the `addr6_register` hook point sets the next step to SKIP. For this particular hook point, the value setting instructs the server to skip the lease add or update operation for the registered address so not maintaining the registration state.

14.70 DHCP6_HOOK_BUFFER_RCVD_DROP

received buffer from %1 to %2 over interface %3 was dropped because a callout set the drop flag

Logged at debug log level 15. This debug message is printed when a callout installed on `buffer6_receive` hook point set the drop flag. For this particular hook point, the setting of the flag by a callout instructs the server to drop the packet. The arguments specify the source and destination address as well as the name of the interface over which the buffer has been received.

14.71 DHCP6_HOOK_BUFFER_RCVD_SKIP

received buffer from %1 to %2 over interface %3 is not parsed because a callout set the next step to SKIP

Logged at debug log level 50. This debug message is printed when a callout installed on buffer6_receive hook point set the next step status to skip. For this particular hook point, this value set by a callout instructs the server to not parse the buffer because it was already parsed by the hook. The arguments specify the source and destination address as well as the name of the interface over which the buffer has been received.

14.72 DHCP6_HOOK_BUFFER_SEND_SKIP

%1: prepared DHCPv6 response was dropped because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on buffer6_send hook point set the next step to SKIP value. For this particular hook point, the SKIP setting a callout instructs the server to drop the packet. Server completed all the processing (e.g. may have assigned, updated or released leases), but the response will not be sent to the client. The argument includes the client and transaction identification information.

14.73 DHCP6_HOOK_DDNS_UPDATE

A hook has updated the DDNS parameters: hostname %1=>%2, forward update %3=>%4, reverse update %5=>%6

Logged at debug log level 15. This message indicates that there was a hook called on ddns6_update hook point and that hook updated the DDNS update parameters: hostname, or whether to conduct forward (A record) or reverse (PTR record) DDNS updates.

14.74 DHCP6_HOOK_DECLINE_DROP

During Decline processing (client=%1, interface=%2, addr=%3) hook callout set next step to DROP, dropping packet.

Logged at debug log level 15. This message indicates that the server received DECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for the lease6_decline hook point and one of the callouts set next step status to DROP. The server will now abort processing of the packet as if it was never received. The lease will continue to be assigned to this client.

14.75 DHCP6_HOOK_DECLINE_SKIP

During Decline processing (client=%1, interface=%2, addr=%3) hook callout set status to SKIP, skipping decline.

Logged at debug log level 50. This message indicates that the server received DECLINE message, it was verified to be correct and matching server's lease information. The server called hooks for the lease6_decline hook point and one of the callouts set next step status to SKIP. The server will skip the operation of moving the lease to the declined state and will continue processing the packet. In particular, it will send a REPLY message as if the decline actually took place.

14.76 DHCP6_HOOK_LEASE6_RELEASE_NA_SKIP

%1: DHCPv6 address lease was not released because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the lease6_release hook point set the next step to SKIP. For this particular hook point, this setting by a callout instructs the server to not release a lease. If a client requested the release of multiple leases (by sending multiple IA options), the server will retain this particular lease and proceed with other releases as usual. The argument holds the client and transaction identification information.

14.77 DHCP6_HOOK_LEASE6_RELEASE_PD_SKIP

%1: prefix lease was not released because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on lease6_release hook point set the next step to SKIP value. For this particular hook point, that setting by a callout instructs the server to not release a lease. If client requested release of multiple leases (by sending multiple IA options), the server will retain this particular lease and will proceed with other renewals as usual. The argument holds the client and transaction identification information.

14.78 DHCP6_HOOK_LEASES6_COMMITTED_DROP

%1: packet is dropped, because a callout set the next step to DROP

Logged at debug log level 15. This debug message is printed when a callout installed on the leases6_committed hook point sets the next step to DROP.

14.79 DHCP6_HOOK_LEASES6_COMMITTED_PARK

%1: packet is parked, because a callout set the next step to PARK

Logged at debug log level 40. This debug message is printed when a callout installed on the leases6_committed hook point sets the next step to PARK.

14.80 DHCP6_HOOK_LEASES6_PARKING_LOT_FULL

The parked-packet-limit %1, has been reached, dropping query: %2

Logged at debug log level 15. This debug message occurs when the parking lot used to hold client queries while the hook library work for them completes has reached or exceeded the limit set by the parked-packet-limit global parameter. This can occur when kea-dhcp6 is using hook libraries (e.g. HA) that implement the "leases6-committed" callout and client queries are arriving faster than those callouts can fulfill them.

14.81 DHCP6_HOOK_PACKET_RCVD_SKIP

%1: packet is dropped, because a callout set the next step to SKIP

Logged at debug log level 40. This debug message is printed when a callout installed on the pkt6_receive hook point sets the next step to SKIP. For this particular hook point, the value setting instructs the server to drop the packet.

14.82 DHCP6_HOOK_PACKET_SEND_DROP

%1: prepared DHCPv6 response was not sent because a callout set the next step to DROP

Logged at debug log level 15. This debug message is printed when a callout installed on the pkt6_send hook point set the next step to DROP. For this particular hook point, the setting of the value by a callout instructs the server to drop the packet. This effectively means that the client will not get any response, even though the server processed client's request and acted on it (e.g. possibly allocated a lease). The argument specifies the client and transaction identification information.

14.83 DHCP6_HOOK_PACKET_SEND_SKIP

```
%1: prepared DHCPv6 response is not built because a callout set the next step to SKIP
```

Logged at debug log level 40. This debug message is printed when a callout installed on the `pkt6_send` hook point set the next step to `SKIP`. For this particular hook point, the setting of the value by a callout instructs the server to not build the wire data (pack) because it was already done by the book. The argument specifies the client and transaction identification information.

14.84 DHCP6_HOOK_SUBNET6_SELECT_DROP

```
%1: packet was dropped because a callout set the drop flag
```

Logged at debug log level 40. This debug message is printed when a callout installed on the `subnet6_select` hook point set the drop flag. For this particular hook point, the setting of the flag instructs the server to drop the received packet. The argument holds the client and transaction identification information.

14.85 DHCP6_HOOK_SUBNET6_SELECT_PARK

```
%1: packet was parked
```

Logged at debug log level 40. This debug message is printed when a callout installed on the `subnet6_select` hook point set the park flag. The argument holds the client and transaction identification information.

14.86 DHCP6_HOOK_SUBNET6_SELECT_SKIP

```
%1: no subnet was selected because a callout set the next step to SKIP
```

Logged at debug log level 40. This debug message is printed when a callout installed on the `subnet6_select` hook point set the next step to `SKIP` value. For this particular hook point, the setting of this value instructs the server not to choose a subnet, an action that severely limits further processing; the server will be only able to offer global options - no addresses or prefixes will be assigned. The argument holds the client and transaction identification information.

14.87 DHCP6_INIT_FAIL

```
failed to initialize Kea server: %1
```

The server has failed to establish communication with the rest of Kea, failed to read JSON configuration file or encountered any other critical issue that prevents it from starting up properly. Attached error message provides more details about the issue.

14.88 DHCP6_LEASE_ADVERT

```
%1: lease for address %2 and iaid=%3 will be advertised
```

Logged at debug log level 50. This informational message indicates that the server will advertise an address to the client in the `ADVERTISE` message. The client will request allocation of this address with the `REQUEST` message sent in the next message exchange. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and `IAID`.

14.89 DHCP6_LEASE_ADVERT_FAIL

```
%1: failed to advertise an address lease for iaid=%2
```

Logged at debug log level 50. This message indicates that in response to a received SOLICIT, the server failed to advertise a non-temporary lease for a given client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

14.90 DHCP6_LEASE_ALLOC

```
%1: lease for address %2 and iaid=%3 has been allocated for %4 seconds
```

Logged at debug log level 50. This informational message indicates that in response to a client's REQUEST message, the server successfully granted a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address, IAID and validity lifetime.

14.91 DHCP6_LEASE_ALLOC_FAIL

```
%1: failed to grant an address lease for iaid=%2
```

Logged at debug log level 50. This message indicates that in response to a received REQUEST, the server failed to grant a non-temporary address lease for the client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

14.92 DHCP6_LEASE_DATA

```
%1: detailed lease information for iaid=%2: %3
```

Logged at debug log level 55. This debug message is used to print the detailed information about the allocated lease or a lease which will be advertised to the client. The first argument holds the client and the transaction identification information. The second argument holds the IAID. The third argument holds the detailed lease information.

14.93 DHCP6_LEASE_NA_WITHOUT_DUID

```
%1: address lease for address %2 does not have a DUID
```

This error message indicates a database consistency problem. The lease database has an entry indicating that the given address is in use, but the lease does not contain any client identification. This is most likely due to a software error: please raise a bug report. As a temporary workaround, manually remove the lease entry from the database. The first argument includes the client and transaction identification information. The second argument holds the address to be released.

14.94 DHCP6_LEASE_PD_WITHOUT_DUID

```
%1: lease for prefix %2/%3 does not have a DUID
```

This error message indicates a database consistency failure. The lease database has an entry indicating that the given prefix is in use, but the lease does not contain any client identification. This is most likely due to a software error: please raise a bug report. As a temporary workaround, manually remove the lease entry from the database. The first

argument includes client and transaction identification information. The second and third argument hold the prefix and the prefix length.

14.95 DHCP6_LEASE_QUERY_ERROR_GETTING_RELAY_INFO

```
failed to get relay information for lease: %1, reason: %2
```

This is warning message that indicates the server was unable to use the relay information stored in the lease's user-context to construct the lq-relay-data option for the DHCPV6_LEASEQUERY_REPLY. The server will still send the reply with to the requester but without the lq-relay-data option. The most likely cause for this would be either a corrupted lease file or a programmatic error and it should be reported. The first argument is the lease detail, the second argument is the specific error.

14.96 DHCP6_LEASE_QUERY_PACKET_PACK

```
%1: preparing on-wire format of the packet to be sent
```

This debug message is issued when the server starts preparing the on-wire format of the packet to be sent back to the client. The argument specifies the client and the transaction identification information.

14.97 DHCP6_LEASE_QUERY_PACKET_PACK_FAILED

```
%1: preparing on-wire-format of the packet to be sent failed %2
```

This error message is issued when preparing an on-wire format of the packet has failed. The first argument identifies the client and the

14.98 DHCP6_LEASE_QUERY_PACKET_UNPACK_FAILED

```
failed to parse query from %1 to %2, received over interface %3, reason: %4
```

Logged at debug log level 40. This debug message is issued when the received DHCPV6_LEASEQUERY is malformed and can't be parsed by the buffer6_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

14.99 DHCP6_LEASE_QUERY_PREFIX_LENGTH_LIST

```
the list of prefix lengths to use when searching will be: %1
```

Logged at debug log level 40. This debug message is emitted after a (re)configuration event to display the list of delegated prefix lengths that will be used when searching for a delegated prefix to which the query address belongs. The argument is the list of prefix lengths in the order they will be used during searches.

14.100 DHCP6_LEASE_QUERY_PROCESS_FAILED

```
processing failed for lease query: %1, reason: %2
```

Logged at debug log level 40. This error message is issued when the server encountered an error processing a DHCPV6_LEASEQUERY. The first argument provides query details, the second an explanation of the error.

14.101 DHCP6_LEASE_QUERY_RECEIVED

```
received query: %1
```

Logged at debug log level 40. This debug message is printed when the DHCPV6_LEASEQUERY query has been received.

14.102 DHCP6_LEASE_QUERY_REPLY_SEND_FAILED

```
unable to send response: %1, iface: %2, address %3:%4 error: %5
```

This error message is issued when the server was unable to send a lease query reply back to the requester. The first argument provides query details, followed by the output interface, IP address and port, and finally the error itself.

14.103 DHCP6_LEASE_QUERY_REPLY_SENT

```
response: %1, sent to %2:%3
```

Logged at debug log level 40. This debug message is printed when a response to a DHCPV6_LEASEQUERY has been sent to a requester. The first argument provides response details, the second and third arguments are the IP address and port to which the response was sent.

14.104 DHCP6_LEASE_RENEW

```
%1: lease for address %2 and iaid=%3 has been allocated
```

This informational message indicates that in response to a client's REQUEST message, the server successfully renewed a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address and IAID.

14.105 DHCP6_LEASE_REUSE

```
%1: lease for address %2 and iaid=%3 has been reused for %4 seconds
```

This informational message indicates that in response to a client's message, the server successfully reused a non-temporary address lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated address, IAID and validity lifetime.

14.106 DHCP6_MULTI_THREADING_INFO

```
enabled: %1, number of threads: %2, queue size: %3
```

This is a message listing some information about the multi-threading parameters with which the server is running.

14.107 DHCP6_NOT_RUNNING

```
IPv6 DHCP server is not running
```

A warning message is issued when an attempt is made to shut down the IPv6 DHCP server but it is not running.

14.108 DHCP6_NO_INTERFACES

failed to detect any network interfaces

During startup the IPv6 DHCP server failed to detect any network interfaces and is therefore shutting down.

14.109 DHCP6_OPEN_SOCKET

opening service sockets on port %1

Logged at debug log level 0. This debug message is issued during startup, this indicates that the IPv6 DHCP server is about to open sockets on the specified port.

14.110 DHCP6_OPEN_SOCKETS_FAILED

maximum number of open service sockets attempts: %1, has been exhausted without success

This error indicates that the server failed to bind service sockets after making the maximum configured number of open attempts.

14.111 DHCP6_OPEN_SOCKETS_NO_RECONNECT_CTL

unexpected error in bind service sockets.

This is an error message indicating a programmatic error that should not occur. It prohibits the server from attempting to bind to its service sockets if they are unavailable, and the server exits. This error should be reported.

14.112 DHCP6_PACKET_DROP_DHCP_DISABLED

%1: DHCP service is globally disabled

Logged at debug log level 15. This debug message is issued when a packet is dropped because the DHCP service has been temporarily disabled. This affects all received DHCP packets. The service may be enabled by the "dhcp-enable" control command or automatically after a specified amount of time since receiving "dhcp-disable" command.

14.113 DHCP6_PACKET_DROP_DROP_CLASS

dropped as member of the special class 'DROP': %1 %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified into the special class 'DROP' and dropped. The packet details are displayed.

14.114 DHCP6_PACKET_DROP_DROP_CLASS2

dropped as member of the special class 'DROP' after host reservation lookup: %1 %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after host reservation lookup into the special class 'DROP' and dropped. The packet details are displayed.

14.115 DHCP6_PACKET_DROP_DROP_CLASS_EARLY

dropped as member of the special class 'DROP' after early global host reservations lookup: %1 %2

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified after early global host reservations lookup into the special class 'DROP' and dropped. The packet details are displayed.

14.116 DHCP6_PACKET_DROP_DUPLICATE

dropped as sent by the same client as a packet being processed by another thread: dropped %1 %2 by thread %3 as duplicate of %4 processed by thread %5

Logged at debug log level 15. Currently multi-threading processing avoids races between packets sent by the same client by dropping new packets until processing is finished. Packet details or summary, and thread identifiers are included for both packets in this warning message.

14.117 DHCP6_PACKET_DROP_PARSE_FAIL

%1: failed to parse packet from %2 to %3, received over interface %4, reason: %5, %6

Logged at debug log level 15. The DHCPv6 server has received a packet that it is unable to interpret. The reason why the packet is invalid is included in the message.

14.118 DHCP6_PACKET_DROP_SERVERID_MISMATCH

%1: dropping packet with server identifier: %2, server is using: %3

Logged at debug log level 15. A debug message noting that server has received message with server identifier option that not matching server identifier that server is using.

14.119 DHCP6_PACKET_DROP_UNICAST

%1: dropping unicast %2 packet as this packet should be sent to multicast

Logged at debug log level 15. This debug message is issued when the server drops the unicast packet, because packets of this type must be sent to multicast. The first argument specifies the client and transaction identification information, the second argument specifies packet type.

14.120 DHCP6_PACKET_OPTIONS_SKIPPED

%1: An error unpacking an option, caused subsequent options to be skipped: %2

Logged at debug log level 50. This debug message is issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the packet. The server will still attempt to service the packet.

14.121 DHCP6_PACKET_PROCESS_EXCEPTION

%1: exception occurred during packet processing

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

14.122 DHCP6_PACKET_PROCESS_EXCEPTION_MAIN

```
exception occurred during packet processing
```

This error message indicates that a non-standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

14.123 DHCP6_PACKET_PROCESS_FAIL

```
%1: processing of %2 message received from %3 failed: %4
```

Logged at debug log level 40. This is a general catch-all message indicating that the processing of the specified packet type from the indicated address failed. The reason is given in the message. The server will not send a response but will instead ignore the packet.

14.124 DHCP6_PACKET_PROCESS_STD_EXCEPTION

```
%1: exception occurred during packet processing: %2
```

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation.

14.125 DHCP6_PACKET_PROCESS_STD_EXCEPTION_MAIN

```
exception occurred during packet processing: %1
```

This error message indicates that a standard exception was raised during packet processing that was not caught by other, more specific exception handlers. This packet will be dropped and the server will continue operation. This error message may appear in main server processing loop.

14.126 DHCP6_PACKET_QUEUE_FULL

```
multi-threading packet queue is full
```

Logged at debug log level 40. A debug message noting that the multi-threading packet queue is full so the oldest packet of the queue was dropped to make room for the received one.

14.127 DHCP6_PACKET_RECEIVED

```
%1: %2 (type %3) received from %4 to %5 on interface %6
```

An INFO message noting that the server has received the specified type of packet on the specified interface. The first argument specifies the client and transaction identification information. The second and third argument specify the name of the DHCPv6 message and its numeric type respectively. The remaining arguments specify the source address, destination IP address and the name of the interface on which the message has been received.

14.128 DHCP6_PACKET_RECEIVE_FAIL

```
error on attempt to receive packet: %1
```

The IPv6 DHCP server tried to receive a packet but an error occurred during this attempt. The reason for the error is included in the message.

14.129 DHCP6_PACKET_REJECT_CLASS

```
assignment rejected as member of the special class 'REJECT': %1 %2
```

Logged at debug log level 15. This debug message is emitted when an incoming packet was classified into the special class 'REJECT' and no resource was assigned. The packet details are displayed.

14.130 DHCP6_PACKET_SEND

```
%1: trying to send packet %2 (type %3) from [%4]:%5 to [%6]:%7 on interface %8
```

An INFO message noting that the server is attempting to send the specified type of packet. The arguments specify the client identification information (HW address and client identifier), DHCP message name and type, source IPv6 address and port, destination IPv6 address and port and the interface name.

14.131 DHCP6_PACKET_SEND_FAIL

```
%1: failed to send DHCPv6 packet: %2
```

This error is output if the IPv6 DHCP server fails to send an assembled DHCP message to a client. The reason for the error is included in the message.

14.132 DHCP6_PACK_FAIL

```
%1: failed to assemble response correctly: %2
```

This error is output if the server failed to assemble the data to be returned to the client into a valid packet. The reason is most likely to be to a programming error: please raise a bug report.

14.133 DHCP6_PARSER_COMMIT_EXCEPTION

```
parser failed to commit changes
```

On receipt of message containing details to a change of the IPv6 DHCP server configuration, a set of parsers were successfully created, but one of them failed to commit its changes due to a low-level system exception being raised. Additional messages may be output indicating the reason.

14.134 DHCP6_PARSER_COMMIT_FAIL

```
parser failed to commit changes: %1
```

On receipt of message containing details to a change of the IPv6 DHCP server configuration, a set of parsers were successfully created, but one of them failed to commit its changes. The reason for the failure is given in the message.

14.135 DHCP6_PARSER_EXCEPTION

```
failed to create or run parser for configuration element %1
```

On receipt of message containing details to a change of its configuration, the IPv6 DHCP server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The message has been output in response to a non-Kea exception being raised. Additional messages may give further information. The most likely cause of this is that the specification file for the server (which

details the allowable contents of the configuration) is not correct for this version of Kea. This may be the result of an interrupted installation of an update to Kea.

14.136 DHCP6_PARSER_FAIL

```
%1: failed to create or run parser for configuration element %1: %2
```

On receipt of message containing details to a change of its configuration, the IPv6 DHCP server failed to create a parser to decode the contents of the named configuration element, or the creation succeeded but the parsing actions and committal of changes failed. The reason for the failure is given in the message.

14.137 DHCP6_PD_LEASE_ADVERT

```
%1: lease for prefix %2/%3 and iaid=%4 will be advertised
```

Logged at debug log level 50. This informational message indicates that the server will advertise a prefix to the client in the ADVERTISE message. The client will request allocation of this prefix with the REQUEST message sent in the next message exchange. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and IAID.

14.138 DHCP6_PD_LEASE_ADVERT_FAIL

```
%1: failed to advertise a prefix lease for iaid=%2
```

Logged at debug log level 50. This message indicates that in response to a received SOLICIT, the server failed to advertise a prefix lease for a given client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

14.139 DHCP6_PD_LEASE_ALLOC

```
%1: lease for prefix %2/%3 and iaid=%4 has been allocated for %5 seconds
```

Logged at debug log level 50. This informational message indicates that in response to a client's REQUEST message, the server successfully granted a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length, IAID and validity lifetime.

14.140 DHCP6_PD_LEASE_ALLOC_FAIL

```
%1: failed to grant a prefix lease for iaid=%2
```

Logged at debug log level 50. This message indicates that in response to a received REQUEST, the server failed to grant a prefix lease for the client. There may be many reasons for such failure. Each failure is logged in a separate log entry. The first argument holds the client and transaction identification information. The second argument holds the IAID.

14.141 DHCP6_PD_LEASE_RENEW

```
%1: lease for prefix %2/%3 and iaid=%4 has been allocated
```


This informational message indicates that in response to a client's REQUEST message, the server successfully renewed a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length and IAID.

14.142 DHCP6_PD_LEASE_REUSE

```
%1: lease for prefix %2/%3 and iaid=%4 has been reused for %5 seconds
```

This informational message indicates that in response to a client's message, the server successfully reused a prefix lease. This is a normal behavior and indicates successful operation. The first argument includes the client and transaction identification information. The remaining arguments hold the allocated prefix, prefix length, IAID and validity lifetime.

14.143 DHCP6_PROCESS_IA_NA_EXTEND

```
%1: extending lease lifetime for IA_NA option with iaid=%2
```

Logged at debug log level 50. This message is logged when the server is starting to extend the lifetime of the address lease associated with the particular IAID. The first argument includes the client and transaction identification information. The second argument contains the IAID.

14.144 DHCP6_PROCESS_IA_NA_RELEASE

```
%1: releasing lease for IA_NA option with iaid=%2
```

Logged at debug log level 50. This message is logged when the server is trying to release the client's as a result of receiving the RELEASE message. The first argument includes the client and transaction identification information. The second argument contains the IAID.

14.145 DHCP6_PROCESS_IA_NA_REQUEST

```
%1: server is processing IA_NA option with iaid=%2 and hint=%3
```

Logged at debug log level 50. This is a debug message that indicates the processing of a received IA_NA option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA_NA option. The third argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

14.146 DHCP6_PROCESS_IA_NA_SOLICIT

```
%1: server is processing IA_NA option with iaid=%2 and hint=%3
```

Logged at debug log level 50. This is a debug message that indicates the processing of a received IA_NA option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA_NA option. The third argument may hold the hint for the server about the address that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

14.147 DHCP6_PROCESS_IA_PD_EXTEND

```
%1: extending lease lifetime for IA_PD option with iaid=%2
```

Logged at debug log level 50. This message is logged when the server is starting to extend the lifetime of the prefix lease associated with the particular IAID. The first argument includes the client and transaction identification information. The second argument contains the IAID.

14.148 DHCP6_PROCESS_IA_PD_REQUEST

```
%1: server is processing IA_PD option with iaid=%2 and hint=%3
```

Logged at debug log level 50. This is a debug message that indicates a processing of received IA_PD option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA_PD option. The third argument may hold the hint for the server about the prefix that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

14.149 DHCP6_PROCESS_IA_PD_SOLICIT

```
%1: server is processing IA_PD option with iaid=%2 and hint=%3
```

Logged at debug log level 50. This is a debug message that indicates a processing of received IA_PD option. The first argument contains the client and the transaction identification information. The second argument holds the IAID of the IA_PD option. The third argument may hold the hint for the server about the prefix that the client would like to have allocated. If there is no hint, the argument should provide the text indicating that the hint hasn't been sent.

14.150 DHCP6_QUERY_DATA

```
%1, packet details: %2
```

Logged at debug log level 55. A debug message printing the details of the received packet. The first argument includes the client and the transaction identification information.

14.151 DHCP6_QUERY_LABEL

```
received query: %1
```

This information message indicates that a query was received. It displays the client and the transaction identification information.

14.152 DHCP6_RAPID_COMMIT

```
%1: Rapid Commit option received, following 2-way exchange
```

Logged at debug log level 50. This debug message is issued when the server found a Rapid Commit option in the client's message and 2-way exchanges are supported by the server for the subnet on which the client is connected. The argument specifies the client and transaction identification information.

14.153 DHCP6_RECLAIM_EXPIRED_LEASES_FAIL

```
failed to reclaim expired leases: %1
```

This error message indicates that the reclaim expired leases operation failed and provides the cause of failure.

14.154 DHCP6_RECLAIM_EXPIRED_LEASES_SKIPPED

```
dhcp6 service is currently disabled. Try again in %1 seconds.
```

Logged at debug log level 40. This debug message is emitted when lease reclamation was scheduled to begin but skipped because DHCPv6 service was disabled. Reclamation will continue to be scheduled according to the configured value of reclaim-timer-wait-time.

14.155 DHCP6_REGISTERED_LEASE_ADD_FAIL

```
error in registered lease add for %1
```

This error message indicates that the registered lease add failed and provides the address being registered.

14.156 DHCP6_REGISTERED_LEASE_UPDATE_FAIL

```
error in registered lease update for %1: %2
```

This error message indicates that the registered lease update failed and provides the registered address and the cause of failure.

14.157 DHCP6_RELEASE_NA

```
%1: binding for address %2 and iaid=%3 was released properly
```

This informational message indicates that an address was released properly. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second and third argument hold the released IPv6 address and IAID respectively.

14.158 DHCP6_RELEASE_NA_DELETED

```
%1: binding for address %2 and iaid=%3 was deleted on release
```

This informational message indicates that an address was deleted on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second and third argument hold the released IPv6 address and IAID respectively.

14.159 DHCP6_RELEASE_NA_EXPIRED

```
%1: binding for address %2 and iaid=%3 expired on release
```

This informational message indicates that an address expired on release. It is a normal operation during client shutdown. The first argument includes the client and transaction identification information. The second and third argument hold the released IPv6 address and IAID respectively.

14.160 DHCP6_RELEASE_NA_FAIL

```
%1: failed to remove address lease for address %2 and iaid=%3
```

This error message indicates that the software failed to remove an address lease from the lease database. It probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually

removed from the database during RELEASE message processing. The first argument holds the client and transaction identification information. The second and third argument hold the released address and IAID respectively.

14.161 DHCP6_RELEASE_NA_FAIL_NOT_ASSIGNED

%1: client tried to release address %2 which is not assigned

Logged at debug log level 40. This debug message is issued when a client is trying to release an address for which there is no lease or the lease is not in default / assigned state (e.g. kept for the client by the lease affinity feature in the released state). The first argument includes the client and the transaction identification information. The second argument specifies the address.

14.162 DHCP6_RELEASE_NA_FAIL_WRONG_DUID

%1: client tried to release address %2, but it belongs to another client using duid=%3

This warning message indicates that a client tried to release an address that belongs to a different client. This should not happen in normal circumstances and may indicate a misconfiguration of the client. However, since the client releasing the address will stop using it anyway, there is a good chance that the situation will correct itself.

14.163 DHCP6_RELEASE_NA_FAIL_WRONG_IAID

%1: client tried to release address %2, but it used wrong IAID (expected %3, but got %4)

This warning message indicates that client tried to release an address that does belong to it, but the address was expected to be in a different IA (identity association) container. This probably means that the client's support for multiple addresses is flawed.

14.164 DHCP6_RELEASE_PD

%1: prefix %2/%3 for iaid=%4 was released properly

This informational message indicates that a prefix was released properly. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument hold the prefix and its length. The fourth argument holds IAID.

14.165 DHCP6_RELEASE_PD_DELETED

%1: prefix %2/%3 for iaid=%4 was deleted on release

This informational message indicates that a prefix was deleted on release. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument hold the prefix and its length. The fourth argument holds IAID.

14.166 DHCP6_RELEASE_PD_EXPIRED

%1: prefix %2/%3 for iaid=%4 expired on release

This informational message indicates that a prefix expired on release. It is a normal operation during client shutdown. The first argument holds the client and transaction identification information. The second and third argument hold the prefix and its length. The fourth argument holds IAID.

14.167 DHCP6_RELEASE_PD_FAIL

```
%1: failed to release prefix %2/%3 for iaid=%4
```

This error message indicates that the software failed to remove a prefix lease from the lease database. It probably due to an error during a database operation: resolution will most likely require administrator intervention (e.g. check if DHCP process has sufficient privileges to update the database). It may also be triggered if a lease was manually removed from the database during RELEASE message processing. The first argument hold the client and transaction identification information. The second and third argument define the prefix and its length. The fourth argument holds the IAID.

14.168 DHCP6_RELEASE_PD_FAIL_NOT_ASSIGNED

```
%1: client tried to release prefix %2/%3 which is not assigned
```

Logged at debug log level 40. This debug message is issued when a client is trying to release a prefix for which there is no lease or the lease is not in default / assigned state (e.g. kept for the client by the lease affinity feature in the released state). The first argument includes the client and the transaction identification information. The second and third arguments specify the prefix.

14.169 DHCP6_RELEASE_PD_FAIL_WRONG_DUID

```
%1: client tried to release prefix %2/%3, but it belongs to another client (duid=%4)
```

This warning message indicates that client tried to release a prefix that belongs to a different client. This should not happen in normal circumstances and may indicate a misconfiguration of the client. However, since the client releasing the prefix will stop using it anyway, there is a good chance that the situation will correct itself. The first argument includes the client and the transaction identification information. The second and third argument include the prefix and prefix length. The last argument holds the DUID of the client holding the lease.

14.170 DHCP6_RELEASE_PD_FAIL_WRONG_IAID

```
%1: client tried to release prefix %2/%3, but it used wrong IAID (expected %4, but got %5)
```

This warning message indicates that client tried to release a prefix that does belong to it, but the address was expected to be in a different IA (identity association) container. This probably means that the client's support for multiple prefixes is flawed. The first argument includes the client and transaction identification information. The second and third argument identify the prefix. The fourth and fifth argument hold the expected IAID and IAID found respectively.

14.171 DHCP6_REQUIRED_OPTIONS_CHECK_FAIL

```
%1: %2 message received from %3 failed the following check: %4
```

Logged at debug log level 40. This message indicates that received DHCPv6 packet is invalid. This may be due to a number of reasons, e.g. the mandatory client-id option is missing, the server-id forbidden in that particular type of message is present, there is more than one instance of client-id or server-id present, etc. The exact reason for rejecting the packet is included in the message.

14.172 DHCP6_RESERVATIONS_LOOKUP_FIRST_ENABLED

```
Multi-threading is enabled and host reservations lookup is always performed first.
```

This is a message informing that host reservations lookup is performed before lease lookup when multi-threading is enabled overwriting configured value.

14.173 DHCP6_RESPONSE_DATA

```
%1: responding with packet %2 (type %3), packet details: %4
```

Logged at debug log level 55. A debug message including the detailed data about the packet being sent to the client. The first argument contains the client and the transaction identification information. The second and third argument contains the packet name and type respectively. The fourth argument contains detailed packet information.

14.174 DHCP6_ROOT_USER_SECURITY_WARNING

```
kea-dhcp6 running as root user!
```

This warning is emitted when kea-dhcp6 is running as a root user. While the server will function fully, this mode of operation may expose your environment to security vulnerabilities and should only be used after careful consideration

14.175 DHCP6_SECURITY_CHECKS_DISABLED

```
Invoked with command line option -X, Security checks are disabled!!
```

This warning is emitted when internal security checks normally performed by kea-dhcp6 have been disabled via command line option '-X'. This means the server is not enforcing restrictions on resource paths or permissions. This mode of operation may expose your environment to security vulnerabilities and should only be used after careful consideration.

14.176 DHCP6_SERVER_FAILED

```
server failed: %1
```

The IPv6 DHCP server has encountered a fatal error and is terminating. The reason for the failure is included in the message.

14.177 DHCP6_SHUTDOWN

```
server shutdown
```

Logged at debug log level 40. The IPv6 DHCP server has terminated normally.

14.178 DHCP6_SHUTDOWN_REQUEST

```
shutdown of server requested
```

Logged at debug log level 40. This debug message indicates that a shutdown of the IPv6 server has been requested via a call to the 'shutdown' method of the core Dhcpv6Srv object.

14.179 DHCP6_SRV_CONSTRUCT_ERROR

```
error creating Dhcpv6Srv object, reason: %1
```

This error message indicates that during startup, the construction of a core component within the IPv6 DHCP server (the Dhcpv6 server object) has failed. As a result, the server will exit. The reason for the failure is given within the message.

14.180 DHCP6_SRV_D2STOP_ERROR

```
error stopping IO with DHCP_DDNS during shutdown: %1
```

This error message indicates that during shutdown, an error occurred while stopping IO between the DHCPv6 server and the DHCP_DDNS server. This is probably due to a programmatic error is not likely to impact either server upon restart. The reason for the failure is given within the message.

14.181 DHCP6_SRV_UNLOAD_LIBRARIES_ERROR

```
error unloading hooks libraries during shutdown: %1
```

This error message indicates that during shutdown, unloading hooks libraries failed to close them. If the list of libraries is empty it is a programmatic error in the server code. If it is not empty it could be a programmatic error in one of the hooks libraries which could lead to a crash during finalization.

14.182 DHCP6_STARTED

```
Kea DHCPv6 server version %1 started
```

This informational message indicates that the IPv6 DHCP server has processed all configuration information and is ready to process DHCPv6 packets. The version is also printed.

14.183 DHCP6_STARTING

```
Kea DHCPv6 server version %1 (%2) starting
```

This informational message indicates that the IPv6 DHCP server has processed any command-line switches and is starting. The version is also printed.

14.184 DHCP6_START_INFO

```
pid: %1, server port: %2, client port: %3, verbose: %4
```

Logged at debug log level 0. This is a debug message issued during the IPv6 DHCP server startup. It lists some information about the parameters with which the server is running.

14.185 DHCP6_SUBNET_DATA

```
%1: the selected subnet details: %2
```

Logged at debug log level 55. This debug message includes the details of the subnet selected for the client. The first argument includes the client and the transaction identification information. The second argument includes the subnet details.

14.186 DHCP6_SUBNET_DYNAMICALLY_CHANGED

```
%1: changed selected subnet %2 to subnet %3 from shared network %4 for client assignments
```

Logged at debug log level 45. This debug message indicates that the server is using another subnet than initially selected for client assignments. This newly selected subnet belongs to the same shared network as the original subnet. Some reasons why the new subnet was selected include: address pool exhaustion in the original subnet or the fact that the new subnet includes some static reservations for this client.

14.187 DHCP6_SUBNET_SELECTED

%1: the subnet with ID %2 was selected for client assignments

Logged at debug log level 45. This is a debug message noting the selection of a subnet to be used for address and option assignment. Subnet selection is one of the early steps in the processing of incoming client message. The first argument includes the client and the transaction identification information. The second argument holds the selected subnet id.

14.188 DHCP6_SUBNET_SELECTION_FAILED

%1: failed to select subnet for the client

Logged at debug log level 50. This debug message indicates that the server failed to select the subnet for the client which has sent a message to the server. The cause is likely due to a misconfiguration of the server. The packet processing will continue, but the response will only contain generic configuration and no addresses or prefixes. The argument includes the client and the transaction identification information.

14.189 DHCP6_UNKNOWN_MSG_RECEIVED

%1: received unknown message (type %2) on interface %3

Logged at debug log level 40. This debug message is printed when server receives a message of unknown type. That could either mean missing functionality or invalid or broken relay or client. The list of formally defined message types is available here: <http://www.iana.org/assignments/dhcpv6-parameters>.

14.190 DHCP6_USING_SERVERID

server is using server-id %1 and stores in the file %2

This info message is logged when the server reads its server-id from a file or generates it. This message is a notification to the administrator what server-id will be used and where it is persisted. Typically, there is no need to modify the server id. However, it is possible to do it in the Kea configuration file. It is important to understand the implications of such modification. The clients will remember previous server-id, and will use it to extend their leases. As a result, they will have to go through a rebinding phase to re-acquire their leases and associate them with a new server id.

DHCPDPSRV

15.1 DHCPDPSRV_CFGMGR_ADD_IFACE

listening on interface %1

An info message issued when a new interface is being added to the collection of interfaces on which the server listens to DHCP messages.

15.2 DHCPDPSRV_CFGMGR_ADD_SUBNET4

adding subnet %1

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is adding the specified IPv4 subnet to its database.

15.3 DHCPDPSRV_CFGMGR_ADD_SUBNET6

adding subnet %1

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is adding the specified IPv6 subnet to its database.

15.4 DHCPDPSRV_CFGMGR_ALL_IFACES_ACTIVE

enabling listening on all interfaces

Logged at debug log level 40. This debug message is issued when the server is being configured to listen on all interfaces.

15.5 DHCPDPSRV_CFGMGR_CFG_DHCP_DDNS

Setting DHCP-DDNS configuration to: %1

Logged at debug log level 40. This debug message is issued when the server's DHCP-DDNS settings are changed.

15.6 DHCPDPSRV_CFGMGR_CONFIG4_MERGED

Configuration backend data has been merged.

This is an informational message emitted when the DHCPv4 server has successfully merged configuration data retrieved from its configuration backends into the current configuration.

15.7 DHCPDRV_CFGMGR_CONFIG6_MERGED

```
Configuration backend data has been merged.
```

This is an informational message emitted when the DHCPv6 server has successfully merged configuration data retrieved from its configuration backends into the current configuration.

15.8 DHCPDRV_CFGMGR_CONFIGURE_SERVERID

```
server configuration includes specification of a server identifier
```

This warning message is issued when the server specified configuration of a server identifier. If this new configuration overrides an existing server identifier, this will affect existing bindings of the clients. Clients will use old server identifier when they renew their bindings. The server will not respond to those renews, and the clients will eventually transition to rebinding state. The server should reassign existing bindings and the clients will subsequently use new server identifier. It is recommended to not modify the server identifier, unless there is a good reason for it, to avoid increased number of renewals and a need for rebinding (increase of multicast traffic, which may be received by multiple servers).

15.9 DHCPDRV_CFGMGR_DEL_SUBNET4

```
IPv4 subnet %1 removed
```

Logged at debug log level 40. This debug message is issued when a subnet is successfully removed from the server configuration. The argument identifies the removed subnet.

15.10 DHCPDRV_CFGMGR_DEL_SUBNET6

```
IPv6 subnet %1 removed
```

Logged at debug log level 40. This debug message is issued when a subnet is successfully removed from the server configuration. The argument identifies the removed subnet.

15.11 DHCPDRV_CFGMGR_FLQ_POPULATE_FREE_ADDRESS_LEASES

```
populating free address leases for the FLQ allocator in subnet %1; it can take a while!
```

This informational message is issued when the server begins building a queue of free address leases for the given subnet. It can take a considerable amount of time, depending on the size of the address pools.

15.12 DHCPDRV_CFGMGR_FLQ_POPULATE_FREE_ADDRESS_LEASES_DONE

```
populated %1 free address leases for the FLQ allocator in subnet %2 in %3
```

This informational message is issued when the server ends building a queue of free address leases for a given subnet. The first argument logs the number of free leases, the second argument logs the subnet, and the third argument logs a duration.

15.13 DHCPDRV_CFGMGR_FLQ_POPULATE_FREE_PREFIX_LEASES

```
populating free prefix leases for the FLQ allocator in subnet %1; it can take a while!
```

This informational message is issued when the server begins building a queue of free leases for the given subnet. It can take a considerable amount of time, depending on the size of the delegated prefix pools.

15.14 DHCPDRV_CFGMGR_FLQ_POPULATE_FREE_PREFIX_LEASES_DONE

```
populated %1 free prefix leases for the FLQ allocator in subnet %2 completed in %3
```

This informational message is issued when the server ends building a queue of free prefix leases for a given subnet. The first argument logs the number of free leases, the second argument logs the subnet, and the third argument logs a duration.

15.15 DHCPDRV_CFGMGR_IPV4_RESERVATIONS_NON_UNIQUE_IGNORED

```
ignoring "ip-reservations-unique" setting because at least one of the host database backends does not support non-unique IP reservations in a subnet
```

This warning message is issued when the server failed to use the new setting of the ip-reservations-unique global parameter configured via the configuration backend. Some host database backends used apparently do not support specifying several reservations for the same IP address in a subnet. The administrator should either stop using the backend that does not support this setting or set the value of the ip-reservations-unique to true to resolve the configuration issue.

15.16 DHCPDRV_CFGMGR_IPV6_RESERVATIONS_NON_UNIQUE_IGNORED

```
ignoring "ip-reservations-unique" setting because at least one of the host database backends does not support non unique IP reservations in a subnet
```

This warning message is issued when the server failed to use the new setting of the ip-reservations-unique global parameter configured via the configuration backend. Some host database backends used apparently do not support specifying several reservations for the same IP address or delegated prefix in a subnet. The administrator should either stop using the backend that does not support this setting or set the value of the ip-reservations-unique to true to resolve the configuration issue.

15.17 DHCPDRV_CFGMGR_IP_RESERVATIONS_UNIQUE_DUPLICATES_DETECTED

```
the "ip-reservations-unique" flag is set to true and multiple reservations for the IP address %1 in subnet %2 are not allowed causing error: %3
```

This warning message is issued when the DHCP server is configured to not allow multiple reservations for the same IP address. However, the host database backend contains multiple reservations for the IP address logged as the first argument, in the subnet logged as second argument, causing problems with lease allocation logged as third argument.

15.18 DHCPDRV_CFGMGR_IP_RESERVATIONS_UNIQUE_DUPLICATES_POSSIBLE

```
setting "ip-reservations-unique" from false to true poses a risk that some host backends may still contain multiple reservations for the same IP address
```

This warning message is issued when the DHCP server is configured to not allow multiple reservations for the same IP address. However, the host database backends may still contain multiple reservations for the same IP addresses causing problems with lease allocation for certain addresses. Please ensure that all such duplicates are removed.

15.19 DHCPDRV_CFGMGR_NEW_SUBNET4

```
a new subnet has been added to configuration: %1
```

This is an informational message reporting that the configuration has been extended to include the specified IPv4 subnet.

15.20 DHCPDRV_CFGMGR_NEW_SUBNET6

```
a new subnet has been added to configuration: %1
```

This is an informational message reporting that the configuration has been extended to include the specified subnet.

15.21 DHCPDRV_CFGMGR_OPTION_DEFINITION_MISMATCH

```
failed to create option: %1
```

This warning message is issued when an option has been specified for which there is no suitable option definition. Either there is no definition at all or the option contents do not fit the option definition. The argument will provide a detailed reason for the failure. The server will continue to operate but it will exclude the option from packet processing until the situation is corrected. This is considered a configuration error.

15.22 DHCPDRV_CFGMGR_OPTION_DUPLICATE

```
multiple options with the code: %1 added to the subnet: %2
```

This warning message is issued on an attempt to configure multiple options with the same option code for the particular subnet. Adding multiple options is uncommon for DHCPv6, but it is not prohibited.

15.23 DHCPDRV_CFGMGR_RENEW_GTR_REBIND

```
in %1, the value of renew-timer %2 is greater than the value of rebind-timer %3, ignoring renew-timer
```

A warning message that indicates the configured renew-timer is greater than the configured rebind-timer. The server will ignore the renew timer value and send the rebind timer value only. This is considered a non-fatal configuration error.

15.24 DHCPDRV_CFGMGR_SOCKET_RAW_UNSUPPORTED

```
use of raw sockets is unsupported on this OS, UDP sockets will be used
```

This warning message is logged when the user specified that the DHCPv4 server should use the raw sockets to receive the DHCP messages and respond to the clients, but the use of raw sockets is not supported on the particular environment. The raw sockets are useful when the server must respond to the directly connected clients which don't have an address yet. If the raw sockets are not supported by Kea on the particular platform, Kea will fall back to use of the IP/UDP sockets. The responses to the directly connected clients will be broadcast. The responses to relayed clients will be unicast as usual.

15.25 DHCPDRV_CFGMGR_SOCKET_TYPE_DEFAULT

```
"dhcp-socket-type" not specified , using default socket type %1
```

This informational message is logged when the administrator hasn't specified the "dhcp-socket-type" parameter in configuration for interfaces. In such case, the default socket type will be used.

15.26 DHCPDRV_CFGMGR_SOCKET_TYPE_SELECT

```
using socket type %1
```

This informational message is logged when the DHCPv4 server selects the socket type to be used for all sockets that will be opened on the interfaces. Typically, the socket type is specified by the server administrator. If the socket type hasn't been specified, the raw socket will be selected. If the raw socket has been selected but Kea doesn't support the use of raw sockets on the particular OS, it will use an UDP socket instead.

15.27 DHCPDRV_CFGMGR_SUBNET4

```
retrieved subnet %1 for address hint %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet when given the address hint specified as the address is within the subnet.

15.28 DHCPDRV_CFGMGR_SUBNET4_ADDR

```
selected subnet %1 for packet received by matching address %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet for a received packet. This particular subnet was selected, because an IPv4 address was matched which belonged to that subnet.

15.29 DHCPDRV_CFGMGR_SUBNET4_IFACE

```
selected subnet %1 for packet received over interface %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet for a packet received over the given interface. This particular subnet was selected, because it was specified as being directly reachable over the given interface. (see 'interface' parameter in the subnet4 definition).

15.30 DHCPDRV_CFGMGR_SUBNET4_RELAY

```
selected subnet %1, because of matching relay addr %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv4 subnet, because detected relay agent address matches value specified for this subnet.

15.31 DHCPDRV_CFGMGR_SUBNET6

```
retrieved subnet %1 for address hint %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet when given the address hint specified as the address is within the subnet.

15.32 DHCPDRV_CFGMGR_SUBNET6_IFACE

```
selected subnet %1 for packet received over interface %2
```

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet for a packet received over given interface. This particular subnet was selected, because it was specified as being directly reachable over given interface. (see 'interface' parameter in the subnet6 definition).

15.33 DHCPDRV_CFGMGR_SUBNET6_IFACE_ID

selected subnet %1 (interface-id match) for incoming packet

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet for a received packet. This particular subnet was selected, because value of interface-id option matched what was configured in the server's interface-id option for that selected subnet6. (see 'interface-id' parameter in the subnet6 definition).

15.34 DHCPDRV_CFGMGR_SUBNET6_RELAY

selected subnet %1, because of matching relay addr %2

Logged at debug log level 40. This is a debug message reporting that the DHCP configuration manager has returned the specified IPv6 subnet, because detected relay agent address matches value specified for this subnet.

15.35 DHCPDRV_CFGMGR_UNICAST_LINK_LOCAL

specified link local address %1 for unicast traffic on interface %2

This warning message is logged when user specified a link-local address to receive unicast traffic. The warning message is issued because it is an uncommon use.

15.36 DHCPDRV_CFGMGR_UPDATE_SUBNET4

updating subnet %1 (result %2)

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is updating the specified IPv4 subnet in its current configuration. Subnet ID and result (expected to be true) are displayed.

15.37 DHCPDRV_CFGMGR_UPDATE_SUBNET6

updating subnet %1 (result %2)

Logged at debug log level 40. A debug message reported when the DHCP configuration manager is replacing the specified IPv6 subnet in its current configuration. Subnet ID and result (expected to be true) are displayed.

15.38 DHCPDRV_CFGMGR_USE_ADDRESS

listening on address %1, on interface %2

A message issued when the server is configured to listen on the explicitly specified IP address on the given interface.

15.39 DHCPDRV_CFGMGR_USE_ALLOCATOR

using the %1 allocator for %2 leases in subnet %3

A message issued when the configuration manager starts using a given allocator for a subnet.

15.40 DHCPDRV_CFGMGR_USE_UNICAST

listening on unicast address %1, on interface %2

An info message issued when configuring the DHCP server to listen on the unicast address on the specific interface.

15.41 DHCPDRV_CLASS_BAD_NAME

class name '%1' includes problematic characters: suggest to use '%2' instead

The warning is emitted whenever a class is configured with a name which includes problematic characters. The name and an escaped proposal are displayed.

15.42 DHCPDRV_CLASS_WITH_ADDITIONAL_AND_LIFETIMES

class: %1 has 'only-in-additional-list' true while specifying one or more lease life time values. Life time values will be ignored.

This warning is emitted whenever a class is configured with 'only-in-addition-list' true as well as specifying one or more lease life time parameters (e.g. 'valid-lifetime', 'preferred-lifetime', or 'offer-lifetime'). Additional list classes are evaluated after lease assignment, thus parameters that would otherwise impact lease life times will have no affect.

15.43 DHCPDRV_CLIENT_CLASS_DEPRECATED

The parameter 'client-class' is deprecated. Use 'client-classes' list parameter instead

This warning message is emitted when configuration parsing detects the use of the deprecated 'client-class' parameter. It has been replaced by 'client-classes'. Users should migrate to the new list parameter.

15.44 DHCPDRV_CLOSE_DB

closing currently open %1 database

Logged at debug log level 40. This is a debug message, issued when the DHCP server closes the currently open lease database. It is issued at program shutdown and whenever the database access parameters are changed: in the latter case, the server closes the currently open database, and opens a database using the new parameters.

15.45 DHCPDRV_DDNS_TTL_TOO_LARGE

%1 of lease life time %2 is %3, using maximum of %4 instead.

Logged at debug log level 55. This debug message is issued when the DDNS TTL value calculated using the ddns-ttl-percent if specified or (0.33 if not) is larger than the the specified value of ddns-ttl-max. Kea will ignore the value and use the specified maximum instead. The message details include the percentage, the lease life time, the calculated TTL, and the value actually used.

15.46 DHCPDRV_DDNS_TTL_TOO_SMALL

%1 of lease life time %2 is %3, using minimum of %4 instead.

Logged at debug log level 55. This debug message is issued when the DDNS TTL value calculated using the ddns-ttl-percent if specified or (0.33 if not) is too small. Kea will ignore the value and use the minimum (ddns-ttl-min if specified or 600 seconds if not). The message details include the percentage, the lease life time, the calculated TTL, and the value actually used.

15.47 DHCP_SRV_DHCP4O6_RECEIVED_BAD_PACKET

```
received bad DHCPv4o6 packet: %1
```

A bad DHCPv4o6 packet was received.

15.48 DHCP_SRV_DHCP_DDNS_ERROR_EXCEPTION

```
error handler for DHCP_DDNS IO generated an expected exception: %1
```

This is an error message that occurs when an attempt to send a request to kea-dhcp-ddns fails there registered error handler threw an uncaught exception. This is a programmatic error which should not occur. By convention, the error handler should not propagate exceptions. Please report this error.

15.49 DHCP_SRV_DHCP_DDNS_HANDLER_NULL

```
error handler for DHCP_DDNS IO is not set.
```

This is an error message that occurs when an attempt to send a request to kea-dhcp-ddns fails and there is no registered error handler. This is a programmatic error which should never occur and should be reported.

15.50 DHCP_SRV_DHCP_DDNS_NCR_REJECTED

```
NameChangeRequest rejected by the sender: %1, ncr: %2
```

This is an error message indicating that NameChangeSender used to deliver DDNS update requests to kea-dhcp-ddns rejected the request. This most likely cause is the sender's queue has reached maximum capacity. This would imply that requests are being generated faster than they can be delivered.

15.51 DHCP_SRV_DHCP_DDNS_NCR_SENT

```
NameChangeRequest sent to kea-dhcp-ddns: %1
```

Logged at debug log level 50. This debug message is issued when a NameChangeRequest has been successfully sent to kea-dhcp-ddns.

15.52 DHCP_SRV_DHCP_DDNS_SENDER_STARTED

```
NameChangeRequest sender has been started: %1
```

An informational message issued when a communication with kea-dhcp-ddns has been successfully started.

15.53 DHCP_SRV_DHCP_DDNS_SENDER_STOPPED

```
NameChangeRequest sender has been stopped.
```

An informational message issued when a communication with kea-dhcp-ddns has been stopped. This normally occurs during reconfiguration and as part of normal shutdown. It may occur if kea-dhcp-ddns communications break down.

15.54 DHCPDRV_DHCP_DDNS_SUSPEND_UPDATES

```
DHCP_DDNS updates are being suspended.
```

This is a warning message indicating the DHCP_DDNS updates have been turned off. This should only occur if IO errors communicating with kea-dhcp-ddns have been experienced. Any such errors should have preceding entries in the log with details. No further attempts to communicate with kea-dhcp-ddns will be made without intervention.

15.55 DHCPDRV_EVAL_ERROR

```
%1: Expression '%2' evaluated to %3
```

This error message indicates that a problem was encountered while evaluating an expression of a client class. A description of the problem is printed.

15.56 DHCPDRV_EVAL_RESULT

```
%1: Expression '%2' evaluated to %3
```

Logged at debug log level 50. This debug message indicates that the expression of a client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

15.57 DHCPDRV_FORENSIC_BACKENDS_REGISTERED

```
the following forensic backend types are available: %1
```

This informational message lists all possible forensic backends that could be used in forensic logging.

15.58 DHCPDRV_FORENSIC_BACKEND_DEREGISTER

```
deregistered forensic backend type: %1
```

Logged at debug log level 40. This debug message is issued when a backend factory was deregistered. It is no longer possible to use forensic backend of this type.

15.59 DHCPDRV_FORENSIC_BACKEND_REGISTER

```
registered forensic backend type: %1
```

Logged at debug log level 40. This debug message is issued when a backend factory was successfully registered. It is now possible to use forensic backend of this type.

15.60 DHCPDRV_GENERATE_NCR4_FAILED

```
%1: generating %2 name change request failed for lease %3: %4
```

This error message is logged when generating a v4 NameChangeRequest to DHCP DDNS failed. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument specifies the leased address. The last argument provides the reason for failure.

15.61 DHCPDRV_GENERATE_NCR6_FAILED

```
%1: generating %2 name change request failed for lease %3: %4
```

This error message is logged when generating a v6 NameChangeRequest to DHCP DDNS failed. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument specifies the leased address. The last argument provides the reason for failure.

15.62 DHCPDRV_HOOK_LEASE4_RECOVER_SKIP

```
DHCPv4 lease %1 was not recovered from the declined state because a callout set the skip status.
```

Logged at debug log level 40. This debug message is printed when a callout installed on lease4_recover hook point set the next step status to SKIP. For this particular hook point, this indicates that the server should not recover the lease from declined state. The server will leave the lease as it is, in the declined state. The server will attempt to recover it the next time decline recovery procedure takes place.

15.63 DHCPDRV_HOOK_LEASE4_RENEW_SKIP

```
DHCPv4 lease was not renewed because a callout set the skip flag.
```

Logged at debug log level 40. This debug message is printed when a callout installed on lease4_renew hook point set the skip flag. For this particular hook point, the setting of the flag by a callout instructs the server to not renew a lease. The server will use existing lease as it is, without extending its lifetime.

15.64 DHCPDRV_HOOK_LEASE4_SELECT_SKIP

```
Lease4 creation was skipped, because of callout skip flag.
```

Logged at debug log level 40. This debug message is printed when a callout installed on lease4_select hook point sets the skip flag. It means that the server was told that no lease4 should be assigned. The server will not put that lease in its database and the client will get a NAK packet.

15.65 DHCPDRV_HOOK_LEASE6_EXTEND_SKIP

```
DHCPv6 lease lifetime was not extended because a callout set the skip flag for message %1
```

Logged at debug log level 40. This debug message is printed when a callout installed on lease6_renew or the lease6_rebind hook point set the skip flag. For this particular hook point, the setting of the flag by a callout instructs the server to not extend the lifetime for a lease. If the client requested renewal of multiple leases (by sending multiple IA options), the server will skip the renewal of the one in question and will proceed with other renewals as usual.

15.66 DHCPDRV_HOOK_LEASE6_RECOVER_SKIP

```
DHCPv6 lease %1 was not recovered from declined state because a callout set the skip status.
```

Logged at debug log level 40. This debug message is printed when a callout installed on lease6_recover hook point set the next step status to SKIP. For this particular hook point, this indicates that the server should not recover the lease from declined state. The server will leave the lease as it is, in the declined state. The server will attempt to recover it the next time decline recovery procedure takes place.

15.67 DHCPDRV_HOOK_LEASE6_SELECT_SKIP

```
Lease6 (non-temporary) creation was skipped, because of callout skip flag.
```

Logged at debug log level 40. This debug message is printed when a callout installed on lease6_select hook point sets the skip flag. It means that the server was told that no lease6 should be assigned. The server will not put that lease in its database and the client will get a NoAddrsAvail for that IA_NA option.

15.68 DHCPDRV_HOST_MGR_DB_OPEN_CONNECTION_WITH_RETRY_FAILED

```
Failed to connect to database: %1 with error: %2
```

This is an informational message issued when the server failed to connect to the host database. The operation started a retry to connect procedure. The database access string with password redacted is logged, along with the error and details for the reconnect procedure.

15.69 DHCPDRV_LEASE4_EXTENDED_INFO_SANITY_FAIL

```
extended info for lease %1 failed checks (%2)
```

This error message is printed when a lease extended info failed to pass sanity checks. The detail of the found problem was displayed and the extended info deleted from the lease user context.

15.70 DHCPDRV_LEASE4_EXTENDED_INFO_UPGRADED

```
extended info for lease %1 was upgraded
```

Logged at debug log level 40. This debug message is printed when a lease extended info was upgraded.

15.71 DHCPDRV_LEASE6_EXTENDED_INFO_SANITY_FAIL

```
extended info for lease %1 failed checks (%2)
```

This error message is printed when a lease extended info failed to pass sanity checks. The detail of the found problem was displayed and the extended info deleted from the lease user context.

15.72 DHCPDRV_LEASE6_EXTENDED_INFO_UPGRADED

```
extended info for lease %1 was upgraded
```

Logged at debug log level 40. This debug message is printed when a lease extended info was upgraded.

15.73 DHCPDRV_LEASE_MGR_BACKENDS_REGISTERED

```
the following lease backend types are available: %1
```

This informational message lists all possible lease backends that could be used in lease-database.

15.74 DHCPDRV_LEASE_MGR_BACKEND_DEREGISTER

```
deregistered lease backend type: %1
```

Logged at debug log level 40. This debug message is issued when a backend factory was deregistered. It is no longer possible to use lease backend of this type.

15.75 DHCPDRV_LEASE_MGR_BACKEND_REGISTER

```
registered lease backend type: %1
```

Logged at debug log level 40. This debug message is issued when a backend factory was successfully registered. It is now possible to use lease backend of this type.

15.76 DHCPDRV_LEASE_MGR_CALLBACK_EXCEPTION

```
exception occurred in a lease manager callback for callback type %1, subnet id %2, and lease %3: %4
```

This warning message is printed when one of the callback functions registered in the lease manager causes an error. The callback functions can serve different purposes and they likely log the detailed error messages. This error message possibly indicates an unhandled error. The first argument indicates a callback type. The second argument prints the subnet id. The third argument prints the lease for which the error has occurred. The last argument prints the error text.

15.77 DHCPDRV_LEASE_MGR_CALLBACK_UNKNOWN_EXCEPTION

```
unknown exception occurred in a lease manager callback for callback type %1, subnet id %2, and lease %3
```

This warning message is printed when one of the callback functions registered in the lease manager causes an unknown error. The callback functions can serve different purposes and they likely log the detailed error messages. This error message possibly indicates an unhandled error. The first argument indicates a callback type. The second argument prints the subnet id. The third argument prints the lease for which the error has occurred. This log message variant contains no error text because it is triggered by an unknown exception.

15.78 DHCPDRV_LEASE_MGR_DB_OPEN_CONNECTION_WITH_RETRY_FAILED

```
Failed to connect to database: %1 with error: %2
```

This is an informational message issued when the server failed to connect to the lease database. The operation started a retry to connect procedure. The database access string with password redacted is logged, along with the error and details for the reconnect procedure.

15.79 DHCPDRV_LEASE_SANITY_FAIL

```
The lease %1 with subnet-id %2 failed subnet-id checks (%3).
```

This warning message is printed when the lease being loaded does not match the configuration. Due to lease-checks value, the lease will be loaded, but it will most likely be unused by Kea, as there is no subnet that matches the IP address associated with the lease.

15.80 DHCPDRV_LEASE_SANITY_FAIL_DISCARD

The lease %1 with subnet-id %2 failed subnet-id checks (%3) and was dropped.

This warning message is printed when a lease was loaded, but Kea was told (by setting lease-checks parameter) to discard leases with inconsistent data. The lease was discarded, because either there is no subnet configured with matching subnet-id or the address of the lease does not belong to the subnet.

15.81 DHCPDRV_LEASE_SANITY_FIXED

The lease %1 with subnet-id %2 failed subnet-id checks, but was corrected to subnet-id %3.

This informational message is printed when a lease was loaded, but had incorrect subnet-id value. The lease-checks parameter was set to a value that told Kea to try to correct the problem. There is a matching subnet, so Kea updated subnet-id and loaded the lease successfully.

15.82 DHCPDRV_MEMFILE_ADD_ADDR4

adding IPv4 lease with address %1

Logged at debug log level 50. This debug message is issued when the server is about to add an IPv4 lease with the specified address to the memory file backend database.

15.83 DHCPDRV_MEMFILE_ADD_ADDR6

adding IPv6 lease with address %1

Logged at debug log level 50. This debug message is issued when the server is about to add an IPv6 lease with the specified address to the memory file backend database.

15.84 DHCPDRV_MEMFILE_BEGIN_BUILD_EXTENDED_INFO_TABLES6

building extended info tables with %1 sanity check level, tables %2

Logged at debug log level 40. This debug message is issued when the server is building extended info tables. The extended info sanity check level and the fact tables are enabled or disabled are displayed.

15.85 DHCPDRV_MEMFILE_BEGIN_EXTRACT_EXTENDED_INFO4

extract extended info with %1 sanity check level %2

Logged at debug log level 40. This debug message is issued when the server is extracting extended info. The extended info sanity check level and update in file when requested are displayed.

15.86 DHCPDRV_MEMFILE_BUILD_EXTENDED_INFO_TABLES6

building extended info tables saw %1 leases, extended info sanity checks modified %2 leases and %3 leases were entered into tables

Extended info tables build was finished. Some statistics are displayed, the updated in database is returned to the command interface.

15.87 DHCPDRV_MEMFILE_BUILD_EXTENDED_INFO_TABLES6_ERROR

```
building extended info tables got an exception on the lease for %1: %2
```

An error message issued when the server is building extended info tables and receives an exception processing a lease.

15.88 DHCPDRV_MEMFILE_COMMIT

```
committing to memory file database
```

Logged at debug log level 50. The code has issued a commit call. For the memory file database this is a no-op.

15.89 DHCPDRV_MEMFILE_CONVERTING_LEASE_FILES

```
running LFC now to convert lease files to the current schema: %1.%2
```

A warning message issued when the server has detected lease files that need to be either upgraded or downgraded to match the server's schema, and that the server is automatically running the LFC process to perform the conversion. This should only occur the first time the server is launched following a Kea installation upgrade (or downgrade).

15.90 DHCPDRV_MEMFILE_DB

```
opening memory file lease database: %1
```

This informational message is logged when a DHCP server (either V4 or V6) is about to open a memory file lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

15.91 DHCPDRV_MEMFILE_DELETE_ADDR4

```
deleting lease for address %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to delete a lease for the specified address from the memory file database for the specified address.

15.92 DHCPDRV_MEMFILE_DELETE_ADDR6

```
deleting lease for address %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to delete a lease for the specified address from the memory file database for the specified address.

15.93 DHCPDRV_MEMFILE_DELETE_EXPIRED_RECLAIMED4

```
deleting reclaimed IPv4 leases that expired more than %1 seconds ago
```

Logged at debug log level 50. This debug message is issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

15.94 DHCPDRV_MEMFILE_DELETE_EXPIRED_RECLAIMED6

```
deleting reclaimed IPv6 leases that expired more than %1 seconds ago
```

Logged at debug log level 50. This debug message is issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

15.95 DHCPDRV_MEMFILE_DELETE_EXPIRED_RECLAIMED_START

```
starting deletion of %1 expired-reclaimed leases
```

Logged at debug log level 50. This debug message is issued when the server has found expired-reclaimed leases to be removed. The number of leases to be removed is logged in the message.

15.96 DHCPDRV_MEMFILE_EXTRACT_EXTENDED_INFO4

```
extracting extended info saw %1 leases, extended info sanity checks modified %2 / updated %3 leases and %4 leases have relay or remote id
```

Logged at debug log level 40. Extended info extraction was finished. Some statistics are displayed, the updated in database is returned to the command interface.

15.97 DHCPDRV_MEMFILE_EXTRACT_EXTENDED_INFO4_ERROR

```
extracting extended info got an exception on the lease for %1: %2
```

Logged at debug log level 40. This debug message is issued when the server is extracting extended info and receives an exception processing a lease.

15.98 DHCPDRV_MEMFILE_FAILED_TO_OPEN

```
Could not open lease file: %1
```

This error is issued when the lease file could not be opened. The argument contains the details. The most likely cause is that the *name* parameter for memfile back end contains a path other than the supported path. The argument will contain the details. The path component may simply be omitted. To override the default supported path, set the environment variable KEA_DHCP_DATA_DIR prior to starting the server.

15.99 DHCPDRV_MEMFILE_GET4

```
obtaining all IPv4 leases
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv4 leases from the memory file database.

15.100 DHCPDRV_MEMFILE_GET6

```
obtaining all IPv6 leases
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv6 leases from the memory file database.

15.101 DHCPDRV_MEMFILE_GET6_DUID

obtaining IPv6 leases for DUID %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain IPv6 leases from the memory file database for the DUID.

15.102 DHCPDRV_MEMFILE_GET_ADDR4

obtaining IPv4 lease for address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv4 lease from the memory file database for the specified address.

15.103 DHCPDRV_MEMFILE_GET_ADDR6

obtaining IPv6 lease for address %1 and lease type %2

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv6 lease from the memory file database for the specified address.

15.104 DHCPDRV_MEMFILE_GET_CLIENTID

obtaining IPv4 leases for client ID %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified client identification.

15.105 DHCPDRV_MEMFILE_GET_EXPIRED4

obtaining maximum %1 of expired IPv4 leases

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

15.106 DHCPDRV_MEMFILE_GET_EXPIRED6

obtaining maximum %1 of expired IPv6 leases

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

15.107 DHCPDRV_MEMFILE_GET_HOSTNAME4

obtaining IPv4 leases for hostname %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified hostname.

15.108 DHCPDRV_MEMFILE_GET_HOSTNAME6

```
obtaining IPv6 leases for hostname %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the memory file database for a client with the specified hostname.

15.109 DHCPDRV_MEMFILE_GET_HWADDR4

```
obtaining IPv4 leases for hardware address %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the memory file database for a client with the specified hardware address.

15.110 DHCPDRV_MEMFILE_GET_HWADDR6

```
obtaining IPv6 leases for hardware address %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the memory file database for a client with the specified hardware address.

15.111 DHCPDRV_MEMFILE_GET_IAID_DUID

```
obtaining IPv6 leases for IAID %1 and DUID %2 and lease type %3
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the memory file database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

15.112 DHCPDRV_MEMFILE_GET_IAID_SUBID_DUID

```
obtaining IPv6 leases for IAID %1, Subnet ID %2, DUID %3 and lease type %4
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv6 lease from the memory file database for a client with the specified IAID (Identity Association ID), Subnet ID and DUID (DHCP Unique Identifier).

15.113 DHCPDRV_MEMFILE_GET_PAGE4

```
obtaining at most %1 IPv4 leases starting from address %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of leases beginning with the specified address.

15.114 DHCPDRV_MEMFILE_GET_PAGE6

```
obtaining at most %1 IPv6 leases starting from address %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of leases beginning with the specified address.

15.115 DHCPDRV_MEMFILE_GET_RELAYID4

obtaining at most %1 IPv4 leases starting from address %2 with relay id %3 and cltt between %4 and %5

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a relay id and client transaction time between start and end dates.

15.116 DHCPDRV_MEMFILE_GET_RELAYID6

obtaining at most %1 IPv6 leases starting from address %2 with relay id %3

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a relay id.

15.117 DHCPDRV_MEMFILE_GET_REMOTEID4

obtaining at most %1 IPv4 leases starting from address %2 with remote id %3 and cltt between %4 and %5

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a remote id and client transaction time between start and end dates.

15.118 DHCPDRV_MEMFILE_GET_REMOTEID6

obtaining at most %1 IPv6 leases starting from address %2 with remote id %3

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a remote id.

15.119 DHCPDRV_MEMFILE_GET_SUBID4

obtaining IPv4 leases for subnet ID %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the memory file database.

15.120 DHCPDRV_MEMFILE_GET_SUBID6

obtaining IPv6 leases for subnet ID %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the memory file database.

15.121 DHCPDRV_MEMFILE_GET_SUBID_CLIENTID

obtaining IPv4 lease for subnet ID %1 and client ID %2

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified subnet ID and client ID.

15.122 DHCPDRV_MEMFILE_GET_SUBID_HWADDR

```
obtaining IPv4 lease for subnet ID %1 and hardware address %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv4 lease from the memory file database for a client with the specified subnet ID and hardware address.

15.123 DHCPDRV_MEMFILE_GET_SUBID_PAGE6

```
obtaining at most %1 IPv6 leases starting from address %2 for subnet ID %3
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv6 leases from the memory file database beginning with the specified address for a given subnet identifier.

15.124 DHCPDRV_MEMFILE_LEASE_FILE_LOAD

```
loading leases from file %1
```

An info message issued when the server is about to start reading DHCP leases from the lease file. All leases currently held in the memory will be replaced by those read from the file.

15.125 DHCPDRV_MEMFILE_LEASE_LOAD

```
loading lease %1
```

Logged at debug log level 55. This debug message is issued when DHCP lease is being loaded from the file to memory.

15.126 DHCPDRV_MEMFILE_LEASE_LOAD_ROW_ERROR

```
discarding row %1, error: %2
```

An error message issued if the DHCP lease being loaded from the given row of the lease file fails. The log message should contain the specific reason the row was discarded. The server continues loading the remaining data. This may indicate a corrupt lease file.

15.127 DHCPDRV_MEMFILE_LFC_EXECUTE

```
executing Lease File Cleanup using: %1
```

An informational message issued when the memfile lease database backend starts a new process to perform Lease File Cleanup.

15.128 DHCPDRV_MEMFILE_LFC_FAIL_PID_CREATE

```
Lease File Cleanup pid file create: %1
```

This error message is issued if the LFC execute code detects a failure when trying to create the PID file. It includes a more specific error string.

15.129 DHCPDRV_MEMFILE_LFC_LEASE_FILE_RENAME_FAIL

failed to rename the current lease file %1 to %2, reason: %3

An error message logged when the memfile lease database backend fails to move the current lease file to a new file on which the cleanup should be performed. This effectively means that the lease file cleanup does not take place.

15.130 DHCPDRV_MEMFILE_LFC_LEASE_FILE_REOPEN_FAIL

failed to reopen lease file %1 after preparing input file for lease file cleanup, reason: %2, new leases will not persist!

An error message logged when the memfile lease database backend failed to re-open or re-create the lease file after renaming the lease file for lease file cleanup. The server continues to operate but leases do not persist to disk.

15.131 DHCPDRV_MEMFILE_LFC_RESCHEDULED

rescheduled Lease File Cleanup

An informational message issued when the memfile lease database backend rescheduled the periodic Lease File Cleanup at the reception of a "kea-lfc-start" command.

15.132 DHCPDRV_MEMFILE_LFC_RUNNING

Lease File Cleanup instance already running

This informational message is issued when the LFC execute code detects that a previous instance of the LFC process is still running via the PID check.

15.133 DHCPDRV_MEMFILE_LFC_SETUP

setting up the Lease File Cleanup interval to %1 sec

An informational message logged when the memfile lease database backend configures the LFC to be executed periodically. The argument holds the interval in seconds in which the LFC will be executed.

15.134 DHCPDRV_MEMFILE_LFC_SPAWN_FAIL

lease file cleanup failed to run because kea-lfc process couldn't be spawned

This error message is logged when the Kea server fails to run kea-lfc, the program that cleans up the lease file. The server will try again the next time a lease file cleanup is scheduled. Although this message should not appear and the reason why it did should be investigated, the occasional failure to start the lease file cleanup will not impact operations. Should the failure persist however, the size of the lease file will increase without bound.

15.135 DHCPDRV_MEMFILE_LFC_START

starting Lease File Cleanup

An informational message issued when the Memfile lease database backend starts the periodic Lease File Cleanup.

15.136 DHCPDRV_MEMFILE_LFC_UNREGISTER_TIMER_FAILED

```
failed to unregister timer 'memfile-lfc': %1
```

Logged at debug log level 40. This debug message is logged when Memfile backend fails to unregister timer used for lease file cleanup scheduling. There are several reasons why this could occur, although the most likely cause is that the system is being shut down and some other component has unregistered the timer. The message includes the reason for this error.

15.137 DHCPDRV_MEMFILE_NEEDS_DOWNGRADING

```
version of lease file: %1 schema is later than version %2
```

A warning message issued when the schema of the lease file loaded by the server is newer than the memfile schema of the server. The server converts the lease data from newer schemas to its schema as it is read, therefore the lease information in use by the server will be correct. Note though, that any data stored in newer schema fields will be dropped. What remains is for the file itself to be rewritten using the current schema.

15.138 DHCPDRV_MEMFILE_NEEDS_UPGRADING

```
version of lease file: %1 schema is earlier than version %2
```

A warning message issued when the schema of the lease file loaded by the server pre-dates the memfile schema of the server. Note that the server converts the lease data from older schemas to the current schema as it is read, therefore the lease information in use by the server will be correct. What remains is for the file itself to be rewritten using the current schema.

15.139 DHCPDRV_MEMFILE_NO_STORAGE

```
running in non-persistent mode, leases will be lost after restart
```

A warning message issued when writes of leases to disk have been disabled in the configuration. This mode is useful for some kinds of performance testing but should not be enabled in normal circumstances. Non-persistence mode is enabled when 'persist4=no persist6=no' parameters are specified in the database access string.

15.140 DHCPDRV_MEMFILE_PATH_SECURITY_WARNING

```
Lease file path specified is NOT SECURE: %1
```

This warning message is issued when security enforcement is disabled and the lease file path specified for does not comply with the supported path. The server will still use the specified path but is warning that doing so may pose a security risk.

15.141 DHCPDRV_MEMFILE_READ_HWADDR_FAIL

```
failed to read hardware address from lease file: %1
```

A warning message issued when read attempt of the hardware address stored in a disk file failed. The parameter should provide the exact nature of the failure. The database read will continue, but that particular lease will no longer have hardware address associated with it.

15.142 DHCPDRV_MEMFILE_ROLLBACK

rolling back memory file database

Logged at debug log level 50. The code has issued a rollback call. For the memory file database this is a no-op.

15.143 DHCPDRV_MEMFILE_UPDATE_ADDR4

updating IPv4 lease for address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to update IPv4 lease from the memory file database for the specified address.

15.144 DHCPDRV_MEMFILE_UPDATE_ADDR6

updating IPv6 lease for address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to update IPv6 lease from the memory file database for the specified address.

15.145 DHCPDRV_MEMFILE_WIPE_LEASES4

removing all IPv4 leases from subnet %1

This informational message is printed when removal of all leases from specified IPv4 subnet is commencing. This is a result of receiving administrative command.

15.146 DHCPDRV_MEMFILE_WIPE_LEASES4_FINISHED

removing all IPv4 leases from subnet %1 finished, removed %2 leases

This informational message is printed when removal of all leases from a specified IPv4 subnet has finished. The number of removed leases is printed.

15.147 DHCPDRV_MEMFILE_WIPE_LEASES6

removing all IPv6 leases from subnet %1

This informational message is printed when removal of all leases from specified IPv6 subnet is commencing. This is a result of receiving administrative command.

15.148 DHCPDRV_MEMFILE_WIPE_LEASES6_FINISHED

removing all IPv6 leases from subnet %1 finished, removed %2 leases

This informational message is printed when removal of all leases from a specified IPv6 subnet has finished. The number of removed leases is printed.

15.149 DHCPDRV_MT_DISABLED_QUEUE_CONTROL

disabling dhcp queue control when multi-threading is enabled.

This warning message is issued when dhcp queue control is disabled automatically if multi-threading is enabled. These two options are incompatible and can not both be enabled at the same time.

15.150 DHCPDRV_MULTIPLE_RAW_SOCKETS_PER_IFACE

current configuration will result in opening multiple broadcast capable sockets on some interfaces and some DHCP messages may be duplicated

A warning message issued when the current configuration indicates that multiple sockets, capable of receiving broadcast traffic, will be opened on some of the interfaces. It must be noted that this may lead to receiving and processing the same DHCP message multiple times, as it will be received by each socket individually.

15.151 DHCPDRV_NOTYPE_DB

no 'type' keyword to determine database backend: %1

This is an error message, logged when an attempt has been made to access a database backend, but where no 'type' keyword has been included in the access string. The access string (less any passwords) is included in the message.

15.152 DHCPDRV_NO_SOCKETS_OPEN

no interface configured to listen to DHCP traffic

This warning message is issued when the current server configuration specifies no interfaces that the server should listen on, or when the specified interfaces are not configured to receive the traffic.

15.153 DHCPDRV_ONLY_IF_REQUIRED_DEPRECATED

The parameter 'only-if-required' is deprecated. Use 'only-in-additional-list' instead

This warning message is emitted when configuration parsing detects the use of the deprecated 'only-if-required' parameter. It has been replaced by 'only-in-additional-list'. Users should migrate to the new parameter.

15.154 DHCPDRV_OPEN_SOCKET_FAIL

failed to open socket: %1

A warning message issued when IfaceMgr fails to open and bind a socket. The reason for the failure is appended as an argument of the log message.

15.155 DHCPDRV_QUEUE_NCR

%1: Name change request to %2 DNS entry queued: %3

Logged at debug log level 55. A debug message which is logged when the NameChangeRequest to add or remove a DNS entries for a particular lease has been queued. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument carries the details of the NameChangeRequest.

15.156 DHCPDRV_QUEUE_NCR_FAILED

```
%1: queuing %2 name change request failed for lease %3: %4
```

This error message is logged when sending a NameChangeRequest to DHCP DDNS failed. The first argument includes the client identification information. The second argument indicates whether the DNS entry is to be added or removed. The third argument specifies the leased address. The last argument provides the reason for failure.

15.157 DHCPDRV_QUEUE_NCR_SKIP

```
%1: skip queuing name change request for lease: %2
```

Logged at debug log level 50. This debug message is issued when the server decides to not queue the name change request because the lease doesn't include the FQDN, the forward and reverse update is disabled for this lease or the DNS updates are disabled in the configuration. The first argument includes the client identification information. The second argument includes the leased address.

15.158 DHCPDRV_REQUIRE_CLIENT_CLASSES_DEPRECATED

```
The parameter 'require-client-classes' is deprecated. Use 'evaluate-additional-classes' instead
```

This warning message is emitted when configuration parsing detects the use of the deprecated 'require-client-classes' parameter. It has been replaced by 'evaluate-additional-classes'. Users should migrate to the new parameter.

15.159 DHCPDRV_SUBNET4O6_SELECT_FAILED

```
Failed to select any subnet for the DHCPv4o6 packet
```

Logged at debug log level 40. This debug message is issued when the server was unable to select any subnet for the DHCPv4o6 packet.

15.160 DHCPDRV_SUBNET4_SELECT_BY_ADDRESS_NO_MATCH

```
No subnet matches address: %1
```

Logged at debug log level 40. This debug message is issued when the server was unable to select a subnet using the specified address.

15.161 DHCPDRV_SUBNET4_SELECT_BY_INTERFACE_NO_MATCH

```
No subnet matches interface: %1
```

Logged at debug log level 40. This debug message is issued when the server was unable to select a subnet using the specified interface name.

15.162 DHCPDRV_SUBNET4_SELECT_BY_RELAY_ADDRESS_NO_MATCH

```
No subnet matches relay address: %1
```

Logged at debug log level 40. This debug message is issued when the server was unable to select a subnet using the specified relay address.

15.163 DHCPDRV_SUBNET4_SELECT_NO_RAI_OPTIONS

No RAI options found to use for subnet selection.

Logged at debug log level 40. This debug message is issued by the server when the client query does not include RAI options suitable for use with subnet selection.

15.164 DHCPDRV_SUBNET4_SELECT_NO_RELAY_ADDRESS

Relay address (giaddr) in client packet is empty.

Logged at debug log level 40. This debug message is issued when no relay address was specified to use for subnet selection.

15.165 DHCPDRV_SUBNET4_SELECT_NO_USABLE_ADDRESS

No subnet selected because no suitable address to use for subnet selection was found.

Logged at debug log level 40. This debug message is issued when the server could not find a suitable address to use for subnet selection.

15.166 DHCPDRV_SUBNET6_SELECT_BY_ADDRESS_NO_MATCH

No subnet matches address: %1

Logged at debug log level 40. This debug message is issued when the server was unable to select a subnet using the specified address.

15.167 DHCPDRV_SUBNET6_SELECT_BY_INTERFACE_ID_NO_MATCH

No subnet matches interface id: %1

Logged at debug log level 40. This debug message is issued when the server was unable to select a subnet using the specified interface id.

15.168 DHCPDRV_SUBNET6_SELECT_BY_INTERFACE_NO_MATCH

No subnet matches interface: %1

Logged at debug log level 40. This debug message is issued when the server was unable to select a subnet using the specified interface name.

15.169 DHCPDRV_TEMPLATE_EVAL_ERROR

%1: Expression '%2' evaluated to %3

This error message indicates that a problem was encountered while evaluating an expression of a template client class. A description of the problem is printed.

15.170 DHCPDRV_TEMPLATE_EVAL_RESULT

```
%1: Expression '%2' evaluated to %3
```

Logged at debug log level 50. This debug message indicates that the expression of a template client class has been successfully evaluated. The client class name and the result value of the evaluation are printed.

15.171 DHCPDRV_TIMERMGR_CALLBACK_FAILED

```
running handler for timer %1 caused exception: %2
```

This error message is emitted when the timer elapsed and the operation associated with this timer has thrown an exception. The timer name and the reason for exception is logged.

15.172 DHCPDRV_TIMERMGR_REGISTER_TIMER

```
registering timer: %1, using interval: %2 ms
```

Logged at debug log level 40. This debug message is issued when the new interval timer is registered in the Timer Manager. This timer will have a callback function associated with it, and this function will be executed according to the interval specified. The unique name of the timer and the interval at which the callback function will be executed is included in the message.

15.173 DHCPDRV_TIMERMGR_RUN_TIMER_OPERATION

```
running operation for timer: %1
```

Logged at debug log level 50. This debug message is issued when the Timer Manager is about to run a periodic operation associated with the given timer. An example of such operation is a periodic cleanup of expired leases. The name of the timer is included in the message.

15.174 DHCPDRV_TIMERMGR_START_TIMER

```
starting timer: %1
```

Logged at debug log level 40. This debug message is issued when the registered interval timer is being started. If this operation is successful the timer will periodically execute the operation associated with it. The name of the started timer is included in the message.

15.175 DHCPDRV_TIMERMGR_STOP_TIMER

```
stopping timer: %1
```

Logged at debug log level 40. This debug message is issued when the registered interval timer is being stopped. The timer remains registered and can be restarted if necessary. The name of the timer is included in the message.

15.176 DHCPDRV_TIMERMGR_UNREGISTER_ALL_TIMERS

```
unregistering all timers
```

Logged at debug log level 40. This debug message is issued when all registered interval timers are being unregistered from the Timer Manager.

15.177 DHCPDRV_TIMERMGR_UNREGISTER_TIMER

unregistering timer: %1

Logged at debug log level 40. This debug message is issued when one of the registered interval timers is unregistered from the Timer Manager. The name of the timer is included in the message.

15.178 DHCPDRV_UNKNOWN_DB

unknown database type: %1

The database access string specified a database type (given in the message) that is unknown to the software. This is a configuration error.

16.1 DHCP_ADD_EXTERNAL_SOCKET_ALREADY_EXISTS

Adding an already existing external socket %1

This warning message indicates that an external socket was added but it already exists i.e. adds and deletes are not correctly balanced.

16.2 DHCP_ADD_EXTERNAL_SOCKET_BAD_THREAD

Attempted to register external socket %1 from different thread %2 than main thread %3

This error message indicates that a different thread than the main thread has registered an external socket. This is a programming error and should be fixed. Only the main thread is allowed to perform operations on the external sockets. The file descriptor and the respective thread ids are included in the message.

16.3 DHCP_DDNS_ADD_FAILED

DHCP_DDNS Request ID %1: Transaction outcome %2

This is an error message issued after DHCP_DDNS attempts to submit DNS mapping entry additions have failed. The precise reason for the failure should be documented in preceding log entries.

16.4 DHCP_DDNS_ADD_SUCCEEDED

DHCP_DDNS Request ID %1: successfully added the DNS mapping addition for this request: %2

This is an informational message issued after DHCP_DDNS has submitted DNS mapping additions which were received and accepted by an appropriate DNS server.

16.5 DHCP_DDNS_AT_MAX_TRANSACTIONS

application has %1 queued requests but has reached maximum number of %2 concurrent transactions

Logged at debug log level 55. This is a debug message that indicates that the application has DHCP_DDNS requests in the queue but is working as many concurrent requests as allowed.

16.6 DHCP_DDNS_CLEARED_FOR_SHUTDOWN

```
application has met shutdown criteria for shutdown type: %1
```

Logged at debug log level 0. This is a debug message issued when the application has been instructed to shutdown and has met the required criteria to exit.

16.7 DHCP_DDNS_CONFIGURE

```
configuration %1 received: %2
```

Logged at debug log level 40. This is a debug message issued when the DHCP-DDNS application configure method has been invoked.

16.8 DHCP_DDNS_CONFIGURED_CALLOUT_DROP

```
configuration was rejected because a callout set the next step to 'drop': %1
```

This error message indicates that the DHCP-DDNS had failed configuration attempt because the next step of the configured callout was set to 'drop' by a hook library. The error message provided by the hook library is displayed.

16.9 DHCP_DDNS_CONFIG_CHECK_FAIL

```
DHCP-DDNS server configuration check failed: %1
```

This error message indicates that the DHCP-DDNS had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

16.10 DHCP_DDNS_CONFIG_FAIL

```
DHCP-DDNS server configuration failed: %1
```

This error message indicates that the DHCP-DDNS had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

16.11 DHCP_DDNS_CONFIG_SYNTAX_WARNING

```
DHCP-DDNS server configuration syntax warning: %1
```

This warning message indicates that the DHCP-DDNS configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

16.12 DHCP_DDNS_FAILED

```
application experienced a fatal error: %1
```

This is a debug message issued when the DHCP-DDNS application encounters an unrecoverable error from within the event loop.

16.13 DHCP_DDNS_FORWARD_ADD_BAD_DNSCLIENT_STATUS

DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while adding a forward address mapping for FQDN %3 to DNS server %4

This is an error message issued when DNSClient returns an unrecognized status while DHCP_DDNS was adding a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

16.14 DHCP_DDNS_FORWARD_ADD_BUILD_FAILURE

DNS Request ID %1: update message to add a forward DNS entry could not be constructed for this request: %2, reason: %3

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address addition. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

16.15 DHCP_DDNS_FORWARD_ADD_IO_ERROR

DHCP_DDNS Request ID %1: encountered an IO error sending a forward mapping add for FQDN %2 to DNS server %3

This is an error message issued when a communication error occurs while DHCP_DDNS is carrying out a forward address add. The application will retry against the same server or others as appropriate.

16.16 DHCP_DDNS_FORWARD_ADD_REJECTED

DNS Request ID %1: Server, %2, rejected a DNS update request to add the address mapping for FQDN, %3, with an RCODE: %4

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

16.17 DHCP_DDNS_FORWARD_ADD_RESP_CORRUPT

DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while adding forward address mapping for FQDN, %3

This is an error message issued when the response received by DHCP_DDNS, to a update request to add a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

16.18 DHCP_DDNS_FORWARD_ADD_TIMEOUT

DHCP_DDNS Request ID %1: timed out waiting for a response to forward mapping add for FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP_DDNS is carrying out a forward address add. The application will retry against the same server or others as appropriate.

16.19 DHCP_DDNS_FORWARD_REMOVE_ADDRS_BAD_DNSCLIENT_STATUS

DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while removing a forward address mapping for FQDN %3 to DNS server %4

This is an error message issued when DNSClient returns an unrecognized status while DHCP_DDNS was removing a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

16.20 DHCP_DDNS_FORWARD_REMOVE_ADDRS_BUILD_FAILURE

DNS Request ID %1: update message to remove a forward DNS Address entry could not be constructed for this request: %2, reason: %3

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address (A or AAAA) removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue. */sar/*

16.21 DHCP_DDNS_FORWARD_REMOVE_ADDRS_IO_ERROR

DHCP_DDNS Request ID %1: encountered an IO error sending a forward mapping address removal for FQDN %2 to DNS server %3

This is an error message issued when a communication error occurs while DHCP_DDNS is carrying out a forward address remove. The application will retry against the same server or others as appropriate.

16.22 DHCP_DDNS_FORWARD_REMOVE_ADDRS_REJECTED

DNS Request ID %1: Server, %2, rejected a DNS update request to remove the forward address mapping for FQDN, %3, with an RCODE: %4

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

16.23 DHCP_DDNS_FORWARD_REMOVE_ADDRS_RESP_CORRUPT

DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while removing forward address mapping for FQDN, %3

This is an error message issued when the response received by DHCP_DDNS, to a update request to remove a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

16.24 DHCP_DDNS_FORWARD_REMOVE_ADDRS_TIMEOUT

DHCP_DDNS Request ID %1: timed out waiting for a response to forward mapping address removal for FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP_DDNS is carrying out a forward mapping address removal. The application will retry against the same server or others as appropriate.

16.25 DHCP_DDNS_FORWARD_REMOVE_RRS_BAD_DNSCLIENT_STATUS

DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while removing forward RRs for FQDN %3 to DNS server %4

This is an error message issued when DNSClient returns an unrecognized status while DHCP_DDNS was removing forward RRs. The request will be aborted. This is most likely a programmatic issue and should be reported.

16.26 DHCP_DDNS_FORWARD_REMOVE_RRS_BUILD_FAILURE

DNS Request ID %1: update message to remove forward DNS RR entries could not be constructed for this request: %2, reason: %3

This is an error message issued when an error occurs attempting to construct the server bound packet requesting forward RR (DHCID RR) removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

16.27 DHCP_DDNS_FORWARD_REMOVE_RRS_IO_ERROR

DHCP_DDNS Request ID %1: encountered an IO error sending a forward RR removal for FQDN %2 to DNS server %3

This is an error message issued when a communication error occurs while DHCP_DDNS is carrying out a forward RR remove. The application will retry against the same server.

16.28 DHCP_DDNS_FORWARD_REMOVE_RRS_REJECTED

DNS Request ID %1: Server, %2, rejected a DNS update request to remove forward RR entries for FQDN, %3, with an RCODE: %4

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

16.29 DHCP_DDNS_FORWARD_REMOVE_RRS_RESP_CORRUPT

DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while removing forward RRs for FQDN, %3

This is an error message issued when the response received by DHCP_DDNS, to a update request to remove forward RRs mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.
/sar/

16.30 DHCP_DDNS_FORWARD_REMOVE_RRS_TIMEOUT

DHCP_DDNS Request ID %1: timed out waiting for response to forward RR removal for FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP_DDNS is carrying out a forward RR removal. The application will retry against the same server or others as appropriate.

16.31 DHCP_DDNS_FORWARD_REPLACE_BAD_DNSCLIENT_STATUS

DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while replacing forward address mapping for FQDN %3 to DNS server %4

This is an error message issued when DNSClient returns an unrecognized status while DHCP_DDNS was replacing a forward address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

16.32 DHCP_DDNS_FORWARD_REPLACE_BUILD_FAILURE

DNS Request ID %1: update message to replace a forward DNS entry could not be constructed from this request: %2, reason: %3

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a forward address replacement. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

16.33 DHCP_DDNS_FORWARD_REPLACE_IO_ERROR

DHCP_DDNS Request ID %1: encountered an IO error sending a forward mapping replace for FQDN %2 to DNS server %3

This is an error message issued when a communication error occurs while DHCP_DDNS is carrying out a forward mapping replace. The application will retry against the same server or others as appropriate.

16.34 DHCP_DDNS_FORWARD_REPLACE_REJECTED

DNS Request ID %1: Server, %2, rejected a DNS update request to replace the address mapping for FQDN, %3, with an RCODE: %4

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

16.35 DHCP_DDNS_FORWARD_REPLACE_RESP_CORRUPT

DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while replacing forward address mapping for FQDN, %3

This is an error message issued when the response received by DHCP_DDNS, to a update request to replace a forward address mapping, is mangled or malformed. The application will retry against the same server or others as appropriate.

16.36 DHCP_DDNS_FORWARD_REPLACE_TIMEOUT

DHCP_DDNS Request ID %1: timed out waiting for a response to forward mapping replace for FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP_DDNS is carrying out a forward mapping replace. The application will retry against the same server or others as appropriate.

16.37 DHCP_DDNS_FWD_REQUEST_IGNORED

Request ID %1: Forward updates are disabled, the forward portion of request will be ignored: %2

Logged at debug log level 55. This is a debug message issued when forward DNS updates are disabled and DHCP_DDNS receives an update request containing a forward DNS update. The forward update will not performed.

16.38 DHCP_DDNS_INVALID_NCR

application received an invalid DNS update request: %1

This is an error message that indicates that an invalid request to update a DNS entry was received by the application. Either the format or the content of the request is incorrect. The request will be ignored.

16.39 DHCP_DDNS_INVALID_RESPONSE

received response to DNS Update message is malformed: %1

Logged at debug log level 50. This is a debug message issued when the DHCP-DDNS application encountered an error while decoding a response to DNS Update message. Typically, this error will be encountered when a response message is malformed.

16.40 DHCP_DDNS_IO_FETCH_RESULT

DNS update callback handling IO result: %1.

Logged at debug log level 50. This debug message indicates that the DNS update callback has been called with the IOFetch result contained in the message argument.

16.41 DHCP_DDNS_LISTENING_ON_ALL_INTERFACES

the DHCP-DDNS server has been configured to listen on %1. This is an insecure configuration supported for testing purposes only

This is a warning message issued when the DHCP-DDNS server is configured to listen at either *0.0.0.0* or *::*. It is possible for a malicious attacker to send bogus NameChangeRequests to it and change entries in the DNS. For this reason, listening on all interfaces should only be used when deploying in containers or for testing purposes. A future version of Kea will disable this ability by default.

16.42 DHCP_DDNS_NCR_FLUSH_IO_ERROR

DHCP-DDNS Last send before stopping did not complete successfully: %1

This is an error message that indicates the DHCP-DDNS client was unable to complete the last send prior to exiting send mode. This is a programmatic error, highly unlikely to occur, and should not impair the application's ability to process requests.

16.43 DHCP_DDNS_NCR_LISTEN_CLOSE_ERROR

application encountered an error while closing the listener used to receive NameChangeRequests : %1

This is an error message that indicates the application was unable to close the listener connection used to receive NameChangeRequests. Closure may occur during the course of error recovery or during normal shutdown procedure. In either case the error is unlikely to impair the application's ability to process requests but it should be reported for analysis.

16.44 DHCP_DDNS_NCR_RECV_NEXT_ERROR

application could not initiate the next read following a request receive: %1

This is an error message indicating that NameChangeRequest listener could not start another read after receiving a request. While possible, this is highly unlikely and is probably a programmatic error. The application should recover on its own. The error is given in the message.

16.45 DHCP_DDNS_NCR_SEND_CLOSE_ERROR

DHCP-DDNS client encountered an error while closing the sender connection used to send NameChangeRequests: %1

This is an error message that indicates the DHCP-DDNS client was unable to close the connection used to send NameChangeRequests. Closure may occur during the course of error recovery or during normal shutdown procedure. In either case the error is unlikely to impair the client's ability to send requests but it should be reported for analysis.

16.46 DHCP_DDNS_NCR_SEND_NEXT_ERROR

DHCP-DDNS client could not initiate the next request send following send completion: %1

This is an error message indicating that NameChangeRequest sender could not start another send after completing the send of the previous request. While possible, this is highly unlikely and is probably a programmatic error. The application should recover on its own.

16.47 DHCP_DDNS_NCR_UDP_CLEAR_READY_ERROR

NCR UDP watch socket failed to clear: %1

This is an error message that indicates the application was unable to reset the UDP NCR sender ready status after completing a send. This is programmatic error that should be reported. The application may or may not continue to operate correctly.

16.48 DHCP_DDNS_NCR_UDP_RECV_CANCELED

UDP socket receive was canceled while listening for DNS Update requests

Logged at debug log level 40. This is a debug message indicating that the listening on a UDP socket for DNS update requests has been canceled. This is a normal part of suspending listening operations.

16.49 DHCP_DDNS_NCR_UDP_RECV_ERROR

UDP socket receive error while listening for DNS Update requests: %1

This is an error message indicating that an I/O error occurred while listening over a UDP socket for DNS update requests. This could indicate a network connectivity or system resource issue.

16.50 DHCP_DDNS_NCR_UDP_SEND_CANCELED

UDP socket send was canceled while sending a DNS Update request to DHCP_DDNS: %1

This is an informational message indicating that sending requests via UDP socket to DHCP_DDNS has been interrupted. This is a normal part of suspending send operations.

16.51 DHCP_DDNS_NCR_UDP_SEND_ERROR

UDP socket send error while sending a DNS Update request: %1

This is an error message indicating that an IO error occurred while sending a DNS update request to DHCP_DDNS over a UDP socket. This could indicate a network connectivity or system resource issue.

16.52 DHCP_DDNS_NOT_ON_LOOPBACK

the DHCP-DDNS server has been configured to listen on %1 which is not the local loopback. This is an insecure configuration supported for testing purposes only

This is a warning message issued when the DHCP-DDNS server is configured to listen at an address other than the loopback address (127.0.0.1 or ::1). It is possible for a malicious attacker to send bogus NameChangeRequests to it and change entries in the DNS. For this reason, addresses other than the IPv4 or IPv6 loopback addresses should only be used for testing purposes. A future version of Kea will implement authentication to guard against such attacks.

16.53 DHCP_DDNS_NO_ELIGIBLE_JOBS

although there are queued requests, there are pending transactions for each, Queue count: %1 Transaction count: %2

Logged at debug log level 55. This is a debug message issued when all of the queued requests represent clients for which there is an update already in progress. This may occur under normal operations but should be temporary situation.

16.54 DHCP_DDNS_NO_FWD_MATCH_ERROR

Request ID %1: the configured list of forward DDNS domains does not contain a match for: %2 The request has been discarded.

This is an error message that indicates that DHCP_DDNS received a request to update the forward DNS information for the given FQDN but for which there are no configured DDNS domains in the DHCP_DDNS configuration. Either the DHCP_DDNS configuration needs to be updated or the source of the FQDN itself should be investigated.

16.55 DHCP_DDNS_NO_MATCH

No DNS servers match FQDN %1

This is warning message issued when there are no domains in the configuration which match the cited fully qualified domain name (FQDN). The DNS Update request for the FQDN cannot be processed.

16.56 DHCP_DDNS_NO_REV_MATCH_ERROR

Request ID %1: the configured list of reverse DDNS domains does not contain a match for: %2 The request has been discarded.

This is an error message that indicates that DHCP_DDNS received a request to update the reverse DNS information for the given FQDN but for which there are no configured DDNS domains in the DHCP_DDNS configuration. Either the DHCP_DDNS configuration needs to be updated or the source of the FQDN itself should be investigated.

16.57 DHCP_DDNS_QUEUE_MGR_QUEUE_FULL

application request queue has reached maximum number of entries %1

This is an error message indicating that DHCP-DDNS is receiving DNS update requests faster than they can be processed. This may mean the maximum queue needs to be increased, the DHCP-DDNS clients are simply generating too many requests too quickly, or perhaps upstream DNS servers are experiencing load issues.

16.58 DHCP_DDNS_QUEUE_MGR_QUEUE_RECEIVE

Request ID %1: received and queued a request.

Logged at debug log level 55. This is an informational message indicating that the NameChangeRequest listener used by DHCP-DDNS to receive a request has received a request and queued it for further processing.

16.59 DHCP_DDNS_QUEUE_MGR_RECONFIGURING

application is reconfiguring the queue manager

Logged at debug log level 40. This is an informational message indicating that DHCP_DDNS is reconfiguring the queue manager as part of normal startup or in response to a new configuration.

16.60 DHCP_DDNS_QUEUE_MGR_RECOVERING

application is attempting to recover from a queue manager IO error

This is an informational message indicating that DHCP_DDNS is attempting to restart the queue manager after it suffered an IO error while receiving requests.

16.61 DHCP_DDNS_QUEUE_MGR_RECV_ERROR

application's queue manager was notified of a request receive error by its listener.

This is an error message indicating that the NameChangeRequest listener used by DHCP-DDNS to receive requests encountered an IO error. There should be corresponding log messages from the listener layer with more details. This may indicate a network connectivity or system resource issue.

16.62 DHCP_DDNS_QUEUE_MGR_RESUME_ERROR

application could not restart the queue manager, reason: %1

This is an error message indicating that DHCP_DDNS's Queue Manager could not be restarted after stopping due to a full receive queue. This means that the application cannot receive requests. This is most likely due to DHCP_DDNS configuration parameters referring to resources such as an IP address or port, that is no longer unavailable. DHCP_DDNS will attempt to restart the queue manager if given a new configuration.

16.63 DHCP_DDNS_QUEUE_MGR_RESUMING

application is resuming listening for requests now that the request queue size has reached %1 of a maximum %2 allowed

This is an informational message indicating that DHCP_DDNS, which had stopped accepting new requests, has processed enough entries from the receive queue to resume accepting requests.

16.64 DHCP_DDNS_QUEUE_MGR_STARTED

application's queue manager has begun listening for requests.

Logged at debug log level 0. This is a debug message indicating that DHCP_DDNS's Queue Manager has successfully started and is now listening for NameChangeRequests.

16.65 DHCP_DDNS_QUEUE_MGR_START_ERROR

application could not start the queue manager, reason: %1

This is an error message indicating that DHCP_DDNS's Queue Manager could not be started. This means that the application cannot receive requests. This is most likely due to DHCP_DDNS configuration parameters referring to resources such as an IP address or port, that are unavailable. DHCP_DDNS will attempt to restart the queue manager if given a new configuration.

16.66 DHCP_DDNS_QUEUE_MGR_STOPPED

application's queue manager has stopped listening for requests.

Logged at debug log level 40. This is a debug message indicating that DHCP_DDNS's Queue Manager has stopped listening for NameChangeRequests. This may be because of normal event such as reconfiguration or as a result of an error. There should be log messages preceding this one to indicate why it has stopped.

16.67 DHCP_DDNS_QUEUE_MGR_STOPPING

```
application is stopping the queue manager for %1
```

Logged at debug log level 0. This is an informational message indicating that DHCP_DDNS is stopping the queue manager either to reconfigure it or as part of application shutdown.

16.68 DHCP_DDNS_QUEUE_MGR_STOP_ERROR

```
application encountered an error stopping the queue manager: %1
```

This is an error message indicating that DHCP_DDNS encountered an error while trying to stop the queue manager. This error is unlikely to occur or to impair the application's ability to function but it should be reported for analysis.

16.69 DHCP_DDNS_QUEUE_MGR_UNEXPECTED_HANDLER_ERROR

```
application's queue manager request receive handler experienced an unexpected exception %1:
```

This is an error message indicating that an unexpected error occurred within the DHCP_DDNS's Queue Manager request receive completion handler. This is most likely a programmatic issue that should be reported. The application may recover on its own.

16.70 DHCP_DDNS_QUEUE_MGR_UNEXPECTED_STOP

```
application's queue manager receive was
```

aborted unexpectedly while queue manager state is: %1 This is an error message indicating that DHCP_DDNS's Queue Manager request receive was unexpectedly interrupted. Normally, the read is receive is only interrupted as a normal part of stopping the queue manager. This is most likely a programmatic issue that should be reported.

16.71 DHCP_DDNS_REMOVE_FAILED

```
DHCP_DDNS Request ID %1: Transaction outcome: %2
```

This is an error message issued after DHCP_DDNS attempts to submit DNS mapping entry removals have failed. The precise reason for the failure should be documented in preceding log entries.

16.72 DHCP_DDNS_REMOVE_SUCCEEDED

```
DHCP_DDNS Request ID %1: successfully removed the DNS mapping addition for this request: %2
```

This is an informational message issued after DHCP_DDNS has submitted DNS mapping removals which were received and accepted by an appropriate DNS server.

16.73 DHCP_DDNS_REQUEST_DROPPED

```
Request ID %1: Request contains no enabled update requests and will be dropped: %2
```

Logged at debug log level 55. This is a debug message issued when DHCP_DDNS receives a request which does not contain updates in a direction that is enabled. In other words, if only forward updates are enabled and request is received that asks only for reverse updates then the request is dropped.

16.74 DHCP_DDNS_REVERSE_REMOVE_BAD_DNSCLIENT_STATUS

DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while removing reverse address mapping for FQDN %3 to DNS server %4

This is an error message issued when DNSClient returns an unrecognized status while DHCP_DDNS was removing a reverse address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

16.75 DHCP_DDNS_REVERSE_REMOVE_BUILD_FAILURE

DNS Request ID %1: update message to remove a reverse DNS entry could not be constructed from this request: %2, reason: %3

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a reverse PTR removal. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

16.76 DHCP_DDNS_REVERSE_REMOVE_IO_ERROR

DHCP_DDNS Request ID %1: encountered an IO error sending a reverse mapping remove for FQDN %2 to DNS server %3

This is an error message issued when a communication error occurs while DHCP_DDNS is carrying out a reverse mapping remove. The application will retry against the same server or others as appropriate.

16.77 DHCP_DDNS_REVERSE_REMOVE_REJECTED

DNS Request ID %1: Server, %2, rejected a DNS update request to remove the reverse mapping for FQDN, %3, with an RCODE: %4

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

16.78 DHCP_DDNS_REVERSE_REMOVE_RESP_CORRUPT

DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while removing reverse address mapping for FQDN, %3

This is an error message issued when the response received by DHCP_DDNS, to a update request to remove a reverse address, is mangled or malformed. The application will retry against the same server or others as appropriate.

16.79 DHCP_DDNS_REVERSE_REMOVE_TIMEOUT

DHCP_DDNS Request ID %1: timed out waiting for a response to reverse mapping remove for FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP_DDNS is carrying out a reverse mapping remove. The application will retry against the same server or others as appropriate.

16.80 DHCP_DDNS_REVERSE_REPLACE_BAD_DNSCLIENT_STATUS

DHCP_DDNS Request ID %1: received an unknown DNSClient status: %2, while replacing reverse address mapping for FQDN %3 to DNS server %4

This is an error message issued when DNSClient returns an unrecognized status while DHCP_DDNS was replacing a reverse address mapping. The request will be aborted. This is most likely a programmatic issue and should be reported.

16.81 DHCP_DDNS_REVERSE_REPLACE_BUILD_FAILURE

DNS Request ID %1: update message to replace a reverse DNS entry could not be constructed from this request: %2, reason: %3

This is an error message issued when an error occurs attempting to construct the server bound packet requesting a reverse PTR replacement. This is due to invalid data contained in the NameChangeRequest. The request will be aborted. This is most likely a configuration issue.

16.82 DHCP_DDNS_REVERSE_REPLACE_IO_ERROR

DHCP_DDNS Request ID %1: encountered an IO error sending a reverse mapping replacement for FQDN %2 to DNS server %3

This is an error message issued when a communication error occurs while DHCP_DDNS is carrying out a reverse mapping replacement. The application will retry against the same server or others as appropriate.

16.83 DHCP_DDNS_REVERSE_REPLACE_REJECTED

DNS Request ID %1: Server, %2, rejected a DNS update request to replace the reverse mapping for FQDN, %3, with an RCODE: %4

This is an error message issued when an update was rejected by the DNS server it was sent to for the reason given by the RCODE. The rcode values are defined in RFC 2136.

16.84 DHCP_DDNS_REVERSE_REPLACE_RESP_CORRUPT

DHCP_DDNS Request ID %1: received a corrupt response from the DNS server, %2, while replacing reverse address mapping for FQDN, %3

This is an error message issued when the response received by DHCP_DDNS, to a update request to replace a reverse address, is mangled or malformed. The application will retry against the same server or others as appropriate.

16.85 DHCP_DDNS_REVERSE_REPLACE_TIMEOUT

DHCP_DDNS Request ID %1: timed out waiting for a response to reverse mapping replacement for FQDN %2 to DNS server %3

This is an error message issued when no response is received from the DNS server before exceeding dns-server-timeout while DHCP_DDNS is carrying out a reverse mapping replacement. The application will retry against the same server or others as appropriate.

16.86 DHCP_DDNS_REV_REQUEST_IGNORED

Request ID %1: Reverse updates are disabled, the reverse portion of request will be ignored: %2

Logged at debug log level 55. This is a debug message issued when reverse DNS updates are disabled and DHCP_DDNS receives an update request containing a reverse DNS update. The reverse update will not be performed.

16.87 DHCP_DDNS_RUN_EXIT

application is exiting the event loop

Logged at debug log level 0. This is a debug message issued when the DHCP-DDNS server exits its event loop.

16.88 DHCP_DDNS_SECURITY_CHECKS_DISABLED

Invoked with command line option -X, Security checks are disabled!!

This warning is emitted when internal security checks normally performed by kea-dhcp-ddns have been disabled via command line option '-X'. This means the server is not enforcing restrictions on resource paths or permissions. This mode of operation may expose your environment to security vulnerabilities and should only be used after consideration.

16.89 DHCP_DDNS_SHUTDOWN_COMMAND

application received shutdown command with args: %1

Logged at debug log level 0. This is a debug message issued when the application has been instructed to shut down by the controller.

16.90 DHCP_DDNS_STARTED

Kea DHCP-DDNS server version %1 started

This informational message indicates that the DHCP-DDNS server has processed all configuration information and is ready to begin processing. The version is also printed.

16.91 DHCP_DDNS_STARTING_TRANSACTION

Request ID %1:

Logged at debug log level 50. This is a debug message issued when DHCP-DDNS has begun a transaction for a given request.

16.92 DHCP_DDNS_STATE_MODEL_UNEXPECTED_ERROR

Request ID %1: application encountered an unexpected error while carrying out a NameChangeRequest: %2

This is error message issued when the application fails to process a NameChangeRequest correctly. Some or all of the DNS updates requested as part of this update did not succeed. This is a programmatic error and should be reported.

16.93 DHCP_DDNS_TRANS_SEND_ERROR

Request ID %1: application encountered an unexpected error while attempting to send a DNS update: %2

This is error message issued when the application is able to construct an update message but the attempt to send it suffered an unexpected error. This is most likely a programmatic error, rather than a communications issue. Some or all of the DNS updates requested as part of this request did not succeed.

16.94 DHCP_DDNS_TSIG_SECRET_SECURITY_WARNING

use of clear text TSIG 'secret' is NOT SECURE: %1

This warning message is issued when security enforcement is disabled and TSIG key configuration uses clear text 'secret' rather than 'secret-file'. The server will still use the key as configured but is warning that doing so may pose a security risk.

16.95 DHCP_DDNS_UDP_SENDER_WATCH_SOCKET_CLOSE_ERROR

```
watch socket failed to close: %1
```

This is an error message that indicates the application was unable to close the inbound or outbound side of a NCR sender's watch socket. While technically possible the error is highly unlikely to occur and should not impair the application's ability to process requests.

16.96 DHCP_DDNS_UNCAUGHT_NCR_RECV_HANDLER_ERROR

```
unexpected exception thrown from the application receive completion handler: %1
```

This is an error message that indicates that an exception was thrown but not caught in the application's request receive completion handler. This is a programmatic error that needs to be reported. Dependent upon the nature of the error the application may or may not continue operating normally.

16.97 DHCP_DDNS_UNCAUGHT_NCR_SEND_HANDLER_ERROR

```
unexpected exception thrown from the DHCP-DDNS client send completion handler: %1
```

This is an error message that indicates that an exception was thrown but not caught in the application's send completion handler. This is a programmatic error that needs to be reported. Dependent upon the nature of the error the client may or may not continue operating normally.

16.98 DHCP_DDNS_UPDATE_REQUEST_SENT

```
Request ID %1: %2 to server: %3
```

Logged at debug log level 50. This is a debug message issued when DHCP_DDNS sends a DNS request to a DNS server.

16.99 DHCP_DDNS_UPDATE_RESPONSE_RECEIVED

```
Request ID %1: to server: %2 status: %3
```

Logged at debug log level 50. This is a debug message issued when DHCP_DDNS receives sends a DNS update response from a DNS server.

16.100 DHCP_DELETE_ALL_EXTERNAL_SOCKETS_BAD_THREAD

```
Attempted to unregister external sockets from different thread %1 than main thread %2
```

This error message indicates that a different thread than the main thread has deleted all external sockets. This is a programming error and should be fixed. Only the main thread is allowed to perform operations on the external sockets. The respective thread ids are included in the message.

16.101 DHCP_DELETE_EXTERNAL_SOCKET_BAD_THREAD

```
Attempted to unregister external socket %1 from different thread %2 than main thread %3
```

This error message indicates that a different thread than the main thread has unregistered an external socket. This is a programming error and should be fixed. Only the main thread is allowed to perform operations on the external sockets. The file descriptor and the respective thread ids are included in the message.

16.102 DHCP_DELETE_EXTERNAL_SOCKET_NOT_FOUND

Deleting a not found external socket %1

This warning message indicates that an external socket was deleted but it can't be found i.e. adds and deletes are not correctly balanced.

16.103 DHCP_IFACE_OPEN_SOCKET

Opened socket on the interface %1 with address %2 and port %3

Logged at debug log level 40. This debug message indicates that a socket has been opened for a specific interface. The interface name, address and port are logged.

16.104 DHCP_IFACE_SOCKET_ERROR

Got an error on the interface socket %1 of interface %2: %3

This error message indicates that an error was raised on an interface socket. The file descriptor, interface name and error message are displayed.

16.105 DHCP_RECEIVE4_UNKNOWN

Received data over unknown socket

This warning message indicates that the file descriptor event handler returns with received data but it was not possible to find which one.

16.106 DHCP_RECEIVE6_UNKNOWN

Received data over unknown socket

This warning message indicates that the file descriptor event handler returns with received data but it was not possible to find which one.

EVAL

17.1 EVAL_DEBUG_AND

%1: Popping %2 and %3 pushing %4

Logged at debug log level 55. This debug message indicates that two values are popped from the value stack. They are then combined via logical "and" and the result is pushed onto the value stack.

17.2 EVAL_DEBUG_BRANCH

Branching to %1

Logged at debug log level 55. This debug message indicates that an unconditional branch is performed to the displayed target.

17.3 EVAL_DEBUG_CONCAT

%1: Popping %2 and %3 pushing %4

Logged at debug log level 55. This debug message indicates that the two strings are being popped off of the stack. They are then concatenated and the resulting string is pushed onto the stack. The strings are displayed in hex.

17.4 EVAL_DEBUG_EQUAL

%1: Popping %2 and %3 pushing result %4

Logged at debug log level 55. This debug message indicates that the two strings are being popped off of the value stack and the result of comparing them is being pushed onto the value stack. The strings are displayed in hex.

17.5 EVAL_DEBUG_HEXSTRING

%1: Pushing hex string %2

Logged at debug log level 55. This debug message indicates that the given binary string is being pushed onto the value stack. The string is displayed in hex.

17.6 EVAL_DEBUG_IFELSE_FALSE

%1: Popping %2 (false) and %3, leaving %4

Logged at debug log level 55. This debug message indicates that the condition is false so the iftrue branch value is removed and the ifelse branch value is left on the value stack.

17.7 EVAL_DEBUG_IFELSE_TRUE

%1: Popping %2 (true) and %3, leaving %4

Logged at debug log level 55. This debug message indicates that the condition is true so the ifelse branch value is removed and the iftrue branch value is left on the value stack.

17.8 EVAL_DEBUG_INT16TOTEXT

%1: Pushing Int16 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 16 bit integer.

17.9 EVAL_DEBUG_INT32TOTEXT

%1: Pushing Int32 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 32 bit integer.

17.10 EVAL_DEBUG_INT8TOTEXT

%1: Pushing Int8 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents an 8 bit integer.

17.11 EVAL_DEBUG_IPADDRESS

%1: Pushing IPAddress %2

Logged at debug log level 55. This debug message indicates that the given binary string is being pushed onto the value stack. This represents either an IPv4 or IPv6 address. The string is displayed in hex.

17.12 EVAL_DEBUG_IPADDRESSTOTEXT

%1: Pushing IPAddress %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents either an IPv4 or IPv6 address.

17.13 EVAL_DEBUG_LCASE

```
%1: Popping string %2 and pushing converted value to lower case %3
```

Logged at debug log level 55. This debug message indicates that the given string representation is being converted to lower case and pushed onto the value stack.

17.14 EVAL_DEBUG_MATCH

```
Matching '%1' on %2, result %3
```

Logged at debug log level 55. This debug message indicates that the given regular expression was matched with the popped value. The result was pushed onto the value stack.

17.15 EVAL_DEBUG_MATCH_ERROR

```
Matching '%1' on %2 raised an error: %3
```

This error message indicates that an error occurred while evaluating the given regular expression against the popped value.

17.16 EVAL_DEBUG_MEMBER

```
%1: Checking membership of '%2', pushing result %3
```

Logged at debug log level 55. This debug message indicates that the membership of the packet for the client class was checked.

17.17 EVAL_DEBUG_NOT

```
%1: Popping %2 pushing %3
```

Logged at debug log level 55. This debug message indicates that the first value is popped from the value stack, negated and then pushed onto the value stack. The string is displayed in text.

17.18 EVAL_DEBUG_OPTION

```
%1: Pushing %2 with value %3
```

Logged at debug log level 55. This debug message indicates that the given string representing the value of the requested option is being pushed onto the value stack. The string may be the text or binary value of the string based on the representation type requested (.text or .hex) or "true" or "false" if the requested type is .exists. The option code may be for either an option or a sub-option as requested in the classification statement.

17.19 EVAL_DEBUG_OR

```
%1: Popping %2 and %3 pushing %4
```

Logged at debug log level 55. This debug message indicates that two values are popped from the value stack. They are then combined via logical "or" and the result is pushed onto the value stack. The string is displayed in text.

17.20 EVAL_DEBUG_PKT

%1: Pushing PKT meta data %2 with value %3

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested meta data is being pushed onto the value stack. The string is displayed in hex at the exception of interface name.

17.21 EVAL_DEBUG_PKT4

%1: Pushing PKT4 field %2 with value %3

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

17.22 EVAL_DEBUG_PKT6

%1: Pushing PKT6 field %2 with value %3

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

17.23 EVAL_DEBUG_POP_AND_BRANCH_FALSE

Value is false: branching to %1

Logged at debug log level 55. This debug message indicates that a branch on false condition is performed to the displayed target.

17.24 EVAL_DEBUG_POP_OR_BRANCH_FALSE

Value is false: keeping it and branching to %1

Logged at debug log level 55. This debug message indicates that a branch on false condition is performed to the displayed target.

17.25 EVAL_DEBUG_POP_OR_BRANCH_TRUE

Value is true: keeping it and branching to %1

Logged at debug log level 55. This debug message indicates that a branch on true condition is performed to the displayed target.

17.26 EVAL_DEBUG_RELAY6

%1: Pushing PKT6 relay field %2 nest %3 with value %4

Logged at debug log level 55. This debug message indicates that the given binary string representing the value of the requested field is being pushed onto the value stack. The string is displayed in hex.

17.27 EVAL_DEBUG_RELAY6_RANGE

%1: Pushing PKT6 relay field %2 nest %3 with value %4

Logged at debug log level 55. This debug message is generated if the nest field is out of range. The empty string will always be the value pushed onto the stack.

17.28 EVAL_DEBUG_SPLIT

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that three values are being popped from the stack and a result is being pushed onto the stack. The values being popped are the field, delimiter and string. The result is the extracted field which is pushed onto the stack. The strings are displayed in hex.

17.29 EVAL_DEBUG_SPLIT_DELIM_EMPTY

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that the delimiter popped from the stack was empty and so the result will be the entire string. The field, delimiter and string are still popped from the stack and the result is still pushed.

17.30 EVAL_DEBUG_SPLIT_EMPTY

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that the string popped from the stack was empty and so the result will also be empty. The field, delimiter and string are still popped from the stack and the result is still pushed.

17.31 EVAL_DEBUG_SPLIT_FIELD_OUT_OF_RANGE

%1: Popping field %2, delimiters %3, string %4, pushing result %5

Logged at debug log level 55. This debug message indicates that the field is either less than one or larger than the number of fields in the string popped from the stack. The result will be empty. The field, delimiter and string are still popped from the stack and the result is still pushed.

17.32 EVAL_DEBUG_STRING

%1: Pushing text string %2

Logged at debug log level 55. This debug message indicates that the given text string is being pushed onto the value stack. The string is displayed in text.

17.33 EVAL_DEBUG_SUBSTRING

%1: Popping length %2, start %3, string %4 pushing result %5

Logged at debug log level 55. This debug message indicates that three values are being popped from the value stack and a result is being pushed onto the value stack. The values being popped are the starting point and length of a substring to extract from the given string. The resulting string is pushed onto the stack. The strings are displayed in hex.

17.34 EVAL_DEBUG_SUBSTRING_EMPTY

%1: Popping length %2, start %3, string %4 pushing result %5

Logged at debug log level 55. This debug message indicates that the string popped from the stack was empty and so the result will also be empty. The start, length and string are still popped from the stack and the result is still pushed.

17.35 EVAL_DEBUG_SUBSTRING_RANGE

%1: Popping length %2, start %3, string %4 pushing result %5

Logged at debug log level 55. This debug message indicates that the value of start is outside of the string and an empty result will be pushed onto the stack. The start, length and string are still popped from the stack and the result is still pushed. The strings are displayed in hex.

17.36 EVAL_DEBUG_TOHEXSTRING

%1: Popping binary value %2 and separator %3, pushing result %4

Logged at debug log level 55. This debug message indicates that two values are being popped from the value stack and a result is being pushed onto the value stack. The values being popped are the binary value to convert and the separator. The binary value is converted to its hexadecimal string representation and pushed onto the stack. The binary value is displayed in hex.

17.37 EVAL_DEBUG_UCASE

%1: Popping string %2 and pushing converted value to upper case %3

Logged at debug log level 55. This debug message indicates that the given string representation is being converted to upper case and pushed onto the value stack.

17.38 EVAL_DEBUG_UINT16TOTEXT

%1: Pushing UInt16 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 16 bit unsigned integer.

17.39 EVAL_DEBUG_UINT32TOTEXT

%1: Pushing UInt32 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents a 32 bit unsigned integer.

17.40 EVAL_DEBUG_UINT8TOTEXT

%1: Pushing UInt8 %2

Logged at debug log level 55. This debug message indicates that the given address string representation is being pushed onto the value stack. This represents an 8 bit unsigned integer.

17.41 EVAL_DEBUG_VENDOR_CLASS_DATA

```
%1: Data %2 (out of %3 received) in vendor class found, pushing result '%4'
```

Logged at debug log level 55. This debug message indicates that vendor class option was found and passed enterprise-id checks and has sufficient number of data chunks. The total number of chunks and value pushed are reported as debugging aid.

17.42 EVAL_DEBUG_VENDOR_CLASS_DATA_NOT_FOUND

```
%1: Requested data index %2, but option with enterprise-id %3 has only %4 data tuple(s), pushing result '%5'
```

Logged at debug log level 55. This debug message indicates that vendor class option was found and passed enterprise-id checks, but does not have sufficient number of data chunks. Note that the index starts at 0, so there has to be at least (index + 1) data chunks.

17.43 EVAL_DEBUG_VENDOR_CLASS_ENTERPRISE_ID

```
%1: Pushing enterprise-id %2 as result 0x%3
```

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was found and its enterprise-id is being reported.

17.44 EVAL_DEBUG_VENDOR_CLASS_ENTERPRISE_ID_MISMATCH

```
%1: Was looking for %2, option had %3, pushing result '%4'
```

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was found, but has different enterprise-id than specified in the expression.

17.45 EVAL_DEBUG_VENDOR_CLASS_EXISTS

```
%1: Option with enterprise-id %2 found, pushing result '%3'
```

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was found.

17.46 EVAL_DEBUG_VENDOR_CLASS_NO_OPTION

```
%1: Option with code %2 missing, pushing result '%3'
```

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor class option was not found.

17.47 EVAL_DEBUG_VENDOR_ENTERPRISE_ID

```
%1: Pushing enterprise-id %2 as result 0x%3
```

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor option was found and its enterprise-id is being reported.

17.48 EVAL_DEBUG_VENDOR_ENTERPRISE_ID_MISMATCH

%1: Was looking for %2, option had %3, pushing result '%4'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor option was found, but has different enterprise-id than specified in the expression.

17.49 EVAL_DEBUG_VENDOR_EXISTS

%1: Option with enterprise-id %2 found, pushing result '%3'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor option was found.

17.50 EVAL_DEBUG_VENDOR_NO_OPTION

%1: Option with code %2 missing, pushing result '%3'

Logged at debug log level 55. This debug message indicates that the expression has been evaluated and vendor option was not found.

18.1 FLEX_ID_CID_AS_RFC4361_DUID_ENABLED

```
cid-as-rfc4361-duid is true.
```

Logged at debug log level 40. This debug message is issued to indicate that the library will format the new client identifier as containing a DUID per RFC 4361. This applies to v4 client packets only.

18.2 FLEX_ID_CID_AS_RFC4361_DUID_JSON_TYPE

```
the cid-as-rfc4361-duid is %1 but expected boolean value
```

This error message is printed when the flex-id library is being loaded, but the cid-as-rfc4361-duid parameter is malformed, i.e. it has a different type than expected. It is expected to be a boolean value.

18.3 FLEX_ID_EXPRESSION_EVALUATED

```
Expression evaluated for packet to "%1" (size: %2)
```

Logged at debug log level 40. This debug message is printed every time a packet evaluation is successful. This means that the identifier expression has been generated. Note that depending on the expression and content of the incoming packet, the expression may be evaluated to an empty string.

18.4 FLEX_ID_EXPRESSION_EVALUATED_NP

```
Expression evaluated for packet to 0x%1 (size: %2)
```

Logged at debug log level 40. This debug message is printed every time a packet evaluation is successful. This means that the identifier expression has been generated. As it is not printable it is converted to hexadecimal.

18.5 FLEX_ID_EXPRESSION_HEX

```
evaluated expression in hexadecimal form "%1"
```

Logged at debug log level 40. This debug message provides a hexadecimal representation of the evaluated expression. This is useful for debugging purposes because further logs use hexadecimal format for logging.

18.6 FLEX_ID_EXPRESSION_INVALID_JSON_TYPE

The identifier-expression is %1, but expected JSON string

This error message is printed when the flex-id library is being loaded, but the expression used to generate the identifier is malformed. It has a different JSON type (e.g. is a map) rather than expected string.

18.7 FLEX_ID_EXPRESSION_PARSE_FAILED

The identifier-expression is [%1], but fails to parse with error: %2

This error message is printed when the flex-id library is being loaded, but the expression used to generate the identifier is malformed. It failed to parse.

18.8 FLEX_ID_IGNORE_IAID_APPLIED_ON_NA

the ignore-iaid has changed IAID (%1) to 0 for the IA_NA option.

Logged at debug log level 40. This DEBUG message is printed when the flex-id library did apply the ignore-iaid flag and changed IAID to 0 because the received packet contains exactly one IA_NA.

18.9 FLEX_ID_IGNORE_IAID_APPLIED_ON_PD

the ignore-iaid has changed IAID (%1) to 0 for the IA_PD option.

Logged at debug log level 40. This DEBUG message is printed when the flex-id library did apply the ignore-iaid flag and changed IAID to 0 because the received packet contains exactly one IA_PD.

18.10 FLEX_ID_IGNORE_IAID_ENABLED

the ignore-iaid is set. It only has an effect on clients with at most one IA_NA and one IA_PD.

This WARNING message is printed when the flex-id library is being loaded, and the ignore-iaid parameter is set. This flag will enable the server to drop packets which contain more than one IA_NA and one IA_PD.

18.11 FLEX_ID_IGNORE_IAID_JSON_TYPE

the ignore-iaid is %1 but expected boolean value

This error message is printed when the flex-id library is being loaded, but the ignore-iaid parameter is malformed, i.e. it has a different type than expected. It is expected to be a boolean value.

18.12 FLEX_ID_IGNORE_IAID_NOT_APPLIED_ON_NA

the ignore-iaid was not applied on the packet because it contains more than one IA_NA.

Logged at debug log level 40. This WARNING message is printed when the flex-id library did not apply the ignore-iaid flag because the received packet contains more than one IA_NA.

18.13 FLEX_ID_IGNORE_IAID_NOT_APPLIED_ON_PD

the ignore-iaid was not applied on the packet because it contains more than one IA_PD.

Logged at debug log level 40. This WARNING message is printed when the flex-id library did not apply the ignore-iaid flag because the received packet contains more than one IA_PD.

18.14 FLEX_ID_LOAD_ERROR

An error occurred loading the library %1

This error message will be printed when an error is encountered during loading of the library. Details of the problem are printed as parameter to this message.

18.15 FLEX_ID_NO_IDENTIFIER_EXPRESSION

identifier-expression is either not specified or empty

Logged at debug log level 40. This debug message is printed when the flex-id library is being loaded, but the expression used to generate the identifier was either omitted or is empty. The library will load, but will neither generate nor replace client identifiers. Typically this occurs when users are only interested in using ignore-iaid, which operates independently of the expression.

18.16 FLEX_ID_REPLACE_CLIENT_ID_JSON_TYPE

the replace-client-id is %1 but expected boolean value

This error message is printed when the flex-id library is being loaded, but the replace-client-id parameter is malformed, i.e. it has a different type than expected. It is expected to be a boolean value.

18.17 FLEX_ID_RESTORE_CLIENT_ID

restoring original client identifier '%1' in the response

Logged at debug log level 40. This debug message is issued when the original (client supplied) client identifier is restored into the server's response.

18.18 FLEX_ID_RESTORE_DUID

restoring original DUID "%1" in the response

Logged at debug log level 40. This debug message is issued when the original (client supplied) client identifier is restored into the server's response.

18.19 FLEX_ID_UNLOAD

Flex-id library has been unloaded.

This informational message signifies that the flexible-identifier library has been unloaded.

18.20 FLEX_ID_USED_AS_CLIENT_ID

using flexible identifier "%1" as client identifier

Logged at debug log level 40. This debug message is issued to indicate that the library is removing client supplied client identifier from the received message and is inserting flexible identifier based client identifier instead. The server will use this new client identifier for processing the packet. The original client identifier will be restored in the pkt4_send callout and sent back to the client.

18.21 FLEX_ID_USED_AS_DUID

using flexible identifier "%1" as DUID

Logged at debug log level 40. This debug message is issued to indicate that the library is removing client supplied DUID from the received message and is inserting flexible identifier based DUID instead. The server will use this new DUID for processing the packet. The original DUID will be restored in the pkt6_send callout and sent back to the client.

18.22 FLEX_OPTION_CONFIG_SUB_USELESS_CLASS

For the sub-option code %1 in option code %2 the client class %3 is required before classification for a query destination

This warning message indicates the config specifies a class requirement when the destination is the query but the callout point for patching queries is before the classification so it will very likely not work as expected. The codes of the sub-option and option, and the client class name are displayed.

18.23 FLEX_OPTION_CONFIG_SUB_USELESS_MEMBER

For the sub-option code %1 in option code %2 the member expression %3 is evaluated before classification for a query destination

This warning message indicates the config specifies an expression with a member clause when the destination is the query but the callout point for patching queries is before the classification so it will very likely not work as expected. The codes of the sub-option and option, and the expression are displayed.

18.24 FLEX_OPTION_CONFIG_USELESS_CLASS

For the option code %1 the client class %2 is required before classification for a query destination

This warning message indicates the config specifies a class requirement when the destination is the query but the callout point for patching queries is before the classification so it will very likely not work as expected. The code of the option and the client class name are displayed.

18.25 FLEX_OPTION_CONFIG_USELESS_MEMBER

For the option code %1 the member expression %2 is evaluated before classification for a query destination

This warning message indicates the config specifies an expression with a member clause when the destination is the query but the callout point for patching queries is before the classification so it will very likely not work as expected. The code of the option and the expression are displayed.

18.26 FLEX_OPTION_LOAD_ERROR

```
loading Flex Option hooks library failed: %1
```

This error message indicates an error during loading the Flex Option hooks library. The details of the error are provided as argument of the log message.

18.27 FLEX_OPTION_PROCESS_ADD

```
Added the option code %1 with value %2
```

Logged at debug log level 40. This debug message is printed when an option was added into the response packet. The option code and the value (between quotes if printable, in hexadecimal if not) are provided.

18.28 FLEX_OPTION_PROCESS_CLIENT_CLASS

```
Skip processing of the option code %1 for class '%2'
```

Logged at debug log level 40. This debug message is printed when the processing for an option is skipped because the query does not belongs to the client class. The option code and the client class name are provided.

18.29 FLEX_OPTION_PROCESS_ERROR

```
An error occurred processing query %1: %2
```

This error message indicates an error during processing of a query by the Flex Option hooks library. The client identification information from the query and the details of the error are provided as arguments of the log message.

18.30 FLEX_OPTION_PROCESS_REMOVE

```
Removed option code %1
```

Logged at debug log level 40. This debug message is printed when an option was removed from the response packet. The option code is provided.

18.31 FLEX_OPTION_PROCESS_SUB_ADD

```
Added the sub-option code %1 in option code %2 with value %3
```

Logged at debug log level 40. This debug message is printed when an sub-option was added into the response packet. The sub-option and container option codes, and the value (between quotes if printable, in hexadecimal if not) are provided.

18.32 FLEX_OPTION_PROCESS_SUB_CLIENT_CLASS

```
Skip processing of the sub-option code %1 in option code %2 for class '%3'
```

Logged at debug log level 40. This debug message is printed when the processing for a sub-option is skipped because the query does not belongs to the client class. The sub-option and container option codes, and the client class name are provided.

18.33 FLEX_OPTION_PROCESS_SUB_REMOVE

Removed sub-option code %1 in option code %2

Logged at debug log level 40. This debug message is printed when a sub-option was removed from the response packet. The sub-option and container option codes are provided.

18.34 FLEX_OPTION_PROCESS_SUB_SUPERSEDE

Supersedes the sub-option code %1 in option code %2 with value %3

Logged at debug log level 40. This debug message is printed when a sub-option was superseded into the response packet. The sub-option and container option codes, and the value (between quotes if printable, in hexadecimal if not) are provided.

18.35 FLEX_OPTION_PROCESS_SUPERSEDE

Supersedes the option code %1 with value %2

Logged at debug log level 40. This debug message is printed when an option was superseded into the response packet. The option code and the value (between quotes if printable, in hexadecimal if not) are provided.

18.36 FLEX_OPTION_PROCESS_VENDOR_ID_MISMATCH

Skip processing of vendor option code %1 with vendor id %2 not matching wanted %3

Logged at debug log level 40. This debug message is printed when a sub-option of a vendor option is processed but vendor ids do not match. The code of the vendor option and the two vendor ids are provided.

18.37 FLEX_OPTION_UNLOAD

Flex Option hooks library has been unloaded

This info message indicates that the Flex Option hooks library has been unloaded.

FUZZ

19.1 FUZZ_DATA_READ

```
read %1 byte(s) from AFL via stdin
```

Logged at debug log level 50. A debug message output to indicate how much data has been received from the fuzzer via stdin

19.2 FUZZ_INIT_COMPLETE

```
fuzz initialization complete: interface %1, address %2, port %3, max loops %4
```

An informational message output when the fuzzing initialization function has completed successfully. The parameters listed are those which must be/can be set via environment variables.

19.3 FUZZ_INIT_FAIL

```
fuzz initialization failure, reason: %1
```

An error message reported if the fuzzing initialization failed. The reason for the failure is given in the message.

19.4 FUZZ_READ_FAIL

```
error reading input from fuzzer: %1
```

This error is reported if the read of data from the fuzzer (which is received over stdin) fails, or if a read returns zero bytes. If this occurs, the thread will sleep for a short period before retrying the read. The message includes the reason for the failure.

19.5 FUZZ_SEND

```
sent %1 byte(s) to the socket connected to the Kea interface
```

Logged at debug log level 50. A debug message stating that the sendto() call in the main fuzzing function has successfully completed and reporting the number of bytes sent. This call sends data received from AFL to the port on which Kea is listening.

19.6 FUZZ_SEND_ERROR

failed to send data to Kea input socket: %1

This error will be reported if the `sendto()` call in the fuzzing thread (which sends data received from AFL to the socket on which Kea is listening) fails. The reason for the failure is given in the message. The fuzzing code will attempt to continue from this, but it may cause the fuzzing process to fail.

19.7 FUZZ_SHORT_SEND

expected to send %1 bytes to Kea input socket but only sent %2

A warning message that is output if the `sendto()` call (used to send data from the fuzzing thread to the main Kea processing) did not send as much data as that read from AFL. This may indicate a problem in the underlying communications between the fuzzing thread and the main Kea processing.

19.8 FUZZ_SOCKET_CREATE_FAIL

failed to crease socket for use by fuzzing thread: %1

An error message output when the fuzzing code has failed to create a socket through which it will copy data received on stdin from the AFL fuzzer to the port on which Kea is listening. The program will most likely hang if this occurs.

20.1 GSS_TSIG_COMMAND_PROCESSED_FAILED

command_processed callout failed: %1.

This error message is issued when the callout for the command_processed callout point failed. The argument contains a reason for the error.

20.2 GSS_TSIG_IGNORED_BAD_DIRECTION

ignored bad direction verify failure.

This info message indicates that a verify failed because the message was in the wrong direction but this failure was ignored.

20.3 GSS_TSIG_LOAD_FAILED

GSS-TSIG hooks library failed to load: %1.

This error message indicates that an error occurred attempting to load the GSS-TSIG hooks library. The argument details the error.

20.4 GSS_TSIG_LOAD_OK

GSS-TSIG hooks library loaded successfully.

This info message indicates that the GSS-TSIG hooks library has been loaded successfully.

20.5 GSS_TSIG_MANAGER_STARTED

hooks library GSS-TSIG key periodic manager started.

Logged at debug log level 40. This debug message is issued when the GSS-TSIG key periodic manager has started.

20.6 GSS_TSIG_MANAGER_STOPPED

hooks library GSS-TSIG key periodic manager stopped.

Logged at debug log level 40. This debug message is issued when the GSS-TSIG key periodic manager has stopped.

20.7 GSS_TSIG_MANAGER_STOP_ERROR

```
manager stop error: %1
```

This error message is issued when the GSS-TSIG key periodic manager has stopped but an error is detected. The error message in the argument gives details about the problem.

20.8 GSS_TSIG_MANAGER_STOP_GENERAL_ERROR

```
manager stop general error
```

This error message is issued when the GSS-TSIG key periodic manager has stopped but a general error is detected.

20.9 GSS_TSIG_NEW_KEY

```
new GSS-TSIG key '%1' was created.
```

Logged at debug log level 40. This info message indicates that the GSS-TSIG hooks library has created a new GSS-TSIG key. The name of the new key is displayed.

20.10 GSS_TSIG_NEW_KEY_SETUP_FAILED

```
new GSS-TSIG key '%1' setup failed: %2.
```

This warning message is issued when the setup of a new GSS-TSIG key failed. The name of the new key and the error are displayed.

20.11 GSS_TSIG_NEW_KEY_SETUP_SUCCEED

```
new GSS-TSIG key '%1' setup succeeded.
```

Logged at debug log level 40. This debug message is issued when the setup of a new GSS-TSIG key successfully finished. The name of the new key is displayed.

20.12 GSS_TSIG_OLD_KEY_REMOVED

```
%1 old GSS-TSIG keys were removed
```

Logged at debug log level 40. This debug message is issued when some old keys (older than 2 times the maximum TKEY lifetime) were removed. The number of removed keys is displayed.

20.13 GSS_TSIG_UNLOAD_OK

```
GSS-TSIG hooks library unloaded successfully.
```

This info message indicates that the GSS-TSIG hooks library has been unloaded successfully.

20.14 GSS_TSIG_VERIFIED

```
GSS-TSIG verify succeeded.
```

Logged at debug log level 40. This debug message is issued when GSS-TSIG verification succeeded.

20.15 GSS_TSIG_VERIFY_FAILED

GSS-TSIG verify failed: %1.

This info message indicates that GSS-TSIG verification failed. The argument details the error.

21.1 HA_BUFFER4_RECEIVE_FAILED

```
buffer4_receive callout failed: %1
```

This error message is issued when the callout for the buffer4_receive hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

21.2 HA_BUFFER4_RECEIVE_NOT_FOR_US

```
%1: dropping query to be processed by another server
```

Logged at debug log level 40. This debug message is issued when the received DHCPv4 query is dropped by this server because it should be served by another server. This is the case when the remote server was designated to process the packet as a result of load balancing or because it is a primary server in the hot standby configuration. The argument provides client identification information retrieved from the query.

21.3 HA_BUFFER4_RECEIVE_PACKET_OPTIONS_SKIPPED

```
an error unpacking an option, caused subsequent options to be skipped: %1
```

Logged at debug log level 40. This debug message is issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv4 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

21.4 HA_BUFFER4_RECEIVE_UNPACK_FAILED

```
failed to parse query from %1 to %2, received over interface %3, reason: %4
```

Logged at debug log level 40. This debug message is issued when received DHCPv4 query is malformed and can't be parsed by the buffer4_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

21.5 HA_BUFFER6_RECEIVE_FAILED

```
buffer6_receive callout failed: %1
```

This error message is issued when the callout for the buffer6_receive hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

21.6 HA_BUFFER6_RECEIVE_NOT_FOR_US

%1: dropping query to be processed by another server

Logged at debug log level 40. This debug message is issued when the received DHCPv6 query is dropped by this server because it should be served by another server. This is the case when the remote server was designated to process the packet as a result of load balancing or because it is a primary server in the hot standby configuration. The argument provides client identification information retrieved from the query.

21.7 HA_BUFFER6_RECEIVE_PACKET_OPTIONS_SKIPPED

an error unpacking an option, caused subsequent options to be skipped: %1

Logged at debug log level 40. This debug message is issued when an option failed to unpack correctly, making it impossible to unpack the remaining options in the DHCPv6 query. The server will still attempt to service the packet. The sole argument provides a reason for unpacking error.

21.8 HA_BUFFER6_RECEIVE_UNPACK_FAILED

failed to parse query from %1 to %2, received over interface %3, reason: %4

Logged at debug log level 40. This debug message is issued when received DHCPv6 query is malformed and can't be parsed by the buffer6_receive callout. The query will be dropped by the server. The first three arguments specify source IP address, destination IP address and the interface. The last argument provides a reason for failure.

21.9 HA_COMMAND_PROCESSED_FAILED

command_processed callout failed: %1

This error message is issued when the callout for the command_processed hook point failed. The argument contains a reason for the error.

21.10 HA_COMMUNICATION_INTERRUPTED

%1: communication with %2 is interrupted

This warning message is issued by the server which discovered that the communication to the active partner has been interrupted for a time period longer than the configured heartbeat-delay time. At this stage the server starts the failover procedure by monitoring the DHCP traffic sent to the partner and checking whether the partner server responds to this traffic. If the max-unacked-clients value is set to 0 such verification is disabled in which case the server will transition to the partner-down state.

21.11 HA_COMMUNICATION_INTERRUPTED_CLIENT4

%1: new client %2 attempting to get a lease from the partner

This informational message is issued when the surviving server observes a DHCP packet sent to the partner with which the communication is interrupted. The client whose packet is observed is not yet considered "unacked" because the secs field value does not exceed the configured threshold specified with max-ack-delay.

21.12 HA_COMMUNICATION_INTERRUPTED_CLIENT4_UNACKED

```
%1: partner server failed to respond to %2, %3 clients unacked so far, %4 clients left before transitioning to the partner-down state
```

This informational message is issued when the surviving server determines that its partner failed to respond to the DHCP query and that this client is considered to not be served by the partner. The surviving server counts such clients and if the number of such clients exceeds the max-unacked-clients threshold, the server will transition to the partner-down state. The first argument specifies the relationship name. The second argument contains client identification information. The third argument specifies the number of clients to which the server has failed to respond. The fourth argument specifies the number of additional clients which, if not provisioned, will cause the server to transition to the partner-down state.

21.13 HA_COMMUNICATION_INTERRUPTED_CLIENT6

```
%1: new client %2 attempting to get a lease from the partner
```

This informational message is issued when the surviving server observes a DHCP packet sent to the partner with which the communication is interrupted. The client whose packet is observed is not yet considered "unacked" because the elapsed time option value does not exceed the configured threshold specified with max-ack-delay. The sole argument specifies client identification information.

21.14 HA_COMMUNICATION_INTERRUPTED_CLIENT6_UNACKED

```
%1: partner server failed to respond to %2, %3 clients unacked so far, %4 clients left before transitioning to the partner-down state
```

This informational message is issued when the surviving server determines that its partner failed to respond to the DHCP query and that this client is considered to not be served by the partner. The surviving server counts such clients and if the number of such clients exceeds the max-unacked-clients threshold, the server will transition to the partner-down state. The first argument specifies the relationship name. The second argument contains client identification information. The third argument specifies the number of clients to which the server has failed to respond. The fourth argument specifies the number of additional clients which, if not provisioned, will cause the server to transition to the partner-down state.

21.15 HA_CONFIGURATION_FAILED

```
failed to configure High Availability hooks library: %1
```

This error message is issued when there is an error configuring the HA hooks library. The argument provides the detailed error message.

21.16 HA_CONFIGURATION_SUCCESSFUL

```
HA hook library has been successfully configured
```

This informational message is issued when the HA hook library configuration parser successfully parses and validates the new configuration.

21.17 HA_CONFIG_AUTO_FAILOVER_DISABLED

```
%1: auto-failover disabled
```

This warning message is issued to indicate that the 'auto-failover' parameter was administratively disabled for the specified server. The server will not automatically start serving partner's scope when the partner failure is detected. The server administrator will need to enable this scope manually by sending appropriate ha-scopes command.

21.18 HA_CONFIG_DHCP_MT_DISABLED

%1: HA multi-threading has been disabled, it cannot be enabled when Kea global multi-threading is disabled

This informational message is issued when HA configuration has enabled multi-threading while Kea global configuration has multi-threading disabled.

21.19 HA_CONFIG_DHCP_MT_DISABLED_AND_KEA_MT_ENABLED

%1: HA multi-threading is disabled while Kea global multi-threading is enabled which most likely cause performance degradation.

This warning message is issued when HA configuration has disabled multi-threading while Kea global configuration has multi-threading enabled. This will likely cause performance degradation.

21.20 HA_CONFIG_LEASE_SYNCING_DISABLED

%1: lease database synchronization between HA servers is disabled

This warning message is issued when the lease database synchronization is administratively disabled. This is valid configuration if the leases are replicated between lease databases via some other mechanism, e.g. SQL database replication.

21.21 HA_CONFIG_LEASE_SYNCING_DISABLED_REMINDER

%1: bypassing SYNCING state because lease database synchronization is administratively disabled

This informational message is issued as a reminder that lease database synchronization is administratively disabled and therefore the server transitions directly from the "waiting" to "ready" state.

21.22 HA_CONFIG_LEASE_UPDATES_AND_SYNCING_DIFFER

%1: unusual configuration where "send-lease-updates": %2 and "sync-leases": %3

This warning message is issued when the configuration values of the send-lease-updates and sync-leases parameters differ. This may be a valid configuration but is unusual. Normally, if the lease database with replication is in use, both values are set to false. If a lease database without replication is in use (e.g. memfile), both values are set to true. Providing different values for those parameters means that an administrator either wants the server to not synchronize leases upon startup but later send lease updates to the partner, or the lease database should be synchronized upon startup, but no lease updates are later sent as a result of leases allocation.

21.23 HA_CONFIG_LEASE_UPDATES_DISABLED

%1: lease updates will not be generated

This warning message is issued when the lease updates are administratively disabled. This is valid configuration if the leases are replicated to the partner's database via some other mechanism, e.g. SQL database replication.

21.24 HA_CONFIG_LEASE_UPDATES_DISABLED_REMINDER

%1: Lease updates are administratively disabled and will not be generated while in %2 state

This informational message is issued as a reminder that the lease updates are administratively disabled and will not be issued in the HA state to which the server has transitioned. The sole argument specifies the state into which the server has transitioned.

21.25 HA_CONFIG_SYSTEM_MT_UNSUPPORTED

%1: HA multi-threading has been disabled, auto-detection of thread support reports 0

This informational message is issued when HA multi-threading configuration has specified auto-detection for the number of threads to use and the system reports the number of concurrent threads as 0. If you know your system can support multiple threads, then you may override this condition by specifying explicit values for http-listener-threads and http-client-threads.

21.26 HA_CONTINUE_HANDLER_FAILED

ha-continue command failed: %1

This error message is issued to indicate that the ha-continue command handler failed while processing the command. The argument provides the reason for failure.

21.27 HA_DEINIT_OK

unloading High Availability hooks library successful

This informational message indicates that the High Availability hooks library has been unloaded successfully.

21.28 HA_DHCP4_START_SERVICE_FAILED

failed to start DHCPv4 HA services in dhcp4_srv_configured callout: %1

This error message is issued when an attempt to start High Availability services for the DHCPv4 server failed in the dhcp4_srv_configured callout. This is internal server error and a bug report should be created.

21.29 HA_DHCP6_START_SERVICE_FAILED

failed to start DHCPv6 HA services in dhcp6_srv_configured callout: %1

This error message is issued when an attempt to start High Availability services for the DHCPv6 server failed in the dhcp6_srv_configured callout. This is internal server error and a bug report should be created.

21.30 HA_DHCP_DISABLE_COMMUNICATIONS_FAILED

%1: failed to send request to disable DHCP service of %2: %3

This warning message indicates that there was a problem in communication with a HA peer while sending the dhcp-disable command. The first argument specifies the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

21.31 HA_DHCP_DISABLE_FAILED

%1: failed to disable DHCP service of %2: %3

This warning message indicates that a peer returned an error status code in response to a dhcp-disable command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

21.32 HA_DHCP_ENABLE_COMMUNICATIONS_FAILED

%1: failed to send request to enable DHCP service of %2: %3

This warning message indicates that there was a problem in communication with a HA peer while sending the dhcp-enable command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

21.33 HA_DHCP_ENABLE_FAILED

%1: failed to enable DHCP service of %2: %3

This warning message indicates that a peer returned an error status code in response to a dhcp-enable command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

21.34 HA_HEARTBEAT_COMMUNICATIONS_FAILED

%1: failed to send heartbeat to %2: %3

This warning message indicates that there was a problem in communication with a HA peer while sending a heartbeat. This is a first sign that the peer may be down. The server will keep trying to send heartbeats until it considers that communication is interrupted.

21.35 HA_HEARTBEAT_FAILED

%1: heartbeat to %2 failed: %3

This warning message indicates that a peer returned an error status code in response to a heartbeat. This is the sign that the peer may not function properly. The server will keep trying to send heartbeats until it considers that communication is interrupted.

21.36 HA_HEARTBEAT_HANDLER_FAILED

heartbeat command failed: %1

This error message is issued to indicate that the heartbeat command handler failed while processing the command. The argument provides the reason for failure.

21.37 HA_HIGH_CLOCK_SKEW

%1: %2, please synchronize clocks!

This warning message is issued when the clock skew between the active servers exceeds 30 seconds. The HA service continues to operate but may not function properly, especially for low lease lifetimes. The administrator should synchronize the clocks, e.g. using NTP. If the clock skew exceeds 60 seconds, the HA service will terminate.

21.38 HA_HIGH_CLOCK_SKEW_CAUSED_TERMINATION

```
%1: %2, causing HA service to terminate
```

This warning message is issued when the clock skew between the active servers exceeds 60 seconds. The HA service stops. The servers will continue to respond to the DHCP queries but won't exchange lease updates or send heartbeats. The administrator is required to synchronize the clocks and then restart the servers to resume the HA service.

21.39 HA_INIT_OK

```
loading High Availability hooks library successful
```

This informational message indicates that the High Availability hooks library has been loaded successfully. Enjoy!

21.40 HA_INVALID_PARTNER_STATE_COMMUNICATION_RECOVERY

```
%1: partner is in the communication-recovery state unexpectedly
```

This warning message is issued when a partner is in the communication-recovery state, and this server is not running in the load balancing mode. The server may only transition to the communication-recovery state when it runs in the load balancing mode. The HA mode of both servers must be the same.

21.41 HA_INVALID_PARTNER_STATE_HOT_STANDBY

```
%1: partner is in the hot-standby state unexpectedly
```

This warning message is issued when a partner is in the hot-standby state, and this server is not running in the hot standby mode. The server may only transition to the hot-standby state when it runs in the hot standby mode. The HA mode of both servers must be the same.

21.42 HA_INVALID_PARTNER_STATE_LOAD_BALANCING

```
%1: partner is in the load-balancing state unexpectedly
```

This warning message is issued when a partner is in the load-balancing state, and this server is not running in the load balancing mode. The server may only transition to the load-balancing state when it runs in the load balancing mode. The HA mode of both servers must be the same.

21.43 HA_LEASE4_EXPIRE_FAILED

```
lease4_expire callout failed: %1
```

This error message is issued when the callout for the lease4_expire hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

21.44 HA_LEASE4_EXPIRE_INVALID_HA_SERVER_NAME

%1: invalid ha-server-name value for subnet %2

This error message is issued when the reclaimed DHCPv4 lease belongs to a subnet which includes ha-server-name value in the user-context but this value is not a string or is empty. It is a server's misconfiguration. The first argument holds the lease information. The second argument is a subnet prefix.

21.45 HA_LEASE4_EXPIRE_RECLAMATION_SKIP

%1: skipping reclamation of the lease that belongs to a partner

Logged at debug log level 40. This debug message is issued when the server is in the terminated state and skips reclamation of the lease that was probably allocated by another server, or is maintained by the other server while the servers are in the HA terminated state. The argument is the lease address.

21.46 HA_LEASE4_SERVER_DECLINE_FAILED

lease4_server_decline callout failed: %1

This error message is issued when the callout for the lease4_server_decline hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

21.47 HA_LEASE6_EXPIRE_FAILED

lease4_expire callout failed: %1

This error message is issued when the callout for the lease4_expire hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

21.48 HA_LEASE6_EXPIRE_INVALID_HA_SERVER_NAME

%1: invalid ha-server-name value for subnet %2

This error message is issued when the reclaimed DHCPv6 lease belongs to a subnet which includes ha-server-name value in the user-context but this value is not a string or is empty. It is a server's misconfiguration. The first argument holds the lease information. The second argument is a subnet prefix.

21.49 HA_LEASE6_EXPIRE_RECLAMATION_SKIP

%1: skipping reclamation of the lease that belongs to a partner

Logged at debug log level 40. This debug message is issued when the server is in the terminated state and skips reclamation of the lease that was probably allocated by another server, or is maintained by the other server while the servers are in the HA terminated state. The argument is the lease address.

21.50 HA_LEASES4_COMMITTED_FAILED

```
leases4_committed callout failed: %1
```

This error message is issued when the callout for the leases4_committed hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

21.51 HA_LEASES4_COMMITTED_NOTHING_TO_UPDATE

```
%1: leases4_committed callout was invoked without any leases
```

Logged at debug log level 40. This debug message is issued when the "leases4_committed" callout returns because there are neither new leases nor deleted leases for which updates should be sent. The sole argument specifies the details of the client which sent the packet.

21.52 HA_LEASES4_COMMITTED_NO_RELATIONSHIP

```
%1: HA relationship not found: %2
```

This error message is issued when the relationship for the server name provided by the earlier callouts was not found in the HA configuration. This error is highly unlikely and rather indicates some programming error. The first argument is the client identification information. The second argument holds a more detailed error message.

21.53 HA_LEASES6_COMMITTED_FAILED

```
leases6_committed callout failed: %1
```

This error message is issued when the callout for the leases6_committed hook point failed. This includes unexpected errors like wrong arguments provided to the callout by the DHCP server (unlikely internal server error). The argument contains a reason for the error.

21.54 HA_LEASES6_COMMITTED_NOTHING_TO_UPDATE

```
%1: leases6_committed callout was invoked without any leases
```

Logged at debug log level 40. This debug message is issued when the "leases6_committed" callout returns because there are neither new leases nor deleted leases for which updates should be sent. The sole argument specifies the details of the client which sent the packet.

21.55 HA_LEASES6_COMMITTED_NO_RELATIONSHIP

```
%1: HA relationship not found: %2
```

This error message is issued when the relationship for the server name provided by the earlier callouts was not found in the HA configuration. This error is highly unlikely and rather indicates some programming error. The first argument is the client identification information. The second argument holds a more detailed error message.

21.56 HA_LEASES_BACKLOG_COMMUNICATIONS_FAILED

%1: failed to communicate with %2 while sending lease updates backlog: %3

This error message is issued to indicate that there was a communication error with a partner server while sending outstanding lease updates after resuming connection. The third argument contains a reason for the error.

21.57 HA_LEASES_BACKLOG_FAILED

%1: failed to send lease updates backlog to %2: %3

This error message is issued to indicate that sending lease updates backlog to a partner server failed. The lease updates backlog is sent to the partner after resuming temporarily broken communication with the partner. If this operation fails the server will transition to the waiting state to initiate full lease database synchronization.

21.58 HA_LEASES_BACKLOG_NOTHING_TO_SEND

%1: no leases in backlog after communication recovery

This informational message is issued when there are no outstanding leases to be sent after communication recovery with a partner. This means that the communication interruption was short enough that no DHCP clients obtained any leases from the server while it was in the communication-recovery state. The server may now transition to the load-balancing state.

21.59 HA_LEASES_BACKLOG_START

%1: starting to send %2 outstanding lease updates to %3

This informational message is issued when the server starts to send outstanding lease updates to the partner after resuming communications. The first argument specifies the local server's name. The second argument specifies the number of lease updates to be sent. The name of the partner is specified with the third argument.

21.60 HA_LEASES_BACKLOG_SUCCESS

%1: sending lease updates backlog to %2 successful in %3

This informational message is issued when server successfully completes sending lease updates backlog to the partner. The first argument specifies the local server's name. The second argument specifies the name of the remote server. The third argument specifies the duration of this operation.

21.61 HA_LEASES_SYNC_APPLIED_LEASES

%1: applied %2 leases received from the partner in the local lease database

This informational message outputs the number of leases received from the partner during the database synchronization and applied in the local database. A typical case when only some leases are applied is when the server has multiple relationships and some of the received leases belong to another relationship. The first argument specifies this server name. The second argument specifies the number of applied leases.

21.62 HA_LEASES_SYNC_COMMUNICATIONS_FAILED

```
%1: failed to communicate with %2 while syncing leases: %3
```

This error message is issued to indicate that there was a communication error with a partner server while trying to fetch leases from its lease database. The argument contains a reason for the error.

21.63 HA_LEASES_SYNC_FAILED

```
%1: failed to synchronize leases with %2: %3
```

This error message is issued to indicate that there was a problem while parsing a response from the server from which leases have been fetched for local database synchronization. The third argument contains a reason for the error.

21.64 HA_LEASES_SYNC_LEASE_PAGE_RECEIVED

```
%1: received %2 leases from %3
```

This informational message is issued during lease database synchronization to indicate that a bulk of leases have been received. The first argument specifies the local server's name. The second argument holds the count of leases received. The third argument specifies the partner server name.

21.65 HA_LEASE_SYNC_FAILED

```
%1: synchronization failed for lease: %2, reason: %3
```

This warning message is issued when creating or updating a lease in the local lease database fails. The lease information in the JSON format is provided as a first argument. The third argument provides a reason for the failure.

21.66 HA_LEASE_SYNC_STALE_LEASE4_SKIP

```
%1: skipping stale lease %2 in subnet %3
```

Logged at debug log level 40. This debug message is issued during lease database synchronization, when fetched IPv4 lease instance appears to be older than the instance in the local database. The newer instance is left in the database and the fetched lease is dropped. The remote server will still hold the older lease instance until it synchronizes its database with this server. The first argument specifies the local server's name. The second argument specifies leased address. The third argument specifies a subnet to which the lease belongs.

21.67 HA_LEASE_SYNC_STALE_LEASE6_SKIP

```
%1: skipping stale lease %2 in subnet %3
```

Logged at debug log level 40. This debug message is issued during lease database synchronization, when fetched IPv6 lease instance appears to be older than the instance in the local database. The newer instance is left in the database and the fetched lease is dropped. The remote server will still hold the older lease instance until it synchronizes its database with this server. The first argument specifies the local server's name. The second argument specifies leased address. The second argument specifies a subnet to which the lease belongs.

21.68 HA_LEASE_UPDATES_DISABLED

%1: lease updates will not be sent to the partner while in %2 state

This informational message is issued to indicate that lease updates will not be sent to the partner while the server is in the current state. The second argument specifies the server's current state name. The lease updates are still sent to the backup servers if they are configured but any possible errors in communication with the backup servers are ignored.

21.69 HA_LEASE_UPDATES_ENABLED

%1: lease updates will be sent to the partner while in %2 state

This informational message is issued to indicate that lease updates will be sent to the partner while the server is in the current state. The second specifies the server's current state name.

21.70 HA_LEASE_UPDATE_COMMUNICATIONS_FAILED

%1: failed to send lease update %2 to %3: %4

This warning message indicates that there was a problem in communication with a HA peer while processing a DHCP client query and sending lease update. The client's DHCP message will be dropped.

21.71 HA_LEASE_UPDATE_CONFLICT

%1: lease update %2 sent to %3 returned conflict status code: %4

This warning message indicates that the partner returned a conflict status code in response to a lease update. The client's DHCP message will be dropped. If the server is configured to track conflicting lease updates, it may eventually transition to the terminated state when the configured threshold is exceeded.

21.72 HA_LEASE_UPDATE_CREATE_UPDATE_FAILED_ON_PEER

%1: failed to create or update the lease having type %2 for address %3, reason: %4

This informational message is issued when one of the leases failed to be created or updated on the HA peer while processing the lease updates sent from this server. This may indicate an issue with communication between the peer and its lease database.

21.73 HA_LEASE_UPDATE_DELETE_FAILED_ON_PEER

%1: failed to delete the lease having type %2 for address %3, reason: %4

This informational message is issued when one of the leases failed to delete on the HA peer while processing lease updates sent from this server. Typically, the lease fails to delete when it doesn't exist in the peer's database.

21.74 HA_LEASE_UPDATE_FAILED

%1: lease update %2 sent to %3 failed: %4

This warning message indicates that a peer returned an error status code in response to a lease update. The client's DHCP message will be dropped.

21.75 HA_LEASE_UPDATE_REJECTS_CAUSED_TERMINATION

%1: too many rejected lease updates cause the HA service to terminate

This error message is issued when the HA service terminates because the number of lease updates for which a conflict status code was returned by the partner exceeds the limit set with max-rejected-lease-updates configuration parameter.

21.76 HA_LOAD_BALANCING_DUID_MISSING

%1: load balancing failed for the DHCPv6 message (transaction id: %2) because DUID is missing

Logged at debug log level 40. This debug message is issued when the HA hook library was unable to load balance an incoming DHCPv6 query because neither client identifier nor HW address was included in the query. The query will be dropped. The sole argument contains transaction id.

21.77 HA_LOAD_BALANCING_IDENTIFIER_MISSING

%1: load balancing failed for the DHCPv4 message (transaction id: %2) because HW address and client identifier are missing

Logged at debug log level 40. This debug message is issued when the HA hook library was unable to load balance an incoming DHCPv4 query because neither client identifier nor HW address was included in the query. The query will be dropped. The sole argument contains transaction id.

21.78 HA_LOAD_BALANCING_LEASE_DUID_MISSING

%1: load balancing failed for the DHCPv6 lease %2 because DUID is missing

Logged at debug log level 40. This debug message is issued when the HA hook library was unable to load balance a reclaimed DHCPv6 lease because client identifier was not included found in the lease.

21.79 HA_LOAD_BALANCING_LEASE_IDENTIFIER_MISSING

%1: load balancing failed for the DHCPv4 lease %2 because HW address and client identifier are missing

Logged at debug log level 40. This debug message is issued when the HA hook library was unable to load balance a reclaimed DHCPv4 lease because neither client identifier nor HW address was included in the query.

21.80 HA_LOCAL_DHCP_DISABLE

local DHCP service is disabled while the %1 is in the %2 state

This informational message is issued to indicate that the local DHCP service is disabled because the server remains in a state in which the server should not respond to DHCP clients, e.g. the server hasn't synchronized its lease database. The first argument specifies server name. The second argument specifies server's state.

21.81 HA_LOCAL_DHCP_ENABLE

local DHCP service is enabled while the %1 is in the %2 state

This informational message is issued to indicate that the local DHCP service is enabled because the server remains in a state in which it should respond to the DHCP clients. The first argument specifies server name. The second argument specifies server's state.

21.82 HA_MAINTENANCE_CANCEL_HANDLER_FAILED

ha-maintenance-cancel command failed: %1

This error message is issued to indicate that the ha-maintenance-cancel command handler failed while processing the command. The argument provides the reason for failure.

21.83 HA_MAINTENANCE_NOTIFY_CANCEL_COMMUNICATIONS_FAILED

%1: failed to send ha-maintenance-notify to %2 in attempt to cancel its maintenance: %3

This warning message indicates that there was a problem in communication with a HA peer while sending the ha-maintenance-notify command with the cancel flag set to true. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

21.84 HA_MAINTENANCE_NOTIFY_CANCEL_FAILED

%1: error returned while processing ha-maintenance-notify by %2 in attempt to cancel its maintenance: %3

This warning message indicates that a peer returned an error status code in response to a ha-maintenance-notify command with the cancel flag set to true. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

21.85 HA_MAINTENANCE_NOTIFY_COMMUNICATIONS_FAILED

%1: failed to send ha-maintenance-notify to %2: %3

This warning message indicates that there was a problem in communication with a HA peer while sending the ha-maintenance-notify command. The first argument provides the local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

21.86 HA_MAINTENANCE_NOTIFY_FAILED

%1: error returned while processing ha-maintenance-notify by %2: %3

This warning message indicates that a peer returned an error status code in response to a ha-maintenance-notify command. The first argument provides the remote server's name. The second argument provides a reason for failure.

21.87 HA_MAINTENANCE_NOTIFY_HANDLER_FAILED

ha-maintenance-notify command failed: %1

This error message is issued to indicate that the ha-maintenance-notify command handler failed while processing the command. The argument provides the reason for failure.

21.88 HA_MAINTENANCE_SHUTDOWN_SAFE

%1: the server can now be shutdown for maintenance as the partner has taken over the DHCP traffic

This informational message is displayed after the server transitions to the in-maintenance state. This server no longer responds to any DHCP queries and its partner - in partner-in-maintenance state - has taken over the DHCP traffic. When the server in-maintenance state is shut down, the partner moves to the partner-down state immediately.

21.89 HA_MAINTENANCE_STARTED

%1: the server is now in the partner-in-maintenance state and the partner is in-maintenance state

This informational message is displayed when the server receiving the ha-maintenance-start command transitions to the partner-in-maintenance state. The server does it after sending the ha-maintenance-notify to its partner to put the partner in the in-maintenance state. From now on, the server in the partner-in-maintenance state will be responding to all queries and the partner will respond to no queries. The partner may be safely shut down for maintenance in which case this server will automatically transition from the partner-in-maintenance state to the partner-down state.

21.90 HA_MAINTENANCE_STARTED_IN_PARTNER_DOWN

%1: the server is now in the partner-down mode as a result of requested maintenance

This informational message is displayed when the server receiving the ha-maintenance-start command transitions to the partner-down state because it was unable to communicate with the partner while receiving the command. It is assumed that in such situation the partner is already offline for the maintenance. Note that in this case the normal failover procedure does not take place. The server does not wait for a heartbeat to fail several times, nor it monitors the DHCP traffic for not responded queries. In the maintenance case the server transitions to the partner-down state when it first encounters a communication problem with the partner.

21.91 HA_MAINTENANCE_START_HANDLER_FAILED

ha-maintenance-start command failed: %1

This error message is issued to indicate that the ha-maintenance-start command handler failed while processing the command. The argument provides the reason for failure.

21.92 HA_MISSING_CONFIGURATION

high-availability parameter not specified for High Availability hooks library

This error message is issued to indicate that the configuration for the High Availability hooks library hasn't been specified. The 'high-availability' parameter must be specified for the hooks library to load properly.

21.93 HA_PAUSE_CLIENT_LISTENER_FAILED

%1: pausing multi-threaded HTTP processing failed: %2

This error message is emitted when attempting to pause HA's HTTP client and listener threads. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect. The server name and the cause of the error are printed.

21.94 HA_PAUSE_CLIENT_LISTENER_ILLEGAL

%1: pausing multi-threaded HTTP processing failed: %2

This error message is emitted when attempting to pause HA's HTTP client or listener thread pools from a worker thread. This error indicates that a command run on the listener threads is trying to use a critical section which would result in a dead-lock.

21.95 HA_RESET_COMMUNICATIONS_FAILED

```
%1: failed to send ha-reset command to %2: %3
```

This warning message indicates a problem with communication with a HA peer while sending the ha-reset command. The first argument specifies the local server name. The second argument specifies a remote server name. The third argument specifies a reason for failure.

21.96 HA_RESET_FAILED

```
%1: failed to reset HA state machine of %2: %3
```

This warning message indicates that a peer returned an error status code in response to the ha-reset command. The first argument specifies a local server name. The second argument specifies a remote server name. The third argument specifies a reason for failure.

21.97 HA_RESET_HANDLER_FAILED

```
ha-reset command failed: %1
```

This error message is issued to indicate that the ha-reset command handler failed while processing the command. The argument provides the reason for failure.

21.98 HA_RESUME_CLIENT_LISTENER_FAILED

```
%1: resuming multi-threaded HTTP processing failed: %2
```

This error message is emitted when attempting to resume HA's HTTP client and listener threads. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

21.99 HA_SCOPES_HANDLER_FAILED

```
ha-scopes command failed: %1
```

This error message is issued to indicate that the ha-scopes command handler failed while processing the command. The argument provides reason for the failure.

21.100 HA_SERVICE_STARTED

```
%1: started high availability service in %2 mode as %3 server
```

This informational message is issued when the HA service is started as a result of server startup or reconfiguration. The first argument specifies a local server name. The second argument provides the HA mode. The third argument specifies the role of this server instance in this configuration.

21.101 HA_STATE_MACHINE_CONTINUED

```
%1: state machine is un-paused
```

This informational message is issued when the HA state machine is un-paused. This unlocks the server from the current state. It may transition to any other state if it needs to do so, e.g. 'partner-down' if its partner appears to be offline. The server may also remain in the current state if the HA setup state warrants such behavior.

21.102 HA_STATE_MACHINE_PAUSED

%1: state machine paused in state %2

This informational message is issued when the HA state machine is paused. HA state machine may be paused in certain states specified in the HA hooks library configuration. When the state machine is paused, the server remains in the given state until it is explicitly unpaused (via the ha-continue command). If the state machine is paused, the server operates normally but cannot transition to any other state.

21.103 HA_STATE_TRANSITION

%1: server transitions from %2 to %3 state, partner state is %4

This informational message is issued when the server transitions to a new state as a result of some interaction (or lack of thereof) with its partner. The arguments specify local server name, initial server state, new server state and the partner's state.

21.104 HA_STATE_TRANSITION_PASSIVE_BACKUP

%1: server transitions from %2 to %3 state

This informational message is issued when the server in passive-backup mode transitions to a new state. The arguments specify local server name, initial server state and a new server state.

21.105 HA_SUBNET4_SELECT_FAILED

subnet4_select callout failed: %1

This error message is issued when the callout for the subnet4_select hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

21.106 HA_SUBNET4_SELECT_INVALID_HA_SERVER_NAME

%1: invalid ha-server-name value for subnet %2

This error message is issued when the received DHCPv4 query is dropped by this server because the specified ha-server-name value in the subnet's user-context has non-string type or is empty. It is a server's misconfiguration. The first argument is the client identification information. The second argument is a subnet prefix.

21.107 HA_SUBNET4_SELECT_NOT_FOR_US

%1: dropping query in relationship %2 to be processed by another server

Logged at debug log level 40. This debug message is issued when the received DHCPv4 query is dropped by this server because it should be served by another server. This is the case when a remote primary server is operational. The first argument is the client identification information. The second argument is the relationship name.

21.108 HA_SUBNET4_SELECT_NO_RELATIONSHIP_FOR_SUBNET

%1: HA relationship not found for %2

This error message is issued when the received DHCPv4 query is dropped by this server because the server could not find a relationship matching the specified ha-server-name for a subnet. The server name matches no relationship specified in the HA configuration. A typical reason for it is a typo. The first argument is the client identification information. The second argument is the relationship name.

21.109 HA_SUBNET4_SELECT_NO_RELATIONSHIP_SELECTOR_FOR_SUBNET

%1: unable to determine HA relationship because selected subnet %2 lacks the ha-server-name

This error message is issued when the received DHCPv4 query is dropped by this server because it was unable to determine the HA relationship to which the received query belongs. If there are multiple relationships, it is required to specify ha-server-name value in the user-context at the subnet or shared network level for each subnet and/or shared network. The server uses them as a relationship selector. If these selectors are unspecified for any of the subnets it is a configuration error. The first argument is the client identification information. The second argument is a subnet prefix.

21.110 HA_SUBNET4_SELECT_NO_SUBNET_SELECTED

%1: unable to determine HA relationship because no subnet has been selected for the client

Logged at debug log level 40. This debug message is issued when the received DHCPv4 query is dropped by this server because it could not select a subnet for this client. Selecting the subnet is required to find a suitable HA relationship. This message is not emitted when the server has only one relationship. The argument is the client identification information.

21.111 HA_SUBNET6_SELECT_FAILED

subnet6_select callout failed: %1

This error message is issued when the callout for the subnet6_select hook point failed. This may occur as a result of an internal server error. The argument contains a reason for the error.

21.112 HA_SUBNET6_SELECT_INVALID_HA_SERVER_NAME

%1: invalid ha-server-name value for subnet %2

This error message is issued when the received DHCPv6 query is dropped by this server because the specified ha-server-name value in the subnet's user-context has non-string type or is empty. It is a server's misconfiguration. The first argument is the client identification information. The second argument is a subnet prefix.

21.113 HA_SUBNET6_SELECT_NOT_FOR_US

%1: dropping query in relationship %2 to be processed by another server

Logged at debug log level 40. This debug message is issued when the received DHCPv6 query is dropped by this server because it should be served by another server. This is the case when a remote primary server is operational. The first argument is the client identification information. The second argument is the relationship name.

21.114 HA_SUBNET6_SELECT_NO_RELATIONSHIP_FOR_SUBNET

%1: HA relationship not found for %2

This error message is issued when the received DHCPv6 query is dropped by this server because the server could not find a relationship matching the specified ha-server-name for a subnet. The server name matches no relationship specified in the HA configuration. A typical reason for it is a typo. The first argument is the client identification information. The second argument is the relationship name.

21.115 HA_SUBNET6_SELECT_NO_RELATIONSHIP_SELECTOR_FOR_SUBNET

```
%1: unable to determine HA relationship because selected subnet %2 lacks the ha-server-name
```

This error message is issued when the received DHCPv6 query is dropped by this server because it was unable to determine the HA relationship to which the received query belongs. If there are multiple relationships, it is required to specify ha-server-name value in the user-context at the subnet or shared network level for each subnet and/or shared network. The server uses them as a relationship selector. If these selectors are unspecified for any of the subnets it is a configuration error. The first argument is the client identification information. The second argument is a subnet prefix.

21.116 HA_SUBNET6_SELECT_NO_SUBNET_SELECTED

```
%1: unable to determine HA relationship because no subnet has been selected for the client
```

Logged at debug log level 40. This debug message is issued when the received DHCPv6 query is dropped by this server because it could not select a subnet for this client. Selecting the subnet is required to find a suitable HA relationship. This message is not emitted when the server has only one relationship. The argument is the client identification information.

21.117 HA_SYNC_COMPLETE_NOTIFY_COMMUNICATIONS_FAILED

```
%1: failed to send ha-sync-complete-notify to %2: %3
```

This warning message indicates that there was a problem in communication with an HA peer while sending the ha-sync-complete-notify command. The first argument provides a local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

21.118 HA_SYNC_COMPLETE_NOTIFY_FAILED

```
%1: error processing ha-sync-complete-notify command on %2: %3
```

This warning message indicates that a peer returned an error status code in response to the ha-sync-complete-notify command. The first argument provides a local server's name. The second argument provides the remote server's name. The third argument provides a reason for failure.

21.119 HA_SYNC_COMPLETE_NOTIFY_HANDLER_FAILED

```
ha-sync-complete-notify command failed: %1
```

This error message is issued to indicate that the ha-sync-complete-notify command handler failed while processing the command. The argument provides the reason for failure.

21.120 HA_SYNC_FAILED

```
%1: lease database synchronization with %2 failed: %3
```

This error message is issued to indicate that the lease database synchronization failed. The first argument provides the local server's name. The second argument provides the partner server's name. The third argument provides a reason for the failure.

21.121 HA_SYNC_HANDLER_FAILED

```
ha-sync command failed: %1
```

This error message is issued to indicate that the ha-sync command handler failed while processing the command. The argument provides the reason for failure.

21.122 HA_SYNC_START

```
%1: starting lease database synchronization with %2
```

This informational message is issued when the server starts lease database synchronization with a partner. The arguments specify the local and remote server names.

21.123 HA_SYNC_SUCCESSFUL

```
%1: lease database synchronization with %2 completed successfully in %3
```

This informational message is issued when the server successfully completed lease database synchronization with the partner. The first argument specifies local server name. The second argument specifies the name of the partner server. The third argument specifies the duration of the synchronization.

21.124 HA_TERMINATED

```
HA %1: service terminated due to an unrecoverable condition. Check previous error message(s), address the problem and restart!
```

This error message is issued to indicate that the HA service has been stopped due to an unacceptable condition (e.g. too large of a clock skew). The exact cause should appear in a previous error message. Address the condition reported then restart the servers to resume service.

21.125 HA_TERMINATED_PARTNER_DID_NOT_RESTART

```
%1: service is terminating because the terminated partner was not restarted within %2 minutes
```

This warning message is issued to indicate that the HA service is terminating because partner server is in the terminated state and was not restarted within an expected time frame. The terminated servers should be restarted after correcting the problem that caused the termination. They can be restarted sequentially but the duration between the restarts should not be too long. If it is long it may mean that the restart of one of the servers was unintentional (e.g., power outage). If the restarted server remains in the waiting state it cannot serve DHCP clients. Moving to the terminated state at least allows for responding to the DHCP traffic.

21.126 HA_TERMINATED_RESTART_PARTNER

```
%1: waiting for the partner in the TERMINATED state to be restarted
```

This informational message is issued when the server has been restarted after correcting the clock skew. The partner server is still in the terminated state. The partner must be restarted before the server can synchronize the database and start normal operation.

22.1 HOOKS_ALL_CALLOUTS_DEREGISTERED

```
hook library at index %1 removed all callouts on hook %2
```

Logged at debug log level 55. This debug message is issued when all callouts on the specified hook registered by the library with the given index were removed. This is similar to the `HOOKS_CALLOUTS_REMOVED` message (and the two are likely to be seen together), but is issued at a lower-level in the hook framework.

22.2 HOOKS_CALLOUTS_BEGIN

```
begin all callouts for hook %1
```

Logged at debug log level 45. This debug message is issued when callout manager begins to invoke callouts for the hook. The argument specifies the hook name.

22.3 HOOKS_CALLOUTS_COMPLETE

```
completed callouts for hook %1 (total callouts duration: %2)
```

Logged at debug log level 45. This debug message is issued when callout manager has completed execution of all callouts for the particular hook. The arguments specify the hook name and total execution time for all callouts in milliseconds.

22.4 HOOKS_CALLOUTS_REMOVED

```
callouts removed from hook %1 for library %2
```

Logged at debug log level 45. This is a debug message issued during library unloading. It notes that one of more callouts registered by that library have been removed from the specified hook. This is similar to the `HOOKS_DEREGISTER_ALL_CALLOUTS` message (and the two are likely to be seen together), but is issued at a higher-level in the hook framework.

22.5 HOOKS_CALLOUT_CALLED

```
hooks library with index %1 has called a callout on hook %2 that has address %3 (callout duration: %4)
```

Logged at debug log level 55. Only output at a high debugging level, this message indicates that a callout on the named hook registered by the library with the given index (in the list of loaded libraries) has been called and returned a success state. The address of the callout is given in the message. The message includes the callout execution time in milliseconds.

22.6 HOOKS_CALLOUT_DEREGISTERED

```
hook library at index %1 deregistered a callout on hook %2
```

Logged at debug log level 55. This debug message is issued when all instances of a particular callouts on the hook identified in the message that were registered by the library with the given index have been removed.

22.7 HOOKS_CALLOUT_ERROR

```
error returned by callout on hook %1 registered by library with index %2 (callout address %3) (callout duration %4)
```

If a callout returns an error status when called, this error message is issued. It identifies the hook to which the callout is attached, the index of the library (in the list of loaded libraries) that registered it and the address of the callout. The error is otherwise ignored. The error message includes the callout execution time in milliseconds.

22.8 HOOKS_CALLOUT_EXCEPTION

```
exception thrown by callout on hook %1 registered by library with index %2 (callout address %3): %4 (callout duration: %5)
```

If a callout throws an exception when called, this error message is issued. It identifies the hook to which the callout is attached, the index of the library (in the list of loaded libraries) that registered it and the address of the callout. The error is otherwise ignored. The error message includes the callout execution time in milliseconds.

22.9 HOOKS_CALLOUT_REGISTRATION

```
hooks library with index %1 registering callout for hook '%2'
```

Logged at debug log level 45. This is a debug message, output when a library (whose index in the list of libraries (being) loaded is given) registers a callout.

22.10 HOOKS_CLOSE_ERROR

```
failed to close hook library %1: %2
```

Kea has failed to close the named hook library for the stated reason. Although this is an error, this should not affect the running system other than as a loss of resources. If this error persists, you should restart Kea.

22.11 HOOKS_HOOK_LIST_RESET

```
the list of hooks has been reset
```

This is a message indicating that the list of hooks has been reset. While this is usual when running the Kea test suite, it should not be seen when running Kea in a production environment. If this appears, please report a bug through the usual channels.

22.12 HOOKS_INCORRECT_VERSION

```
hook library %1 is at version %2, require version %3
```

Kea has detected that the named hook library has been built against a version of Kea that is incompatible with the version of Kea running on your system. It has not loaded the library. This is most likely due to the installation of a new version of Kea without rebuilding the hook library. A rebuild and re-install of the library should fix the problem in most cases.

22.13 HOOKS_LIBPATH_SECURITY_WARNING

```
Library path specified is NOT SECURE: %1
```

This warning message is issued when security enforcement is disabled and the library path specified for a given hook library does not comply with the supported path. The server will still load the hook library but is warning that doing so may pose a security risk.

22.14 HOOKS_LIBRARY_CLOSED

```
hooks library %1 successfully closed
```

This information message is issued when a user-supplied hooks library has been successfully closed.

22.15 HOOKS_LIBRARY_LOADED

```
hooks library %1 successfully loaded
```

This information message is issued when a user-supplied hooks library has been successfully loaded.

22.16 HOOKS_LIBRARY_LOADING

```
loading hooks library %1
```

Logged at debug log level 40. This is a debug message output just before the specified library is loaded. If the action is successful, it will be followed by the HOOKS_LIBRARY_LOADED informational message.

22.17 HOOKS_LIBRARY_MULTI_THREADING_COMPATIBLE

```
hooks library %1 reports its multi-threading compatibility as %2
```

Logged at debug log level 45. This debug message is issued when the "multi_threading_compatible" function was called. The returned value (0 means not compatible, others compatible) is displayed.

22.18 HOOKS_LIBRARY_MULTI_THREADING_NOT_COMPATIBLE

```
hooks library %1 is not compatible with multi-threading
```

When multi-threading is enabled and the library is not compatible (either because the "multi_threading_compatible" function returned 0 or was not implemented) this error message is issued. The library must be removed from the configuration or the multi-threading disabled.

22.19 HOOKS_LIBRARY_UNLOADED

```
hooks library %1 successfully unloaded
```

This information message is issued when a user-supplied hooks library has been successfully unloaded.

22.20 HOOKS_LIBRARY_UNLOADING

```
unloading library %1
```

Logged at debug log level 40. This is a debug message called when the specified library is being unloaded. If all is successful, it will be followed by the HOOKS_LIBRARY_UNLOADED informational message.

22.21 HOOKS_LIBRARY_VERSION

```
hooks library %1 reports its version as %2
```

Logged at debug log level 45. A debug message issued when the version check on the hooks library has succeeded.

22.22 HOOKS_LOAD_ERROR

```
'load' function in hook library %1 returned error %2
```

A "load" function was found in the library named in the message and was called. The function returned a non-zero status (also given in the message) which was interpreted as an error. The library has been unloaded and no callouts from it will be installed.

22.23 HOOKS_LOAD_EXCEPTION

```
'load' function in hook library %1 threw an exception
```

A "load" function was found in the library named in the message and was called. The function threw an exception (an error indication) during execution, which is an error condition. The library has been unloaded and no callouts from it will be installed.

22.24 HOOKS_LOAD_FRAMEWORK_EXCEPTION

```
'load' function in hook library %1 threw an exception: reason %2
```

A "load" function was found in the library named in the message and was called. Either the hooks framework or the function threw an exception (an error indication) during execution, which is an error condition; the cause of the exception is recorded in the message. The library has been unloaded and no callouts from it will be installed.

22.25 HOOKS_LOAD_SUCCESS

```
'load' function in hook library %1 returned success
```

Logged at debug log level 40. This is a debug message issued when the "load" function has been found in a hook library and has been successfully called.

22.26 HOOKS_MULTI_THREADING_COMPATIBLE_EXCEPTION

```
'multi_threading_compatible' function in hook library %1 threw an exception
```

This error message is issued if the multi_threading_compatible() function in the specified hooks library was called and generated an exception. The library is considered unusable and will not be loaded.

22.27 HOOKS_NO_LOAD

```
no 'load' function found in hook library %1
```

Logged at debug log level 40. This is a debug message saying that the specified library was loaded but no function called "load" was found in it. Providing the library contained some "standard" functions (i.e. functions with the names of the hooks for the given server), this is not an issue.

22.28 HOOKS_NO_UNLOAD

```
no 'unload' function found in hook library %1
```

Logged at debug log level 40. This is a debug message issued when the library is being unloaded. It merely states that the library did not contain an "unload" function.

22.29 HOOKS_NO_VERSION

```
no 'version' function found in hook library %1
```

The shared library named in the message was found and successfully loaded, but Kea did not find a function named "version" in it. This function is required and should return the version of Kea against which the library was built. The value is used to check that the library was built against a compatible version of Kea. The library has not been loaded.

22.30 HOOKS_OPEN_ERROR

```
failed to open hook library %1: %2
```

Kea failed to open the specified hook library for the stated reason. The library has not been loaded. Kea will continue to function, but without the services offered by the library.

22.31 HOOKS_STD_CALLOUT_REGISTERED

```
hooks library %1 registered standard callout for hook %2 at address %3
```

Logged at debug log level 45. This is a debug message, output when the library loading function has located a standard callout (a callout with the same name as a hook point) and registered it. The address of the callout is indicated.

22.32 HOOKS_UNLOAD_ERROR

```
'unload' function in hook library %1 returned error %2
```

During the unloading of a library, an "unload" function was found. It was called, but returned an error (non-zero) status, resulting in the issuing of this message. The unload process continued after this message and the library has been unloaded.

22.33 HOOKS_UNLOAD_EXCEPTION

```
'unload' function in hook library %1 threw an exception
```

During the unloading of a library, an "unload" function was found. It was called, but in the process generated an exception (an error indication). The unload process continued after this message and the library has been unloaded.

22.34 HOOKS_UNLOAD_FRAMEWORK_EXCEPTION

'unload' function in hook library %1 threw an exception, reason %2

During the unloading of a library, an "unload" function was found. It was called, but in the process either it or the hooks framework generated an exception (an error indication); the cause of the error is recorded in the message. The unload process continued after this message and the library has been unloaded.

22.35 HOOKS_UNLOAD_SUCCESS

'unload' function in hook library %1 returned success

Logged at debug log level 40. This is a debug message issued when an "unload" function has been found in a hook library during the unload process, called, and returned success.

22.36 HOOKS_VERSION_EXCEPTION

'version' function in hook library %1 threw an exception

This error message is issued if the version() function in the specified hooks library was called and generated an exception. The library is considered unusable and will not be loaded.

HOSTS

23.1 HOSTS_BACKENDS_REGISTERED

```
the following host backend types are available: %1
```

This informational message lists all possible host backends that could be used in hosts-databases.

23.2 HOSTS_BACKEND_DEREGISTER

```
deregistered host backend type: %1
```

Logged at debug log level 40. This debug message is issued when a backend factory was deregistered. It is no longer possible to use host backend of this type.

23.3 HOSTS_BACKEND_REGISTER

```
registered host backend type: %1
```

Logged at debug log level 40. This debug message is issued when a backend factory was successfully registered. It is now possible to use host backend of this type.

23.4 HOSTS_CFG_ADD_HOST

```
add the host for reservations: %1
```

Logged at debug log level 40. This debug message is issued when new host (with reservations) is added to the server's configuration. The argument describes the host and its reservations in detail.

23.5 HOSTS_CFG_CACHE_HOST_DATA_SOURCE

```
get host cache data source: %1
```

This informational message is issued when a host cache data source is detected by the host manager.

23.6 HOSTS_CFG_CLOSE_HOST_DATA_SOURCE

```
Closing host data source: %1
```

Logged at debug log level 40. This is a normal message being printed when the server closes host data source connection.

23.7 HOSTS_CFG_DEL

```
deleted %1 host(s) having %2 IPv6 reservation(s) for subnet id %3 and address %4
```

Logged at debug log level 40. This debug message is issued when reservations are deleted for the specified subnet and address. The first argument specifies how many hosts have been deleted. The second argument specifies how many reservations have been deleted. The third argument is the subnet identifier. The fourth argument is the IP address.

23.8 HOSTS_CFG_DEL4

```
deleted %1 host(s) for subnet id %2 and identifier %3
```

Logged at debug log level 40. This debug message is issued when IPv4 reservations are deleted for the specified subnet and identifier. The first argument specifies how many hosts have been deleted. The second argument is the subnet identifier. The third argument is the identifier.

23.9 HOSTS_CFG_DEL6

```
deleted %1 host(s) having %2 IPv6 reservation(s) for subnet id %3 and identifier %4
```

Logged at debug log level 40. This debug message is issued when IPv6 reservations are deleted for the specified subnet and identifier. The first argument specifies how many hosts have been deleted. The second argument specifies how many reservations have been deleted. The third argument is the subnet identifier. The fourth argument is the identifier.

23.10 HOSTS_CFG_DEL_ALL_SUBNET4

```
deleted all %1 host(s) for subnet id %2
```

Logged at debug log level 40. This debug message is issued when all IPv4 reservations are deleted for the specified subnet. The first argument specifies how many reservations have been deleted. The second argument is the subnet identifier.

23.11 HOSTS_CFG_DEL_ALL_SUBNET6

```
deleted all %1 host(s) having %2 IPv6 reservation(s) for subnet id %3
```

Logged at debug log level 40. This debug message is issued when all IPv6 reservations are deleted for the specified subnet. The first argument specifies how many hosts have been deleted. The second argument specifies how many IPv6 (addresses and prefixes) reservations have been deleted. The third argument is the subnet identifier.

23.12 HOSTS_CFG_GET_ALL

```
get all hosts with reservations
```

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts.

23.13 HOSTS_CFG_GET_ALL_ADDRESS4

```
get all hosts with reservations for IPv4 address %1
```

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts, holding the reservation for the specific IPv4 address, from the configuration. The argument specifies the IPv4 address used to search the hosts.

23.14 HOSTS_CFG_GET_ALL_ADDRESS4_COUNT

```
using address %1, found %2 host(s)
```

Logged at debug log level 45. This debug message logs the number of hosts found using the specified IPv4 address. The arguments specify the IPv4 address used and the number of hosts found respectively.

23.15 HOSTS_CFG_GET_ALL_ADDRESS4_HOST

```
using address %1 found host: %2
```

Logged at debug log level 55. This debug message is issued when found host with the reservation for the specified IPv4 address. The arguments specify the IPv4 address and the detailed description of the host found.

23.16 HOSTS_CFG_GET_ALL_ADDRESS6

```
get all hosts with reservations for IPv6 address %1
```

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts, holding the reservation for the specific IPv6 address, from the configuration. The argument specifies the IPv6 address used to search the hosts.

23.17 HOSTS_CFG_GET_ALL_ADDRESS6_COUNT

```
using address %1, found %2 host(s)
```

Logged at debug log level 45. This debug message logs the number of hosts found using the specified IPv6 address. The arguments specify the IPv6 address used and the number of hosts found respectively.

23.18 HOSTS_CFG_GET_ALL_ADDRESS6_HOST

```
using address %1 found host: %2
```

Logged at debug log level 55. This debug message is issued when found host with the reservation for the specified IPv6 address. The arguments specify the IPv6 address and the detailed description of the host found.

23.19 HOSTS_CFG_GET_ALL_COUNT

```
found %1 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found. The argument specifies the number of hosts found.

23.20 HOSTS_CFG_GET_ALL_HOST

```
found host: %1
```

Logged at debug log level 55. This debug message includes the details of the host found. The argument specifies found host details.

23.21 HOSTS_CFG_GET_ALL_HOSTNAME

```
get all hosts with reservations for hostname %1
```

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts with the specific hostname. The argument specifies hostname.

23.22 HOSTS_CFG_GET_ALL_HOSTNAME_COUNT

```
using hostname %1, found %2 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the hostname. The arguments specify hostname and the number of hosts found respectively.

23.23 HOSTS_CFG_GET_ALL_HOSTNAME_HOST

```
using hostname %1, found host: %2
```

Logged at debug log level 55. This debug message includes the details of the host found using the hostname. The arguments specify hostname and found host details respectively.

23.24 HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4

```
get all hosts with reservations for hostname %1 and IPv4 subnet %2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts with the specific hostname connected to the specific DHCPv4 subnet. The argument specifies hostname and subnet id.

23.25 HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4_COUNT

```
using hostname %1 and IPv4 subnet %2, found %3 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the hostname and the DHCPv4 subnet id. The arguments specify hostname, subnet id and the number of hosts found respectively.

23.26 HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4_HOST

```
using hostname %1 and IPv4 subnet %2, found host: %3
```

Logged at debug log level 55. This debug message includes the details of the host found using the hostname and the DHCPv4 subnet id. The arguments specify hostname, subnet id and found host details respectively.

23.27 HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6

```
get all hosts with reservations for hostname %1 and IPv6 subnet %2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts with the specific hostname connected to the specific DHCPv6 subnet. The argument specifies hostname and subnet id.

23.28 HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6_COUNT

```
using hostname %1 and IPv6 subnet %2, found %3 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the hostname and the DHCPv6 subnet id. The arguments specify hostname, subnet id and the number of hosts found respectively.

23.29 HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6_HOST

```
using hostname %1 and IPv6 subnet %2, found host: %3
```

Logged at debug log level 55. This debug message includes the details of the host found using the hostname and the DHCPv6 subnet id. The arguments specify hostname, subnet id and found host details respectively.

23.30 HOSTS_CFG_GET_ALL_IDENTIFIER

```
get all hosts with reservations using identifier: %1
```

Logged at debug log level 40. This debug message is issued when starting to retrieve reservations for all hosts identified by HW address or DUID. The argument holds both the identifier type and the value.

23.31 HOSTS_CFG_GET_ALL_IDENTIFIER_COUNT

```
using identifier %1, found %2 host(s)
```

Logged at debug log level 45. This debug message logs the number of hosts found using the specified identifier. The arguments specify the identifier used and the number of hosts found respectively.

23.32 HOSTS_CFG_GET_ALL_IDENTIFIER_HOST

```
using identifier: %1, found host: %2
```

Logged at debug log level 55. This debug message is issued when found host identified by the specific identifier. The arguments specify the identifier and the detailed description of the host found.

23.33 HOSTS_CFG_GET_ALL_SUBNET_ID4

```
get all hosts with reservations for IPv4 subnet %1
```

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts connected to the specific DHCPv4 subnet. The argument specifies subnet id.

23.34 HOSTS_CFG_GET_ALL_SUBNET_ID4_COUNT

```
using IPv4 subnet %1, found %2 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the DHCPv4 subnet id. The arguments specify subnet id and the number of hosts found respectively.

23.35 HOSTS_CFG_GET_ALL_SUBNET_ID4_HOST

```
using IPv4 subnet %1, found host: %2
```

Logged at debug log level 55. This debug message includes the details of the host found using the DHCPv4 subnet id. The arguments specify subnet id and found host details respectively.

23.36 HOSTS_CFG_GET_ALL_SUBNET_ID6

```
get all hosts with reservations for IPv6 subnet %1
```

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts connected to the specific DHCPv6 subnet. The argument specifies subnet id.

23.37 HOSTS_CFG_GET_ALL_SUBNET_ID6_COUNT

```
using IPv6 subnet %1, found %2 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the DHCPv6 subnet id. The arguments specify subnet id and the number of hosts found respectively.

23.38 HOSTS_CFG_GET_ALL_SUBNET_ID6_HOST

```
using IPv6 subnet %1, found host: %2
```

Logged at debug log level 55. This debug message includes the details of the host found using the DHCPv6 subnet id. The arguments specify subnet id and found host details respectively.

23.39 HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4

```
get all hosts with reservations for subnet id %1 and IPv4 address %2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts having the reservation for the given IPv4 address within the given subnet. The first argument specifies subnet identifier. The second argument specifies the IPv4 address for which the reservation is to be returned.

23.40 HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4_COUNT

```
using IPv4 subnet %1 and IPv4 address %2, found %3 host(s)
```

Logged at debug log level 45. This debug message logs the number of hosts found having the reservation for the specified IPv4 address within the specified subnet. The first argument specifies the subnet identifier. The second argument specifies the reserved IPv4 address. The third argument specifies the number of hosts found.

23.41 HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4_HOST

```
using IPv4 subnet %1 and IPv4 address %2, found host: %3
```

Logged at debug log level 55. This debug message is issued when found host having the reservation for the specified IPv4 address in the specified subnet. The first argument specifies the subnet identifier. The second argument specifies the reserved IPv4 address. The third argument specifies host details.

23.42 HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6

```
get all hosts with reservations for subnet id %1 and IPv6 address %2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve all hosts connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

23.43 HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6_COUNT

```
using subnet id %1 and address %2, found %3 host(s)
```

Logged at debug log level 45. This debug message include the details of the host found using the subnet id and address. The arguments specify subnet id, address and the number of hosts found respectively.

23.44 HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6_HOST

```
using subnet id %1 and address %2, found host: %3
```

Logged at debug log level 55. This debug message includes the details of the host found using the subnet id and address. The arguments specify subnet id, address and the number of hosts found respectively. found host details respectively.

23.45 HOSTS_CFG_GET_ONE_PREFIX

```
get one host with reservation for prefix %1/%2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host having a reservation for a specified prefix. The arguments specify a prefix and prefix length.

23.46 HOSTS_CFG_GET_ONE_PREFIX_HOST

```
using prefix %1/%2, found host: %3
```

Logged at debug log level 55. This debug message includes the details of the host found using the specific prefix/prefix length. The arguments specify prefix, prefix length and host details respectively.

23.47 HOSTS_CFG_GET_ONE_PREFIX_NULL

```
host not found using prefix %1/%2
```

Logged at debug log level 55. This debug message is issued when no host was found for a specified prefix and prefix length.

23.48 HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4

```
get one host with reservation for subnet id %1 and IPv4 address %2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host connected to the specific subnet and having the specific IPv4 address reserved. The arguments specify subnet id and IPv4 address respectively.

23.49 HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4_HOST

```
using subnet id %1 and address %2, found host: %3
```

Logged at debug log level 45. This debug message logs the details of the host found using the subnet id and IPv4 address.

23.50 HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4_NULL

```
host not found using subnet id %1 and address %2
```

Logged at debug log level 45. This debug message is issued when no host was found for the specified subnet id and IPv4 address.

23.51 HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6

```
get one host with reservation for subnet id %1 and having IPv6 address %2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

23.52 HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6_HOST

```
using subnet id %1 and address %2, found host: %3
```

Logged at debug log level 45. This debug message logs the details of the host found using the subnet id and IPv6 address.

23.53 HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6_NULL

```
host not found using subnet id %1 and address %2
```

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet if and IPv6 address.

23.54 HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER

```
get one host with %1 reservation for subnet id %2, identified by %3
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host holding IPv4 or IPv6 reservations, which is connected to a specific subnet and is identified by a specific unique identifier. The first argument identifies if the IPv4 or IPv6 reservation is desired.

23.55 HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER_HOST

```
using subnet id %1 and identifier %2, found host: %3
```

Logged at debug log level 45. This debug message includes the details of a host found using a subnet id and specific host identifier.

23.56 HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER_NULL

```
host not found using subnet id %1 and identifier %2
```

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet id and host identifier.

23.57 HOSTS_CFG_UPDATE_ADD

```
add the host for reservations: %1
```

Logged at debug log level 40. This debug message is issued when a new host (with reservations) is added to the server's configuration during an update. The argument describes the host and its reservations in detail.

23.58 HOSTS_CFG_UPDATE_DEL4

```
deleted %1 host(s) for subnet id %2 and identifier %3
```

Logged at debug log level 40. This debug message is issued when IPv4 reservations are deleted for the specified subnet and identifier during an update. The first argument specifies how many hosts have been deleted. The second argument is the subnet identifier. The third argument is the identifier.

23.59 HOSTS_CFG_UPDATE_DEL6

```
deleted %1 host(s) having %2 IPv6 reservation(s) for subnet id %3 and identifier %4
```

Logged at debug log level 40. This debug message is issued when IPv6 reservations are deleted for the specified subnet and identifier during an update. The first argument specifies how many hosts have been deleted. The second argument specifies how many reservations have been deleted. The third argument is the subnet identifier. The fourth argument is the identifier.

23.60 HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_ADDRESS4

```
trying alternate sources for host using subnet id %1 and address %2
```

Logged at debug log level 40. This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specific IPv4 address, and it is starting to search for this host in alternate host data sources.

23.61 HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER

```
get one host with IPv4 reservation for subnet id %1, identified by %2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host holding IPv4 reservation, which is connected to a specific subnet and is identified by a specific unique identifier.

23.62 HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER_HOST

```
using subnet id %1 and identifier %2, found in %3 host: %4
```

Logged at debug log level 45. This debug message includes the details of a host returned by an alternate hosts data source using a subnet id and specific host identifier.

23.63 HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER_NULL

```
host not found using subnet id %1 and identifier %2
```

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet id and host identifier.

23.64 HOSTS_MGR_ALTERNATE_GET6_PREFIX

```
trying alternate sources for host using prefix %1/%2
```

Logged at debug log level 40. This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specified prefix, and it is starting to search for this host in alternate host data sources.

23.65 HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_ADDRESS6

```
trying alternate sources for host using subnet id %1 and IPv6 address %2
```

Logged at debug log level 40. This debug message is issued when the Host Manager doesn't find the host connected to the specific subnet and having the reservation for the specified IPv6 address, and it is starting to search for this host in alternate host data sources.

23.66 HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER

```
get one host with IPv6 reservation for subnet id %1, identified by %2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host holding IPv4 reservation, which is connected to a specific subnet and is identified by a specific unique identifier.

23.67 HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER_HOST

```
using subnet id %1 and identifier %2, found in %3 host: %4
```

Logged at debug log level 45. This debug message includes the details of a host returned by an alternate host data source using a subnet id and specific host identifier.

23.68 HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER_NULL

```
host not found using subnet id %1 and identifier %2
```

Logged at debug log level 45. This debug message is issued when no host was found using the specified subnet id and host identifier.

23.69 HOSTS_MGR_ALTERNATE_GET_ALL_SUBNET_ID_ADDRESS4

```
trying alternate sources for hosts using subnet id %1 and address %2
```

Logged at debug log level 40. This debug message is issued when the Host Manager is starting to search for hosts in alternate host data sources by subnet ID and IPv4 address.

23.70 HOSTS_MGR_ALTERNATE_GET_ALL_SUBNET_ID_ADDRESS6

trying alternate sources for hosts using subnet id %1 and address %2

Logged at debug log level 40. This debug message is issued when the Host Manager is starting to search for hosts in alternate host data sources by subnet ID and IPv6 address.

23.71 HOSTS_MGR_NON_UNIQUE_IP_UNSUPPORTED

host data source %1 does not support the mode in which IP reservations are non-unique

This warning message is issued when an administrator attempted to configure the server to allow multiple host reservations for the same IP address or prefix. Some host database backends may not support this mode of operation. In this case the administrator should stop using these backends or fall back to the default setting which requires that IP addresses are unique within a subnet. This setting is guaranteed to work for MySQL and Postgres host backends.

24.1 HOST_CACHE_ADD

```
add host: %1
```

Logged at debug log level 45. This debug message logs the details of the added host cache entry.

24.2 HOST_CACHE_ADD_DUPLICATE

```
duplicate host: %1
```

Logged at debug log level 45. The add operation failed because the entry conflicts with an already existing one. The details of the add operation argument are logged.

24.3 HOST_CACHE_COMMAND_CLEAR

```
cache-clear command successful
```

The cache-clear command has been successful.

24.4 HOST_CACHE_COMMAND_CLEAR_FAILED

```
cache-clear command failed (reason: %1)
```

The cache-clear command has failed. The reason is logged.

24.5 HOST_CACHE_COMMAND_FLUSH

```
cache-flush command successful
```

The cache-flush command has been successful.

24.6 HOST_CACHE_COMMAND_FLUSH_FAILED

```
cache-flush command failed (parameters: %1, reason: %2)
```

The cache-flush command has failed. Both the reason as well as the parameters passed are logged.

24.7 HOST_CACHE_COMMAND_GET

```
cache-get command successful (returned: %1)
```

The cache-get command has been successful. The number of returned entries is logged.

24.8 HOST_CACHE_COMMAND_GET_BY_ID

```
cache-get-by-id command successful (returned: %1)
```

The cache-get-by-id command has been successful. The number of returned entries is logged.

24.9 HOST_CACHE_COMMAND_GET_BY_ID_FAILED

```
cache-get-by-id command failed (reason: %1)
```

The cache-get-by-id command has failed. The reason is logged.

24.10 HOST_CACHE_COMMAND_GET_FAILED

```
cache-get command failed (reason: %1)
```

The cache-get command has failed. The reason is logged.

24.11 HOST_CACHE_COMMAND_INSERT

```
cache-insert command successful (inserted: %1, overwritten: %2)
```

The cache-insert command has been successful. The number of inserted entries and the number of entries overwritten by more recent entries are logged.

24.12 HOST_CACHE_COMMAND_INSERT_FAILED

```
cache-insert command failed (parameters: %1, reason: %2)
```

The cache-insert command has failed. Both the reason as well as the parameters passed are logged.

24.13 HOST_CACHE_COMMAND_LOAD

```
cache-load command successful (loaded: %1, overwritten: %2)
```

The cache-load command has been successful. The number of loaded entries and the number of entries overwritten by more recent entries are logged.

24.14 HOST_CACHE_COMMAND_LOAD_FAILED

```
cache-load command failed (parameters: %1, reason: %2)
```

The cache-load command has failed. Both the reason as well as the parameters passed are logged.

24.15 HOST_CACHE_COMMAND_REMOVE

```
cache-remove command successful (parameters: %1)
```

The cache-remove command has been successful. Parameters of the host deleted are logged.

24.16 HOST_CACHE_COMMAND_REMOVE_FAILED

```
cache-remove command failed (parameters: %1, reason: %2)
```

The cache-remove command has failed. Both the reason as well as the parameters passed are logged.

24.17 HOST_CACHE_COMMAND_SIZE

```
cache-clear command successful: %1
```

The cache-size command has been successful and returned the number of entries in the host cache.

24.18 HOST_CACHE_COMMAND_SIZE_FAILED

```
cache-size command failed (reason: %1)
```

The cache-size command has failed. The reason is logged.

24.19 HOST_CACHE_COMMAND_WRITE

```
cache-write command successful (dumped: %1)
```

The cache-write command has been successful. The number of dumped entries is logged.

24.20 HOST_CACHE_COMMAND_WRITE_FAILED

```
cache-write command failed (parameters: %1, reason: %2)
```

The cache-write command has failed. Both the reason as well as the parameters passed are logged.

24.21 HOST_CACHE_CONFIGURATION_FAILED

```
failed to configure Host Cache hooks library: %1
```

This error message is issued when there is an error configuring the Host Cache hooks library. The argument provides the detailed error message.

24.22 HOST_CACHE_DEINIT_OK

```
unloading Host Cache hooks library successful
```

This informational message indicates that the Host Cache hooks library has been unloaded successfully.

24.23 HOST_CACHE_DEL_SUBNET_ID_ADDRESS4

```
using subnet id %1 and address %2, delete host: %3
```

Logged at debug log level 45. This debug message logs the details of the host cache entry deleted using the subnet id and IPv4 address.

24.24 HOST_CACHE_DEL_SUBNET_ID_ADDRESS6

```
using subnet id %1 and address %2, delete host: %3
```

Logged at debug log level 45. This debug message logs the details of the host cache entry deleted using the subnet id and IPv6 address.

24.25 HOST_CACHE_DEL_SUBNET_ID_IDENTIFIER4

```
using subnet id %1 and identifier %2, delete host: %3
```

Logged at debug log level 45. This debug message logs the details of the host cache entry deleted using a subnet id and specific host identifier.

24.26 HOST_CACHE_DEL_SUBNET_ID_IDENTIFIER6

```
using subnet id %1 and identifier %2, delete host: %3
```

Logged at debug log level 45. This debug message logs the details of the host cache entry deleted using a subnet id and specific host identifier.

24.27 HOST_CACHE_GET_ONE_PREFIX

```
get one host with reservation for prefix %1/%2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host cache entry having a reservation for a specified prefix. The arguments specify a prefix and prefix length.

24.28 HOST_CACHE_GET_ONE_PREFIX_HOST

```
using prefix %1/%2, found host: %3
```

Logged at debug log level 45. This debug message includes the details of the host cache entry found using the specific prefix/prefix length. The arguments specify prefix, prefix length and host details respectively.

24.29 HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS4

```
get one host with reservation for subnet id %1 and IPv4 address %2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host cache entry connected to the specific subnet and having the specific IPv4 address reserved. The arguments specify subnet id and IPv4 address respectively.

24.30 HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS4_HOST

```
using subnet id %1 and address %2, found host: %3
```

Logged at debug log level 45. This debug message logs the details of the host cache entry found using the subnet id and IPv4 address.

24.31 HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS6

```
get one host with reservation for subnet id %1 and including IPv6 address %2
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host cache entry connected to the specific subnet and having the specific IPv6 address reserved. The arguments specify subnet id and IPv6 address respectively.

24.32 HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS6_HOST

```
using subnet id %1 and address %2, found host: %3
```

Logged at debug log level 45. This debug message logs the details of the host cache entry found using the subnet id and IPv6 address.

24.33 HOST_CACHE_GET_ONE_SUBNET_ID_IDENTIFIER

```
get one host with %1 reservation for subnet id %2, identified by %3
```

Logged at debug log level 40. This debug message is issued when starting to retrieve a host cache entry holding IPv4 or IPv6 reservations, which is connected to a specific subnet and is identified by a specific unique identifier. The first argument identifies if the IPv4 or IPv6 reservation is desired.

24.34 HOST_CACHE_GET_ONE_SUBNET_ID_IDENTIFIER_HOST

```
using subnet id %1 and identifier %2, found host: %3
```

Logged at debug log level 45. This debug message includes the details of a host cache entry found using a subnet id and specific host identifier.

24.35 HOST_CACHE_INIT_OK

```
loading Host Cache hooks library successful
```

This info message indicates that the Host Cache hooks library has been loaded successfully. Enjoy!

24.36 HOST_CACHE_PATH_SECURITY_WARNING

```
Cache file path specified is NOT SECURE: %1
```

This warning message is issued when security enforcement is disabled and the host cache file path specified does not comply with the supported path. The server will still use the specified path but is warning that doing so may pose a security risk.

24.37 HOST_CMDS_DEINIT_OK

```
unloading Host Commands hooks library successful
```

This info message indicates that the Host Commands hooks library has been removed successfully.

24.38 HOST_CMDS_INIT_FAILED

```
loading Host Commands hooks library failed: %1
```

This error message indicates an error during loading the Host Commands hooks library. The details of the error are provided as argument of the log message.

24.39 HOST_CMDS_INIT_OK

```
loading Host Commands hooks library successful
```

This info message indicates that the Host Commands hooks library has been loaded successfully. Enjoy!

24.40 HOST_CMDS_RESERV_ADD

```
reservation-add command called (parameters: %1)
```

The reservation-add command has been called. Parameters passed are logged.

24.41 HOST_CMDS_RESERV_ADD_FAILED

```
reservation-add command failed (parameters: %1, reason: %2)
```

The reservation-add command has failed. Both the reason as well as the parameters passed are logged.

24.42 HOST_CMDS_RESERV_ADD_SUCCESS

```
reservation-add command success (parameters: %1)
```

The reservation-add command has been successful. Parameters passed are logged.

24.43 HOST_CMDS_RESERV_DEL

```
reservation-del command called (parameters: %1)
```

The reservation-del command has been called. Parameters passed are logged.

24.44 HOST_CMDS_RESERV_DEL_FAILED

```
reservation-del command failed (parameters: %1, reason: %2)
```

The reservation-del command has failed. Both the reason as well as the parameters passed are logged.

24.45 HOST_CMDS_RESERV_DEL_SUCCESS

```
reservation-del command success (parameters: %1)
```

The reservation-del command has been successful. Parameters passed are logged.

24.46 HOST_CMDS_RESERV_GET

```
reservation-get command called (parameters: %1)
```

The reservation-get command has been called. Parameters passed are logged.

24.47 HOST_CMDS_RESERV_GET_ALL

```
reservation-get-all command called (parameters: %1)
```

The reservation-get-all command has been called. Parameters passed are logged.

24.48 HOST_CMDS_RESERV_GET_ALL_FAILED

```
reservation-get-all command failed (parameters: %1, reason: %2)
```

The reservation-get-all command has failed. Both the reason as well as the parameters passed are logged.

24.49 HOST_CMDS_RESERV_GET_ALL_SUCCESS

```
reservation-get-all command success (parameters: %1)
```

The reservation-get-all command has been successful. Parameters passed are logged.

24.50 HOST_CMDS_RESERV_GET_BY_ADDRESS

```
reservation-get-by-address command called (parameters: %1)
```

The reservation-get-by-address command has been called. Parameters passed are logged.

24.51 HOST_CMDS_RESERV_GET_BY_ADDRESS_FAILED

```
reservation-get-by-address command failed (parameters: %1, reason: %2)
```

The reservation-get-by-address command has failed. Both the reason as well as the parameters passed are logged.

24.52 HOST_CMDS_RESERV_GET_BY_ADDRESS_SUCCESS

```
reservation-get-by-address command success (parameters: %1)
```

The reservation-get-by-address command has been successful. Parameters passed are logged.

24.53 HOST_CMDS_RESERV_GET_BY_HOSTNAME

```
reservation-get-by-hostname command called (parameters: %1)
```

The reservation-get-by-hostname command has been called. Parameters passed are logged.

24.54 HOST_CMDS_RESERV_GET_BY_HOSTNAME_FAILED

```
reservation-get-by-hostname command failed (parameters: %1, reason: %2)
```

The reservation-get-by-hostname command has failed. Both the reason as well as the parameters passed are logged.

24.55 HOST_CMDS_RESERV_GET_BY_HOSTNAME_SUCCESS

```
reservation-get-by-hostname command success (parameters: %1)
```

The reservation-get-by-hostname command has been successful. Parameters passed are logged.

24.56 HOST_CMDS_RESERV_GET_BY_ID

```
reservation-get-by-id command called (parameters: %1)
```

The reservation-get-by-id command has been called. Parameters passed are logged.

24.57 HOST_CMDS_RESERV_GET_BY_ID_FAILED

```
reservation-get-by-id command failed (parameters: %1, reason: %2)
```

The reservation-get-by-id command has failed. Both the reason as well as the parameters passed are logged.

24.58 HOST_CMDS_RESERV_GET_BY_ID_SUCCESS

```
reservation-get-by-id command success (parameters: %1)
```

The reservation-get-by-id command has been successful. Parameters passed are logged.

24.59 HOST_CMDS_RESERV_GET_FAILED

```
reservation-get command failed (parameters: %1, reason: %2)
```

The reservation-add command has failed. Both the reason as well as the parameters passed are logged.

24.60 HOST_CMDS_RESERV_GET_PAGE

```
reservation-get-page command called (parameters: %1)
```

The reservation-get-page command has been called. Parameters passed are logged.

24.61 HOST_CMDS_RESERV_GET_PAGE_FAILED

```
reservation-get-page command failed (parameters: %1, reason: %2)
```

The reservation-get-page command has failed. Both the reason as well as the parameters passed are logged.

24.62 HOST_CMDS_RESERV_GET_PAGE_SUCCESS

```
reservation-get-page command success (parameters: %1)
```

The reservation-get-page command has been successful. Parameters passed are logged.

24.63 HOST_CMDS_RESERV_GET_SUCCESS

```
reservation-get command success (parameters: %1)
```

The reservation-get command has been successful. Parameters passed are logged.

24.64 HOST_CMDS_RESERV_UPDATE

```
reservation-update command called (parameters: %1)
```

The reservation-update command has been called. Parameters passed are logged.

24.65 HOST_CMDS_RESERV_UPDATE_FAILED

```
reservation-update command failed (parameters: %1, reason: %2)
```

The reservation-update command has failed. Both the reason as well as the parameters passed are logged.

24.66 HOST_CMDS_RESERV_UPDATE_SUCCESS

```
reservation-update command success (parameters: %1)
```

The reservation-update command has been successful. Parameters passed are logged.

25.1 HTTPS_REQUEST_RECEIVE_START

start receiving request from %l

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The argument specifies the address of the remote endpoint.

26.1 HTTP_BAD_CLIENT_REQUEST_RECEIVED

bad request received from %1: %2

Logged at debug log level 40. This debug message is issued when an HTTP client sends malformed request to the server. This includes HTTP requests using unexpected content types, including malformed JSON etc. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides a detailed error message.

26.2 HTTP_BAD_CLIENT_REQUEST_RECEIVED_DETAILS

detailed information about bad request received from %1:\n%2

Logged at debug log level 45. This debug message is issued when an HTTP client sends malformed request to the server. It includes detailed information about the received request rejected by the server. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides a request in the textual format. The request is truncated by the logger if it is too large to be printed.

26.3 HTTP_BAD_SERVER_RESPONSE_RECEIVED

bad response received when communicating with %1: %2

Logged at debug log level 40. This debug message is issued when an HTTP client fails to receive a response from the server or when this response is malformed. The first argument specifies the server URL. The second argument provides a detailed error message.

26.4 HTTP_BAD_SERVER_RESPONSE_RECEIVED_DETAILS

detailed information about bad response received from %1:\n%2

Logged at debug log level 45. This debug message is issued when an HTTP client receives malformed response from the server. The first argument specifies an URL of the server. The second argument provides a response in the textual format. The request is truncated by the logger if it is too large to be printed.

26.5 HTTP_CLIENT_MT_STARTED

HttpClient has been started in multi-threaded mode running %1 threads

Logged at debug log level 40. This debug message is issued when a multi-threaded HTTP client instance has been created. The argument specifies the maximum number of threads.

26.6 HTTP_CLIENT_PASSWORD_SECURITY_WARNING

```
use of clear text 'password' is NOT SECURE: %1
```

This warning message is issued when security enforcement is disabled and command socket configuration uses clear text 'password' rather than 'password-file'. The server will still use the socket as configured but is warning that doing so may pose a security risk.

26.7 HTTP_CLIENT_QUEUE_SIZE_GROWING

```
queue for URL: %1, now has %2 entries and may be growing too quickly
```

This warning message is issued when the queue of pending requests for the given URL appears to be growing more quickly than the requests can be handled. It will be emitted periodically as long as the queue size continues to grow. This may occur with a surge of client traffic creating a momentary backlog which then subsides as the surge subsides. If it happens continually then it most likely indicates a deployment configuration that cannot sustain the client load.

26.8 HTTP_CLIENT_REQUEST_AUTHORIZED

```
received HTTP request authorized for '%1'
```

This information message is issued when the server receives with a matching authentication header. The argument provides the user id.

26.9 HTTP_CLIENT_REQUEST_BAD_AUTH_HEADER

```
received HTTP request with malformed authentication header: %1
```

This information message is issued when the server receives a request with a malformed authentication header. The argument explains the problem.

26.10 HTTP_CLIENT_REQUEST_NOT_AUTHORIZED

```
received HTTP request with not matching authentication header
```

This information message is issued when the server receives a request with authentication header carrying not recognized credential: the user provided incorrect user id and/or password.

26.11 HTTP_CLIENT_REQUEST_NO_AUTH_HEADER

```
received HTTP request without required authentication header
```

This information message is issued when the server receives a request without a required authentication header.

26.12 HTTP_CLIENT_REQUEST_RECEIVED

```
received HTTP request from %1
```

Logged at debug log level 40. This debug message is issued when the server finished receiving a HTTP request from the remote endpoint. The address of the remote endpoint is specified as an argument.

26.13 HTTP_CLIENT_REQUEST_RECEIVED_DETAILS

detailed information about well-formed request received from %1:\n%2

Logged at debug log level 45. This debug message is issued when the HTTP server receives a well-formed request. It includes detailed information about the received request. The first argument specifies an address of the remote endpoint which sent the request. The second argument provides the request in the textual format. The request is truncated by the logger if it is too large to be printed.

26.14 HTTP_CLIENT_REQUEST_SEND

sending HTTP request %1 to %2

Logged at debug log level 50. This debug message is issued when the client is starting to send a HTTP request to a server. The first argument holds basic information about the request (HTTP version number and status code). The second argument specifies a URL of the server.

26.15 HTTP_CLIENT_REQUEST_SEND_DETAILS

detailed information about request sent to %1:\n%2

Logged at debug log level 55. This debug message is issued right before the client sends an HTTP request to the server. It includes detailed information about the request. The first argument specifies an URL of the server to which the request is being sent. The second argument provides the request in the textual form. The request is truncated by the logger if it is too large to be printed.

26.16 HTTP_CLIENT_REQUEST_TIMEOUT_OCCURRED

HTTP request timeout occurred when communicating with %1

Logged at debug log level 50. This debug message is issued when the HTTP request timeout has occurred and the server is going to send a response with Http Request timeout status code.

26.17 HTTP_CLIENT_USER_SECURITY_WARNING

use of clear text 'user' is NOT SECURE: %1

This warning message is issued when security enforcement is disabled and command socket configuration uses clear text 'user' rather than 'user-file'. The server will still use the socket as configured but is warning that doing so may pose a security risk.

26.18 HTTP_COMMAND_MGR_HTTPS_SERVICE_REUSE_FAILED

failed to reused HTTPS service bound to address: %1 port: %2

This error message indicates that the server has failed to reuse existing HTTPS service on the specified address and port. The server cannot swith from HTTPS to HTTP sockets using the same address and port.

26.19 HTTP_COMMAND_MGR_HTTPS_SERVICE_UPDATED

reused HTTPS service bound to address: %1 port: %2 and updated TLS settings

This informational message indicates that the server has reused existing HTTPS service on the specified address and port. Note that any change in the TLS setup has been applied.

26.20 HTTP_COMMAND_MGR_HTTP_SERVICE_REUSE_FAILED

failed to reused HTTP service bound to address: %1 port: %2

This error message indicates that the server has failed to reuse existing HTTP service on the specified address and port. The server cannot switch from HTTP to HTTPS sockets using the same address and port.

26.21 HTTP_COMMAND_MGR_HTTP_SERVICE_UPDATED

reused HTTP service bound to address: %1 port: %2

This informational message indicates that the server has reused existing HTTP service on the specified address and port.

26.22 HTTP_COMMAND_MGR_SERVICE_STARTED

started %1 service bound to address: %2 port: %3

This informational message indicates that the server has started HTTP/HTTPS service on the specified address and port for receiving control commands.

26.23 HTTP_COMMAND_MGR_SERVICE_STOPPING

Server is stopping %1 service %2

This informational message indicates that the server has stopped HTTP/HTTPS service. When known the address and port are displayed.

26.24 HTTP_CONNECTION_CLOSE_CALLBACK_FAILED

Connection close callback threw an exception

This is an error message emitted when the close connection callback registered on the connection failed unexpectedly. This is a programmatic error that should be submitted as a bug.

26.25 HTTP_CONNECTION_HANDSHAKE_FAILED

TLS handshake with %1 failed with %2

This information message is issued when the TLS handshake failed at the server side. The client address and the error message are displayed.

26.26 HTTP_CONNECTION_HANDSHAKE_START

```
start TLS handshake with %1 with timeout %2
```

Logged at debug log level 50. This debug message is issued when the server starts the TLS handshake with the remote endpoint. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

26.27 HTTP_CONNECTION_SHUTDOWN

```
shutting down HTTP connection from %1
```

Logged at debug log level 40. This debug message is issued when one of the HTTP connections is shut down. The connection can be stopped as a result of an error or after the successful message exchange with a client.

26.28 HTTP_CONNECTION_SHUTDOWN_FAILED

```
shutting down HTTP connection failed
```

This error message is issued when an error occurred during shutting down a HTTP connection with a client.

26.29 HTTP_CONNECTION_STOP

```
stopping HTTP connection from %1
```

Logged at debug log level 40. This debug message is issued when one of the HTTP connections is stopped. The connection can be stopped as a result of an error or after the successful message exchange with a client.

26.30 HTTP_CONNECTION_STOP_FAILED

```
stopping HTTP connection failed
```

This error message is issued when an error occurred during closing a HTTP connection with a client.

26.31 HTTP_CONNECTION_WATCH_SOCKET_CLEAR_ERROR

```
clearing connection watch socket failed: %1
```

This error message is issued when an error occurred during clearing the watch socket associated with a HTTP connection with a client. The error is displayed.

26.32 HTTP_CONNECTION_WATCH_SOCKET_CLOSE_ERROR

```
closing connection watch socket failed: %1
```

This error message is issued when an error occurred during closing the watch socket associated with a HTTP connection with a client. The error is displayed.

26.33 HTTP_CONNECTION_WATCH_SOCKET_MARK_READY_ERROR

```
marking ready connection watch socket failed: %1
```

This error message is issued when an error occurred during marking as ready the watch socket associated with a HTTP connection with a client. The error is displayed.

26.34 HTTP_DATA_RECEIVED

```
received %1 bytes from %2
```

Logged at debug log level 55. This debug message is issued when the server receives a chunk of data from the remote endpoint. This may include the whole request or only a part of the request. The first argument specifies the amount of received data. The second argument specifies an address of the remote endpoint which produced the data.

26.35 HTTP_IDLE_CONNECTION_TIMEOUT_OCCURRED

```
closing persistent connection with %1 as a result of a timeout
```

Logged at debug log level 50. This debug message is issued when the persistent HTTP connection is being closed as a result of being idle.

26.36 HTTP_PREMATURE_CONNECTION_TIMEOUT_OCCURRED

```
premature connection timeout occurred: in transaction ? %1, transid: %2, current_transid: %3
```

This warning message is issued when unexpected timeout occurred during the transaction. This is proven to occur when the system clock is moved manually or as a result of synchronization with a time server. Any ongoing transactions will be interrupted. New transactions should be conducted normally.

26.37 HTTP_REQUEST_RECEIVE_START

```
start receiving request from %1 with timeout %2
```

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

26.38 HTTP_SERVER_RESPONSE_RECEIVED

```
received HTTP response from %1
```

Logged at debug log level 40. This debug message is issued when the client finished receiving an HTTP response from the server. The URL of the server is specified as an argument.

26.39 HTTP_SERVER_RESPONSE_RECEIVED_DETAILS

```
detailed information about well-formed response received from %1:\n%2
```

Logged at debug log level 45. This debug message is issued when the HTTP client receives a well-formed response from the server. It includes detailed information about the received response. The first argument specifies a URL of the server which sent the response. The second argument provides the response in the textual format. The response is truncated by the logger if it is too large to be printed.

26.40 HTTP_SERVER_RESPONSE_SEND

sending HTTP response %1 to %2

Logged at debug log level 40. This debug message is issued when the server is starting to send a HTTP response to a remote endpoint. The first argument holds basic information about the response (HTTP version number and status code). The second argument specifies an address of the remote endpoint.

26.41 HTTP_SERVER_RESPONSE_SEND_DETAILS

detailed information about response sent to %1:\n%2

Logged at debug log level 45. This debug message is issued right before the server sends a HTTP response to the client. It includes detailed information about the response. The first argument specifies an address of the remote endpoint to which the response is being sent. The second argument provides a response in the textual form. The response is truncated by the logger if it is too large to be printed.

KEY

27.1 KEY_LOOKUP_DISABLED

hooks library lookup for a key: GSS-TSIG is not enabled for the current DNS server.

Logged at debug log level 40. This debug message is issued when the lookup for a GSS-TSIG key was performed for a DNS server where GSS-TSIG is not enabled.

27.2 KEY_LOOKUP_FOUND

hooks library lookup for a key: return GSS-TSIG key '%1'.

Logged at debug log level 40. This debug message is issued when the lookup for a GSS-TSIG key returned an usable key for protecting the DNS update. The key name is displayed.

27.3 KEY_LOOKUP_NONE

hooks library lookup for a key: found no usable key.

Logged at debug log level 40. This debug message is issued when the lookup for a GSS-TSIG key failed to find an usable key.

27.4 KEY_PROCESSING_FAILED

The GSS-TKEY processing for server %1 failed because of an error: %2

This error message is issued when the key processing for a specific server has failed. The first argument specifies the server identifier and the second argument gives more information about the error.

27.5 KEY_PROCESSING_FAILED_UNSPECIFIED_ERROR

The GSS-TKEY processing for server %1 failed because of an unspecified error

This error message is issued when the key processing for a specific server has failed. The first argument specifies the server identifier.

LEASE

28.1 LEASE_CMDS_ADD4

```
lease4-add command successful (address: %1)
```

Logged at debug log level 20. The lease4-add command has been successful. Lease IPv4 address is logged.

28.2 LEASE_CMDS_ADD4_CONFLICT

```
lease4-add command failed due to conflict (parameters: %1, reason: %2)
```

The received lease4-add is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

28.3 LEASE_CMDS_ADD4_FAILED

```
lease4-add command failed (parameters: %1, reason: %2)
```

The lease4-add command has failed. Both the reason as well as the parameters passed are logged.

28.4 LEASE_CMDS_ADD6

```
lease6-add command successful (address: %1)
```

Logged at debug log level 20. The lease6-add command has been successful. Lease IPv6 address is logged.

28.5 LEASE_CMDS_ADD6_CONFLICT

```
lease6-add command failed due to conflict (parameters: %1, reason: %2)
```

The received lease6-add is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

28.6 LEASE_CMDS_ADD6_FAILED

```
lease6-add command failed (parameters: %1, reason: %2)
```

The lease6-add command has failed. Both the reason as well as the parameters passed are logged.

28.7 LEASE_CMDS_BULK_APPLY6

```
lease6-bulk-apply command successful (applied addresses count: %1)
```

Logged at debug log level 20. The lease6-bulk-apply command has been successful. The number of applied addresses is logged.

28.8 LEASE_CMDS_BULK_APPLY6_FAILED

```
lease6-bulk-apply command failed (parameters: %1, reason: %2)
```

The lease6-bulk-apply command has failed. Both the reason as well as the parameters passed are logged.

28.9 LEASE_CMDS_DEINIT_OK

```
unloading Lease Commands hooks library successful
```

This info message indicates that the Lease Commands hooks library has been removed successfully.

28.10 LEASE_CMDS_DEL4

```
lease4-del command successful (address: %1)
```

Logged at debug log level 20. The attempt to delete an IPv4 lease (lease4-del command) has been successful. Lease IPv4 address is logged.

28.11 LEASE_CMDS_DEL4_FAILED

```
lease4-del command failed (parameters: %1, reason: %2)
```

The attempt to delete an IPv4 lease (lease4-del command) has failed. Both the reason as well as the parameters passed are logged.

28.12 LEASE_CMDS_DEL6

```
lease4-del command successful (address: %1)
```

Logged at debug log level 20. The attempt to delete an IPv4 lease (lease4-del command) has been successful. Lease IPv6 address is logged.

28.13 LEASE_CMDS_DEL6_FAILED

```
lease6-del command failed (parameters: %1, reason: %2)
```

The attempt to delete an IPv6 lease (lease4-del command) has failed. Both the reason as well as the parameters passed are logged.

28.14 LEASE_CMDS_FATAL_WRITE_LEASES4

```
fatal lease4-write command failure: %1
```

The attempt to write leases into the lease file failed. This situation requires a manual recovery. Details are logged.

28.15 LEASE_CMDS_FATAL_WRITE_LEASES6

```
fatal lease6-write command failure: %1
```

The attempt to write leases into the lease file failed. This situation requires a manual recovery. Details are logged.

28.16 LEASE_CMDS_GET4_FAILED

```
lease4-get command failed (parameters: %1, reason: %2)
```

The lease4-get command has failed. Both the reason as well as the parameters passed are logged.

28.17 LEASE_CMDS_GET6_FAILED

```
lease6-get command failed (parameters: %1, reason: %2)
```

The lease4-get command has failed. Both the reason as well as the parameters passed are logged.

28.18 LEASE_CMDS_INIT_OK

```
loading Lease Commands hooks library successful
```

This info message indicates that the Lease Commands hooks library has been loaded successfully. Enjoy!

28.19 LEASE_CMDS_LEASE4_OFFER_FAILED

```
processing error occurred evaluating binding variables: %1
```

This error log is emitted when an error occurs in the lease4_offer handler is invoked. The argument provides an explanation.

28.20 LEASE_CMDS_LEASES4_COMMITTED_FAILED

```
processing error occurred evaluating binding variables: %1
```

This error log is emitted when an error occurs in the leases4_committed handler is invoked. The argument provides an explanation.

28.21 LEASE_CMDS_LEASES6_COMMITTED_CONFLICT

```
could not updating lease: %1 for: %2
```

This error log is emitted by the leases6_committed callback when attempting to update a lease with new binding-variable values but a conflicting change has occurred rendering the update invalid. The arguments provide the lease address and the query details.

28.22 LEASE_CMDS_LEASES6_COMMITTED_FAILED

```
reason: %1
```

This error log is emitted when one or more leases associated with a client query failed to be updated with binding-variable values. The argument provides details. Individual errors for each lease should precede this log.

28.23 LEASE_CMDS_LEASES6_COMMITTED_LEASE_ERROR

```
evaluating binding-variables for lease: %1 for: %2, reason: %3
```

This error log is emitted by the `leases6_committed` callback when an unexpected error occurs evaluating the binding-variables for a given lease. The arguments provide the lease address, the query details, and an error explanation.

28.24 LEASE_CMDS_LOAD_ERROR

```
loading Lease Commands hooks library failed: %1
```

This error message indicates an error loading the Lease Commands hooks library. The details of the error are provided as argument of the log message.

28.25 LEASE_CMDS_PATH_SECURITY_WARNING

```
lease file path specified is NOT SECURE: %1
```

This warning message is issued when security enforcement is disabled and the path portion of the *filename* parameter of the `lease4-write` or `lease6-write` command does not comply with the supported path. The server will still use the specified path but is warning that doing so may pose a security risk.

28.26 LEASE_CMDS_RESEND_DDNS4

```
lease4-resend-ddns command successful: %1
```

A request to update DNS for the requested IPv4 lease has been successfully queued for transmission to `kea-dhcp-ddns`.

28.27 LEASE_CMDS_RESEND_DDNS4_FAILED

```
lease4-resend-ddns command failed: %1
```

A request to update DNS for the requested IPv4 lease has failed. The reason for the failure is logged.

28.28 LEASE_CMDS_RESEND_DDNS6

```
lease6-resend-ddns command successful: %1
```

A request to update DNS for the requested IPv6 lease has been successfully queued for transmission to `kea-dhcp-ddns`.

28.29 LEASE_CMDS_RESEND_DDNS6_FAILED

```
lease6-resend-ddns command failed: %1
```

A request to update DNS for the requested IPv6 lease has failed. The reason for the failure is logged.

28.30 LEASE_CMDS_UPDATE4

```
lease4-update command successful (address: %1)
```

Logged at debug log level 20. The `lease4-update` command has been successful. Lease IPv4 address is logged.

28.31 LEASE_CMDS_UPDATE4_CONFLICT

```
lease4-update command failed due to conflict (parameters: %1, reason: %2)
```

The received lease4-update is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

28.32 LEASE_CMDS_UPDATE4_FAILED

```
lease4-update command failed (parameters: %1, reason: %2)
```

The lease4-update command has failed. Both the reason as well as the parameters passed are logged.

28.33 LEASE_CMDS_UPDATE6

```
lease6-update command successful (address: %1)
```

Logged at debug log level 20. The lease6-update command has been successful. Lease IPv6 address is logged.

28.34 LEASE_CMDS_UPDATE6_CONFLICT

```
lease6-update command failed due to conflict (parameters: %1, reason: %2)
```

The received lease6-update is well-formed and contains valid parameters but the lease could not be created because it is in conflict with the server state or configuration. The reason for a conflict is logged in the message.

28.35 LEASE_CMDS_UPDATE6_FAILED

```
lease6-add command failed (parameters: %1, reason: %2)
```

The lease6-update command has failed. Both the reason as well as the parameters passed are logged.

28.36 LEASE_CMDS_WIPE4

```
lease4-wipe command successful (parameters: %1)
```

The lease4-wipe command has been successful. Parameters of the command are logged.

28.37 LEASE_CMDS_WIPE4_FAILED

```
lease4-wipe command failed (parameters: %1, reason: %2)
```

The lease4-wipe command has failed. Both the reason as well as the parameters passed are logged.

28.38 LEASE_CMDS_WIPE6

```
lease6-wipe command successful (parameters: %1)
```

The lease6-wipe command has been successful. Parameters of the command are logged.

28.39 LEASE_CMDS_WIPE6_FAILED

```
lease6-wipe command failed (parameters: %1, reason: %2)
```

The lease6-wipe command has failed. Both the reason as well as the parameters passed are logged.

28.40 LEASE_QUERY_LOAD_FAILED

```
Lease Query hooks library failed to load: %1
```

This error message indicates that an error occurred attempting to load the Lease Query hooks library. The argument details the error.

28.41 LEASE_QUERY_LOAD_OK

```
Lease Query hooks library loaded successfully.
```

This info message indicates that the Lease Query hooks library has been loaded successfully.

28.42 LEASE_QUERY_UNLOAD_OK

```
Lease Query hooks library unloaded successfully.
```

This info message indicates that the Lease Query hooks library has been unloaded successfully.

LEGAL

29.1 LEGAL_LOG_COMMAND_NO_LEGAL_STORE

LegalStore instance is null

This is an error message issued when the Legal Log library attempted to write a control command entry to the legal store and the store instance has not been created. This is a programmatic error and should not occur.

29.2 LEGAL_LOG_COMMAND_WRITE_ERROR

Could not write command entry to the legal store: %1

This is an error message issued when the Legal Log library attempted to write a control command entry to the legal store and the write failed. The message content should provide an detailed explanation. error.

29.3 LEGAL_LOG_DB_OPEN_CONNECTION_WITH_RETRY_FAILED

Failed to connect to database: %1 with error: %2

This is an informational message issued when the the server failed to connect to the store database. The operation started a retry to connect procedure. The database access string with password redacted is logged, along with the error and details for the reconnect procedure.

29.4 LEGAL_LOG_LEASE4_NO_LEGAL_STORE

LegalStore instance is null

This is an error message issued when the Legal Log library attempted to write a IPv4 lease entry to the legal store and the store instance has not been created. This is a programmatic error and should not occur.

29.5 LEGAL_LOG_LEASE4_RENDER_ERROR

custom request/response-parser-format failed for lease %1 hwaddr %2 (%3); falling back to default format

This error message is issued when an error occurs while evaluating a custom legal log message expression. When this occurs the legal log library will then attempt to output an entry using the default expression. This is most likely caused by an invalid expression such as attempting to evaluate uint32totext() on an uint8 byte option. The arguments provide the lease address, hardware address, and a description of the error.

29.6 LEGAL_LOG_LEASE4_WRITE_ERROR

Could not write to the legal store: %1

This is an error message issued when the Legal Log library attempted to write a IPv4 lease entry to the legal store and the write failed. The message content should include the physical store name and the nature of the error.

29.7 LEGAL_LOG_LEASE6_NO_LEGAL_STORE

LegalStore instance is null

This is an error message issued when the Legal Log library attempted to write a IPv6 lease entry to the legal store and the store instance has not been created. This is a programmatic error and should not occur.

29.8 LEGAL_LOG_LEASE6_RENDER_ERROR

custom request/response-parser-format failed for lease %1 duid %2 (%3); falling back to default format

This error message is issued when an error occurs while evaluating a custom legal log message expression. When this occurs the legal log library will then attempt to output an entry using the default expression. This is most likely caused by an invalid expression such as attempting to evaluate `uint32totext()` on an `uint8` byte option. The arguments provide the lease address, duid, and a description of the error.

29.9 LEGAL_LOG_LEASE6_WRITE_ERROR

Could not write to the legal store: %1

This is an error message issued when the Legal Log library attempted to write a IPv6 lease entry to the legal store and the write failed. The message content should include the physical store name and the nature of the error.

29.10 LEGAL_LOG_LOAD_ERROR

LEGAL LOGGING DISABLED! An error occurred loading the library: %1

This is an error message issued when the DHCP Legal Log library could not be loaded. The exact cause should be explained in the log message. No existing stores will be altered, nor any legal logging entries emitted.

29.11 LEGAL_LOG_MYSQL_COMMIT

committing to MySQL database

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the committal may not include a write to disk.

29.12 LEGAL_LOG_MYSQL_DB_RECONNECT_ATTEMPT_FAILED

database reconnect failed: %1

An error message issued when an attempt to reconnect has failed.

29.13 LEGAL_LOG_MYSQL_DB_RECONNECT_ATTEMPT_SCHEDULE

scheduling attempt %1 of %2 in %3 milliseconds

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

29.14 LEGAL_LOG_MYSQL_DB_RECONNECT_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

29.15 LEGAL_LOG_MYSQL_FATAL_ERROR

Unrecoverable MySQL error occurred: %1 for <%2>, reason: %3 (error code: %4).

An error message indicating that communication with the MySQL database server has been lost. When this occurs the server exits immediately with a non-zero exit code. This is most likely due to a network issue.

29.16 LEGAL_LOG_MYSQL_GET_VERSION

obtaining schema version information

Logged at debug log level 50. This debug message is issued when the server is about to obtain schema version information from the MySQL database.

29.17 LEGAL_LOG_MYSQL_INSERT_LOG

Adding a log entry to the database: %1

Logged at debug log level 50. An informational message logged when a log entry is inserted.

29.18 LEGAL_LOG_MYSQL_INVALID_ACCESS

invalid database access string: %1

This is logged when an attempt has been made to parse a database access string and the attempt ended in error. The access string in question - which should be of the form 'keyword=value keyword=value...' is included in the message.

29.19 LEGAL_LOG_MYSQL_NO_TLS

TLS was required but is not used

This error message is issued when TLS for the connection was required but TLS is not used.

29.20 LEGAL_LOG_MYSQL_ROLLBACK

rolling back MySQL database

The code has issued a rollback call. All outstanding transactions will be rolled back and not committed to the database.

29.21 LEGAL_LOG_MYSQL_START_TRANSACTION

starting new MySQL transaction

This debug message is issued when a new MySQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

29.22 LEGAL_LOG_MYSQL_TLS_CIPHER

TLS cipher: %1

Logged at debug log level 50. This debug message is issued when a new MySQL connected is created with TLS. The TLS cipher name is logged.

29.23 LEGAL_LOG_PATH_SECURITY_WARNING

Forensic log path specified is NOT SECURE: %1

This warning message is issued when security enforcement is disabled and the path specified for forensic logging output does not comply with the supported path. The server will still use the specified path but is warning that doing so may pose a security risk.

29.24 LEGAL_LOG_PGSQL_COMMIT

committing to PostgreSQL database

The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the committal may not include a write to disk.

29.25 LEGAL_LOG_PGSQL_DB_RECONNECT_ATTEMPT_FAILED

database reconnect failed: %1

An error message issued when an attempt to reconnect has failed.

29.26 LEGAL_LOG_PGSQL_DB_RECONNECT_ATTEMPT_SCHEDULE

scheduling attempt %1 of %2 in %3 milliseconds

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

29.27 LEGAL_LOG_PGSQL_DB_RECONNECT_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

29.28 LEGAL_LOG_PGSQL_DEALLOC_ERROR

An error occurred deallocating SQL statements while closing the PostgreSQL log database: %1

This is an error message issued when the legal log hook library experienced an error freeing database SQL resources as part of closing its connection to the PostgreSQL database. The connection is closed as part of normal server shutdown. This error is most likely a programmatic issue that is highly unlikely to occur or negatively impact server operation.

29.29 LEGAL_LOG_PGSQL_FATAL_ERROR

Unrecoverable PostgreSQL error occurred: Statement: <%1>, reason: %2 (error code: %3).

An error message indicating that communication with the PostgreSQL database server has been lost. When this occurs the server exits immediately with a non-zero exit code. This is most likely due to a network issue.

29.30 LEGAL_LOG_PGSQL_GET_VERSION

obtaining schema version information

Logged at debug log level 50. This debug message is issued when the server is about to obtain schema version information from the PostgreSQL database.

29.31 LEGAL_LOG_PGSQL_INSERT_LOG

Adding a log entry to the database: %1

Logged at debug log level 50. An informational message logged when a log entry is inserted.

29.32 LEGAL_LOG_PGSQL_INVALID_ACCESS

invalid database access string: %1

This is logged when an attempt has been made to parse a database access string and the attempt ended in error. The access string in question - which should be of the form 'keyword=value keyword=value...' is included in the message.

29.33 LEGAL_LOG_PGSQL_ROLLBACK

rolling back PostgreSQL database

The code has issued a rollback call. All outstanding transactions will be rolled back and not committed to the database.

29.34 LEGAL_LOG_PGSQL_START_TRANSACTION

starting a new PostgreSQL transaction

This debug message is issued when a new PostgreSQL transaction is being started. This message is typically not issued when inserting data into a single table because the server doesn't explicitly start transactions in this case. This message is issued when data is inserted into multiple tables with multiple INSERT statements and there may be a need to rollback the whole transaction if any of these INSERT statements fail.

29.35 LEGAL_LOG_STORE_CLOSED

Legal store closed: %1

This is an informational message issued when the Legal Log library has successfully closed the legal store.

29.36 LEGAL_LOG_STORE_CLOSE_ERROR

An error occurred closing the store: %1, error: %2

This is an error message issued when the legal log library experienced an error attempting to close a legal store. This is highly unlikely to occur and should not affect the store content or subsequent legal store operations.

29.37 LEGAL_LOG_STORE_OPEN

opening Legal Log file: %1

This informational message is logged when a DHCP server (either V4 or V6) is about to open a legal log file. The parameters of the backend are logged.

29.38 LEGAL_LOG_STORE_OPENED

Legal store opened: %1

This is an informational message issued when the Legal Log library has successfully opened the legal store.

29.39 LEGAL_LOG_SYSLOG

%1

This informational message contains the message being logged to syslog.

29.40 LEGAL_LOG_SYSLOG_STORE_OPEN

opening Legal Syslog: %1

This informational message is logged when a DHCP server (either V4 or V6) is about to open a legal syslog store. The parameters of the backend are logged.

29.41 LEGAL_LOG_UNLOAD_ERROR

An error occurred unloading the library: %1

This is an error message issued when an error occurs while unloading the Legal Log library. This is unlikely to occur and normal operations of the library will likely resume when it is next loaded.

LFC

30.1 LFC_FAIL_PID_CREATE

: %1

This message is issued if LFC detected a failure when trying to create the PID file. It includes a more specific error string.

30.2 LFC_FAIL_PID_DEL

: %1

This message is issued if LFC detected a failure when trying to delete the PID file. It includes a more specific error string.

30.3 LFC_FAIL_PROCESS

: %1

This message is issued if LFC detected a failure when trying to process the files. It includes a more specific error string.

30.4 LFC_FAIL_ROTATE

: %1

This message is issued if LFC detected a failure when trying to rotate the files. It includes a more specific error string.

30.5 LFC_PROCESSING

Previous file: %1, copy file: %2

This message is issued just before LFC starts processing the lease files.

30.6 LFC_READ_STATS

Leases: %1, attempts: %2, errors: %3.

This message prints out the number of leases that were read, the number of attempts to read leases and the number of errors encountered while reading.

30.7 LFC_ROTATING

LFC rotating files

This message is issued just before LFC starts rotating the lease files - removing the old and replacing them with the new.

30.8 LFC_RUNNING

LFC instance already running

This message is issued if LFC detects that a previous copy of LFC may still be running via the PID check.

30.9 LFC_START

Starting lease file cleanup

This message is issued as the LFC process starts.

30.10 LFC_TERMINATE

LFC finished processing

This message is issued when the LFC process completes. It does not indicate that the process was successful only that it has finished.

30.11 LFC_WRITE_STATS

Leases: %1, attempts: %2, errors: %3.

This message prints out the number of leases that were written, the number of attempts to write leases and the number of errors encountered while writing.

LIMITS

31.1 LIMITS_CONFIGURATION_LEASE_BACKEND_NOT_AVAILABLE

Lease backend not available. Could not check JSON support in the database. Continuing without checking...

Warning message logged to notify that limits might not work if the recovering database does not have JSON support.

31.2 LIMITS_CONFIGURATION_LEASE_BACKEND_SHOULD_HAVE_BEEN_AVAILABLE

Lease backend not available when configuration shows it should have been. This is likely a programmatic error. Continuing...

Error message logged to notify about an unexpected situation where the lease backend was expected to be available, but it was not. Runtime errors might occur.

31.3 LIMITS_CONFIGURED_ADDRESS_LIMIT_BY_CLIENT_CLASS

New lease limit of %1 addresses for client class %2 has been configured.

Logged at debug log level 40. Debug message logged to notify about the successful configuration of an address limit per client class

31.4 LIMITS_CONFIGURED_ADDRESS_LIMIT_BY_SUBNET

New lease limit of %1 addresses for subnet with ID %2 has been configured.

Logged at debug log level 40. Debug message logged to notify about the successful configuration of an address limit per subnet

31.5 LIMITS_CONFIGURED_PREFIX_LIMIT_BY_CLIENT_CLASS

New lease limit of %1 prefixes for client class %2 has been configured.

Logged at debug log level 40. Debug message logged to notify about the successful configuration of a prefix limit per client class

31.6 LIMITS_CONFIGURED_PREFIX_LIMIT_BY_SUBNET

New lease limit of %1 prefixes for subnet with ID %2 has been configured.

Logged at debug log level 40. Debug message logged to notify about the successful configuration of a prefix limit per subnet

31.7 LIMITS_CONFIGURED_RATE_LIMIT_BY_CLIENT_CLASS

New rate limit of %1 for client class %2 has been configured.

Logged at debug log level 40. Debug message logged to notify about the successful configuration of a rate limit per client class

31.8 LIMITS_CONFIGURED_RATE_LIMIT_BY_SUBNET

New rate limit of %1 for subnet with ID %2 has been configured.

Logged at debug log level 40. Debug message logged to notify about the successful configuration of a rate limit per subnet

31.9 LIMITS_LEASE_LIMIT_EXCEEDED

Lease was not allocated due to exceeding %1.

Logged at debug log level 40. Debug message logged to indicate that the current number of leased addresses or prefixes for a client class or a subnet has exceeded the limit.

31.10 LIMITS_LEASE_WITHIN_LIMITS

Lease with address %1 is within limits.

Logged at debug log level 40. Debug message logged to indicate that the current number of leased addresses or prefixes for a client class or a subnet has not exceeded the limit.

31.11 LIMITS_PACKET_WIHH_SUBNET_ID_RATE_NO_SUBNET

Packet is not being rate limited due to no subnet specified.

Logged at debug log level 55. Debug message logged to indicate that the current packet's subnet rate limit, if any, is not being checked due to the subnet not being set in the callout handle. This can happen e.g. if the subnet had been deleted after it was selected for the currently processed packet.

31.12 LIMITS_PACKET_WITH_CLIENT_CLASSES_RATE_LIMIT_DROPPED

Packet assigned to client classes %1 is being dropped for exceeding the rate limit of %2 for client class %3.

Logged at debug log level 40. Debug message logged to indicate that the current packet has exceeded one of the rate limits configured under at least one client class

31.13 LIMITS_PACKET_WITH_CLIENT_CLASSES_RATE_LIMIT_HONORED

Packet assigned to client classes %1 is being honored.

Logged at debug log level 55. Debug message logged to indicate that the current packet has not exceeded any of the rate limits configured under any client class

31.14 LIMITS_PACKET_WITH_SUBNET_ID_RATE_LIMIT_DROPPED

Packet assigned to subnet with ID %1 is being dropped for exceeding the rate limit of %2.

Logged at debug log level 40. Debug message logged to indicate that the current packet has exceeded the limit configured under the assigned subnet ID, if any is configured

31.15 LIMITS_PACKET_WITH_SUBNET_ID_RATE_LIMIT_HONORED

Packet under subnet with ID %1 and limit %2 is being honored.

Logged at debug log level 55. Debug message logged to indicate that the current packet has not exceeded the limit configured under the assigned subnet ID. This message is also logged when no rate limit is configured for this subnet ID.

LOGIMPL

32.1 LOGIMPL_ABOVE_MAX_DEBUG

debug level of %1 is too high and will be set to the maximum of %2

A message from the interface to the underlying logger implementation reporting that the debug level (as set by an internally-created string `DEBUGn`, where `n` is an integer, e.g. `DEBUG22`) is above the maximum allowed value and has been reduced to that value. The appearance of this message may indicate a programming error - please submit a bug report.

32.2 LOGIMPL_BAD_DEBUG_STRING

debug string '%1' has invalid format

A message from the interface to the underlying logger implementation reporting that an internally-created string used to set the debug level is not of the correct format (it should be of the form `DEBUGn`, where `n` is an integer, e.g. `DEBUG22`). The appearance of this message indicates a programming error - please submit a bug report.

32.3 LOGIMPL_BELOW_MIN_DEBUG

debug level of %1 is too low and will be set to the minimum of %2

A message from the interface to the underlying logger implementation reporting that the debug level (as set by an internally-created string `DEBUGn`, where `n` is an integer, e.g. `DEBUG22`) is below the minimum allowed value and has been increased to that value. The appearance of this message may indicate a programming error - please submit a bug report.

33.1 LOG_BAD_DESTINATION

```
unrecognized log destination: %1
```

This error message is printed when a logger destination value was given that was not recognized. The destination should be one of "console", "file", or "syslog".

33.2 LOG_BAD_SEVERITY

```
unrecognized log severity: %1
```

This error message is printed when a logger severity value was given that was not recognized. The severity should be one of "DEBUG", "INFO", "WARN", "ERROR", "FATAL" or "NONE".

33.3 LOG_BAD_STREAM

```
bad log console output stream: %1
```

Logging has been configured so that output is written to the terminal (console) but the stream on which it is to be written is not recognized. Allowed values are "stdout" and "stderr".

33.4 LOG_DUPLICATE_MESSAGE_ID

```
duplicate message ID (%1) in compiled code
```

During start-up, Kea detected that the given message identification had been defined multiple times in the Kea code. This indicates a programming error; please submit a bug report.

33.5 LOG_DUPLICATE_NAMESPACE

```
line %1: duplicate $NAMESPACE directive found
```

When reading a message file, more than one \$NAMESPACE directive was found. (This directive is used to set a C++ namespace when generating header files during software development.) Such a condition is regarded as an error and the read will be abandoned.

33.6 LOG_INPUT_OPEN_FAIL

```
unable to open message file %1 for input: %2
```

The program was not able to open the specified input message file for the reason given.

33.7 LOG_INVALID_MESSAGE_ID

```
line %1: invalid message identification '%2'
```

An invalid message identification (ID) has been found during the read of a message file. Message IDs should comprise only alphanumeric characters and the underscore, and should not start with a digit.

33.8 LOG_LOCK_TEST_MESSAGE

```
this is a test message.
```

This is a log message used in testing.

33.9 LOG_NAMESPACE_EXTRA_ARGS

```
line %1: $NAMESPACE directive has too many arguments
```

The `$NAMESPACE` directive in a message file takes a single argument, a namespace in which all the generated symbol names are placed. This error is generated when the compiler finds a `$NAMESPACE` directive with more than one argument.

33.10 LOG_NAMESPACE_INVALID_ARG

```
line %1: $NAMESPACE directive has an invalid argument ('%2')
```

The `$NAMESPACE` argument in a message file should be a valid C++ namespace. This message is output if the simple check on the syntax of the string carried out by the reader fails.

33.11 LOG_NAMESPACE_NO_ARGS

```
line %1: no arguments were given to the $NAMESPACE directive
```

The `$NAMESPACE` directive in a message file takes a single argument, a C++ namespace in which all the generated symbol names are placed. This error is generated when the compiler finds a `$NAMESPACE` directive with no arguments.

33.12 LOG_NO_MESSAGE_ID

```
line %1: message definition line found without a message ID
```

Within a message file, messages are defined by lines starting with a `"%"`. The rest of the line should comprise the message ID and text describing the message. This error indicates the message compiler found a line in the message file comprising just the `"%"` and nothing else.

33.13 LOG_NO_MESSAGE_TEXT

```
line %1: line found containing a message ID ('%2') and no text
```

Within a message file, messages are defined by lines starting with a "%". The rest of the line should comprise the message ID and text describing the message. This error indicates the message compiler found a line in the message file comprising just the "%" and message identification, but no text.

33.14 LOG_NO_SUCH_MESSAGE

```
could not replace message text for '%1': no such message
```

During start-up a local message file was read. A line with the listed message identification was found in the file, but the identification is not one contained in the compiled-in message dictionary. This message may appear a number of times in the file, once for every such unknown message identification. There are several reasons why this message may appear: - The message ID has been misspelled in the local message file. - The program outputting the message may not use that particular message (e.g. it originates in a module not used by the program). - The local file was written for an earlier version of the Kea software and the later version no longer generates that message. Whatever the reason, there is no impact on the operation of Kea.

33.15 LOG_OPEN_OUTPUT_FAIL

```
unable to open %1 for output: %2
```

Originating within the logging code, the program was not able to open the specified output file for the reason given.

33.16 LOG_PREFIX_EXTRA_ARGS

```
line %1: $PREFIX directive has too many arguments
```

Within a message file, the \$PREFIX directive takes a single argument, a prefix to be added to the symbol names when a C++ file is created. This error is generated when the compiler finds a \$PREFIX directive with more than one argument. Note: the \$PREFIX directive is deprecated and will be removed in a future version of Kea.

33.17 LOG_PREFIX_INVALID_ARG

```
line %1: $PREFIX directive has an invalid argument ('%2')
```

Within a message file, the \$PREFIX directive takes a single argument, a prefix to be added to the symbol names when a C++ file is created. As such, it must adhere to restrictions on C++ symbol names (e.g. may only contain alphanumeric characters or underscores, and may not start with a digit). A \$PREFIX directive was found with an argument (given in the message) that violates those restrictions. Note: the \$PREFIX directive is deprecated and will be removed in a future version of Kea.

33.18 LOG_READING_LOCAL_FILE

```
reading local message file %1
```

This is an informational message output by Kea when it starts to read a local message file. (A local message file may replace the text of one or more messages; the ID of the message will not be changed though.)

33.19 LOG_READ_ERROR

```
error reading from message file %1: %2
```

The specified error was encountered reading from the named message file.

33.20 LOG_UNRECOGNIZED_DIRECTIVE

```
line %1: unrecognized directive '%2'
```

Within a message file, a line starting with a dollar symbol was found (indicating the presence of a directive) but the first word on the line (shown in the message) was not recognized.

33.21 LOG_WRITE_ERROR

```
error writing to %1: %2
```

The specified error was encountered by the message compiler when writing to the named output file.

34.1 MT_TCP_LISTENER_MGR_STARTED

```
MtTcpListenerMgr started with %1 threads, listening on %2:%3, use TLS: %4
```

Logged at debug log level 40. This debug messages is issued when an MtTcpListenerMgr has been started to accept connections. Arguments detail the number of threads that the listener is using, the address and port at which it is listening, and if TLS is used or not.

34.2 MT_TCP_LISTENER_MGR_STOPPED

```
MtTcpListenerMgr for %1:%2 stopped.
```

Logged at debug log level 40. This debug messages is issued when the MtTcpListenerMgr, listening at the given address and port, has completed shutdown.

34.3 MT_TCP_LISTENER_MGR_STOPPING

```
Stopping MtTcpListenerMgr for %1:%2
```

Logged at debug log level 40. This debug messages is issued when the MtTcpListenerMgr, listening at the given address and port, has begun to shutdown.

35.1 MYSQL_CB_CREATE_UPDATE_BY_POOL_OPTION4

create or update option pool start: %1 pool end: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

35.2 MYSQL_CB_CREATE_UPDATE_BY_POOL_OPTION6

create or update option pool start: %1 pool end: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

35.3 MYSQL_CB_CREATE_UPDATE_BY_PREFIX_OPTION6

create or update option prefix: %1 prefix len: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by prefix

35.4 MYSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION4

create or update option by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

35.5 MYSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION6

create or update option by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

35.6 MYSQL_CB_CREATE_UPDATE_CLIENT_CLASS4

create or update client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

35.7 MYSQL_CB_CREATE_UPDATE_CLIENT_CLASS6

create or update client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

35.8 MYSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER4

create or update global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

35.9 MYSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER6

create or update global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

35.10 MYSQL_CB_CREATE_UPDATE_OPTION4

create or update option

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

35.11 MYSQL_CB_CREATE_UPDATE_OPTION6

create or update option

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

35.12 MYSQL_CB_CREATE_UPDATE_OPTION_DEF4

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

35.13 MYSQL_CB_CREATE_UPDATE_OPTION_DEF6

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

35.14 MYSQL_CB_CREATE_UPDATE_SERVER4

create or update server: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv4 server information.

35.15 MYSQL_CB_CREATE_UPDATE_SERVER6

```
create or update server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv6 server information.

35.16 MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK4

```
create or update shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

35.17 MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK6

```
create or update shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

35.18 MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION4

```
create or update shared network: %1 option
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

35.19 MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION6

```
create or update shared network: %1 option
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

35.20 MYSQL_CB_CREATE_UPDATE_SUBNET4

```
create or update subnet: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

35.21 MYSQL_CB_CREATE_UPDATE_SUBNET6

```
create or update subnet: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

35.22 MYSQL_CB_DELETE_ALL_CLIENT_CLASSES4

```
delete all client classes
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

35.23 MYSQL_CB_DELETE_ALL_CLIENT_CLASSES4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

35.24 MYSQL_CB_DELETE_ALL_CLIENT_CLASSES6

delete all client classes

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

35.25 MYSQL_CB_DELETE_ALL_CLIENT_CLASSES6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

35.26 MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4

delete all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

35.27 MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

35.28 MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6

delete all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

35.29 MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

35.30 MYSQL_CB_DELETE_ALL_OPTION_DEFS4

delete all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

35.31 MYSQL_CB_DELETE_ALL_OPTION_DEFS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

35.32 MYSQL_CB_DELETE_ALL_OPTION_DEFS6

delete all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

35.33 MYSQL_CB_DELETE_ALL_OPTION_DEFS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

35.34 MYSQL_CB_DELETE_ALL_SERVERS4

delete all DHCPv4 servers

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

35.35 MYSQL_CB_DELETE_ALL_SERVERS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

35.36 MYSQL_CB_DELETE_ALL_SERVERS6

delete all DHCPv6 servers

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

35.37 MYSQL_CB_DELETE_ALL_SERVERS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

35.38 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS4

delete all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

35.39 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

35.40 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS6

delete all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

35.41 MYSQL_CB_DELETE_ALL_SHARED_NETWORKS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

35.42 MYSQL_CB_DELETE_ALL_SUBNETS4

delete all subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

35.43 MYSQL_CB_DELETE_ALL_SUBNETS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

35.44 MYSQL_CB_DELETE_ALL_SUBNETS6

delete all subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

35.45 MYSQL_CB_DELETE_ALL_SUBNETS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

35.46 MYSQL_CB_DELETE_BY_POOL_OPTION4

delete pool start: %1 pool end: %2 option code: %3 space: %4

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

35.47 MYSQL_CB_DELETE_BY_POOL_OPTION4_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

35.48 MYSQL_CB_DELETE_BY_POOL_OPTION6

```
delete pool start: %1 pool end: %2 option code: %3 space: %4
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

35.49 MYSQL_CB_DELETE_BY_POOL_OPTION6_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

35.50 MYSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6

```
delete prefix: %1 prefix len: %2 option code: %3 space: %4
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by prefix

35.51 MYSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by prefix

35.52 MYSQL_CB_DELETE_BY_PREFIX_SUBNET4

```
delete subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

35.53 MYSQL_CB_DELETE_BY_PREFIX_SUBNET4_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

35.54 MYSQL_CB_DELETE_BY_PREFIX_SUBNET6

```
delete subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

35.55 MYSQL_CB_DELETE_BY_PREFIX_SUBNET6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

35.56 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION4

delete by subnet id: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

35.57 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

35.58 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION6

delete by subnet id: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

35.59 MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

35.60 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4

delete subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

35.61 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

35.62 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6

delete subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

35.63 MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

35.64 MYSQL_CB_DELETE_CLIENT_CLASS4

delete client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

35.65 MYSQL_CB_DELETE_CLIENT_CLASS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

35.66 MYSQL_CB_DELETE_CLIENT_CLASS6

delete client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

35.67 MYSQL_CB_DELETE_CLIENT_CLASS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

35.68 MYSQL_CB_DELETE_GLOBAL_PARAMETER4

delete global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

35.69 MYSQL_CB_DELETE_GLOBAL_PARAMETER4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

35.70 MYSQL_CB_DELETE_GLOBAL_PARAMETER6

delete global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

35.71 MYSQL_CB_DELETE_GLOBAL_PARAMETER6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

35.72 MYSQL_CB_DELETE_OPTION4

delete option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option

35.73 MYSQL_CB_DELETE_OPTION4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option

35.74 MYSQL_CB_DELETE_OPTION6

delete option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option

35.75 MYSQL_CB_DELETE_OPTION6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option

35.76 MYSQL_CB_DELETE_OPTION_DEF4

delete option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

35.77 MYSQL_CB_DELETE_OPTION_DEF4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

35.78 MYSQL_CB_DELETE_OPTION_DEF6

delete option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

35.79 MYSQL_CB_DELETE_OPTION_DEF6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

35.80 MYSQL_CB_DELETE_SERVER4

delete DHCPv4 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

35.81 MYSQL_CB_DELETE_SERVER4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

35.82 MYSQL_CB_DELETE_SERVER6

delete DHCPv6 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

35.83 MYSQL_CB_DELETE_SERVER6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

35.84 MYSQL_CB_DELETE_SHARED_NETWORK4

delete shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

35.85 MYSQL_CB_DELETE_SHARED_NETWORK4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

35.86 MYSQL_CB_DELETE_SHARED_NETWORK6

delete shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

35.87 MYSQL_CB_DELETE_SHARED_NETWORK6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

35.88 MYSQL_CB_DELETE_SHARED_NETWORK_OPTION4

delete shared network: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

35.89 MYSQL_CB_DELETE_SHARED_NETWORK_OPTION4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

35.90 MYSQL_CB_DELETE_SHARED_NETWORK_OPTION6

delete shared network: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

35.91 MYSQL_CB_DELETE_SHARED_NETWORK_OPTION6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

35.92 MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4

delete shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

35.93 MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

35.94 MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6

delete shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

35.95 MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT

deleted: %l entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

35.96 MYSQL_CB_GET_ALL_CLIENT_CLASSES4

retrieving all client classes

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

35.97 MYSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

35.98 MYSQL_CB_GET_ALL_CLIENT_CLASSES6

retrieving all client classes

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

35.99 MYSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

35.100 MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS4

retrieving all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

35.101 MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

35.102 MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS6

retrieving all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

35.103 MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

35.104 MYSQL_CB_GET_ALL_OPTIONS4

retrieving all options

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

35.105 MYSQL_CB_GET_ALL_OPTIONS4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

35.106 MYSQL_CB_GET_ALL_OPTIONS6

retrieving all options

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

35.107 MYSQL_CB_GET_ALL_OPTIONS6_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

35.108 MYSQL_CB_GET_ALL_OPTION_DEFS4

retrieving all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

35.109 MYSQL_CB_GET_ALL_OPTION_DEFS4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

35.110 MYSQL_CB_GET_ALL_OPTION_DEFS6

retrieving all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

35.111 MYSQL_CB_GET_ALL_OPTION_DEFS6_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

35.112 MYSQL_CB_GET_ALL_SERVERS4

retrieving all servers

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv4 servers

35.113 MYSQL_CB_GET_ALL_SERVERS4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv4 servers

35.114 MYSQL_CB_GET_ALL_SERVERS6

retrieving all DHCPv6 servers

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv6 servers

35.115 MYSQL_CB_GET_ALL_SERVERS6_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv6 servers

35.116 MYSQL_CB_GET_ALL_SHARED_NETWORKS4

retrieving all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

35.117 MYSQL_CB_GET_ALL_SHARED_NETWORKS4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

35.118 MYSQL_CB_GET_ALL_SHARED_NETWORKS6

retrieving all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

35.119 MYSQL_CB_GET_ALL_SHARED_NETWORKS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

35.120 MYSQL_CB_GET_ALL_SUBNETS4

retrieving all subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

35.121 MYSQL_CB_GET_ALL_SUBNETS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

35.122 MYSQL_CB_GET_ALL_SUBNETS6

retrieving all subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

35.123 MYSQL_CB_GET_ALL_SUBNETS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

35.124 MYSQL_CB_GET_CLIENT_CLASS4

retrieving client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

35.125 MYSQL_CB_GET_CLIENT_CLASS6

retrieving client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

35.126 MYSQL_CB_GET_GLOBAL_PARAMETER4

retrieving global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

35.127 MYSQL_CB_GET_GLOBAL_PARAMETER6

```
retrieving global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

35.128 MYSQL_CB_GET_HOST4

```
get host
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

35.129 MYSQL_CB_GET_HOST6

```
get host
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

35.130 MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES4

```
retrieving modified client classes from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

35.131 MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES4_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

35.132 MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES6

```
retrieving modified client classes from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

35.133 MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES6_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

35.134 MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4

```
retrieving modified global parameters from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

35.135 MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

35.136 MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6

retrieving modified global parameters from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

35.137 MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

35.138 MYSQL_CB_GET_MODIFIED_OPTIONS4

retrieving modified options from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

35.139 MYSQL_CB_GET_MODIFIED_OPTIONS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

35.140 MYSQL_CB_GET_MODIFIED_OPTIONS6

retrieving modified options from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

35.141 MYSQL_CB_GET_MODIFIED_OPTIONS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

35.142 MYSQL_CB_GET_MODIFIED_OPTION_DEFS4

retrieving modified option definitions from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

35.143 MYSQL_CB_GET_MODIFIED_OPTION_DEFS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

35.144 MYSQL_CB_GET_MODIFIED_OPTION_DEFS6

retrieving modified option definitions from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

35.145 MYSQL_CB_GET_MODIFIED_OPTION_DEFS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

35.146 MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS4

retrieving modified shared networks from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

35.147 MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

35.148 MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS6

retrieving modified shared networks from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

35.149 MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

35.150 MYSQL_CB_GET_MODIFIED_SUBNETS4

retrieving modified subnets from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

35.151 MYSQL_CB_GET_MODIFIED_SUBNETS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

35.152 MYSQL_CB_GET_MODIFIED_SUBNETS6

retrieving modified subnets from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

35.153 MYSQL_CB_GET_MODIFIED_SUBNETS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

35.154 MYSQL_CB_GET_OPTION4

retrieving option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

35.155 MYSQL_CB_GET_OPTION6

retrieving option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

35.156 MYSQL_CB_GET_OPTION_DEF4

retrieving option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

35.157 MYSQL_CB_GET_OPTION_DEF6

```
retrieving option definition code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

35.158 MYSQL_CB_GET_PORT4

```
get port
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

35.159 MYSQL_CB_GET_PORT6

```
get port
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

35.160 MYSQL_CB_GET_RECENT_AUDIT_ENTRIES4

```
retrieving audit entries from: %1 %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id.

35.161 MYSQL_CB_GET_RECENT_AUDIT_ENTRIES4_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

35.162 MYSQL_CB_GET_RECENT_AUDIT_ENTRIES6

```
retrieving audit entries from: %1 %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id

35.163 MYSQL_CB_GET_RECENT_AUDIT_ENTRIES6_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

35.164 MYSQL_CB_GET_SERVER4

```
retrieving DHCPv4 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv4 server information.

35.165 MYSQL_CB_GET_SERVER6

```
retrieving DHCPv6 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv6 server information.

35.166 MYSQL_CB_GET_SHARED_NETWORK4

```
retrieving shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

35.167 MYSQL_CB_GET_SHARED_NETWORK6

```
retrieving shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

35.168 MYSQL_CB_GET_SHARED_NETWORK_SUBNETS4

```
retrieving shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

35.169 MYSQL_CB_GET_SHARED_NETWORK_SUBNETS4_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

35.170 MYSQL_CB_GET_SHARED_NETWORK_SUBNETS6

```
retrieving shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

35.171 MYSQL_CB_GET_SHARED_NETWORK_SUBNETS6_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

35.172 MYSQL_CB_GET_SUBNET4_BY_PREFIX

```
retrieving subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

35.173 MYSQL_CB_GET_SUBNET4_BY_SUBNET_ID

```
retrieving subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

35.174 MYSQL_CB_GET_SUBNET6_BY_PREFIX

```
retrieving subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

35.175 MYSQL_CB_GET_SUBNET6_BY_SUBNET_ID

```
retrieving subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

35.176 MYSQL_CB_GET_TYPE4

```
get type
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

35.177 MYSQL_CB_GET_TYPE6

```
get type
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

35.178 MYSQL_CB_NO_TLS

```
TLS was required but is not used
```

This error message is issued when TLS for the connection was required but TLS is not used.

35.179 MYSQL_CB_RECONNECT_ATTEMPT_FAILED4

```
database reconnect failed: %1
```

Error message issued when an attempt to reconnect has failed.

35.180 MYSQL_CB_RECONNECT_ATTEMPT_FAILED6

```
database reconnect failed: %1
```

Error message issued when an attempt to reconnect has failed.

35.181 MYSQL_CB_RECONNECT_ATTEMPT_SCHEDULE4

scheduling attempt %1 of %2 in %3 milliseconds

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

35.182 MYSQL_CB_RECONNECT_ATTEMPT_SCHEDULE6

scheduling attempt %1 of %2 in %3 milliseconds

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

35.183 MYSQL_CB_RECONNECT_FAILED4

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

35.184 MYSQL_CB_RECONNECT_FAILED6

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

35.185 MYSQL_CB_REGISTER_BACKEND_TYPE4

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

35.186 MYSQL_CB_REGISTER_BACKEND_TYPE6

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

35.187 MYSQL_CB_TLS_CIPHER

TLS cipher: %1

Logged at debug log level 40. This debug message is issued when a new MySQL connected is created with TLS. The TLS cipher name is logged.

35.188 MYSQL_CB_UNREGISTER_BACKEND_TYPE4

unregister backend

Logged at debug log level 40. Debug message issued when triggered an action to unregister backend

35.189 MYSQL_CB_UNREGISTER_BACKEND_TYPE6

```
unregister backend
```

Logged at debug log level 40. Debug message issued when triggered an action to unregister backend

35.190 MYSQL_DEINIT_OK

```
unloading MySQL hooks library successful
```

This informational message indicates that the MySQL Backend hooks library has been unloaded successfully.

35.191 MYSQL_FB_DB

```
opening MySQL log database: %1
```

This informational message is logged when the legal log hook library is about to open a MySQL log database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

35.192 MYSQL_HB_DB

```
opening MySQL hosts database: %1
```

This informational message is logged when a DHCP server (either V4 or V6) is about to open a MySQL hosts database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

35.193 MYSQL_HB_DB_GET_VERSION

```
obtaining schema version information for the MySQL hosts database
```

Logged at debug log level 50. This debug message is issued when the server is about to obtain schema version information from the MySQL hosts database.

35.194 MYSQL_HB_DB_READONLY

```
MySQL host database opened for read access only
```

This informational message is issued when the user has configured the MySQL database in read-only mode. Kea will not be able to insert or modify host reservations but will be able to retrieve existing ones and assign them to the clients communicating with the server.

35.195 MYSQL_HB_DB_RECONNECT_ATTEMPT_FAILED

```
database reconnect failed: %1
```

An error message issued when an attempt to reconnect has failed.

35.196 MYSQL_HB_DB_RECONNECT_ATTEMPT_SCHEDULE

scheduling attempt %1 of %2 in %3 milliseconds

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

35.197 MYSQL_HB_DB_RECONNECT_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

35.198 MYSQL_HB_NO_TLS

TLS was required but is not used

This error message is issued when TLS for the connection was required but TLS is not used.

35.199 MYSQL_HB_TLS_CIPHER

TLS cipher: %1

Logged at debug log level 40. This debug message is issued when a new MySQL connection is created with TLS. The TLS cipher name is logged.

35.200 MYSQL_INIT_OK

loading MySQL hooks library successful

This informational message indicates that the MySQL Backend hooks library has been loaded successfully. Enjoy!

35.201 MYSQL_LB_ADD_ADDR4

adding IPv4 lease with address %1

Logged at debug log level 50. This debug message is issued when the server is about to add an IPv4 lease with the specified address to the MySQL backend database.

35.202 MYSQL_LB_ADD_ADDR6

adding IPv6 lease with address %1, lease type %2

Logged at debug log level 50. This debug message is issued when the server is about to add an IPv6 lease with the specified address to the MySQL backend database.

35.203 MYSQL_LB_COMMIT

committing to MySQL database

Logged at debug log level 50. The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the MySQL settings, the commit may not include a write to disk.

35.204 MYSQL_LB_DB

```
opening MySQL lease database: %1
```

This informational message is logged when a DHCP server (either V4 or V6) is about to open a MySQL lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

35.205 MYSQL_LB_DB_RECONNECT_ATTEMPT_FAILED

```
database reconnect failed: %1
```

An error message issued when an attempt to reconnect has failed.

35.206 MYSQL_LB_DB_RECONNECT_ATTEMPT_SCHEDULE

```
scheduling attempt %1 of %2 in %3 milliseconds
```

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

35.207 MYSQL_LB_DB_RECONNECT_FAILED

```
maximum number of database reconnect attempts: %1, has been exhausted without success
```

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

35.208 MYSQL_LB_DELETED_EXPIRED_RECLAIMED

```
deleted %1 reclaimed leases from the database
```

Logged at debug log level 50. This debug message is issued when the server has removed a number of reclaimed leases from the database. The number of removed leases is included in the message.

35.209 MYSQL_LB_DELETED_SUBNET4_ID

```
deleted %1 leases that match subnet ID %2.
```

Logged at debug log level 50. This debug message is issued when the server is removing leases which match respective subnet ID.

35.210 MYSQL_LB_DELETED_SUBNET6_ID

```
deleted %1 leases that match subnet ID %2.
```

Logged at debug log level 50. This debug message is issued when the server is removing leases which match respective subnet ID.

35.211 MYSQL_LB_DELETE_ADDR4

deleting lease for address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to delete a lease for the specified address from the MySQL database for the specified address.

35.212 MYSQL_LB_DELETE_ADDR6

deleting lease for address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to delete a lease for the specified address from the MySQL database for the specified address.

35.213 MYSQL_LB_DELETE_EXPIRED_RECLAIMED4

deleting reclaimed IPv4 leases that expired more than %1 seconds ago

Logged at debug log level 50. This debug message is issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

35.214 MYSQL_LB_DELETE_EXPIRED_RECLAIMED6

deleting reclaimed IPv6 leases that expired more than %1 seconds ago

Logged at debug log level 50. This debug message is issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

35.215 MYSQL_LB_GET4

obtaining all IPv4 leases

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv4 leases from the MySQL database.

35.216 MYSQL_LB_GET6

obtaining all IPv6 leases

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv6 leases from the MySQL database.

35.217 MYSQL_LB_GET_ADDR4

obtaining IPv4 lease for address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv4 lease from the MySQL database for the specified address.

35.218 MYSQL_LB_GET_ADDR6

```
obtaining IPv6 lease for address %1, lease type %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv6 lease from the MySQL database for the specified address.

35.219 MYSQL_LB_GET_CLIENTID

```
obtaining IPv4 leases for client ID %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified client identification.

35.220 MYSQL_LB_GET_DUID

```
obtaining IPv6 lease for duid %1,
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv6 lease from the MySQL database for the specified duid.

35.221 MYSQL_LB_GET_EXPIRED4

```
obtaining maximum %1 of expired IPv4 leases
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

35.222 MYSQL_LB_GET_EXPIRED6

```
obtaining maximum %1 of expired IPv6 leases
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

35.223 MYSQL_LB_GET_HOSTNAME4

```
obtaining IPv4 leases for hostname %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified hostname.

35.224 MYSQL_LB_GET_HOSTNAME6

```
obtaining IPv6 leases for hostname %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database for a client with the specified hostname.

35.225 MYSQL_LB_GET_HWADDR4

obtaining IPv4 leases for hardware address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database for a client with the specified hardware address.

35.226 MYSQL_LB_GET_HWADDR6

obtaining IPv6 leases for hardware address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database for a client with the specified hardware address.

35.227 MYSQL_LB_GET_IAID_DUID

obtaining IPv6 leases for IAID %1, DUID %2, lease type %3

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

35.228 MYSQL_LB_GET_IAID_SUBID_DUID

obtaining IPv6 leases for IAID %1, subnet ID %2, DUID %3, lease type %4

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv6 lease from the MySQL database for a client with the specified IAID (Identity Association ID), subnet ID and DUID (DHCP Unique Identifier).

35.229 MYSQL_LB_GET_PAGE4

obtaining at most %1 IPv4 leases starting from address %2

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of leases beginning with the specified address.

35.230 MYSQL_LB_GET_PAGE6

obtaining at most %1 IPv6 leases starting from address %2

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of leases beginning with the specified address.

35.231 MYSQL_LB_GET_RELAYID4

obtaining at most %1 IPv4 leases starting from address %2 with relay id %3 and cltt between %4 and %5

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a relay id and client transaction time between start and end dates.

35.232 MYSQL_LB_GET_RELAYID6

```
obtaining at most %1 IPv6 leases starting from address %2 with relay id %3
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a relay id.

35.233 MYSQL_LB_GET_REMOTEID4

```
obtaining at most %1 IPv4 leases starting from address %2 with remote id %3 and cltt between %4 and %5
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a remote id and client transaction time between start and end dates.

35.234 MYSQL_LB_GET_REMOTEID6

```
obtaining at most %1 IPv6 leases starting from address %2 with remote id %3
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a remote id.

35.235 MYSQL_LB_GET_STATE4

```
obtaining IPv4 leases with state %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database with the specified state.

35.236 MYSQL_LB_GET_STATE6

```
obtaining IPv6 leases with state %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database with the specified state.

35.237 MYSQL_LB_GET_STATE_SUBID4

```
obtaining IPv4 leases with state %1 in subnet %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the MySQL database with the specified state in the specified subnet.

35.238 MYSQL_LB_GET_STATE_SUBID6

```
obtaining IPv6 leases with state %1 in subnet %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the MySQL database with the specified state in the specified subnet.

35.239 MYSQL_LB_GET_SUBID4

obtaining IPv4 leases for subnet ID %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the MySQL database.

35.240 MYSQL_LB_GET_SUBID6

obtaining IPv6 leases for subnet ID %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the MySQL database.

35.241 MYSQL_LB_GET_SUBID_CLIENTID

obtaining IPv4 lease for subnet ID %1 and client ID %2

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv4 lease from the MySQL database for a client with the specified subnet ID and client ID.

35.242 MYSQL_LB_GET_SUBID_HWADDR

obtaining IPv4 lease for subnet ID %1 and hardware address %2

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv4 lease from the MySQL database for a client with the specified subnet ID and hardware address.

35.243 MYSQL_LB_GET_SUBID_PAGE6

obtaining at most %1 IPv6 leases starting from address %2 for subnet ID %3

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv6 leases from the MySQL database beginning with the specified address for the specified subnet identifier.

35.244 MYSQL_LB_GET_VERSION

obtaining schema version information

Logged at debug log level 50. This debug message is issued when the server is about to obtain schema version information from the MySQL database.

35.245 MYSQL_LB_NEGATIVE_LEASES_STAT

recount of leases returned a negative value

This warning message is issued when the recount of leases using counters in the MySQL database returned a negative value. This shows a problem which can be fixed only by an offline direct recount on the database. This message is issued only once.

35.246 MYSQL_LB_NO_TLS

TLS was required but is not used

This error message is issued when TLS for the connection was required but TLS is not used.

35.247 MYSQL_LB_ROLLBACK

rolling back MySQL database

Logged at debug log level 50. The code has issued a rollback call. All outstanding transactions will be rolled back and not committed to the database.

35.248 MYSQL_LB_SFLQ_CREATE_POOL4

creating shared-flq pool for address range %1 - %2, subnet id %3, recreate %4, capacity %5

Logged at debug log level 50. This debug message is issued when the server asks the lease back end to (re)create the shared free lease data for the pool described in the arguments.

35.249 MYSQL_LB_SFLQ_CREATE_POOL6

creating shared-flq pool for address range %1 - %2, type %3, delegated length: %4, subnet id %5, recreate %6, capacity %7

Logged at debug log level 50. This debug message is issued when the server asks the lease back end to (re)create the shared free lease data for the pool described in the arguments.

35.250 MYSQL_LB_SFLQ_PICK_LEASE4

picking a free lease from address range %1 - %2

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a free address from the pool described in the arguments.

35.251 MYSQL_LB_SFLQ_PICK_LEASE6

picking a free lease from address range %1 - %2

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a free lease from the pool described in the arguments.

35.252 MYSQL_LB_SFLQ_POOL4_DELETE

delete the V4 SFLQ pool with start address %1 and end address %2, force = %3

Logged at debug log level 50. This debug message is issued when the server asks the lease back to delete the v4 SFLQ pool (and it's free lease data) that match the given start and end addresses.

35.253 MYSQL_LB_SFLQ_POOL4_GET_ALL

```
fetch all V4 SFLQ pools
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a list of all v4 SFLQ pools.

35.254 MYSQL_LB_SFLQ_POOL4_GET_BY_RANGE

```
fetch all V4 SFLQ pools that overlap the range %1 and %2
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for the v4 SFLQ pool that overlap the given address range.

35.255 MYSQL_LB_SFLQ_POOL4_GET_BY_SUBNET

```
fetch all V4 SFLQ pools for subnet-id %1
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a list of all v4 SFLQ pools belonging to a subnet.

35.256 MYSQL_LB_SFLQ_POOL6_DELETE

```
delete the V6 SFLQ pool with start address %1 and end address %2, force = %3
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back to delete the v6 SFLQ pool (and it's free lease data) that match the given start and end addresses.

35.257 MYSQL_LB_SFLQ_POOL6_GET_ALL

```
fetch all V6 SFLQ pools
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a list of all v6 SFLQ pools.

35.258 MYSQL_LB_SFLQ_POOL6_GET_BY_RANGE

```
fetch all V6 SFLQ pools that overlap the range %1 and %2
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for the v6 SFLQ pool that overlap the given address range.

35.259 MYSQL_LB_SFLQ_POOL6_GET_BY_SUBNET

```
fetch all V6 SFLQ pools for subnet-id %1
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a list of all v6 SFLQ pools belonging to a subnet.

35.260 MYSQL_LB_TLS_CIPHER

```
TLS cipher: %1
```

Logged at debug log level 40. This debug message is issued when a new MySQL connected is created with TLS. The TLS cipher name is logged.

35.261 MYSQL_LB_UPDATE_ADDR4

```
updating IPv4 lease for address %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to update IPv4 lease from the MySQL database for the specified address.

35.262 MYSQL_LB_UPDATE_ADDR6

```
updating IPv6 lease for address %1, lease type %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to update IPv6 lease from the MySQL database for the specified address.

35.263 MYSQL_LB_UPGRADE_EXTENDED_INFO4

```
upgrading IPv4 leases done in %1 pages with %2 updated leases
```

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

35.264 MYSQL_LB_UPGRADE_EXTENDED_INFO4_ERROR

```
upgrading extending info for IPv4 lease at %1 failed with %2
```

Logged at debug log level 40. This debug message is issued when the server failed to upgrade an extended info. The address of the lease and the error message are displayed.

35.265 MYSQL_LB_UPGRADE_EXTENDED_INFO4_PAGE

```
upgrading IPv4 lease extended info at page %1 starting at %2 (updated %3)
```

Logged at debug log level 50. This debug message is issued when the server upgrades IPv4 lease extended info. The page number and started address, and the count of already updated leases are displayed.

35.266 MYSQL_LB_UPGRADE_EXTENDED_INFO6

```
upgrading IPv6 leases done in %1 pages with %2 updated leases
```

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

35.267 MYSQL_LB_UPGRADE_EXTENDED_INFO6_ERROR

upgrading extending info for IPv6 lease at %1 failed with %2

Logged at debug log level 40. This debug message is issued when the server failed to upgrade the extended info for a lease. The address of the lease and the error message are displayed.

35.268 MYSQL_LB_UPGRADE_EXTENDED_INFO6_PAGE

upgrading IPv6 lease extended info at page %1 starting at %2 (updated %3)

Logged at debug log level 50. This debug message is issued when the server upgrades IPv6 lease extended info. The page number and started address, and the count of already updated leases are displayed.

36.1 NETCONF_BOOT_UPDATE_COMPLETED

```
Boot-update configuration completed for server %1
```

This informational message is issued when the initial configuration was retrieved using NETCONF and successfully applied to Kea server.

36.2 NETCONF_CONFIG_CHANGED_DETAIL

```
YANG configuration changed: %1
```

Logged at debug log level 55. This debug message indicates a YANG configuration change. The format is the change operation (created, modified, deleted or moved) followed by xpaths and values of old and new nodes.

36.3 NETCONF_CONFIG_CHANGE_EVENT

```
Received YANG configuration change %1 event
```

This informational message is issued when kea-netconf receives a YANG configuration change event. The type of event is printed.

36.4 NETCONF_CONFIG_CHECK_FAIL

```
NETCONF configuration check failed: %1
```

This error message indicates that kea-netconf had failed configuration check. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

36.5 NETCONF_CONFIG_FAIL

```
NETCONF configuration failed: %1
```

This error message indicates that kea-netconf had failed configuration attempt. Details are provided. Additional details may be available in earlier log entries, possibly on lower levels.

36.6 NETCONF_CONFIG_SYNTAX_WARNING

```
NETCONF configuration syntax warning: %1
```

This warning message indicates that the NETCONF configuration had a minor syntax error. The error was displayed and the configuration parsing resumed.

36.7 NETCONF_CONTROL_SOCKET_INFO

```
the service: %1 started using control socket type: %2 %3
```

This info message provides details of the control socket used for the respective service. The service name, socket type and details are logged.

36.8 NETCONF_FAILED

```
application experienced a fatal error: %1
```

This is a fatal error message issued when kea-netconf got an unrecoverable error from within the event loop.

36.9 NETCONF_GET_CONFIG

```
got configuration from %1 server: %2
```

Logged at debug log level 55. This debug message indicates that kea-netconf got the configuration from a Kea server. The server name and the retrieved configuration are printed.

36.10 NETCONF_GET_CONFIG_FAILED

```
getting configuration from %1 server failed: %2
```

The error message indicates that kea-netconf got an error getting the configuration from a Kea server. Make sure that the server is up and running, has appropriate control socket defined and that the controls socket configuration on the server matches that of kea-netconf. The name of the server and the error are printed.

36.11 NETCONF_GET_CONFIG_STARTED

```
getting configuration from %1 server
```

This informational message indicates that kea-netconf is trying to get the configuration from a Kea server.

36.12 NETCONF_MODULE_CHANGE_INTERNAL_ERROR

```
an internal error occurred while processing changes for module %1: %2
```

The error message indicates that kea-netconf got an error while sysrepo was processing modules changes. This usually follows a config validation failure, and can be recovered from. The name of the module and the internal error message are printed.

36.13 NETCONF_MODULE_MISSING_ERR

Missing essential module %1 in sysrepo

This fatal error message indicates that a module required by Netconf configuration is not available in the sysrepo repository. The name of the module is printed.

36.14 NETCONF_MODULE_MISSING_WARN

Missing module %1 in sysrepo

This warning message indicates that a module used by Kea is not available in the sysrepo repository. The name of the module is printed.

36.15 NETCONF_MODULE_REVISION_ERR

Essential module %1 does NOT have the right revision: expected %2, got %3

This fatal error message indicates that a module required by Netconf configuration is not at the right revision in the sysrepo repository. The name, expected and available revisions of the module are printed.

36.16 NETCONF_MODULE_REVISION_WARN

Module %1 does NOT have the right revision: expected %2, got %3

This warning message indicates that a module used by Kea is not at the right revision in the sysrepo repository. The name, expected and available revisions of the module are printed.

36.17 NETCONF_NOTIFICATION_INTERNAL_ERROR

an internal error occurred while sending an event notification for module %1: %2

The error message indicates that kea-netconf got an error while sysrepo was sending an event notification. This error is not fatal and can be recovered from. The name of the module and the internal error message are printed.

36.18 NETCONF_NOTIFICATION_RECEIVED

Received notification of type %1 for module %2: '%3'

This informational message logs any YANG notification that has been signaled by the server, sent to kea-netconf which then was forwarded to subscribed clients. To achieve this, kea-netconf subscribes itself as a client to all notifications for the configured module.

36.19 NETCONF_NOT_SUBSCRIBED_TO_NOTIFICATIONS

subscribing to notifications for %1 server with %2 module failed: %3

The warning message indicates that kea-netconf got an error subscribing to notifications for a Kea server. The most probable cause is probably that the model that kea-netconf subscribed to does not have any notification nodes, but there may be other more unexpected causes as well. The server name, module name and the error are printed.

36.20 NETCONF_RUN_EXIT

```
application is exiting the event loop
```

Logged at debug log level 0. This is a debug message issued when kea-netconf exits its event loop. This is a normal step during kea-netconf shutdown.

36.21 NETCONF_SET_CONFIG

```
set configuration to %1 server: %2
```

Logged at debug log level 55. This debug message indicates that kea-netconf set the configuration to a Kea server. The server name and the applied configuration are printed.

36.22 NETCONF_SET_CONFIG_FAILED

```
setting configuration to %1 server failed: %2
```

The error message indicates that kea-netconf got an error setting the configuration to a Kea server. Make sure that the server is up and running, has appropriate control socket defined and that the controls socket configuration on the server matches that of kea-netconf. The name of the server and the error are printed.

36.23 NETCONF_SET_CONFIG_STARTED

```
setting configuration to %1 server
```

This informational message indicates that kea-netconf is trying to set the configuration to a Kea server.

36.24 NETCONF_STARTED

```
kea-netconf (version %1) started
```

This informational message indicates that kea-netconf has processed all configuration information and is ready to begin processing. The version is also printed.

36.25 NETCONF_SUBSCRIBE_CONFIG

```
subscribing configuration changes for %1 server with %2 module
```

This information message indicates that kea-netconf is trying to subscribe configuration changes for a Kea server. The names of the server and the module are printed.

36.26 NETCONF_SUBSCRIBE_CONFIG_FAILED

```
subscribe configuration changes for %1 server with %2 module failed: %3
```

The error message indicates that kea-netconf got an error subscribing configuration changes for a Kea server. The names of the server and the module, and the error are printed.

36.27 NETCONF_SUBSCRIBE_NOTIFICATIONS

```
subscribing to notifications for %1 server with %2 module
```

This information message indicates that kea-netconf is trying to subscribe to notifications for a Kea server. The server name and module name are printed.

36.28 NETCONF_UPDATE_CONFIG

```
updating configuration with %1 server: %2
```

Logged at debug log level 55. This debug message indicates that kea-netconf update the configuration of a Kea server. The server name and the updated configuration are printed.

36.29 NETCONF_UPDATE_CONFIG_COMPLETED

```
completed updating configuration for %1 server
```

This informational message indicates that kea-netconf updated with success the configuration of a Kea server.

36.30 NETCONF_UPDATE_CONFIG_FAILED

```
updating configuration with %1 server: %2
```

The error message indicates that kea-netconf got an error updating the configuration of a Kea server. This includes a configuration rejected by a Kea server when it tried to apply it. The name of the server and the error are printed.

36.31 NETCONF_UPDATE_CONFIG_STARTED

```
started updating configuration for %1 server
```

This informational message indicates that kea-netconf is trying to update the configuration of a Kea server.

36.32 NETCONF_VALIDATE_CONFIG

```
validating configuration with %1 server: %2
```

Logged at debug log level 55. This debug message indicates that kea-netconf is validating the configuration with a Kea server. The server name and the validated configuration are printed.

36.33 NETCONF_VALIDATE_CONFIG_COMPLETED

```
completed validating configuration for %1 server
```

This informational message indicates that kea-netconf validated with success the configuration with a Kea server.

36.34 NETCONF_VALIDATE_CONFIG_FAILED

```
validating configuration with %1 server got an error: %2
```

The error message indicates that kea-netconf got an error validating the configuration with a Kea server. This message is produced when exception is thrown during an attempt to validate received configuration. Additional explanation may be provided as a parameter. You may also take a look at earlier log messages. The name of the server and the error are printed.

36.35 NETCONF_VALIDATE_CONFIG_REJECTED

```
validating configuration with %1 server was rejected: %2
```

The warning message indicates that kea-netconf got an error validating the configuration with a Kea server. This message is printed when the configuration was rejected during normal processing. Additional explanation may be provided as a parameter. You may also take a look at earlier log messages. The name of the server and the error are printed.

36.36 NETCONF_VALIDATE_CONFIG_STARTED

```
started validating configuration for %1 server
```

This informational message indicates that kea-netconf is trying to validate the configuration with a Kea server.

PERFMON

37.1 PERFMON_ALARM_CLEARED

```
Alarm for %1 has been cleared, reported mean duration %2 is now below low-water-ms: %3
```

This info message is emitted when the reported mean duration for an alarm that has been triggered has fallen below the value of its low-water-ms parameter. The arguments detail the alarm's key and the most recently reported mean.

37.2 PERFMON_ALARM_TRIGGERED

```
Alarm for %1 has been triggered since %2, reported mean duration %3 exceeds high-water-ms: %4
```

This warning message is emitted when the reported mean duration for an alarm exceeds its high-water-ms value. As long as the reported averages remain above the low-water-ms value, the alarm will remain triggered and this message will be repeated every alarm-report-secs. Arguments detail the alarm's key, the time the alarm was first triggered, the most recent reported mean, and the high-water-ms value.

37.3 PERFMON_CMDS_CONTROL_ERROR

```
perfmon-control command processing failed: %1
```

This error message is issued when the PerfMon hook library encounters an error processing a perfmon-control command. The argument explains the command error.

37.4 PERFMON_CMDS_CONTROL_OK

```
perfmon-control command success: active monitoring: %1, stats-mgr-reporting: %2
```

This info log is issued when perfmon-control command has successfully enabled/disabled active monitoring and/or statistics mgr reporting. Arguments reflect the current state of both.

37.5 PERFMON_CMDS_GET_ALL_DURATIONS_ERROR

```
perfmon-get-all-durations command processing failed: %1
```

This error message is issued when the PerfMon hook library encounters an error processing a perfmon-get-all-durations command. The argument explains the command error.

37.6 PERFMON_CMDS_GET_ALL_DURATIONS_OK

```
perfmon-get-all-durations returning %1 durations
```

This info log is issued when perfmon-get-all-durations command has completed successfully. The argument contains the number of durations returned.

37.7 PERFMON_DEINIT_OK

```
unloading PerfMon hooks library successful
```

This info message indicates that the PerfMon hooks library has been removed successfully.

37.8 PERFMON_DHCP4_PKT_EVENTS

```
query: %1 events=[%2]
```

Logged at debug log level 50. This debug message is emitted after an inbound DHCPv4 query has been processed, the arguments are the query label and the dump of the query's packet event stack.

37.9 PERFMON_DHCP4_PKT_PROCESS_ERROR

```
Packet event stack was not processed for query %1, reason %2
```

Logged at debug log level 50. This debug message is emitted when the query's event stack could not be processed. This is most likely a programmatic error and should be reported. The arguments identify the query and the reason it could not be processed. These errors should not affect server's normal operations.

37.10 PERFMON_DHCP4_SOCKET_RECEIVED_TIME_SUPPORT

```
Kernel supports socket received time? %1
```

Logged at debug log level 40. This debug message is emitted after a (re)configuration and indicates whether or not the packet filter being used by kea-dhcp4 can supply the timestamp a packet was received by the kernel for recording SOCKET_RECEIVED events. If it does not, perfmon will still function but will not have data available to determine kernel buffer wait times.

37.11 PERFMON_DHCP6_PKT_EVENTS

```
query: %1 events=[%2]
```

Logged at debug log level 50. The debug message is emitted after an inbound DHCPv6 query has been processed, the arguments are the query label and the dump of the query's packet event stack.

37.12 PERFMON_DHCP6_PKT_PROCESS_ERROR

```
Packet event stack was not processed for query %1, reason %2
```

Logged at debug log level 50. This debug message is emitted when the query's event stack could not be processed. This is most likely a programmatic error and should be reported. The arguments identify the query and the reason it could not be processed. These errors should not affect server's normal operations.

37.13 PERFMON_DHCP6_SOCKET_RECEIVED_TIME_SUPPORT

```
Kernel supports socket received time? %1
```

Logged at debug log level 40. This debug message is emitted after a (re)configuration and indicates whether or not the packet filter being used by kea-dhcp6 can supply the timestamp a packet was received by the kernel for recording SOCKET_RECEIVED events. If it does not, perfmon will still function but will not have data available to determine kernel buffer wait times.

37.14 PERFMON_INIT_FAILED

```
loading PerfMon hooks library failed: %1
```

This error message indicates an error during loading the PerfMon hooks library. The details of the error are provided as argument of the log message.

37.15 PERFMON_INIT_OK

```
loading PerfMon hooks library successful
```

This info message indicates that the PerfMon hooks library has been loaded successfully. Enjoy!

38.1 PGSQL_CB_CREATE_UPDATE_BY_POOL_OPTION4

create or update option pool start: %1 pool end: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

38.2 PGSQL_CB_CREATE_UPDATE_BY_POOL_OPTION6

create or update option pool start: %1 pool end: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by pool

38.3 PGSQL_CB_CREATE_UPDATE_BY_PREFIX_OPTION6

create or update option prefix: %1 prefix len: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by prefix

38.4 PGSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION4

create or update option by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

38.5 PGSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION6

create or update option by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update option by subnet id

38.6 PGSQL_CB_CREATE_UPDATE_CLIENT_CLASS4

create or update client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

38.7 PGSQL_CB_CREATE_UPDATE_CLIENT_CLASS6

create or update client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update client class

38.8 PGSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER4

create or update global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

38.9 PGSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER6

create or update global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update global parameter

38.10 PGSQL_CB_CREATE_UPDATE_OPTION4

create or update option

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

38.11 PGSQL_CB_CREATE_UPDATE_OPTION6

create or update option

Logged at debug log level 40. Debug message issued when triggered an action to create or update option

38.12 PGSQL_CB_CREATE_UPDATE_OPTION_DEF4

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

38.13 PGSQL_CB_CREATE_UPDATE_OPTION_DEF6

create or update option definition: %1 code: %2

Logged at debug log level 40. Debug message issued when triggered an action to create or update option definition

38.14 PGSQL_CB_CREATE_UPDATE_SERVER4

create or update server: %1

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv4 server information.

38.15 PGSQL_CB_CREATE_UPDATE_SERVER6

```
create or update server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update a DHCPv6 server information.

38.16 PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK4

```
create or update shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

38.17 PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK6

```
create or update shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network

38.18 PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION4

```
create or update shared network: %1 option
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

38.19 PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION6

```
create or update shared network: %1 option
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update shared network option

38.20 PGSQL_CB_CREATE_UPDATE_SUBNET4

```
create or update subnet: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

38.21 PGSQL_CB_CREATE_UPDATE_SUBNET6

```
create or update subnet: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to create or update subnet

38.22 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES4

```
delete all client classes
```

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

38.23 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

38.24 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES6

delete all client classes

Logged at debug log level 40. Debug message issued when triggered an action to delete all client classes

38.25 PGSQL_CB_DELETE_ALL_CLIENT_CLASSES6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all client classes

38.26 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4

delete all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

38.27 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

38.28 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6

delete all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to delete all global parameters

38.29 PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all global parameters

38.30 PGSQL_CB_DELETE_ALL_OPTION_DEFS4

delete all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

38.31 PGSQL_CB_DELETE_ALL_OPTION_DEFS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

38.32 PGSQL_CB_DELETE_ALL_OPTION_DEFS6

delete all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to delete all option definitions

38.33 PGSQL_CB_DELETE_ALL_OPTION_DEFS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all option definitions

38.34 PGSQL_CB_DELETE_ALL_SERVERS4

delete all DHCPv4 servers

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

38.35 PGSQL_CB_DELETE_ALL_SERVERS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

38.36 PGSQL_CB_DELETE_ALL_SERVERS6

delete all DHCPv6 servers

Logged at debug log level 40. Debug message issued when triggered an action to delete all servers.

38.37 PGSQL_CB_DELETE_ALL_SERVERS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all servers.

38.38 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS4

delete all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

38.39 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

38.40 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS6

delete all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to delete all shared networks

38.41 PGSQL_CB_DELETE_ALL_SHARED_NETWORKS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all shared networks

38.42 PGSQL_CB_DELETE_ALL_SUBNETS4

delete all subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

38.43 PGSQL_CB_DELETE_ALL_SUBNETS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

38.44 PGSQL_CB_DELETE_ALL_SUBNETS6

delete all subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete all subnets

38.45 PGSQL_CB_DELETE_ALL_SUBNETS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete all subnets

38.46 PGSQL_CB_DELETE_BY_POOL_OPTION4

delete pool start: %1 pool end: %2 option code: %3 space: %4

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

38.47 PGSQL_CB_DELETE_BY_POOL_OPTION4_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

38.48 PGSQL_CB_DELETE_BY_POOL_OPTION6

```
delete pool start: %1 pool end: %2 option code: %3 space: %4
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by pool

38.49 PGSQL_CB_DELETE_BY_POOL_OPTION6_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by pool

38.50 PGSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6

```
delete prefix: %1 prefix len: %2 option code: %3 space: %4
```

Logged at debug log level 40. Debug message issued when triggered an action to delete option by prefix

38.51 PGSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete option by prefix

38.52 PGSQL_CB_DELETE_BY_PREFIX_SUBNET4

```
delete subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

38.53 PGSQL_CB_DELETE_BY_PREFIX_SUBNET4_RESULT

```
deleted: %1 entries
```

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

38.54 PGSQL_CB_DELETE_BY_PREFIX_SUBNET6

```
delete subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by prefix

38.55 PGSQL_CB_DELETE_BY_PREFIX_SUBNET6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by prefix

38.56 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION4

delete by subnet id: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

38.57 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

38.58 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION6

delete by subnet id: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete option by subnet id

38.59 PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option by subnet id

38.60 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4

delete subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

38.61 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

38.62 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6

delete subnet by subnet id: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete subnet by subnet id

38.63 PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete subnet by subnet id

38.64 PGSQL_CB_DELETE_CLIENT_CLASS4

delete client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

38.65 PGSQL_CB_DELETE_CLIENT_CLASS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

38.66 PGSQL_CB_DELETE_CLIENT_CLASS6

delete client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete client class

38.67 PGSQL_CB_DELETE_CLIENT_CLASS6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete client class

38.68 PGSQL_CB_DELETE_GLOBAL_PARAMETER4

delete global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

38.69 PGSQL_CB_DELETE_GLOBAL_PARAMETER4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

38.70 PGSQL_CB_DELETE_GLOBAL_PARAMETER6

delete global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete global parameter

38.71 PGSQL_CB_DELETE_GLOBAL_PARAMETER6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete global parameter

38.72 PGSQL_CB_DELETE_OPTION4

delete option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option

38.73 PGSQL_CB_DELETE_OPTION4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option

38.74 PGSQL_CB_DELETE_OPTION6

delete option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option

38.75 PGSQL_CB_DELETE_OPTION6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option

38.76 PGSQL_CB_DELETE_OPTION_DEF4

delete option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

38.77 PGSQL_CB_DELETE_OPTION_DEF4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

38.78 PGSQL_CB_DELETE_OPTION_DEF6

delete option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to delete option definition

38.79 PGSQL_CB_DELETE_OPTION_DEF6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete option definition

38.80 PGSQL_CB_DELETE_SERVER4

delete DHCPv4 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

38.81 PGSQL_CB_DELETE_SERVER4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

38.82 PGSQL_CB_DELETE_SERVER6

delete DHCPv6 server: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete a server.

38.83 PGSQL_CB_DELETE_SERVER6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete a server.

38.84 PGSQL_CB_DELETE_SHARED_NETWORK4

delete shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

38.85 PGSQL_CB_DELETE_SHARED_NETWORK4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

38.86 PGSQL_CB_DELETE_SHARED_NETWORK6

delete shared network: %1

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network

38.87 PGSQL_CB_DELETE_SHARED_NETWORK6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network

38.88 PGSQL_CB_DELETE_SHARED_NETWORK_OPTION4

delete shared network: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

38.89 PGSQL_CB_DELETE_SHARED_NETWORK_OPTION4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

38.90 PGSQL_CB_DELETE_SHARED_NETWORK_OPTION6

delete shared network: %1 option code: %2 space: %3

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network option

38.91 PGSQL_CB_DELETE_SHARED_NETWORK_OPTION6_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network option

38.92 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4

delete shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

38.93 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT

deleted: %1 entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

38.94 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6

delete shared network: %1 subnets

Logged at debug log level 40. Debug message issued when triggered an action to delete shared network subnets

38.95 PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT

deleted: %l entries

Logged at debug log level 40. Debug message indicating the result of an action to delete shared network subnets

38.96 PGSQL_CB_GET_ALL_CLIENT_CLASSES4

retrieving all client classes

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

38.97 PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

38.98 PGSQL_CB_GET_ALL_CLIENT_CLASSES6

retrieving all client classes

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all client classes

38.99 PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all client classes

38.100 PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4

retrieving all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

38.101 PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

38.102 PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6

retrieving all global parameters

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all global parameters

38.103 PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all global parameters

38.104 PGSQL_CB_GET_ALL_OPTIONS4

retrieving all options

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

38.105 PGSQL_CB_GET_ALL_OPTIONS4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

38.106 PGSQL_CB_GET_ALL_OPTIONS6

retrieving all options

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all options

38.107 PGSQL_CB_GET_ALL_OPTIONS6_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all options

38.108 PGSQL_CB_GET_ALL_OPTION_DEFS4

retrieving all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

38.109 PGSQL_CB_GET_ALL_OPTION_DEFS4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

38.110 PGSQL_CB_GET_ALL_OPTION_DEFS6

retrieving all option definitions

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all option definitions

38.111 PGSQL_CB_GET_ALL_OPTION_DEFS6_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all option definitions

38.112 PGSQL_CB_GET_ALL_SERVERS4

retrieving all servers

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv4 servers

38.113 PGSQL_CB_GET_ALL_SERVERS4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv4 servers

38.114 PGSQL_CB_GET_ALL_SERVERS6

retrieving all DHCPv6 servers

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all DHCPv6 servers

38.115 PGSQL_CB_GET_ALL_SERVERS6_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all DHCPv6 servers

38.116 PGSQL_CB_GET_ALL_SHARED_NETWORKS4

retrieving all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

38.117 PGSQL_CB_GET_ALL_SHARED_NETWORKS4_RESULT

retrieving: %l elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

38.118 PGSQL_CB_GET_ALL_SHARED_NETWORKS6

retrieving all shared networks

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all shared networks

38.119 PGSQL_CB_GET_ALL_SHARED_NETWORKS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all shared networks

38.120 PGSQL_CB_GET_ALL_SUBNETS4

retrieving all subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

38.121 PGSQL_CB_GET_ALL_SUBNETS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

38.122 PGSQL_CB_GET_ALL_SUBNETS6

retrieving all subnets

Logged at debug log level 40. Debug message issued when triggered an action to retrieve all subnets

38.123 PGSQL_CB_GET_ALL_SUBNETS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve all subnets

38.124 PGSQL_CB_GET_CLIENT_CLASS4

retrieving client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

38.125 PGSQL_CB_GET_CLIENT_CLASS6

retrieving client class: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a client class

38.126 PGSQL_CB_GET_GLOBAL_PARAMETER4

retrieving global parameter: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

38.127 PGSQL_CB_GET_GLOBAL_PARAMETER6

```
retrieving global parameter: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve global parameter

38.128 PGSQL_CB_GET_HOST4

```
get host
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

38.129 PGSQL_CB_GET_HOST6

```
get host
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve host

38.130 PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES4

```
retrieving modified client classes from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

38.131 PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES4_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

38.132 PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES6

```
retrieving modified client classes from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified client classes from specified time

38.133 PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES6_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified client classes from specified time

38.134 PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4

```
retrieving modified global parameters from: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

38.135 PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

38.136 PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6

retrieving modified global parameters from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified global parameters from specified time

38.137 PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified global parameters from specified time

38.138 PGSQL_CB_GET_MODIFIED_OPTIONS4

retrieving modified options from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

38.139 PGSQL_CB_GET_MODIFIED_OPTIONS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

38.140 PGSQL_CB_GET_MODIFIED_OPTIONS6

retrieving modified options from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified options from specified time

38.141 PGSQL_CB_GET_MODIFIED_OPTIONS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified options from specified time

38.142 PGSQL_CB_GET_MODIFIED_OPTION_DEFS4

retrieving modified option definitions from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

38.143 PGSQL_CB_GET_MODIFIED_OPTION_DEFS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

38.144 PGSQL_CB_GET_MODIFIED_OPTION_DEFS6

retrieving modified option definitions from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified option definitions from specified time

38.145 PGSQL_CB_GET_MODIFIED_OPTION_DEFS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified option definitions from specified time

38.146 PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS4

retrieving modified shared networks from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

38.147 PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

38.148 PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS6

retrieving modified shared networks from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified shared networks from specified time

38.149 PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified shared networks from specified time

38.150 PGSQL_CB_GET_MODIFIED_SUBNETS4

retrieving modified subnets from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

38.151 PGSQL_CB_GET_MODIFIED_SUBNETS4_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

38.152 PGSQL_CB_GET_MODIFIED_SUBNETS6

retrieving modified subnets from: %1

Logged at debug log level 40. Debug message issued when triggered an action to retrieve modified subnets from specified time

38.153 PGSQL_CB_GET_MODIFIED_SUBNETS6_RESULT

retrieving: %1 elements

Logged at debug log level 40. Debug message indicating the result of an action to retrieve modified subnets from specified time

38.154 PGSQL_CB_GET_OPTION4

retrieving option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

38.155 PGSQL_CB_GET_OPTION6

retrieving option code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option

38.156 PGSQL_CB_GET_OPTION_DEF4

retrieving option definition code: %1 space: %2

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

38.157 PGSQL_CB_GET_OPTION_DEF6

```
retrieving option definition code: %1 space: %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve option definition

38.158 PGSQL_CB_GET_PORT4

```
get port
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

38.159 PGSQL_CB_GET_PORT6

```
get port
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve port

38.160 PGSQL_CB_GET_RECENT_AUDIT_ENTRIES4

```
retrieving audit entries from: %1 %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id.

38.161 PGSQL_CB_GET_RECENT_AUDIT_ENTRIES4_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

38.162 PGSQL_CB_GET_RECENT_AUDIT_ENTRIES6

```
retrieving audit entries from: %1 %2
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve audit entries from specified time and id

38.163 PGSQL_CB_GET_RECENT_AUDIT_ENTRIES6_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve audit entries from specified time

38.164 PGSQL_CB_GET_SERVER4

```
retrieving DHCPv4 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv4 server information.

38.165 PGSQL_CB_GET_SERVER6

```
retrieving DHCPv6 server: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve a DHCPv6 server information.

38.166 PGSQL_CB_GET_SHARED_NETWORK4

```
retrieving shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

38.167 PGSQL_CB_GET_SHARED_NETWORK6

```
retrieving shared network: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network

38.168 PGSQL_CB_GET_SHARED_NETWORK_SUBNETS4

```
retrieving shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

38.169 PGSQL_CB_GET_SHARED_NETWORK_SUBNETS4_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

38.170 PGSQL_CB_GET_SHARED_NETWORK_SUBNETS6

```
retrieving shared network: %1 subnets
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve shared network subnets

38.171 PGSQL_CB_GET_SHARED_NETWORK_SUBNETS6_RESULT

```
retrieving: %1 elements
```

Logged at debug log level 40. Debug message indicating the result of an action to retrieve shared network subnets

38.172 PGSQL_CB_GET_SUBNET4_BY_PREFIX

```
retrieving subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

38.173 PGSQL_CB_GET_SUBNET4_BY_SUBNET_ID

```
retrieving subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

38.174 PGSQL_CB_GET_SUBNET6_BY_PREFIX

```
retrieving subnet by prefix: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by prefix

38.175 PGSQL_CB_GET_SUBNET6_BY_SUBNET_ID

```
retrieving subnet by subnet id: %1
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve subnet by subnet id

38.176 PGSQL_CB_GET_TYPE4

```
get type
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

38.177 PGSQL_CB_GET_TYPE6

```
get type
```

Logged at debug log level 40. Debug message issued when triggered an action to retrieve type

38.178 PGSQL_CB_RECONNECT_ATTEMPT_FAILED4

```
database reconnect failed: %1
```

Error message issued when an attempt to reconnect has failed.

38.179 PGSQL_CB_RECONNECT_ATTEMPT_FAILED6

```
database reconnect failed: %1
```

Error message issued when an attempt to reconnect has failed.

38.180 PGSQL_CB_RECONNECT_ATTEMPT_SCHEDULE4

```
scheduling attempt %1 of %2 in %3 milliseconds
```

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

38.181 PGSQL_CB_RECONNECT_ATTEMPT_SCHEDULE6

scheduling attempt %1 of %2 in %3 milliseconds

Info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

38.182 PGSQL_CB_RECONNECT_FAILED4

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

38.183 PGSQL_CB_RECONNECT_FAILED6

maximum number of database reconnect attempts: %1, has been exhausted without success

Error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

38.184 PGSQL_CB_REGISTER_BACKEND_TYPE4

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

38.185 PGSQL_CB_REGISTER_BACKEND_TYPE6

register backend

Logged at debug log level 40. Debug message issued when triggered an action to register backend

38.186 PGSQL_CB_UNREGISTER_BACKEND_TYPE4

unregister backend

Logged at debug log level 40. Debug message issued when triggered an action to unregister backend

38.187 PGSQL_CB_UNREGISTER_BACKEND_TYPE6

unregister backend

Logged at debug log level 40. Debug message issued when triggered an action to unregister backend

38.188 PGSQL_DEINIT_OK

unloading PostgreSQL hooks library successful

This informational message indicates that the PostgreSQL Backend hooks library has been unloaded successfully.

38.189 PGSQL_FB_DB

opening PostgreSQL log database: %1

This informational message is logged when the legal log hook library is about to open a PostgreSQL log database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

38.190 PGSQL_HB_DB

opening PostgreSQL hosts database: %1

This informational message is logged when a DHCP server (either V4 or V6) is about to open a PostgreSQL hosts database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

38.191 PGSQL_HB_DB_GET_VERSION

obtaining schema version information for the PostgreSQL hosts database

Logged at debug log level 50. This debug message is issued when the server is about to obtain schema version information from the PostgreSQL hosts database.

38.192 PGSQL_HB_DB_READONLY

PostgreSQL host database opened for read access only

This informational message is issued when the user has configured the PostgreSQL database in read-only mode. Kea will not be able to insert or modify host reservations but will be able to retrieve existing ones and assign them to the clients communicating with the server.

38.193 PGSQL_HB_DB_RECONNECT_ATTEMPT_FAILED

database reconnect failed: %1

An error message issued when an attempt to reconnect has failed.

38.194 PGSQL_HB_DB_RECONNECT_ATTEMPT_SCHEDULE

scheduling attempt %1 of %2 in %3 milliseconds

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

38.195 PGSQL_HB_DB_RECONNECT_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

38.196 PGSQL_INIT_OK

```
loading PostgreSQL hooks library successful
```

This informational message indicates that the PostgreSQL Backend hooks library has been loaded successfully. Enjoy!

38.197 PGSQL_LB_ADD_ADDR4

```
adding IPv4 lease with address %1
```

Logged at debug log level 50. This debug message is issued when the server is about to add an IPv4 lease with the specified address to the PostgreSQL backend database.

38.198 PGSQL_LB_ADD_ADDR6

```
adding IPv6 lease with address %1, lease type %2
```

Logged at debug log level 50. This debug message is issued when the server is about to add an IPv6 lease with the specified address to the PostgreSQL backend database.

38.199 PGSQL_LB_COMMIT

```
committing to PostgreSQL database
```

Logged at debug log level 50. The code has issued a commit call. All outstanding transactions will be committed to the database. Note that depending on the PostgreSQL settings, the commit may not include a write to disk.

38.200 PGSQL_LB_DB

```
opening PostgreSQL lease database: %1
```

This informational message is logged when a DHCP server (either V4 or V6) is about to open a PostgreSQL lease database. The parameters of the connection including database name and username needed to access it (but not the password if any) are logged.

38.201 PGSQL_LB_DB_RECONNECT_ATTEMPT_FAILED

```
database reconnect failed: %1
```

An error message issued when an attempt to reconnect has failed.

38.202 PGSQL_LB_DB_RECONNECT_ATTEMPT_SCHEDULE

```
scheduling attempt %1 of %2 in %3 milliseconds
```

An info message issued when the server is scheduling the next attempt to reconnect to the database. This occurs when the server has lost database connectivity and is attempting to reconnect automatically.

38.203 PGSQL_LB_DB_RECONNECT_FAILED

maximum number of database reconnect attempts: %1, has been exhausted without success

An error message issued when the server failed to reconnect. Loss of connectivity is typically a network or database server issue.

38.204 PGSQL_LB_DELETED_SUBNET4_ID

deleted %1 leases that match subnet ID %2.

Logged at debug log level 50. This debug message is issued when the server is removing leases which match respective subnet ID.

38.205 PGSQL_LB_DELETED_SUBNET6_ID

deleted %1 leases that match subnet ID %2.

Logged at debug log level 50. This debug message is issued when the server is removing leases which match respective subnet ID.

38.206 PGSQL_LB_DELETE_ADDR4

deleting lease for address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to delete a lease for the specified address from the PostgreSQL database for the specified address.

38.207 PGSQL_LB_DELETE_ADDR6

deleting lease for address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to delete a lease for the specified address from the PostgreSQL database for the specified address.

38.208 PGSQL_LB_DELETE_EXPIRED_RECLAIMED4

deleting reclaimed IPv4 leases that expired more than %1 seconds ago

Logged at debug log level 50. This debug message is issued when the server is removing reclaimed DHCPv4 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

38.209 PGSQL_LB_DELETE_EXPIRED_RECLAIMED6

deleting reclaimed IPv6 leases that expired more than %1 seconds ago

Logged at debug log level 50. This debug message is issued when the server is removing reclaimed DHCPv6 leases which have expired longer than a specified period of time. The argument is the amount of time Kea waits after a reclaimed lease expires before considering its removal.

38.210 PGSQL_LB_GET4

obtaining all IPv4 leases

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv4 leases from the PostgreSQL database.

38.211 PGSQL_LB_GET6

obtaining all IPv6 leases

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv6 leases from the PostgreSQL database.

38.212 PGSQL_LB_GET_ADDR4

obtaining IPv4 lease for address %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for the specified address.

38.213 PGSQL_LB_GET_ADDR6

obtaining IPv6 lease for address %1 (lease type %2)

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv6 lease from the PostgreSQL database for the specified address.

38.214 PGSQL_LB_GET_CLIENTID

obtaining IPv4 leases for client ID %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified client identification.

38.215 PGSQL_LB_GET_DUID

obtaining IPv6 leases for DUID %1,

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified DUID (DHCP Unique Identifier).

38.216 PGSQL_LB_GET_EXPIRED4

obtaining maximum %1 of expired IPv4 leases

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain expired IPv4 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

38.217 PGSQL_LB_GET_EXPIRED6

```
obtaining maximum %1 of expired IPv6 leases
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain expired IPv6 leases to reclaim them. The maximum number of leases to be retrieved is logged in the message.

38.218 PGSQL_LB_GET_HOSTNAME4

```
obtaining IPv4 leases for hostname %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified hostname.

38.219 PGSQL_LB_GET_HOSTNAME6

```
obtaining IPv6 leases for hostname %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified hostname.

38.220 PGSQL_LB_GET_HWADDR4

```
obtaining IPv4 leases for hardware address %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database for a client with the specified hardware address.

38.221 PGSQL_LB_GET_HWADDR6

```
obtaining IPv6 leases for hardware address %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified hardware address.

38.222 PGSQL_LB_GET_IAID_DUID

```
obtaining IPv4 leases for IAID %1 and DUID %2, lease type %3
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database for a client with the specified IAID (Identity Association ID) and DUID (DHCP Unique Identifier).

38.223 PGSQL_LB_GET_IAID_SUBID_DUID

```
obtaining IPv4 leases for IAID %1, subnet ID %2, DUID %3, and lease type %4
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv6 lease from the PostgreSQL database for a client with the specified IAID (Identity Association ID), subnet ID and DUID (DHCP Unique Identifier).

38.224 PGSQL_LB_GET_PAGE4

obtaining at most %1 IPv4 leases starting from address %2

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of leases beginning with the specified address.

38.225 PGSQL_LB_GET_PAGE6

obtaining at most %1 IPv6 leases starting from address %2

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of leases beginning with the specified address.

38.226 PGSQL_LB_GET_RELAYID4

obtaining at most %1 IPv4 leases starting from address %2 with relay id %3 and cltt between %4 and %5

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a relay id and client transaction time between start and end dates.

38.227 PGSQL_LB_GET_RELAYID6

obtaining at most %1 IPv6 leases starting from address %2 with relay id %3

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a relay id.

38.228 PGSQL_LB_GET_REMOTEID4

obtaining at most %1 IPv4 leases starting from address %2 with remote id %3 and cltt between %4 and %5

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv4 leases beginning with the specified address with a remote id and client transaction time between start and end dates.

38.229 PGSQL_LB_GET_REMOTEID6

obtaining at most %1 IPv6 leases starting from address %2 with remote id %3

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv6 leases beginning with the specified address with a remote id.

38.230 PGSQL_LB_GET_STATE4

obtaining IPv4 leases with state %1

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database with the specified state.

38.231 PGSQL_LB_GET_STATE6

```
obtaining IPv6 leases with state %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database with the specified state.

38.232 PGSQL_LB_GET_STATE_SUBID4

```
obtaining IPv4 leases with state %1 in subnet %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv4 leases from the PostgreSQL database with the specified state in the specified subnet.

38.233 PGSQL_LB_GET_STATE_SUBID6

```
obtaining IPv6 leases with state %1 in subnet %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a set of IPv6 leases from the PostgreSQL database with the specified state in the specified subnet.

38.234 PGSQL_LB_GET_SUBID4

```
obtaining IPv4 leases for subnet ID %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv4 leases for a given subnet identifier from the PostgreSQL database.

38.235 PGSQL_LB_GET_SUBID6

```
obtaining IPv6 leases for subnet ID %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain all IPv6 leases for a given subnet identifier from the PostgreSQL database.

38.236 PGSQL_LB_GET_SUBID_CLIENTID

```
obtaining IPv4 lease for subnet ID %1 and client ID %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for a client with the specified subnet ID and client ID.

38.237 PGSQL_LB_GET_SUBID_HWADDR

```
obtaining IPv4 lease for subnet ID %1 and hardware address %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain an IPv4 lease from the PostgreSQL database for a client with the specified subnet ID and hardware address.

38.238 PGSQL_LB_GET_SUBID_PAGE6

obtaining at most %1 IPv6 leases starting from address %2 for subnet ID %3

Logged at debug log level 50. This debug message is issued when the server is attempting to obtain a page of IPv6 leases from the PostgreSQL database beginning with the specified address for the specified subnet identifier.

38.239 PGSQL_LB_GET_VERSION

obtaining schema version information

Logged at debug log level 50. This debug message is issued when the server is about to obtain schema version information from the PostgreSQL database.

38.240 PGSQL_LB_NEGATIVE_LEASES_STAT

recount of leases returned a negative value

This warning message is issued when the recount of leases using counters in the PostgreSQL database returned a negative value. This shows a problem which can be fixed only by an offline direct recount on the database. This message is issued only once.

38.241 PGSQL_LB_ROLLBACK

rolling back PostgreSQL database

Logged at debug log level 50. The code has issued a rollback call. All outstanding transactions will be rolled back and not committed to the database.

38.242 PGSQL_LB_SFLQ_CREATE_POOL4

creating shared-flq pool for address range %1 - %2, subnet id %3, recreate %4, capacity %5

Logged at debug log level 50. This debug message is issued when the server asks the lease back end to (re)create the shared free lease data for the pool described in the arguments.

38.243 PGSQL_LB_SFLQ_CREATE_POOL6

creating shared-flq pool for address range %1 - %2, type %3, delegated length: %4, subnet id %5, recreate %6, capacity %7

Logged at debug log level 50. This debug message is issued when the server asks the lease back end to (re)create the shared free lease data for the pool described in the arguments.

38.244 PGSQL_LB_SFLQ_PICK_LEASE4

picking a free lease from address range %1 - %2

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a free address from the pool described in the arguments.

38.245 PGSQL_LB_SFLQ_PICK_LEASE6

```
picking a free lease from address range %1 - %2
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a free lease from the pool described in the arguments.

38.246 PGSQL_LB_SFLQ_POOL4_DELETE

```
delete the V4 SFLQ pool with start address %1 and end address %2, force = %3
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back to delete the v4 SFLQ pool (and it's free lease data) that match the given start and end addresses.

38.247 PGSQL_LB_SFLQ_POOL4_GET_ALL

```
fetch all V4 SFLQ pools
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a list of all v4 SFLQ pools.

38.248 PGSQL_LB_SFLQ_POOL4_GET_BY_RANGE

```
fetch all V4 SFLQ pools that overlap the range %1 and %2
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for the v4 SFLQ pool that overlap the given address range.

38.249 PGSQL_LB_SFLQ_POOL4_GET_BY_SUBNET

```
fetch all V4 SFLQ pools for subnet-id %1
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a list of all v4 SFLQ pools belonging to a subnet.

38.250 PGSQL_LB_SFLQ_POOL6_DELETE

```
delete the V6 SFLQ pool with start address %1 and end address %2, force = %3
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back to delete the v6 SFLQ pool (and it's free lease data) that match the given start and end addresses

38.251 PGSQL_LB_SFLQ_POOL6_GET_ALL

```
fetch all V6 SFLQ pools
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a list of all v6 SFLQ pools.

38.252 PGSQL_LB_SFLQ_POOL6_GET_BY_RANGE

```
fetch all V6 SFLQ pools that overlap the range %1 and %2
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for the v6 SFLQ pool that overlap the given address range.

38.253 PGSQL_LB_SFLQ_POOL6_GET_BY_SUBNET

```
fetch all V6 SFLQ pools for subnet-id %1
```

Logged at debug log level 50. This debug message is issued when the server asks the lease back end for a list of all v6 SFLQ pools belonging to a subnet.

38.254 PGSQL_LB_UPDATE_ADDR4

```
updating IPv4 lease for address %1
```

Logged at debug log level 50. This debug message is issued when the server is attempting to update IPv4 lease from the PostgreSQL database for the specified address.

38.255 PGSQL_LB_UPDATE_ADDR6

```
updating IPv6 lease for address %1, lease type %2
```

Logged at debug log level 50. This debug message is issued when the server is attempting to update IPv6 lease from the PostgreSQL database for the specified address.

38.256 PGSQL_LB_UPGRADE_EXTENDED_INFO4

```
upgrading IPv4 leases done in %1 pages with %2 updated leases
```

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

38.257 PGSQL_LB_UPGRADE_EXTENDED_INFO4_ERROR

```
upgrading extending info for IPv4 lease at %1 failed with %2
```

Logged at debug log level 40. This debug message is issued when the server failed to upgrade an extended info. The address of the lease and the error message are displayed.

38.258 PGSQL_LB_UPGRADE_EXTENDED_INFO4_PAGE

```
upgrading IPv4 lease extended info at page %1 starting at %2 (updated %3)
```

Logged at debug log level 50. This debug message is issued when the server upgrades IPv4 lease extended info. The page number and started address, and the count of already updated leases are displayed.

38.259 PGSQL_LB_UPGRADE_EXTENDED_INFO6

```
upgrading IPv6 leases done in %1 pages with %2 updated leases
```

Logged at debug log level 40. The server upgraded extended info. The number of pages and the final count of updated leases are displayed.

38.260 PGSQL_LB_UPGRADE_EXTENDED_INFO6_ERROR

```
upgrading extending info for IPv6 lease at %1 failed with %2
```

Logged at debug log level 40. This debug message is issued when the server failed to upgrade the extended info for a lease. The address of the lease and the error message are displayed.

38.261 PGSQL_LB_UPGRADE_EXTENDED_INFO6_PAGE

```
upgrading IPv6 lease extended info at page %1 starting at %2 (updated %3)
```

Logged at debug log level 50. This debug message is issued when the server upgrades IPv6 lease extended info. The page number and started address, and the count of already updated leases are displayed.

PING

39.1 PING_CHECK_CB4_UPDATE_FAILED

A subnet ping-check parameters failed to parse after being updated %1

This error message is emitted when an error occurs trying to parse a subnet ping-check parameters after the subnet was updated via configuration backend. This implies one or more of the parameters is invalid and must be corrected.

39.2 PING_CHECK_CHANNEL_ECHO_REPLY_RECEIVED

from address %1, id %2, sequence %3

Logged at debug log level 50. This debug message is issued when an ECHO REPLY has been received on the ping channel's ICMP socket.

39.3 PING_CHECK_CHANNEL_ECHO_REQUEST_SENT

to address %1, id %2, sequence %3

Logged at debug log level 50. This debug message is issued when an ECHO REQUEST has been written to the ping channel's ICMP socket.

39.4 PING_CHECK_CHANNEL_MALFORMED_PACKET_RECEIVED

error occurred unpacking message %1, discarding it

Logged at debug log level 40. This debug message is emitted when an ICMP packet has been received that could not be unpacked.

39.5 PING_CHECK_CHANNEL_NETWORK_WRITE_ERROR

occurred trying to ping %1, error %2

This error message occurs when an asynchronous write on the ICMP socket failed trying to send on the ping target's network. This may mean an interface is down or there is a configuration error. The lease address to ping and the type of the error are provided in the arguments.

39.6 PING_CHECK_CHANNEL_SOCKET_CLOSED

ICMP socket has been closed.

Logged at debug log level 40. This debug message is emitted when the ICMP socket for carrying out ping checks has been closed.

39.7 PING_CHECK_CHANNEL_SOCKET_CLOSE_ERROR

an attempt to close the ICMP socket failed %1

This error message is emitted when an unexpected error occurred while closing the ping check ICMP socket. The error detail is provided as an argument of the log message.

39.8 PING_CHECK_CHANNEL_SOCKET_OPENED

ICMP socket been opened successfully.

Logged at debug log level 40. This debug message is emitted when the ICMP socket for carrying out ping checks has been successfully opened.

39.9 PING_CHECK_CHANNEL_SOCKET_READ_FAILED

socket read completed with an error %1

This error message occurs when an asynchronous read on the ICMP socket failed. The details of the error are provided as an argument of the log message.

39.10 PING_CHECK_CHANNEL_SOCKET_WRITE_FAILED

socket write completed with an error %1

This error message occurs when an asynchronous write on the ICMP socket failed. The details of the error are provided as an argument of the log message.

39.11 PING_CHECK_CHANNEL_STOP

channel is stopping operations.

Logged at debug log level 40. This debug message indicates that the channel is stopping operations and closing the ICMP socket. The reason for stopping should be apparent in preceding log messages.

39.12 PING_CHECK_CHANNEL_WATCH_SOCKET_CLEAR_ERROR

an attempt to clear the WatchSocket associated with

the single-threaded ping-channel failed %1 This error message is emitted when an unexpected error occurred while clearing the ready marker of the WatchSocket associated with the ping check channel. This can only occur when running in single-threaded mode. The error detail is provided as an argument of the log message.

39.13 PING_CHECK_CHANNEL_WATCH_SOCKET_CLOSE_ERROR

an attempt to close the WatchSocket associated with

the single-threaded ping-channel failed %1 This error message is emitted when an unexpected error occurred while closing the WatchSocket associated with the ping check channel. This can only occur when running in single-threaded mode. The error detail is provided as an argument of the log message.

39.14 PING_CHECK_DHCP4_SRV_CONFIGURED_FAILED

dhcp4_srv_configured callout failed %1

This error message indicates an error during the Ping Check hook library dhcp4_srv_configured callout. The details of the error are provided as argument of the log message.

39.15 PING_CHECK_DUPLICATE_CHECK

Ping check already in progress for %1, initiated by %2

Logged at debug log level 40. This debug message is emitted when a duplicate request to test an address is received. When this occurs the duplicate test will be skipped and the associated DHCPOFFER will be dropped.

39.16 PING_CHECK_LEASE4_OFFER_FAILED

lease4_offer callout failed for query %1, lease address %2, reason %3

This error message indicates an error during the Ping Check hook library lease4_offer callout. The details of the error are provided as argument of the log message.

39.17 PING_CHECK_LOAD_ERROR

loading Ping Check hooks library failed %1

This error message indicates an error during loading the Ping Check hooks library. The details of the error are provided as argument of the log message.

39.18 PING_CHECK_LOAD_OK

Ping Check hooks library loaded successfully.

This info message indicates that the Ping Check hooks library has been loaded successfully.

39.19 PING_CHECK_MGR_CHANNEL_DOWN

Ping Channel has shutdown, ping checking will be skipped

This error message is emitted when the underlying ICMP channel has stopped due to an unrecoverable error. DHCP service may continue to function but without performing ping checks. Prior log messages should provide details.

39.20 PING_CHECK_MGR_LEASE_FREE_TO_USE

address %1 is free to use for %2

Logged at debug log level 40. This debug message is emitted when ping check has deemed an address is free to use. The log arguments detail the lease address checked and the query which initiated the check.

39.21 PING_CHECK_MGR_NEXT_ECHO_SCHEDULED

for %1, scheduling ECHO_REQUEST %2 of %3

Logged at debug log level 50. This debug message is emitted when the minimum number of ECHO REQUESTs is greater than 1 and the next ECHO REQUEST for a given lease address has been scheduled.

39.22 PING_CHECK_MGR_RECEIVED_ECHO_REPLY

from %1, id %2, sequence %3

Logged at debug log level 40. This debug message is emitted when an ECHO REPLY message has been received. The log argument details the source IP address, id, and sequence number of the ECHO REPLY.

39.23 PING_CHECK_MGR_RECEIVED_UNEXPECTED_ECHO_REPLY

from %1, id %2, sequence %3 received after reply-timeout expired

Logged at debug log level 50. This debug message is emitted when an ECHO REPLY has been received after the reply-timeout has expired and is no longer of interest. This may be an errant ECHO REPLY or it may indicate that the reply-timeout value is too short. The log argument details the source IP address, id, and sequence number of the reply.

39.24 PING_CHECK_MGR_RECEIVED_UNEXPECTED_UNREACHABLE_MSG

for %1, id %2, sequence %3 received after reply-timeout expired

Logged at debug log level 50. This debug message is emitted when an UNREACHABLE message has been received after the reply-timeout has expired and is no longer of interest. This may be an errant message or it may indicate that the reply-timeout value is too short.

39.25 PING_CHECK_MGR_RECEIVED_UNREACHABLE_MSG

for %1, id %2, sequence %3

Logged at debug log level 50. This debug message is emitted when an UNREACHABLE message has been received. The log argument details the target IP address, id, and sequence number from the embedded ECHO REQUEST.

39.26 PING_CHECK_MGR_REPLY_RECEIVED_ERROR

an error occurred processing an ICMP reply message %1

This debug message is emitted when an error occurred while processing an inbound ICMP message. The log argument describes the specific error.

39.27 PING_CHECK_MGR_REPLY_TIMEOUT_EXPIRED

for %1, ECHO REQUEST %2 of %3, reply-timeout %4

Logged at debug log level 50. This debug message is emitted when no reply is received to an ECHO REQUEST before the configured timeout value, *reply-timeout* was reached. The log arguments provides details.

39.28 PING_CHECK_MGR_SEND_COMPLETED_ERROR

an error occurred in the send completion callback %1

This error message is emitted when an unexpected error occurred after the completion of a successful write to the PingChannel socket. The log argument describes the specific error.

39.29 PING_CHECK_MGR_STARTED

ping channel operations are running, number of threads %1

This message is emitted when the ping check channel has been opened and is ready to process requests. The log argument includes the number of threads in the channel's thread pool.

39.30 PING_CHECK_MGR_STARTED_SINGLE_THREADED

single-threaded ping channel operations are running

This message is emitted when the ping check channel has been opened and is ready to process requests in single-threaded mode.

39.31 PING_CHECK_MGR_START_PING_CHECK

for %1, initiated by %2

Logged at debug log level 40. This debug message is emitted when a ping check for an address has been initiated. The log arguments detail the lease address to ping and the query which initiated the check.

39.32 PING_CHECK_MGR_STOPPED

channel operations have stopped

This message is emitted when the ping check channel operations have been stopped.

39.33 PING_CHECK_MGR_STOPPING

ping channel operations are stopping

Logged at debug log level 40. This debug message is emitted when the ping check channel is stopping operations, typically due to configuration event or server shutdown.

39.34 PING_CHECK_MGR_SUBNET_CONFIG_FAILED

user-context for subnet id %1, contains invalid ping-check %2

This error message indicates that a subnet was updated via subnet commands and its 'user-context' contains invalid 'ping-check' configuration. The server will log the error once and then use global ping-check parameters for the subnet until the configuration is corrected.

39.35 PING_CHECK_NO_LEASE_OR_LEASE_REUSED

Ping check skipped: no lease

Logged at debug log level 50. This debug message is emitted when the ping check request made by the server does not contain a lease. This typically happens when a lease is being reused. The ping check will be skipped and the offer processing will continue as normal.

39.36 PING_CHECK_PAUSE_FAILED

Pausing ping channel operations failed %1

This error message is emitted when an unexpected error occurred while attempting to pause the ping channel's thread pool. This error is highly unlikely and indicates a programmatic issue that should be reported as defect.

39.37 PING_CHECK_PAUSE_ILLEGAL

Pausing ping channel operations not allowed %1

This error message is emitted when attempting to pause the ping channel's thread pool. This indicates that a channel thread attempted to use a critical section which would result in a dead-lock. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

39.38 PING_CHECK_PAUSE_PERMISSIONS_FAILED

Permissions check for ping-channel pause failed %1

This error message is emitted when an unexpected error occurred while validating an attempt to pause the ping channel's thread pool. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

39.39 PING_CHECK_RESUME_FAILED

Resuming ping channel operations failed %1

This error message is emitted when an unexpected error occurred while attempting to resume operation of the ping channel's thread pool. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

39.40 PING_CHECK_UNEXPECTED_READ_ERROR

could not start next socket read %1

This error message occurs when initiating an asynchronous read on the ICMP socket failed in an unexpected fashion. The details of the error are provided as an argument of the log message.

39.41 PING_CHECK_UNEXPECTED_WRITE_ERROR

could not start next socket write %1

This error message occurs when initiating an asynchronous write on the ICMP socket failed in an unexpected fashion. The details of the error are provided as an argument of the log message.

39.42 PING_CHECK_UNLOAD

Ping Check hooks library has been unloaded

This info message indicates that the Ping Check hooks library has been unloaded.

40.1 RADIUS_ACCESS_BUILD_FAILED

```
building Access-Request failed: %1 for incoming message %2
```

This error message is issued when an error was raised during building of Access-Request.

40.2 RADIUS_ACCESS_CACHE_GET

```
host %1 with attributes %2 was retrieved from the cache
```

Logged at debug log level 40. This debug message is issued when a host is retrieved from the host cache.

40.3 RADIUS_ACCESS_CACHE_INSERT

```
host %1 with attributes %2 was inserted into the cache
```

Logged at debug log level 40. This debug message is issued when a new host is inserted into the host cache.

40.4 RADIUS_ACCESS_CONFLICT

```
query %1 triggers a conflict for %2
```

Logged at debug log level 40. This debug message is issued when a query triggers a conflict with a pending access request for the same identifier.

40.5 RADIUS_ACCESS_DROP_PARKED_QUERY

```
access request terminate callback decided to drop the parked query %1
```

Logged at debug log level 40. This debug message is issued when an access request terminates with the decision to drop the parked query.

40.6 RADIUS_ACCESS_ERROR

```
Access-Request failed with %1 (%2)
```

This error message is issued when no valid Access-Accept or Access-Reject message was received. The return code and name are logged.

40.7 RADIUS_ACCESS_GET_IDENTIFIER

```
identifier %1 of type %2 and User-Name %3 were set from incoming message %4
```

Logged at debug log level 40. This debug message is issued when the host identifier and User-Name attribute were set from an incoming message.

40.8 RADIUS_ACCESS_GET_IDENTIFIER_FAILED

```
no identifier of type %1 can be set from incoming message %2, reason: %3
```

This error message is issued when it was not possible to build the host identifier from the incoming message.

40.9 RADIUS_ACCESS_HOST_BACKEND_ERROR

```
Configuring access failed during host backend '%1' setup, reason: %2
```

This error message is issued when access/authentication is enabled in the configuration but something in host backend setup went wrong. The name of the host backend and the reason are logged.

40.10 RADIUS_ACCESS_MAX_PENDING_REQUESTS

```
query '%1' with identifier '%2' was dropped for too many pending access requests
```

Logged at debug log level 40. This debug message is issued when the number of pending access requests is over the configured limit. The query and its identifier are displayed.

40.11 RADIUS_ACCESS_NO_HOST_CACHE

```
Configuring access failed: host cache library not loaded.
```

This error message is issued when access/authentication is enabled in the configuration but no host cache was found. The Radius hook requires Host Cache hook to be loaded to store (cache) parameters received from exchanges with RADIUS server.

40.12 RADIUS_ACCESS_ORPHAN

```
orphan pending access request for %1
```

This error message is issued when an access request terminates without the corresponding pending request for the identifier.

40.13 RADIUS_ACCESS_RESUME_PARKED_QUERY

```
access request terminate callback resumes processing of parked query %1 in %2
```

Logged at debug log level 40. This debug message is issued when access request terminate callback resumes the processing of a parked query after the subnet select callout point.

40.14 RADIUS_ACCESS_SUBNET_RESELECT

```
subnet was reselected from 'ID %1' to 'ID %2'
```

Logged at debug log level 40. This debug message is issued when access/authentication triggered a subnet reselect. The original and new subnet IDs are logged.

40.15 RADIUS_ACCESS_TERMINATE_ERROR

```
access request terminate callback got an error: %1
```

This error message is issued when an access request terminates with an unexpected internal error.

40.16 RADIUS_ACCOUNTING_ASYNC

```
Asynchronous send Accounting-Request for NAS port %1 with %2
```

Logged at debug log level 40. This debug message is issued when starting to send an Accounting-Request message to accounting servers. The NAS port and message attributes are logged.

40.17 RADIUS_ACCOUNTING_ASYNC_FAILED

```
Asynchronous Accounting-Request failed: return code %1 (%2)
```

Logged at debug log level 40. This debug message is issued when no valid Accounting-Response message was received.

40.18 RADIUS_ACCOUNTING_ASYNC_SUCCEED

```
received valid Accounting-Response (asynchronously)
```

Logged at debug log level 40. This debug message indicates that a valid Accounting-Response was received.

40.19 RADIUS_ACCOUNTING_ERROR

```
Accounting-Request failed for %1 on event %2 (%3) failed with %4 (%5)
```

This error message is issued when accounting communication failed. The session Id, the event code and name, and return code and name are logged.

40.20 RADIUS_ACCOUNTING_HISTORY_UPDATE_FAILED

```
failed to insert a record for %1 in the history container
```

This error message is issued when it was not possible to insert a record in the create timestamp aka history container. This should break the session, i.e. it will not be possible for instance to match start and stop status messages.

40.21 RADIUS_ACCOUNTING_NO_HISTORY

```
failed to find the date the lease for %1 was created
```

Logged at debug log level 40. This debug message is issued when an address was not found in create timestamp aka history container. This should lead to a accounting session without a start status message.

40.22 RADIUS_ACCOUNTING_STATUS

send Status-Server with %1

Logged at debug log level 40. This debug message is issued when starting to send a Status-Server message to accounting servers. The message attributes are logged.

40.23 RADIUS_ACCOUNTING_STATUS_ERROR

received error response to Status-Server: %1 (%2) with %3

This error message indicates that a valid response to Status-Server message was received from accounting servers but with an unexpected code or an Error-Cause attribute. The response details are logged.

40.24 RADIUS_ACCOUNTING_STATUS_FAILED

Status-Server failed: return code %1 (%2)

Logged at debug log level 40. This debug message is issued when no valid response to Status-Server message was received from accounting servers.

40.25 RADIUS_ACCOUNTING_STATUS_SUCCEED

received valid response to Status-Server

Logged at debug log level 40. This debug message indicates that a valid response to Status-Server message was received from accounting servers.

40.26 RADIUS_ACCOUNTING_SYNC

Synchronous send Accounting-Request for NAS port %1 with %2

Logged at debug log level 40. This debug message is issued when starting to send an Accounting-Request message to accounting servers. The NAS port and message attributes are logged.

40.27 RADIUS_ACCOUNTING_SYNC_FAILED

Synchronous Accounting-Request failed: return code %1 (%2)

Logged at debug log level 40. This debug message is issued when no valid Accounting-Response message was received.

40.28 RADIUS_ACCOUNTING_SYNC_SUCCEED

received valid Accounting-Response (synchronously)

Logged at debug log level 40. This debug message indicates that a valid Accounting-Response was received.

40.29 RADIUS_AUTHENTICATION_ASYNC

send Access-Request for NAS port %1 with %2

Logged at debug log level 40. This debug message is issued when starting to send an Access-Request message to access servers. The NAS port and message attributes are logged.

40.30 RADIUS_AUTHENTICATION_ASYNC_ACCEPTED

```
received valid Access-Accept with %1
```

Logged at debug log level 40. This debug message indicates that a valid Access-Accept message was received. Attributes from the message are logged.

40.31 RADIUS_AUTHENTICATION_ASYNC_FAILED

```
Access-Request failed: return code %1 (%2)
```

Logged at debug log level 40. This debug message is issued when no correct Access-Accept or Access-Reject message was received.

40.32 RADIUS_AUTHENTICATION_ASYNC_REJECTED

```
received valid Access-Reject with %1
```

Logged at debug log level 40. This debug message indicates that a valid Access-Reject message was received. Attributes from the message are logged.

40.33 RADIUS_AUTHENTICATION_STATUS

```
send Status-Server with %1
```

Logged at debug log level 40. This debug message is issued when starting to send a Status-Server message to access servers. The message attributes are logged.

40.34 RADIUS_AUTHENTICATION_STATUS_ERROR

```
received error response to Status-Server: %1 (%2) with %3
```

This error message indicates that a valid response to Status-Server message was received from access servers but with an unexpected code or an Error-Cause attribute. The response details are logged.

40.35 RADIUS_AUTHENTICATION_STATUS_FAILED

```
Status-Server failed: return code %1 (%2)
```

Logged at debug log level 40. This debug message is issued when no valid response to Status-Server message was received from access servers.

40.36 RADIUS_AUTHENTICATION_STATUS_SUCCEED

```
received valid response to Status-Server
```

Logged at debug log level 40. This debug message indicates that a valid response to Status-Server message was received from access servers.

40.37 RADIUS_AUTHENTICATION_SYNC

```
send Access-Request for NAS port %1 with %2
```

Logged at debug log level 40. This debug message is issued when starting to send an Access-Request message to access servers. The NAS port and message attributes are logged.

40.38 RADIUS_AUTHENTICATION_SYNC_ACCEPTED

```
received valid Access-Accept with %1
```

Logged at debug log level 40. This debug message indicates that a valid Access-Accept message was received. Attributes from the message are logged.

40.39 RADIUS_AUTHENTICATION_SYNC_FAILED

```
Access-Request failed: return code %1 (%2)
```

Logged at debug log level 40. This debug message is issued when no correct Access-Accept or Access-Reject message was received.

40.40 RADIUS_AUTHENTICATION_SYNC_REJECTED

```
received valid Access-Reject with %1
```

Logged at debug log level 40. This debug message indicates that a valid Access-Reject message was received. Attributes from the message are logged.

40.41 RADIUS_BACKEND_GET4

```
spurious lookup for IPv4 subnet %1 and id %2 of type %3
```

Logged at debug log level 40. This debug message is issued when the radius host backend is unexpectedly called for looking for an IPv4 entry. Details of the lookup are logged.

40.42 RADIUS_BACKEND_GET6

```
spurious lookup for IPv6 subnet %1 and id %2 of type %3
```

Logged at debug log level 40. This debug message is issued when the radius host backend is unexpectedly called for looking for an IPv6 entry. Details of the lookup are logged.

40.43 RADIUS_CLEANUP_EXCEPTION

```
Exception on RADIUS cleanup: %1
```

This warning message is issued when there is an exception thrown when destroying an object in the RADIUS hook library. The exception is not allowed to continue propagating to not obfuscate another exception, so it is logged. It generally means a programmatic error and should be reported to ISC, but could also be harmless. The argument provides the detailed error message.

40.44 RADIUS_CONFIGURATION_FAILED

```
failed to configure Radius hooks library: %1
```

This error message is issued when there is an error configuring the Radius hooks library. The argument provides the detailed error message.

40.45 RADIUS_DECODE_MESSAGE

```
Decoded message '%1' (%2) id %3 length %4 with %5 attributes.
```

Logged at debug log level 40. This debug message is issued when a message is decoded. The message type name and value, the identifier, the length and the number of attributes are displayed.

40.46 RADIUS_DEINIT_OK

```
unloading Radius hooks library successful
```

This informational message indicates that the Radius hooks library has been unloaded successfully.

40.47 RADIUS_ENCODE_MESSAGE

```
Encoded message '%1' (%2) id %3 length %4 with %5 attributes.
```

Logged at debug log level 40. This debug message is issued when a message is encoded. The message type name and value, the identifier, the length and the number of attributes are displayed.

40.48 RADIUS_EXCHANGE_RECEIVED_ACCESS_ACCEPT

```
Exchange %1 received an Access-Accept.
```

Logged at debug log level 40. This debug message is issued when an exchange received an Access-Accept response. The exchange identifier is displayed.

40.49 RADIUS_EXCHANGE_RECEIVED_ACCESS_REJECT

```
Exchange %1 received an Access-Reject.
```

Logged at debug log level 40. This debug message is issued when an exchange received an Access-Reject response. The exchange identifier is displayed.

40.50 RADIUS_EXCHANGE_RECEIVED_ACCOUNTING_RESPONSE

```
Exchange %1 received an Accounting-Response.
```

Logged at debug log level 40. This debug message is issued when an exchange received an Accounting-Response response. The exchange identifier is displayed.

40.51 RADIUS_EXCHANGE_RECEIVED_BAD_RESPONSE

Exchange %1 received a bad response: %2

This error message is issued when an exchange received a bad response. The exchange identifier and the error message are displayed.

40.52 RADIUS_EXCHANGE_RECEIVED_MISMATCH

Exchange %1: received response with identifier %2 when %3 was expected.

This error message is issued when the sent request and the received response have different identifiers. The exchange identifier and the two RADIUS message identifiers are displayed.

40.53 RADIUS_EXCHANGE_RECEIVED_RESPONSE

Exchange %1 received response: %2

Logged at debug log level 40. This debug message is issued at the end of the reception routine. The exchange identifier and the error code are displayed.

40.54 RADIUS_EXCHANGE_RECEIVED_UNEXPECTED

Exchange %1: sent %2, received unexpected %3

This error message is issued when the sent request and the received response do not match. The exchange identifier and the two RADIUS message codes are displayed.

40.55 RADIUS_HOOK_FAILED

processing for hook %1 failed: %2

This error message is issued when processing at a standard hook point failed. The reason of the failure is displayed.

40.56 RADIUS_INIT_OK

loading Radius hooks library successful

This informational message indicates that the Radius hooks library has been loaded successfully. Enjoy!

40.57 RADIUS_INTEGER_ATTRIBUTE_FROM_BYTES_FAILED

Creating an integer attribute %1 '%2' failed: %3

This error message is issued when an integer attribute can't be created. Attribute type, name and error message are displayed.

40.58 RADIUS_INTEGER_ATTRIBUTE_FROM_TEXT_FAILED

Creating an integer attribute %1 '%2' from %3 failed.

This error message is issued when an integer attribute can't be created. Attribute type, name and bad submitted value are displayed.

40.59 RADIUS_IPADDR_ATTRIBUTE_FROM_BYTES_FAILED

Creating an IP address attribute %1 '%2' failed: %3

This error message is issued when an IP address attribute can't be created. Attribute type, name and error message are displayed.

40.60 RADIUS_IPADDR_ATTRIBUTE_FROM_TEXT_FAILED

Creating an IP address attribute %1 '%2' from %3 failed.

This error message is issued when an IP address attribute can't be created. Attribute type, name and bad submitted value are displayed.

40.61 RADIUS_IPV6ADDR_ATTRIBUTE_FROM_BYTES_FAILED

Creating an IPv6 address attribute %1 '%2' failed: %3

This error message is issued when an IPv6 address attribute can't be created. Attribute type, name and error message are displayed.

40.62 RADIUS_IPV6ADDR_ATTRIBUTE_FROM_TEXT_FAILED

Creating an IPv6 address attribute %1 '%2' from %3 failed.

This error message is issued when an IPv6 address attribute can't be created. Attribute type, name and bad submitted value are displayed.

40.63 RADIUS_IPV6PREFIX_ATTRIBUTE_FROM_BYTES_FAILED

Creating an IPv6 prefix attribute %1 '%2' failed: %3

This error message is issued when an IPv6 prefix attribute can't be created. Attribute type, name and error message are displayed.

40.64 RADIUS_IPV6PREFIX_ATTRIBUTE_FROM_TEXT_FAILED

Creating an IPv6 prefix attribute %1 '%2' from %3 failed.

This error message is issued when an IPv6 prefix attribute can't be created. Attribute type, name and bad submitted value are displayed.

40.65 RADIUS_PAUSE_FAILED

Pausing the RADIUS thread pool failed: %1

This error message is emitted when an unexpected error occurred while validating an attempt to pause the thread pool. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

40.66 RADIUS_PAUSE_ILLEGAL

Pausing the RADIUS thread pool not allowed: %1

This error message is emitted when attempting to pause the thread pool. This indicates that a thread attempted to use a critical section which would result in a dead-lock. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

40.67 RADIUS_PAUSE_PERMISSIONS_FAILED

Checking for permissions to pause the RADIUS thread pool failed: %1

This error message is emitted when an unexpected error occurred while validating an attempt to pause the thread pool. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

40.68 RADIUS_REPLY_MESSAGE_ATTRIBUTE

Message %1 on exchange %2 has a Reply-Message attribute with value '%3'.

This informational message is issued when a Reply-Message attribute is found in a message received from the RADIUS server. One log message is printed per attribute. A log message can contain multiple attributes, so there can be multiple log messages per RADIUS message. It displays the message identifier, the exchange identifier and the value of the Reply-Message attribute.

40.69 RADIUS_RESUME_FAILED

Resuming the RADIUS thread pool failed: %1

This error message is emitted when an unexpected error occurred while attempting to resume the thread pool. This error is highly unlikely and indicates a programmatic issue that should be reported as a defect.

40.70 RADIUS_SERVER_CONFIGURED

configured an %1 server: %2

This informational message is issued when a RADIUS server is configured. The kind of the server (access or accounting) and configuration details are logged with the secret replaced by stars.

40.71 RADIUS_SESSION_HISTORY_APPEND_FAILED

appending of a new record for %1 to the session history file failed: %2

This warning message is issued when appending a new record to the session history file failed. The address of the new record and the reason of the failure are displayed.

40.72 RADIUS_SESSION_HISTORY_LOADED

loading of the session history file succeeded: read %1 records including %2 active records

This informational message is issued when loading of the session history file completed with success. Numbers of loaded and active records are displayed.

40.73 RADIUS_SESSION_HISTORY_LOAD_FAILED

loading of the session history file

failed: loaded %1, skipped %2 and active %3 records. This error message is issued when loading of the session history file did not completed with success. Numbers of loaded, skipped and active records displayed.

40.74 RADIUS_SESSION_HISTORY_OPENED

opening of the session history file %1 succeeded

This informational message is issued when opening of the CSV file providing session history persistence succeeded. The name of the file is displayed.

40.75 RADIUS_SESSION_HISTORY_OPEN_FAILED

opening of the session history file %1 failed: %2

This error message is issued when opening of the CSV file providing session history persistence failed. The name of the file and the reason of the failure are displayed.

40.76 RADIUS_SESSION_HISTORY_STORED

Storing to the session history file succeeded: stored %1 records

This informational message is issued when writing to a new session history file completed with success. The number of stored records is displayed.

40.77 RADIUS_SESSION_HISTORY_STORE_FAILED

Writing to the session history file %1 failed: %2 (stored %3 over %4 records)

This error message is issued when writing to a new session history file failed. The name of the file, the reason of the failure, the number of stored records before the failure and the expected number of records are displayed.

40.78 RADIUS_TCP_EXCHANGE_FAILURE

TCP exchange %1 failed: %2

This error message is issued when a TCP exchange terminates with an error. The exchange identifier and the error return code are displayed.

40.79 RADIUS_TCP_EXCHANGE_RECEIVED

TCP exchange %1 received %2 bytes.

Logged at debug log level 40. This debug message is issued when a TCP exchange received a response. The exchange identifier and the response size are displayed.

40.80 RADIUS_TCP_EXCHANGE_RECEIVE_FAILED

```
Receive for TCP exchange %1 failed: %2
```

This error message is issued when a TCP exchange failed to receive a message. The exchange identifier and the error message are displayed.

40.81 RADIUS_TCP_EXCHANGE_SEND

```
TCP exchange %1 sends %2 bytes to server %3 on port %4%5
```

Logged at debug log level 40. This debug message is issued when a TCP exchange sends a message to a server. The exchange identifier, message size, server address and port, and usage of TLS are displayed.

40.82 RADIUS_TCP_EXCHANGE_START

```
Start TCP exchange %1
```

Logged at debug log level 40. This debug message is issued when a TCP exchange starts. The exchange identifier is displayed.

40.83 RADIUS_TCP_EXCHANGE_START_ERROR

```
TCP exchange %1 failed: %2
```

This error message is issued when a TCP exchange failed to start. The exchange identifier and the error message are displayed.

40.84 RADIUS_TCP_EXCHANGE_SUCCESS

```
TCP exchange %1 succeeded: %2
```

Logged at debug log level 40. This debug message is issued when a TCP exchange terminates with success. The exchange identifier and the return code are displayed.

40.85 RADIUS_THREAD_POOL_STARTED

```
RADIUS thread pool started with %1 threads.
```

This informational message is issued when the thread pool is started. The number of threads is displayed.

40.86 RADIUS_TLS_STATUS

```
send Status-Server with %1
```

Logged at debug log level 40. This debug message is issued when starting to send a Status-Server message to TLS servers. The message attributes are logged.

40.87 RADIUS_TLS_STATUS_ERROR

```
received error response to Status-Server: %1 (%2) with %3
```

This error message indicates that a valid response to Status-Server message was received from TLS servers but with an unexpected code or an Error-Cause attribute. The response details are logged.

40.88 RADIUS_TLS_STATUS_FAILED

```
Status-Server failed: return code %1 (%2)
```

Logged at debug log level 40. This debug message is issued when no valid response to Status-Server message was received from TLS servers.

40.89 RADIUS_TLS_STATUS_SUCCEED

```
received valid response to Status-Server
```

Logged at debug log level 40. This debug message indicates that a valid response to Status-Server message was received from TLS servers.

40.90 RADIUS_UDP_EXCHANGE_FAILED

```
UDP exchange %1 failed: %2
```

This error message is issued when an UDP exchange terminates with an error. The exchange identifier and the error return code are displayed.

40.91 RADIUS_UDP_EXCHANGE_MAX_PENDING

```
accounting UDP exchange can't be created because already more than %1 exchanges are pending
```

This error message is issued when the number of pending UDP exchanges is too large when a new accounting request will be issued.

40.92 RADIUS_UDP_EXCHANGE_OPEN_FAILED

```
Open socket for UDP exchange %1 failed: %2
```

This error message is issued when an UDP exchange failed to open a new socket. The exchange identifier and the error message are displayed.

40.93 RADIUS_UDP_EXCHANGE_RECEIVED

```
UDP exchange %1 received %2 bytes.
```

Logged at debug log level 40. This debug message is issued when an UDP exchange received a response. The exchange identifier and the response size are displayed.

40.94 RADIUS_UDP_EXCHANGE_RECEIVE_FAILED

Receive for UDP exchange %1 failed: %2

This error message is issued when an UDP exchange failed to receive a message. The exchange identifier and the error message are displayed.

40.95 RADIUS_UDP_EXCHANGE_SEND_FAILED

Send for UDP exchange %1 failed: %2

This error message is issued when an UDP exchange failed to send a message. The exchange identifier and the error message are displayed.

40.96 RADIUS_UDP_EXCHANGE_SEND_NEW

UDP exchange %1 sends %2 bytes to new server[%3] %4 on port %5

Logged at debug log level 40. This debug message is issued when an UDP exchange sends a message to a new server. The exchange identifier, message size, server index, address and port are displayed.

40.97 RADIUS_UDP_EXCHANGE_SEND_RETRY

UDP exchange %1 sends %2 bytes for the %3 try.

Logged at debug log level 40. This debug message is issued when an UDP exchange sends a message to a new server. The exchange identifier, message size and retry counter are displayed.

40.98 RADIUS_UDP_EXCHANGE_SENT

UDP exchange %1 sent %2 bytes.

Logged at debug log level 40. This debug message is issued when an UDP exchange sent a request and is ready to receive the response. The exchange identifier and request size are displayed.

40.99 RADIUS_UDP_EXCHANGE_START

Start UDP exchange %1

Logged at debug log level 40. This debug message is issued when an UDP exchange starts. The exchange identifier is displayed.

40.100 RADIUS_UDP_EXCHANGE_SYNC_RETURN

Synchronous UDP exchange %1 returns with %2

Logged at debug log level 40. This debug message is issued when a synchronous UDP exchange returns. The exchange identifier and the error/return code are displayed.

40.101 RADIUS_UDP_EXCHANGE_TERMINATE

UDP exchange %1 terminates with %2

Logged at debug log level 40. This debug message is issued when an UDP exchange terminates with success. The exchange identifier and the return code are displayed.

40.102 RADIUS_UDP_EXCHANGE_TIMEOUT

UDP exchange %1 timeout

This error message is issued when an UDP exchange failed on timeout. The exchange identifier is displayed.

41.1 RBAC_CONFIGURED_ACLS

RBAC hooks library has configured %1 named ACLs.

Logged at debug log level 40. This debug message indicates that some named access control lists have been configured. The count is displayed.

41.2 RBAC_CONFIGURED_COMMANDS

RBAC hooks library has configured %1 extra commands.

Logged at debug log level 40. This debug message indicates that some extra commands have been configured. The count is displayed.

41.3 RBAC_CONFIGURED_ROLES

hooks library has configured %1 roles.

Logged at debug log level 40. This debug message indicates that some roles have been configured. The count is displayed.

41.4 RBAC_HTTP_AUTH_ERROR

Error in http_auth callout: %1.

This error messages indicates that an error has been raised in http_auth callout by the RBAC hooks library. The argument details the error.

41.5 RBAC_HTTP_AUTH_FAILED

RBAC processing in http_auth callout failed for unexpected condition: %1.

The info message indicates that the RBAC hooks library reached an unexpected condition in the http_auth callout point. The reason of the failure is summarized and details are available in a debug log.

41.6 RBAC_HTTP_AUTH_REJECT

```
Role configuration '%1' for role '%2' has rejected command '%3'.
```

This info message indicates that the command has been rejected in http_auth callout. The role configuration name, the role name and the command are displayed.

41.7 RBAC_HTTP_AUTH_RESPONSE

```
RBAC hooks library has returned response: %1.
```

This info message indicates that the RBAC hooks library has returned a response in http_auth callout. The response is summarized.

41.8 RBAC_HTTP_RESPONSE_FAILED

```
RBAC processing in http_response callout failed for unexpected condition: %1.
```

The info message indicates that the RBAC hooks library reached an unexpected condition in the http_response callout point. The reason of the failure is summarized and details are available in a debug log.

41.9 RBAC_LOAD_FAILED

```
RBAC hooks library failed to load: %1.
```

This error message indicates that an error occurred attempting to load the RBAC hooks library. The argument details the error.

41.10 RBAC_LOAD_OK

```
RBAC hooks library loaded successfully.
```

This info message indicates that the RBAC hooks library has been loaded successfully.

41.11 RBAC_READ_API_FILES

```
RBAC hooks library read API files from '%1' getting %2 commands, %3 access types and %4 hooks.
```

This info message indicates that the RBAC hooks library has read API files from the configured directory. The name of the directory and some statistics are displayed.

41.12 RBAC_TRACE_HTTP_AUTH_ACCEPT

```
Role configuration '%1' for role '%2' has accepted command '%3'.
```

Logged at debug log level 40. The command has been accepted in http_auth callout. The role configuration name, the role name and the command are displayed.

41.13 RBAC_TRACE_HTTP_AUTH_BAD_BODY_TYPE

Bad body type in JSON request in http_auth callout.

Logged at debug log level 40. The http_auth callout has been called with a bad body type in the JSON request. The RBAC hooks library immediately returns. This is an error condition.

41.14 RBAC_TRACE_HTTP_AUTH_BAD_COMMAND_TYPE

Bad command type in JSON request in http_auth callout.

Logged at debug log level 40. The http_auth callout has been called with a bad command type in the JSON request. The RBAC hooks library immediately returns. This is an error condition.

41.15 RBAC_TRACE_HTTP_AUTH_COMMAND

Command '%1' in http_auth callout.

Logged at debug log level 40. The http_auth callout has been called with the displayed command.

41.16 RBAC_TRACE_HTTP_AUTH_DISABLED

RBAC hooks library is disabled in http_auth callout.

Logged at debug log level 40. The http_auth callout has been called with the RBAC hooks library disabled i.e. with no role assigned.

41.17 RBAC_TRACE_HTTP_AUTH_EMPTY_BODY

Empty body in JSON request in http_auth callout.

Logged at debug log level 40. The http_auth callout has been called with an empty body in the JSON request. The RBAC hooks library immediately returns. This is an error condition.

41.18 RBAC_TRACE_HTTP_AUTH_NO_COMMAND

No command entry in JSON request in http_auth callout.

Logged at debug log level 40. The http_auth callout has been called without a command entry in the JSON request. The RBAC hooks library immediately returns. This is an error condition.

41.19 RBAC_TRACE_HTTP_AUTH_NO_JSON

No JSON request in http_auth callout.

Logged at debug log level 40. The http_auth callout has been called with a non JSON request. The RBAC hooks library immediately returns. This is an error condition.

41.20 RBAC_TRACE_HTTP_AUTH_NO_REQUEST

No request in http_auth callout.

Logged at debug log level 40. The http_auth callout has been called without a request. The RBAC hooks library immediately returns. This is an error condition.

41.21 RBAC_TRACE_HTTP_AUTH_NO_TLS_REJECT

Non TLS request has been rejected.

Logged at debug log level 40. The non TLS request has been rejected in http_auth callout.

41.22 RBAC_TRACE_HTTP_AUTH_RESPONSE

Response in http_auth callout: %1.

Logged at debug log level 40. The http_auth callout has been called with a response. The RBAC hooks library immediately returns. The response is summarized.

41.23 RBAC_TRACE_HTTP_AUTH_ROLE

Assigned role '%1' in http_auth callout.

Logged at debug log level 40. The displayed role has been assigned in the http_auth callout.

41.24 RBAC_TRACE_HTTP_RESPONSE_BAD_BODY_TYPE

Bad body type in JSON response in http_response callout.

Logged at debug log level 40. The http_response callout has been called with a bad body type in the JSON response which is likely an error response. The RBAC hooks library immediately returns.

41.25 RBAC_TRACE_HTTP_RESPONSE_CONTEXT

Retrieved command '%1' and role config '%2' in http_response callout.

Logged at debug log level 40. The command and the role config have been retrieved from the request context. They are displayed.

41.26 RBAC_TRACE_HTTP_RESPONSE_DISABLED

RBAC hooks library is disabled in http_response callout.

Logged at debug log level 40. The http_response callout has been called with the RBAC hooks library disabled i.e. with no role assigned.

41.27 RBAC_TRACE_HTTP_RESPONSE_EMPTY_BODY

Empty body in JSON response in http_response callout.

Logged at debug log level 40. The http_response callout has been called with an empty body in the JSON response. The RBAC hooks library immediately returns. This is an error condition.

41.28 RBAC_TRACE_HTTP_RESPONSE_EMPTY_BODY_LIST

Empty list in JSON response in http_response callout.

Logged at debug log level 40. The http_response callout has been called with an empty body list in the JSON response. The RBAC hooks library immediately returns. This is an error condition.

41.29 RBAC_TRACE_HTTP_RESPONSE_MODIFIED

The response has been modified by a response filter in http_response callout.

Logged at debug log level 40. A response filter has modified the HTTP response in http_response callout.

41.30 RBAC_TRACE_HTTP_RESPONSE_NO_ARGUMENTS

No request or response in http_response callout.

Logged at debug log level 40. The http_response callout has been called without request or response. The RBAC hooks library immediately returns. This is an error condition.

41.31 RBAC_UNLOAD_OK

RBAC hooks library unloaded successfully.

This info message indicates that the RBAC hooks library has been unloaded successfully.

RUN

42.1 RUN_SCRIPT_LOAD

Run Script hooks library has been loaded

This info message indicates that the Run Script hooks library has been loaded.

42.2 RUN_SCRIPT_LOAD_ERROR

Run Script hooks library failed: %1

This error message indicates an error during loading the Run Script hooks library. The details of the error are provided as argument of the log message.

42.3 RUN_SCRIPT_UNLOAD

Run Script hooks library has been unloaded

This info message indicates that the RunScript hooks library has been unloaded.

43.1 SFLQ_POOL4_DEL

```
sflq-pool4-del command succeeded, (parameters: %1) pools deleted: %2
```

Logged at debug log level 20. The sflq-pool4-del command was successful. It prints the command arguments along with the number of pools deleted.

43.2 SFLQ_POOL4_DEL_FAILED

```
sflq-pool4-del command failed, (parameters: %1, reason: %2)
```

The sflq-pool4-del command has failed. Both the reason as well as the parameters passed are logged.

43.3 SFLQ_POOL4_GET_ALL

```
sflq-pool4-get-all command succeeded, pools found: %1
```

Logged at debug log level 20. The sflq-pool4-get-all command was successful.

43.4 SFLQ_POOL4_GET_ALL_FAILED

```
sflq-pool4-get-all command failed, (parameters: %1, reason: %2)
```

The sflq-pool4-get-all command has failed. Both the reason as well as the parameters passed are logged.

43.5 SFLQ_POOL4_GET_BY_RANGE

```
sflq-pool4-get-by-range command succeeded, (parameters: %1) pools found: %2
```

Logged at debug log level 20. The sflq-pool4-get-by-range command was successful.

43.6 SFLQ_POOL4_GET_BY_RANGE_FAILED

```
sflq-pool4-get-by-range command failed, (parameters: %1, reason: %2)
```

The sflq-pool4-get-range command has failed. Both the reason as well as the parameters passed are logged.

43.7 SFLQ_POOL4_GET_BY_SUBNET

```
sflq-pool4-get-by-subnet command succeeded, (parameters: %1) pools found: %2
```

Logged at debug log level 20. The sflq-pool4-get-by-subnet command was successful.

43.8 SFLQ_POOL4_GET_BY_SUBNET_FAILED

```
sflq-pool4-get-by-subnet command failed, (parameters: %1, reason: %2)
```

The sflq-pool4-get-subnet command has failed. Both the reason as well as the parameters passed are logged.

43.9 SFLQ_POOL4_REBUILD

```
sflq-pool4-rebuild command succeeded, (parameters: %1) pools rebuilt: %2
```

Logged at debug log level 20. The sflq-pool4-rebuild command was successful. It prints the command arguments along with the number of pools rebuilt.

43.10 SFLQ_POOL4_REBUILD_FAILED

```
sflq-pool4-rebuild command failed, (parameters: %1, reason: %2)
```

The sflq-pool4-rebuild command has failed. Both the reason as well as the parameters passed are logged.

43.11 SFLQ_POOL6_DEL

```
sflq-pool4-del command succeeded, (parameters: %1) pools deleted: %2
```

Logged at debug log level 20. The sflq-pool6-del command was successful. It prints the command arguments along with the number of pools deleted.

43.12 SFLQ_POOL6_DEL_FAILED

```
sflq-pool4-del command failed, (parameters: %1, reason: %2)
```

The sflq-pool6-del command has failed. Both the reason as well as the parameters passed are logged.

43.13 SFLQ_POOL6_GET_ALL

```
sflq-pool6-get-all command succeeded, pools found: %1
```

Logged at debug log level 20. The sflq-pool6-rebuild command was successful.

43.14 SFLQ_POOL6_GET_ALL_FAILED

```
sflq-pool6-get-all command failed, (parameters: %1, reason: %2)
```

The sflq-pool6-get-all command has failed. Both the reason as well as the parameters passed are logged.

43.15 SFLQ_POOL6_GET_BY_RANGE

```
sflq-pool6-get-by-range command succeeded, (parameters: %1) pools found: %2
```

Logged at debug log level 20. The sflq-pool6-get-by-range command was successful.

43.16 SFLQ_POOL6_GET_BY_RANGE_FAILED

```
sflq-pool6-get-by-range command failed, (parameters: %1, reason: %2)
```

The sflq-pool6-get-range command has failed. Both the reason as well as the parameters passed are logged.

43.17 SFLQ_POOL6_GET_BY_SUBNET

```
sflq-pool6-get-by-subnet command succeeded, (parameters: %1) pools found: %2
```

Logged at debug log level 20. The sflq-pool6-get-by-subnet command was successful.

43.18 SFLQ_POOL6_GET_BY_SUBNET_FAILED

```
sflq-pool6-get-by-subnet command failed, (parameters: %1, reason: %2)
```

The sflq-pool6-get-subnet command has failed. Both the reason as well as the parameters passed are logged.

43.19 SFLQ_POOL6_REBUILD

```
sflq-pool6-rebuild command succeeded, (parameters: %1) pools rebuilt: %2
```

Logged at debug log level 20. The sflq-pool6-rebuild command was successful. It prints the command arguments along with the number of pools rebuilt.

43.20 SFLQ_POOL6_REBUILD_FAILED

```
sflq-pool6-rebuild command failed, (parameters: %1, reason: %2)
```

The sflq-pool6-rebuild command has failed. Both the reason as well as the parameters passed are logged.

START

44.1 START_REKEY_TIMER

```
started timer handling rekey for server %1 in %2 seconds.
```

Logged at debug log level 40. This debug message is issued when starting the rekey timer to handle new keys for this server when at least one key is currently available. The first argument specifies the server identifier and the second argument specifies the time interval when the next key processing will be attempted.

44.2 START_RETRY_TIMER

```
started timer handling retry for server %1 in %2 seconds.
```

Logged at debug log level 40. This debug message is issued when starting the retry timer to handle new keys for this server when there is no key currently available. The first argument specifies the server identifier and the second argument specifies the time interval when the next key processing will be attempted.

45.1 STAT_CMDS_DEINIT_OK

```
unloading Stat Commands hooks library successful
```

This info message indicates that the Stat Commands hooks library has been removed successfully.

45.2 STAT_CMDS_INIT_OK

```
loading Stat Commands hooks library successful
```

This info message indicates that the Stat Commands hooks library has been loaded successfully. Enjoy!

45.3 STAT_CMDS_LEASE4_FAILED

```
stat-lease4-get command failed: reason: %1
```

The stat-lease4-get command has failed. The reason for failure is logged.

45.4 STAT_CMDS_LEASE4_GET

```
stat-lease4-get command successful, parameters: %1 rows found: %2
```

The stat-lease4-get command has been successful. The log will contain the parameters supplied and the number of rows found.

45.5 STAT_CMDS_LEASE4_GET_FAILED

```
stat-lease4-get command failed: parameters: %1, reason: %2
```

The stat-lease4-get command has failed. Both the parameters supplied and the reason for failure are logged.

45.6 STAT_CMDS_LEASE4_GET_INVALID

```
stat-lease4-get command is malformed or invalid, reason: %1
```

The stat-lease4-get command was either malformed or contained invalid parameters. A detailed explanation should be logged.

45.7 STAT_CMDS_LEASE4_GET_NO_SUBNETS

```
stat-lease4-get, parameters: %1, %2"
```

The parameters submitted with stat-lease4-get were valid but excluded all known subnets. The parameters supplied along with an explanation should be logged.

45.8 STAT_CMDS_LEASE4_ORPHANED_STATS

```
stat-lease4-get command omitted statistics for one or more non-existent subnets
```

Logged at debug log level 40. During processing the stat-lease4-get found statistics for subnet IDs for non-existent subnets. These values were omitted from the command response returned to the user. This may occur when subnets have been removed from the configuration in a manner that did not also remove the statistics. While the existence of such statistics is not harmful, steps should be considered to remove them. For memfile lease storage, the problem should disappear upon configuration reload or server restart. For database lease storage the issue is more complicated and as of Kea 2.0.0 we do not yet have a clean solution.

45.9 STAT_CMDS_LEASE6_FAILED

```
stat-lease6-get command failed: reason: %1
```

The stat-lease6-get command has failed. The reason for failure is logged.

45.10 STAT_CMDS_LEASE6_GET

```
stat-lease6-get command successful, parameters: %1 rows found: %2
```

The stat-lease6-get command has been successful. The log will contain the parameters supplied and the number of rows found.

45.11 STAT_CMDS_LEASE6_GET_FAILED

```
stat-lease6-get command failed: parameters: %1, reason: %2
```

The stat-lease6-get command has failed. Both the parameters supplied and the reason for failure are logged.

45.12 STAT_CMDS_LEASE6_GET_INVALID

```
stat-lease6-get command is malformed or invalid, reason: %1
```

The stat-lease6-get command was either malformed or contained invalid parameters. A detailed explanation should be logged.

45.13 STAT_CMDS_LEASE6_GET_NO_SUBNETS

```
stat-lease6-get, parameters: %1, %2"
```

The parameters submitted with stat-lease6-get were valid but excluded all known subnets. The parameters supplied along with an explanation should be logged.

45.14 STAT_CMDS_LEASE6_ORPHANED_STATS

stat-lease6-get command omitted statistics for one or more non-existent subnets

Logged at debug log level 40. During processing the stat-lease4-get found statistics for subnet IDs for non-existent subnets. These values were omitted from the command response returned to the user. This may occur when subnets have been removed from the configuration in a manner that did not also remove the statistics. While the existence of such statistics is not harmful, steps should be considered to remove them. For memfile lease storage, the problem should disappear upon configuration reload or server restart. For database lease storage the issue is more complicated and as of Kea 2.0.0 we do not yet have a clean solution.

46.1 SUBNET_CMDS_DEINIT_OK

```
unloading Subnet Commands hooks library successful
```

This informational message indicates that the Host Commands hooks library has been unloaded successfully.

46.2 SUBNET_CMDS_INIT_FAILED

```
loading Subnet Commands hooks library failed: %1
```

This error message indicates an error during loading the Subnet Commands hooks library. The details of the error are provided as argument of the log message.

46.3 SUBNET_CMDS_INIT_OK

```
loading Subnet Commands hooks library successful
```

This informational message indicates that the Host Commands hooks library has been loaded successfully. Enjoy!

46.4 SUBNET_CMDS_NETWORK4_ADD_FAILED

```
failed to add new IPv4 network: %1
```

This error message is issued when the Subnet Commands hooks library fails to add a new IPv4 network to the server configuration. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.5 SUBNET_CMDS_NETWORK4_DEL_FAILED

```
failed to delete IPv4 network: %1
```

This error message is issued when the Subnet Commands hooks library fails to delete an IPv4 network. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.6 SUBNET_CMDS_NETWORK4_GET_FAILED

failed to return an IPv4 network: %1

This error message is issued when the server fails to return an IPv4 network in response to 'network4-get' command. The argument details the reason for failure. The error message will be returned to the controlling client with the error status code. This error may occur when the received command has invalid structure, has not allowed parameters or lacks required parameters. It will also be returned when the command syntax is correct but no network was found.

46.7 SUBNET_CMDS_NETWORK4_LIST_FAILED

failed to return a list of IPv4 networks: %1

This error message is issued when the Subnet Commands hooks library fails to return a list of IPv4 networks requested with 'network4-list' command. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.8 SUBNET_CMDS_NETWORK4_SUBNET_ADD_FAILED

failed to add existing IPv4 subnet to a shared network: %1

This error message is issued when the Subnet Commands hooks library fails to add existing IPv4 subnet to existing shared network. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.9 SUBNET_CMDS_NETWORK4_SUBNET_DEL_FAILED

failed to remove a IPv4 subnet from a shared network: %1

This error message is issued when the Subnet Commands hooks library fails to remove existing IPv4 subnet to existing shared network. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.10 SUBNET_CMDS_NETWORK6_ADD_FAILED

failed to add new IPv6 network: %1

This error message is issued when the Subnet Commands hooks library fails to add a new IPv6 network to the server configuration. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.11 SUBNET_CMDS_NETWORK6_DEL_FAILED

failed to delete IPv6 network: %1

This error message is issued when the Subnet Commands hooks library fails to delete an IPv6 network. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.12 SUBNET_CMDS_NETWORK6_GET_FAILED

failed to return an IPv6 network: %1

This error message is issued when the server fails to return an IPv6 network in response to 'network4-get' command. The argument details the reason for failure. The error message will be returned to the controlling client with the error status code. This error may occur when the received command has invalid structure, has not allowed parameters or lacks required parameters. It will also be returned when the command syntax is correct but no network was found.

46.13 SUBNET_CMDS_NETWORK6_LIST_FAILED

failed to return a list of IPv6 networks: %1

This error message is issued when the Subnet Commands hooks library fails to return a list of IPv4 networks requested with 'network6-list' command. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.14 SUBNET_CMDS_NETWORK6_SUBNET_ADD_FAILED

failed to add existing IPv6 subnet to a shared network: %1

This error message is issued when the Subnet Commands hooks library fails to add existing IPv6 subnet to existing shared network. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.15 SUBNET_CMDS_NETWORK6_SUBNET_DEL_FAILED

failed to remove a IPv6 subnet from a shared network: %1

This error message is issued when the Subnet Commands hooks library fails to remove existing IPv6 subnet to existing shared network. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.16 SUBNET_CMDS_NETWORK_ADD

successfully added shared network %1

This informational message is issued when the Subnet Commands hooks library successfully adds a shared network as a result of receiving a 'network4-add' or 'network6-add' command'. The argument represents the name of added shared network.

46.17 SUBNET_CMDS_NETWORK_DEL

successfully deleted shared network %1

This informational message is issued when the Subnet Commands hooks library successfully deletes a shared network as a result of receiving a 'network4-del' or 'network6-del' command'. The argument represents the name of deleted shared network.

46.18 SUBNET_CMDS_NETWORK_GET

```
successfully retrieved shared network %1
```

This informational message is issued when the Subnet Commands hooks library successfully retrieves a shared network as a result of receiving a 'network4-get' or 'network6-get' command'. The argument represents the name of retrieved shared network.

46.19 SUBNET_CMDS_NETWORK_GET_EMPTY

```
specified shared network is not found: %1
```

This informational message is issued when the Subnet Commands hooks library found no matching shared network as a result of receiving a 'network4-get' or 'network6-get' command'.

46.20 SUBNET_CMDS_NETWORK_LIST

```
successfully retrieved list of %1 %2 shared networks
```

This informational message is issued when the Subnet Commands hooks library successfully retrieves a list of shared networks as a result of receiving 'network4-list' or 'network6-list' command. The first argument specifies a number of networks retrieved. The second parameter specifies a protocol type: 'IPv4' or 'IPv6'.

46.21 SUBNET_CMDS_NETWORK_LIST_EMPTY

```
no %1 shared networks listed
```

This informational message is issued when the Subnet Commands hooks library successfully processes the 'network4-list' or 'network6-list' command but no shared network has been found. This indicates that the server configuration contains no shared networks of the specific type. The argument specifies a protocol type: 'IPv4' or 'IPv6'.

46.22 SUBNET_CMDS_NETWORK_SUBNET_ADD

```
%1 subnet %2 (id %3) added to shared network %4
```

This informational message indicates that specified subnet (address family given in parameter 1, details in parameters 2 and 3) is now part of a shared network. This is a successful result of either network4-subnet-add or network6-subnet-add commands.

46.23 SUBNET_CMDS_NETWORK_SUBNET_DEL

```
%1 subnet %2 (id %3) removed from shared network %4
```

This informational message indicates that specified subnets (address family given in parameter 1, details in parameters 2 and 3) is no longer part of a shared network. The subnet remains in configuration, but is a stand alone subnet. This is a successful result of either network4-subnet-del or network6-subnet-del commands.

46.24 SUBNET_CMDS_SUBNET4_ADD_FAILED

```
failed to add new IPv4 subnet: %1
```

This error message is issued when the Subnet Commands hooks library fails to add a new IPv4 subnet to the server configuration. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.25 SUBNET_CMDS_SUBNET4_DELTA_ADD_FAILED

failed to update IPv4 subnet: %1

This error message is issued when the Subnet Commands hooks library fails to update by adding a delta in a IPv4 subnet to the server configuration. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.26 SUBNET_CMDS_SUBNET4_DELTA_DEL_FAILED

failed to update IPv4 subnet: %1

This error message is issued when the Subnet Commands hooks library fails to update by removing a delta in a IPv4 subnet to the server configuration. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.27 SUBNET_CMDS_SUBNET4_DEL_FAILED

failed to delete IPv4 subnet: %1

This error message is issued when the Subnet Commands hooks library fails to delete an IPv4 subnet. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.28 SUBNET_CMDS_SUBNET4_GET_FAILED

failed to return an IPv4 subnet: %1

This error message is issued when the server fails to return an IPv4 subnet in response to 'subnet4-get' command. The argument details the reason for failure. The error message will be returned to the controlling client with the error status code. This error may occur when the received command has invalid structure, has not allowed parameters or lacks required parameters. It will also be returned when the command syntax is correct but no subnet was found.

46.29 SUBNET_CMDS_SUBNET4_LIST_FAILED

failed to return a list of IPv4 subnets: %1

This error message is issued when the Subnet Commands hooks library fails to return a list of IPv4 subnets requested with 'subnet4-list' command. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.30 SUBNET_CMDS_SUBNET4_UPDATE_FAILED

failed to update IPv4 subnet: %1

This error message is issued when the Subnet Commands hooks library fails to update a IPv4 subnet to the server configuration. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.31 SUBNET_CMDS_SUBNET6_ADD_FAILED

failed to add new IPv6 subnet: %1

This error message is issued when the Subnet Commands hooks library fails to add a new IPv6 subnet to the server configuration. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.32 SUBNET_CMDS_SUBNET6_DELTA_ADD_FAILED

failed to update IPv6 subnet: %1

This error message is issued when the Subnet Commands hooks library fails to update by adding a delta in a IPv6 subnet to the server configuration. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.33 SUBNET_CMDS_SUBNET6_DELTA_DEL_FAILED

failed to update IPv6 subnet: %1

This error message is issued when the Subnet Commands hooks library fails to update by removing a delta in a IPv6 subnet to the server configuration. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.34 SUBNET_CMDS_SUBNET6_DEL_FAILED

failed to delete IPv6 subnet: %1

This error message is issued when the Subnet Commands hooks library fails to delete an IPv6 subnet. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.35 SUBNET_CMDS_SUBNET6_GET_FAILED

failed to return an IPv6 subnet: %1

This error message is issued when the server fails to return an IPv6 subnet in response to 'subnet4-get' command. The argument details the reason for failure. The error message will be returned to the controlling client with the error status code. This error may occur when the received command has invalid structure, has not allowed parameters or lacks required parameters. It will also be returned when the command syntax is correct but no subnet was found.

46.36 SUBNET_CMDS_SUBNET6_LIST_FAILED

failed to return a list of IPv6 subnets: %1

This error message is issued when the Subnet Commands hooks library fails to return a list of IPv6 subnets requested with 'subnet6-list' command. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.37 SUBNET_CMDS_SUBNET6_UPDATE_FAILED

```
failed to update IPv6 subnet: %1
```

This error message is issued when the Subnet Commands hooks library fails to update a IPv6 subnet to the server configuration. The reason for failure is provided within the error message. The error message will be returned to the controlling client with the error status code.

46.38 SUBNET_CMDS_SUBNET_ADD

```
successfully added subnet %1 having id %2
```

This informational message is issued when the Subnet Commands hooks library successfully adds a subnet as a result of receiving a 'subnet4-add' or 'subnet6-add' command'. The first parameter specifies an added subnet prefix. The second parameter specifies a subnet identifier.

46.39 SUBNET_CMDS_SUBNET_DEL

```
successfully deleted subnet %1 having id %2
```

This informational message is issued when the Subnet Commands hooks library successfully deletes a subnet as a result of receiving a 'subnet4-del' or 'subnet6-del' command'. The first parameter specifies a deleted subnet prefix. The second parameter specifies a subnet identifier.

46.40 SUBNET_CMDS_SUBNET_GET

```
successfully retrieved subnet %1 having id %2
```

This informational message is issued when the Subnet Commands hooks library successfully retrieves a subnet as a result of receiving a 'subnet4-get' or 'subnet6-get' command'. The first parameter specifies a retrieved subnet prefix. The second parameter specifies a subnet identifier.

46.41 SUBNET_CMDS_SUBNET_GET_EMPTY

```
specified subnet is not found: %1
```

This informational message is issued when the Subnet Commands hooks library found no a matching subnet as a result of receiving a 'subnet4-get' or 'subnet6-get' command'.

46.42 SUBNET_CMDS_SUBNET_LIST

```
successfully retrieved list of %1 %2 subnets
```

This informational message is issued when the Subnet Commands hooks library successfully retrieves a list of subnets as a result of receiving 'subnet4-list' or 'subnet6-list' command. The first argument specifies a number of subnets retrieved. The second parameter specifies a protocol type: 'IPv4' or 'IPv6'.

46.43 SUBNET_CMDS_SUBNET_LIST_EMPTY

```
no %1 subnets listed
```

This informational message is issued when the Subnet Commands hooks library successfully processes the 'subnet4-list' or 'subnet6-list' command but no subnets have been found. This indicates that the server configuration contains no subnets of the specific type. This is not an error condition but it is unusual case for the DHCP service. The argument specifies a type of the subnets being listed, i.e. 'IPv4' or 'IPv6'.

46.44 SUBNET_CMDS_SUBNET_UPDATE

successfully updated subnet %1 having id %2

This informational message is issued when the Subnet Commands hooks library successfully updates a subnet as a result of receiving a 'subnet4-update' or 'subnet6-update' command'. The first parameter specifies an updated subnet prefix. The second parameter specifies a subnet identifier.

47.1 TCP_CLIENT_BAD_SERVER_RESPONSE_RECEIVED

bad response received when communicating with %1 port %2: %3

Logged at debug log level 40. This debug message is issued when a TCP client fails to receive a response from the server or when this response is malformed. The first arguments specify the server address and port. The last provides a detailed error message.

47.2 TCP_CLIENT_BAD_SERVER_RESPONSE_RECEIVED_DETAILS

detailed information about bad response received from %1 port %2:\n%3

Logged at debug log level 45. This debug message is issued when a TCP client receives malformed response from the server. The first arguments specify the address and port of the server, The last argument provides a dump of the response.

47.3 TCP_CLIENT_CONNECTION_CLOSE_CALLBACK_FAILED

Connection close callback threw an exception

This is an error message emitted when the close connection callback registered on the connection failed unexpectedly. This is a programmatic error that should be submitted as a bug.

47.4 TCP_CLIENT_MT_STARTED

TcpClient has been started in multi-threaded mode running %1 threads

Logged at debug log level 40. This debug message is issued when a multi-threaded TCP client instance has been created. The argument specifies the maximum number of threads.

47.5 TCP_CLIENT_PREMATURE_CONNECTION_TIMEOUT_OCCURRED

premature connection timeout occurred: in transaction ? %1, transid: %2, current_transid: %3

This warning message is issued when unexpected timeout occurred during the transaction. This is proven to occur when the system clock is moved manually or as a result of synchronization with a time server. Any ongoing transactions will be interrupted. New transactions should be conducted normally.

47.6 TCP_CLIENT_QUEUE_SIZE_GROWING

```
queue for address: %1, port %2, now has %3 entries and may be growing too quickly
```

This warning message is issued when the queue of pending requests for the given address and port appears to be growing more quickly than the requests can be handled. It will be emitted periodically as long as the queue size continues to grow. This may occur with a surge of client traffic creating a momentary backlog which then subsides as the surge subsides. If it happens continually then it most likely indicates a deployment configuration that cannot sustain the client load.

47.7 TCP_CLIENT_REQUEST_SEND

```
sending TCP request %1 to %2 port %3
```

Logged at debug log level 50. This debug message is issued when the client is starting to send a TCP request to a server. The first argument dumps the request, next arguments specify address and port of the server.

47.8 TCP_CLIENT_SERVER_RESPONSE_RECEIVED

```
received TCP response from %1 port %2
```

Logged at debug log level 40. This debug message is issued when the client finished receiving a TCP response from the server. The address and port of the server are specified as arguments.

47.9 TCP_CONNECTION_REJECTED_BY_FILTER

```
connection from %1 has been denied by the connection filter.
```

Logged at debug log level 50. This debug message is issued when the server's connection filter rejects a new connection based on the client's ip address.

47.10 TCP_CONNECTION_SHUTDOWN

```
shutting down TCP connection from %1
```

Logged at debug log level 40. This debug message is issued when one of the TCP connections is shut down. The connection can be stopped as a result of an error or after the successful message exchange with a client.

47.11 TCP_CONNECTION_SHUTDOWN_FAILED

```
shutting down TCP connection failed
```

This error message is issued when an error occurred during shutting down a TCP connection with a client.

47.12 TCP_CONNECTION_STOP

```
stopping TCP connection from %1
```

Logged at debug log level 40. This debug message is issued when one of the TCP connections is stopped. The connection can be stopped as a result of an error or after the successful message exchange with a client.

47.13 TCP_CONNECTION_STOP_FAILED

```
stopping TCP connection failed
```

This error message is issued when an error occurred during closing a TCP connection with a client.

47.14 TCP_DATA_RECEIVED

```
received %1 bytes from %2
```

Logged at debug log level 55. This debug message is issued when the server receives a chunk of data from the remote endpoint. This may include the whole request or only a part of the request. The first argument specifies the amount of received data. The second argument specifies an address of the remote endpoint which produced the data.

47.15 TCP_DATA_SENT

```
send %1 bytes to %2
```

Logged at debug log level 55. This debug message is issued when the server sends a chunk of data to the remote endpoint. This may include the whole response or only a part of the response. The first argument specifies the amount of sent data. The second argument specifies an address of the remote endpoint.

47.16 TCP_IDLE_CONNECTION_TIMEOUT_OCCURRED

```
closing connection with %1 as a result of a timeout
```

Logged at debug log level 50. This debug message is issued when the TCP connection is being closed as a result of being idle.

47.17 TCP_REQUEST_RECEIVED_FAILED

```
An unexpected error occurred processing a request from %1, error: %2
```

This error message is issued when an unexpected error occurred while the server attempted to process a received request. The first argument specifies the address of the remote endpoint. The second argument describes the nature error.

47.18 TCP_REQUEST_RECEIVE_START

```
start receiving request from %1 with timeout %2
```

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

47.19 TCP_SERVER_CLIENT_REQUEST_RECEIVED

```
received TCP request from %1
```

Logged at debug log level 40. This debug message is issued when the server finished receiving a TCP request from the remote endpoint. The address of the remote endpoint is specified as an argument.

47.20 TCP_SERVER_RESPONSE_SEND

sending TCP response to %1

Logged at debug log level 40. This debug message is issued when the server is starting to send a TCP response to a remote endpoint. The argument specifies an address of the remote endpoint.

48.1 TKEY_EXCHANGE_ANSWER_CLASS

GSS-TKEY exchange received a response with answer class: %1.

Logged at debug log level 40. This debug message indicates that the GSS-TKEY exchange received a response with specified answer class.

48.2 TKEY_EXCHANGE_FAILED_TO_VERIFY

GSS-TKEY exchange failed because the response failed to verify.

This error message indicates that the GSS-TKEY exchange failed because the response failed to verify.

48.3 TKEY_EXCHANGE_FAIL_EMPTY_IN_TOKEN

GSS-TKEY exchange failed because input token is empty.

This error message indicates that the GSS-TKEY exchange failed because input token is empty.

48.4 TKEY_EXCHANGE_FAIL_EMPTY_OUT_TOKEN

GSS-TKEY exchange failed because output token is empty.

This error message indicates that the GSS-TKEY exchange failed because output token is empty.

48.5 TKEY_EXCHANGE_FAIL_EMPTY_RESPONSE

GSS-TKEY exchange failed because the response is empty.

This error message indicates that the GSS-TKEY exchange failed because the response is empty.

48.6 TKEY_EXCHANGE_FAIL_IO_ERROR

GSS-TKEY exchange failed because of the IO error: %1.

This error message indicates that the GSS-TKEY exchange failed because of an IO error. The argument details the IO error.

48.7 TKEY_EXCHANGE_FAIL_IO_STOPPED

GSS-TKEY exchange failed because the IO service was stopped.

This error message indicates that the GSS-TKEY exchange failed because the IO service was stopped.

48.8 TKEY_EXCHANGE_FAIL_IO_TIMEOUT

GSS-TKEY exchange failed because of IO timeout.

This error message indicates that the GSS-TKEY exchange failed because of IO timeout.

48.9 TKEY_EXCHANGE_FAIL_NOT_SIGNED

GSS-TKEY exchange failed because the response is not signed.

This error message indicates that the GSS-TKEY exchange failed because the response is not signed.

48.10 TKEY_EXCHANGE_FAIL_NO_RDATA

GSS-TKEY exchange failed because the response contains no rdata.

This error message indicates that the GSS-TKEY exchange failed because the response contains no rdata.

48.11 TKEY_EXCHANGE_FAIL_NO_RESPONSE_ANSWER

GSS-TKEY exchange failed because the response contains no answer.

This error message indicates that the GSS-TKEY exchange failed because the response contains no answer.

48.12 TKEY_EXCHANGE_FAIL_NULL_RESPONSE

GSS-TKEY exchange failed because the response is null.

This error message indicates that the GSS-TKEY exchange failed because the response is null.

48.13 TKEY_EXCHANGE_FAIL_RESPONSE_ERROR

GSS-TKEY exchange failed because the response contains an error: %1.

This error message indicates that the GSS-TKEY exchange failed because the response contains an error. The argument details the response error.

48.14 TKEY_EXCHANGE_FAIL_TKEY_ERROR

GSS-TKEY exchange failed because the response contains TKEY error: %1.

This error message indicates that the GSS-TKEY exchange failed because the response contains TKEY error. The argument details the TKEY error.

48.15 TKEY_EXCHANGE_FAIL_TO_INIT

GSS-TKEY exchange failed to initialize because of the error: %1.

This error message indicates that the GSS-TKEY exchange failed in the initialization phase, for instance because the server principal does not exist. The argument details the error.

48.16 TKEY_EXCHANGE_FAIL_WRONG_RESPONSE_ANSWER_COUNT

GSS-TKEY exchange failed because the response contains invalid number of RRs: %1.

This error message indicates that the GSS-TKEY exchange failed because the response contains invalid number of RRs. The argument contains the wrong number of RRs.

48.17 TKEY_EXCHANGE_FAIL_WRONG_RESPONSE_ANSWER_TYPE

GSS-TKEY exchange failed because the response contains wrong answer type: %1.

This error message indicates that the GSS-TKEY exchange failed because the response contains wrong answer type. The argument contains the wrong answer type.

48.18 TKEY_EXCHANGE_FAIL_WRONG_RESPONSE_OPCODE

GSS-TKEY exchange failed because the response contains invalid opcode: %1.

This error message indicates that the GSS-TKEY exchange failed because the response contains invalid opcode. The argument contains the wrong opcode.

48.19 TKEY_EXCHANGE_IO_FETCH_RESULT

exchange callback handling IO result: %1.

Logged at debug log level 40. This debug message indicates that the exchange callback has been called with the IOFetch result contained in the message argument.

48.20 TKEY_EXCHANGE_NOT_A_RESPONSE

GSS-TKEY exchange received a non response type.

Logged at debug log level 40. This debug message indicates that the GSS-TKEY exchange received a non response type.

48.21 TKEY_EXCHANGE_OUT_TOKEN_NOT_EMPTY

GSS-TKEY exchange output token is not empty.

Logged at debug log level 40. This debug message indicates that the GSS-TKEY exchange output token is not empty.

48.22 TKEY_EXCHANGE_RDATA_COUNT

GSS-TKEY exchange received a response with rdata count: %1.

Logged at debug log level 40. This debug message indicates that the GSS-TKEY exchange received a response with specified rdata count.

48.23 TKEY_EXCHANGE_RECEIVE_MESSAGE

GSS-TKEY exchange receives a message of size: %1.

Logged at debug log level 40. This debug message indicates that the GSS-TKEY exchange receives a message of specified size.

48.24 TKEY_EXCHANGE_RESPONSE_TTL

GSS-TKEY exchange received a response with TTL of: %1 seconds.

Logged at debug log level 40. This debug message indicates that the GSS-TKEY exchange received a response with specified TTL.

48.25 TKEY_EXCHANGE_SEND_MESSAGE

GSS-TKEY exchange sends a message of size: %1.

Logged at debug log level 40. This debug message indicates that the GSS-TKEY exchange sends a message of specified size.

48.26 TKEY_EXCHANGE_VALID

GSS-TKEY exchange retrieved a TKEY valid for: %1 seconds.

Logged at debug log level 40. This debug message indicates that the GSS-TKEY exchange retrieved a TKEY valid for the specified time period expressed in seconds.

48.27 TKEY_EXCHANGE_VERIFIED

GSS-TKEY exchange verified.

Logged at debug log level 40. This debug message indicates that the GSS-TKEY exchange is verified.

49.1 TLS_CONNECTION_HANDSHAKE_FAILED

TLS handshake with %1 failed with %2

This information message is issued when the TLS handshake failed at the server side. The client address and the error message are displayed.

49.2 TLS_CONNECTION_HANDSHAKE_START

start TLS handshake with %1 with timeout %2

Logged at debug log level 50. This debug message is issued when the server starts the TLS handshake with the remote endpoint. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

49.3 TLS_REQUEST_RECEIVE_START

start receiving request from %1 with timeout %2

Logged at debug log level 50. This debug message is issued when the server starts receiving new request over the established connection. The first argument specifies the address of the remote endpoint. The second argument specifies request timeout in seconds.

49.4 TLS_SERVER_RESPONSE_SEND

sending TLS response to %1

Logged at debug log level 40. This debug message is issued when the server is starting to send a TLS response to a remote endpoint. The argument specifies an address of the remote endpoint.

50.1 USER_CHK_HOOK_LOAD_ERROR

DHCP UserCheckHook could not be loaded: %1

This is an error message issued when the DHCP UserCheckHook could not be loaded. The exact cause should be explained in the log message. User subnet selection will revert to default processing.

50.2 USER_CHK_HOOK_UNLOAD_ERROR

DHCP UserCheckHook an error occurred unloading the library: %1

This is an error message issued when an error occurs while unloading the UserCheckHook library. This is unlikely to occur and normal operations of the library will likely resume when it is next loaded.

50.3 USER_CHK_SUBNET4_SELECT_ERROR

DHCP UserCheckHook an unexpected error occurred in subnet4_select callout: %1

This is an error message issued when the DHCP UserCheckHook subnet4_select hook encounters an unexpected error. The message should contain a more detailed explanation.

50.4 USER_CHK_SUBNET4_SELECT_REGISTRY_NULL

DHCP UserCheckHook UserRegistry has not been created.

This is an error message issued when the DHCP UserCheckHook subnet4_select hook has been invoked but the UserRegistry has not been created. This is a programmatic error and should not occur.

50.5 USER_CHK_SUBNET6_SELECT_ERROR

DHCP UserCheckHook an unexpected error occurred in subnet6_select callout: %1

This is an error message issued when the DHCP UserCheckHook subnet6_select hook encounters an unexpected error. The message should contain a more detailed explanation.

50.6 USER_CHK_SUBNET6_SELECT_REGISTRY_NULL

DHCP UserCheckHook UserRegistry has not been created.

This is an error message issued when the DHCP UserCheckHook subnet6_select hook has been invoked but the UserRegistry has not been created. This is a programmatic error and should not occur.

KEA DEBUG MESSAGES BY LOG LEVEL

51.1 Messages printed on debuglevel 0

- DCTL_INIT_PROCESS
- DCTL_RUN_PROCESS
- DCTL_SHUTDOWN
- DCTL_SHUTDOWN_SIGNAL_RECVD
- DCTL_STANDALONE
- DHCP4_OPEN_SOCKET
- DHCP4_START_INFO
- DHCP6_OPEN_SOCKET
- DHCP6_START_INFO
- DHCP_DDNS_CLEARED_FOR_SHUTDOWN
- DHCP_DDNS_QUEUE_MGR_STARTED
- DHCP_DDNS_QUEUE_MGR_STOPPING
- DHCP_DDNS_RUN_EXIT
- DHCP_DDNS_SHUTDOWN_COMMAND
- NETCONF_RUN_EXIT

51.2 Messages printed on debuglevel 10

- COMMAND_DEREGISTERED
- COMMAND_EXTENDED_REGISTERED
- COMMAND_HTTP_LISTENER_COMMAND_REJECTED
- COMMAND_HTTP_LISTENER_STARTED
- COMMAND_HTTP_LISTENER_STOPPED
- COMMAND_HTTP_LISTENER_STOPPING
- COMMAND_REGISTERED
- COMMAND_SOCKET_CONNECTION_CLOSED
- COMMAND_SOCKET_CONNECTION_OPENED

- COMMAND_SOCKET_READ
- COMMAND_SOCKET_WRITE
- DCTL_CONFIG_START
- DHCP4_CONFIG_RECEIVED
- DHCP4_CONFIG_START
- DHCP6_CONFIG_RECEIVED
- DHCP6_CONFIG_START

51.3 Messages printed on debuglevel 15

- DHCP4_HOOK_BUFFER_RCVD_DROP
- DHCP4_HOOK_DDNS_UPDATE
- DHCP4_HOOK_DECLINE_SKIP
- DHCP4_HOOK_LEASE4_RELEASE_SKIP
- DHCP4_HOOK_PACKET_SEND_DROP
- DHCP4_HOOK_SUBNET4_SELECT_406_PARKING_LOT_FULL
- DHCP4_HOOK_SUBNET4_SELECT_PARKING_LOT_FULL
- DHCP4_HOOK_SUBNET6_SELECT_PARKING_LOT_FULL
- DHCP4_PACKET_DROP_0001
- DHCP4_PACKET_DROP_0002
- DHCP4_PACKET_DROP_0003
- DHCP4_PACKET_DROP_0004
- DHCP4_PACKET_DROP_0005
- DHCP4_PACKET_DROP_0006
- DHCP4_PACKET_DROP_0007
- DHCP4_PACKET_DROP_0008
- DHCP4_PACKET_DROP_0009
- DHCP4_PACKET_DROP_0010
- DHCP4_PACKET_DROP_0011
- DHCP4_PACKET_DROP_0012
- DHCP4_PACKET_DROP_0013
- DHCP4_PACKET_DROP_0014
- DHCP4_PACKET_NAK_0005
- DHCP6_HOOK_BUFFER_RCVD_DROP
- DHCP6_HOOK_DDNS_UPDATE
- DHCP6_HOOK_DECLINE_DROP
- DHCP6_HOOK_LEASES6_COMMITTED_DROP

- DHCP6_HOOK_LEASES6_PARKING_LOT_FULL
- DHCP6_HOOK_PACKET_SEND_DROP
- DHCP6_PACKET_DROP_DHCP_DISABLED
- DHCP6_PACKET_DROP_DROP_CLASS
- DHCP6_PACKET_DROP_DROP_CLASS2
- DHCP6_PACKET_DROP_DROP_CLASS_EARLY
- DHCP6_PACKET_DROP_DUPLICATE
- DHCP6_PACKET_DROP_PARSE_FAIL
- DHCP6_PACKET_DROP_SERVERID_MISMATCH
- DHCP6_PACKET_DROP_UNICAST
- DHCP6_PACKET_REJECT_CLASS

51.4 Messages printed on debuglevel 20

- LEASE_CMDS_ADD4
- LEASE_CMDS_ADD6
- LEASE_CMDS_BULK_APPLY6
- LEASE_CMDS_DEL4
- LEASE_CMDS_DEL6
- LEASE_CMDS_UPDATE4
- LEASE_CMDS_UPDATE6
- SFLQ_POOL4_DEL
- SFLQ_POOL4_GET_ALL
- SFLQ_POOL4_GET_BY_RANGE
- SFLQ_POOL4_GET_BY_SUBNET
- SFLQ_POOL4_REBUILD
- SFLQ_POOL6_DEL
- SFLQ_POOL6_GET_ALL
- SFLQ_POOL6_GET_BY_RANGE
- SFLQ_POOL6_GET_BY_SUBNET
- SFLQ_POOL6_REBUILD

51.5 Messages printed on debuglevel 40

- ALLOC_ENGINE_IGNORING_UNSUITABLE_GLOBAL_ADDRESS
- ALLOC_ENGINE_IGNORING_UNSUITABLE_GLOBAL_ADDRESS6
- ALLOC_ENGINE_LEASE_RECLAIMED
- ALLOC_ENGINE_V4_DISCOVER_HR

- ALLOC_ENGINE_V4_LEASES_RECLAMATION_COMPLETE
- ALLOC_ENGINE_V4_LEASES_RECLAMATION_START
- ALLOC_ENGINE_V4_LEASES_RECLAMATION_TIMEOUT
- ALLOC_ENGINE_V4_LEASE_RECLAIM
- ALLOC_ENGINE_V4_NO_MORE_EXPIRED_LEASES
- ALLOC_ENGINE_V4_OFFER_EXISTING_LEASE
- ALLOC_ENGINE_V4_OFFER_NEW_LEASE
- ALLOC_ENGINE_V4_OFFER_REQUESTED_LEASE
- ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE
- ALLOC_ENGINE_V4_RECLAIMED_LEASES_DELETE_COMPLETE
- ALLOC_ENGINE_V4_REQUEST_ADDRESS_RESERVED
- ALLOC_ENGINE_V4_REQUEST_ALLOC_REQUESTED
- ALLOC_ENGINE_V4_REQUEST_EXTEND_LEASE
- ALLOC_ENGINE_V4_REQUEST_INVALID
- ALLOC_ENGINE_V4_REQUEST_IN_USE
- ALLOC_ENGINE_V4_REQUEST_OUT_OF_POOL
- ALLOC_ENGINE_V4_REQUEST_PICK_ADDRESS
- ALLOC_ENGINE_V4_REQUEST_REMOVE_LEASE
- ALLOC_ENGINE_V4_REQUEST_USE_HR
- ALLOC_ENGINE_V6_ALLOC_HR_LEASE_EXISTS
- ALLOC_ENGINE_V6_ALLOC_LEASES_HR
- ALLOC_ENGINE_V6_ALLOC_LEASES_NO_HR
- ALLOC_ENGINE_V6_ALLOC_NO_LEASES_HR
- ALLOC_ENGINE_V6_ALLOC_NO_V6_HR
- ALLOC_ENGINE_V6_ALLOC_UNRESERVED
- ALLOC_ENGINE_V6_CALCULATED_PREFERRED_LIFETIME
- ALLOC_ENGINE_V6_EXPIRED_HINT_RESERVED
- ALLOC_ENGINE_V6_EXTEND_ALLOC_UNRESERVED
- ALLOC_ENGINE_V6_HINT_RESERVED
- ALLOC_ENGINE_V6_LEASES_RECLAMATION_COMPLETE
- ALLOC_ENGINE_V6_LEASES_RECLAMATION_START
- ALLOC_ENGINE_V6_LEASES_RECLAMATION_TIMEOUT
- ALLOC_ENGINE_V6_LEASE_RECLAIM
- ALLOC_ENGINE_V6_NO_MORE_EXPIRED_LEASES
- ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE
- ALLOC_ENGINE_V6_RECLAIMED_LEASES_DELETE_COMPLETE

- ALLOC_ENGINE_V6_RENEW_HR
- ALLOC_ENGINE_V6_RENEW_REMOVE_RESERVED
- ASIODNS_FETCH_STOPPED
- BOOTP_BOOTP_QUERY
- BOOTP_PACKET_OPTIONS_SKIPPED
- BOOTP_PACKET_PACK
- BOOTP_PACKET_UNPACK_FAILED
- BULK_LEASE_QUERY_AT_MAX_CONCURRENT_QUERIES
- BULK_LEASE_QUERY_DEQUEUED
- BULK_LEASE_QUERY_QUERY_RECEIVED
- BULK_LEASE_QUERY_RESPONSE_SENT
- DDNS_TUNING4_CALCULATED_HOSTNAME
- DDNS_TUNING4_SKIPPING_DDNS
- DDNS_TUNING6_CALCULATED_HOSTNAME
- DDNS_TUNING6_SKIPPING_DDNS
- DDNS_TUNING_SUBNET_EXPRESSION_PARSE
- DDNS_TUNING_SUBNET_EXPR_CACHED
- DHCP4_ADDITIONAL_CLASS_NO_TEST
- DHCP4_ADDITIONAL_CLASS_UNDEFINED
- DHCP4_BUFFER_RECEIVED
- DHCP4_CLASSES_ASSIGNED
- DHCP4_CLASSES_ASSIGNED_AFTER_SUBNET_SELECTION
- DHCP4_CLASS_ASSIGNED
- DHCP4_CLASS_UNCONFIGURED
- DHCP4_DHCP4O6_HOOK_SUBNET4_SELECT_DROP
- DHCP4_DHCP4O6_HOOK_SUBNET4_SELECT_SKIP
- DHCP4_DHCP4O6_PACKET_RECEIVED
- DHCP4_DHCP4O6_PACKET_SEND
- DHCP4_FLEX_ID
- DHCP4_HOOK_BUFFER_SEND_SKIP
- DHCP4_HOOK_PACKET_RCVD_SKIP
- DHCP4_HOOK_PACKET_SEND_SKIP
- DHCP4_HOOK_SUBNET4_SELECT_DROP
- DHCP4_HOOK_SUBNET4_SELECT_PARK
- DHCP4_HOOK_SUBNET4_SELECT_SKIP
- DHCP4_LEASE_QUERY_PACKET_UNPACK_FAILED

- DHCP4_LEASE_QUERY_PROCESS_FAILED
- DHCP4_LEASE_QUERY_RECEIVED
- DHCP4_LEASE_QUERY_RESPONSE_SENT
- DHCP4_PACKET_QUEUE_FULL
- DHCP4_RECLAIM_EXPIRED_LEASES_SKIPPED
- DHCP4_SHUTDOWN
- DHCP4_SHUTDOWN_REQUEST
- DHCP6_ADDITIONAL_CLASS_NO_TEST
- DHCP6_ADDITIONAL_CLASS_UNDEFINED
- DHCP6_ADDR6_REGISTER_DISABLED_DROP
- DHCP6_BUFFER_RECEIVED
- DHCP6_CLASSES_ASSIGNED
- DHCP6_CLASSES_ASSIGNED_AFTER_SUBNET_SELECTION
- DHCP6_CLASS_ASSIGNED
- DHCP6_CLASS_UNCONFIGURED
- DHCP6_DHCP4O6_PACKET_RECEIVED
- DHCP6_FLEX_ID
- DHCP6_HOOK_ADDR6_REGISTER_DROP
- DHCP6_HOOK_ADDR6_REGISTER_SKIP
- DHCP6_HOOK_BUFFER_SEND_SKIP
- DHCP6_HOOK_LEASE6_RELEASE_NA_SKIP
- DHCP6_HOOK_LEASE6_RELEASE_PD_SKIP
- DHCP6_HOOK_LEASES6_COMMITTED_PARK
- DHCP6_HOOK_PACKET_RCVD_SKIP
- DHCP6_HOOK_PACKET_SEND_SKIP
- DHCP6_HOOK_SUBNET6_SELECT_DROP
- DHCP6_HOOK_SUBNET6_SELECT_PARK
- DHCP6_HOOK_SUBNET6_SELECT_SKIP
- DHCP6_LEASE_QUERY_PACKET_UNPACK_FAILED
- DHCP6_LEASE_QUERY_PREFIX_LENGTH_LIST
- DHCP6_LEASE_QUERY_PROCESS_FAILED
- DHCP6_LEASE_QUERY_RECEIVED
- DHCP6_LEASE_QUERY_REPLY_SENT
- DHCP6_PACKET_PROCESS_FAIL
- DHCP6_PACKET_QUEUE_FULL
- DHCP6_RECLAIM_EXPIRED_LEASES_SKIPPED

- DHCP6_RELEASE_NA_FAIL_NOT_ASSIGNED
- DHCP6_RELEASE_PD_FAIL_NOT_ASSIGNED
- DHCP6_REQUIRED_OPTIONS_CHECK_FAIL
- DHCP6_SHUTDOWN
- DHCP6_SHUTDOWN_REQUEST
- DHCP6_UNKNOWN_MSG_RECEIVED
- DHCPSRV_CFGMGR_ADD_SUBNET4
- DHCPSRV_CFGMGR_ADD_SUBNET6
- DHCPSRV_CFGMGR_ALL_IFACES_ACTIVE
- DHCPSRV_CFGMGR_CFG_DHCP_DDNS
- DHCPSRV_CFGMGR_DEL_SUBNET4
- DHCPSRV_CFGMGR_DEL_SUBNET6
- DHCPSRV_CFGMGR_SUBNET4
- DHCPSRV_CFGMGR_SUBNET4_ADDR
- DHCPSRV_CFGMGR_SUBNET4_IFACE
- DHCPSRV_CFGMGR_SUBNET4_RELAY
- DHCPSRV_CFGMGR_SUBNET6
- DHCPSRV_CFGMGR_SUBNET6_IFACE
- DHCPSRV_CFGMGR_SUBNET6_IFACE_ID
- DHCPSRV_CFGMGR_SUBNET6_RELAY
- DHCPSRV_CFGMGR_UPDATE_SUBNET4
- DHCPSRV_CFGMGR_UPDATE_SUBNET6
- DHCPSRV_CLOSE_DB
- DHCPSRV_FORENSIC_BACKEND_DEREGISTER
- DHCPSRV_FORENSIC_BACKEND_REGISTER
- DHCPSRV_HOOK_LEASE4_RECOVER_SKIP
- DHCPSRV_HOOK_LEASE4_RENEW_SKIP
- DHCPSRV_HOOK_LEASE4_SELECT_SKIP
- DHCPSRV_HOOK_LEASE6_EXTEND_SKIP
- DHCPSRV_HOOK_LEASE6_RECOVER_SKIP
- DHCPSRV_HOOK_LEASE6_SELECT_SKIP
- DHCPSRV_LEASE4_EXTENDED_INFO_UPGRADED
- DHCPSRV_LEASE6_EXTENDED_INFO_UPGRADED
- DHCPSRV_LEASE_MGR_BACKEND_DEREGISTER
- DHCPSRV_LEASE_MGR_BACKEND_REGISTER
- DHCPSRV_MEMFILE_BEGIN_BUILD_EXTENDED_INFO_TABLES6

- DHCPSRV_MEMFILE_BEGIN_EXTRACT_EXTENDED_INFO4
- DHCPSRV_MEMFILE_EXTRACT_EXTENDED_INFO4
- DHCPSRV_MEMFILE_EXTRACT_EXTENDED_INFO4_ERROR
- DHCPSRV_MEMFILE_LFC_UNREGISTER_TIMER_FAILED
- DHCPSRV_SUBNET4O6_SELECT_FAILED
- DHCPSRV_SUBNET4_SELECT_BY_ADDRESS_NO_MATCH
- DHCPSRV_SUBNET4_SELECT_BY_INTERFACE_NO_MATCH
- DHCPSRV_SUBNET4_SELECT_BY_RELAY_ADDRESS_NO_MATCH
- DHCPSRV_SUBNET4_SELECT_NO_RAI_OPTIONS
- DHCPSRV_SUBNET4_SELECT_NO_RELAY_ADDRESS
- DHCPSRV_SUBNET4_SELECT_NO_USABLE_ADDRESS
- DHCPSRV_SUBNET6_SELECT_BY_ADDRESS_NO_MATCH
- DHCPSRV_SUBNET6_SELECT_BY_INTERFACE_ID_NO_MATCH
- DHCPSRV_SUBNET6_SELECT_BY_INTERFACE_NO_MATCH
- DHCPSRV_TIMERMGR_REGISTER_TIMER
- DHCPSRV_TIMERMGR_START_TIMER
- DHCPSRV_TIMERMGR_STOP_TIMER
- DHCPSRV_TIMERMGR_UNREGISTER_ALL_TIMERS
- DHCPSRV_TIMERMGR_UNREGISTER_TIMER
- DHCP_DDNS_CONFIGURE
- DHCP_DDNS_NCR_UDP_RECV_CANCELED
- DHCP_DDNS_QUEUE_MGR_RECONFIGURING
- DHCP_DDNS_QUEUE_MGR_STOPPED
- DHCP_IFACE_OPEN_SOCKET
- FLEX_ID_CID_AS_RFC4361_DUID_ENABLED
- FLEX_ID_EXPRESSION_EVALUATED
- FLEX_ID_EXPRESSION_EVALUATED_NP
- FLEX_ID_EXPRESSION_HEX
- FLEX_ID_IGNORE_IAID_APPLIED_ON_NA
- FLEX_ID_IGNORE_IAID_APPLIED_ON_PD
- FLEX_ID_IGNORE_IAID_NOT_APPLIED_ON_NA
- FLEX_ID_IGNORE_IAID_NOT_APPLIED_ON_PD
- FLEX_ID_NO_IDENTIFIER_EXPRESSION
- FLEX_ID_RESTORE_CLIENT_ID
- FLEX_ID_RESTORE_DUID
- FLEX_ID_USED_AS_CLIENT_ID

- FLEX_ID_USED_AS_DUID
- FLEX_OPTION_PROCESS_ADD
- FLEX_OPTION_PROCESS_CLIENT_CLASS
- FLEX_OPTION_PROCESS_REMOVE
- FLEX_OPTION_PROCESS_SUB_ADD
- FLEX_OPTION_PROCESS_SUB_CLIENT_CLASS
- FLEX_OPTION_PROCESS_SUB_REMOVE
- FLEX_OPTION_PROCESS_SUB_SUPERSEDE
- FLEX_OPTION_PROCESS_SUPERSEDE
- FLEX_OPTION_PROCESS_VENDOR_ID_MISMATCH
- GSS_TSIG_MANAGER_STARTED
- GSS_TSIG_MANAGER_STOPPED
- GSS_TSIG_NEW_KEY
- GSS_TSIG_NEW_KEY_SETUP_SUCCEED
- GSS_TSIG_OLD_KEY_REMOVED
- GSS_TSIG_VERIFIED
- HA_BUFFER4_RECEIVE_NOT_FOR_US
- HA_BUFFER4_RECEIVE_PACKET_OPTIONS_SKIPPED
- HA_BUFFER4_RECEIVE_UNPACK_FAILED
- HA_BUFFER6_RECEIVE_NOT_FOR_US
- HA_BUFFER6_RECEIVE_PACKET_OPTIONS_SKIPPED
- HA_BUFFER6_RECEIVE_UNPACK_FAILED
- HA_LEASE4_EXPIRE_RECLAMATION_SKIP
- HA_LEASE6_EXPIRE_RECLAMATION_SKIP
- HA_LEASES4_COMMITTED_NOTHING_TO_UPDATE
- HA_LEASES6_COMMITTED_NOTHING_TO_UPDATE
- HA_LEASE_SYNC_STALE_LEASE4_SKIP
- HA_LEASE_SYNC_STALE_LEASE6_SKIP
- HA_LOAD_BALANCING_DUID_MISSING
- HA_LOAD_BALANCING_IDENTIFIER_MISSING
- HA_LOAD_BALANCING_LEASE_DUID_MISSING
- HA_LOAD_BALANCING_LEASE_IDENTIFIER_MISSING
- HA_SUBNET4_SELECT_NOT_FOR_US
- HA_SUBNET4_SELECT_NO_SUBNET_SELECTED
- HA_SUBNET6_SELECT_NOT_FOR_US
- HA_SUBNET6_SELECT_NO_SUBNET_SELECTED

- `HOOKS_LIBRARY_LOADING`
- `HOOKS_LIBRARY_UNLOADING`
- `HOOKS_LOAD_SUCCESS`
- `HOOKS_NO_LOAD`
- `HOOKS_NO_UNLOAD`
- `HOOKS_UNLOAD_SUCCESS`
- `HOSTS_BACKEND_DEREGISTER`
- `HOSTS_BACKEND_REGISTER`
- `HOSTS_CFG_ADD_HOST`
- `HOSTS_CFG_CLOSE_HOST_DATA_SOURCE`
- `HOSTS_CFG_DEL`
- `HOSTS_CFG_DEL4`
- `HOSTS_CFG_DEL6`
- `HOSTS_CFG_DEL_ALL_SUBNET4`
- `HOSTS_CFG_DEL_ALL_SUBNET6`
- `HOSTS_CFG_GET_ALL`
- `HOSTS_CFG_GET_ALL_ADDRESS4`
- `HOSTS_CFG_GET_ALL_ADDRESS6`
- `HOSTS_CFG_GET_ALL_HOSTNAME`
- `HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4`
- `HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6`
- `HOSTS_CFG_GET_ALL_IDENTIFIER`
- `HOSTS_CFG_GET_ALL_SUBNET_ID4`
- `HOSTS_CFG_GET_ALL_SUBNET_ID6`
- `HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4`
- `HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6`
- `HOSTS_CFG_GET_ONE_PREFIX`
- `HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4`
- `HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6`
- `HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER`
- `HOSTS_CFG_UPDATE_ADD`
- `HOSTS_CFG_UPDATE_DEL4`
- `HOSTS_CFG_UPDATE_DEL6`
- `HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_ADDRESS4`
- `HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER`
- `HOSTS_MGR_ALTERNATE_GET6_PREFIX`

- HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_ADDRESS6
- HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER
- HOSTS_MGR_ALTERNATE_GET_ALL_SUBNET_ID_ADDRESS4
- HOSTS_MGR_ALTERNATE_GET_ALL_SUBNET_ID_ADDRESS6
- HOST_CACHE_GET_ONE_PREFIX
- HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS4
- HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS6
- HOST_CACHE_GET_ONE_SUBNET_ID_IDENTIFIER
- HTTP_BAD_CLIENT_REQUEST_RECEIVED
- HTTP_BAD_SERVER_RESPONSE_RECEIVED
- HTTP_CLIENT_MT_STARTED
- HTTP_CLIENT_REQUEST_RECEIVED
- HTTP_CONNECTION_SHUTDOWN
- HTTP_CONNECTION_STOP
- HTTP_SERVER_RESPONSE_RECEIVED
- HTTP_SERVER_RESPONSE_SEND
- KEY_LOOKUP_DISABLED
- KEY_LOOKUP_FOUND
- KEY_LOOKUP_NONE
- LIMITS_CONFIGURED_ADDRESS_LIMIT_BY_CLIENT_CLASS
- LIMITS_CONFIGURED_ADDRESS_LIMIT_BY_SUBNET
- LIMITS_CONFIGURED_PREFIX_LIMIT_BY_CLIENT_CLASS
- LIMITS_CONFIGURED_PREFIX_LIMIT_BY_SUBNET
- LIMITS_CONFIGURED_RATE_LIMIT_BY_CLIENT_CLASS
- LIMITS_CONFIGURED_RATE_LIMIT_BY_SUBNET
- LIMITS_LEASE_LIMIT_EXCEEDED
- LIMITS_LEASE_WITHIN_LIMITS
- LIMITS_PACKET_WITH_CLIENT_CLASSES_RATE_LIMIT_DROPPED
- LIMITS_PACKET_WITH_SUBNET_ID_RATE_LIMIT_DROPPED
- MT_TCP_LISTENER_MGR_STARTED
- MT_TCP_LISTENER_MGR_STOPPED
- MT_TCP_LISTENER_MGR_STOPPING
- MYSQL_CB_CREATE_UPDATE_BY_POOL_OPTION4
- MYSQL_CB_CREATE_UPDATE_BY_POOL_OPTION6
- MYSQL_CB_CREATE_UPDATE_BY_PREFIX_OPTION6
- MYSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION4

- MYSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION6
- MYSQL_CB_CREATE_UPDATE_CLIENT_CLASS4
- MYSQL_CB_CREATE_UPDATE_CLIENT_CLASS6
- MYSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER4
- MYSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER6
- MYSQL_CB_CREATE_UPDATE_OPTION4
- MYSQL_CB_CREATE_UPDATE_OPTION6
- MYSQL_CB_CREATE_UPDATE_OPTION_DEF4
- MYSQL_CB_CREATE_UPDATE_OPTION_DEF6
- MYSQL_CB_CREATE_UPDATE_SERVER4
- MYSQL_CB_CREATE_UPDATE_SERVER6
- MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK4
- MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK6
- MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION4
- MYSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION6
- MYSQL_CB_CREATE_UPDATE_SUBNET4
- MYSQL_CB_CREATE_UPDATE_SUBNET6
- MYSQL_CB_DELETE_ALL_CLIENT_CLASSES4
- MYSQL_CB_DELETE_ALL_CLIENT_CLASSES4_RESULT
- MYSQL_CB_DELETE_ALL_CLIENT_CLASSES6
- MYSQL_CB_DELETE_ALL_CLIENT_CLASSES6_RESULT
- MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4
- MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4_RESULT
- MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6
- MYSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6_RESULT
- MYSQL_CB_DELETE_ALL_OPTION_DEFS4
- MYSQL_CB_DELETE_ALL_OPTION_DEFS4_RESULT
- MYSQL_CB_DELETE_ALL_OPTION_DEFS6
- MYSQL_CB_DELETE_ALL_OPTION_DEFS6_RESULT
- MYSQL_CB_DELETE_ALL_SERVERS4
- MYSQL_CB_DELETE_ALL_SERVERS4_RESULT
- MYSQL_CB_DELETE_ALL_SERVERS6
- MYSQL_CB_DELETE_ALL_SERVERS6_RESULT
- MYSQL_CB_DELETE_ALL_SHARED_NETWORKS4
- MYSQL_CB_DELETE_ALL_SHARED_NETWORKS4_RESULT
- MYSQL_CB_DELETE_ALL_SHARED_NETWORKS6

- MYSQL_CB_DELETE_ALL_SHARED_NETWORKS6_RESULT
- MYSQL_CB_DELETE_ALL_SUBNETS4
- MYSQL_CB_DELETE_ALL_SUBNETS4_RESULT
- MYSQL_CB_DELETE_ALL_SUBNETS6
- MYSQL_CB_DELETE_ALL_SUBNETS6_RESULT
- MYSQL_CB_DELETE_BY_POOL_OPTION4
- MYSQL_CB_DELETE_BY_POOL_OPTION4_RESULT
- MYSQL_CB_DELETE_BY_POOL_OPTION6
- MYSQL_CB_DELETE_BY_POOL_OPTION6_RESULT
- MYSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6
- MYSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6_RESULT
- MYSQL_CB_DELETE_BY_PREFIX_SUBNET4
- MYSQL_CB_DELETE_BY_PREFIX_SUBNET4_RESULT
- MYSQL_CB_DELETE_BY_PREFIX_SUBNET6
- MYSQL_CB_DELETE_BY_PREFIX_SUBNET6_RESULT
- MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION4
- MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION4_RESULT
- MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION6
- MYSQL_CB_DELETE_BY_SUBNET_ID_OPTION6_RESULT
- MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4
- MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4_RESULT
- MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6
- MYSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6_RESULT
- MYSQL_CB_DELETE_CLIENT_CLASS4
- MYSQL_CB_DELETE_CLIENT_CLASS4_RESULT
- MYSQL_CB_DELETE_CLIENT_CLASS6
- MYSQL_CB_DELETE_CLIENT_CLASS6_RESULT
- MYSQL_CB_DELETE_GLOBAL_PARAMETER4
- MYSQL_CB_DELETE_GLOBAL_PARAMETER4_RESULT
- MYSQL_CB_DELETE_GLOBAL_PARAMETER6
- MYSQL_CB_DELETE_GLOBAL_PARAMETER6_RESULT
- MYSQL_CB_DELETE_OPTION4
- MYSQL_CB_DELETE_OPTION4_RESULT
- MYSQL_CB_DELETE_OPTION6
- MYSQL_CB_DELETE_OPTION6_RESULT
- MYSQL_CB_DELETE_OPTION_DEF4

- MYSQL_CB_DELETE_OPTION_DEF4_RESULT
- MYSQL_CB_DELETE_OPTION_DEF6
- MYSQL_CB_DELETE_OPTION_DEF6_RESULT
- MYSQL_CB_DELETE_SERVER4
- MYSQL_CB_DELETE_SERVER4_RESULT
- MYSQL_CB_DELETE_SERVER6
- MYSQL_CB_DELETE_SERVER6_RESULT
- MYSQL_CB_DELETE_SHARED_NETWORK4
- MYSQL_CB_DELETE_SHARED_NETWORK4_RESULT
- MYSQL_CB_DELETE_SHARED_NETWORK6
- MYSQL_CB_DELETE_SHARED_NETWORK6_RESULT
- MYSQL_CB_DELETE_SHARED_NETWORK_OPTION4
- MYSQL_CB_DELETE_SHARED_NETWORK_OPTION4_RESULT
- MYSQL_CB_DELETE_SHARED_NETWORK_OPTION6
- MYSQL_CB_DELETE_SHARED_NETWORK_OPTION6_RESULT
- MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4
- MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT
- MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6
- MYSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT
- MYSQL_CB_GET_ALL_CLIENT_CLASSES4
- MYSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT
- MYSQL_CB_GET_ALL_CLIENT_CLASSES6
- MYSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT
- MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS4
- MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT
- MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS6
- MYSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT
- MYSQL_CB_GET_ALL_OPTIONS4
- MYSQL_CB_GET_ALL_OPTIONS4_RESULT
- MYSQL_CB_GET_ALL_OPTIONS6
- MYSQL_CB_GET_ALL_OPTIONS6_RESULT
- MYSQL_CB_GET_ALL_OPTION_DEFS4
- MYSQL_CB_GET_ALL_OPTION_DEFS4_RESULT
- MYSQL_CB_GET_ALL_OPTION_DEFS6
- MYSQL_CB_GET_ALL_OPTION_DEFS6_RESULT
- MYSQL_CB_GET_ALL_SERVERS4

- MYSQL_CB_GET_ALL_SERVERS4_RESULT
- MYSQL_CB_GET_ALL_SERVERS6
- MYSQL_CB_GET_ALL_SERVERS6_RESULT
- MYSQL_CB_GET_ALL_SHARED_NETWORKS4
- MYSQL_CB_GET_ALL_SHARED_NETWORKS4_RESULT
- MYSQL_CB_GET_ALL_SHARED_NETWORKS6
- MYSQL_CB_GET_ALL_SHARED_NETWORKS6_RESULT
- MYSQL_CB_GET_ALL_SUBNETS4
- MYSQL_CB_GET_ALL_SUBNETS4_RESULT
- MYSQL_CB_GET_ALL_SUBNETS6
- MYSQL_CB_GET_ALL_SUBNETS6_RESULT
- MYSQL_CB_GET_CLIENT_CLASS4
- MYSQL_CB_GET_CLIENT_CLASS6
- MYSQL_CB_GET_GLOBAL_PARAMETER4
- MYSQL_CB_GET_GLOBAL_PARAMETER6
- MYSQL_CB_GET_HOST4
- MYSQL_CB_GET_HOST6
- MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES4
- MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES4_RESULT
- MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES6
- MYSQL_CB_GET_MODIFIED_CLIENT_CLASSES6_RESULT
- MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4
- MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4_RESULT
- MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6
- MYSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6_RESULT
- MYSQL_CB_GET_MODIFIED_OPTIONS4
- MYSQL_CB_GET_MODIFIED_OPTIONS4_RESULT
- MYSQL_CB_GET_MODIFIED_OPTIONS6
- MYSQL_CB_GET_MODIFIED_OPTIONS6_RESULT
- MYSQL_CB_GET_MODIFIED_OPTION_DEFS4
- MYSQL_CB_GET_MODIFIED_OPTION_DEFS4_RESULT
- MYSQL_CB_GET_MODIFIED_OPTION_DEFS6
- MYSQL_CB_GET_MODIFIED_OPTION_DEFS6_RESULT
- MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS4
- MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS4_RESULT
- MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS6

- MYSQL_CB_GET_MODIFIED_SHARED_NETWORKS6_RESULT
- MYSQL_CB_GET_MODIFIED_SUBNETS4
- MYSQL_CB_GET_MODIFIED_SUBNETS4_RESULT
- MYSQL_CB_GET_MODIFIED_SUBNETS6
- MYSQL_CB_GET_MODIFIED_SUBNETS6_RESULT
- MYSQL_CB_GET_OPTION4
- MYSQL_CB_GET_OPTION6
- MYSQL_CB_GET_OPTION_DEF4
- MYSQL_CB_GET_OPTION_DEF6
- MYSQL_CB_GET_PORT4
- MYSQL_CB_GET_PORT6
- MYSQL_CB_GET_RECENT_AUDIT_ENTRIES4
- MYSQL_CB_GET_RECENT_AUDIT_ENTRIES4_RESULT
- MYSQL_CB_GET_RECENT_AUDIT_ENTRIES6
- MYSQL_CB_GET_RECENT_AUDIT_ENTRIES6_RESULT
- MYSQL_CB_GET_SERVER4
- MYSQL_CB_GET_SERVER6
- MYSQL_CB_GET_SHARED_NETWORK4
- MYSQL_CB_GET_SHARED_NETWORK6
- MYSQL_CB_GET_SHARED_NETWORK_SUBNETS4
- MYSQL_CB_GET_SHARED_NETWORK_SUBNETS4_RESULT
- MYSQL_CB_GET_SHARED_NETWORK_SUBNETS6
- MYSQL_CB_GET_SHARED_NETWORK_SUBNETS6_RESULT
- MYSQL_CB_GET_SUBNET4_BY_PREFIX
- MYSQL_CB_GET_SUBNET4_BY_SUBNET_ID
- MYSQL_CB_GET_SUBNET6_BY_PREFIX
- MYSQL_CB_GET_SUBNET6_BY_SUBNET_ID
- MYSQL_CB_GET_TYPE4
- MYSQL_CB_GET_TYPE6
- MYSQL_CB_REGISTER_BACKEND_TYPE4
- MYSQL_CB_REGISTER_BACKEND_TYPE6
- MYSQL_CB_TLS_CIPHER
- MYSQL_CB_UNREGISTER_BACKEND_TYPE4
- MYSQL_CB_UNREGISTER_BACKEND_TYPE6
- MYSQL_HB_TLS_CIPHER
- MYSQL_LB_TLS_CIPHER

- MYSQL_LB_UPGRADE_EXTENDED_INFO4
- MYSQL_LB_UPGRADE_EXTENDED_INFO4_ERROR
- MYSQL_LB_UPGRADE_EXTENDED_INFO6
- MYSQL_LB_UPGRADE_EXTENDED_INFO6_ERROR
- PERFMON_DHCP4_SOCKET_RECEIVED_TIME_SUPPORT
- PERFMON_DHCP6_SOCKET_RECEIVED_TIME_SUPPORT
- PGSQL_CB_CREATE_UPDATE_BY_POOL_OPTION4
- PGSQL_CB_CREATE_UPDATE_BY_POOL_OPTION6
- PGSQL_CB_CREATE_UPDATE_BY_PREFIX_OPTION6
- PGSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION4
- PGSQL_CB_CREATE_UPDATE_BY_SUBNET_ID_OPTION6
- PGSQL_CB_CREATE_UPDATE_CLIENT_CLASS4
- PGSQL_CB_CREATE_UPDATE_CLIENT_CLASS6
- PGSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER4
- PGSQL_CB_CREATE_UPDATE_GLOBAL_PARAMETER6
- PGSQL_CB_CREATE_UPDATE_OPTION4
- PGSQL_CB_CREATE_UPDATE_OPTION6
- PGSQL_CB_CREATE_UPDATE_OPTION_DEF4
- PGSQL_CB_CREATE_UPDATE_OPTION_DEF6
- PGSQL_CB_CREATE_UPDATE_SERVER4
- PGSQL_CB_CREATE_UPDATE_SERVER6
- PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK4
- PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK6
- PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION4
- PGSQL_CB_CREATE_UPDATE_SHARED_NETWORK_OPTION6
- PGSQL_CB_CREATE_UPDATE_SUBNET4
- PGSQL_CB_CREATE_UPDATE_SUBNET6
- PGSQL_CB_DELETE_ALL_CLIENT_CLASSES4
- PGSQL_CB_DELETE_ALL_CLIENT_CLASSES4_RESULT
- PGSQL_CB_DELETE_ALL_CLIENT_CLASSES6
- PGSQL_CB_DELETE_ALL_CLIENT_CLASSES6_RESULT
- PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4
- PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS4_RESULT
- PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6
- PGSQL_CB_DELETE_ALL_GLOBAL_PARAMETERS6_RESULT
- PGSQL_CB_DELETE_ALL_OPTION_DEFS4

- PGSQL_CB_DELETE_ALL_OPTION_DEFS4_RESULT
- PGSQL_CB_DELETE_ALL_OPTION_DEFS6
- PGSQL_CB_DELETE_ALL_OPTION_DEFS6_RESULT
- PGSQL_CB_DELETE_ALL_SERVERS4
- PGSQL_CB_DELETE_ALL_SERVERS4_RESULT
- PGSQL_CB_DELETE_ALL_SERVERS6
- PGSQL_CB_DELETE_ALL_SERVERS6_RESULT
- PGSQL_CB_DELETE_ALL_SHARED_NETWORKS4
- PGSQL_CB_DELETE_ALL_SHARED_NETWORKS4_RESULT
- PGSQL_CB_DELETE_ALL_SHARED_NETWORKS6
- PGSQL_CB_DELETE_ALL_SHARED_NETWORKS6_RESULT
- PGSQL_CB_DELETE_ALL_SUBNETS4
- PGSQL_CB_DELETE_ALL_SUBNETS4_RESULT
- PGSQL_CB_DELETE_ALL_SUBNETS6
- PGSQL_CB_DELETE_ALL_SUBNETS6_RESULT
- PGSQL_CB_DELETE_BY_POOL_OPTION4
- PGSQL_CB_DELETE_BY_POOL_OPTION4_RESULT
- PGSQL_CB_DELETE_BY_POOL_OPTION6
- PGSQL_CB_DELETE_BY_POOL_OPTION6_RESULT
- PGSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6
- PGSQL_CB_DELETE_BY_POOL_PREFIX_OPTION6_RESULT
- PGSQL_CB_DELETE_BY_PREFIX_SUBNET4
- PGSQL_CB_DELETE_BY_PREFIX_SUBNET4_RESULT
- PGSQL_CB_DELETE_BY_PREFIX_SUBNET6
- PGSQL_CB_DELETE_BY_PREFIX_SUBNET6_RESULT
- PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION4
- PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION4_RESULT
- PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION6
- PGSQL_CB_DELETE_BY_SUBNET_ID_OPTION6_RESULT
- PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4
- PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET4_RESULT
- PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6
- PGSQL_CB_DELETE_BY_SUBNET_ID_SUBNET6_RESULT
- PGSQL_CB_DELETE_CLIENT_CLASS4
- PGSQL_CB_DELETE_CLIENT_CLASS4_RESULT
- PGSQL_CB_DELETE_CLIENT_CLASS6

- PGSQL_CB_DELETE_CLIENT_CLASS6_RESULT
- PGSQL_CB_DELETE_GLOBAL_PARAMETER4
- PGSQL_CB_DELETE_GLOBAL_PARAMETER4_RESULT
- PGSQL_CB_DELETE_GLOBAL_PARAMETER6
- PGSQL_CB_DELETE_GLOBAL_PARAMETER6_RESULT
- PGSQL_CB_DELETE_OPTION4
- PGSQL_CB_DELETE_OPTION4_RESULT
- PGSQL_CB_DELETE_OPTION6
- PGSQL_CB_DELETE_OPTION6_RESULT
- PGSQL_CB_DELETE_OPTION_DEF4
- PGSQL_CB_DELETE_OPTION_DEF4_RESULT
- PGSQL_CB_DELETE_OPTION_DEF6
- PGSQL_CB_DELETE_OPTION_DEF6_RESULT
- PGSQL_CB_DELETE_SERVER4
- PGSQL_CB_DELETE_SERVER4_RESULT
- PGSQL_CB_DELETE_SERVER6
- PGSQL_CB_DELETE_SERVER6_RESULT
- PGSQL_CB_DELETE_SHARED_NETWORK4
- PGSQL_CB_DELETE_SHARED_NETWORK4_RESULT
- PGSQL_CB_DELETE_SHARED_NETWORK6
- PGSQL_CB_DELETE_SHARED_NETWORK6_RESULT
- PGSQL_CB_DELETE_SHARED_NETWORK_OPTION4
- PGSQL_CB_DELETE_SHARED_NETWORK_OPTION4_RESULT
- PGSQL_CB_DELETE_SHARED_NETWORK_OPTION6
- PGSQL_CB_DELETE_SHARED_NETWORK_OPTION6_RESULT
- PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4
- PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS4_RESULT
- PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6
- PGSQL_CB_DELETE_SHARED_NETWORK_SUBNETS6_RESULT
- PGSQL_CB_GET_ALL_CLIENT_CLASSES4
- PGSQL_CB_GET_ALL_CLIENT_CLASSES4_RESULT
- PGSQL_CB_GET_ALL_CLIENT_CLASSES6
- PGSQL_CB_GET_ALL_CLIENT_CLASSES6_RESULT
- PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4
- PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS4_RESULT
- PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6

- PGSQL_CB_GET_ALL_GLOBAL_PARAMETERS6_RESULT
- PGSQL_CB_GET_ALL_OPTIONS4
- PGSQL_CB_GET_ALL_OPTIONS4_RESULT
- PGSQL_CB_GET_ALL_OPTIONS6
- PGSQL_CB_GET_ALL_OPTIONS6_RESULT
- PGSQL_CB_GET_ALL_OPTION_DEFS4
- PGSQL_CB_GET_ALL_OPTION_DEFS4_RESULT
- PGSQL_CB_GET_ALL_OPTION_DEFS6
- PGSQL_CB_GET_ALL_OPTION_DEFS6_RESULT
- PGSQL_CB_GET_ALL_SERVERS4
- PGSQL_CB_GET_ALL_SERVERS4_RESULT
- PGSQL_CB_GET_ALL_SERVERS6
- PGSQL_CB_GET_ALL_SERVERS6_RESULT
- PGSQL_CB_GET_ALL_SHARED_NETWORKS4
- PGSQL_CB_GET_ALL_SHARED_NETWORKS4_RESULT
- PGSQL_CB_GET_ALL_SHARED_NETWORKS6
- PGSQL_CB_GET_ALL_SHARED_NETWORKS6_RESULT
- PGSQL_CB_GET_ALL_SUBNETS4
- PGSQL_CB_GET_ALL_SUBNETS4_RESULT
- PGSQL_CB_GET_ALL_SUBNETS6
- PGSQL_CB_GET_ALL_SUBNETS6_RESULT
- PGSQL_CB_GET_CLIENT_CLASS4
- PGSQL_CB_GET_CLIENT_CLASS6
- PGSQL_CB_GET_GLOBAL_PARAMETER4
- PGSQL_CB_GET_GLOBAL_PARAMETER6
- PGSQL_CB_GET_HOST4
- PGSQL_CB_GET_HOST6
- PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES4
- PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES4_RESULT
- PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES6
- PGSQL_CB_GET_MODIFIED_CLIENT_CLASSES6_RESULT
- PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4
- PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS4_RESULT
- PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6
- PGSQL_CB_GET_MODIFIED_GLOBAL_PARAMETERS6_RESULT
- PGSQL_CB_GET_MODIFIED_OPTIONS4

- PGSQL_CB_GET_MODIFIED_OPTIONS4_RESULT
- PGSQL_CB_GET_MODIFIED_OPTIONS6
- PGSQL_CB_GET_MODIFIED_OPTIONS6_RESULT
- PGSQL_CB_GET_MODIFIED_OPTION_DEFS4
- PGSQL_CB_GET_MODIFIED_OPTION_DEFS4_RESULT
- PGSQL_CB_GET_MODIFIED_OPTION_DEFS6
- PGSQL_CB_GET_MODIFIED_OPTION_DEFS6_RESULT
- PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS4
- PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS4_RESULT
- PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS6
- PGSQL_CB_GET_MODIFIED_SHARED_NETWORKS6_RESULT
- PGSQL_CB_GET_MODIFIED_SUBNETS4
- PGSQL_CB_GET_MODIFIED_SUBNETS4_RESULT
- PGSQL_CB_GET_MODIFIED_SUBNETS6
- PGSQL_CB_GET_MODIFIED_SUBNETS6_RESULT
- PGSQL_CB_GET_OPTION4
- PGSQL_CB_GET_OPTION6
- PGSQL_CB_GET_OPTION_DEF4
- PGSQL_CB_GET_OPTION_DEF6
- PGSQL_CB_GET_PORT4
- PGSQL_CB_GET_PORT6
- PGSQL_CB_GET_RECENT_AUDIT_ENTRIES4
- PGSQL_CB_GET_RECENT_AUDIT_ENTRIES4_RESULT
- PGSQL_CB_GET_RECENT_AUDIT_ENTRIES6
- PGSQL_CB_GET_RECENT_AUDIT_ENTRIES6_RESULT
- PGSQL_CB_GET_SERVER4
- PGSQL_CB_GET_SERVER6
- PGSQL_CB_GET_SHARED_NETWORK4
- PGSQL_CB_GET_SHARED_NETWORK6
- PGSQL_CB_GET_SHARED_NETWORK_SUBNETS4
- PGSQL_CB_GET_SHARED_NETWORK_SUBNETS4_RESULT
- PGSQL_CB_GET_SHARED_NETWORK_SUBNETS6
- PGSQL_CB_GET_SHARED_NETWORK_SUBNETS6_RESULT
- PGSQL_CB_GET_SUBNET4_BY_PREFIX
- PGSQL_CB_GET_SUBNET4_BY_SUBNET_ID
- PGSQL_CB_GET_SUBNET6_BY_PREFIX

- PGSQL_CB_GET_SUBNET6_BY_SUBNET_ID
- PGSQL_CB_GET_TYPE4
- PGSQL_CB_GET_TYPE6
- PGSQL_CB_REGISTER_BACKEND_TYPE4
- PGSQL_CB_REGISTER_BACKEND_TYPE6
- PGSQL_CB_UNREGISTER_BACKEND_TYPE4
- PGSQL_CB_UNREGISTER_BACKEND_TYPE6
- PGSQL_LB_UPGRADE_EXTENDED_INFO4
- PGSQL_LB_UPGRADE_EXTENDED_INFO4_ERROR
- PGSQL_LB_UPGRADE_EXTENDED_INFO6
- PGSQL_LB_UPGRADE_EXTENDED_INFO6_ERROR
- PING_CHECK_CHANNEL_MALFORMED_PACKET_RECEIVED
- PING_CHECK_CHANNEL_SOCKET_CLOSED
- PING_CHECK_CHANNEL_SOCKET_OPENED
- PING_CHECK_CHANNEL_STOP
- PING_CHECK_DUPLICATE_CHECK
- PING_CHECK_MGR_LEASE_FREE_TO_USE
- PING_CHECK_MGR_RECEIVED_ECHO_REPLY
- PING_CHECK_MGR_START_PING_CHECK
- PING_CHECK_MGR_STOPPING
- RADIUS_ACCESS_CACHE_GET
- RADIUS_ACCESS_CACHE_INSERT
- RADIUS_ACCESS_CONFLICT
- RADIUS_ACCESS_DROP_PARKED_QUERY
- RADIUS_ACCESS_GET_IDENTIFIER
- RADIUS_ACCESS_MAX_PENDING_REQUESTS
- RADIUS_ACCESS_RESUME_PARKED_QUERY
- RADIUS_ACCESS_SUBNET_RESELECT
- RADIUS_ACCOUNTING_ASYNC
- RADIUS_ACCOUNTING_ASYNC_FAILED
- RADIUS_ACCOUNTING_ASYNC_SUCCEED
- RADIUS_ACCOUNTING_NO_HISTORY
- RADIUS_ACCOUNTING_STATUS
- RADIUS_ACCOUNTING_STATUS_FAILED
- RADIUS_ACCOUNTING_STATUS_SUCCEED
- RADIUS_ACCOUNTING_SYNC

- RADIUS_ACCOUNTING_SYNC_FAILED
- RADIUS_ACCOUNTING_SYNC_SUCCEED
- RADIUS_AUTHENTICATION_ASYNC
- RADIUS_AUTHENTICATION_ASYNC_ACCEPTED
- RADIUS_AUTHENTICATION_ASYNC_FAILED
- RADIUS_AUTHENTICATION_ASYNC_REJECTED
- RADIUS_AUTHENTICATION_STATUS
- RADIUS_AUTHENTICATION_STATUS_FAILED
- RADIUS_AUTHENTICATION_STATUS_SUCCEED
- RADIUS_AUTHENTICATION_SYNC
- RADIUS_AUTHENTICATION_SYNC_ACCEPTED
- RADIUS_AUTHENTICATION_SYNC_FAILED
- RADIUS_AUTHENTICATION_SYNC_REJECTED
- RADIUS_BACKEND_GET4
- RADIUS_BACKEND_GET6
- RADIUS_DECODE_MESSAGE
- RADIUS_ENCODE_MESSAGE
- RADIUS_EXCHANGE_RECEIVED_ACCESS_ACCEPT
- RADIUS_EXCHANGE_RECEIVED_ACCESS_REJECT
- RADIUS_EXCHANGE_RECEIVED_ACCOUNTING_RESPONSE
- RADIUS_EXCHANGE_RECEIVED_RESPONSE
- RADIUS_TCP_EXCHANGE_RECEIVED
- RADIUS_TCP_EXCHANGE_SEND
- RADIUS_TCP_EXCHANGE_START
- RADIUS_TCP_EXCHANGE_SUCCESS
- RADIUS_TLS_STATUS
- RADIUS_TLS_STATUS_FAILED
- RADIUS_TLS_STATUS_SUCCEED
- RADIUS_UDP_EXCHANGE_RECEIVED
- RADIUS_UDP_EXCHANGE_SEND_NEW
- RADIUS_UDP_EXCHANGE_SEND_RETRY
- RADIUS_UDP_EXCHANGE_SENT
- RADIUS_UDP_EXCHANGE_START
- RADIUS_UDP_EXCHANGE_SYNC_RETURN
- RADIUS_UDP_EXCHANGE_TERMINATE
- RBAC_CONFIGURED_ACLS

- RBAC_CONFIGURED_COMMANDS
- RBAC_CONFIGURED_ROLES
- RBAC_TRACE_HTTP_AUTH_ACCEPT
- RBAC_TRACE_HTTP_AUTH_BAD_BODY_TYPE
- RBAC_TRACE_HTTP_AUTH_BAD_COMMAND_TYPE
- RBAC_TRACE_HTTP_AUTH_COMMAND
- RBAC_TRACE_HTTP_AUTH_DISABLED
- RBAC_TRACE_HTTP_AUTH_EMPTY_BODY
- RBAC_TRACE_HTTP_AUTH_NO_COMMAND
- RBAC_TRACE_HTTP_AUTH_NO_JSON
- RBAC_TRACE_HTTP_AUTH_NO_REQUEST
- RBAC_TRACE_HTTP_AUTH_NO_TLS_REJECT
- RBAC_TRACE_HTTP_AUTH_RESPONSE
- RBAC_TRACE_HTTP_AUTH_ROLE
- RBAC_TRACE_HTTP_RESPONSE_BAD_BODY_TYPE
- RBAC_TRACE_HTTP_RESPONSE_CONTEXT
- RBAC_TRACE_HTTP_RESPONSE_DISABLED
- RBAC_TRACE_HTTP_RESPONSE_EMPTY_BODY
- RBAC_TRACE_HTTP_RESPONSE_EMPTY_BODY_LIST
- RBAC_TRACE_HTTP_RESPONSE_MODIFIED
- RBAC_TRACE_HTTP_RESPONSE_NO_ARGUMENTS
- START_REKEY_TIMER
- START_RETRY_TIMER
- STAT_CMDS_LEASE4_ORPHANED_STATS
- STAT_CMDS_LEASE6_ORPHANED_STATS
- TCP_CLIENT_BAD_SERVER_RESPONSE_RECEIVED
- TCP_CLIENT_MT_STARTED
- TCP_CLIENT_SERVER_RESPONSE_RECEIVED
- TCP_CONNECTION_SHUTDOWN
- TCP_CONNECTION_STOP
- TCP_SERVER_CLIENT_REQUEST_RECEIVED
- TCP_SERVER_RESPONSE_SEND
- TKEY_EXCHANGE_ANSWER_CLASS
- TKEY_EXCHANGE_IO_FETCH_RESULT
- TKEY_EXCHANGE_NOT_A_RESPONSE
- TKEY_EXCHANGE_OUT_TOKEN_NOT_EMPTY

- TKEY_EXCHANGE_RDATA_COUNT
- TKEY_EXCHANGE_RECEIVE_MESSAGE
- TKEY_EXCHANGE_RESPONSE_TTL
- TKEY_EXCHANGE_SEND_MESSAGE
- TKEY_EXCHANGE_VALID
- TKEY_EXCHANGE_VERIFIED
- TLS_SERVER_RESPONSE_SEND

51.6 Messages printed on debuglevel 45

- DHCP4_DHCP4O6_SUBNET_SELECTED
- DHCP4_SUBNET_DYNAMICALLY_CHANGED
- DHCP4_SUBNET_SELECTED
- DHCP6_SUBNET_DYNAMICALLY_CHANGED
- DHCP6_SUBNET_SELECTED
- HOOKS_CALLOUTS_BEGIN
- HOOKS_CALLOUTS_COMPLETE
- HOOKS_CALLOUTS_REMOVED
- HOOKS_CALLOUT_REGISTRATION
- HOOKS_LIBRARY_MULTI_THREADING_COMPATIBLE
- HOOKS_LIBRARY_VERSION
- HOOKS_STD_CALLOUT_REGISTERED
- HOSTS_CFG_GET_ALL_ADDRESS4_COUNT
- HOSTS_CFG_GET_ALL_ADDRESS6_COUNT
- HOSTS_CFG_GET_ALL_COUNT
- HOSTS_CFG_GET_ALL_HOSTNAME_COUNT
- HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4_COUNT
- HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6_COUNT
- HOSTS_CFG_GET_ALL_IDENTIFIER_COUNT
- HOSTS_CFG_GET_ALL_SUBNET_ID4_COUNT
- HOSTS_CFG_GET_ALL_SUBNET_ID6_COUNT
- HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4_COUNT
- HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6_COUNT
- HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4_HOST
- HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS4_NULL
- HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6_HOST
- HOSTS_CFG_GET_ONE_SUBNET_ID_ADDRESS6_NULL

- HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER_HOST
- HOSTS_CFG_GET_ONE_SUBNET_ID_IDENTIFIER_NULL
- HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER_HOST
- HOSTS_MGR_ALTERNATE_GET4_SUBNET_ID_IDENTIFIER_NULL
- HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER_HOST
- HOSTS_MGR_ALTERNATE_GET6_SUBNET_ID_IDENTIFIER_NULL
- HOST_CACHE_ADD
- HOST_CACHE_ADD_DUPLICATE
- HOST_CACHE_DEL_SUBNET_ID_ADDRESS4
- HOST_CACHE_DEL_SUBNET_ID_ADDRESS6
- HOST_CACHE_DEL_SUBNET_ID_IDENTIFIER4
- HOST_CACHE_DEL_SUBNET_ID_IDENTIFIER6
- HOST_CACHE_GET_ONE_PREFIX_HOST
- HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS4_HOST
- HOST_CACHE_GET_ONE_SUBNET_ID_ADDRESS6_HOST
- HOST_CACHE_GET_ONE_SUBNET_ID_IDENTIFIER_HOST
- HTTP_BAD_CLIENT_REQUEST_RECEIVED_DETAILS
- HTTP_BAD_SERVER_RESPONSE_RECEIVED_DETAILS
- HTTP_CLIENT_REQUEST_RECEIVED_DETAILS
- HTTP_SERVER_RESPONSE_RECEIVED_DETAILS
- HTTP_SERVER_RESPONSE_SEND_DETAILS
- TCP_CLIENT_BAD_SERVER_RESPONSE_RECEIVED_DETAILS

51.7 Messages printed on debuglevel 50

- ALLOC_ENGINE_V6_EXTEND_LEASE
- ASIODNS_READ_TIMEOUT
- DHCP4_ADDITIONAL_CLASS_EVAL_RESULT
- DHCP4_BUFFER_UNPACK
- DHCP4_BUFFER_WAIT_SIGNAL
- DHCP4_CLIENTID_FORCED_USE_FOR_LEASES
- DHCP4_CLIENTID_IGNORED_FOR_LEASES
- DHCP4_CLIENT_FQDN_PROCESS
- DHCP4_CLIENT_FQDN_SCRUBBED_EMPTY
- DHCP4_CLIENT_HOSTNAME_MALFORMED
- DHCP4_CLIENT_HOSTNAME_PROCESS
- DHCP4_CLIENT_HOSTNAME_SCRUBBED_EMPTY

- DHCP4_DEFERRED_OPTION_MISSING
- DHCP4_DEFERRED_OPTION_UNPACK_FAIL
- DHCP4_DHCP4O6_BAD_PACKET
- DHCP4_DHCP4O6_RECEIVE_FAIL
- DHCP4_DHCP4O6_RECEIVING
- DHCP4_DHCP4O6_SUBNET_SELECTION_FAILED
- DHCP4_DISCOVER
- DHCP4_EMPTY_HOSTNAME
- DHCP4_HOOK_BUFFER_RCVD_SKIP
- DHCP4_INFORM_DIRECT_REPLY
- DHCP4_NO_LEASE_INIT_REBOOT
- DHCP4_PACKET_NAK_0002
- DHCP4_PACKET_NAK_0003
- DHCP4_PACKET_NAK_0004
- DHCP4_PACKET_OPTIONS_SKIPPED
- DHCP4_PACKET_PACK
- DHCP4_RELEASE
- DHCP4_RELEASE_FAIL
- DHCP4_RELEASE_FAIL_NOT_ASSIGNED
- DHCP4_RELEASE_FAIL_NO_LEASE
- DHCP4_RELEASE_FAIL_WRONG_CLIENT
- DHCP4_REQUEST
- DHCP4_RESPONSE_HOSTNAME_GENERATE
- DHCP4_SANITIZED_HOSTNAME_MALFORMED
- DHCP4_SUBNET_SELECTION_FAILED
- DHCP4_UNKNOWN_ADDRESS_REQUESTED
- DHCP6_ADDITIONAL_CLASS_EVAL_RESULT
- DHCP6_ADD_GLOBAL_STATUS_CODE
- DHCP6_ADD_STATUS_CODE_FOR_IA
- DHCP6_BUFFER_UNPACK
- DHCP6_BUFFER_WAIT_SIGNAL
- DHCP6_CLIENT_FQDN_SCRUBBED_EMPTY
- DHCP6_DDNS_CREATE_ADD_NAME_CHANGE_REQUEST
- DHCP6_DDNS_GENERATE_FQDN
- DHCP6_DDNS_RECEIVE_FQDN
- DHCP6_DDNS_REMOVE_OLD_LEASE_FQDN

- DHCP6_DDNS_RESPONSE_FQDN_DATA
- DHCP6_DECLINE_PROCESS_IA
- DHCP6_DHCP4O6_RECEIVE_FAIL
- DHCP6_DHCP4O6_RECEIVING
- DHCP6_HOOK_BUFFER_RCVD_SKIP
- DHCP6_HOOK_DECLINE_SKIP
- DHCP6_LEASE_ADVERT
- DHCP6_LEASE_ADVERT_FAIL
- DHCP6_LEASE_ALLOC
- DHCP6_LEASE_ALLOC_FAIL
- DHCP6_PACKET_OPTIONS_SKIPPED
- DHCP6_PD_LEASE_ADVERT
- DHCP6_PD_LEASE_ADVERT_FAIL
- DHCP6_PD_LEASE_ALLOC
- DHCP6_PD_LEASE_ALLOC_FAIL
- DHCP6_PROCESS_IA_NA_EXTEND
- DHCP6_PROCESS_IA_NA_RELEASE
- DHCP6_PROCESS_IA_NA_REQUEST
- DHCP6_PROCESS_IA_NA_SOLICIT
- DHCP6_PROCESS_IA_PD_EXTEND
- DHCP6_PROCESS_IA_PD_REQUEST
- DHCP6_PROCESS_IA_PD_SOLICIT
- DHCP6_RAPID_COMMIT
- DHCP6_SUBNET_SELECTION_FAILED
- DHCP6SRV_DHCP_DDNS_NCR_SENT
- DHCP6SRV_EVAL_RESULT
- DHCP6SRV_MEMFILE_ADD_ADDR4
- DHCP6SRV_MEMFILE_ADD_ADDR6
- DHCP6SRV_MEMFILE_COMMIT
- DHCP6SRV_MEMFILE_DELETE_ADDR4
- DHCP6SRV_MEMFILE_DELETE_ADDR6
- DHCP6SRV_MEMFILE_DELETE_EXPIRED_RECLAIMED4
- DHCP6SRV_MEMFILE_DELETE_EXPIRED_RECLAIMED6
- DHCP6SRV_MEMFILE_DELETE_EXPIRED_RECLAIMED_START
- DHCP6SRV_MEMFILE_GET4
- DHCP6SRV_MEMFILE_GET6

- DHCPSRV_MEMFILE_GET6_DUID
- DHCPSRV_MEMFILE_GET_ADDR4
- DHCPSRV_MEMFILE_GET_ADDR6
- DHCPSRV_MEMFILE_GET_CLIENTID
- DHCPSRV_MEMFILE_GET_EXPIRED4
- DHCPSRV_MEMFILE_GET_EXPIRED6
- DHCPSRV_MEMFILE_GET_HOSTNAME4
- DHCPSRV_MEMFILE_GET_HOSTNAME6
- DHCPSRV_MEMFILE_GET_HWADDR4
- DHCPSRV_MEMFILE_GET_HWADDR6
- DHCPSRV_MEMFILE_GET_IAID_DUID
- DHCPSRV_MEMFILE_GET_IAID_SUBID_DUID
- DHCPSRV_MEMFILE_GET_PAGE4
- DHCPSRV_MEMFILE_GET_PAGE6
- DHCPSRV_MEMFILE_GET_RELAYID4
- DHCPSRV_MEMFILE_GET_RELAYID6
- DHCPSRV_MEMFILE_GET_REMOTEID4
- DHCPSRV_MEMFILE_GET_REMOTEID6
- DHCPSRV_MEMFILE_GET_SUBID4
- DHCPSRV_MEMFILE_GET_SUBID6
- DHCPSRV_MEMFILE_GET_SUBID_CLIENTID
- DHCPSRV_MEMFILE_GET_SUBID_HWADDR
- DHCPSRV_MEMFILE_GET_SUBID_PAGE6
- DHCPSRV_MEMFILE_ROLLBACK
- DHCPSRV_MEMFILE_UPDATE_ADDR4
- DHCPSRV_MEMFILE_UPDATE_ADDR6
- DHCPSRV_QUEUE_NCR_SKIP
- DHCPSRV_TEMPLATE_EVAL_RESULT
- DHCPSRV_TIMERMGR_RUN_TIMER_OPERATION
- DHCP_DDNS_INVALID_RESPONSE
- DHCP_DDNS_IO_FETCH_RESULT
- DHCP_DDNS_STARTING_TRANSACTION
- DHCP_DDNS_UPDATE_REQUEST_SENT
- DHCP_DDNS_UPDATE_RESPONSE_RECEIVED
- FUZZ_DATA_READ
- FUZZ_SEND

- HTTPS_REQUEST_RECEIVE_START
- HTTP_CLIENT_REQUEST_SEND
- HTTP_CLIENT_REQUEST_TIMEOUT_OCCURRED
- HTTP_CONNECTION_HANDSHAKE_START
- HTTP_IDLE_CONNECTION_TIMEOUT_OCCURRED
- HTTP_REQUEST_RECEIVE_START
- LEGAL_LOG_MYSQL_GET_VERSION
- LEGAL_LOG_MYSQL_INSERT_LOG
- LEGAL_LOG_MYSQL_TLS_CIPHER
- LEGAL_LOG_PGSQL_GET_VERSION
- LEGAL_LOG_PGSQL_INSERT_LOG
- MYSQL_HB_DB_GET_VERSION
- MYSQL_LB_ADD_ADDR4
- MYSQL_LB_ADD_ADDR6
- MYSQL_LB_COMMIT
- MYSQL_LB_DELETED_EXPIRED_RECLAIMED
- MYSQL_LB_DELETED_SUBNET4_ID
- MYSQL_LB_DELETED_SUBNET6_ID
- MYSQL_LB_DELETE_ADDR4
- MYSQL_LB_DELETE_ADDR6
- MYSQL_LB_DELETE_EXPIRED_RECLAIMED4
- MYSQL_LB_DELETE_EXPIRED_RECLAIMED6
- MYSQL_LB_GET4
- MYSQL_LB_GET6
- MYSQL_LB_GET_ADDR4
- MYSQL_LB_GET_ADDR6
- MYSQL_LB_GET_CLIENTID
- MYSQL_LB_GET_DUID
- MYSQL_LB_GET_EXPIRED4
- MYSQL_LB_GET_EXPIRED6
- MYSQL_LB_GET_HOSTNAME4
- MYSQL_LB_GET_HOSTNAME6
- MYSQL_LB_GET_HWADDR4
- MYSQL_LB_GET_HWADDR6
- MYSQL_LB_GET_IAID_DUID
- MYSQL_LB_GET_IAID_SUBID_DUID

- MYSQL_LB_GET_PAGE4
- MYSQL_LB_GET_PAGE6
- MYSQL_LB_GET_RELAYID4
- MYSQL_LB_GET_RELAYID6
- MYSQL_LB_GET_REMOTEID4
- MYSQL_LB_GET_REMOTEID6
- MYSQL_LB_GET_STATE4
- MYSQL_LB_GET_STATE6
- MYSQL_LB_GET_STATE_SUBID4
- MYSQL_LB_GET_STATE_SUBID6
- MYSQL_LB_GET_SUBID4
- MYSQL_LB_GET_SUBID6
- MYSQL_LB_GET_SUBID_CLIENTID
- MYSQL_LB_GET_SUBID_HWADDR
- MYSQL_LB_GET_SUBID_PAGE6
- MYSQL_LB_GET_VERSION
- MYSQL_LB_ROLLBACK
- MYSQL_LB_SFLQ_CREATE_POOL4
- MYSQL_LB_SFLQ_CREATE_POOL6
- MYSQL_LB_SFLQ_PICK_LEASE4
- MYSQL_LB_SFLQ_PICK_LEASE6
- MYSQL_LB_SFLQ_POOL4_DELETE
- MYSQL_LB_SFLQ_POOL4_GET_ALL
- MYSQL_LB_SFLQ_POOL4_GET_BY_RANGE
- MYSQL_LB_SFLQ_POOL4_GET_BY_SUBNET
- MYSQL_LB_SFLQ_POOL6_DELETE
- MYSQL_LB_SFLQ_POOL6_GET_ALL
- MYSQL_LB_SFLQ_POOL6_GET_BY_RANGE
- MYSQL_LB_SFLQ_POOL6_GET_BY_SUBNET
- MYSQL_LB_UPDATE_ADDR4
- MYSQL_LB_UPDATE_ADDR6
- MYSQL_LB_UPGRADE_EXTENDED_INFO4_PAGE
- MYSQL_LB_UPGRADE_EXTENDED_INFO6_PAGE
- PERFMON_DHCP4_PKT_EVENTS
- PERFMON_DHCP4_PKT_PROCESS_ERROR
- PERFMON_DHCP6_PKT_EVENTS

- PERFMON_DHCP6_PKT_PROCESS_ERROR
- PGSQL_HB_DB_GET_VERSION
- PGSQL_LB_ADD_ADDR4
- PGSQL_LB_ADD_ADDR6
- PGSQL_LB_COMMIT
- PGSQL_LB_DELETED_SUBNET4_ID
- PGSQL_LB_DELETED_SUBNET6_ID
- PGSQL_LB_DELETE_ADDR4
- PGSQL_LB_DELETE_ADDR6
- PGSQL_LB_DELETE_EXPIRED_RECLAIMED4
- PGSQL_LB_DELETE_EXPIRED_RECLAIMED6
- PGSQL_LB_GET4
- PGSQL_LB_GET6
- PGSQL_LB_GET_ADDR4
- PGSQL_LB_GET_ADDR6
- PGSQL_LB_GET_CLIENTID
- PGSQL_LB_GET_DUID
- PGSQL_LB_GET_EXPIRED4
- PGSQL_LB_GET_EXPIRED6
- PGSQL_LB_GET_HOSTNAME4
- PGSQL_LB_GET_HOSTNAME6
- PGSQL_LB_GET_HWADDR4
- PGSQL_LB_GET_HWADDR6
- PGSQL_LB_GET_IAID_DUID
- PGSQL_LB_GET_IAID_SUBID_DUID
- PGSQL_LB_GET_PAGE4
- PGSQL_LB_GET_PAGE6
- PGSQL_LB_GET_RELAYID4
- PGSQL_LB_GET_RELAYID6
- PGSQL_LB_GET_REMOTEID4
- PGSQL_LB_GET_REMOTEID6
- PGSQL_LB_GET_STATE4
- PGSQL_LB_GET_STATE6
- PGSQL_LB_GET_STATE_SUBID4
- PGSQL_LB_GET_STATE_SUBID6
- PGSQL_LB_GET_SUBID4

- PGSQL_LB_GET_SUBID6
- PGSQL_LB_GET_SUBID_CLIENTID
- PGSQL_LB_GET_SUBID_HWADDR
- PGSQL_LB_GET_SUBID_PAGE6
- PGSQL_LB_GET_VERSION
- PGSQL_LB_ROLLBACK
- PGSQL_LB_SFLQ_CREATE_POOL4
- PGSQL_LB_SFLQ_CREATE_POOL6
- PGSQL_LB_SFLQ_PICK_LEASE4
- PGSQL_LB_SFLQ_PICK_LEASE6
- PGSQL_LB_SFLQ_POOL4_DELETE
- PGSQL_LB_SFLQ_POOL4_GET_ALL
- PGSQL_LB_SFLQ_POOL4_GET_BY_RANGE
- PGSQL_LB_SFLQ_POOL4_GET_BY_SUBNET
- PGSQL_LB_SFLQ_POOL6_DELETE
- PGSQL_LB_SFLQ_POOL6_GET_ALL
- PGSQL_LB_SFLQ_POOL6_GET_BY_RANGE
- PGSQL_LB_SFLQ_POOL6_GET_BY_SUBNET
- PGSQL_LB_UPDATE_ADDR4
- PGSQL_LB_UPDATE_ADDR6
- PGSQL_LB_UPGRADE_EXTENDED_INFO4_PAGE
- PGSQL_LB_UPGRADE_EXTENDED_INFO6_PAGE
- PING_CHECK_CHANNEL_ECHO_REPLY_RECEIVED
- PING_CHECK_CHANNEL_ECHO_REQUEST_SENT
- PING_CHECK_MGR_NEXT_ECHO_SCHEDULED
- PING_CHECK_MGR_RECEIVED_UNEXPECTED_ECHO_REPLY
- PING_CHECK_MGR_RECEIVED_UNEXPECTED_UNREACHABLE_MSG
- PING_CHECK_MGR_RECEIVED_UNREACHABLE_MSG
- PING_CHECK_MGR_REPLY_TIMEOUT_EXPIRED
- PING_CHECK_NO_LEASE_OR_LEASE_REUSED
- TCP_CLIENT_REQUEST_SEND
- TCP_CONNECTION_REJECTED_BY_FILTER
- TCP_IDLE_CONNECTION_TIMEOUT_OCCURRED
- TCP_REQUEST_RECEIVE_START
- TLS_CONNECTION_HANDSHAKE_START
- TLS_REQUEST_RECEIVE_START

51.8 Messages printed on debuglevel 55

- ALLOC_ENGINE_V4_REUSE_EXPIRED_LEASE_DATA
- ALLOC_ENGINE_V6_EXTEND_LEASE_DATA
- ALLOC_ENGINE_V6_EXTEND_NEW_LEASE_DATA
- ALLOC_ENGINE_V6_REUSE_EXPIRED_LEASE_DATA
- DHCP4_CLIENT_FQDN_DATA
- DHCP4_CLIENT_HOSTNAME_DATA
- DHCP4_CLIENT_NAME_PROC_FAIL
- DHCP4_DHCP4O6_RESPONSE_DATA
- DHCP4_DHCP4O6_SUBNET_DATA
- DHCP4_GENERATE_FQDN
- DHCP4_QUERY_DATA
- DHCP4_RECOVERED_STASHED_RELAY_AGENT_INFO
- DHCP4_RESERVED_HOSTNAME_ASSIGNED
- DHCP4_RESPONSE_DATA
- DHCP4_RESPONSE_FQDN_DATA
- DHCP4_RESPONSE_HOSTNAME_DATA
- DHCP4_SUBNET_DATA
- DHCP6_DDNS_FQDN_GENERATED
- DHCP6_DHCP4O6_RESPONSE_DATA
- DHCP6_LEASE_DATA
- DHCP6_QUERY_DATA
- DHCP6_RESPONSE_DATA
- DHCP6_SUBNET_DATA
- DHCP_SRV_DDNS_TTL_TOO_LARGE
- DHCP_SRV_DDNS_TTL_TOO_SMALL
- DHCP_SRV_MEMFILE_LEASE_LOAD
- DHCP_SRV_QUEUE_NCR
- DHCP_DDNS_AT_MAX_TRANSACTIONS
- DHCP_DDNS_FWD_REQUEST_IGNORED
- DHCP_DDNS_NO_ELIGIBLE_JOBS
- DHCP_DDNS_QUEUE_MGR_QUEUE_RECEIVE
- DHCP_DDNS_REQUEST_DROPPED
- DHCP_DDNS_REV_REQUEST_IGNORED
- EVAL_DEBUG_AND
- EVAL_DEBUG_BRANCH

- EVAL_DEBUG_CONCAT
- EVAL_DEBUG_EQUAL
- EVAL_DEBUG_HEXSTRING
- EVAL_DEBUG_IFELSE_FALSE
- EVAL_DEBUG_IFELSE_TRUE
- EVAL_DEBUG_INT16TOTEXT
- EVAL_DEBUG_INT32TOTEXT
- EVAL_DEBUG_INT8TOTEXT
- EVAL_DEBUG_IPADDRESS
- EVAL_DEBUG_IPADDRESSTOTEXT
- EVAL_DEBUG_LCASE
- EVAL_DEBUG_MATCH
- EVAL_DEBUG_MEMBER
- EVAL_DEBUG_NOT
- EVAL_DEBUG_OPTION
- EVAL_DEBUG_OR
- EVAL_DEBUG_PKT
- EVAL_DEBUG_PKT4
- EVAL_DEBUG_PKT6
- EVAL_DEBUG_POP_AND_BRANCH_FALSE
- EVAL_DEBUG_POP_OR_BRANCH_FALSE
- EVAL_DEBUG_POP_OR_BRANCH_TRUE
- EVAL_DEBUG_RELAY6
- EVAL_DEBUG_RELAY6_RANGE
- EVAL_DEBUG_SPLIT
- EVAL_DEBUG_SPLIT_DELIM_EMPTY
- EVAL_DEBUG_SPLIT_EMPTY
- EVAL_DEBUG_SPLIT_FIELD_OUT_OF_RANGE
- EVAL_DEBUG_STRING
- EVAL_DEBUG_SUBSTRING
- EVAL_DEBUG_SUBSTRING_EMPTY
- EVAL_DEBUG_SUBSTRING_RANGE
- EVAL_DEBUG_TOHEXSTRING
- EVAL_DEBUG_UCASE
- EVAL_DEBUG_UINT16TOTEXT
- EVAL_DEBUG_UINT32TOTEXT

- EVAL_DEBUG_UINT8TOTEXT
- EVAL_DEBUG_VENDOR_CLASS_DATA
- EVAL_DEBUG_VENDOR_CLASS_DATA_NOT_FOUND
- EVAL_DEBUG_VENDOR_CLASS_ENTERPRISE_ID
- EVAL_DEBUG_VENDOR_CLASS_ENTERPRISE_ID_MISMATCH
- EVAL_DEBUG_VENDOR_CLASS_EXISTS
- EVAL_DEBUG_VENDOR_CLASS_NO_OPTION
- EVAL_DEBUG_VENDOR_ENTERPRISE_ID
- EVAL_DEBUG_VENDOR_ENTERPRISE_ID_MISMATCH
- EVAL_DEBUG_VENDOR_EXISTS
- EVAL_DEBUG_VENDOR_NO_OPTION
- HOOKS_ALL_CALLOUTS_DEREGISTERED
- HOOKS_CALLOUT_CALLED
- HOOKS_CALLOUT_DEREGISTERED
- HOSTS_CFG_GET_ALL_ADDRESS4_HOST
- HOSTS_CFG_GET_ALL_ADDRESS6_HOST
- HOSTS_CFG_GET_ALL_HOST
- HOSTS_CFG_GET_ALL_HOSTNAME_HOST
- HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID4_HOST
- HOSTS_CFG_GET_ALL_HOSTNAME_SUBNET_ID6_HOST
- HOSTS_CFG_GET_ALL_IDENTIFIER_HOST
- HOSTS_CFG_GET_ALL_SUBNET_ID4_HOST
- HOSTS_CFG_GET_ALL_SUBNET_ID6_HOST
- HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS4_HOST
- HOSTS_CFG_GET_ALL_SUBNET_ID_ADDRESS6_HOST
- HOSTS_CFG_GET_ONE_PREFIX_HOST
- HOSTS_CFG_GET_ONE_PREFIX_NULL
- HTTP_CLIENT_REQUEST_SEND_DETAILS
- HTTP_DATA_RECEIVED
- LIMITS_PACKET_WIIH_SUBNET_ID_RATE_NO_SUBNET
- LIMITS_PACKET_WITH_CLIENT_CLASSES_RATE_LIMIT_HONORED
- LIMITS_PACKET_WITH_SUBNET_ID_RATE_LIMIT_HONORED
- NETCONF_CONFIG_CHANGED_DETAIL
- NETCONF_GET_CONFIG
- NETCONF_SET_CONFIG
- NETCONF_UPDATE_CONFIG

- NETCONF_VALIDATE_CONFIG
- TCP_DATA_RECEIVED
- TCP_DATA_SENT

51.9 Messages printed on debuglevel 70

- ASIODNS_FETCH_COMPLETED